



**FCC Part15, Subpart B
ICES-003**

TEST REPORT

For

TOY Receiver

MODEL NUMBER: 1052UB

FCC ID: G6D1052UB

REPORT NUMBER: 4789522022

ISSUE DATE: July 13, 2020

Prepared for

**NEW BRIGHT INDUSTRIAL CO., LTD
9/F., NEW BRIGHT BUILDING, 11 SHEUNG YUET ROAD, KOWLOON BAY,
KOWLOON, HONG KONG.**

Prepared by

UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch

Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-Tech Development Zone Dongguan, 523808, People's Republic of China

Tel: +86 769 22038881

Fax: +86 769 33244054

Website: www.ul.com

The results reported herein have been performed in accordance with the laboratory's terms of accreditation. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report apply to the test sample(s) mentioned above at the time of the testing period only and are not to be used to indicate applicability to other similar products. This report does not imply that the product(s) has met the criteria for certification.



Revision History

Rev.	Issue Date	Revisions	Revised By
V0	07/13/2020	Initial Issue	



Summary of Test Results				
Standard	Test Item	Limit	Result	Remark
FCC Part15, Subpart B ANSI C63.4-2014 ICES-003 Issue 6	Conducted Disturbance	Class B	PASS	
	Radiated Disturbance below 1 GHz	Class B	PASS	
	Radiated Disturbance above 1 GHz	Class B	PASS	NOTE (1)
Note: (1) If the highest frequency of the internal sources of the EUT is less than 108 MHz, the measurement shall only be made up to 1 GHz. If the highest frequency of the internal sources of the EUT is between 108 MHz and 500 MHz, the measurement shall only be made up to 2 GHz. If the highest frequency of the internal sources of the EUT is between 500 MHz and 1 GHz, measurement shall only be made up to 5 GHz. If the highest frequency of the internal sources of the EUT is above 1 GHz, the measurement shall be made up to 5 times the highest frequency or 40 GHz, whichever is less. This test report is only published to and used by the applicant, and it is not for evidence purpose in China.				



CONTENTS

1. ATTESTATION OF TEST RESULTS.....	5
2. TEST METHODOLOGY.....	6
3. FACILITIES AND ACCREDITATION.....	6
4. CALIBRATION AND UNCERTAINTY	7
4.1. <i>MEASURING INSTRUMENT CALIBRATION</i>	<i>7</i>
4.2. <i>MEASUREMENT UNCERTAINTY.....</i>	<i>7</i>
5. EQUIPMENT UNDER TEST	8
5.1. <i>DESCRIPTION OF EUT</i>	<i>8</i>
5.2. <i>TEST MODE.....</i>	<i>8</i>
5.3. <i>EUT ACCESSORY</i>	<i>8</i>
5.4. <i>SUPPORT UNITS FOR SYSTEM TEST</i>	<i>8</i>
6. MEASURING EQUIPMENT AND SOFTWARE USED.....	10
7. EMISSION TEST	11
7.1. <i>CONDUCTED EMISSIONS MEASUREMENT</i>	<i>11</i>
7.2. <i>RADIATED EMISSIONS MEASUREMENT.....</i>	<i>15</i>



1. ATTESTATION OF TEST RESULTS

Applicant Information

Company Name: NEW BRIGHT INDUSTRIAL CO., LTD
Address: 9/F., NEW BRIGHT BUILDING, 11 SHEUNG YUET ROAD,
KOWLOON BAY, KOWLOON, HONG KONG.

Manufacturer Information

Company Name: NEW BRIGHT INDUSTRIAL CO., LTD
Address: 9/F., NEW BRIGHT BUILDING, 11 SHEUNG YUET ROAD,
KOWLOON BAY, KOWLOON, HONG KONG.

EUT Information

EUT Name: TOY Receiver
Model: 1052UB
Brand: /
Sample Received Date: June 12, 2020
Sample Status: Normal
Sample ID: 3165670
Date of Tested: July 2, 2020 ~ July 10, 2020

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC Part15, Subpart B	PASS
ICES-003 Issue 6	PASS

Prepared By:

Andy Xiong
Engineer Project Associate

Checked By:

Shawn Wen
Laboratory Leader

Approved By:

Stephen Guo
Laboratory Manager



2. TEST METHODOLOGY

All tests were performed in accordance with the standard FCC Part15 Subpart B & ICES-003 Issue 6 & ANSI C63.4-2014.

3. FACILITIES AND ACCREDITATION

Accreditation Certificate	A2LA (Certificate No.: 4102.01) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA. FCC (FCC Recognized No.: CN1187) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules IC (Company No.: 21320) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with Industry Canada. The Company Number is 21320. VCCI (Registration No.: G-20019, R-20004, C-20012 and T-20011) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793. Facility Name: Chamber D, the VCCI registration No. is G-20019 and R-20004 Shielding Room B , the VCCI registration No. is C-20012 and T-20011
---------------------------	--

Note: All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-Tech Development Zone Dongguan, 523808, People's Republic of China

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations and is traceable to recognized national standards.

4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Item	Measurement Frequency Range	K	U(dB)
Conducted emissions from the AC mains power ports	0.009MHz ~ 0.15MHz	2	4.00
Conducted emissions from the AC mains power ports	0.15MHz ~ 30MHz	2	3.62
Radiated emissions	30MHz ~ 1GHz	2	4.00
Radiated emissions	1GHz ~ 18GHz	2	5.78

Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.



5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

EUT Name	TOY Receiver
Model	1052UB
Rated Input	DC 5V
Battery	DC 9.6V 4.8Wh, 500mAh

5.2. TEST MODE

Test Mode	Description
Mode 1	Charging
Mode 2	Running
Mode 3	Receiving

Note: EUT couldn't working under mode 2 and mode 3 while charging by adapter.

5.3. EUT ACCESSORY

I/O PORTS AND CABLES

Cable No	Port	Connector Type	Cable Type	Cable Length(m)	Remarks
/	/	/	/	/	/

Note: No I/O ports and cables

ACCESSORY

Item	Accessory	Brand Name	Model Name	Description
1	Controller	NEW BRIGHT	3705HBL	/

5.4. SUPPORT UNITS FOR SYSTEM TEST

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Specification	Series No.
1	adapter	SAMSUNG	ETA-U90CBC	Input: 100-240V~ 50-60Hz, 0.35A Output: 5.0V 2.0A	RT4DC060PS/B

The following cables were used to form a representative test configuration during the tests.



Item	Type of cable	Shielded Type	Ferrite Core	Length
/	/	/	/	/



6. MEASURING EQUIPMENT AND SOFTWARE USED

Conducted Emissions					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
EMI Test Receiver	R&S	ESR3	101961	Dec. 5, 2019	Dec. 5, 2020
Two-Line V-Network	R&S	ENV216	101983	Dec. 5, 2019	Dec. 5, 2020
Software					
Description			Manufacturer	Name	Version
Test Software for Conducted Emissions			Farad	EZ-EMC	Ver. UL-3A1
Radiated Emissions					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
MXE EMI Receiver	KESIGHT	N9038A	MY56400036	Dec. 6, 2019	Dec. 6, 2020
Hybrid Log Periodic Antenna	TDK	HLP-3003C	130959	Sept. 17, 2018	Sept. 17, 2021
Preamplifier	HP	8447D	2944A09099	Dec. 5, 2019	Dec. 5, 2020
EMI Measurement Receiver	R&S	ESR26	101377	Dec. 5, 2019	Dec. 5, 2020
Horn Antenna	TDK	HRN-0118	130939	Sept. 17, 2018	Sept. 17, 2021
Preamplifier	TDK	PA-02-0118	TRS-305-00067	Dec. 05, 2019	Dec. 05, 2020
Preamplifier	TDK	PA-02-001-3000	TRS-302-00050	Dec. 05, 2019	Dec. 05, 2020
Software					
Description			Manufacturer	Name	Version
Test Software for Radiated Emissions			Farad	EZ-EMC	Ver. UL-3A1

7. EMISSION TEST

7.1. CONDUCTED EMISSIONS MEASUREMENT

LIMITS

CFR 47 FCC Part15 Subpart B ICES-003 Issue 6				
FREQUENCY (MHz)	Class A (dBμV)		Class B (dBμV)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46*
0.50 -5.0	73.00	60.00	56.00	46.00
5.0 -30.0	73.00	60.00	60.00	50.00

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.


The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

TEST PROCEDURE

1. The testing follows the guidelines in ANSI C63.4-2014.
2. The EUT was placed on the top of a rotating table 0.8 meters above the horizontal ground plane and being connected to the power mains through a line impedance stabilization network (LISN). All other support equipment powered from additional LISN(s). The LISN provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
3. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
4. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
5. Cables of hand-operated devices, such as keyboards and mice, shall be placed as for normal used.
6. LISN at least 80 cm from nearest part of EUT chassis.
7. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-Peak and average detector mode.

TEST SETUP



For the actual test configuration, please refer to Appendix I: Photographs of Test Configuration.

TEST ENVIRONMENT


Temperature	27.6°C	Relative Humidity	69.6%
Atmosphere Pressure	101kPa		

TEST MODE

Pre-test Mode:	Mode 1
Final Test Mode:	Mode 1

**TEST RESULTS**

Conducted Emissions			
Test Mode:	Mode 1	Phase:	Line
Test Voltage	AC 120V/60Hz		




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1645	35.26	9.61	44.87	65.23	-20.36	QP
2	0.1645	20.22	9.61	29.83	55.23	-25.40	AVG
3	0.2247	28.77	9.60	38.37	62.64	-24.27	QP
4	0.2247	15.04	9.60	24.64	52.64	-28.00	AVG
5	0.2606	27.05	9.60	36.65	61.41	-24.76	QP
6	0.2606	13.48	9.60	23.08	51.41	-28.33	AVG
7	0.2936	24.27	9.60	33.87	60.42	-26.55	QP
8	0.2936	10.35	9.60	19.95	50.42	-30.47	AVG
9	0.6175	22.53	9.60	32.13	56.00	-23.87	QP
10	0.6175	15.50	9.60	25.10	46.00	-20.90	AVG
11	10.0906	20.02	9.74	29.76	60.00	-30.24	QP
12	10.0906	10.44	9.74	20.18	50.00	-29.82	AVG

Note: 1. Result = Reading +Correct (Insertion Loss + Cable Loss + Attenuator Factor)
2. Margin = Result - Limit



Conducted Emissions			
Test Mode:	Mode 1	Phase:	Neutral
Test Voltage	AC 120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1682	30.10	9.60	39.70	65.05	-25.35	QP
2	0.1682	16.21	9.60	25.81	55.05	-29.24	AVG
3	0.1949	28.33	9.60	37.93	63.83	-25.90	QP
4	0.1949	13.54	9.60	23.14	53.83	-30.69	AVG
5	0.2230	25.36	9.60	34.96	62.71	-27.75	QP
6	0.2230	11.17	9.60	20.77	52.71	-31.94	AVG
7	0.5998	22.54	9.60	32.14	56.00	-23.86	QP
8	0.5998	12.73	9.60	22.33	46.00	-23.67	AVG
9	4.1341	18.58	9.66	28.24	56.00	-27.76	QP
10	4.1341	8.41	9.66	18.07	46.00	-27.93	AVG
11	9.0600	21.09	9.75	30.84	60.00	-29.16	QP
12	9.0600	10.77	9.75	20.52	50.00	-29.48	AVG

Note: 1. Result = Reading + Correct (Insertion Loss + Cable Loss + Attenuator Factor)

2. Margin = Result - Limit

7.2. RADIATED EMISSIONS MEASUREMENT

LIMITS

Below 1 GHz

CFR 47 FCC Part15 Subpart B ICES-003 Issue 6			
Frequency (MHz)	Class A		Class B
	Field strength (uV/m) (at 10m)	Field strength (dBuV/m) (at 3m)	Field strength (dBuV/m) (at 3m)
30 - 88	90	49.5	40
88 - 216	150	53.9	43.5
216 - 960	210	56.9	46
Above 960	300	60	54

Above 1 GHz

CFR 47 FCC Part15 Subpart B ICES-003 Issue 6						
Frequency (MHz)	Class A				Class B	
	(dBuV/m) (at 3m)		(dBuV/m) (at 10m)		(dBuV/m) (at 3m)	
	Peak	Average	Peak	Average	Peak	Average
Above 1000	80	60	69.5	49.5	74	54

Test Frequency Range of Radiated Disturbance Measurement


Highest frequency generated or Upper frequency of measurement used in the device or on which the device operates or tunes (MHz)	Range (MHz)
Below 1.705	30
1.705 - 108	1000
108 - 500	2000
500 - 1000	5000
Above 1000	5 th harmonic of the highest frequency or 40 GHz, whichever is lower

NOTE:

- (1) The limit for radiated test was performed according to FCC Part 15, Subpart B;
- (2) The tighter limit applies at the band edges;
- (3) Emission level (dBuV/m) = 20log Emission level (uV/m),
3m Emission level = 10m Emission level + 20log(10m/3m);

TEST SETUP AND PROCEDURE

Below 1G and above 30MHz




The setting of the spectrum analyser

RBW	120K
VBW	300K
Sweep	Auto
Detector	Peak and QP
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.4-2014.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp was used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80cm above ground.
4. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
5. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
6. Cables of hand-operated devices, such as keyboards and mice, shall be placed as for normal used.
7. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
8. For measurement below 1GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.

Above 1G



The setting of the spectrum analyser

RBW	1M
VBW	3M
Sweep	Auto
Detector	Peak: Peak AVG: RMS
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.4-2014.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80cm above ground.
4. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
5. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
6. Cables of hand-operated devices, such as keyboards and mice, shall be placed as for normal used.
7. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
8. For measurement above 1GHz, the peak emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the peak limit specified in Section 15.109. If peak result complies with average limit, average result is deemed to comply with average limit.
9. The average emission measurement will be measured by the RMS detector and must comply with the average limit specified in Section 15.109.

**TEST ENVIRONMENT**

Radiated Emissions - Below 1 GHz		Radiated Emissions - Above 1 GHz	
Temperature:	23.5°C	Temperature:	21.1°C
Humidity:	65.9%	Humidity:	51%
Atmosphere Pressure	101kPa	Atmosphere Pressure	101kPa


TEST MODE

Radiated Emissions - Below 1 GHz		Radiated Emissions - Above 1 GHz	
Pre-test Mode:	Mode 1 ~ Mode 3	Pre-test Mode:	Mode 1 ~ Mode 3
Final Test Mode:	Mode 1 ~ Mode 3	Final Test Mode:	Mode 2 & Mode 3

Note: All test modes have been tested, but only the worst data was recorded in the report.

**TEST RESULTS**

Radiated Emissions – Below 1GHz			
Measurement Method	Radiated	Polar:	Horizontal
Test Mode:	Mode 1	Test Voltage:	AC120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	89.1700	42.70	-22.05	20.65	43.50	-22.85	QP
2	112.4500	48.69	-20.46	28.23	43.50	-15.27	QP
3	169.6799	43.28	-17.20	26.08	43.50	-17.42	QP
4	298.6900	38.12	-15.67	22.45	46.00	-23.55	QP
5	350.1000	35.66	-14.57	21.09	46.00	-24.91	QP
6	918.5200	28.22	-5.56	22.66	46.00	-23.34	QP

Note: 1. Reading +Correct (Amplifier Factor + Cable Loss + Antenna Factor)

2. Margin = Result - Limit



Radiated Emissions – Below 1GHz			
Measurement Method	Radiated	Polar:	Vertical
Test Mode:	Mode 1	Test Voltage:	AC120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	36.7900	55.50	-19.72	35.78	40.00	-4.22	QP
2	63.9500	54.09	-20.59	33.50	40.00	-6.50	QP
3	109.5400	49.36	-20.66	28.70	43.50	-14.80	QP
4	169.6799	45.90	-17.20	28.70	43.50	-14.80	QP
5	350.1000	36.37	-14.57	21.80	46.00	-24.20	QP
6	942.7700	29.25	-5.25	24.00	46.00	-22.00	QP

Note: 1. Reading +Correct (Amplifier Factor + Cable Loss + Antenna Factor)
2. Margin = Result - Limit



Radiated Emissions – Below 1GHz			
Measurement Method	Radiated	Polar:	Horizontal
Test Mode:	Mode 2	Test Voltage:	DC 9.6V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	126.0300	50.54	-19.76	30.78	43.50	-12.72	QP
2	177.4400	42.66	-17.16	25.50	43.50	-18.00	QP
3	257.9500	51.66	-18.96	32.70	46.00	-13.30	QP
4	379.2000	38.44	-13.90	24.54	46.00	-21.46	QP
5	624.6100	31.61	-9.70	21.91	46.00	-24.09	QP
6	834.1300	34.14	-7.08	27.06	46.00	-18.94	QP

Note: 1. Reading +Correct (Amplifier Factor + Cable Loss + Antenna Factor)

2. Margin = Result - Limit



Radiated Emissions – Below 1GHz			
Measurement Method	Radiated	Polar:	Vertical
Test Mode:	Mode 2	Test Voltage:	DC 9.6V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	111.4800	47.34	-20.52	26.82	43.50	-16.68	QP
2	124.0900	42.86	-19.86	23.00	43.50	-20.50	QP
3	262.8000	34.69	-18.64	16.05	46.00	-29.95	QP
4	350.1000	33.86	-14.57	19.29	46.00	-26.71	QP
5	537.3100	33.24	-11.00	22.24	46.00	-23.76	QP
6	958.2900	28.81	-5.02	23.79	46.00	-22.21	QP

Note: 1. Reading +Correct (Amplifier Factor + Cable Loss + Antenna Factor)
2. Margin = Result - Limit



Radiated Emissions – Below 1GHz

Measurement Method	Radiated	Polar:	Horizontal
Test Mode:	Mode 3	Test Voltage:	DC 9.6V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	122.1500	50.74	-19.96	30.78	43.50	-12.72	QP
2	177.4400	42.18	-17.16	25.02	43.50	-18.48	QP
3	255.0400	52.50	-19.06	33.44	46.00	-12.56	QP
4	302.5700	46.41	-15.53	30.88	46.00	-15.12	QP
5	373.3800	37.76	-13.99	23.77	46.00	-22.23	QP
6	833.1599	33.59	-7.09	26.50	46.00	-19.50	QP

Note: 1. Reading +Correct (Amplifier Factor + Cable Loss + Antenna Factor)

2. Margin = Result - Limit



Radiated Emissions – Below 1GHz			
Measurement Method	Radiated	Polar:	Vertical
Test Mode:	Mode 3	Test Voltage:	DC 9.6V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	110.5100	47.05	-20.59	26.46	43.50	-17.04	QP
2	126.0300	42.01	-19.76	22.25	43.50	-21.25	QP
3	263.7700	34.84	-18.55	16.29	46.00	-29.71	QP
4	350.1000	33.55	-14.57	18.98	46.00	-27.02	QP
5	537.3100	32.88	-11.00	21.88	46.00	-24.12	QP
6	910.7600	29.03	-5.55	23.48	46.00	-22.52	QP

Note: 1. Reading +Correct (Amplifier Factor + Cable Loss + Antenna Factor)
2. Margin = Result - Limit



Radiated Emissions – Above 1GHz

Measurement Method	Radiated	Polar:	Horizontal
Test Mode:	Mode 2	Test Voltage:	DC 9.6V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2410.000	46.74	-8.60	38.14	74.00	-35.86	peak
2	4642.500	42.95	-0.40	42.55	74.00	-31.45	peak
3	6040.750	40.29	2.58	42.87	74.00	-31.13	peak
4	7168.750	39.18	5.41	44.59	74.00	-29.41	peak
5	9342.500	37.10	8.56	45.66	74.00	-28.34	peak
6	12691.250	33.72	13.88	47.60	74.00	-26.40	peak

Note: 1. Reading +Correct (Amplifier Factor + Cable Loss + Antenna Factor)
2. Margin = Result - Limit
3. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
4. Peak: Peak detector.



Radiated Emissions – Above 1GHz			
Measurement Method	Radiated	Polar:	Vertical
Test Mode:	Mode 2	Test Voltage:	DC 9.6V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3479.250	43.84	-5.11	38.73	74.00	-35.27	peak
2	5888.000	40.80	2.25	43.05	74.00	-30.95	peak
3	7168.750	39.37	5.41	44.78	74.00	-29.22	peak
4	10282.500	36.58	9.57	46.15	74.00	-27.85	peak
5	11516.250	35.26	12.35	47.61	74.00	-26.39	peak
6	12679.500	35.03	13.85	48.88	74.00	-25.12	peak

Note: 1. Reading +Correct (Amplifier Factor + Cable Loss + Antenna Factor)
2. Margin = Result - Limit
3. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
4. Peak: Peak detector.



Radiated Emissions – Above 1GHz

Measurement Method	Radiated	Polar:	Horizontal
Test Mode:	Mode 3	Test Voltage:	DC 9.6V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3902.250	41.36	-3.61	37.75	74.00	-36.25	peak
2	5923.250	40.05	2.36	42.41	74.00	-31.59	peak
3	7885.500	37.85	5.80	43.65	74.00	-30.35	peak
4	9542.250	36.65	9.03	45.68	74.00	-28.32	peak
5	11798.250	34.62	13.43	48.05	74.00	-25.95	peak
6	12573.750	34.47	13.62	48.09	74.00	-25.91	peak

Note: 1. Reading +Correct (Amplifier Factor + Cable Loss + Antenna Factor)
2. Margin = Result - Limit
3. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
4. Peak: Peak detector.



Radiated Emissions – Above 1GHz			
Measurement Method	Radiated	Polar:	Vertical
Test Mode:	Mode 3	Test Voltage:	DC 9.6V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2457.000	45.63	-8.55	37.08	74.00	-36.92	peak
2	4901.000	41.15	0.69	41.84	74.00	-32.16	peak
3	8379.000	38.11	6.66	44.77	74.00	-29.23	peak
4	10564.500	36.39	10.63	47.02	74.00	-26.98	peak
5	11704.250	35.49	12.96	48.45	74.00	-25.55	peak
6	12703.000	34.94	13.91	48.85	74.00	-25.15	peak

Note: 1. Reading +Correct (Amplifier Factor + Cable Loss + Antenna Factor)
2. Margin = Result - Limit
3. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
4. Peak: Peak detector.

END OF REPORT