



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AY0017732(9) Date : Mar 14, 2019

Application No. : LY007548(2)

Applicant : New Bright Industrial Co Ltd.
9/F New Bright Building, 11 Sheung Yuet Road,
Kowloon Bay, Kowloon, Hong Kong

Sample Description : One(1) item of submitted sample stated to be:

Sample Description	Model No.
Toy Receiver	60806RR

Radio Frequency : 2411 – 2472 MHz

Rating : DC 12.8V (Li-ion rechargeable battery)

No. of submitted sample : One Unit

Sample registration No. : RY014403-001(2)

Date Received : Mar 8, 2019.

Test Period : Mar 8, 2019 to Mar 13, 2019

Test Requested : FCC 47CFR Part 15 Certification
ISED Certification for License-exempt Device

Test Method : 47 CFR Part 15 (10-1-18 Edition)
ANSI C63.10 – 2013
ANSI C63.4 – 2014
RSS-210 Issue 9
RSS-Gen Issue 5

Test Result : See attached sheet(s) from page 2 to 20.

Conclusion : The submitted sample was found to comply with requirement of FCC 47CFR Part 15 Subpart C, section 15.249 and ISED Canada Radio Standard Specification RSS-210.

For and on behalf of
CMA Industrial Development Foundation Limited

Authorized Signature : _____

Mr. WONG Lap-pong, Andrew
Manager

Page 1 of 20

FCC ID: G6D60806RR
IC: 9650A-60806RR

Document name: FCC/ISED for LPD - Document Ref No: RT-EL-EMC-047 - Issue Date: 13 Mar 2019 - Edition: 2

This document is issued subject to the latest CMA Testing General Terms and Conditions of Testing and Inspection Services, available on request or accessible at website www.cmatcl.com
This document shall not be reproduced except in full or with written approval by CMA Testing

CMA Industrial Development Foundation Limited

Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, N.T., Hong Kong.

Tel: (852) 2698 8198 Fax: (852) 2695 4177 E-mail: info@cmatcl.com Web Site: <http://www.cmatcl.com>



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AY0017732(9)

Date : Mar 14, 2019

Table of Contents

1	General Information	3
1.1	General Description	3
1.2	Location of the test site	4
1.3	List of measuring equipment.....	5
1.4	Measurement Uncertainty.....	6
1.5	Test Summary	6
1.6	External Photo, Internal Photo and Test Configuration Photo.....	6
2	Description of the radiated emission test	7
2.1	Test Procedure	7
2.2	Test Setup	8
2.3	Test Result	10
3	Description of the Line-conducted Test.....	14
3.1	Test Procedure	14
3.2	Test Result	14
3.3	Test Setup	14
3.4	Graph and Table of Conducted Emission Measurement Data	14
4	Bandwidth	15
5	Appendices.....	16



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AY0017732(9)

Date : Mar 14, 2019

1 General Information

1.1 General Description

The equipment under test (EUT) model 60806RR is a remote controlled car. It operates at frequency band 2411 - 2472MHz for transmitter with 21 hopping channel. The oscillation of radio control is generated by a 16 MHz crystal for RF IC, XNS-102. The EUT is powered by one DC 12.8V Li-ion rechargeable battery. The EUT is remote controlled car and controlled by a remote control unit which is certified by FCC with FCC ID: G6DG21HRR

After the pairing with the remote control by the half-duplex communication link, the EUT can be controlled by remote control on moving forward and backward and turn left and right.

The wire antenna with 0dBi antenna gain is used in EUT and the radio output power is unable to adjust.

The brief circuit description is listed as follows:

-U1	and its associated circuit act as RF IC, XNS-102
-U3, U4	and its associated circuit act as Motor Driver
-Y1	and its associated circuit act as oscillation clock, 16MHz
-U2	and its associated circuit act as a 3.3V LDO



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AY0017732(9)

Date : Mar 14, 2019

1.2 Location of the test site

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2014. A Semi-Anechoic Chamber Testing Site is set up for investigation and located at:

Ground Floor, Yan Hing Centre,
9 – 13 Wong Chuk Yeung Street,
Fo Tan, Shatin,
New Territories,
Hong Kong.

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 2014. A shielded room is located at :

Ground Floor, Yan Hing Centre,
9 – 13 Wong Chuk Yeung Street,
Fo Tan, Shatin,
New Territories,
Hong Kong.

FCC Accredited Lab (Designation Number: HK0004)
ISED Wireless Test Site (ISED Assigned Code: 4093A)



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AY0017732(9)

Date : Mar 14, 2019

1.3 List of measuring equipment

Equipment Number	Equipment	Manufacturer	Model No.	Serial No.	Calibration Due Date	Calibration Period
EL-218	EMI Test Receiver	Rohde & Schwarz	ESCS30	100001	21-Jun-19	1Year
EL-373	Spectrum Analyzer	Rohde & Schwarz	FSV40	100964	11-Sep-19	1Year
EL-223	Biconical Antenna	Rohde & Schwarz	HK116	837414/004	8-Oct-20	2Years
EL-1523	Log Periodic Antenna	TESEQ	UPA6109	43666	8-Oct-19	2Years
EL-301	Loop Antenna	EMCO	6502	56620	29-Oct-20	2Years
EL-311	Horn Antenna	Schwarzbeck	BBHA9120D	9120D531	21-Dec-19	2Years
EL-312	Pre-amplifier	Schwarzbeck	BBV9718	9718-119	21-Dec-19	2Years
EL-330	Horn Antenna	Schwarzbeck	BBHA9170	BBHA9170442	24-Aug-19	2Years
EL-331	Pre-amplifier	Schwarzbeck	BBHA9719	9719-010	23-Aug-19	2Years
EL-392-1	Coaxial Cable	HUBER+SUHNER	RG214/U	-	18-Sep-19	1Year
EL-392-2	Coaxial Cable	HUBER+SUHNER	RG214/U	-	18-Sep-19	1Year
EL-331-1	Coaxial Cable	Suhner	Sucoflex_104	124828/4	23-Aug-19	1Year
EL-333	LISN	Rohde & Schwarz	ENV216	101232	22-Jan-20	1Year
EL-335	Coaxial Cable	Tyco Electronics	RG58C/U	-	21-Oct-19	1Year



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AY0017732(9)

Date : Mar 14, 2019

1.4 Measurement Uncertainty

The reported uncertainty is based on a standard uncertainty multiplied by a coverage factor $k=2$, providing a level of confidence of approximately 95%.

Radiated emissions

Frequency	Uncertainty (U_{lab})
30MHz ~ 200MHz (Horizontal)	4.59dB
30MHz ~ 200MHz (Vertical)	4.49dB
200MHz ~ 1000MHz (Horizontal)	4.94dB
200MHz ~ 1000MHz (Vertical)	4.97dB
1GHz ~ 6GHz	4.52dB
6GHz ~ 18GHz	4.58dB
18GHz ~ 40GHz	4.66dB

1.5 Test Summary

TEST ITEM	FCC REFERENCE	RSS REFERENCE	RESULT
Fundamental and harmonic emission	15.249(a)	RSS-210, Annex B.10(a)	Comply
Out-band emission	15.249(d)	RSS-210, Annex B.10(b)	Comply
Peak Limit	15.249(e)	RSS-Gen, 8.1	Comply
Bandwidth	15.215(c)	RSS-Gen, 6.7	Comply

1.6 External Photo, Internal Photo and Test Configuration Photo

The External Photo, Internal Photo and Test Configuration Photo associated with this report for the tested product are saved in separated pdf file listed in the following

File content	File name
External Photo	G6D60806RR_9650A-60806RR External Photo.pdf
Internal Photo	G6D60806RR_9650A-60806RR Internal Photo.pdf
Test Configuration Photo	G6D60806RR_9650A-60806RR Test configuration photo.pdf



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AY0017732(9)

Date : Mar 14, 2019

2 Description of the radiated emission test

2.1 Test Procedure

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.10 – 2013.

A non-conductive turntable with dimensions of 1.5m x 0.4m x 0.8m (L x W x H) placed above the reference ground plane. The equipment under test (EUT) was placed at 0.8m height for below 1GHz measurement and 1.5m height for above 1GHz measurement. The test distance is 3m between EUT and receiving antenna. A broadband antenna mounting on the mast received the signal strength. The turntable was rotated to maximize the emission level. The antenna was moving along the mast from 1m up to 4m until no more higher value was found. Both horizontal and vertical polarization of the antenna were placed and investigated. Additional absorbing material will be placed between the EUT and receiving antenna for above 1GHz measurement.

For below 30MHz, a loop antenna with its vertical plane is placed 3m from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. And the centre of the loop shall be 1 m above the ground.

The device was rotated through three orthogonal axes to determine which attitude and configuration produce the highest emission during measurement.



CMA Testing and Certification Laboratories


廠商會檢定中心

TEST REPORT


Report No. : AY0017732(9)

Date : Mar 14, 2019

2.2 Test Setup



Below 30MHz



30MHz – 1GHz



CMA Testing and Certification Laboratories


廠商會檢定中心

TEST REPORT

Report No. : AY0017732(9)

Date : Mar 14, 2019

2.2 Test Setup



Above 1GHz



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AY0017732(9)

Date : Mar 14, 2019

2.3 Test Result

Peak Detector data was measured unless otherwise stated.

The radiated emissions are measured from 9kHz to 26GHz (the tenth harmonics)

The worst case configuration is shown on the worst case configuration of test setup photo.

The frequencies from fundamental up to tenth harmonics were investigated, and emissions more 20dB below limit were not reported. Thus, those highest emissions were presented in next pages.

The EUT has been tested in Transmission mode.

It was found that the EUT meet the FCC and RSS requirement.



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AY0017732(9)

Date : Mar 14, 2019

2.4 Radiated Emission Measurement Data

Radiated emission

Environmental conditions:

Parameter	Recorded value	
Ambient temperature:	25.3	° C
Relative humidity:	56.5	%

Channel: 2411 MHz

Polarization	Frequency (MHz)	Reading at 3m (dBμV)	Antenna Factor and Cable Loss (dB/m)	Field Strength at 3m (dBμV/m)	Limit at 3m (dBμV/m)	Margin (dB)	Detector Type
V	2411.200	74.6	-4.7	69.9	94.0	-24.1	Peak
H	2411.371	72.0	-4.7	67.3	94.0	-26.7	Peak
V	2400.000	44.4	-4.7	39.7	54.0	-14.3	Peak
V	2483.500	46.4	-4.7	41.7	54.0	-12.3	Peak
V	4822.406	50.5	2.3	52.8	54.0	-1.2	Peak
V	7233.768	41.3	9.6	50.9	54.0	-3.1	Peak

Remark: 1) The peak value of emissions are below the average limit, so no average measurement is performed.



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AY0017732(9)

Date : Mar 14, 2019

Channel: 2441MHz

Polarization	Frequency (MHz)	Reading at 3m (dBμV)	Antenna Factor and Cable Loss (dB/m)	Field Strength at 3m (dBμV/m)	Limit at 3m (dBμV/m)	Margin (dB)	Detector Type
V	2441.298	76.0	-4.7	71.3	94.0	-22.7	Peak
H	2441.164	70.6	-4.7	65.9	94.0	-28.1	Peak
V	2400.000	44.4	-4.7	39.7	54.0	-14.3	Peak
V	2483.500	46.4	-4.7	41.7	54.0	-12.3	Peak
V	4882.316	46.9	2.3	49.2	54.0	-4.8	Peak
V	7323.680	41.6	9.6	51.2	54.0	-2.8	Peak

Remark: 1) The peak value of emissions are below the average limit, so no average measurement is performed.



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AY0017732(9)

Date : Mar 14, 2019

Channel: 2472MHz

Polarization	Frequency (MHz)	Reading at 3m (dBμV)	Antenna Factor and Cable Loss (dB/m)	Field Strength at 3m (dBμV/m)	Limit at 3m (dBμV/m)	Margin (dB)	Detector Type
V	2472.020	76.3	-4.7	71.6	94.0	-22.4	Peak
H	2472.216	71.7	-4.7	67.0	94.0	-27.0	Peak
V	2400.000	44.4	-4.7	39.7	54.0	-14.3	Peak
V	2483.500	46.4	-4.7	41.7	54.0	-12.3	Peak
V	4944.780	47.3	2.8	50.1	54.0	-3.9	Peak
V	7416.681	41.6	9.6	51.2	54.0	-2.8	Peak

Remark: 1) The peak value of emissions are below the average limit, so no average measurement is performed.



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AY0017732(9)

Date : Mar 14, 2019

3 Description of the Line-conducted Test


3.1 Test Procedure

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.10 – 2013. The EUT was setup as described in the procedures, and both lines were measured.

3.2 Test Result

No measurement is required as the EUT is a battery-operated product.

3.3 Test Setup



3.4 Graph and Table of Conducted Emission Measurement Data

Not Applicable



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AY0017732(9)

Date : Mar 14, 2019

4 Bandwidth

Appendices A1 and A2 show the fundamental emission is confined in the specified band. 20dB bandwidth is 1.281MHz and 99% bandwidth is 1.230MHz. Both bandwidths fall in the band of 2400 – 2483.5MHz. It also shows that the EUT met the requirement of FCC Part 15.215(c) and RSS-GEN.



CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AY0017732(9)

Date : Mar 14, 2019

5 Appendices

A1.	20dB Bandwidth Plot	2	page(s)
A2.	99% Bandwidth Plot	2	Page(s)



CMA Testing and Certification Laboratories


廠商會檢定中心

TEST REPORT


Report No. : AY0017732(9)

Date : Mar 14, 2019

A1. 20dB Bandwidth Plot



Channel: 2411 MHz



Channel: 2441 MHz





CMA Testing and Certification Laboratories


廠商會檢定中心

TEST REPORT


Report No. : AY0017732(9)

Date : Mar 14, 2019

A2. 99% Bandwidth Plot



Channel: 2411 MHz



Channel: 2441 MHz




CMA Testing and Certification Laboratories

廠商會檢定中心

TEST REPORT

Report No. : AY0017732(9)

Date : Mar 14, 2019



Channel: 2472 MHz

***** End of Report *****