

RF Exposure Report

Report No.: SA190821E02A

FCC ID: G95FGA2230

Test Model: FGA2230TCH2

Received Date: Aug. 21, 2019

Test Date: Aug. 22 to Sep. 02, 2019

Issued Date: Mar. 23, 2020

Applicant: Technicolor Connected Home USA LLC

Address: 5030 Sugarloaf Parkway, Building 6 Lawrenceville, GA 30044, USA

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan

Test Location: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan

**FCC Registration /
Designation Number:** 723255 / TW2022

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by any government agencies.

Table of Contents

Release Control Record	3
1 Certificate of Conformity.....	4
2 RF Exposure.....	5
2.1 Limits for Maximum Permissible Exposure (MPE)	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
2.4 Antenna Gain	6
2.5 Calculation Result of Maximum Conducted Power	7

Release Control Record

Issue No.	Description	Date Issued
SA190821E02A	Original release.	Mar. 23, 2020

1 Certificate of Conformity

Product: Technicolor Gateway

Brand: Technicolor

Test Model: FGA2230TCH2

Sample Status: ENGINEERING SAMPLE

Applicant: Technicolor Connected Home USA LLC

Test Date: Aug. 22 to Sep. 02, 2019

Standards: FCC Part 2 (Section 2.1091)

IEEE C95.3 -2002

References Test Guidance: KDB 447498 D01 General RF Exposure Guidance v06

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by :



Date:

Mar. 23, 2020

Joyce Kuo / Specialist

Approved by :



Date:

Mar. 23, 2020

Clark Lin / Technical Manager

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	...	...	f/1500	30
1500-100,000	...	...	1.0	30

f = Frequency in MHz ; *Plane-wave equivalent power density

2.2 MPE Calculation Formula

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 26cm away from the body of the user. So, this device is classified as **Mobile Device**.

2.4 Antenna Gain

1 The antennas provided to the EUT, please refer to the following table:

Antenna NO.	RF Chain NO.	Frequency range	Antenna Type	Connector Type
2.4G1	Chain 2	2.4~2.4835GHz	Dipole	i-pex(MHF)
2.4G2	Chain 1	2.4~2.4835GHz	Dipole	NA
2.4G3	Chain 0	2.4~2.4835GHz	PIFA	NA
5G1	Chain 3	5.15~5.25GHz	Dipole	NA
		5.25~5.35GHz		
		5.47~5.725GHz		
		5.725~5.85GHz		
5G2	Chain 2	5.15~5.25GHz	PIFA	NA
		5.25~5.35GHz		
		5.47~5.725GHz		
		5.725~5.85GHz		
5G3	Chain 1	5.15~5.25GHz	PIFA	NA
		5.25~5.35GHz		
		5.47~5.725GHz		
		5.725~5.85GHz		
5G4	Chain 0	5.15~5.25GHz	Dipole	i-pex(MHF)
		5.25~5.35GHz		
		5.47~5.725GHz		
		5.725~5.85GHz		

2 The directional antenna gain, please refer to the following table:

Frequency Range (GHz)	Maximum Peak Gain (dBi)	Directional Antenna Gain (dBi)	Antenna Type	Antenna Connector
2.4 ~ 2.4835	3.48	4.82	Refer to Note 1	Refer to Note 1
5.15 ~ 5.25	4.92	7.58		
5.25 ~ 5.35	5.03	7.70		
5.47 ~ 5.725	3.78	7.15		
5.725 ~ 5.85	3.78	6.81		

2.1 Calculation Result of Maximum Conducted Power

For 2.4GHz and 5GHz (U-NII-1 & U-NII-3 band) data was copied from the original test report (Report No.: SA190821E02)

Operation Mode	Evaluation Frequency (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
WLAN 2.4GHz	2437	833.324	4.82	26	0.29762	1
WLAN 5GHz (U-NII-1)	5230	877.58	7.58	26	0.59174	1
WLAN 5GHz (U-NII-3)	5745	898.529	6.81	26	0.50743	1
WLAN 5GHz (U-NII-2A)	5270	245.107	7.71	26	0.28713	1
WLAN 5GHz (U-NII-2C)	5550	250.784	7.15	26	0.25884	1

Note:

NOTE:

- Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.
- 2.4GHz directional gain = 4.82dBi
5GHz (U-NII-1) directional gain = 7.58dBi
5GHz (U-NII-2A) directional gain = 7.71dBi
5GHz (U-NII-2C) directional gain = 7.15dBi
5GHz (U-NII-3) directional gain = 6.81dBi

Conclusion:

The formula of calculated the MPE is:

$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$

CPD = Calculation power density

LPD = Limit of power density

WLAN 2.4GHz + WLAN 5GHz = $0.29762 / 1 + 0.59174 / 1 = 0.88936$

Therefore the maximum calculations of above situations are less than the "1" limit.

--- END ---