

RF Exposure Report

Report No.: SA190628E02

FCC ID: G95TCHU1AL0

Test Model: TCHU1AL0

PN: APZ0001COM

Received Date: June 28, 2019

Test Date: July 01 to 03, 2019

Issued Date: July 23, 2019

Applicant: Technicolor Connected Home USA LLC

Address: 5030 Sugarloaf Parkway, Building 6, Lawrenceville, GA 30044

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan R.O.C.

Test Location: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan R.O.C.

**FCC Registration /
Designation Number:** 723255 / TW2022

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by any government agencies.

Table of Contents

Release Control Record	3
1 Certificate of Conformity.....	4
2 RF Exposure.....	5
2.1 Limits for Maximum Permissible Exposure (MPE)	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
2.4 Antenna Gain	5
2.5 Calculation Result of Maximum Conducted Power	6
Appendix	7

Release Control Record

Issue No.	Description	Date Issued
SA190628E02	Original release.	July 23, 2019

1 Certificate of Conformity

Product: LTE Power Supply

Brand: Technicolor

Test Model: TCHU1AL0

Sample Status: LAB2b

Applicant: Technicolor Connected Home USA LLC

Test Date: July 01 to 03, 2019


Standards: FCC Part 2 (Section 2.1091)

KDB 447498 D01 General RF Exposure Guidance v06

IEEE C95.1-1992

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.


Prepared by :


Phoenix Huang / Specialist

Date:

July 23, 2019

Approved by :


May Chen / Manager

Date:

July 23, 2019

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	...	...	f/1500	30
1500-100,000	...	...	1.0	30

f = Frequency in MHz ; *Plane-wave equivalent power density

2.2 MPE Calculation Formula

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20 cm away from the body of the user. So, this device is classified as **Mobile Device**.

2.4 Antenna Gain

Zigbee				
Ant. No	Ant. Gain (dBi)	Frequency Range (GHz)	Antenna Type	Antenna Connector
1	3.9	2.4~2.4835	PCB	Morata
WWAN				
Ant. No	Ant. Gain (dBi)	Frequency Range (MHz)	Antenna Type	Antenna Connector
2	2.9	700~787	PCB	Morata
	3.1	1710~2200	PCB	Morata

2.5 Calculation Result of Maximum Conducted Power

Operation Mode	Evaluation Frequency (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
Zigbee	2445	142.561	3.9	20	0.06962	1

For WWAN (FCC ID: QIPEMS31-X)

Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
699.7-715.3	214.783	2.90	20	0.08332	0.466

Note:

1. Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.
2. *Limit of Power Density = F/1500

Conclusion:

The formula of calculated the MPE is:

$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$

CPD = Calculation power density

LPD = Limit of power density

$Zigbee + WWAN = 0.06962 / 1 + 0.08332 / 0.466 = 0.24824$

Therefore the maximum calculations of above situations are less than the “1” limit.

Appendix

Mode	Equipment Category	Transmitter Range (MHz)		Maximum Output Power		Antenna Gain (dBi)	Power Density (mW/cm ²)		Ratio
		Start	Stop	(dBm)	(mW)		Vaule	Limit	
LTE	Band 2	1850.7	1909.3	23.39	218.272	3.10	0.08866	1	0.089
	Band 4	1710.7	1754.3	23.63	230.675	3.10	0.09370	1	0.094
	Band 12	699.7	715.3	23.32	214.783	2.90	0.08332	0.466*	0.179
	Band 13	779.5	784.5	22.92	195.884	2.90	0.07599	0.52*	0.146

Note: *Limit of Power Density = F/1500

--- END ---