RF EXPOSURE EVALUATION

SPECIFIC ABSORPTION RATE

SAR TEST REPORT

FOR

ATLINKS USA, INC.

5.8 GHz FHSS CORDLESS TELEPHONE HANDSET

Model(s) for USA	Model(s) for Canada
28021XXX-A	TC28021XXX-A
28001XXX-A	TC28001XXX-A

FCC ID: G9H2-8021A

IC ID: 3765A-TC28021A

Test Report Serial Number

111705G9H-F695-S15T
Revision 0

Test Report Issue Date

November 30, 2005

Test Lab

Celltech Compliance Testing & Engineering Lab
(Celltech Labs Inc.)
1955 Moss Court
Kelowna, BC
Canada
V1Y 9L3

Test Report Prepared By:	Test Report Approved By:
Cheri Frangiadakis	
Cheri Frangiadakis Test Report Writer Celltech Labs Inc.	Jonathan Hughes General Manager Celltech Labs Inc.

2005 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.

DECLARATION OF COMPLIANCE
SAR RF EXPOSURE EVALUATION

Test Lab

CELLTECH LABS INC.
Testing and Engineering Services
1955 Moss Court
Kelowna, B.C.
Canada V1Y 9L3
Phone: 250-448-7047
Fax: 250-448-7046
e-mail: info@celltechlabs.com
web site: www.celltechlabs.com

Applicant Information

ATLINKS USA, INC.
101 West 103rd St.
Indianapolis, IN 46290-1102
United States

FCC IDENTIFIER:	**G9H2-8021A**
IC IDENTIFER:	**3765A-TC28021A**
Model No.(s):	**28021XXX-A, 28001XXX-A (USA)** **TC28021XXX-A, TC28001XXX-A (Canada)**
Rule Part(s):	**FCC 47 CFR §2.1093; IC RSS-102 Issue 2**
Test Procedure(s):	**FCC OET Bulletin 65, Supplement C (Edition 01-01)** **IEEE Standard 1528-2003**
FCC Device Classification:	**Part 15 Spread Spectrum Transmitter (DSS)**
IC Device Classification:	**Low Power License-Exempt Radiocommunication Device (RSS-210 Issue 6)**
Device Description:	**5.8 GHz FHSS Cordless Telephone Handset**
Transmission System:	**FHSS (Frequency Hopping Spread Spectrum)**
Modulation Scheme(s):	**EDCT TDD/TDMA**
Tx Frequency Range(s):	**5725.809 - 5848.889 MHz**
Max. RF Output Power Tested:	**22.18 mW / 13.46 dBm (Source Based Time-Averaged) - 5848.889 MHz**
Power Measurement Method:	**Radiated Free-Space Power**
Max. Duty Cycle Tested:	**10.5 % (Source-Based Time-Averaged)**
Battery Type(s) Tested:	**Ni-MH 3.6 V, 800 mAh**
Antenna Type(s) Tested:	**Fixed Stubby**
Body-Worn Accessories Tested:	**Plastic Belt-Clip**
Audio Accessories Tested:	**Generic Ear-Microphone**
Max. SAR Level(s) Evaluated:	**Head: 0.0786 W/kg (1g average)** **Body: 0.0720 W/kg (1g average)**

Celltech Labs Inc. declares under its sole responsibility that this wireless portable device was compliant with the Specific Absorption Rate (SAR) RF exposure requirements specified in FCC 47 CFR §2.1093 and Health Canada's Safety Code 6. The device was tested in accordance with the measurement standards and procedures specified in FCC OET Bulletin 65, Supplement C (Edition 01-01), IEEE 1528-2003, and Industry Canada RSS-102 Issue 2 for the General Population / Uncontrolled Exposure environment. All measurements were performed in accordance with the SAR system manufacturer recommendations.

I attest to the accuracy of data. All measurements were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

This test report shall not be reproduced partially, or in full, without the prior written approval of Celltech Labs Inc.
The results and statements contained in this report pertain only to the device(s) evaluated.

Tested By:	Reviewed By:
Sean Johnston **Compliance Technologist** **Celltech Labs Inc.**	**Spencer Watson** **Senior Compliance Technologist** **Celltech Labs Inc.**

TABLE OF CONTENTS

1.0 INTRODUCTION ____ 4
2.0 DESCRIPTION of DEVICE UNDER TEST (DUT) ____ 4
3.0 SAR MEASUREMENT SYSTEM ____ 5
4.0 MEASUREMENT SUMMARY ____ 6
MEASUREMENT SUMMARY (Cont.) ____ 7
5.0 DETAILS OF SAR EVALUATION ____ 8
DETAILS OF SAR EVALUATION (Cont.) ____ 9
6.0 EVALUATION PROCEDURES ____ 9
EVALUATION PROCEDURES (Cont.) ____ 10
7.0 SYSTEM PERFORMANCE CHECK ____ 11
8.0 SIMULATED EQUIVALENT TISSUES ____ 12
9.0 SAR SAFETY LIMITS ____ 12
10.0 ROBOT SYSTEM SPECIFICATIONS ____ 13
11.0 PROBE SPECIFICATION (EX3DV4) ____ 14
12.0 SAM PHANTOM V4.0C ____ 14
13.0 DEVICE HOLDER ____ 14
14.0 TEST EQUIPMENT LIST ____ 15
15.0 MEASUREMENT UNCERTAINTIES ____ 16
MEASUREMENT UNCERTAINTIES (Cont.) ____ 17
16.0 REFERENCES ____ 18
APPENDIX A - SAR MEASUREMENT DATA ____ 19
APPENDIX B - SYSTEM PERFORMANCE CHECK DATA ____ 29
APPENDIX C - MEASURED FLUID DIELECTRIC PARAMETERS ____ 32
APPENDIX D - MANUFACTURER'S TISSUE SIMULANT DATA SHEET ____ 35
APPENDIX E - SAR TEST SETUP PHOTOGRAPHS ____ 38
APPENDIX F - SYSTEM VALIDATION ____ 48
APPENDIX G - PROBE CALIBRATION ____ 49
APPENDIX H - SAM PHANTOM CERTIFICATE OF CONFORMITY ____ 50

1.0 INTRODUCTION

This measurement report demonstrates that the ATLINKS USA, INC. Models: 28021XXX-A/TC28021XXX-A and 28001XXX-A/TC28001XXX-A Portable 5.8GHz FHSS Cordless Telephone Handset FCC ID: G9H2-8021A complies with the SAR (Specific Absorption Rate) RF exposure requirements specified in FCC 47 CFR §2.1093 (see reference [1]), and Health Canada's Safety Code 6 (see reference [2]) for the General Population / Uncontrolled Exposure environment. The test procedures described in FCC OET Bulletin 65, Supplement C, Edition 01-01 (see reference [3]), IEEE Standard 1528-2003 (see reference [4]), and IC RSS-102 Issue 2 (see reference [5]), were employed. A description of the product and operating configuration, detailed summary of the test results, methodology and procedures used in the evaluation, equipment used, and the various provisions of the rules are included within this test report.

2.0 DESCRIPTION of DEVICE UNDER TEST (DUT)

FCC Rule Part(s)	47 CFR §2.1093			
IC Rule Part(s)	RSS-102 Issue 2			
Test Procedure(s)	FCC OET Bulletin 65, Supplement C (01-01)			
	IEEE 1528-2003			
FCC Device Classification	Part 15 Spread Spectrum Transmitter			Part 15.247
IC Device Classification	Low Power License-Exempt Radiocommunication Device			RSS-210 Issue 6
Device Description	Portable 5.8 GHz FHSS Cordless Telephone Handset			
FCC IDENTIFIER	G9H2-8021A			
IC IDENTIFIER	3765A-TC28021A			
Model No.(s)	**USA**		**Canada**	
	28021XXX-A		TC28021XXX-A	
Optional Model(s) (Additional Testing Not Required)	28001XXX-A		TC28001XXX-A	
Serial No.	50000401539HY		Identical Prototype	
Transmission System(s)	FHSS		Frequency Hopping Spread Spectrum	
Modulation Scheme(s)	EDCT TDD/TDMA			
Tx Frequency Range(s)	5725.809 - 5848.889 MHz			
Max. RF Output Power Levels Calculated from Corrected Field Strengths (Source-Based Time Averaged)	13.55 mW	11.32 dBm	Free-Space Power	5725.809 MHz
	13.80 mW	11.40 dBm	Free-Space Power	5788.240 MHz
	22.18 mW	**13.46 dBm**	**Free-Space Power**	**5848.889 MHz**
Max. Duty Cycle Tested	10.5 %	Source-Based Time-Averaged		Crest Factor: 9.52
Battery Type(s) Tested	Ni-MH		3.6 V	800 mAh
Antenna Type(s) Tested	Fixed Stubby			
Body-Worn Accessories Tested	Plastic Belt-Clip			
Audio Accessories Tested	Generic Ear-Microphone			

2005 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.

3.0 SAR MEASUREMENT SYSTEM

Celltech Labs Inc. SAR measurement facility utilizes the Dosimetric Assessment System (DASY™) manufactured by Schmid & Partner Engineering AG (SPEAG™) of Zurich, Switzerland. The DASY4 measurement system is comprised of the measurement server, robot controller, computer, near-field probe, probe alignment sensor, specific anthropomorphic mannequin (SAM) phantom, and alternate planar phantoms for brain and/or body SAR evaluations. The robot is a six-axis industrial robot performing precise movements to position the probe to the location (points) of maximum electromagnetic field (EMF). A cell controller system contains the power supply, robot controller, teach pendant (Joystick), and remote control, is used to drive the robot motors. The Staubli robot is connected to the cell controller to allow software manipulation of the robot. A data acquisition electronic (DAE) circuit performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. is connected to the Electro-optical coupler (EOC). The EOC performs the conversion from the optical into digital electric signal of the DAE and transfers data to the DASY4 measurement server. The DAE4 utilizes a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16-bit AD-converter and a command decoder and control logic unit. Transmission to the DASY4 measurement server is accomplished through an optical downlink for data and status information and an optical uplink for commands and clock lines. The mechanical probe-mounting device includes two different sensor systems for frontal and sidewise probe contacts. The sensor systems are also used for mechanical surface detection and probe collision detection. The robot uses its own controller with a built in VME-bus computer.

DASY4 SAR Measurement System with SAM phantom and 5GHz Fluid

DASY4 Measurement System with SAM Phantom and 5GHz Fluid

2005 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.

4.0 MEASUREMENT SUMMARY

HEAD SAR EVALUATION RESULTS

Freq. (MHz)	Chan.	Test Mode	Battery Type	Antenna Position	Phantom Section	Test Position	DUT SBTA Start Power[2] (mW)	SAR Drift During Test[3] (dB)	Measured SAR 1g (W/kg)
5848.889	139	Modulated Fixed Frequency	Ni-MH	Fixed	Right Ear	Cheek/Touch	22.18	3.45	0.0470
5848.889	139	Modulated Fixed Frequency	Ni-MH	Fixed	Right Ear	Ear/Tilt (15°)	22.18	-2.68	**0.0786**
5848.889	139	Modulated Fixed Frequency	Ni-MH	Fixed	Left Ear	Cheek/Touch	22.18	-0.374	0.0550
5848.889	139	Modulated Fixed Frequency	Ni-MH	Fixed	Left Ear	Ear/Tilt (15°)	22.18	3.70	0.0772

ANSI / IEEE C95.1 1999 - SAFETY LIMIT	BRAIN: 1.6 W/kg (averaged over 1 gram)	Spatial Peak Uncontrolled Exposure / General Population

Test Date(s)	November 21, 2005				Relative Humidity	30	%
Measured Fluid Type	5800 MHz Brain				Atmospheric Pressure	103.6	kPa
Dielectric Constant ε_r	IEEE Target		Measured	Deviation	Ambient Temperature	23.0	°C
	35.3	± 5%	34.3	-2.8%	Fluid Temperature	22.3	°C
Conductivity σ (mho/m)	IEEE Target		Measured	Deviation	Fluid Depth	≥ 15	cm
	5.27	± 5%	5.15	-2.3%	ρ (Kg/m^3)	1000	

BODY SAR EVALUATION RESULTS

Freq. (MHz)	Chan.	Test Mode	Battery Type	Antenna Position	Phantom Section	DUT Position to Planar Phantom	Accessories Tested		Separation Distance to Planar Phantom (cm)	DUT SBTA Start Power[2] (mW)	SAR Drift During Test[3] (dB)	Measured SAR 1g (W/kg)
							Body-Worn	Audio				
5848.889	139	Modulated Fixed Frequency	Ni-MH	Fixed	Planar	Back Side	Plastic Belt-Clip	Generic Ear-Mic	0.7	22.18	3.63	**0.0720**

ANSI / IEEE C95.1 1999 - SAFETY LIMIT	BODY: 1.6 W/kg (averaged over 1 gram)	Spatial Peak Uncontrolled Exposure / General Population

Test Date(s)	November 21, 2005				Relative Humidity	30	%
Measured Fluid Type	5800 MHz Body				Atmospheric Pressure	103.5	kPa
Dielectric Constant ε_r	IEEE Target		Measured	Deviation	Ambient Temperature	23.6	°C
	48.2	± 5%	46.9	-2.7%	Fluid Temperature	22.0	°C
Conductivity σ (mho/m)	IEEE Target		Measured	Deviation	Fluid Depth	≥ 15	cm
	6.00	± 5%	5.99	-0.2%	ρ (Kg/m^3)	1000	

2005 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.

MEASUREMENT SUMMARY (Cont.)

Note(s):

1. The measurement results were obtained with the DUT tested in the conditions described in this report. Detailed measurement data and plots showing the maximum SAR location of the DUT are reported in Appendix A.
2. The reference output power level was determined prior to the SAR evaluations using free space power measurement method (calculated from corrected field strength levels). The reference output power level reported is source based time-averaged power (SBTA).
3. The SAR evaluations were performed at the maximum output channel of the DUT (upper frequency channel). The lower and middle frequencies were not evaluated for SAR based on the upper frequency SAR level measured was ≥ 3 dB below the SAR limit (FCC OET Bulletin 65, Supplement C, Edition 01-01 - see reference [3]).
4. The power drifts reported were measured at the reference position of the phantom with low SAR. The drift values shown are very inaccurate due to the SAR value at the reference point is close to the noise floor. The SAR-versus-Time power drift measurement (performed at the peak SAR location) clearly shows that this device did not drift more than +/- 5% during each evaluation. It is our engineering judgment that power drift scaling should not be applied in this case.
5. The DUT battery was fully charged prior to each SAR evaluation.
6. The ambient and fluid temperatures were measured prior to, and during, the fluid dielectric parameter check and the SAR evaluations. The temperatures reported were consistent for all measurement periods.
7. The dielectric parameters of the simulated tissue mixture were measured prior to the SAR evaluations using an ALS-PR-DIEL Dielectric Probe Kit and an HP 8753ET Network Analyzer (see Appendix C).
8. The SAR evaluations were performed within 24 hours of the system performance check.

Free Space Power Measurements

Project Number:	695		
Company:	Atlinks USA Inc.	**Test Start Date:**	17-Nov-05
Product:	28021	**Test End Date:**	17-Nov-05

Configuration				Polarity	Distance	Carrier Channel	Frequency	Corrected Field Strength	Duty Cycle		Calculated Carrier Level	
DUT#	Orientation	Battery	Accessory		m		MHz	dBuV/m	%	dB	dBm	mW
2	Face Up	NiMH	none	H	3	1	5725.8093	116.34	10.50	-9.79	11.32	13.56
2	Long Edge Up	NiMH	Ear-mic	H	3	1	5725.8093	108.74	10.50	-9.79	3.72	2.36
2	Face Up	NiMH	none	V	3	1	5725.8093	109.24	10.50	-9.79	4.22	2.64
2	Long Edge Up	NiMH	Ear-mic	V	3	1	5725.8093	114.84	10.50	-9.79	9.82	9.60
2	Face Up	NiMH	none	H	3	71	5788.2400	116.42	10.50	-9.79	11.40	13.81
2	Long Edge Up	NiMH	Ear-mic	H	3	71	5788.2400	115.22	10.50	-9.79	10.20	10.47
2	Face Up	NiMH	none	V	3	71	5788.2400	107.42	10.50	-9.79	2.40	1.74
2	Long Edge Up	NiMH	Ear-mic	V	3	71	5788.2400	114.92	10.50	-9.79	9.90	9.77
2	**Face Up**	**NiMH**	**none**	**H**	**3**	**139**	**5848.8889**	**118.48**	**10.50**	**-9.79**	**13.46**	**22.18**
2	Long Edge Up	NiMH	Ear-mic	H	3	139	5848.8889	117.58	10.50	-9.79	12.56	18.05
2	Face Up	NiMH	none	V	3	139	5848.8889	110.78	10.50	-9.79	5.76	3.77
2	Long Edge Up	NiMH	Ear-mic	V	3	139	5848.8889	110.58	10.50	-9.79	5.56	3.60

Note: Measurements made at a 3 meter distance, with the DUT placed 1 meter above the ground plane

2005 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.

5.0 DETAILS OF SAR EVALUATION

The ATLINKS USA, INC. Portable 5.8GHz FHSS Cordless Telephone Handset FCC ID: G9H2-8021A was compliant for localized Specific Absorption Rate (Uncontrolled Exposure) based on the test provisions and conditions described below. The detailed test setup photographs are shown in Appendix E.

Ear-held Configuration

1) The DUT was tested in an ear-held configuration at both the left and right head sections of the SAM phantom (left ear, right ear, cheek/touch, and ear/tilt positions) per FCC OET Bulletin 65, Supplement C, Edition 01-01 (see reference [3]) and IEEE Standard 1528-2003 (see reference [4]).

a) The handset was placed in the device holder in a normal operating position with the test device reference point located along the vertical centerline on the front of the device aligned to the ear reference point, with the center of the earpiece touching the center of the ear spacer of the SAM phantom.

b) With the handset positioned parallel to the cheek, the test device reference point was aligned to the ear reference point on the head phantom, and the vertical centerline was aligned to the phantom reference plane (initial ear position).

c) While maintaining the three alignments, the body of the handset was gradually adjusted to each of the following test positions:

- Cheek/Touch Position: the handset was brought toward the mouth of the head phantom by pivoting against the ear reference point until any point of the mouthpiece or keypad touched the phantom.



Figure 1. Phone position 1, "cheek" or "touch" position. The reference points for the right ear (RE), left ear (LE) and mouth (M), which define the reference plane for phone positioning, are indicated (Shoulders are shown for illustration only).

- Ear/Tilt Position: With the phone aligned in the Cheek/Touch position, the handset was tilted away from the mouth with respect to the test device reference point by 15 degrees.



Figure 2. Phone position 2, "tilted position." The reference points for the right ear (RE), left ear (LE) and mouth (M), which define the reference plane for phone positioning, are indicated (Shoulders are shown for illustration only).

2005 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.

DETAILS OF SAR EVALUATION (Cont.)

Body-worn Configuration

2) The DUT was tested in a body-worn configuration with the back of the handset placed parallel to the outer surface of the SAM phantom (planar section). The attached plastic belt-clip accessory was touching the outer surface of the SAM phantom (planar section) and provided a 0.7 cm separation distance from the back of the handset to the SAM phantom (planar section).
3) A generic ear-microphone audio accessory was connected to the DUT for the duration of the body-worn test(s).

DUT Test Modes & Power Settings

4) The DUT was programmed in test mode via internal software controlled by the keypad.
5) SAR measurements were performed with the DUT transmitting at maximum power in 1 time slot on a fixed frequency with a modulated signal and a 10.5% source-based time-averaged duty cycle (crest factor: 1:9.52).
6) The conducted power level(s) of the DUT could not be measured for the SAR evaluation due to internal antenna. The DUT was evaluated for SAR at the maximum conducted power level preset by the manufacturer. The RF output power reference levels of the DUT were evaluated prior to the SAR evaluations using the free-space power measurement method (output power calculated from measured field strengths using Celltech Labs' 3-meter OATS in accordance with the measurement procedures described in ANSI TIA/EIA-603-C-2004).
7) The power drift of the DUT during the SAR evaluations was measured by the DASY4 system.
8) The DUT battery was fully charged prior to each SAR evaluation.
9) The ambient and fluid temperatures were measured prior to, and during, the fluid dielectric parameter checks and the SAR evaluations. The temperatures reported were consistent for all measurement periods.
10) The dielectric parameters of the simulated tissue mixtures were measured prior to the SAR evaluations using an ALS-PR-DIEL Dielectric Probe Kit and an HP 8753ET Network Analyzer (see Appendix C).
11) The SAR measurements were performed within 24 hours of the system performance check.

6.0 EVALUATION PROCEDURES

a. (i) The evaluation was performed in the applicable area of the phantom depending on the type of device being tested. For devices held to the ear during normal operation, both the left and right ear positions were evaluated using the SAM phantom.

   (ii) For body-worn and face-held devices a planar phantom was used.
b. The SAR was determined by a pre-defined procedure within the DASY4 software. Upon completion of a reference and optical surface check, the exposed region of the phantom was scanned near the inner surface with a grid spacing of 15mm x 15mm.

   An area scan was determined as follows:
c. Based on the defined area scan grid, a more detailed grid is created to increase the points by a factor of 10. The interpolation function then evaluates all field values between corresponding measurement points.
d. A linear search is applied to find all the candidate maxima. Subsequently, all maxima are removed that are >2 dB from the global maximum. The remaining maxima are then used to position the cube scans.

   A 1g and 10g spatial peak SAR was determined as follows:
e. Extrapolation is used to determine the values between the dipole center of the probe and the surface of the phantom. This data cannot be measured because the center of the dipole sensors is 1.0 mm away from the probe tip and the distance between the probe, and the boundary must be larger than 25% of the probe diameter. The probe diameter is 2.4 mm. In the DASY4 software, the distance between the sensor center and phantom surface is set to 2.0 mm. This provides a distance of 1.0 mm between the probe tip and the surface. The extrapolation of the values between the dipole center and the surface of the phantom was based on trivariate quadratics computed from the previously calculated 3D interpolated points nearest the phantom surface.
f. Interpolated data is used to calculate the average SAR over 1g and 10g cubes by spatially discretizing the entire measured cube. The volume used to determine the averaged SAR is a 1mm grid (42875 interpolated points).
g. A zoom scan volume of 32 mm x 32 mm x 30 mm (5x5x7 points) centered at the peak SAR location determined from the area scan is used for all zoom scans for devices with a transmit frequency < 800 MHz. Zoom scans for frequencies ≥ 800 MHz are determined with a scan volume of 30 mm x 30 mm x 30 mm (7x7x7 points) to ensure complete capture of the peak spatial-average SAR.

2005 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.

EVALUATION PROCEDURES (Cont.)



Figure 3. Flow Chart for determining the largest peak spatial-average SAR from all device configurations per IEEE Standard 1528-2003 (see reference [4]).

2005 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.

7.0 SYSTEM PERFORMANCE CHECK

Prior to the SAR evaluation a system check was performed in the planar section of the SAM phantom with a SPEAG D5GHzV2 validation dipole (see Appendix F for system validation procedures). The dielectric parameters of the simulated tissue mixture were measured prior to the system performance check using an ALS-PR-DIEL Dielectric Probe Kit and an HP 8753ET Network Analyzer (see Appendix C). A forward power of 250 mW was applied to the dipole and the system was verified to a tolerance of ±10% (see Appendix B for system performance check test plot). See table at bottom of page for system manufacturer's reference SAR values from the DASY 4 Manual, March 2005 (see reference [6]).

SYSTEM PERFORMANCE CHECK EVALUATION

Test Date	5.8GHz Equiv. Tissue	SAR 1g (W/kg)			Dielectric Constant ε_r			Conductivity σ (mho/m)			ρ (Kg/m^3)	Amb. Temp. (°C)	Fluid Temp. (°C)	Fluid Depth (cm)	Humid. (%)	Barom. Press. (kPa)
		Target	Meas.	Dev.	IEEE Target	Meas.	Dev.	IEEE Target	Meas.	Dev.						
11/21/05	**Brain**	**19.5 ±10%**	19.4	-0.5%	**35.3 ±5%**	34.3	-2.8%	**5.27 ±5%**	5.15	-2.3%	1000	23.3	22.3	≥ 15	30	103.6

Note(s):
1. The ambient and fluid temperatures were measured prior to, and during, the fluid dielectric parameter check and the system performance check. The temperatures listed in the table above were consistent for all measurement periods.



Figure 4. System Performance Check Setup Diagram

5 GHz Dipole Setup

Reference SAR values

The reference SAR values were calculated using finite-difference time-domain FDTD method (feed-point impedance set to 50 Ω) and the mechanical dimensions of the D5GHzV2 dipole (manufactured by SPEAG).

f (GHz)	Head Tissue			Body Tissue		
	SAR_{1g}	SAR_{10g}	SAR_{peak}	SAR_{1g}	SAR_{10g}	SAR_{peak}
5.0	72.9	20.7	285.6	68.1	19.2	260.3
5.1	74.6	21.1	297.5	78.8	19.6	272.3
5.2	76.5	21.6	310.3	71.8	20.1	284.7
5.5	83.3	23.4	349.4	79.1	22.0	326.3
5.8	78.0	21.9	340.9	74.1	20.5	324.7

Table 27.2: Numerical reference SAR values for D5GHzV2 dipole and flat phantom.

5 GHz Dipole Setup

2005 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.

8.0 SIMULATED EQUIVALENT TISSUES

The 5.8GHz simulated tissue mixtures provided by the SAR system manufacturer (SPEAG) are listed below. The dielectric parameters of the tissue mixture (permittivity and conductivity) were measured prior to the SAR evaluations. See Appendix D for manufacturer's fluid data sheet.

SIMULATED TISSUE MIXTURES			
INGREDIENT	System Performance Check & DUT Evaluation		
	5.8 GHz Brain	5.8 GHz Body	5 GHz Fluid
Water	64 - 78%	64 - 78%	
Mineral Oil	11 - 18%	11 - 18%	
Emulsifiers	9 - 15%	9 - 15%	
Additives and Salt	2 - 3%	2 - 3%	

9.0 SAR SAFETY LIMITS

EXPOSURE LIMITS	SAR (W/kg)	
	(General Population / Uncontrolled Exposure Environment)	(Occupational / Controlled Exposure Environment)
Spatial Average (averaged over the whole body)	0.08	0.4
Spatial Peak (averaged over any 1 g of tissue)	1.60	8.0
Spatial Peak (hands/wrists/feet/ankles averaged over 10 g)	4.0	20.0

Notes:
1. Uncontrolled environments are defined as locations where there is potential exposure of individuals who have no knowledge or control of their potential exposure.
2. Controlled environments are defined as locations where there is potential exposure of individuals who have knowledge of their potential exposure and can exercise control over their exposure.

2005 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.

10.0 ROBOT SYSTEM SPECIFICATIONS

Specifications

POSITIONER: Stäubli Unimation Corp. Robot Model: RX60L
Repeatability: 0.02 mm
No. of axis: 6

Data Acquisition Electronic (DAE) System

Cell Controller

Processor: AMD Athlon XP 2400+
Clock Speed: 2.0 GHz
Operating System: Windows XP Professional

Data Converter

Features: Signal Amplifier, multiplexer, A/D converter, and control logic
Software: DASY4 software
Connecting Lines: Optical downlink for data and status info.
Optical uplink for commands and clock

DASY4 Measurement Server

Function: Real-time data evaluation for field measurements and surface detection
Hardware: PC/104 166MHz Pentium CPU; 32 MB chipdisk; 64 MB RAM
Connections: COM1, COM2, DAE, Robot, Ethernet, Service Interface

E-Field Probe

Model: EX3DV4
Serial No.: 3547
Construction: Symmetrical design with triangular core
Frequency: 10 MHz to 6 GHz
Linearity: ±0.2 dB (30 MHz to 3 GHz)

Phantom(s)

Type: SAM V4.0C
Shell Material: Fiberglass
Thickness: 2.0 ±0.1 mm
Volume: Approx. 25 liters

2005 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.

11.0 PROBE SPECIFICATION (EX3DV4)

Construction:	Symmetrical design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g. DGBE)
Calibration:	Basic Broadband Calibration in air: 10-3000 MHz Conversion Factors (CF) for HSL 900 and HSL 1750
Frequency:	10 MHz to >6 GHz; Linearity: ±0.2 dB (30 MHz to 3 GHz)
Directivity:	±0.3 dB in HSL (rotation around probe axis) ±0.5 dB in tissue material (rotation normal to probe axis)
Dynamic Range:	10 μW/g to >100 mW/g; Linearity: ±0.2 dB (noise: typically < 1 μW/g)
Dimensions:	Overall length: 330 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 1.0 mm
Application:	High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields). Only probe which enables compliance testing for frequencies up to 6 GHz with precision of better than 30%.

EX3DV4 E-Field Probe

12.0 SAM PHANTOM V4.0C

The SAM phantom V4.0C is a fiberglass shell phantom with a 2.0 mm (+/-0.2 mm) shell thickness for left and right head and flat planar area integrated in a wooden table. The shape of the fiberglass shell corresponds to the phantom defined by SCC34-SC2. The device holder positions are adjusted to the standard measurement positions in the three sections (see Appendix H for specifications of the SAM phantom V4.0C).

SAM Phantom

13.0 DEVICE HOLDER

The DASY4 device holder has two scales for device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear openings). The plane between the ear openings and the mouth tip has a rotation angle of 65°. The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections.

Device Holder

14.0 TEST EQUIPMENT LIST

TEST EQUIPMENT		ASSET NO.	SERIAL NO.	DATE CALIBRATED		CALIBRATION DUE DATE
USED	DESCRIPTION					
x	Schmid & Partner DASY4 System	-	-	-		-
x	-DASY4 Measurement Server	00158	1078	N/A		N/A
x	-Robot	00046	599396-01	N/A		N/A
x	-DAE4	00019	353	15Jun05		15Jun06
	-DAE3	00018	370	25Jan05		25Jan06
	-ET3DV6 E-Field Probe	00016	1387	18Mar05		18Mar06
	-ET3DV6 E-Field Probe	00017	1590	20May05		20May06
x	-EX3DV4 E-Field Probe	00125	3547	21Jan05		21Jan06
	-300MHz Validation Dipole	00023	135	25Oct05		25Oct06
	-450MHz Validation Dipole	00024	136	25Oct05		25Oct06
	-835MHz Validation Dipole	00022	411	**Brain**	30Mar05	30Mar06
				Body	12Apr05	12Apr06
	-900MHz Validation Dipole	00020	054	**Brain**	10Jun05	10Jun06
				Body	10Jun05	10Jun06
	-1800MHz Validation Dipole	00021	247	**Brain**	14Jun05	14Jun06
				Body	14Jun05	14Jun06
	-1900MHz Validation Dipole	00032	151	**Brain**	17Jun05	17Jun06
				Body	22Apr05	22Apr06
	-2450MHz Validation Dipole	00025	150	**Brain**	20Sep05	20Sep06
				Body	22Apr05	22Apr06
x	-5000MHz Validation Dipole	00126	1031	**Brain**	11Jan05	11Jan06
				Body	11Jan05	11Jan06
x	-SAM Phantom V4.0C	00154	1033	N/A		N/A
	-Barski Planar Phantom	00155	03-01	N/A		N/A
	-Plexiglas Side Planar Phantom	00156	161	N/A		N/A
	-Plexiglas Validation Planar Phantom	00157	137	N/A		N/A
	HP 85070C Dielectric Probe Kit	00033	N/A	N/A		N/A
x	ALS-PR-DIEL Dielectric Probe Kit	00160	260-00953	N/A		N/A
	Gigatronics 8652A Power Meter	00110	1835801	16Apr05		16Apr06
x	Gigatronics 8652A Power Meter	00008	1835267	29Apr05		29Apr06
x	Gigatronics 80701A Power Sensor	00012	1834350	12Sep05		12Sep06
x	Gigatronics 80701A Power Sensor	00014	1833699	07Sep05		07Sep06
	Gigatronics 80701A Power Sensor	00109	1834366	16Apr05		16Apr06
x	HP 8753ET Network Analyzer	00134	US39170292	04May05		04May06
x	HP 8648D Signal Generator	00005	3847A00611	29Apr05		29Apr06
x	Rohde & Schwarz SMR40 Signal Generator	00006	100104	12Apr05		12Apr06
x	Amplifier Research 5S1G4 Power Amplifier	00106	26235	N/A		N/A

2005 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.

15.0 MEASUREMENT UNCERTAINTIES

UNCERTAINTY BUDGET FOR DEVICE EVALUATION						
Error Description	**Uncertainty Value ±%**	**Probability Distribution**	**Divisor**	**ci 1g**	**Uncertainty Value ±% (1g)**	**V_i or V_{eff}**
Measurement System						
Probe calibration	6.8	Normal	1	1	6.8	∞
Axial isotropy of the probe	4.7	Rectangular	1.732050808	0.7	1.9	∞
Spherical isotropy of the probe	9.6	Rectangular	1.732050808	0.7	3.9	∞
Spatial resolution	0	Rectangular	1.732050808	1	0.0	∞
Boundary effects	2	Rectangular	1.732050808	1	1.2	∞
Probe linearity	4.7	Rectangular	1.732050808	1	2.7	∞
Detection limit	1	Rectangular	1.732050808	1	0.6	∞
Readout electronics	0.3	Normal	1	1	0.3	∞
Response time	0.8	Rectangular	1.732050808	1	0.5	∞
Integration time	2.6	Rectangular	1.732050808	1	1.5	∞
RF ambient conditions	3	Rectangular	1.732050808	1	1.7	∞
Mech. constraints of robot	0.8	Rectangular	1.732050808	1	0.5	∞
Probe positioning	5.7	Rectangular	1.732050808	1	3.3	∞
Extrapolation & integration	4	Rectangular	1.732050808	1	2.3	∞
Test Sample Related						
Device positioning	2.9	Normal	1	1	2.9	12
Device holder uncertainty	3.6	Normal	1	1	3.6	8
Power drift	5	Rectangular	1.732050808	1	2.9	∞
Phantom and Setup						
Phantom uncertainty	4	Rectangular	1.732050808	1	2.3	∞
Liquid conductivity (target)	5	Rectangular	1.732050808	0.64	1.8	∞
Liquid conductivity (measured)	2.5	Normal	1	0.64	1.6	∞
Liquid permittivity (target)	5	Rectangular	1.732050808	0.6	1.7	∞
Liquid permittivity (measured)	2.5	Normal	1	0.6	1.5	∞
Combined Standard Uncertainty					**11.92**	
Expanded Uncertainty (k=2)					**23.84**	

Measurement Uncertainty Table in accordance with IEEE Standard 1528-2003 (see reference [4])

2005 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.

MEASUREMENT UNCERTAINTIES (Cont.)

UNCERTAINTY BUDGET FOR SYSTEM VALIDATION						
Error Description	**Uncertainty Value ±%**	**Probability Distribution**	**Divisor**	**ci 1g**	**Uncertainty Value ±% (1g)**	**V_i or V_{eff}**
Measurement System						
Probe calibration	6.8	Normal	1	1	6.8	∞
Axial isotropy of the probe	4.7	Rectangular	1.732050808	1	2.7	∞
Spherical isotropy of the probe	9.6	Rectangular	1.732050808	1	5.5	∞
Spatial resolution	0	Rectangular	1.732050808	1	0.0	∞
Boundary effects	2	Rectangular	1.732050808	1	1.2	∞
Probe linearity	4.7	Rectangular	1.732050808	1	2.7	∞
Detection limit	1	Rectangular	1.732050808	1	0.6	∞
Readout electronics	0.3	Normal	1	1	0.3	∞
Response time	0	Rectangular	1.732050808	1	0.0	∞
Integration time	0	Rectangular	1.732050808	1	0.0	∞
RF ambient conditions	3	Rectangular	1.732050808	1	1.7	∞
RF Ambient Reflections	3	Rectangular	1.732050808	1	1.7	∞
Mech. constraints of robot	0.8	Rectangular	1.732050808	1	0.5	∞
Probe positioning	9.9	Rectangular	1.732050808	1	5.7	∞
Extrapolation & integration	4	Rectangular	1.732050808	1	2.3	∞
Dipole						
Device positioning	2	Rectangular	1.732050808	1	1.2	∞
Power & Power Drift	4.7	Rectangular	1.732050808	1	2.7	∞
Phantom and Setup						
Phantom uncertainty	4	Rectangular	1.732050808	1	2.3	∞
Liquid conductivity (target)	5	Rectangular	1.732050808	0.64	1.8	∞
Liquid conductivity (measured)	2.5	Normal	1	0.64	1.6	∞
Liquid permittivity (target)	5	Rectangular	1.732050808	0.6	1.7	∞
Liquid permittivity (measured)	2.5	Normal	1	0.6	1.5	∞
Combined Standard Uncertainty					**12.65**	
Expanded Uncertainty (k=2)					**25.29**	

Measurement Uncertainty Table in accordance with IEEE Standard 1528-2003 (see reference [4])

16.0 REFERENCES

[1] Federal Communications Commission, “Radiofrequency radiation exposure evaluation: portable devices”, Rule Part 47 CFR §2.1093: 1999.

[2] Health Canada, “Limits of Human Exposure to Radiofrequency Electromagnetic Fields in the Frequency Range from 3 kHz to 300 GHz”, Safety Code 6: 1999.

[3] Federal Communications Commission, “Evaluating Compliance with FCC Guidelines for Human Exposure to Radio frequency Electromagnetic Fields”, OET Bulletin 65, Supplement C (Edition 01-01), FCC, Washington, D.C.: June 2001.

[4] IEEE Standard 1528-2003, “Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques”: December 2003.

[5] Industry Canada, “Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands)”, Radio Standards Specification RSS-102 Issue 2: November 2005.

[6] Schmid & Partner Engineering AG, “DASY4 Manual V4.5”: March 2005.

2005 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.

APPENDIX A - SAR MEASUREMENT DATA

Date Tested: 11/21/2005

Head SAR - Right Ear - Cheek/Touch Position

DUT: Atlinks Model: 28021XXX-A; Type: Portable 5.8GHz FHSS Cordless Telephone Handset; Serial: 50000401539HY

Ambient Temp: 23.0 °C; Fluid Temp: 22.3 °C; Barometric Pressure: 103.6 kPa; Humidity: 30%

Communication System: Modulated Fixed Frequency
3.6V, 800mAh NiMH Battery Pack
RF Output Power: 22.18 mW (Free-Space)
Frequency: 5848.889420 MHz; Channel 139; Duty Cycle: 1:9.52
Medium: HSL5200-5800 (σ = 5.15 mho/m; ε_r = 34.3; ρ = 1000 kg/m^3)
- Probe: EX3DV4 - SN3547; ConvF(4.71, 4.71, 4.71); Calibrated: 21/01/2005
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn353; Calibrated: 15/06/2005
- Phantom: SAM 4.0; Type: Fiberglas; Serial: 1033
- Measurement SW: DASY4, V4.6 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 159

Head SAR - Right Ear - Cheek/Touch Position - High Channel/Area Scan (9x22x1):
Measurement grid: dx=10mm, dy=10mm

Head SAR - Right Ear - Cheek/Touch Position - High Channel/Zoom Scan (8x8x8)/Cube 0:
Measurement grid: dx=4.3mm, dy=4.3mm, dz=3mm
Reference Value = 0.280 V/m; Power Drift = 3.45 dB
Peak SAR (extrapolated) = 0.157 W/kg
SAR(1 g) = 0.0470 mW/g; SAR(10 g) = 0.016 mW/g



2005 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.

Date Tested: 11/21/2005

Head SAR - Right Ear - Tilt Position (15°)

DUT: Atlinks Model: 28021XXX-A; Type: Portable 5.8GHz FHSS Cordless Telephone Handset; Serial: 50000401539HY

Ambient Temp: 23.0 °C; Fluid Temp: 22.3 °C; Barometric Pressure: 103.6 kPa; Humidity: 30%

Communication System: Modulated Fixed Frequency
3.6V, 800mAh NiMH Battery Pack
RF Output Power: 22.18 mW (Free-Space)
Frequency: 5848.889420 MHz; Channel 139; Duty Cycle: 1:9.52
Medium: HSL5200-5800 (σ = 5.15 mho/m; ε_r = 34.3; ρ = 1000 kg/m^3)
- Probe: EX3DV4 - SN3547; ConvF(4.71, 4.71, 4.71); Calibrated: 21/01/2005
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn353; Calibrated: 15/06/2005
- Phantom: SAM 4.0; Type: Fiberglas; Serial: 1033
- Measurement SW: DASY4, V4.6 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 159

Head SAR - Right Ear - Tilt Position (15°) - High Channel/Area Scan (9x22x1):
Measurement grid: dx=10mm, dy=10mm

Head SAR - Right Ear - Tilt Position (15°) - High Channel/Zoom Scan (8x8x8)/Cube 0:
Measurement grid: dx=4.3mm, dy=4.3mm, dz=3mm
Reference Value = 1.02 V/m; Power Drift = -2.68 dB
Peak SAR (extrapolated) = 0.271 W/kg
SAR(1 g) = 0.0786 mW/g; SAR(10 g) = 0.025 mW/g



2005 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.

Z-Axis Scan



2005 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.

Fluid Depth (>15cm)



2005 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.

Date Tested: 11/21/2005

Head SAR - Left Ear - Cheek/Touch Position

DUT: Atlinks Model: 28021XXX-A; Type: Portable 5.8GHz FHSS Cordless Telephone Handset; Serial: 50000401539HY

Ambient Temp: 23.0 °C; Fluid Temp: 22.3 °C; Barometric Pressure: 103.6 kPa; Humidity: 30%

Communication System: Modulated Fixed Frequency
3.6V, 800mAh NiMH Battery Pack
RF Output Power: 22.18 mW (Free-Space)
Frequency: 5848.889420 MHz; Channel 139; Duty Cycle: 1:9.52
Medium: HSL5200-5800 (σ = 5.15 mho/m; ε_r = 34.3; ρ = 1000 kg/m^3)
- Probe: EX3DV4 - SN3547; ConvF(4.71, 4.71, 4.71); Calibrated: 21/01/2005
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn353; Calibrated: 15/06/2005
- Phantom: SAM 4.0; Type: Fiberglas; Serial: 1033
- Measurement SW: DASY4, V4.6 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 159

Head SAR - Left Ear - Cheek/Touch Position - High Channel/Area Scan (9x22x1):
Measurement grid: dx=10mm, dy=10mm

Head SAR - Left Ear - Cheek/Touch Position - High Channel/Zoom Scan (8x8x8)/Cube 0:
Measurement grid: dx=4.3mm, dy=4.3mm, dz=3mm
Reference Value = 1.51 V/m; Power Drift = -0.374 dB
Peak SAR (extrapolated) = 0.180 W/kg
SAR(1 g) = 0.0550 mW/g; SAR(10 g) = 0.019 mW/g



2005 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.

Date Tested: 11/21/2005

Head SAR - Left Ear - Tilt Position (15°)

DUT: Atlinks Model: 28021XXX-A; Type: Portable 5.8GHz FHSS Cordless Telephone Handset; Serial: 50000401539HY

Ambient Temp: 23.0 °C; Fluid Temp: 22.3 °C; Barometric Pressure: 103.6 kPa; Humidity: 30%

Communication System: Modulated Fixed Frequency
3.6V, 800mAh NiMH Battery Pack
RF Output Power: 22.18 mW (Free-Space)
Frequency: 5848.889420 MHz; Channel 139; Duty Cycle: 1:9.52
Medium: HSL5200-5800 (σ = 5.15 mho/m; ε_r = 34.3; ρ = 1000 kg/m^3)
- Probe: EX3DV4 - SN3547; ConvF(4.71, 4.71, 4.71); Calibrated: 21/01/2005
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn353; Calibrated: 15/06/2005
- Phantom: SAM 4.0; Type: Fiberglas; Serial: 1033
- Measurement SW: DASY4, V4.6 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 159

Head SAR - Left Ear - Tilt Position (15°) - High Channel/Area Scan (9x22x1):
Measurement grid: dx=10mm, dy=10mm

Head SAR - Left Ear - Tilt Position (15°) - High Channel/Zoom Scan (8x8x8)/Cube 0:
Measurement grid: dx=4.3mm, dy=4.3mm, dz=3mm
Reference Value = 0.987 V/m; Power Drift = 3.70 dB
Peak SAR (extrapolated) = 0.261 W/kg
SAR(1 g) = 0.0772 mW/g; SAR(10 g) = 0.026 mW/g



2005 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.

Date Tested: 11/21/2005

Body-Worn SAR - Back Side of DUT

DUT: Atlinks Model: 28021XXX-A; Type: Portable 5.8GHz FHSS Cordless Telephone Handset; Serial: 50000401539HY

Body-Worn Accessory: Plastic Belt-Clip; Audio Accessory: Generic Ear-Microphone

Ambient Temp: 23.6 °C; Fluid Temp: 22.0 °C; Barometric Pressure: 103.5 kPa; Humidity: 30%

Communication System: Modulated Fixed Frequency
3.6V, 800mAh NiMH Battery Pack
RF Output Power: 22.18 mW (Free-Space)
Frequency: 5848.889420 MHz; Channel 139; Duty Cycle: 1:9.52
Medium: M5200-5800 (σ = 5.99 mho/m; ε_r = 46.9; ρ = 1000 kg/m^3

- Probe: EX3DV4 - SN3547; ConvF(4.59, 4.59, 4.59); Calibrated: 21/01/2005
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn353; Calibrated: 15/06/2005
- Phantom: SAM 4.0; Type: Fiberglas; Serial: 1033
- Measurement SW: DASY4, V4.6 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 159

Body-Worn SAR - 0.7 cm Belt-Clip Separation Distance to planar phantom - High Channel/Area Scan (9x22x1):
Measurement grid: dx=10mm, dy=10mm

Body-Worn SAR - 0.7 cm Belt-Clip Separation Distance to planar phantom - High Channel/Zoom Scan (8x8x8)/Cube 0:
Measurement grid: dx=4.3mm, dy=4.3mm, dz=3mm
Reference Value = 0.287 V/m; Power Drift = 3.63 dB
Peak SAR (extrapolated) = 0.226 W/kg
SAR(1 g) = 0.0720 mW/g; SAR(10 g) = 0.029 mW/g



2005 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.

Z-Axis Scan



2005 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.

Fluid Depth (>15cm)

2005 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.

APPENDIX B - SYSTEM PERFORMANCE CHECK DATA

2005 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.

Date Tested: 11/21/2005

System Performance Check (Brain) - 5800 MHz Dipole

DUT: Dipole 5GHz; Model: D5GHzV2; Type: System Performance Check; Serial: 1031; Calibrated: 01/11/2005

Ambient Temp: 23.3 °C; Fluid Temp: 22.3 °C; Barometric Pressure: 103.6 kPa; Humidity: 30%

Communication System: CW
Forward Conducted Power: 250 mW
Frequency: 5800 MHz; Duty Cycle: 1:1
Medium: HSL5200-5800 (σ = 5.15 mho/m; ε_r = 34.3; ρ = 1000 kg/m^3)

- Probe: EX3DV4 - SN3547; ConvF(4.71, 4.71, 4.71); Calibrated: 21/01/2005
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn353; Calibrated: 15/06/2005
- Phantom: SAM 4.0; Type: Fiberglas; Serial: 1033
- Measurement SW: DASY4, V4.6 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 159

5800 MHz Dipole - System Performance Check/Area Scan (9x13x1):
Measurement grid: dx=5mm, dy=5mm

5800 MHz Dipole - System Performance Check/Zoom Scan (8x8x8)/Cube 0:
Measurement grid: dx=4.3mm, dy=4.3mm, dz=3mm
Reference Value = 96.6 V/m; Power Drift = 0.071 dB
Peak SAR (extrapolated) = 80.6 W/kg
SAR(1 g) = 19.4 mW/g; SAR(10 g) = 5.45 mW/g



2005 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.

Z-Axis Scan



2005 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.

APPENDIX C - MEASURED FLUID DIELECTRIC PARAMETERS

5800 MHz System Performance Check & DUT Evaluation (Brain)

****

Celltech Labs Inc.
Test Result for UIM Dielectric Parameter
Mon 21/Nov/2005
Frequency(GHz)
FCC_eH FCC OET 65 Supplement C (June 2001) Limits for Head Epsilon
FCC_sH FCC OET 65 Supplement C (June 2001) Limits for Head Sigma
Test_e Epsilon of UIM
Test_s Sigma of UIM

****

Freq	FCC_eH	FCC_sH	Test_e	Test_s
5.7000	35.41	5.17	33.96	5.003
5.7100	35.40	5.18	34.13	4.985
5.7200	35.39	5.19	34.09	5.053
5.7300	35.38	5.20	34.11	5.117
5.7400	35.37	5.21	33.97	5.041
5.7500	35.36	5.22	34.22	5.120
5.7600	35.35	5.23	34.07	5.113
5.7700	35.33	5.24	34.20	5.133
5.7800	35.32	5.25	34.27	5.166
5.7900	35.31	5.26	34.18	5.171
5.8000	35.30	5.27	34.30	5.152
5.8100	35.29	5.28	34.18	5.152
5.8200	35.28	5.29	34.04	5.173
5.8300	35.27	5.30	33.88	5.154
5.8400	35.25	5.31	33.82	5.247
5.8500	35.24	5.32	34.19	5.227
5.8600	35.23	5.33	33.98	5.212
5.8700	35.22	5.34	34.13	5.251
5.8800	35.21	5.35	34.25	5.213
5.8900	35.20	5.36	34.12	5.255
5.9000	35.19	5.37	34.25	5.349

2005 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.

5800 MHz DUT Evaluation (Body)

****

Celltech Labs Inc.
Test Result for UIM Dielectric Parameter
Mon 21/Nov/2005
Frequency(GHz)
FCC_eH FCC Bulletin 65 Supplement C (June 2001) Limits for Head Epsilon
FCC_sH FCC Bulletin 65 Supplement C (June 2001) Limits for Head Sigma
FCC_eB FCC Limits for Body Epsilon
FCC_sB FCC Limits for Body Sigma
Test_e Epsilon of UIM
Test_s Sigma of UIM

****

Freq	FCC_eB	FCC_sB	Test_e	Test_s
5.7000	48.34	5.88	46.44	5.734
5.7100	48.32	5.89	46.46	5.659
5.7200	48.31	5.91	46.66	5.748
5.7300	48.30	5.92	46.81	5.854
5.7400	48.28	5.93	46.55	5.839
5.7500	48.27	5.94	46.81	5.920
5.7600	48.25	5.95	46.64	5.892
5.7700	48.24	5.96	46.76	5.971
5.7800	48.23	5.98	47.08	5.994
5.7900	48.21	5.99	47.09	5.980
5.8000	48.20	6.00	46.87	5.985
5.8100	48.19	6.01	46.74	5.962
5.8200	48.17	6.02	46.50	5.949
5.8300	48.16	6.04	46.70	5.908
5.8400	48.15	6.05	46.44	6.053
5.8500	48.13	6.06	46.99	5.928
5.8600	48.12	6.07	46.61	5.997
5.8700	48.10	6.08	46.82	6.016
5.8800	48.09	6.09	46.78	5.962
5.8900	48.08	6.11	46.64	6.008
5.9000	48.06	6.12	46.71	6.160

2005 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.

APPENDIX D - MANUFACTURER'S TISSUE SIMULANT DATA SHEET

Schmid & Partner Engineering AG

s p e a g

Zeughausstrasse 43, 8004 Zurich, Switzerland
Phone +41 1 245 9700, Fax +41 1 245 9779
info@speag.com, http://www.speag.com

Material Safety Data Sheet

1 Identification of the substance and of the manufacturer / origin

Item	Head Tissue Simulation Liquid HSL5800 Muscle Tissue Simulation Liquid MSL 5800
Type No	SL AAH 580, SL AAM 580
Series No	N/A
Manufacturer / Origin	Schmid & Partner Engineering AG Zeughausstrasse 43 8004 Zürich Switzerland Phone +41 1 245 9700, Fax +41 1 245 9779, support@speag.com

Use of the substance:
Liquid simulating physical parameters of Head or Muscle Tissue in the RF range to 6GHz.

2 Composition / Information on ingredients

The Item is composed of the following ingredients:

Water	64 - 78%
Mineral Oil	11 - 18%
Emulsifiers	9 - 15%
Additives and Salt	2 - 3%

Safety relevant ingredients according to EU directives:

CAS-No 107-41-5	< 4%	2-Methyl-2,4-pentandiol (Hexylene Glycol): Xi irritant, R36/38 irritant for eyes and skin
CAS-No 770-35-4	< 2%	1-Phenoxy-2-propanol (Propylene Glycol Phenyl Ether): Xi irritant, R36 irritant for eyes
CAS-No 93-83-4	< 2%	N,N-bis(2-Hydroxyethyl)oleamide: Xi irritant, R36/38 irritant for eyes and skin
CAS-No 9004-95-9	< 0.5%	Polyethylene glycol cetyl ether: Xi irritant, R22 harmful if swallowed, R36/38 irritant for eyes and skin R50 Very toxic to aquatic organisms

According to EU guidelines and Swiss rules, the product is not a dangerous mixture and therefore not required to be marked by symbols.

3 Hazards identification

Identification not required.

4 First aid measures

The product reacts slightly alkaline.

After skin contact:	Wash with fresh water and mild sope
After eye contact:	Rinse out with plenty of water for several minutes with the eyelid held open. Consult an ophthalmologist if necessary.
After ingestion:	Do not induce vomiting. Get medical attention.

5 Fire-fighting measures

Firefighting media	CO_2, foam, dry chemical
Combustion products	Carbon oxides, nitrogen and traces of oxides of chlorine and sulfur, HCl

Due to the high water content, the liquid is self-extinguishing.

6 Accidental release measures

Person-related precaution measures: wash with water and mild soap.
Environmental-protection measures: do not allow to enter sewerage system.
Procedures for cleaning / absorption: Use oil-binding agents., forward for disposal. Spills may cause slippery conditions.

7 Handling and storage

Handling: Keep in open container only for minimum required time in order to avoid water evaporation.
Storage: tightly closed, between >0 to 40°C. Avoid direct solar irradiation of the storage containers.

8 Exposure controls / personal protection

Protection measures are not generally required. For eye protection, industrial safety glasses are recommended.
Personal hygiene and clean working practices are sufficient.

9 Physical and chemical properties

Form:	liquid
Colour:	medium to dark brown, transparent to opaque
Odour:	almost odourless / slightly oily
pH-Value:	slightly alcalic
Boiling point:	100°C
Density:	1g/cm^3

10 Stability and reactivity

Conditions to be avoided: heating above 40°C
The product contains water and is not compatible with strong oxidizers or magnesium.

11 Toxicological information

LD50 > 40 g/kg
Further data: the product should be handled with the care usual when dealing with chemicals

12 Ecological information

Contains mineral oil. Do not allow to enter waters, waste water, or soil!

13 Disposal considerations

Disposal is possible by splitting the mineral oil from the emulsion with absorbing agents, with salt or ultra-filtration. Dispose as other mineral oil containing products according to local regulations.
Product packing must be disposed of in compliance with respect national regulations.

14 Transport information

Not subject to transport regulations.

15 Regulatory information

No special labelling required.

16 Other information

Release date:	6.1.2005
Responsible:	FB

APPENDIX E - SAR TEST SETUP PHOTOGRAPHS

2005 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.

HEAD SAR TEST SETUP PHOTOGRAPHS

Right Head Section / Cheek-Touch Position





HEAD SAR TEST SETUP PHOTOGRAPHS

Right Head Section / Ear-Tilt Position (15°)

2005 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.

HEAD SAR TEST SETUP PHOTOGRAPHS

Left Head Section / Cheek-Touch Position

2005 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.

HEAD SAR TEST SETUP PHOTOGRAPHS

Left Head Section / Ear-Tilt Position (15°)

2005 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.

BODY-WORN SAR TEST SETUP PHOTOGRAPHS

0.7 cm Belt-Clip Spacing from Back of DUT to Planar Phantom with Plastic Belt-Clip and Generic Ear-Microphone Accessories





2005 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.

DUT PHOTOGRAPHS

Front of DUT

Back of DUT

Back of DUT with Belt-Clip

Top end of DUT

Bottom end of DUT

2005 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.

DUT PHOTOGRAPHS

Left Side of DUT

Right Side of DUT

Plastic Belt-Clip Accessory

2005 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.

DUT PHOTOGRAPHS

DUT Battery Compartment

DUT with NiMH Battery 3.6 V, 800 mAh



NiMH Battery 3.6 V, 800 mAh

2005 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.

DUT PHOTOGRAPHS

DUT with Generic Ear-Microphone Accessory

2005 Celltech Labs Inc. This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.

APPENDIX H - SAM PHANTOM CERTIFICATE OF CONFORMITY

Schmid & Partner
Engineering AG

Zeughausstrasse 43, 8004 Zurich, Switzerland, Phone +41 1 245 97 00, Fax +41 1 245 97 79

Certificate of conformity / First Article Inspection

Item	SAM Twin Phantom V4.0
Type No	QD 000 P40 BA
Series No	TP-1002 and higher
Manufacturer / Origin	Untersee Composites Hauptstr. 69 CH-8559 Fruthwilen Switzerland

Tests

The series production process used allows the limitation to test of first articles.
Complete tests were made on the pre-series Type No. QD 000 P40 AA, Serial No. TP-1001 and on the series first article Type No. QD 000 P40 BA, Serial No. TP-1006. Certain parameters have been retested using further series units (called samples).

Test	Requirement	Details	Units tested
Shape	Compliance with the geometry according to the CAD model.	IT'IS CAD File (*)	First article, Samples
Material thickness	Compliant with the requirements according to the standards	2mm +/- 0.2mm in specific areas	First article, Samples
Material parameters	Dielectric parameters for required frequencies	200 MHz – 3 GHz Relative permittivity < 5 Loss tangent < 0.05.	Material sample TP 104-5
Material resistivity	The material has been tested to be compatible with the liquids defined in the standards	Liquid type HSL 1800 and others according to the standard.	Pre-series, First article

Standards

[1] CENELEC EN 50361
[2] IEEE P1528-200x draft 6.5
[3] IEC PT 62209 draft 0.9
(*) The IT'IS CAD file is derived from [2] and is also within the tolerance requirements of the shapes of [1] and [3].

Conformity

Based on the sample tests above, we certify that this item is in compliance with the uncertainty requirements of SAR measurements specified in standard [1] and draft standards [2] and [3].

Date 18.11.2001

Signature / Stamp

Schmid & Partner
Engineering AG
Zeughausstrasse 43, CH-8004 Zurich
Tel. +41 1 245 97 00, Fax +41 1 245 97 79