

● Product specification

WM-200

MOUSE

- Operation: Two button & wheel
- RF (radio frequency) Technology: Feel free operation within 2M
- Combination: Compatible with WINDOWS 95®/ME®/98®/NT®/2000®/LINUX...etc
- Easy installation : Plug & Play
- Battery : 2.2V ~ 3V (AAA BATTERY 2EA)
- Battery life : More than 3 months
- Resolution : 400DPI
- Frequency Range : 27Mhz

RECEIVER

- Connector : PS/2
- 1.8M WIRE

WS-200

MOUSE

- Operation: Two button & wheel
- RF (radio frequency) Technology: Feel free operation within 2M
- Combination: Compatible with WINDOWS 95®/ME®/98®/NT®/2000®/LINUX...etc
- Easy installation : Plug & Play
- Battery : 2.2V ~ 3V (AAA BATTERY 2EA)
- Battery life : More than 3 months
- Resolution : 400DPI
- Frequency Range : 27Mhz

KEYBOARD

- Operation: Compact type 100key (Multi-language available)
- RF Technology: Feel free operation within 2M
- Combination: Compatible with WINDOWS 95®/ME®/98®/NT®/2000®/LINUX...etc
- Easy installation : Plug & Play
- Battery : 3V (AA BATTERY 2EA)
- Battery life : 10 ~ 12 months
- Frequency Range : 27Mhz

RECEIVER

- Connector : Two PS/2 port connector
(One for mouse, Another for Keyboard)
- 1.8M WIRE

● Function description

WM-200

► MOUSE UNIT (TOP SIDE)

- 1. Left button : used for execute programs
- 2. Right button : usually used for invoke menu
- 3. Scroll wheel : used to scroll window at any time without click scroll bar




► KEYBOARD UNIT (TOP SIDE)

- lamp : used for notify user working status and power-on blinking



► MOUSE UNIT (BOTTOM SIDE)

- 1. Ball cover : open to clean ball and roller when movement is not correct
- 2. Battery cover : open to put or replace batteries (check correct direction)
- 3. Feets : 2 feets let user move mouse smoothly and softly



WS-200

► MOUSE UNIT (TOP SIDE)

- 1. Left button : used for execute programs
- 2. Right button : usually used for invoke menu
- 3. Scroll wheel : used to scroll window at any time without click scroll bar




► KEYBOARD UNIT (TOP SIDE)

- 1. Fn keys : if press these keys with pressed Fn key, function inside box is executed
- All function is possible with this 100 keys




► RECEIVER UNIT (TOP SIDE)

- LED lamp
- 1. Mouse : used for notify user working status and power-on blinking
- 2. Keyboard : used for notify user working status and power-on blinking
- 3. NumLock, CapsLock, ScrollLock : power-on blinking and toggle function if press each key
- 4. PS/2 cable : Keyboard and mouse cable is for PS/2 port and very similar each other. So check carefully before plug in




► **MOUSE UNIT (BOTTOM SIDE)**

- 1. Ball cover : open to clean ball and roller when movement is not correct
- 2. Battery cover : open to put or replace batteries (check correct direction)
- 3. Fools : 2 fools let user move mouse smoothly and softly



► **MOUSE KEYBOARD UNIT (BOTTOM SIDE)**

- 1. LEG :
there is 2 LEGS to adjust angle of keyboard, so user can fix it to favorite angle
- 2. Battery cover : open to put or replace batteries (check correct direction)



● **Installation of receiver unit**

WM-200

1. Turn the power off of your IBM compatible PC
2. Plug connector of receiver unit into PS/2 port(keyboard and mouse is very similar, so be careful not to plug in wrong position)
3. Turn the power on of your PC.
4. lamp on receiver unit blink for some seconds (blinking time is differ from the system)
5. 'WING MOUSE' is automatically detected by the system.
6. Put 2 AAA batteries in 'WING MOUSE'. If mouse does not work, remove batteries and put again after 10 seconds. If it does not work after 2 or 3 times trial, check battery.
7. After Windows® boot, movement of mouse s can be easily checked by the lamp of receiver unit.

WS-200

1. Turn the power off of your IBM compatible PC(if you must plug during power-on, you must plug mouse cable first)
2. Plug connector of receiver unit into PS/2 port(keyboard and mouse is very similar, so be careful not to plug in wrong position)