

## Partial FCC Test Report

**Report No.:** RF150722C27-2

**FCC ID:** GKR-TP00078A

**Test Model:** TP00078A

**Received Date:** Jul. 22, 2015

**Test Date:** Jul. 28, 2015 ~ Aug. 18, 2015

**Issued Date:** Aug. 26, 2015

**Applicant:** Compal Electronics Inc

**Address:** No.581, Ruiguang Rd., Neihu District, Taipei City, Taiwan 11492, R.O.C.

**Issued By:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

**Lab Address:** No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan ( R.O.C )

**Test Location (1):** No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

**Test Location (2):** No.215, Sec. 3, Beixin Rd., Xindian Dist., New Taipei City 231, Taiwan, R.O.C



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

## Table of Contents

|                                                                  |           |
|------------------------------------------------------------------|-----------|
| <b>Release Control Record .....</b>                              | <b>3</b>  |
| <b>1 Certificate of Conformity .....</b>                         | <b>4</b>  |
| <b>2 Summary of Test Results.....</b>                            | <b>5</b>  |
| 2.1 Measurement Uncertainty.....                                 | 5         |
| 2.2 Modification Record .....                                    | 5         |
| <b>3 General Information .....</b>                               | <b>6</b>  |
| 3.1 General Description of EUT .....                             | 6         |
| 3.2 Description of Test Modes.....                               | 7         |
| 3.2.1 Test Mode Applicability and Tested Channel Detail.....     | 8         |
| 3.3 Description of Support Units .....                           | 10        |
| 3.3.1 Configuration of System under Test .....                   | 10        |
| 3.4 General Description of Applied Standards.....                | 10        |
| <b>4 Test Types and Results .....</b>                            | <b>11</b> |
| 4.1 Radiated Emission and Bandedge Measurement .....             | 11        |
| 4.1.1 Limits of Radiated Emission and Bandedge Measurement ..... | 11        |
| 4.1.2 Test Instruments .....                                     | 12        |
| 4.1.3 Test Procedures.....                                       | 13        |
| 4.1.4 Deviation from Test Standard .....                         | 13        |
| 4.1.5 Test Set Up .....                                          | 14        |
| 4.1.6 EUT Operating Conditions.....                              | 14        |
| 4.1.7 Test Results .....                                         | 15        |
| 4.2 Conducted Emission Measurement.....                          | 21        |
| 4.2.1 Limits of Conducted Emission Measurement .....             | 21        |
| 4.2.2 Test Instruments .....                                     | 21        |
| 4.2.3 Test Procedures.....                                       | 22        |
| 4.2.4 Deviation From Test Standard .....                         | 22        |
| 4.2.5 Test Setup.....                                            | 22        |
| 4.2.6 EUT Operating Condition .....                              | 22        |
| 4.2.7 Test Results .....                                         | 23        |
| 4.3 Maximum Output Power .....                                   | 27        |
| 4.3.1 Limits of Maximum Output Power Measurement .....           | 27        |
| 4.3.2 Test Setup.....                                            | 27        |
| 4.3.3 Test Instruments .....                                     | 27        |
| 4.3.4 Test Procedure .....                                       | 27        |
| 4.3.5 Deviation fromTest Standard .....                          | 27        |
| 4.3.6 EUT Operating Condition .....                              | 27        |
| 4.3.7 Test Results .....                                         | 28        |
| <b>5 Pictures of Test Arrangements.....</b>                      | <b>30</b> |
| <b>Appendix – Information on the Testing Laboratories .....</b>  | <b>31</b> |



A D T

### Release Control Record

| Issue No.     | Description      | Date Issued   |
|---------------|------------------|---------------|
| RF150722C27-2 | Original Release | Aug. 26, 2015 |

## 1 Certificate of Conformity

**Product:** Tablet Computer

**Brand:** Lenovo

**Test Model:** TP00078A

**Sample Status:** Production Unit

**Applicant:** Compal Electronics Inc

**Test Date:** Jul. 28, 2015 ~ Aug. 18, 2015

**Standards:** 47 CFR FCC Part 15, Subpart C (Section 15.247)  
ANSI C63.10:2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**Prepared by :**

*Rona Chen*

**Date:**

Aug. 26, 2015

Rona Chen / Specialist

**Approved by :**

*Kay Wu*

**Date:**

Aug. 26, 2015

Kay Wu / Supervisor

## 2 Summary of Test Results

| 47 CFR FCC Part 15, Subpart C (SECTION 15.247) |                                                                                                               |        |                                                                                     |
|------------------------------------------------|---------------------------------------------------------------------------------------------------------------|--------|-------------------------------------------------------------------------------------|
| FCC Clause                                     | Test Item                                                                                                     | Result | Remarks                                                                             |
| 15.207                                         | AC Power Conducted Emission                                                                                   | PASS   | Meet the requirement of limit.<br>Minimum passing margin is -16.68dB at 0.15391MHz. |
| 15.247(a)(1)(iii)                              | Number of Hopping Frequency Used                                                                              | N/A    | Refer to Note                                                                       |
| 15.247(a)(1)(iii)                              | Dwell Time on Each Channel                                                                                    | N/A    | Refer to Note                                                                       |
| 15.247(a)(1)                                   | 1. Hopping Channel Separation<br>2. Spectrum Bandwidth of a Frequency Hopping Sequence Spread Spectrum System | N/A    | Refer to Note                                                                       |
| 15.247(b)                                      | Maximum Peak Output Power                                                                                     | PASS   | Meet the requirement of limit.                                                      |
| 15.205 & 209                                   | Radiated Emissions                                                                                            | PASS   | Meet the requirement of limit.<br>Minimum passing margin is -3.16dB at 533.1MHz.    |
| 15.247(d)                                      | Band Edge Measurement                                                                                         | N/A    | Refer to Note                                                                       |
| 15.247(d)                                      | Antenna Port Emission                                                                                         | N/A    | Refer to Note                                                                       |
| 15.203                                         | Antenna Requirement                                                                                           | PASS   | No antenna connector is used.                                                       |

Note: Only test item of Maximum Peak Output Power, AC power Conducted Emission, and Radiated Emissions were performed for this report. Other testing data please refer to SPORTON International Inc. report no.: FR473142AC for module (Brand: Broadcom, Model: BCM94356Z, FCC ID: QDS-BRCM1085).

### 2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT:

The listed uncertainties are the worst case uncertainty for the entire range of measurement. Please note that the uncertainty values are provided for informational purposes only and are not used in determining the PASS/FAIL results.

| Measurement                        | Frequency       | Expanded Uncertainty (k=2) (±) |
|------------------------------------|-----------------|--------------------------------|
| Conducted Emissions at mains ports | 150kHz ~ 30MHz  | 2.44 dB                        |
| Radiated Emissions up to 1 GHz     | 30MHz ~ 200MHz  | 2.0153 dB                      |
|                                    | 200MHz ~1000MHz | 2.0224 dB                      |
| Radiated Emissions above 1 GHz     | 1GHz ~ 18GHz    | 1.0121 dB                      |
|                                    | 18GHz ~ 40GHz   | 1.1508 dB                      |

### 2.2 Modification Record

There were no modifications required for compliance.

### 3 General Information

#### 3.1 General Description of EUT

|                     |                                             |
|---------------------|---------------------------------------------|
| Product             | Tablet Computer                             |
| Brand               | Lenovo                                      |
| Test Model          | TP00078A                                    |
| Status of EUT       | Production Unit                             |
| Power Supply Rating | 20Vdc (Adapter)<br>15.2Vdc (Li-ion battery) |
| Modulation Type     | GFSK, $\pi/4$ -DQPSK, 8DPSK                 |
| Transfer Rate       | 1/2/3 Mbps                                  |
| Operating Frequency | 2402 ~ 2480 MHz                             |
| Number of Channel   | 79                                          |
| Antenna Type        | Refer to Note as below                      |
| Antenna Connector   | N/A                                         |
| Accessory Device    | Refer to Note as below                      |
| Data Cable Supplied | Refer to Note as below                      |

Note:

1. This EUT contains two samples listed as below.

| Sample | Difference                                       |
|--------|--------------------------------------------------|
| EUT 1  | Tablet computer with Antenna (Ethertronics Inc.) |
| EUT 2  | Tablet computer with Antenna (HIGH-TEK)          |

2. The antenna information is listed as below.

| Antenna Type | Brand Name        | Parts Number                                                     | Antenna Gain               |                          |
|--------------|-------------------|------------------------------------------------------------------|----------------------------|--------------------------|
|              |                   |                                                                  | 2.4GHz                     | 5GHz                     |
| PIFA         | Ethertronics Inc. | WLAN Main Antenna: 5002022<br>WLAN Aux. Antenna: 5002030         | Main: 0.85<br>Aux.: -0.71  | Main: 0.46<br>Aux.: 0.36 |
|              | HIGH-TEK          | WLAN Main Antenna: DC33001RQ00<br>WLAN Aux. Antenna: DC33001RQ10 | Main: -0.17<br>Aux.: -0.30 | Main: 1.84<br>Aux.: 1.56 |

3. The EUT contains following accessory devices.

| Product     | Brand    | Model       | Description                                         |
|-------------|----------|-------------|-----------------------------------------------------|
| Adapter 1   | lenovo   | ADLX45NCC2A | I/P: 100-240Vac, 50~60Hz, 1.3A<br>O/P: 20Vdc, 2.25A |
| Adapter 2   | lenovo   | ADLX45NDC2A | I/P: 100-240Vac, 50~60Hz, 1.3A<br>O/P: 20Vdc, 2.25A |
| Battery     | lenovo   | SB10F46465  | 15.2Vdc, 2.895Ah                                    |
| WLAN Module | Broadcom | BCM94356Z   | --                                                  |

4. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

### 3.2 Description of Test Modes

79 channels are provided to this EUT:

| Channel | Freq. (MHz) | Channel | Freq. (MHz) | Channel | Freq. (MHz) | Channel | Freq. (MHz) |
|---------|-------------|---------|-------------|---------|-------------|---------|-------------|
| 0       | 2402        | 20      | 2422        | 40      | 2442        | 60      | 2462        |
| 1       | 2403        | 21      | 2423        | 41      | 2443        | 61      | 2463        |
| 2       | 2404        | 22      | 2424        | 42      | 2444        | 62      | 2464        |
| 3       | 2405        | 23      | 2425        | 43      | 2445        | 63      | 2465        |
| 4       | 2406        | 24      | 2426        | 44      | 2446        | 64      | 2466        |
| 5       | 2407        | 25      | 2427        | 45      | 2447        | 65      | 2467        |
| 6       | 2408        | 26      | 2428        | 46      | 2448        | 66      | 2468        |
| 7       | 2409        | 27      | 2429        | 47      | 2449        | 67      | 2469        |
| 8       | 2410        | 28      | 2430        | 48      | 2450        | 68      | 2470        |
| 9       | 2411        | 29      | 2431        | 49      | 2451        | 69      | 2471        |
| 10      | 2412        | 30      | 2432        | 50      | 2452        | 70      | 2472        |
| 11      | 2413        | 31      | 2433        | 51      | 2453        | 71      | 2473        |
| 12      | 2414        | 32      | 2434        | 52      | 2454        | 72      | 2474        |
| 13      | 2415        | 33      | 2435        | 53      | 2455        | 73      | 2475        |
| 14      | 2416        | 34      | 2436        | 54      | 2456        | 74      | 2476        |
| 15      | 2417        | 35      | 2437        | 55      | 2457        | 75      | 2477        |
| 16      | 2418        | 36      | 2438        | 56      | 2458        | 76      | 2478        |
| 17      | 2419        | 37      | 2439        | 57      | 2459        | 77      | 2479        |
| 18      | 2420        | 38      | 2440        | 58      | 2460        | 78      | 2480        |
| 19      | 2421        | 39      | 2441        | 59      | 2461        |         |             |

### 3.2.1 Test Mode Applicability and Tested Channel Detail

| EUT Configure Mode | Applicable To |       |     |      | Description              |
|--------------------|---------------|-------|-----|------|--------------------------|
|                    | RE≥1G         | RE<1G | PLC | APCM |                          |
| A                  | √             | √     | √   | √    | EUT 1 (Ant. Ethertronic) |
| B                  | √             | √     | √   | √    | EUT 2 (Ant. HIGH-TEK)    |

Where **RE≥1G**: Radiated Emission above 1GHz

**RE<1G**: Radiated Emission below 1GHz

**PLC**: Power Line Conducted Emission

**APCM**: Antenna Port Conducted Measurement

#### NOTE:

1. For Radiated emission test, pre-tested GFSK,  $\pi/4$ -DQPSK, 8DPSK modulation type and found GFSK was the worse, therefore chosen for the final test and presented in the test report.

#### Radiated Emission Test (Above 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

| EUT Configure Mode | Available Channel | Tested Channel | Modulation Technology | Modulation Type | Packet Type |
|--------------------|-------------------|----------------|-----------------------|-----------------|-------------|
| A                  | 0 to 78           | 0, 39, 78      | FHSS                  | GFSK            | DH5         |
| B                  | 0 to 78           | 78             | FHSS                  | GFSK            | DH5         |

#### Radiated Emission Test (Below 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

| EUT Configure Mode | Available Channel | Tested Channel | Modulation Technology | Modulation Type | Packet Type |
|--------------------|-------------------|----------------|-----------------------|-----------------|-------------|
| A, B               | 0 to 78           | 78             | FHSS                  | GFSK            | DH5         |

#### Power Line Conducted Emission Test:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

| EUT Configure Mode | Available Channel | Tested Channel | Modulation Technology | Modulation Type | Packet Type |
|--------------------|-------------------|----------------|-----------------------|-----------------|-------------|
| A, B               | 0 to 78           | 78             | FHSS                  | GFSK            | DH5         |

### Antenna Port Conducted Measurement:

- ☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.


| EUT<br>Configure Mode | Available Channel | Tested Channel | Modulation<br>Technology | Modulation Type | Packet Type |
|-----------------------|-------------------|----------------|--------------------------|-----------------|-------------|
| A, B                  | 0 to 78           | 0, 39, 78      | FHSS                     | GFSK            | DH5         |
| A, B                  | 0 to 78           | 0, 39, 78      | FHSS                     | $\pi/4$ -DQPSK  | DH5         |
| A, B                  | 0 to 78           | 0, 39, 78      | FHSS                     | 8DPSK           | DH5         |

### Test Condition:

| Applicable To | Environmental Conditions | Input Power  | Tested by  |
|---------------|--------------------------|--------------|------------|
| RE $\geq$ 1G  | 25deg. C, 65%RH          | 120Vac, 60Hz | Karl Lee   |
| RE<1G         | 25deg. C, 65%RH          | 120Vac, 60Hz | Karl Lee   |
| PLC           | 25deg. C, 68%RH          | 120Vac, 60Hz | Toby Tian  |
| APCM          | 25deg. C, 65%RH          | 120Vac, 60Hz | Howard Kao |

### 3.3 Description of Support Units

#### 3.3.1 Configuration of System under Test



### 3.4 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC Part 15, Subpart C (15.247)**

**FCC Public Notice DA 00-705**

ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

**NOTE:** The EUT has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.

## 4 Test Types and Results

### 4.1 Radiated Emission and Bandedge Measurement

#### 4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

| Frequencies (MHz) | Field Strength (microvolts/meter) | Measurement Distance (meters) |
|-------------------|-----------------------------------|-------------------------------|
| 0.009 ~ 0.490     | 2400/F(kHz)                       | 300                           |
| 0.490 ~ 1.705     | 24000/F(kHz)                      | 30                            |
| 1.705 ~ 30.0      | 30                                | 30                            |
| 30 ~ 88           | 100                               | 3                             |
| 88 ~ 216          | 150                               | 3                             |
| 216 ~ 960         | 200                               | 3                             |
| Above 960         | 500                               | 3                             |

#### NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

#### 4.1.2 Test Instruments

| Description & Manufacturer                     | Model No.       | Serial No.                                                        | Date of Calibration | Due Date of Calibration |
|------------------------------------------------|-----------------|-------------------------------------------------------------------|---------------------|-------------------------|
| Spectrum Analyzer<br>Agilent Technologies      | N9038A          | MY52260177                                                        | May 19, 2015        | May 18, 2016            |
| Spectrum Analyzer<br>ROHDE & SCHWARZ           | FSU43           | 101261                                                            | Dec. 10, 2014       | Dec. 09, 2015           |
| BILOG Antenna<br>SCHWARZBECK                   | VULB9168        | 9168-472                                                          | Feb. 04, 2015       | Feb. 04, 2016           |
| HORN Antenna<br>ETS-Lindgren                   | 3117            | 00143293                                                          | Aug. 28, 2014       | Aug. 27, 2015           |
| Bluetooth Tester                               | CBT             | 100980                                                            | Apr. 27, 2015       | Apr. 26, 2016           |
| Preamplifier<br>Agilent                        | 310N            | 187226                                                            | Jun. 29, 2015       | Jun. 28, 2016           |
| Preamplifier<br>Agilent                        | 83017A          | 980116                                                            | Jan. 09, 2015       | Jan. 08, 2016           |
| Power Meter<br>Anritsu                         | ML2495A         | 1232002                                                           | Sep. 17, 2014       | Sep. 16, 2015           |
| Power Sensor<br>Anritsu                        | MA2411B         | 1207325                                                           | Sep. 17, 2014       | Sep. 16, 2015           |
| RF signal cable<br>ETS-LINDGREN                | 5D-FB           | Cable-CH1-01(R<br>FC-SMS-100-SM<br>S-120+RFC-SMS<br>-100-SMS-400) | Jun. 27, 2015       | Jun. 26, 2016           |
| RF signal cable<br>ETS-LINDGREN                | 8D-FB           | Cable-CH1-02(R<br>FC-SMS-100-SM<br>S-24)                          | Jun. 27, 2015       | Jun. 26, 2016           |
| Software<br>BV ADT                             | E3<br>8.130425b | NA                                                                | NA                  | NA                      |
| Antenna Tower<br>MF                            | NA              | NA                                                                | NA                  | NA                      |
| Turn Table<br>MF                               | NA              | NA                                                                | NA                  | NA                      |
| Antenna Tower & Turn<br>Table Controller<br>MF | MF-7802         | NA                                                                | NA                  | NA                      |

- Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in HsinTien Chamber 1.
3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
4. The FCC Site Registration No. is 149147.
5. The IC Site Registration No. is IC7450I-1.

#### 4.1.3 Test Procedures

- a. The EUT was placed on the top of a rotating table 0.8 meters (for below 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

**Note:**


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for RMS Average (Duty cycle < 98%) for Average detection (AV) at frequency above 1GHz, then the measurement results was added to a correction factor ( $10 \log(1/\text{duty cycle})$ ).
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz (Duty cycle  $\geq 98\%$ ) for Average detection (AV) at frequency above 1GHz.
5. All modes of operation were investigated and the worst-case emissions are reported.

#### 4.1.4 Deviation from Test Standard


No deviation.

#### 4.1.5 Test Set Up

##### <Frequency Range below 1GHz>



##### <Frequency Range above 1GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.1.6 EUT Operating Conditions

Set the EUT under transmission condition continuously at specific channel frequency.

#### 4.1.7 Test Results

#### ABOVE 1GHz DATA :

#### Mode A

#### GFSK

| EUT TEST CONDITION       |                 | MEASUREMENT DETAIL |                           |
|--------------------------|-----------------|--------------------|---------------------------|
| CHANNEL                  | Channel 0       | FREQUENCY RANGE    | 1GHz ~ 25GHz              |
| INPUT POWER              | 120Vac, 60 Hz   | DETECTOR FUNCTION  | Peak (PK)<br>Average (AV) |
| ENVIRONMENTAL CONDITIONS | 25deg. C, 65%RH | TESTED BY          | Karl Lee                  |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                               |                         |                   |                |                             |                       |                          |                           |                            |         |
|-----------------------------------------------------|-------------------------------|-------------------------|-------------------|----------------|-----------------------------|-----------------------|--------------------------|---------------------------|----------------------------|---------|
| FREQ.<br>(MHz)                                      | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB/m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK  |
| 2328                                                | 42.66                         | 41.15                   | 54                | -11.34         | 31.73                       | 5.3                   | 35.52                    | 100                       | 64                         | Average |
| 2328                                                | 62.07                         | 60.56                   | 74                | -11.93         | 31.73                       | 5.3                   | 35.52                    | 100                       | 64                         | Peak    |
| 2402                                                | 93.95                         | 92.22                   |                   |                | 31.8                        | 5.4                   | 35.47                    | 100                       | 64                         | Average |
| 2402                                                | 95.12                         | 93.39                   |                   |                | 31.8                        | 5.4                   | 35.47                    | 100                       | 64                         | Peak    |
| 2488                                                | 42.72                         | 40.71                   | 54                | -11.28         | 31.9                        | 5.53                  | 35.42                    | 100                       | 64                         | Average |
| 2488                                                | 62.54                         | 60.53                   | 74                | -11.46         | 31.9                        | 5.53                  | 35.42                    | 100                       | 64                         | Peak    |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                               |                         |                   |                |                             |                       |                          |                           |                            |         |
| FREQ.<br>(MHz)                                      | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB/m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK  |
| 2374                                                | 42.06                         | 40.4                    | 54                | -11.94         | 31.78                       | 5.37                  | 35.49                    | 103                       | 267                        | Average |
| 2374                                                | 55.35                         | 53.69                   | 74                | -18.65         | 31.78                       | 5.37                  | 35.49                    | 103                       | 267                        | Peak    |
| 2402                                                | 92.99                         | 91.26                   |                   |                | 31.8                        | 5.4                   | 35.47                    | 103                       | 267                        | Average |
| 2402                                                | 93.46                         | 91.73                   |                   |                | 31.8                        | 5.4                   | 35.47                    | 103                       | 267                        | Peak    |
| 2498                                                | 42.62                         | 40.6                    | 54                | -11.38         | 31.9                        | 5.53                  | 35.41                    | 103                       | 267                        | Average |
| 2498                                                | 55.23                         | 53.21                   | 74                | -18.77         | 31.9                        | 5.53                  | 35.41                    | 103                       | 267                        | Peak    |

#### REMARKS:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor  
Margin value = Emission level – Limit value
- 2402MHz: Fundamental frequency.



| EUT TEST CONDITION       |                 | MEASUREMENT DETAIL |                           |
|--------------------------|-----------------|--------------------|---------------------------|
| CHANNEL                  | Channel 39      | FREQUENCY RANGE    | 1GHz ~ 25GHz              |
| INPUT POWER              | 120Vac, 60 Hz   | DETECTOR FUNCTION  | Peak (PK)<br>Average (AV) |
| ENVIRONMENTAL CONDITIONS | 25deg. C, 65%RH | TESTED BY          | Karl Lee                  |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                               |                         |                   |                |                             |                       |                          |                           |                            |         |
|-----------------------------------------------------|-------------------------------|-------------------------|-------------------|----------------|-----------------------------|-----------------------|--------------------------|---------------------------|----------------------------|---------|
| FREQ.<br>(MHz)                                      | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB/m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK  |
| 2350                                                | 41.94                         | 40.37                   | 54                | -12.06         | 31.74                       | 5.33                  | 35.5                     | 100                       | 64                         | Average |
| 2350                                                | 55.82                         | 54.25                   | 74                | -18.18         | 31.74                       | 5.33                  | 35.5                     | 100                       | 64                         | Peak    |
| 2441                                                | 94.75                         | 92.88                   |                   |                | 31.85                       | 5.46                  | 35.44                    | 100                       | 64                         | Average |
| 2441                                                | 95.49                         | 93.62                   |                   |                | 31.85                       | 5.46                  | 35.44                    | 100                       | 64                         | Peak    |
| 2492                                                | 42.93                         | 40.91                   | 54                | -11.07         | 31.9                        | 5.53                  | 35.41                    | 100                       | 64                         | Average |
| 2492                                                | 55.94                         | 53.92                   | 74                | -18.06         | 31.9                        | 5.53                  | 35.41                    | 100                       | 64                         | Peak    |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                               |                         |                   |                |                             |                       |                          |                           |                            |         |
| FREQ.<br>(MHz)                                      | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB/m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK  |
| 2384                                                | 42.12                         | 40.43                   | 54                | -11.88         | 31.78                       | 5.4                   | 35.49                    | 103                       | 267                        | Average |
| 2384                                                | 55.72                         | 54.03                   | 74                | -18.28         | 31.78                       | 5.4                   | 35.49                    | 103                       | 267                        | Peak    |
| 2441                                                | 92.85                         | 90.98                   |                   |                | 31.85                       | 5.46                  | 35.44                    | 103                       | 267                        | Average |
| 2441                                                | 93.91                         | 92.04                   |                   |                | 31.85                       | 5.46                  | 35.44                    | 103                       | 267                        | Peak    |
| 2494                                                | 42.58                         | 40.56                   | 54                | -11.42         | 31.9                        | 5.53                  | 35.41                    | 103                       | 267                        | Average |
| 2494                                                | 55.72                         | 53.7                    | 74                | -18.28         | 31.9                        | 5.53                  | 35.41                    | 103                       | 267                        | Peak    |

**REMARKS:**

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor  
Margin value = Emission level – Limit value
- 2441MHz: Fundamental frequency.

| EUT TEST CONDITION       |                 | MEASUREMENT DETAIL |                           |
|--------------------------|-----------------|--------------------|---------------------------|
| CHANNEL                  | Channel 78      | FREQUENCY RANGE    | 1GHz ~ 25GHz              |
| INPUT POWER              | 120Vac, 60 Hz   | DETECTOR FUNCTION  | Peak (PK)<br>Average (AV) |
| ENVIRONMENTAL CONDITIONS | 25deg. C, 65%RH | TESTED BY          | Karl Lee                  |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                               |                         |                   |                |                             |                       |                          |                           |                            |         |
|-----------------------------------------------------|-------------------------------|-------------------------|-------------------|----------------|-----------------------------|-----------------------|--------------------------|---------------------------|----------------------------|---------|
| FREQ.<br>(MHz)                                      | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB/m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK  |
| 2384                                                | 42.42                         | 40.73                   | 54                | -11.58         | 31.78                       | 5.4                   | 35.49                    | 102                       | 126                        | Average |
| 2384                                                | 56.12                         | 54.43                   | 74                | -17.88         | 31.78                       | 5.4                   | 35.49                    | 102                       | 126                        | Peak    |
| 2480                                                | 94.53                         | 92.57                   |                   |                | 31.88                       | 5.5                   | 35.42                    | 102                       | 126                        | Average |
| 2480                                                | 95.77                         | 93.81                   |                   |                | 31.88                       | 5.5                   | 35.42                    | 102                       | 126                        | Peak    |
| 2498                                                | 42.83                         | 40.81                   | 54                | -11.17         | 31.9                        | 5.53                  | 35.41                    | 102                       | 126                        | Average |
| 2498                                                | 56.86                         | 54.84                   | 74                | -17.14         | 31.9                        | 5.53                  | 35.41                    | 102                       | 126                        | Peak    |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                               |                         |                   |                |                             |                       |                          |                           |                            |         |
| FREQ.<br>(MHz)                                      | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB/m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK  |
| 2390                                                | 42.26                         | 40.53                   | 54                | -11.74         | 31.8                        | 5.4                   | 35.47                    | 100                       | 267                        | Average |
| 2390                                                | 56.03                         | 54.3                    | 74                | -17.97         | 31.8                        | 5.4                   | 35.47                    | 100                       | 267                        | Peak    |
| 2480                                                | 92.72                         | 90.76                   |                   |                | 31.88                       | 5.5                   | 35.42                    | 100                       | 267                        | Average |
| 2480                                                | 93.86                         | 91.9                    |                   |                | 31.88                       | 5.5                   | 35.42                    | 100                       | 267                        | Peak    |
| 2484                                                | 43.11                         | 41.15                   | 54                | -10.89         | 31.88                       | 5.5                   | 35.42                    | 100                       | 267                        | Average |
| 2484                                                | 56.33                         | 54.37                   | 74                | -17.67         | 31.88                       | 5.5                   | 35.42                    | 100                       | 267                        | Peak    |

#### REMARKS:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor  
Margin value = Emission level – Limit value
- 2480MHz: Fundamental frequency.

### Mode B

| EUT TEST CONDITION       |                 | MEASUREMENT DETAIL |                           |
|--------------------------|-----------------|--------------------|---------------------------|
| CHANNEL                  | Channel 78      | FREQUENCY RANGE    | 1GHz ~ 25GHz              |
| INPUT POWER              | 120Vac, 60 Hz   | DETECTOR FUNCTION  | Peak (PK)<br>Average (AV) |
| ENVIRONMENTAL CONDITIONS | 25deg. C, 65%RH | TESTED BY          | Karl Lee                  |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                               |                         |                   |                |                             |                       |                          |                           |                            |         |
|-----------------------------------------------------|-------------------------------|-------------------------|-------------------|----------------|-----------------------------|-----------------------|--------------------------|---------------------------|----------------------------|---------|
| FREQ.<br>(MHz)                                      | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB/m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK  |
| 2352                                                | 39.1                          | 37.51                   | 54                | -14.9          | 31.76                       | 5.33                  | 35.5                     | 101                       | 127                        | Average |
| 2352                                                | 54.54                         | 52.95                   | 74                | -19.46         | 31.76                       | 5.33                  | 35.5                     | 101                       | 127                        | Peak    |
| 2480                                                | 94.98                         | 93.02                   |                   |                | 31.88                       | 5.5                   | 35.42                    | 101                       | 127                        | Average |
| 2480                                                | 95.65                         | 93.69                   |                   |                | 31.88                       | 5.5                   | 35.42                    | 101                       | 127                        | Peak    |
| 2494                                                | 40.13                         | 38.11                   | 54                | -13.87         | 31.9                        | 5.53                  | 35.41                    | 101                       | 127                        | Average |
| 2494                                                | 55.17                         | 53.15                   | 74                | -18.83         | 31.9                        | 5.53                  | 35.41                    | 101                       | 127                        | Peak    |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                               |                         |                   |                |                             |                       |                          |                           |                            |         |
| FREQ.<br>(MHz)                                      | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB/m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK  |
| 2356                                                | 39.13                         | 37.5                    | 54                | -14.87         | 31.76                       | 5.37                  | 35.5                     | 102                       | 31                         | Average |
| 2356                                                | 54.6                          | 52.97                   | 74                | -19.4          | 31.76                       | 5.37                  | 35.5                     | 102                       | 31                         | Peak    |
| 2480                                                | 92.02                         | 90.06                   |                   |                | 31.88                       | 5.5                   | 35.42                    | 102                       | 31                         | Average |
| 2480                                                | 93.06                         | 91.1                    |                   |                | 31.88                       | 5.5                   | 35.42                    | 102                       | 31                         | Peak    |
| 2486                                                | 40.11                         | 38.12                   | 54                | -13.89         | 31.88                       | 5.53                  | 35.42                    | 102                       | 31                         | Average |
| 2486                                                | 55.54                         | 53.55                   | 74                | -18.46         | 31.88                       | 5.53                  | 35.42                    | 102                       | 31                         | Peak    |

### REMARKS:

- Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor  
Margin value = Emission level – Limit value
- 2480MHz: Fundamental frequency.

# BELOW 1GHz WORST-CASE DATA:

## Mode A

| EUT TEST CONDITION       |                 | MEASUREMENT DETAIL |                              |
|--------------------------|-----------------|--------------------|------------------------------|
| CHANNEL                  | Channel 78      | FREQUENCY RANGE    | 30MHz ~ 1GHz                 |
| INPUT POWER              | 120Vac, 60 Hz   | DETECTOR FUNCTION  | Peak (PK)<br>Quasi-peak (QP) |
| ENVIRONMENTAL CONDITIONS | 25deg. C, 65%RH | TESTED BY          | Karl Lee                     |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                               |                         |                   |                |                             |                       |                          |                           |                            |             |
|-----------------------------------------------------|-------------------------------|-------------------------|-------------------|----------------|-----------------------------|-----------------------|--------------------------|---------------------------|----------------------------|-------------|
| FREQ.<br>(MHz)                                      | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB/m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK      |
| 163.65                                              | 28.78                         | 49.01                   | 43.5              | -14.72         | 10.51                       | 1.52                  | 32.26                    | 146                       | 321                        | Peak        |
| 206.31                                              | 35.65                         | 55.1                    | 43.5              | -7.85          | 11.17                       | 1.65                  | 32.27                    | 100                       | 240                        | QP          |
| 271.38                                              | 28.14                         | 44.69                   | 46                | -17.86         | 13.62                       | 1.94                  | 32.11                    | 127                       | 38                         | Peak        |
| 531.7                                               | 39.37                         | 48.26                   | 46                | -6.63          | 20.57                       | 2.7                   | 32.16                    | 153                       | 114                        | Peak        |
| 711.6                                               | 34.28                         | 40.04                   | 46                | -11.72         | 23.23                       | 3.11                  | 32.1                     | 177                       | 177                        | Peak        |
| 879.6                                               | 32.17                         | 35.45                   | 46                | -13.83         | 24.84                       | 3.49                  | 31.61                    | 131                       | 165                        | Peak        |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                               |                         |                   |                |                             |                       |                          |                           |                            |             |
| FREQ.<br>(MHz)                                      | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB/m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK      |
| 37.02                                               | 34.65                         | 53.12                   | 40                | -5.35          | 13.02                       | 0.74                  | 32.23                    | 102                       | 137                        | Peak        |
| 146.1                                               | 32.41                         | 53.51                   | 43.5              | -11.09         | 9.79                        | 1.38                  | 32.27                    | 146                       | 1                          | Peak        |
| 208.74                                              | 37.15                         | 56.5                    | 43.5              | -6.35          | 11.26                       | 1.65                  | 32.26                    | 100                       | 209                        | QP          |
| <b>533.1</b>                                        | <b>42.84</b>                  | <b>51.74</b>            | <b>46</b>         | <b>-3.16</b>   | <b>20.57</b>                | <b>2.7</b>            | <b>32.17</b>             | <b>154</b>                | <b>215</b>                 | <b>Peak</b> |
| 710.9                                               | 35.63                         | 41.39                   | 46                | -10.37         | 23.23                       | 3.11                  | 32.1                     | 147                       | 142                        | Peak        |
| 883.1                                               | 35.09                         | 38.31                   | 46                | -10.91         | 24.88                       | 3.49                  | 31.59                    | 111                       | 125                        | Peak        |

**REMARKS:** Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor

Margin value = Emission level – Limit value

**Mode B**

| EUT TEST CONDITION       |                 | MEASUREMENT DETAIL |              |
|--------------------------|-----------------|--------------------|--------------|
| CHANNEL                  | Channel 78      | FREQUENCY RANGE    | 30MHz ~ 1GHz |
| INPUT POWER              | 120Vac, 60 Hz   | DETECTOR FUNCTION  | Peak (PK)    |
| ENVIRONMENTAL CONDITIONS | 25deg. C, 65%RH | TESTED BY          | Karl Lee     |

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

| FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB/m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK |
|----------------|-------------------------------|-------------------------|-------------------|----------------|-----------------------------|-----------------------|--------------------------|---------------------------|----------------------------|--------|
| 126.66         | 27.57                         | 49.4                    | 43.5              | -15.93         | 9.03                        | 1.38                  | 32.24                    | 166                       | 275                        | Peak   |
| 189.3          | 35.22                         | 55.46                   | 43.5              | -8.28          | 10.4                        | 1.61                  | 32.25                    | 189                       | 33                         | Peak   |
| 265.17         | 36.4                          | 53.12                   | 46                | -9.6           | 13.45                       | 1.94                  | 32.11                    | 194                       | 221                        | Peak   |
| 533.1          | 39.37                         | 48.27                   | 46                | -6.63          | 20.57                       | 2.7                   | 32.17                    | 120                       | 268                        | Peak   |
| 760.6          | 36.09                         | 41.7                    | 46                | -9.91          | 23.3                        | 3.22                  | 32.13                    | 130                       | 141                        | Peak   |
| 798.4          | 38.9                          | 43.22                   | 46                | -7.1           | 24.42                       | 3.32                  | 32.06                    | 198                       | 84                         | Peak   |

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

| FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | READ<br>LEVEL<br>(dBuV) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>FACTOR<br>(dB/m) | CABLE<br>LOSS<br>(dB) | PREAMP<br>FACTOR<br>(dB) | ANTENNA<br>HEIGHT<br>(cm) | TABLE<br>ANGLE<br>(Degree) | REMARK |
|----------------|-------------------------------|-------------------------|-------------------|----------------|-----------------------------|-----------------------|--------------------------|---------------------------|----------------------------|--------|
| 125.04         | 31.43                         | 53.32                   | 43.5              | -12.07         | 8.97                        | 1.38                  | 32.24                    | 125                       | 4                          | Peak   |
| 193.35         | 34.13                         | 54.22                   | 43.5              | -9.37          | 10.57                       | 1.61                  | 32.27                    | 126                       | 85                         | Peak   |
| 266.25         | 33.1                          | 49.78                   | 46                | -12.9          | 13.49                       | 1.94                  | 32.11                    | 176                       | 250                        | Peak   |
| 531.7          | 38.66                         | 47.55                   | 46                | -7.34          | 20.57                       | 2.7                   | 32.16                    | 153                       | 17                         | Peak   |
| 700.4          | 34.15                         | 40.03                   | 46                | -11.85         | 23.1                        | 3.11                  | 32.09                    | 131                       | 14                         | Peak   |
| 797.7          | 37.09                         | 41.41                   | 46                | -8.91          | 24.42                       | 3.32                  | 32.06                    | 179                       | 77                         | Peak   |

**REMARKS:** Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor

Margin value = Emission level – Limit value

## 4.2 Conducted Emission Measurement

### 4.2.1 Limits of Conducted Emission Measurement

| Frequency (MHz) | Conducted Limit (dBuV) |         |
|-----------------|------------------------|---------|
|                 | Quasi-peak             | Average |
| 0.15 - 0.5      | 66 - 56                | 56 - 46 |
| 0.50 - 5.0      | 56                     | 46      |
| 5.0 - 30.0      | 60                     | 50      |

Note: 1. The lower limit shall apply at the transition frequencies.  
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.  
 3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

### 4.2.2 Test Instruments

| Description & Manufacturer              | Model No.                | Serial No.     | Date Of Calibration | Due Date Of Calibration |
|-----------------------------------------|--------------------------|----------------|---------------------|-------------------------|
| Test Receiver<br>ROHDE & SCHWARZ        | ESCI                     | 100613         | Nov. 11, 2014       | Nov. 10, 2015           |
| RF signal cable<br>Woken                | 5D-FB                    | Cable-HYC01-01 | Dec. 26, 2014       | Dec. 25, 2015           |
| LISN<br>ROHDE & SCHWARZ<br>(EUT)        | ESH3-Z5                  | 835239/001     | Mar. 02, 2015       | Mar. 01, 2016           |
| LISN<br>ROHDE & SCHWARZ<br>(Peripheral) | ESH3-Z5                  | 100311         | Jul. 24, 2015       | Jul. 23, 2016           |
| Software<br>ADT                         | BV ADT_Cond_<br>V7.3.7.3 | NA             | NA                  | NA                      |

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.  
 2. The test was performed in HwaYa Shielded Room 1.  
 3. The VCCI Site Registration No. is C-2040.

#### 4.2.3 Test Procedures


- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

**NOTE:** All modes of operation were investigated and the worst-case emissions are reported.

#### 4.2.4 Deviation From Test Standard

No deviation.

#### 4.2.5 Test Setup



**Note: 1.**Support units were connected to second LISN.

**2.**Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.2.6 EUT Operating Condition

Same as 4.1.6.

## 4.2.7 Test Results

### Mode A


#### CONDUCTED WORST-CASE DATA : GFSK

|       |        |               |      |
|-------|--------|---------------|------|
| PHASE | Line 1 | 6dB BANDWIDTH | 9kHz |
|-------|--------|---------------|------|

| No | Frequency (MHz) | Correction Factor (dB) | Reading Value (dBuV) |       | Emission Level (dBuV) |       | Limit (dBuV) |       | Margin (dB) |        |
|----|-----------------|------------------------|----------------------|-------|-----------------------|-------|--------------|-------|-------------|--------|
|    |                 |                        | Q.P.                 | AV.   | Q.P.                  | AV.   | Q.P.         | AV.   | Q.P.        | AV.    |
| 1  | 0.16922         | 0.05                   | 38.42                | 14.31 | 38.47                 | 14.36 | 65.00        | 55.00 | -26.52      | -40.63 |
| 2  | 0.18519         | 0.06                   | 46.71                | 30.30 | 46.77                 | 30.36 | 64.25        | 54.25 | -17.48      | -23.89 |
| 3  | 0.26339         | 0.06                   | 37.98                | 21.29 | 38.04                 | 21.35 | 61.32        | 51.32 | -23.28      | -29.97 |
| 4  | 0.32204         | 0.06                   | 33.26                | 16.10 | 33.32                 | 16.16 | 59.65        | 49.65 | -26.33      | -33.49 |
| 5  | 2.36306         | 0.13                   | 26.49                | 15.25 | 26.62                 | 15.38 | 56.00        | 46.00 | -29.38      | -30.62 |
| 6  | 4.24377         | 0.20                   | 30.28                | 19.70 | 30.48                 | 19.90 | 56.00        | 46.00 | -25.52      | -26.10 |

#### REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




|       |        |               |      |
|-------|--------|---------------|------|
| PHASE | Line 2 | 6dB BANDWIDTH | 9kHz |
|-------|--------|---------------|------|

| No | Frequency (MHz) | Correction Factor (dB) | Reading Value (dBuV) |       | Emission Level (dBuV) |       | Limit (dBuV) |       | Margin (dB) |        |
|----|-----------------|------------------------|----------------------|-------|-----------------------|-------|--------------|-------|-------------|--------|
|    |                 |                        | Q.P.                 | AV.   | Q.P.                  | AV.   | Q.P.         | AV.   | Q.P.        | AV.    |
| 1  | 0.15000         | 0.05                   | 42.63                | 24.39 | 42.68                 | 24.44 | 66.00        | 56.00 | -23.32      | -31.56 |
| 2  | 0.19255         | 0.05                   | 46.19                | 31.26 | 46.24                 | 31.31 | 63.93        | 53.93 | -17.69      | -22.62 |
| 3  | 0.25125         | 0.05                   | 39.84                | 24.22 | 39.89                 | 24.27 | 61.72        | 51.72 | -21.82      | -27.44 |
| 4  | 0.30615         | 0.06                   | 36.13                | 19.70 | 36.19                 | 19.76 | 60.07        | 50.07 | -23.89      | -30.32 |
| 5  | 0.45107         | 0.06                   | 30.51                | 15.70 | 30.57                 | 15.76 | 56.86        | 46.86 | -26.28      | -31.09 |
| 6  | 0.75214         | 0.07                   | 29.49                | 14.88 | 29.56                 | 14.95 | 56.00        | 46.00 | -26.44      | -31.05 |

#### REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.



## Mode B


### CONDUCTED WORST-CASE DATA : GFSK

|       |        |               |      |
|-------|--------|---------------|------|
| PHASE | Line 1 | 6dB BANDWIDTH | 9kHz |
|-------|--------|---------------|------|

| No | Frequency (MHz) | Correction Factor (dB) | Reading Value (dBuV) |       | Emission Level (dBuV) |       | Limit (dBuV) |       | Margin (dB) |        |
|----|-----------------|------------------------|----------------------|-------|-----------------------|-------|--------------|-------|-------------|--------|
|    |                 |                        | Q.P.                 | AV.   | Q.P.                  | AV.   | Q.P.         | AV.   | Q.P.        | AV.    |
| 1  | 0.15000         | 0.05                   | 49.18                | 34.66 | 49.23                 | 34.71 | 66.00        | 56.00 | -16.77      | -21.29 |
| 2  | 0.18508         | 0.06                   | 39.54                | 20.22 | 39.60                 | 20.28 | 64.25        | 54.25 | -24.66      | -33.98 |
| 3  | 0.22791         | 0.06                   | 34.94                | 20.88 | 35.00                 | 20.94 | 62.53        | 52.53 | -27.53      | -31.59 |
| 4  | 0.28685         | 0.06                   | 28.55                | 14.46 | 28.61                 | 14.52 | 60.62        | 50.62 | -32.01      | -36.10 |
| 5  | 0.46301         | 0.06                   | 25.73                | 16.56 | 25.79                 | 16.62 | 56.64        | 46.64 | -30.85      | -30.02 |
| 6  | 4.06000         | 0.19                   | 21.22                | 12.43 | 21.41                 | 12.62 | 56.00        | 46.00 | -34.59      | -33.38 |

#### REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




|       |        |               |      |
|-------|--------|---------------|------|
| PHASE | Line 2 | 6dB BANDWIDTH | 9kHz |
|-------|--------|---------------|------|

| No | Frequency (MHz) | Correction Factor (dB) | Reading Value (dBuV) |       | Emission Level (dBuV) |       | Limit (dBuV) |       | Margin (dB) |        |
|----|-----------------|------------------------|----------------------|-------|-----------------------|-------|--------------|-------|-------------|--------|
|    |                 |                        | Q.P.                 | AV.   | Q.P.                  | AV.   | Q.P.         | AV.   | Q.P.        | AV.    |
| 1  | 0.15391         | 0.05                   | 49.06                | 33.83 | 49.11                 | 33.88 | 65.79        | 55.79 | -16.68      | -21.91 |
| 2  | 0.16967         | 0.05                   | 46.63                | 30.71 | 46.68                 | 30.76 | 64.98        | 54.98 | -18.30      | -24.22 |
| 3  | 0.19692         | 0.05                   | 38.33                | 19.08 | 38.38                 | 19.13 | 63.74        | 53.74 | -25.36      | -34.61 |
| 4  | 0.23993         | 0.05                   | 32.57                | 16.53 | 32.62                 | 16.58 | 62.10        | 52.10 | -29.48      | -35.52 |
| 5  | 0.36896         | 0.06                   | 27.92                | 17.66 | 27.98                 | 17.72 | 58.52        | 48.52 | -30.55      | -30.81 |
| 6  | 0.50581         | 0.06                   | 28.42                | 20.26 | 28.48                 | 20.32 | 56.00        | 46.00 | -27.52      | -25.68 |

#### REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




### 4.3 Maximum Output Power

#### 4.3.1 Limits of Maximum Output Power Measurement

The Maximum Output Power Measurement is 125mW.

#### 4.3.2 Test Setup



#### 4.3.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

#### 4.3.4 Test Procedure

- Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- The center frequency of the spectrum analyzer is set to the fundamental frequency and using 3MHz RBW and 10 MHz VBW.
- Measure the captured power within the band and recording the plot.
- Repeat above procedures until all frequencies required were complete.

#### 4.3.5 Deviation from Test Standard

No deviation.


#### 4.3.6 EUT Operating Condition

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

### 4.3.7 Test Results


#### Mode A

| Channel | Frequency (MHz) | Output Power (mW) |                |       | Output Power (dBm) |                |       | Power Limit (mW) | Pass / Fail |
|---------|-----------------|-------------------|----------------|-------|--------------------|----------------|-------|------------------|-------------|
|         |                 | GFSK              | $\pi/4$ -DQPSK | 8DPSK | GFSK               | $\pi/4$ -DQPSK | 8DPSK |                  |             |
| 0       | 2402            | 1.315             | 1.117          | 1.119 | 1.19               | 0.48           | 0.49  | 125              | PASS        |
| 39      | 2441            | 1.291             | 1.169          | 1.172 | 1.11               | 0.68           | 0.69  | 125              | PASS        |
| 78      | 2480            | 1.199             | 1.104          | 1.102 | 0.79               | 0.43           | 0.42  | 125              | PASS        |



## Mode B

| Channel | Frequency (MHz) | Output Power (mW) |                |       | Output Power (dBm) |                |       | Power Limit (mW) | Pass / Fail |
|---------|-----------------|-------------------|----------------|-------|--------------------|----------------|-------|------------------|-------------|
|         |                 | GFSK              | $\pi/4$ -DQPSK | 8DPSK | GFSK               | $\pi/4$ -DQPSK | 8DPSK |                  |             |
| 0       | 2402            | 1.309             | 1.117          | 1.117 | 1.17               | 0.48           | 0.48  | 125              | PASS        |
| 39      | 2441            | 1.291             | 1.169          | 1.178 | 1.11               | 0.68           | 0.71  | 125              | PASS        |
| 78      | 2480            | 1.197             | 1.099          | 1.107 | 0.78               | 0.41           | 0.44  | 125              | PASS        |



## 5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

## Appendix – Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

**Linko EMC/RF Lab**

Tel: 886-2-26052180

Fax: 886-2-26051924

**Hsin Chu EMC/RF Lab/Telecom Lab**

Tel: 886-3-5935343

Fax: 886-3-5935342

**Hwa Ya EMC/RF/Safety**

Tel: 886-3-3183232

Fax: 886-3-3270892

**Email:** [service.adt@tw.bureauveritas.com](mailto:service.adt@tw.bureauveritas.com)

**Web Site:** [www.bureauveritas-adt.com](http://www.bureauveritas-adt.com)

The address and road map of all our labs can be found in our web site also.

--- END ---