

Test Engineer:	Derek Hsu	Temperature:	21~25	°C
Test Date:	2015/9/10~2015/09/16	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB Bandwidth

Band IV							
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	6 dB Bandwidth (MHz)	FCC 6dB Bandwidth Limit (MHz)	Pass/Fail
11a	6M bps	1	149	5745	15.32	0.5	Pass
11a	6Mbps	1	157	5785	15.44	0.5	Pass
11a	6Mbps	1	165	5825	15.44	0.5	Pass
HT20	MCS 0	1	149	5745	15.68	0.5	Pass
HT20	MCS 0	1	157	5785	15.56	0.5	Pass
HT20	MCS 0	1	165	5825	15.52	0.5	Pass

TEST RESULTS DATA
Average Power Table

Band IV										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)	FCC Conducted Power Limit (dBm)	DG (dBi)		Pass/Fail
11a	6M bps	1	149	5745	0.09	9.69	30.00	2.00		Pass
11a	6Mbps	1	157	5785	0.09	9.39	30.00	2.00		Pass
11a	6Mbps	1	165	5825	0.09	9.19	30.00	2.00		Pass
HT20	MCS 0	1	149	5745	0.10	9.60	30.00	2.00		Pass
HT20	MCS 0	1	157	5785	0.10	9.30	30.00	2.00		Pass
HT20	MCS 0	1	165	5825	0.10	8.48	30.00	2.00		Pass

TEST RESULTS DATA
Power Spectral Density

Band IV										
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Duty Factor (dB)	10log (500kHz /RBW) Factor (dB)	Average Power Density (dBm/500kHz)	Average PSD Limit (dBm/500kHz)	DG (dBi)	Pass/Fail
11a	6M bps	1	149	5745	0.09	2.22	-4.74	30.00	2.00	Pass
11a	6Mbps	1	157	5785	0.09	2.22	-4.56	30.00	2.00	Pass
11a	6Mbps	1	165	5825	0.09	2.22	-5.42	30.00	2.00	Pass
HT20	MCS 0	1	149	5745	0.10	2.22	-4.77	30.00	2.00	Pass
HT20	MCS 0	1	157	5785	0.10	2.22	-4.87	30.00	2.00	Pass
HT20	MCS 0	1	165	5825	0.10	2.22	-6.31	30.00	2.00	Pass

TEST RESULTS DATA
Frequency Stability

Band IV										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Center Frequency (MHz)	Frequency Deviation (MHz)	Frequency Stability (ppm)	Temperature (°C)	Voltage (V)	Note
11a	6M bps	1	149	5745	5745.000	0.000	0.00	20	3.2	
11a	6M bps	1	149	5745	5745.000	0.000	0.00	20	4.2	
11a	6M bps	1	149	5745	5745.000	0.000	0.00	20	3.7	
11a	6M bps	1	149	5745	5745.000	0.000	0.00	-20	3.7	
11a	6M bps	1	149	5745	5745.000	0.000	0.00	55	3.7	