

TEST REPORT

FOR ZIGBEE TESTING

Report No.: SRTC2019-9004(F)-19070806(E-2)

Product Name: DALI module without power supply

Product Model: 201-50X.NPS

Applicant: Honeywell International Inc.

Manufacturer: Honeywell International Inc.

Specification: FCC Part 15, Subpart C (2019)

FCC ID: GTC-20150XNPS

The State Radio_monitoring_center Testing Center (SRTC)

15th Building, No.30 Shixing Street, Shijingshan District,

Beijing, P.R.China

Tel: 86-10-57996183 Fax: 86-10-57996388

CONTENTS

1. GENERAL INFORMATION	2
1.1 NOTES OF THE TEST REPORT	2
1.2 INFORMATION ABOUT THE TESTING LABORATORY	2
1.3 APPLICANT'S DETAILS	2
1.4 MANUFACTURER'S DETAILS	2
1.5 TEST ENVIRONMENT	2
2 DESCRIPTION OF THE DEVICE UNDER TEST	4
2.1 FINAL EQUIPMENT BUILD STATUS	4
2.2 DESCRIPTION OF TEST MODES	5
2.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL	5
2.3 DUTY CYCLE OF TEST SIGNAL	6
2.4 EUT OPERATING CONDITIONS	7
2.5 SUPPORT EQUIPMENT	7
3 REFERENCE SPECIFICATION	8
4 KEY TO NOTES AND RESULT CODES	8
5 RESULT SUMMARY	9
6 TEST RESULT	10
6.1 OCCUPIED BANDWIDTH	10
6.2 PEAK POWER OUTPUT	11
6.3 TRANSMITTER POWER SPECTRAL DENSITY	12
6.4 CONDUCTED OUT OF BAND EMISSION MEASUREMENT	13
6.5 BAND-EDGE MEASUREMENT	14
6.6 SPURIOUS RADIATED EMISSIONS	16
6.7 AC POWER LINE CONDUCTED EMISSION	21
7 MEASUREMENT UNCERTAINTIES	23
8 TEST EQUIPMENTS	24
APPENDIX A – TEST DATA OF CONDUCTED EMISSION	24
APPENDIX B – TEST DATA OF RADIATED EMISSION	24

1. GENERAL INFORMATION

1.1 Notes of the test report

The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written permission of The State Radio_monitoring_center Testing Center (SRTC).

The test results relate only to individual items of the samples which have been tested.

The certification and accreditation identifiers used in this report shall not be applicable to the tested or calibrated samples thereof. The manufacturer shall not mark the tested samples or items (or a separate part of the item) with the identifiers of certification and accreditation to mislead relevant parties about the tested samples or items.

1.2 Information about the testing laboratory

Company:	The State Radio_monitoring_center Testing Center (SRTC)
Address:	15th Building, No.30 Shixing Street, Shijingshan District, P.R.China
City:	Beijing
Country or Region:	P.R.China
Contacted person:	Liu Jia
Tel:	+86 10 57996183
Fax:	+86 10 57996388
Email:	liujiaf@srtc.org.cn

1.3 Applicant's details

Company:	Honeywell International Inc.
Address:	12 Clintonville Road, Northford, CT 06472, United States
City:	Northford
Country or Region:	United States
Contacted person:	Hardik Upadhyay
Tel:	+1 2034846127
Fax:	---
Email:	mailto:Hardik.Upadhyay@Honeywell.com

1.4 Manufacturer's details

Company:	Honeywell International Inc.
Address:	12 Clintonville Road, Northford, CT 06472, United States
City:	Northford
Country or Region:	United States
Contacted person:	Hardik Upadhyay
Tel:	+1 2034846127
Fax:	---
Email:	mailto:Hardik.Upadhyay@Honeywell.com

1.5 Test Environment

Date of Receipt of test sample at SRTC:	2019-07-08
Testing Start Date:	2019-07-19
Testing End Date:	2019-09-12

Environmental Data:	Temperature (°C)	Humidity (%)
Ambient	25	40

Normal Supply Voltage (V d.c.):	12.0
---------------------------------	------

2 DESCRIPTION OF THE DEVICE UNDER TEST

2.1 Final Equipment Build Status

Frequency Range	2.405GHz~2.480GHz
Number of Channel	16
Modulation Type	QPSK
Equipment Class	DTS
Channel Spacing	5MHz
Power Supply	DC Adapter
HW Version	Rev 05
SW Version	Compliance Testing Code V1.0
IMEI	Sample #1
Antenna type	Refer to Note
Antenna connector	Refer to Note

Note:

The antenna provide to the EUT, please refer to the following table:

Brand	Model	Antenna gain	Frequency range(GHz)	Antenna type	Connector Type
N/A	N/A	1.3dBi	2.405GHz~2.480GHz	Integral Antenna	N/A
Manufacturers ensure that their designs will not be modified by the user or third parties arbitrary antenna parameters and performance.					

2.2 Description of Test Modes

16 channels are provided to this EUT:

CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)
11	2405	15	2425	19	2445	23	2465
12	2410	16	2430	20	2450	24	2470
13	2415	17	2435	21	2455	25	2475
14	2420	18	2440	22	2460	26	2480

2.2.1 Test Mode Applicability and Tested Channel Detail

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE $\geq$ 1G	RE<1G	PLC	APCM	-
QPSK	√	√	√	√	-

Where RE $\geq$ 1G: Radiated Emission above 1GHz
RE<1G: Radiated Emission below 1GHz

PLC: Power Line Conducted Emission

APCM: Antenna Port Conducted Measurement

Radiated Emission Test (Above 1GHz):

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE
11 to 26	19	QPSK

Radiated Emission Test (Below 1GHz):

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE
11 to 26	19	QPSK

Power Line Conducted Emission Test:

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE
11 to 26	19	QPSK

Antenna Port Conducted Measurement:

This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE
11 to 26	19	QPSK

2.3 Duty Cycle of Test Signal

Duty cycle of test signal is > 98 %, duty factor shall not be considered.

Duty cycle = 100%

2.4 EUT Operating conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

2.5 Support Equipment

The following support equipment was used to exercise the DUT during testing:

NA.

3 REFERENCE SPECIFICATION


Specification	Version	Title
15.35	2019	Measurement detector functions and bandwidths.
15.209	2019	Radiated emission limits; general requirements.
15.247	2019	Operation within the bands 902-928 MHz, 2400-2483.5 MHz, and 5725-5850MHz.
15.203	2019	Antenna requirement
ANSI C63.10	2013	Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
KDB 558074D01 V05r02	April 2, 2019	GUIDANCE FOR PERFORMING COMPLIANCE MEASUREMENTS ON DIGITAL TRANSMISSION SYSTEMS (DTS) OPERATING UNDER SECTION 15.247

4 KEY TO NOTES AND RESULT CODES

Code	Meaning
PASS	Test result shows that the requirements of the relevant specification have been met.
FAIL	Test result shows that the requirements of the relevant specification have not been met.
N/T	Test case is not tested.
NTC	Nominal voltage, Normal Temperature
HV	High voltage, Normal Temperature
LV	Low voltage, Normal Temperature
HTHV	high voltage, High Temperature
LTHV	High voltage, Low Temperature
HTLV	Low voltage, High Temperature
LTLV	Low voltage, Low Temperature

5 RESULT SUMMARY

No.	Test case	Reference	Verdict
1	Occupied Bandwidth	15.247(a)(2)	Pass
2	Peak Power Output	15.247(b)(3))	Pass
3	Transmitter Power Spectral Density	15.247(e))	Pass
4	Conducted Out of band emission measurement	15.247(d)	Pass
5	Band-edge	15.247(d)	Pass
6	Spurious Radiated Emissions	15.247(d)/15.35(b)/15.209	Pass
7	AC Power line Conducted Emission	15.207	Pass
8	Antenna requirement	15.203	Pass (refer to section 2.1)

This Test Report Is Issued by: Mr. Peng Zhen 	Checked by: Mr. Li Bin 
Tested by: Mr. Tong Daocheng 	Issued date: 20190912

6 TEST RESULT

6.1 Occupied Bandwidth

6.1.1 Ambient condition

Temperature	Relative humidity	Pressure
22°C	40%	101.5kPa

6.1.2 Test Description

The bandwidth at 6dB down from the highest in-band spectral density is measured with a spectrum analyzer and Bluetooth test set via a power splitter with a known loss. Which connected to the transmitter antenna terminal of the EUT while the EUT is operating at maximum power and at the appropriate frequencies. All modes of operation were investigated and the worst case configuration results are reported in this section.

6.1.3 Test limit

Part15.247 (a)(2)

The minimum permissible 6dB bandwidth is 500 kHz

6.1.4 Test Procedure Used


KDB 558074 D01 DTS Meas Guidance v05r02 – Section 8.2.

6.1.5 Test Settings

- Set RBW = 100 kHz.
- Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Allow the trace to stabilize.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

6.1.6 Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



6.1.7 Test result

The test results are shown in Appendix A .

6.2 Peak Power Output

6.2.1 Ambient condition

Temperature	Relative humidity	Pressure
22°C	40%	101.5kPa

6.2.2 Test Description

The transmitter antenna terminal of the EUT is connected to the spectrum analyzer and Bluetooth test set via a power splitter with a known loss. Measurements are made while the EUT is operating at maximum power and at the appropriate frequencies.

6.2.3 Test limit

Part15.247(b)(3)

The maximum permissible conducted output power is 1 Watt.

Used conversion factor: Limit (dBm) = 10 log (Limit (W)/1mW)

==> Maximum Output Power: 30.0 dBm

6.2.4 Test Procedure Used


KDB 558074 D01 DTS Meas Guidance v05r02 - Section 9.1.3

6.2.5 Test Settings

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

6.2.6 Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



6.2.7 Test result

The test results are shown in Appendix A .

6.3 Transmitter Power Spectral Density

6.3.1 Ambient condition

Temperature	Relative humidity	Pressure
22°C	40%	101.5kPa

6.3.2 Test Description

The peak power density is measured with a spectrum analyzer and Bluetooth test set via a power splitter with a known loss connected to the antenna terminal of the EUT while the EUT is operating at maximum power and at the appropriate frequencies.

6.3.3 Test limit

Part15.247(e)

The maximum permissible power spectral density is 8.0 dBm in any 3 kHz band.

6.3.4 Test Procedure Used


KDB 558074 D01 DTS Meas Guidance v05r02 Section 10.2.

6.3.5 Test Settings

- Set analyzer center frequency to DTS channel center frequency.
- Set the span to 1.5 times the DTS bandwidth.
- Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- Set the VBW $\geq 3 \times \text{RBW}$.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level within the RBW.
- If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

6.3.6 Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



6.3.7 Test result

The test results are shown in Appendix A.

6.4 Conducted Out of band emission measurement

6.4.1 Ambient condition

Temperature	Relative humidity	Pressure
22°C	40%	101.5kPa

6.4.2 Test Description

For the following out of band conducted spurious emissions plots, the EUT was set to transmit at maximum power with the largest packet size available. The worst case spurious emissions were found in this configuration.

6.4.3 Test limit

Part 15.247(d) The limit for out-of-band spurious emissions at the band edge is 20dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100 kHz bandwidth.

6.4.4 Test Procedure Used

KDB 558074 D01 DTS Meas Guidance v05r02 Section 11.3,11.2

6.4.5 Reference level measurement Settings

Establish a reference level by using the following procedure:


- Set instrument center frequency to DTS channel center frequency.
- Set the span to ≥ 1.5 MHz
- Set the RBW = 100 kHz.
- Set the VBW ≥ 300 kHz.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum PSD level.

6.4.6 Test Settings

- Set the center frequency and span to encompass frequency range to be measured.
- Set the RBW = 100kHz.
- Set the VBW ≥ 300 kHz.
- Detector = peak.
- Set span to encompass the spectrum to be examined
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level.

6.4.8 Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



6.4.9 Test result

The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement. The test results are shown in Appendix A .

6.5 Band-edge measurement

6.5.1 Ambient condition

Temperature	Relative humidity	Pressure
22°C	40%	101.5kPa

6.5.2 Test Description

For the following out of band conducted spurious emissions plots, the EUT was set to transmit at maximum power with the largest packet size available. The worst case spurious emissions were found in this configuration.

6.5.3 Test limit

Part 15.247(d)

The limit for out-of-band spurious emissions at the band edge is 20dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100 kHz bandwidth.

6.5.4 Test Procedure Used

KDB 558074 D01 DTS Meas Guidance v05r02 Section 11.2

6.5.5 Reference level measurement Settings

Establish a reference level by using the following procedure:

- Set instrument center frequency to DTS channel center frequency.
- Set the span to ≥ 1.5 MHz
- Set the RBW = 100 kHz.
- Set the VBW ≥ 300 kHz.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum PSD level.


6.5.6 Test Settings

- Set the center frequency and span to encompass frequency range to be measured.
- Set the RBW = 100kHz.
- Set the VBW ≥ 300 kHz.
- Detector = peak.
- Set span to encompass the spectrum to be examined

- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum amplitude level.

6.5.8 Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



6.5.9 Test result

The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement. The test results are shown in Appendix A .

6.6 Spurious Radiated Emissions

6.6.1 Ambient condition

Temperature	Relative humidity	Pressure
22°C	40%	101.5kPa

6.6.2 Test Description

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at maximum power and at the appropriate frequencies. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section. The measurements shall be repeated with orthogonal polarization of the test antenna. The results shall be showed the worst case of the three orthogonal axes of EUT.

6.6.3 Test limit

Part15.205, 15.209, 15.247(d)

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in below Table per Section 15.209.

Frequency [MHz]	Field strength [$\mu\text{V/m}$]	Measured Distance [meters]
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Radiated Limits

Part15.35(b):

There is also a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit

Used conversion factor: Limit (dB $\mu\text{V/m}$) = 20 log (Limit ($\mu\text{V/m}$)/1 $\mu\text{V/m}$)

Frequency [MHz]	Detector	Unit (dB $\mu\text{V/m}$)
30~88	Quasi-peak	40.0
88~216	Quasi-peak	43.5
216~960	Quasi-peak	46.0
960~1000	Quasi-peak	54.0
1000~5th harmonic of the highest frequency or 40GHz, whichever is lower	Average	54.0
	Peak	74.0

Conversion Radiated limits

6.6.4 Test Procedure Used

KDB 558074 D01 DTS Meas Guidance v05r02 - Section 12.2.7

For Radiated emission below 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Both X and Y axes of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

For Radiated emission above 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

For the radiated emission test above 1GHz:

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna

elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Average detection (AV) at frequency above 1GHz. If duty cycle of test signal is < 98%, the duty factor need added to measured value.
4. All modes of operation were investigated and the worst-case emissions are reported.

6.6.5 Test Settings

Average Field Strength Measurements per Section 12.2.7 of KDB 558074 (Part 15.35)

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz > 1/T
4. Averaging type was set to RMS to ensure that video filtering was applied in the power domain
5. Detector = average
6. Sweep time = auto
7. Trace mode = max hold
8. Trace was allowed to run for at least 50 times (1/duty cycle) traces

Peak Field Strength Measurements per Section 12.2.7 of KDB 558074 (Part 15.35)


1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW is set depending on measurement frequency, as specified in following table

Frequency	RBW
9-150kHz	200-300Hz
0.15-30MHz	9-10kHz
30-1000MHz	100-120kHz
>1000MHz	1MHz


3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

6.6.6 Test Setup


For Radiated emission below 30MHz



For Radiated emission 30MHz to 1GHz



For Radiated emission above 1GHz



6.6.7 Test result

The test results are shown in Appendix B.

6.7 AC Power line Conducted Emission

6.7.1 Ambient condition

Temperature	Relative humidity	Pressure
22°C	40%	101.5kPa

6.7.2 Test limit

FCC Part15.207

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56 *	56 to 46 *
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

The measurement is made according to ANSI C63.10-2013

6.7.3 Test Procedures

a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.


b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.

c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

NOTE: The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.

The EUT shall test under the power AC120V/60Hz.

6.7.4 Test Setup



For the actual test configuration, please refer to the attached file (Test Setup Photo).

6.7.5 Test result

The test results are shown in AppendixB .

7 MEASUREMENT UNCERTAINTIES

Items	Uncertainty	
Occupied Bandwidth	3kHz	
Peak power output	0.67dB	
Band edge compliance	1.20dB	
Spurious emissions	30MHz~1GHz	2.83dB
	1GHz~12.75GHz	2.50dB
	12.75GHz~25GHz	2.75dB

8 TEST EQUIPMENTS

No.	Name/ Model	Manufacturer	S/N	Cal date	Cal Due date
1.	Spectrum Analyzer FSV	ROHDE&SCHWARZ	101065	2019.08.20	2020.08.19
2.	Power Meter E4416A	Agilent	MY52370013	2019.03.01	2020.02.29
3.	Power Sensor E9327A	Agilent	MY52420006	2019.03.01	2020.02.29
4.	23.18m×16.88m×9.60m Semi-Anechoic Chamber	FRANKONIA	---	-----	-----
5.	Turn table Diameter:5m	FRANKONIA	-----	-----	-----
6.	Antenna master SAC(MA4.0)	MATURO	-----	-----	-----
7.	9.080m×5.255m×3.525m Shielding room	FRANKONIA	-----	-----	-----
8.	HF 907 Double-Ridged Waveguide Horn Antenna	R&S	100512	2019.08.20	2020.08.19
9.	3160-09 Receive antenna	SCHWARZ-BECK	002058-002	2019.08.20	2020.08.19
10.	ESI 40 EMI test receiver	R&S	100015	2019.08.20	2020.08.19
11.	ESCS30 EMI test receiver	R&S	100029	2019.08.20	2020.08.19
12.	HL562 Receive antenna	R&S	100167	2019.08.20	2020.08.19
13.	ENV216 AMN	R&S	3560.6550.12	2019.08.20	2020.08.19

APPENDIX A – TEST DATA OF CONDUCTED EMISSION

Please refer to the attachment.

APPENDIX B – TEST DATA OF RADIATED EMISSION

Please refer to the attachment.


APPENDIX A – TEST DATA OF CONDUCTED EMISSION

6dB Bandwidth

Offset 10.8dB = Attenuator 10dB+Temporary antenna connector loss 0.2dB+ Cable loss 0.6dB

Modulation type: QPSK


Carrier frequency (MHz)	Channel No.	6 dB bandwidth(kHz)
2405	11	1569.84
2445	19	1582.64
2480	26	1566.64




Carrier frequency (MHz): 2405

Channel No.:11

Modulation type: QPSK



Carrier frequency (MHz): 2445
Channel No.:19
Modulation type: QPSK




Carrier frequency (MHz): 2480
Channel No.:26
Modulation type: QPSK

99% Occupied Bandwidth

Offset 10.8dB = Attenuator 10dB+Temporary antenna connector loss 0.2dB+ Cable loss 0.6dB

Modulation type: QPSK



Carrier frequency (MHz)	Channel No.	99% bandwidth(MHz)
2405	11	2.28
2445	19	2.33
2480	26	2.40



Carrier frequency (MHz): 2402

Channel No.:11

Modulation type: QPSK



Peak Power Output

Modulation type	Peak Power Output (dBm)		
	2405MHz (Ch11)	2445MHz (Ch19)	2480MHz (Ch26)
QPSK	22.66	21.87	21.43


Modulation type	Average Power Output (dBm)		
	2405MHz (Ch11)	2445MHz (Ch19)	2480MHz (Ch26)
QPSK	19.68	19.34	19.22

Transmitter Power Spectral Density


Offset 10.8dB = Attenuator 10dB+Temporary antenna connector loss 0.2dB+ Cable loss 0.6dB

Modulation type: QPSK


Carrier frequency (MHz)	Channel No	Power Density(dBm/10kHz)
2405	11	5.51
2445	19	5.41
2480	26	4.89



Carrier frequency (MHz): 2405
Channel No.:11
Modulation type: QPSK



Carrier frequency (MHz): 2445
Channel No.:19
Modulation type: QPSK





Carrier frequency (MHz): 2480
Channel No.:26
Modulation type: QPSK

Conducted Out of band emission measurement



Offset 10.8dB = Attenuator 10dB+Temporary antenna connector loss 0.2dB+ Cable loss 0.6dB

Modulation type: QPSK



CH11



CH19




CH26





Band edge measurement (RF Conducted measurement)

Offset 10.8dB = Attenuator 10dB+Temporary antenna connector loss 0.2dB+ Cable loss 0.6dB

CH11



CH26



APPENDIX B – TEST DATA OF RADIATED EMISSION

Radiated Emission Band Edge

The worst case attitude: The EUT lay down.

The measurement results are obtained as described below:

Measure Level = Reading Level + cable loss + antenna factor

Sample calculation: (109.71 dBuV/m) = (75.71 dBμV) + (8.90 dB) + (25.10 dB), the corresponding frequency is 2405MHz.

The measurement results include two polarizations: Horizontal and Vertical, pick the worst of them.

Carrier frequency (MHz): 2405

Channel No.:11

Polarity: Vertical

Detector: Peak

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2405	109.71	75.71	N/A	N/A	8.90	25.10
2	2400	58.06	24.06	-15.94	74.00	8.90	25.10

Carrier frequency (MHz): 2405

Channel No.:11

Polarity: Horizontal

Detector: Peak

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2405	104.27	70.27	N/A	N/A	8.90	25.10
2	2400	53.33	19.33	-20.67	74.00	8.90	25.10

Carrier frequency (MHz): 2405

Channel No.:11

Polarity: Vertical

Detector: Average

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2405	106.06	72.06	N/A	N/A	8.90	25.10
2	2400	45.42	11.42	-8.58	54.00	8.90	25.10

Carrier frequency (MHz): 2405

Channel No.:11

Polarity: Horizontal

Detector: Average

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2405	103.44	69.44	N/A	N/A	8.90	25.10
2	2400	44.39	10.39	-9.61	54.00	8.90	25.10

Carrier frequency (MHz): 2480

Channel No.:26

Polarity: Vertical

Detector: Peak

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2480	110.30	76.30	N/A	N/A	8.90	25.10
2	2485	58.04	24.04	-15.96	74.00	8.90	25.10

Carrier frequency (MHz): 2480

Channel No.:26

Polarity: Horizontal

Detector: Peak

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2480	105.00	71.00	N/A	N/A	8.90	25.10
2	2485	53.26	19.26	-20.74	74.00	8.90	25.10

Carrier frequency (MHz): 2480

Channel No.:26

Polarity: Vertical

Detector: Average

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2480	105.46	71.46	N/A	N/A	8.90	25.10
2	2485	44.65	10.65	-9.35	54.00	8.90	25.10

Carrier frequency (MHz): 2480

Channel No.:26

Polarity: Horizontal

Detector: Average

No	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	cable loss (dB)	antenna factor (dB)
1	2480	102.56	68.56	N/A	N/A	8.90	25.10
2	2485	44.56	10.56	-9.44	54.00	8.90	25.10

Sample Calculations

Determining Spurious Emissions Levels

A “reference path loss” is established and the A_{Rpl} is the attenuation of “reference path loss”, and including the gain of receive antenna, the gain of the preamplifier, the cable loss.

The measurement results are obtained as described below:

Result= $P_{mea} + A_{Rpl}$

Sample calculation: $(19.73 \text{ dBuV/m}) = (33.23 \text{ dBuV}) + (-13.5 \text{ dB/m})$, the corresponding frequency is 38.898000MHz.

The test data in the graph includes two polarizations: horizontal and vertical

Channel No.:11

Frequency (MHz)	Result (dBuV/m)	A_{Rpl} (dB)	P_{mea} (dBuV/m)	Polarity	Limit (dBuV/m)
38.898000	19.73	-13.5	33.23	Vertical	40.00
58.027500	21.29	-13.8	35.09	Vertical	40.00
63.773500	17.90	-14.0	31.9	Vertical	40.00
80.725500	20.04	-13.9	33.94	Vertical	40.00
900.156000	16.99	-13.7	30.69	Vertical	46.00
908.894500	17.05	-13.8	30.85	Vertical	46.00
921.210000	17.10	-16.1	33.2	Vertical	46.00
926.211500	17.17	-17.1	34.27	Vertical	46.00
953.651500	17.08	-16.4	33.48	Vertical	46.00
957.993500	17.10	-17.7	34.8	Vertical	46.00

Channel No.:19

Frequency (MHz)	Result (dBuV/m)	A_{Rpl} (dB)	P_{mea} (dBuV/m)	Polarity	Limit (dBuV/m)
30.000000	16.74	-13.0	29.74	Vertical	40.00
38.832500	19.61	-13.0	32.61	Vertical	40.00
57.796000	21.40	-13.2	34.6	Vertical	40.00
63.813500	18.04	-14.0	32.04	Vertical	40.00
79.464500	19.64	-13.6	33.24	Vertical	40.00
907.767000	17.04	-15.6	32.64	Vertical	46.00
913.441500	17.06	-15.7	32.76	Vertical	46.00
922.317000	17.11	-16.9	34.01	Vertical	46.00
936.350500	17.14	-16.8	33.94	Vertical	46.00


954.244500	17.05	-16.7	33.75	Vertical	46.00
------------	-------	-------	-------	----------	-------

Channel No.:26


Frequency (MHz)	Result (dBuV/m)	ARpl (dB)	Pmea (dBuV/m)	Polarity	Limit (dBuV/m)
31.038500	15.21	-13.0	30.55	Vertical	40.00
38.884500	19.52	-13.7	33.59	Vertical	40.00
57.821500	22.26	-14.0	35.26	Vertical	40.00
63.787000	18.70	-14.4	32.18	Vertical	40.00
79.669500	19.94	-13.5	34.56	Vertical	40.00
865.985500	16.30	-15.1	32.82	Vertical	46.00
905.205000	16.96	-15.7	33.56	Vertical	46.00
933.210000	17.06	-16.3	34.2	Vertical	46.00
951.868000	17.07	-18.1	35.69	Vertical	46.00
956.290000	17.05	-16.7	34.58	Vertical	46.00

Channel No.:11

Full Spectrum



Frequency Range: 30MHz-1000 MHz
Detector: QP mode




Frequency Range: 1GHz-3GHz
Detector: Av mode and PK mode

Result:

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
2252.200000	46.59	---	74.00	27.41
2307.000000	---	41.68	54.00	12.32
2307.200000	46.61	---	74.00	27.39
2340.200000	52.82	---	74.00	21.18
2341.200000	---	46.71	54.00	7.29
2350.600000	54.47	---	74.00	19.53
2350.800000	---	49.15	54.00	4.85
2373.600000	---	45.41	54.00	8.59
2405.400000	---	104.22	54.00	-50.22
2405.600000	109.60	---	74.00	-35.60
2408.400000	---	70.30	54.00	-16.30
2408.400000	76.20	---	74.00	-2.20
2459.000000	---	48.19	54.00	5.81
2459.400000	54.00	---	74.00	20.00
2469.000000	---	46.50	54.00	7.50
2469.400000	51.75	---	74.00	22.25
2503.400000	---	42.54	54.00	11.46
2503.400000	49.69	---	74.00	24.31
2557.400000	---	40.45	54.00	13.55
2557.400000	47.94	---	74.00	26.06

Full Spectrum




Frequency Range: 3GHz-18GHz
Detector: Av mode and PK mode

Result:

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
3060.640000	24.34	---	74.00	49.66
3066.704000	---	16.70	54.00	37.30
3864.878000	---	19.98	54.00	34.02
3874.732000	28.50	---	74.00	45.50
5111.418500	31.59	---	74.00	42.41
5117.318000	---	24.81	54.00	29.19
7599.144500	---	27.71	54.00	26.29
7605.044000	35.94	---	74.00	38.06
9595.500000	---	32.13	54.00	21.87
9641.900000	41.09	---	74.00	32.91
13615.700000	44.56	---	74.00	29.44
13615.900000	---	37.62	54.00	16.38

Full Spectrum




Frequency Range: 18GHz-26.5GHz
Detector: Av mode and PK mode

Result:


Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
22004.916667	37.74	---	74.00	36.26
24927.075000	37.91	---	74.00	36.09
24927.075000	---	36.41	54.00	17.59
24982.608333	37.79	---	74.00	36.21
25518.250000	37.87	---	74.00	36.13
25634.275000	---	36.07	54.00	17.93
26033.491667	37.80	---	74.00	36.20
26163.683333	---	36.14	54.00	17.86
26359.041667	---	38.72	54.00	15.28
26359.041667	39.99	---	74.00	34.01
26389.075000	---	36.29	54.00	17.71
26481.441667	---	36.94	54.00	17.06

Channel No.:19

Full Spectrum




Frequency Range: 30MHz-1000 MHz
Detector: QP mode



Frequency Range: 1GHz-3GHz
Detector: Av mode and PK mode

Result:

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
2318.400000	44.22	---	74.00	29.78
2319.000000	---	36.71	54.00	17.29
2344.000000	44.38	---	74.00	29.62
2372.800000	47.77	---	74.00	26.23
2380.600000	52.32	---	74.00	21.68
2380.800000	---	46.82	54.00	7.18
2413.800000	---	48.33	54.00	5.67
2414.000000	53.82	---	74.00	20.18
2419.400000	54.61	---	74.00	19.39
2419.400000	---	49.89	54.00	4.11
2445.000000	---	105.94	54.00	-51.94
2445.600000	109.83	---	74.00	-35.83
2471.200000	---	49.06	54.00	4.94
2471.400000	53.51	---	74.00	20.49
2489.400000	---	45.25	54.00	8.75
2508.600000	50.99	---	74.00	23.01
2508.800000	---	44.87	54.00	9.13
2571.000000	---	36.54	54.00	17.46
2837.200000	---	36.65	54.00	17.35
2977.000000	44.18	---	74.00	29.82




Frequency Range: 3GHz-18GHz
Detector: Av mode and PK mode

Result:

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
3476.024000	---	17.88	54.00	36.12
3493.647500	25.97	---	74.00	48.03
4980.387500	31.24	---	74.00	42.76
5001.501500	---	23.76	54.00	30.24
8000.000000	38.54	---	74.00	35.46
8002.250000	---	28.86	54.00	25.14
12517.550000	42.44	---	74.00	31.56
12575.650000	---	33.29	54.00	20.71
15100.500000	45.93	---	74.00	28.07
15100.800000	---	38.03	54.00	15.97
17482.100000	53.50	---	74.00	20.50
17482.650000	---	46.57	54.00	7.43

Full Spectrum




Frequency Range: 18GHz-26.5GHz
Detector: Av mode and PK mode

Result:

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
21984.516667	38.99	---	74.00	35.01
21984.516667	---	37.45	54.00	16.55
26007.283333	37.83	---	74.00	36.17
26016.066667	38.18	---	74.00	35.82
26117.641667	---	36.66	54.00	17.34
26144.841667	38.92	---	74.00	35.08
26144.841667	---	37.47	54.00	16.53
26372.075000	38.85	---	74.00	35.15
26372.075000	---	37.39	54.00	16.61
26396.725000	---	36.96	54.00	17.04
26413.158333	---	36.49	54.00	17.51
26467.983333	38.15	---	74.00	35.85


Channel No.:26

Full Spectrum



Frequency Range: 30MHz-1000 MHz
Detector: QP mode

Full Spectrum




Frequency Range: 1GHz-3GHz
Detector: Av mode and PK mode

Result:

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
2231.800000	---	37.37	54.00	16.63
2272.400000	---	37.80	54.00	16.20
2327.400000	46.05	---	74.00	27.95
2328.000000	---	40.69	54.00	13.31
2340.600000	45.58	---	74.00	28.42
2384.000000	---	44.28	54.00	9.72
2384.000000	49.89	---	74.00	24.11
2415.600000	54.46	---	74.00	19.54
2415.800000	---	49.12	54.00	4.88
2424.200000	---	49.95	54.00	4.06
2424.200000	56.13	---	74.00	17.87
2448.400000	56.83	---	74.00	17.17
2479.600000	108.43	---	74.00	-34.43
2480.400000	---	105.93	54.00	-51.93
2512.600000	51.86	---	74.00	22.14
2536.200000	54.65	---	74.00	19.35
2536.400000	---	48.09	54.00	5.91
2575.600000	---	40.52	54.00	13.48
2575.800000	47.45	---	74.00	26.55
2631.600000	---	37.96	54.00	16.04

Full Spectrum




Frequency Range: 3GHz-18GHz
Detector: Av mode and PK mode

Result:

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
3187.415500	---	17.07	54.00	36.93
3192.153000	24.21	---	74.00	49.79
4108.954000	---	20.40	54.00	33.60
4112.933500	29.15	---	74.00	44.85
5111.729000	32.30	---	74.00	41.70
5135.016500	---	23.74	54.00	30.26
8181.500000	37.14	---	74.00	36.86
8314.700000	---	29.07	54.00	24.93
9753.650000	43.10	---	74.00	30.90
9820.100000	---	32.99	54.00	21.01
16874.850000	51.95	---	74.00	22.05
16918.650000	---	42.54	54.00	11.46

Full Spectrum



Frequency Range: 18GHz-26.5GHz

Detector: Av mode and PK mode

Result:

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
22080.708333	---	37.74	54.00	16.26
22080.708333	39.70	---	74.00	34.30
22153.666667	37.70	---	74.00	36.30
25145.100000	37.24	---	74.00	36.76
25905.566667	37.94	---	74.00	36.06
26129.116667	38.50	---	74.00	35.50
26129.116667	---	37.03	54.00	16.97
26318.100000	---	36.70	54.00	17.30
26375.191667	---	37.25	54.00	16.75
26375.191667	38.49	---	74.00	35.51
26388.791667	---	36.60	54.00	17.40
26403.950000	---	37.08	54.00	16.92

AC Power line Conducted Emission(EUT TX on ZIGBEE+ charging)


A "reference path loss" Corr.(dB) is established and the $L_{\text{cable}} + \text{ATT} + \text{VDF}$ is the attenuation of "reference path loss", and including the cable loss, the attenuation of the attenuator, the voltage division factor of AMN.

The measurement results are obtained as described below:

$$P_{\text{result}} = P_{\text{mea}} + \text{Corr. (dB)}$$

Sample calculation: $(39.17 \text{ dB}\mu\text{V}) = (8.23 \text{ dB}\mu\text{V}) + (29.7 \text{ dB})$, the corresponding frequency is 0.308750MHz.

Full Spectrum



L+N Line

MEASUREMENT RESULT:

Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Line	Corr. (dB)	Pmea Quasi Peak (dBμV)	Pmea Average (dBμV)
0.308750	---	39.17	50.00	10.83	L1	29.7	---	8.23
0.349114	---	42.57	48.98	6.41	L1	29.7	---	9.47
0.450000	---	43.38	46.88	3.50	L1	29.7	---	12.87
0.525318	---	35.35	46.00	10.65	L1	29.7	---	13.68
0.599250	49.52	---	56.00	6.48	L1	29.7	19.82	---
0.676136	52.45	---	56.00	3.55	L1	29.7	22.75	---
0.676136	---	38.57	46.00	7.43	N	29.7	---	8.87
0.866614	50.36	---	56.00	5.64	L1	29.7	20.66	---
0.969591	46.97	---	56.00	9.03	L1	29.7	17.27	---
1.124409	---	39.06	46.00	6.94	L1	29.7	---	9.36
1.156068	54.20	---	56.00	1.80	N	29.7	24.5	---
1.358023	47.02	---	56.00	8.98	N	29.7	17.32	---

---End of Test Report---