

ACCO Brands, Inc.

DATE:2015/02/02

TUV SUD BABT
Octagon House, Concorde Way
Segensworth Rd N, Fareham
PO15 5RL

Subject: SAR Evaluation Exemption Compliance information

FCC ID: GV3M01287

IC: 6128A-M01287

Portable Exposure SAR Exemption

$f_{\text{(GHz)}} = 2.402$

Maximum e.r.p. power = 0.00032 W erp

Per RSS-102 Issue 4 Section 2.5.1 Exemption from Routine Evaluation Limits – SAR Evaluation

$f_{\text{(GHz)}} = 2.402$

Maximum e.r.p. power = 0.00032 W erp, which is less than 20mW, therefore SAR evaluation is not required.

Per FCC KDB 447498 D01 RF Exposure v05r01 Clause 4.3.1.1 SAR test exemption criteria

$\left[\frac{(\text{max. power of channel, including tune-up tolerance, mW})}{(\text{min. test separation distance, mm})} \right] \sqrt{f_{\text{(GHz)}}} \leq 3.0$

$f_{\text{(GHz)}}$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation¹⁷

The result is rounded to one decimal place for comparison

[Ref: Clause 4.3.1.1]


A test separation distance of 5 mm has been applied to the SAR test exclusion calculation.

$\left[\frac{(0.32\text{mW})}{(5, \text{mm})} \right] \sqrt{2.402_{\text{(GHz)}}} \leq 3.0$

$0.10 \leq 3.0$ for 2.402GHz

Therefore, the device meets the FCC SAR exemption requirements.

Yours sincerely,



Maggie.Zhang
Company: ACCO Brands, Inc.
Tel: 650.267.2711
Fax: 604.341.5155
Mail: Maggie.Zhang@kensington.com