

BX-29 Outdoor Bell Box

Powerful Siren with Multi-Purpose Voice Prompts to Protect Your Home



- Multi-Purpose Voice Prompts
- Unique Alarm Sounds for Fire & Burglary
- Four Selectable Siren Volume Levels
- IP56 Waterproof and Dustproof Housing
- Battery Operated or AC Powered

BX-29 is a wireless outdoor sounder with voice prompts to provide visible and audible alarm alerts. During an alarm, the BX-29 generates a loud 110 dB siren sounds and flashing strobe lights to warn off possible intruders, and notify of emergencies and safety incidents.

BX-29 generates unique voice prompts and alarm sounds to inform users of the type of danger at hand. It allows for four selectable siren volume levels, programmable strobe activation, and programmable siren durations of 3, 5, or 10 minutes. BX-29 emits beep notifications for low battery status, door chime, and arming/disarming of a security system.

BX-29 model leverages Climax's cutting-edge F1 technology to accelerate the speed of signal transmission and deliver extensive, reliable RF communication range, allowing users to stay in control, and provide a peace of mind.

With tamper-deterrent feature to protect against unauthorized removal and sabotage, and transmits supervisory and low battery signals to check system integrity. Enclosed in its IP56 waterproof and dustproof housing, the BX-29 easy-to-install outdoor siren is a premium choice to protect residential and commercial premises.

Features

- Siren output level is 110dB at 1 meter
- Voice Prompts to warn off intruders and report system status
- Extensive RF range, accelerated transmission speed, and reduced signal collisions (BX-29 only)
- Unique alarm sounds for fire and burglary
- Four selectable siren volume levels & programmable siren duration options
- IP56 rated waterproof and dustproof housing
- Beep notification of arming/disarming, door chime, and low battery status
- Regular supervision signals to check system integrity
- Tamper protection prevents unauthorized removal
- Low battery detection
- Compliant with CE requirement

Specifications

BX-29

Frequency	902 - 928 MHz
Power Source	1.5V, D Alkaline batteries x 4
Optional Power Source	NA
Battery Life	4.9 years
Siren Output	110dB at 1 meter
Strobe Light Cover	Blue (other colors available upon request)
Operating Temperature	-25°C to 60°C (-13°F to 140°F)
Operating Humidity	Up to 85% non-condensing
Dimensions	205mm x 83mm x 317mm

* Note: Actual battery life may vary due to device settings, operating environment, and usage activity

Federal Communication Commission Interference Statement

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation.

This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one of the following measures:

- . Reorient or relocate the receiving antenna.
- . Increase the separation between the equipment and receiver.
- . Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- . Consult the dealer or an experienced radio/TV technician for help.

FCC Caution: To assure continued compliance, any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate this equipment. (Example - use only shielded interface cables when connecting to computer or peripheral devices).

FCC Radiation Exposure Statement

This equipment complies with FCC RF radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with a minimum distance of 20 centimeters between the radiator and your body.

This transmitter must not be co-located or operating in conjunction with any other antenna or transmitter.

The antennas used for this transmitter must be installed to provide a separation distance of at least 20 cm from all persons and must not be co-located or operating in conjunction with any other antenna or transmitter.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

- (1) This device may not cause harmful interference, and (2) This device must accept any interference received, including interference that may cause undesired operation.