

Climax Technology Co Ltd
No. 258, Sinhu 2nd Rd., Neihu District Taipei City 114 Taiwan

Federal Communications Commission
Authorization and Evaluation Division
Equipment Authorization Branch
7435 Oakland Mills Road
Columbia, MD 21046

Applicant's declaration concerning RF Radiation Exposure

We hereby indicate that the product
Product description: Smart Home Alarm System
Model No: HSGWx-xxxxx-xxxxx Series (x=0~9, A~Z or blank),

The equipment complies with FCC RF radiation exposure limits set forth for an uncontrolled environment. The integral antennas used for this transmitter must not be co-located or operating in conjunction with any other antenna or transmitter within the host device.

A safety statement concerning minimum separation distances from enclosure of the
Product: Smart Home Alarm System
will be integrated in the user's manual to provide end-users with transmitter operating conditions for satisfying RF exposure compliance.

The appropriate information can be drawn from the test report no: W6M21710-17467-P-2244 and the accompanying calculations.


Company: Climax Technology Co Ltd

Address: No. 258, Sinhu 2nd Rd., Neihu District Taipei City 114 Taiwan

Date: 2017-10-11

Signature

George Lin



Report Number: W6M21710-17467-P-2224

FCC ID: GX9HSGW3G

9 Maximum Permissible Exposure

9.1 Applicable Standard

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.7 m normally can be maintained between the user and the device.

9.2 MPE Calculation Method

(A) Limits for Occupational/Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f ²)*	6
30-300	61.4	0.163	1.0	6
300-1500	--	--	f/300	6
1500-100,000	--	--	5	6

(B) Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	--	--	f/1500	30
1500-100,000	--	--	1.0	30

f = frequency in MHz

*Plane-wave equivalent power density

$$E \text{ (V/m)} \cdot \frac{\sqrt{30 \times P \times G}}{d}$$


$$\text{Power Density: } Pd \text{ (W/m}^2\text{)} \cdot \frac{E^2}{377}$$

E = Electric field (V/m) P = output power (W) G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd \cdot \frac{30 \times P \times G}{377 \times d^2}$$



Report Number: W6M21710-17467-P-2224

FCC ID: GX9HSGW3G

Frequency	Max output power (dBm) / (W)		Antenna Gain	Power Density(S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
GSM 850	31.27	1.33968	-5.17	0.154	1.0	Pass
PCS 1900	28.23	0.66527	2.6	0.83	1.0	Pass
WCDMA Band II	22.15	0.16406	2.6	0.655	1.0	Pass
WCDMA Band V	22.13	0.16331	-5.17	0.109	1.0	Pass

From the peak EUT RF output power, the minimum mobile separation distance, $d=0.7$ m, as well as the gain of the used antenna, the RF power density can be obtained.