

47 CFR PART 15 SUBPART C TEST REPORT

for

Power Relay Controller

Model No.: PRL-1

FCC ID: GX9PRL1F1919

of

Applicant: CLIMAX TECHNOLOGY CO., LTD.

**Address: No. 258, Sinhu 2nd Rd., Neihu District,
Taipei City 114, Taiwan (R.O.C.)**

Tested and Prepared

By

Worldwide Testing Services (Taiwan) Co., Ltd.

FCC Registration No.: TW1072, TW1140, TW1146, TW1477, TW0037

Industry Canada filed test laboratory Reg. No.: 20037, 31634



Report No.: W6M22512-24854-C-1

6F., No. 58, Ln. 188, Rueiguang Rd., Neihu Dist., Taipei City , Taiwan (R.O.C.)
TEL: 886-2-66068877 FAX: 886-2-66068879 E-mail: wtst@wtst-lab.com



Registration number: W6M22512-24854-C-1

FCC ID: GX9PRL1F1919

TABLE OF CONTENTS

1	GENERAL INFORMATION.....	2
1.1	NOTES.....	2
1.2	TESTING LABORATORY.....	3
1.2.1	<i>Location</i>	<i>3</i>
1.2.2	<i>Details of accreditation status</i>	<i>3</i>
1.3	DETAILS OF APPROVAL HOLDER	3
1.4	APPLICATION DETAILS.....	3
1.5	GENERAL INFORMATION OF TEST ITEM.....	4
1.6	TEST STANDARDS.....	4
1.7	TEST PROCEDURE.....	4
2	TECHNICAL TEST.....	5
2.1	SUMMARY OF TEST RESULTS.....	5
2.2	TEST ENVIRONMENT.....	5
2.3	TEST EQUIPMENT LIST	6
2.4	GENERAL TEST PROCEDURE.....	7
3	TEST RESULTS (ENCLOSURE)	9
3.1	PEAK OUTPUT POWER (TRANSMITTER).....	10
3.2	TRANSMITTER RADIATED EMISSIONS IN RESTRICTED BANDS	13
3.3	SPURIOUS EMISSIONS (TX)	14
3.4	CARRIER FREQUENCY SEPARATION.....	15
3.5	NUMBER OF HOPPING FREQUENCIES	17
3.5.1	<i>Pseudorandom Frequency Hopping Sequence</i>	<i>18</i>
3.5.2	<i>Coordination of hopping sequences to other transmitters.....</i>	<i>18</i>
3.5.3	<i>System Receiver Hopping Capability</i>	<i>18</i>
3.6	TIME OF OCCUPANCY (DWELL TIME).....	19
3.7	20dB BANDWIDTH	22
3.7.1	<i>System Receiver Input Bandwidth.....</i>	<i>23</i>
3.8	BAND-EDGE COMPLIANCE OF RF EMISSIONS.....	24
3.9	RADIATED EMISSIONS FROM DIGITAL PART	27
3.10	POWER LINE CONDUCTED EMISSION.....	28



Registration number: W6M22512-24854-C-1

FCC ID: GX9PRL1F1919

1 General Information

1.1 Notes

The purpose of conformity testing is to increase the probability of adherence to the essential requirements or conformity specifications, as appropriate.

The complexity of the technical specifications, however, means that full and thorough testing is impractical for both technical and economic reasons.

Furthermore, there is no guarantee that a test sample which has passed all the relevant tests conforms to a specification.

Neither is there any guarantee that such a test sample will interwork with other genuinely open systems.

The existence of the tests nevertheless provides the confidence that the test sample possesses the qualities as maintained and that its performance generally conforms to representative cases of communications equipment.

Laboratory disclaimer-

1. The test results of this test report relate exclusively to the item tested as specified in 1.5.
2. The test report may only be reproduced or published in full.
3. Reproduction or publication of extracts from the report requires the prior written approval of the Worldwide Testing Services(Taiwan) Co., Ltd.
4. Antenna gain is provided by applicant and laboratory issue relevant data and results.

Tester:

December 26, 2025

Kent Lin

Date

WTS-Lab.

Name

Signature

Technical responsibility for area of testing:

December 26, 2025

Kevin Wang

Date

WTS

Name

Signature



Registration number: W6M22512-24854-C-1

FCC ID: GX9PRL1F1919

1.2 Testing laboratory

1.2.1 Location

10m OATS

No.5-1, Lishui, Shuang Sing Village, Wanli Dist.,
New Taipei City 207, Taiwan (R.O.C.)

3 meter semi-anechoic chamber

No. 99, Sec. 1, Balian Rd., Xizhi Dist.,
New Taipei City 221032, Taiwan (R.O.C.)

Worldwide Testing Services (Taiwan) Co., Ltd.
6F., No. 58, Ln. 188, Ruiguang Rd., Neihu Dist.,
Taipei City 114, Taiwan (R.O.C.)
Tel: 886-2-6606-8877

1.2.2 Details of accreditation status

Accredited testing laboratory

FCC filed test laboratory Reg. No.: TW1072, TW1140, TW1146, TW1477, TW0037

Industry Canada filed test laboratory Reg. No.: 20037, 31634

Test location, where different from Worldwide Testing Services (Taiwan) Co., Ltd. :

Name: ./.
Accredited number: ./.
Street: ./.
Town: ./.
Country: ./.

1.3 Details of approval holder

Name: CLIMAX TECHNOLOGY CO., LTD.
Street: No. 258, Sinhu 2nd Rd., Neihu District,
Town: Taipei City 114,
Country: Taiwan (R.O.C.)

1.4 Application details

Date of receipt of test item: December 09, 2025

Date of test: from December 10, 2025 to December 18, 2025



Registration number: W6M22512-24854-C-1

FCC ID: GX9PRL1F1919

1.5 General information of Test item

Type of test item: Power Relay Controller

Model number: PRL-1

Multi-listing model number: ./.

Sample no.: #01

Technical data

Frequency band: 918.0375-924.48 MHz

Mode	Frequency (MHz)	Power 12Vd.c. (dBm)	Power 24Vd.c. (dBm)
900M	918.0375 MHz	10.42	10.55
	924.48 MHz	10.21	10.28

Power supply: 12Vd.c. and 24Vd.c.

Operation modes: Duplex

Modulation type: FSK

Antenna type: Monopole antenna

Antenna gain: -5.97 dBi

Host device: none

Classification:

Manufacturer: (if applicable)

Name: ./.

Street: ./.

Town: ./.

Country: ./.

1.6 Test standards

47 CFR PART 15 SUBPART C § 15.247 (2024-10)

1.7 Test procedure

ANSI C63.10-2020+ Cor.1-2023+C63.10a-2024



Registration number: W6M22512-24854-C-1

FCC ID: GX9PRL1F1919

2 Technical test

2.1 Summary of test results

No deviations from the technical specification(s) were ascertained in the course of the tests performed. ☒

or

The deviations were ascertained in the course of the tests performed. ☐

2.2 Test environment

Relative humidity content: 20 ... 75 %

Air pressure: 86 ... 103 kPa

Details of power supply: 12Vd.c. and 24Vd.c.

Extreme conditions parameters: test voltage : -- extreme
min : -- V
max : -- V

Test item Name	Uncertainty
Estimation Result of Uncertainty of Conducted Emission (Power Line Conducted Emission)	Expanded Uncertainty : AMN : 0.94 dB Voltage probe : 1.21 dB Include Pulse Limiter : 1.5 dB
Estimation Result of Uncertainty of Radiated Emission(3M - 966A) (Transmitter Radiated Emissions in restricted Bands, Spurious emissions (tx), Radiated Emissions from Receiver Part)	Expanded Uncertainty : 0.009-30 MHz : 1.85 dB 30-1000 MHz : 3.92 dB 1-18 GHz : 3.19 dB 18-40 GHz : 1.90 dB
Estimation Result of Uncertainty of Bandwidth Measurement (20 dB Bandwidth)	Expanded Uncertainty : 0.37 kHz
Estimation Result of Uncertainty of Conducted Output Power Measurement (Peak Output Power (transmitter))	Expanded Uncertainty : 1.63 dB
Estimation Result of Uncertainty of Band Edge Measurement (Band-edge Compliance of RF Emissions)	Expanded Uncertainty : 0.63 dBc
Estimation Result of Uncertainty of Frequency Separation Measurement (Carrier Frequency Separation, Number of Hopping Frequencies)	Expanded Uncertainty : 554.14 Hz
Estimation Result of Uncertainty of Duty Cycle Measurement (Time of Occupancy (Dwell Time))	Expanded Uncertainty : 0.18 ms

The decision rule is: Measurement uncertainty is not included in the calculation of test results.



Registration number: W6M22512-24854-C-1

FCC ID: GX9PRL1F1919

2.3 Test Equipment List

MaxOutput Power&20DB BANDWIDTH&BANDEDGE&

FREQUENCY SEPARATION&NUMBER OF HOPPING&DWELL TIME

Code No.	Test equipment	Mode No.	Serial No.	Brand	Cal. Date	Next Cal. Date
ETSTW-RE 050	Attenuator 10dB	50HF-010-1	None	JFW	2025/2/14	2026/2/13
ETSTW-RE 055	SPECTRUM ANALYZER	FSU 26	200074	R&S	2025/3/5	2026/3/4
ETSTW-RE 099	DC Block	50DB-007-1	None	JFW	2025/2/14	2026/2/13
ETSTW-Cable 030	Microwave Cable	SUCOFLEX 104 (S_Cable 9)	279067	HUBER+SUHNER	2025/2/14	2026/2/13

Code No.	Test equipment	Mode No.	Serial No.	Brand	Cal. Date	Next Cal. Date
ETSTW-RE 153	Signal Analyzer	FSV40	101929	R&S	2025/9/10	2026/9/9
ETSTW-RE 154	EMI Test Receiver	ESR3	102829	R&S	2025/2/14	2026/4/8
ETSTW-RE 160	Amplifier Module	CHC 3	None	WTS	2025/7/11	2026/7/10
ETSTW-RE 177	TRILOG Broadband Antenna	VULB 9168&EMCI-N-6-06	01380&AT-06007	SCHWARZBECK&EMC	2025/3/10	2026/3/9
ETSTW-RE 178	Double Ridged Guide Horn Antenna	DRH18-E	210505A18ES	RFSPIN	2025/3/7	2026/3/6
ETSTW-Cable 077	SMA type cable (10m)	EMC104-SM-SM-10000	230511	EMCI	2025/7/11	2026/7/10
ETSTW-Cable 084	SMA type cable (1m)	SF104-11SMA-1000	816477/4	HONOVA	2025/7/11	2026/7/10
ETSTW-Cable 089	SMA type cable (2m)	SF104-11SMA-2000	SN 811889/4	HUBER+SUHNER	2025/7/11	2026/7/10
WTSTW-SW 002	EMI TEST SOFTWARE	EZ_EMC	None	Farad	Version ETS-03A1 Version EMEC-3A1+	



Registration number: W6M22512-24854-C-1

FCC ID: GX9PRL1F1919

2.4 General Test Procedure

POWER LINE CONDUCTED INTERFERENCE: The procedure used was ANSI C63.10-2020+ Cor.1-2023+C63.10a-2024 6.2 using a LISN (if necessary). Both lines were observed. The bandwidth of the spectrum analyzer was 10 kHz with an appropriate sweep speed.

RADIATION INTERFERENCE: The test procedure used was according to ANSI C63.10-2020+ Cor.1-2023+C63.10a-2024 6.3 employing a spectrum analyzer. For investigated frequency is equal to or below 1GHz, the RBW and VBW of the spectrum analyzer was 100 kHz and 100kHz respectively with an appropriate sweep speed. For investigated frequency is above 1GHz, both of RBW and VBW of the spectrum analyzer were 1 MHz with an appropriate sweep speed. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The ambient temperature of the UUT was 23°C with a humidity of 40 %.

FORMULA OF CONVERSION FACTORS: The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dBμV) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB.

Example:

Freq (MHz) METER READING + ACF + CABLE LOSS (to the receiver) = FS
20 dBμV + 10.36 dB + 6 dB = 36.36 dBμV/m @3m

The EUT was placed on a table 80 cm high and with dimensions of 1m by 1.5m (non metallic table) and arranged according to ANSI C63.10-2020+ Cor.1-2023+C63.10a-2024 6.2.2. The table used for radiated measurements is capable of continuous rotation. The spectrum was scanned from 30 MHz to the frequency specified as follows:

- (1) If the intentional radiator operates below 10 GHz: to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.
- (2) If the intentional radiator operates at or above 10 GHz and below 30 GHz: to the fifth harmonic of the highest fundamental frequency or to 100 GHz, whichever is lower.
- (3) If the intentional radiator operates at or above 30 GHz: to the fifth harmonic of the highest fundamental frequency or to 200 GHz, whichever is lower, unless specified otherwise elsewhere in the rules.
- (4) If the intentional radiator contains a digital device, regardless of whether this digital device controls the functions of the intentional radiator or the digital device is used for additional control or function purposes other than to enable the operation of the intentional radiator, the frequency range shall be investigated up to the range specified in paragraphs (a)(1)-(a)(3) of this section or the range applicable to the digital device, as shown in paragraph (b)(1) of this Section, whichever is the higher frequency range of investigation.

For hand-held devices, a exploratory test was performed with three (3) orthogonal planes to determine the highest emissions.

When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes.



Registration number: W6M22512-24854-C-1

FCC ID: GX9PRL1F1919

When the radiated emission limits are expressed in terms of the average value of the emission, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.

The formula is as follows:

Average = Peak + Duty Factor

Duty Factor = $20 \log (\text{dwell time}/T)$

$T = 100\text{ms}$ when the pulse train period is over 100 ms or the period of the pulse train.

Modified Limits for peak according to 15.35 (b) = Max Permitted average Limits + 20dB

ANSI C63.10-2020+ Cor.1-2023+C63.10a-2024 B.2.7: Any measurements that utilize special test software shall be indicated and referenced in the test report. During testing, test software 'EZ EMC' was used for setting up different operation modes.



Registration number: W6M22512-24854-C-1

FCC ID: GX9PRL1F1919

3 Test results (enclosure)

TEST CASE	Para. Number	Required	Test passed	Test failed
Peak Output Power	15.247(b)	☒	☒	☐
Equivalent radiated Power	15.247(b)	☒	☒	☐
Spurious Emissions radiated – Transmitter operating	15.247(d):15.209	☒	☒	☐
Spurious Emissions conducted – Transmitter operating	15.247	☐	☐	☐
Carrier Frequency Separation	15.247(a) (1)	☒	☒	☐
Number of Hopping Frequencies	15.247(a) (1)(i)	☒	☒	☐
Time of Occupancy (Dwell Time)	15.247(a) (1)(i)	☒	☒	☐
20 dB Bandwidth	15.247(a) (1)(i)	☒	☒	☐
Band-edge Compliance of RF Emission	15.247(d)	☒	☒	☐
Radiated Emission from Digital Part	15.109	☐	☐	☐
Power Line Conducted Emission	15.207(a)	☒	☒	☐

The follows is intended to leave blank.



Registration number: W6M22512-24854-C-1

FCC ID: GX9PRL1F1919

3.1 Peak Output Power (transmitter)

FCC Rule: 15.247

This measurement applies to equipment with an integral antenna and to equipment with an antenna connector and equipped with an antenna as declared by the applicant.

The power was measured with modulation (declared by the applicant).

Test date: December 10, 2025


Temperature: 23°C

Humidity: 58.8%

Tester: Sky

Band	Channel	Power 12Vd.c. (dBm)	Power 24Vd.c. (dBm)	Limit (dBm)
900M	918.0375 MHz	10.42	10.55	30
	924.48 MHz	10.21	10.28	30


12Vd.c.



MAX OUTPUT POWER 918.0375MHz
Date: 10.DEC.2025 21:14:32




Registration number: W6M22512-24854-C-1
FCC ID: GX9PRL1F1919



MAX OUTPUT POWER 924.48MHz
Date: 10.DEC.2025 21:16:25


24Vd.c.



MAX OUTPUT POWER 918.0375MHz
Date: 10.DEC.2025 21:19:01



Registration number: W6M22512-24854-C-1
FCC ID: GX9PRL1F1919



MAX OUTPUT POWER 924.48MHz
Date: 10.DEC.2025 21:20:44

Limits:

Frequency (MHz)	Number of hopping channels			
	≥ 75	≥ 50	$49 \geq 25$	$74 \geq 15$
902-928	--	30 dBm	24 dBm	--
2400-2483.5 MHz	30 dBm	--	--	21 dBm
5725-5850 MHz	30 dBm	--	--	--

In case of employing transmitter antennas having antenna gain >dBi and using fixed point-to point operation consider §15.247 (b)(4).



Registration number: W6M22512-24854-C-1

FCC ID: GX9PRL1F1919

3.2 Transmitter Radiated Emissions in restricted Bands

FCC Rules: 15.247 (d), 15.205, 15.209, 15.35

Radiated emission measurements were performed from 30 MHz to 26000 MHz.

For radiated emission tests, the analyzer setting was as followings:

RES BW VID BW

Frequency <1 GHz 100 kHz 100 kHz (Peak measurements)

Frequency >1 GHz 1 MHz 1 MHz (Peak measurements)

1 MHz 1 MHz (Average measurements)

Limits:

For frequencies below 1GHz :

Frequency of Emission (MHz)	Field strength (microvolts/meter)	Field Strength (dB microvolts/meter)
30 – 88	100	40.0
88 – 216	150	43.5
216 – 960	200	46.0
Above 960	500	54.0

For frequencies above 1GHz (Average measurements).

Guidance on Measurement of FHSS Systems:

“If the emission is pulsed, modify the unit for continues operation , use the settings shown above, then correct the reading by subtracting the peak-average correction factor, derived from the appropriate duty cycle calculation.” Here the correction was added to the limit instead subtracted from the reading.

Duty cycle correction = $20 \log (\text{dwell time}/100\text{ms})$

For frequencies above 1GHz (Average measurements).

Limit – duty cycle correction

No duty cycle correction was added to the reading.

54.0dB μ V/m

For frequencies above 1GHz (Peak measurements).

Limit + 20dB

54.0dB μ V/m + 20 dB= 74 dB μ V/m

Explanation: After evaluated, the test result in this report adopt the worst case to measure, please see attached diagrams in appendix.



Registration number: W6M22512-24854-C-1

FCC ID: GX9PRL1F1919

3.3 Spurious emissions (tx)

Spurious emission was measured with modulation (declared by manufacturer).

In any 100 kHz bandwidth outside the frequency band in which the intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c))

SAMPLE CALCULATION OF LIMIT. All results will be updated by an automatic measuring system in accordance to point 2.3.

Calculation of test results:

Such factors like antenna correction, cable loss, external attenuation etc. are already included in the provided measurement results. This is done by using validated test software and calibrated test system according the accreditation requirements.

The peak and average spurious emission plots was measured with the average limits.

In the Table being listed the critical peak and average value an exhibit the compliance with the above calculated Limits.

If in the column's correction factor states a value then the max. Field strength in the same row is corrected by a value gained from the "Marker-Delta-Method" or the „Duty-Cycle Correction Factor“.

Summary table with radiated data of the test plots

- Note**
- 1. Correction Factor = Antenna factor + Cable loss - Preamplifier**
 - 2. The formula of measured value as: Test Result = Reading + Correction Factor**
 - 3. Detector function in the form : PK = Peak, QP = Quasi Peak, AV = Average**
 - 4. All not in the table noted test results are more than 20 dB below the relevant limits.**
 - 5. After evaluated, the test result in this report adopt the worst case to measure, please see attached diagrams in appendix.**

All other not noted test plots do not contain significant test results in relation to the limits.

TEST RESULT (Transmitter): The unit DOES meet the FCC requirements.



Registration number: W6M22512-24854-C-1

FCC ID: GX9PRL1F1919

3.4 Carrier Frequency Separation

Carrier Frequency Separation was measured with modulation (declared by manufacturer).


According to FCC rules part 15 subpart C §15.247 frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or 20 dB bandwidth of the hopping channel, whichever is greater.

Test date: December 11, 2025

Temperature: 22.6°C

Humidity: 57.7%

Tester: Sky




FREQUENCY SEPARATION 918.0375MHz

Date: 11.DEC.2025 15:07:48



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22512-24854-C-1
FCC ID: GX9PRL1F1919



FREQUENCY SEPARATION 924.48MHz
Date: 11.DEC.2025 15:12:30

Limits:

Frequency (MHz)	20 dB bandwidth < 25 kHz	20 dB bandwidth > 25 kHz
902-928	25 kHz	20 dB bandwidth
2400-2483.5 5725-5850	25 kHz	20 dB bandwidth



Registration number: W6M22512-24854-C-1

FCC ID: GX9PRL1F1919

3.5 Number of Hopping Frequencies

According to FCC rules part 15 subpart C §15.247 frequency hopping systems operating in the 2400-2483.5 MHz band shall use at least 15 hopping frequencies. Frequency hopping systems in 5725-5850 MHz bands shall use least 75 hopping frequencies.


For frequency hopping systems operating in the 902-928 MHz band: if the 20dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies; if the 20dB bandwidth of the hopping channel 250 kHz or greater, the system shall use at least 25 hopping frequencies.

Test date: December 11, 2025

Temperature: 22.6°C

Humidity: 57.7%

Tester: Sky



NUMBER OF HOPPING
Date: 11.DEC.2025 15:21:19

Limits:

Frequency (MHz)	20dB Bandwidth	Number of Channels
902-928	Bandwidth < 250 kHz	≥ 50
	Bandwidth ≥ 250 kHz	≥ 25
2400-2483.5	not defined	15
5725-5850	1 MHz	75



Registration number: W6M22512-24854-C-1

FCC ID: GX9PRL1F1919

3.5.1 Pseudorandom Frequency Hopping Sequence

The generation of the hopping sequence is determined by the Bluetooth core specification and complies with the FCC requirements.

3.5.2 Coordination of hopping sequences to other transmitters

According to the Bluetooth core specification such a coordination is not possible. During scatternet function only one of the two hopping sequences will be used at a definite moment.

3.5.3 System Receiver Hopping Capability

According to the Bluetooth core specification. The system receivers shift frequencies in synchronization with the transmitted signals.



Registration number: W6M22512-24854-C-1

FCC ID: GX9PRL1F1919

3.6 Time of Occupancy (Dwell Time)

Frequency hopping systems operating in the 5725-5850 MHz band shall use an average time of occupancy on any frequency not greater than 0.4 seconds within a 30 second period.

In 2400-2483.5 MHz band the average time of occupancy on any channel shall not be greater than 0.4 seconds multiplied by the number of hopping channels employed.


For frequency hopping systems operating in the 902-928 MHz band: if the 20dB bandwidth of the hopping channel is less than 250 kHz, the average time of occupancy on any frequency shall not greater than 0.4 seconds within a 20 second period; if the 20dB bandwidth of the hopping channel is 250 kHz or greater, the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period.

Test date: December 11, 2025

Temperature: 22.6°C

Humidity: 57.7%


Tester: Sky




DWELL TIME 918.0375MHz
Date: 11.DEC.2025 13:45:09



Registration number: W6M22512-24854-C-1
FCC ID: GX9PRL1F1919




DWELL TIME 918.0375MHz (9.214ms * 5events = 46.07ms)
Date: 11.DEC.2025 14:03:50



DWELL TIME 924.48MHz
Date: 11.DEC.2025 14:56:36



Registration number: W6M22512-24854-C-1
FCC ID: GX9PRL1F1919



DWELL TIME 924.48MHz (9.214ms * 5events = 46.07ms)
Date: 11.DEC.2025 14:59:58

Limits and measurement periods:

Frequency (MHz)	Number of channels	Measurement Period	Limit
902 – 928	≥ 50	20 s	0.4 s
	$49 \geq 25$	10 s	0.4 s
2400 – 2483.5	≥ 15	0.4 s * number of used channels	0.4 s
5725- 5850	≥ 75	30 s	0.4s



Registration number: W6M22512-24854-C-1

FCC ID: GX9PRL1F1919

3.7 20dB Bandwidth


The 20dB bandwidth is measured on the lowest, middle and highest hopping channel.

Test date: December 10, 2025

Temperature: 23°C

Humidity: 58.8%


Tester: Sky



20DB BANDWIDTH 918.0375MHz
Date: 10.DEC.2025 21:53:30



Registration number: W6M22512-24854-C-1
FCC ID: GX9PRL1F1919




20dB BANDWIDTH 924.48MHz
Date: 10.DEC.2025 21:55:14

Limits:

Frequency (MHz)	Limit
902-928	≤ 500 kHz
2400-2483.5	not defined
5725-5850	≤ 1 MHz

3.7.1 System Receiver Input Bandwidth


It is determined in the Bluetooth core specification. The value matches to the bandwidth of transmitter signal.




FCC ID: GX9PRL1F1919



Registration number: W6M22512-24854-C-1
FCC ID: GX9PRL1F1919




BANDEDGE 924.48MHz
Date: 10.DEC.2025 22:01:11



BANDEDGE 918.0375MHz HOPPING
Date: 10.DEC.2025 22:07:48



Registration number: W6M22512-24854-C-1
FCC ID: GX9PRL1F1919



Limits:

Frequency (MHz)	Limit
902 – 928	- 20 dB
2400 – 2483.5	
5725 - 5850	



Registration number: W6M22512-24854-C-1

FCC ID: GX9PRL1F1919

3.9 Radiated Emissions from Digital Part

FCC Rule: 15.109

Summary table with radiated data of the test plots

Except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency of Emission (MHz)	Field Strength (microvolts/meter)	Field Strength (dBmicrovolts/meter)
30 – 88	100	40.0
88 – 216	150	43.5
216 – 960	200	46.0
Above 960	500	54.0

Explanation: The test results are listed in the separated test report no.: W6M22512-24854-P-15B.



Registration number: W6M22512-24854-C-1


FCC ID: GX9PRL1F1919

3.10 Power Line Conducted Emission

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the table bellows with this provision shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminals.

This measurement was transact first with instrumentation using an average and peak detector and a 10 kHz bandwidth. If the peak detector achieves a calculated level, the measurement is repeated by an instrumentation using a quasi-peak detector.

12Vd.c.




Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corrected factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Comment
	0.1540	1.24	QP	9.87	11.11	65.78	-54.67	
	0.1540	-6.85	AVG	9.87	3.02	55.78	-52.76	
	0.1680	0.10	QP	9.89	9.99	65.06	-55.07	
	0.1680	-6.60	AVG	9.89	3.29	55.06	-51.77	
	0.1974	-0.24	QP	9.93	9.69	63.72	-54.03	
	0.1974	-7.04	AVG	9.93	2.89	53.72	-50.83	
	0.2174	-2.07	QP	9.93	7.86	62.92	-55.06	
	0.2174	-7.50	AVG	9.93	2.43	52.92	-50.49	
	0.2377	-1.46	QP	9.93	8.47	62.18	-53.71	
*	0.2377	-7.09	AVG	9.93	2.84	52.18	-49.34	
	0.2578	-2.47	QP	9.92	7.45	61.50	-54.05	
	0.2578	-7.96	AVG	9.92	1.96	51.50	-49.54	



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22512-24854-C-1
FCC ID: GX9PRL1F1919



Site : Chamber_03

Condition : FCC Part 15 Class B Conduction (QP)

EUT : W6M22512-24854

M/N:

Test Mode :

Note :

Phase: L1

Power : 12Vd.c.

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corrected factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Comment
	0.1507	3.61	QP	9.88	13.49	65.96	-52.47	
	0.1507	-6.69	AVG	9.88	3.19	55.96	-52.77	
	0.1645	1.70	QP	9.89	11.59	65.23	-53.64	
	0.1645	-6.33	AVG	9.89	3.56	55.23	-51.67	
	0.2065	-1.77	QP	9.93	8.16	63.34	-55.18	
	0.2065	-7.50	AVG	9.93	2.43	53.34	-50.91	
	0.2608	-2.51	QP	9.92	7.41	61.41	-54.00	
	0.2608	-7.86	AVG	9.92	2.06	51.41	-49.35	
	0.3091	-2.92	QP	9.92	7.00	59.99	-52.99	
	0.3091	-7.85	AVG	9.92	2.07	49.99	-47.92	
	0.3453	-2.61	QP	9.92	7.31	59.07	-51.76	
*	0.3453	-7.63	AVG	9.92	2.29	49.07	-46.78	




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22512-24854-C-1

FCC ID: GX9PRL1F1919

24Vd.c.



Site : Chamber_03

Condition : FCC Part 15 Class B Conduction (QP)

EUT : W6M22512-24854

M/N:

Test Mode :

Note :

Phase: N


Power : 24Vd.c.

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corrected factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Comment
	0.1516	4.55	QP	9.87	14.42	65.91	-51.49	
	0.1516	-6.51	AVG	9.87	3.36	55.91	-52.55	
	0.1652	2.88	QP	9.89	12.77	65.20	-52.43	
	0.1652	-6.46	AVG	9.89	3.43	55.20	-51.77	
	0.1785	1.04	QP	9.90	10.94	64.56	-53.62	
	0.1785	-7.13	AVG	9.90	2.77	54.56	-51.79	
	0.2011	-0.48	QP	9.93	9.45	63.57	-54.12	
	0.2011	-7.33	AVG	9.93	2.60	53.57	-50.97	
	0.2500	-2.11	QP	9.93	7.82	61.76	-53.94	
	0.2500	-7.65	AVG	9.93	2.28	51.76	-49.48	
	0.2872	-2.84	QP	9.92	7.08	60.60	-53.52	
*	0.2872	-7.90	AVG	9.92	2.02	50.60	-48.58	



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22512-24854-C-1
FCC ID: GX9PRL1F1919



Site : Chamber_03

Condition : FCC Part 15 Class B Conduction (QP)

EUT : W6M22512-24854

M/N:

Test Mode :

Note :

Phase: L1

Power : 24Vd.c.

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corrected factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Comment
	0.1530	5.06	QP	9.88	14.94	65.84	-50.90	
	0.1530	-6.60	AVG	9.88	3.28	55.84	-52.56	
	0.1686	2.99	QP	9.90	12.89	65.03	-52.14	
	0.1686	-6.42	AVG	9.90	3.48	55.03	-51.55	
	0.1992	0.64	QP	9.93	10.57	63.64	-53.07	
	0.1992	-7.18	AVG	9.93	2.75	53.64	-50.89	
	0.2321	-0.20	QP	9.93	9.73	62.37	-52.64	
	0.2321	-6.00	AVG	9.93	3.93	52.37	-48.44	
	0.2627	-2.76	QP	9.92	7.16	61.35	-54.19	
	0.2627	-7.90	AVG	9.92	2.02	51.35	-49.33	
	0.3007	-2.66	QP	9.92	7.26	60.22	-52.96	
*	0.3007	-7.95	AVG	9.92	1.97	50.22	-48.25	

- Note:
1. The formula of measured value as: Test Result = Reading + Correction Factor
 2. The Correction Factor = Cable Loss + LISN Insertion Loss + Pulse Limit Loss
 3. Detector function in the form : PK = Peak, QP = Quasi Peak, AV = Average
 4. All not in the table noted test results are more than 20 dB below the relevant limits.
 5. Up Line: QP Limit Line, Down Line: Ave Limit Line.



Registration number: W6M22512-24854-C-1
FCC ID: GX9PRL1F1919

Appendix

Measurement diagrams

Spurious Emissions radiated



Radiated Emission Measurement

Operator: Jeff

File :1_12V

Data :#1


Date: 2025/12/12

Temperature:27.3 °C

100.0 dBuV/m

Time: 上午 11:45:43

Humidity:47.5 %



Site : 966A Chamber

Condition : FCC Restriction Band 30-300

EUT : W6M22512-24854

M/N:

Test Mode : TX 918.0375MHz

Note :

Polarization: Horizontal

Power : 12 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	49.1700	33.25	peak	-12.79	20.46	74.00	100	282	-53.54	
	142.0500	38.78	peak	-12.76	26.02	74.00	100	90	-47.98	
	182.2800	37.78	peak	-14.10	23.68	74.00	100	118	-50.32	
*	257.0700	36.33	peak	-13.57	22.76	46.00	100	107	-23.24	



Radiated Emission Measurement


Operator: Jeff

File : 1_12V
100.0 dBuV/m

Data : #3

Date: 2025/12/12
Time: 上午 11:47:12

Temperature: 27.3 °C
Humidity: 47.5 %



Site : 966A Chamber

Condition : FCC Restriction Band 300-1000

EUT : W6M22512-24854

M/N:

Test Mode : TX 918.0375MHz

Note :

Polarization: **Horizontal**

Power : 12 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	440.0000	33.75	peak	-8.28	25.47	74.00	100	318	-48.53	
	580.0000	33.51	peak	-5.48	28.03	74.00	100	113	-45.97	
	790.7000	33.14	peak	-1.93	31.21	74.00	100	135	-42.79	
*	965.7000	34.18	peak	-0.34	33.84	54.00	100	74	-20.16	



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement


Operator: Jeff

File : 1_12V
100.0 dBuV/m

Data : #2

Date: 2025/12/12
Time: 上午 11:46:27

Temperature: 27.3 °C
Humidity: 47.5 %



Site : 966A Chamber

Condition : FCC Restriction Band 30-300

EUT : W6M22512-24854

M/N:

Test Mode : TX 918.0375MHz

Note :

Polarization: Vertical

Power : 12 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	48.3600	33.55	peak	-12.87	20.68	74.00	100	18	-53.32	
	145.2900	34.61	peak	-12.63	21.98	74.00	100	356	-52.02	
	177.9600	40.19	peak	-13.68	26.51	74.00	100	281	-47.49	
*	281.9100	34.70	peak	-12.47	22.23	46.00	100	247	-23.77	

*:Maximum data x:Over limit !:over margin



Radiated Emission Measurement


Operator: Jeff

File :1_12V
100.0 dBuV/m

Data :#4

Date: 2025/12/12
Time: 上午 11:47:57

Temperature:27.3 °C
Humidity:47.5 %



Site : 966A Chamber

Condition : FCC Restriction Band 300-1000

EUT : W6M22512-24854

M/N:

Test Mode : TX 918.0375MHz

Note :

Polarization: **Vertical**

Power : 12 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	432.3000	33.94	peak	-8.56	25.38	74.00	100	359	-48.62	
	586.3000	32.63	peak	-5.32	27.31	74.00	100	248	-46.69	
	780.9000	33.19	peak	-1.99	31.20	74.00	100	165	-42.80	
*	955.9000	34.20	peak	-0.34	33.86	74.00	100	356	-40.14	



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement


Operator: Jeff

File : 1_24V
100.0 dBuV/m

Data : #1

Date: 2025/12/12
Time: 下午 01:43:54

Temperature: 27.3 °C
Humidity: 47.5 %



Site : 966A Chamber

Condition : FCC Restriction Band 30-300

EUT : W6M22512-24854

M/N:

Test Mode : TX 918.0375MHz

Note :

Polarization: **Horizontal**

Power : 24 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	58.6200	33.70	peak	-12.76	20.94	74.00	100	345	-53.06	
	142.3200	36.45	peak	-12.75	23.70	74.00	100	95	-50.30	
	196.0500	40.15	peak	-15.46	24.69	74.00	100	100	-49.31	
*	255.9900	38.42	peak	-13.58	24.84	46.00	100	89	-21.16	

*:Maximum data x:Over limit !:over margin



Radiated Emission Measurement


Operator: Jeff

File :1_24V
100.0 dBuV/m

Data :#3

Date: 2025/12/12
Time: 下午 01:45:23

Temperature:27.3 °C
Humidity:47.5 %



Site : 966A Chamber

Condition : FCC Restriction Band 300-1000

EUT : W6M22512-24854

M/N:

Test Mode : TX 918.0375MHz

Note :

Polarization: *Horizontal*

Power : 24 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	332.9000	38.51	peak	-11.31	27.20	46.00	100	124	-18.80	
*	405.7000	41.32	peak	-9.47	31.85	46.00	100	247	-14.15	
	492.5000	39.62	peak	-7.57	32.05	74.00	100	252	-41.95	
	787.2000	44.48	peak	-1.95	42.53	74.00	100	208	-31.47	



Radiated Emission Measurement


Operator: Jeff

File :1_24V
100.0 dBuV/m

Data :#2

Date: 2025/12/12
Time: 下午 01:44:39

Temperature:27.3 °C
Humidity:47.5 %



Site : 966A Chamber

Condition : FCC Restriction Band 30-300

EUT : W6M22512-24854

M/N:

Test Mode : TX 918.0375MHz

Note :

Polarization: **Vertical**

Power : 24 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	54.8400	32.92	peak	-12.73	20.19	74.00	100	359	-53.81	
	149.6100	33.26	peak	-12.46	20.80	74.00	100	1	-53.20	
*	171.7500	36.53	peak	-13.12	23.41	43.50	100	173	-20.09	
	189.5700	40.63	peak	-14.82	25.81	74.00	100	283	-48.19	



Radiated Emission Measurement


Operator: Jeff

File :1_24V
100.0 dBuV/m

Data :#4

Date: 2025/12/12
Time: 下午 01:46:09

Temperature:27.3 °C
Humidity:47.5 %



Site : 966A Chamber

Condition : FCC Restriction Band 300-1000

EUT : W6M22512-24854

M/N:

Test Mode : TX 918.0375MHz

Note :

Polarization: **Vertical**

Power : 24 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	407.8000	42.13	peak	-9.41	32.72	46.00	100	204	-13.28	
	447.7000	41.57	peak	-8.14	33.43	74.00	100	215	-40.57	
	511.4000	41.43	peak	-6.92	34.51	74.00	100	210	-39.49	
	790.7000	41.79	peak	-1.93	39.86	74.00	100	170	-34.14	



Radiated Emission Measurement


Operator: Jeff

File :1_12V
100.0 dBuV/m

Data :#1

Date: 2025/12/12
Time: 下午 01:31:48

Temperature:27.3 °C
Humidity:47.5 %



Site : 966A Chamber

Condition : FCC Restriction Band 30-300

EUT : W6M22512-24854

M/N:

Test Mode : TX 924.48MHz

Note :

Polarization: **Horizontal**

Power : 12 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	52.4100	32.60	peak	-12.72	19.88	74.00	100	173	-54.12	
	143.4000	38.91	peak	-12.71	26.20	74.00	100	100	-47.80	
*	172.8300	36.39	peak	-13.22	23.17	43.50	100	100	-20.33	
	254.1000	37.03	peak	-13.61	23.42	46.00	100	106	-22.58	



Radiated Emission Measurement


Operator: Jeff

File :1_12V
100.0 dBuV/m

Data :#3

Date: 2025/12/12
Time: 下午 01:33:17

Temperature:27.3 °C
Humidity:47.5 %



Site : 966A Chamber

Condition : FCC Restriction Band 300-1000

EUT : W6M22512-24854

M/N:

Test Mode : TX 924.48MHz

Note :

Polarization: **Horizontal**

Power : 12 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	332.9000	37.62	peak	-11.31	26.31	46.00	100	229	-19.69	
	412.7000	42.23	peak	-9.25	32.98	74.00	100	241	-41.02	
	494.6000	40.75	peak	-7.53	33.22	74.00	100	274	-40.78	
	785.8000	44.63	peak	-1.96	42.67	74.00	100	218	-31.33	



Radiated Emission Measurement


Operator: Jeff

File :1_12V
100.0 dBuV/m

Data :#2

Date: 2025/12/12
Time: 下午 01:32:32

Temperature:27.3 °C
Humidity:47.5 %



Site : 966A Chamber

Condition : FCC Restriction Band 30-300

EUT : W6M22512-24854

M/N:

Test Mode : TX 924.48MHz

Note :

Polarization: Vertical

Power : 12 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	48.9000	33.32	peak	-12.82	20.50	74.00	100	22	-53.50	
	147.4500	35.74	peak	-12.55	23.19	74.00	100	22	-50.81	
*	170.6700	38.44	peak	-13.02	25.42	43.50	100	348	-18.08	
	298.1100	33.40	peak	-11.95	21.45	74.00	100	359	-52.55	



Radiated Emission Measurement


Operator: Jeff

File :1_12V
100.0 dBuV/m

Data :#4

Date: 2025/12/12
Time: 下午 01:34:02

Temperature:27.3 °C
Humidity:47.5 %



Site : 966A Chamber
Condition : FCC Restriction Band 300-1000
EUT : W6M22512-24854
M/N:
Test Mode : TX 924.48MHz
Note :

Polarization: **Vertical**
Power : 12 Vd.c.
Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	409.9000	41.52	peak	-9.34	32.18	46.00	100	197	-13.82	
	443.5000	41.15	peak	-8.22	32.93	74.00	100	203	-41.07	
	512.1000	41.71	peak	-6.88	34.83	74.00	100	203	-39.17	
	688.5000	37.07	peak	-3.32	33.75	74.00	100	208	-40.25	
	784.4000	41.51	peak	-1.97	39.54	74.00	100	174	-34.46	



Radiated Emission Measurement


Operator: Jeff

File :1_24V
100.0 dBuV/m

Data :#1

Date: 2025/12/12
Time: 下午 02:00:34

Temperature:27.3 °C
Humidity:47.5 %



Site : 966A Chamber

Condition : FCC Restriction Band 30-300

EUT : W6M22512-24854

M/N:

Test Mode : TX 924.48MHz

Note :

Polarization: **Horizontal**

Power : 24 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	49.9800	33.32	peak	-12.70	20.62	74.00	100	196	-53.38	
	141.2400	35.55	peak	-12.79	22.76	74.00	100	257	-51.24	
	196.0500	40.74	peak	-15.46	25.28	74.00	100	95	-48.72	
*	256.2600	38.39	peak	-13.58	24.81	46.00	100	106	-21.19	



Radiated Emission Measurement


Operator: Jeff

File :1_24V
100.0 dBuV/m

Data :#3

Date: 2025/12/12
Time: 下午 02:02:03

Temperature:27.3 °C
Humidity:47.5 %



Site : 966A Chamber

Condition : FCC Restriction Band 300-1000

EUT : W6M22512-24854

M/N:

Test Mode : TX 924.48MHz

Note :

Polarization: **Horizontal**

Power : 24 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	335.7000	38.18	peak	-11.26	26.92	74.00	100	235	-47.08	
*	407.8000	41.63	peak	-9.41	32.22	46.00	100	229	-13.78	
	483.4000	39.78	peak	-7.72	32.06	74.00	100	280	-41.94	
	796.3000	43.77	peak	-1.89	41.88	74.00	100	207	-32.12	



Radiated Emission Measurement


Operator: Jeff

File :1_24V
100.0 dBuV/m

Data :#2

Date: 2025/12/12
Time: 下午 02:01:18

Temperature:27.3 °C
Humidity:47.5 %



Site : 966A Chamber

Condition : FCC Restriction Band 30-300

EUT : W6M22512-24854

M/N:

Test Mode : TX 924.48MHz

Note :

Polarization: **Vertical**

Power : 24 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	48.9000	33.80	peak	-12.82	20.98	74.00	100	131	-53.02	
	147.4500	33.64	peak	-12.55	21.09	74.00	100	2	-52.91	
*	188.4900	40.05	peak	-14.71	25.34	74.00	100	270	-48.66	
	297.3000	34.06	peak	-11.98	22.08	74.00	100	303	-51.92	



Radiated Emission Measurement


Operator: Jeff

File : 1_24V
100.0 dBuV/m

Data : #4

Date: 2025/12/12
Time: 下午 02:02:48

Temperature: 27.3 °C
Humidity: 47.5 %



Site : 966A Chamber
Condition : FCC Restriction Band 300-1000
EUT : W6M22512-24854
M/N:
Test Mode : TX 924.48MHz
Note :

Polarization: **Vertical**
Power : 24 Vd.c.
Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	409.2000	41.55	peak	-9.36	32.19	46.00	100	125	-13.81	
	447.7000	41.98	peak	-8.14	33.84	74.00	100	214	-40.16	
	511.4000	40.32	peak	-6.92	33.40	74.00	100	208	-40.60	
	771.1000	41.63	peak	-2.05	39.58	74.00	100	191	-34.42	



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Jeff

File : 3

Data : #1


Date: 2025/12/12

Temperature: 27.3 °C

Time: 下午 02:33:20

Humidity: 47.5 %

90.0 dBuV/m



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22512-24854

M/N:

Test Mode : TX 918.0375MHz

Note :

Polarization: **Horizontal**

Power : 24 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	1837.000	60.87	peak	-6.19	54.68	74.00	150	85	-19.32	

*:Maximum data x:Over limit !:over margin



Radiated Emission Measurement

Operator: Jeff

File :3

Data :#5


Date: 2025/12/12

Temperature:27.3 °C

Time: 下午 02:36:09

Humidity:47.5 %

90.0 dBuV/m



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22512-24854

M/N:

Test Mode : TX 918.0375MHz

Note :

Polarization: **Vertical**

Power : 24 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	1837.000	63.19	peak	-6.19	57.00	74.00	150	25	-17.00	



Radiated Emission Measurement

Operator: Jeff

File : 3

Data : #2


Date: 2025/12/12

Temperature: 27.3 °C

Time: 下午 02:34:01

Humidity: 47.5 %

90.0 dBuV/m



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22512-24854

M/N:

Test Mode : TX 918.0375MHz

Note :

Polarization: **Horizontal**

Power : 24 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	2754.000	59.31	peak	-2.11	57.20	74.00	150	17	-16.80	
	2754.000	39.45	AVG	-2.11	37.34	54.00	150	17	-16.66	
	3672.000	58.12	peak	0.72	58.84	74.00	150	142	-15.16	
*	3672.000	38.26	AVG	0.72	38.98	54.00	150	142	-15.02	



Radiated Emission Measurement

Operator: Jeff

File :3

Data :#6


Date: 2025/12/12

Temperature:27.3 °C

Time: 下午 02:36:50

Humidity:47.5 %

90.0 dBuV/m



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22512-24854

M/N:

Test Mode : TX 918.0375MHz

Note :

Polarization: Vertical

Power : 24 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	2758.000	59.89	peak	-2.08	57.81	74.00	150	138	-16.19	
*	2758.000	40.03	AVG	-2.08	37.95	54.00	150	138	-16.05	
	3672.000	55.52	peak	0.72	56.24	74.00	150	62	-17.76	
	3672.000	35.66	AVG	0.72	36.38	54.00	150	62	-17.62	



Radiated Emission Measurement

Operator: Jeff

File :3

Data :#3


Date: 2025/12/12

Temperature:27.3 °C

Time: 下午 02:34:43

Humidity:47.5 %

90.0 dBuV/m



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22512-24854

M/N:

Test Mode : TX 918.0375MHz

Note :

Polarization: *Horizontal*

Power : 24 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4588.000	40.29	peak	4.72	45.01	74.00	150	312	-28.99	
	5508.225	32.60	peak	6.24	38.84	74.00	150	243	-35.16	
	6426.263	32.22	peak	10.55	42.77	74.00	150	112	-31.23	
*	7344.300	33.05	peak	12.29	45.34	74.00	150	85	-28.66	



Radiated Emission Measurement

Operator: Jeff

File : 3

Data : #7


Date: 2025/12/12

Temperature: 27.3 °C

Time: 下午 02:37:32

Humidity: 47.5 %

90.0 dBuV/m



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22512-24854

M/N:

Test Mode : TX 918.0375MHz

Note :

Polarization: Vertical

Power : 24 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4590.188	32.54	peak	4.73	37.27	74.00	150	13	-36.73	
	5508.225	32.09	peak	6.24	38.33	74.00	150	214	-35.67	
	6426.262	32.36	peak	10.55	42.91	74.00	150	91	-31.09	
*	7344.300	32.84	peak	12.29	45.13	74.00	150	135	-28.87	



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Jeff

File : 3


Data : #4

Date: 2025/12/12

Temperature: 27.3 °C

Time: 下午 02:35:24

Humidity: 47.5 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22512-24854

M/N:

Test Mode : TX 918.0375MHz

Note :

Polarization: **Horizontal**

Power : 24 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	8262.338	32.10	peak	12.79	44.89	74.00	150	70	-29.11	
*	9180.375	32.30	peak	13.08	45.38	74.00	150	190	-28.62	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Jeff

File : 3

Data : #8


Date: 2025/12/12

Temperature: 27.3 °C

Time: 下午 02:38:14

Humidity: 47.5 %

90.0 dBuV/m



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22512-24854

M/N:

Test Mode : TX 918.0375MHz

Note :

Polarization: Vertical

Power : 24 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	8262.337	32.20	peak	12.79	44.99	74.00	150	297	-29.01	
*	9180.375	32.42	peak	13.08	45.50	74.00	150	257	-28.50	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Jeff

File : 3

Data : #1


Date: 2025/12/12

Temperature: 27.3 °C

Time: 下午 03:05:05

Humidity: 47.5 %

90.0 dBuV/m



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22512-24854

M/N:

Test Mode : TX 924.48MHz

Note :

Polarization: **Horizontal**

Power : 24 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	1849.000	62.25	peak	-6.08	56.17	74.00	150	45	-17.83	

*:Maximum data x:Over limit !:over margin



Radiated Emission Measurement

Operator: Jeff

File :3


Data :#5

Date: 2025/12/12

Temperature:27.3 °C

Time: 下午 03:07:54

Humidity:47.5 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22512-24854

M/N:

Test Mode : TX 924.48MHz

Note :

Polarization: **Vertical**

Power : 24 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	1849.000	64.67	peak	-6.08	58.59	74.00	150	16	-15.41	



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Jeff

File : 3

Data : #2


Date: 2025/12/12

Temperature: 27.3 °C

Time: 下午 03:05:46

Humidity: 47.5 %

90.0 dBuV/m



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22512-24854

M/N:

Test Mode : TX 924.48MHz

Note :

Polarization: **Horizontal**

Power : 24 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	2774.000	58.46	peak	-1.98	56.48	74.00	150	89	-17.52	
	2774.000	38.60	AVG	-1.98	36.62	54.00	150	89	-17.38	
	3698.000	57.68	peak	0.83	58.51	74.00	150	144	-15.49	
*	3698.000	37.82	AVG	0.83	38.65	54.00	150	144	-15.35	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Jeff

File : 3

Data : #6


Date: 2025/12/12

Temperature: 27.3 °C

Time: 下午 03:08:35

Humidity: 47.5 %

90.0 dBuV/m



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22512-24854

M/N:

Test Mode : TX 924.48MHz

Note :

Polarization: Vertical

Power : 24 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	2774.000	60.42	peak	-1.98	58.44	74.00	150	237	-15.56	
*	2774.000	40.56	AVG	-1.98	38.58	54.00	150	237	-15.42	
	3698.000	53.33	peak	0.83	54.16	74.00	150	96	-19.84	
	3698.000	33.47	AVG	0.83	34.30	54.00	150	96	-19.70	

*:Maximum data x:Over limit !:over margin



Radiated Emission Measurement

Operator: Jeff

File : 3

Data : #3


Date: 2025/12/12

Temperature: 27.3 °C

Time: 下午 03:06:27

Humidity: 47.5 %

90.0 dBuV/m



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22512-24854

M/N:

Test Mode : TX 924.48MHz

Note :

Polarization: **Horizontal**

Power : 24 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4620.000	37.82	peak	4.80	42.62	74.00	150	203	-31.38	
	5546.880	32.25	peak	6.45	38.70	74.00	150	155	-35.30	
	6471.360	32.61	peak	10.68	43.29	74.00	150	107	-30.71	
*	7395.840	32.64	peak	12.44	45.08	74.00	150	84	-28.92	



Radiated Emission Measurement

Operator: Jeff

File : 3

Data : #7


Date: 2025/12/12

Temperature: 27.3 °C

Time: 下午 03:09:17

Humidity: 47.5 %

90.0 dBuV/m



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22512-24854

M/N:

Test Mode : TX 924.48MHz

Note :

Polarization: Vertical

Power : 24 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4622.400	32.51	peak	4.80	37.31	74.00	150	94	-36.69	
	5546.880	32.21	peak	6.45	38.66	74.00	150	135	-35.34	
	6471.360	32.82	peak	10.68	43.50	74.00	150	207	-30.50	
*	7395.840	32.18	peak	12.44	44.62	74.00	150	314	-29.38	



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Jeff

File : 3


Data : #4

Date: 2025/12/12

Temperature: 27.3 °C

Time: 下午 03:07:09

Humidity: 47.5 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22512-24854

M/N:

Test Mode : TX 924.48MHz

Note :

Polarization: **Horizontal**

Power : 24 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	8320.320	32.56	peak	12.96	45.52	74.00	150	72	-28.48	
	9244.800	32.21	peak	13.14	45.35	74.00	150	115	-28.65	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Jeff

File : 3

Data : #8


Date: 2025/12/12

Temperature: 27.3 °C

Time: 下午 03:09:58

Humidity: 47.5 %

90.0 dBuV/m



Site : 966A Chamber

Condition : FCC_part 15 RE-Class C_Above 1GHz_PK

EUT : W6M22512-24854

M/N:

Test Mode : TX 924.48MHz

Note :

Polarization: Vertical

Power : 24 Vd.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	8320.320	32.93	peak	12.96	45.89	74.00	150	359	-28.11	
	9244.800	32.30	peak	13.14	45.44	74.00	150	169	-28.56	

*:Maximum data x:Over limit !:over margin