

TEST REPORT

CERTIFICATE OF CONFORMITY

Standard: 47 CFR FCC Part 15, Subpart C (Section 15.249)
Report No.: RFBBDJ-WTW-P25080234
FCC ID: H4ISD2166
Product: Dongle
Brand: hp
Model No.: TPA-L002D
Received Date: 2025/8/12
Test Date: 2025/8/20 ~ 2025/9/17
Issued Date: 2025/9/30
Applicant: Lite-On Technology Corporation
Address: 16F, 392, Ruey Kuang Road, Neihu, Taipei 11492, Taiwan, R.O.C
Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories
Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan
Test Location: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan
FCC Registration / 198487 / TW2021
Designation Number:

Approved by:

Jeremy Lin

, Date:

2025/9/30

Jeremy Lin / Project Engineer

This test report consists of 32 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The test results in the report only apply to the tested sample. The test results in this report are traceable to the national or international standards.



Prepared by : Jessica Cheng / Senior Specialist

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Table of Contents

Release Control Record	3
1 Certificate.....	4
2 Summary of Test Results	5
2.1 Measurement Uncertainty	5
2.2 Supplementary Information	5
3 General Information	6
3.1 General Description.....	6
3.2 Antenna Description of EUT.....	7
3.3 Channel List.....	7
3.4 Test Mode Applicability and Tested Channel Detail.....	8
3.5 Duty Cycle of Test Signal.....	8
3.6 Test Program Used and Operation Descriptions	9
3.7 Connection Diagram of EUT and Peripheral Devices	9
3.8 Configuration of Peripheral Devices and Cable Connections	10
4 Test Instruments	11
4.1 AC Power Conducted Emissions	11
4.2 Radiated Emissions below 1 GHz.....	12
4.3 Radiated Emissions above 1 GHz.....	13
4.4 20 dB Bandwidth	14
5 Limits of Test Items.....	15
5.1 AC Power Conducted Emissions	15
5.2 Radiated Emissions below 1 GHz.....	15
5.3 Radiated Emissions above 1 GHz.....	16
5.4 20 dB Bandwidth	16
6 Test Arrangements.....	17
6.1 AC Power Conducted Emissions	17
6.1.1 Test Setup	17
6.1.2 Test Procedure.....	17
6.2 Radiated Emissions below 1 GHz.....	18
6.2.1 Test Setup	18
6.2.2 Test Procedure.....	19
6.3 Radiated Emissions above 1 GHz.....	20
6.3.1 Test Setup	20
6.3.2 Test Procedure.....	20
6.4 20 dB Bandwidth	21
6.4.1 Test Setup	21
6.4.2 Test Procedure.....	21
7 Test Results of Test Item	22
7.1 AC Power Conducted Emissions	22
7.2 Radiated Emissions below 1 GHz.....	24
7.3 Radiated Emissions above 1 GHz.....	26
7.4 20 dB Bandwidth	30
8 Pictures of Test Arrangements	31
9 Information of the Testing Laboratories	32

Release Control Record

Issue No.	Description	Date Issued
RFBBDJ-WTW-P25080234	Original release.	2025/9/30

1 Certificate

Product: Dongle

Brand: hp

Test Model: TPA-L002D

Sample Status: Engineering sample

Applicant: Lite-On Technology Corporation

Test Date: 2025/8/20 ~ 2025/9/17

Standard: 47 CFR FCC Part 15, Subpart C (Section 15.249)

**Measurement
procedure:** ANSI C63.10-2020

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (Section 15.249)			
Standard / Clause	Test Item	Result	Remark
15.207	AC Power Conducted Emissions	Pass	Minimum passing margin is -10.70 dB at 0.54500 MHz
15.209 / 15.249(d)	Radiated Emissions below 1 GHz	Pass	Minimum passing margin is -4.1 dB at 72.00 MHz
15.209 / 15.249(a) / 15.249(d) / 15.249(e)	Radiated Emissions above 1 GHz	Pass	Minimum passing margin is -12.6 dB at 2390.00 MHz
15.215 (c)	20 dB Bandwidth	Pass	Meet the requirement of limit.
15.203	Antenna Requirement	Pass	No antenna connector is used.

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Specification	Expanded Uncertainty (k=2) (±)
AC Power Conducted Emissions	9 kHz ~ 30 MHz	2.9 dB
Radiated Emissions below 1 GHz	9 kHz ~ 30 MHz	2.55 dB
	30 MHz ~ 1 GHz	5.77 dB
Radiated Emissions above 1 GHz	1 GHz ~ 6 GHz	4.71 dB
	6 GHz ~ 18 GHz	5.3 dB
	18 GHz ~ 40 GHz	4.98 dB
20 dB Bandwidth	-	960 Hz

The other instruments specified are routine verified to remain within the calibrated levels, no measurement uncertainty is required to be calculated.

2.2 Supplementary Information

There is not any deviation from the test standards for the test method, and no modifications required for compliance.

3 General Information

3.1 General Description

Product	Dongle
Brand	hp
Test Model	TPA-L002D
Status of EUT	Engineering sample
Power Supply Rating	5Vdc form host equipment
Modulation Type	GFSK
Transfer Rate	1Mbps
Operating Frequency	2.405 GHz ~ 2.476 GHz
Number of Channel	12
Field Strength Of Fundamental	70.9 dBuV/m (Average) at 3 meters

Note:

1. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

3.2 Antenna Description of EUT

1. The antenna information is listed as below.

Gain(dBi)	Antenna Type	Connector Type
-3.32	Chip	none

* Due to radiated measurements are made and the antenna gain is already accounted for this device, so provide an antenna datasheet and/or antenna measurement report is not required. The antenna dimensions and pictures (include antenna wire length if have) are stated in EUT photo exhibit.

3.3 Channel List

12 channels are provided to this EUT:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2405	7	2423
2	2447	8	2474
3	2422	9	2408
4	2473	10	2452
5	2407	11	2427
6	2451	12	2476

3.4 Test Mode Applicability and Tested Channel Detail


Pre-Scan:	1. EUT can be used in the following ways: X-axis/ Y-axis/ Z-axis. Pre-scan these ways and find the worst case as a representative test condition.
Worst Case:	1. X-axis/ Y-axis/ Z-axis Worst Condition: Y-axis.

Following channel(s) was (were) selected for the final test as listed below:

Test Item	Tested Channel	Modulation	Data Rate Parameter
AC Power Conducted Emissions	1	GFSK	1Mb/s
Radiated Emissions below 1 GHz	1	GFSK	1Mb/s
Radiated Emissions above 1 GHz	1, 2, 12	GFSK	1Mb/s
20 dB Bandwidth	1, 2, 12	GFSK	1Mb/s

3.5 Duty Cycle of Test Signal


GFSK: Duty cycle = $0.105 \text{ ms} / 1.177 \text{ ms} \times 100\% = 8.9\%$



3.6 Test Program Used and Operation Descriptions

Controlling software (PXI_Link_EMI_Tool_V3_0_3) has been activated to set the EUT under transmission condition continuously at specific channel frequency.

3.7 Connection Diagram of EUT and Peripheral Devices



3.8 Configuration of Peripheral Devices and Cable Connections

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A	NB	Lenovo	IdeaPad 5 15ITL05	N/A	N/A	Provided by Lab
B	NB Adapter	Lenovo	ADLX65CLGU2A	N/A	N/A	Provided by Lab

ID	Cable Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1	USB A to A	1	1	Y	0	Provided by Lab
2	NB Adapter DC cable	1	1.9	N	0	Provided by Lab

4 Test Instruments

The calibration interval of the all test instruments are 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.1 AC Power Conducted Emissions

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
50 ohm terminal resistance LYNICS	0900510	E1-011284	2024/9/16	2025/9/15
		E1-011285	2024/9/25	2025/9/24
DC LISN R&S	ESH3-Z6	100219	2025/7/10	2026/7/9
		844950/018	2025/7/10	2026/7/9
Diode Pulse Limiter Schwarzbeck	VTSD 9561 F-N	01631	2025/5/2	2026/5/1
EMI Test Receiver R&S	ESR3	102412	2024/12/26	2025/12/25
		102414	2024/12/11	2025/12/10
High Pass Filter EMCI	150HPF-ME	114005	2025/5/2	2026/5/1
		114006	2025/5/2	2026/5/1
	150HPF-MF	113009	2025/5/2	2026/5/1
High Voltage Probe Schwarzbeck	TK9420	00982	2024/12/6	2025/12/5
LISN R&S	ENV216	101195	2025/7/18	2026/7/17
		101196	2025/5/19	2026/5/18
		101197	2025/7/4	2026/7/3
LISN Schwarzbeck	NNLK 8121	8121-731	2025/6/10	2026/6/9
		8121-00759	2025/8/12	2026/8/11
		8121-808	2025/4/23	2026/4/22
	NNLK 8129	00624	2024/10/9	2025/10/8
		8129229	2024/10/14	2025/10/13
	NSLK 8128	8128-244	2024/11/11	2025/11/10
Passive Voltage Probe R&S	ESH2-Z3	100073	2025/5/26	2026/5/25
RF Coaxial Cable PEWC	5D-FB	Cable-CO5-01	2025/1/17	2026/1/16
Software BVADT	Cond_V7.4.1.0	N/A	N/A	N/A

Notes:

1. The test was performed in Linkou Conduction 5.
2. Tested Date: 2025/8/20

4.2 Radiated Emissions below 1 GHz

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Bi_Log Antenna Schwarzbeck	VULB 9168	137	2024/10/9	2025/10/8
Coupling / Decoupling Network Schwarzbeck	CDNE-M2	00097	2025/5/28	2026/5/27
	CDNE-M3	00091	2025/3/20	2026/3/19
Loop Antenna TESEQ	HLA 6121	64095	2024/10/17	2025/10/16
MXE EMI Receiver Agilent	N9038A	MY50010158	2024/10/11	2025/10/10
Preamplifier Agilent	8447D	2944A11064	2025/2/14	2026/2/13
RF Coaxial Cable Pacific	8D-FB	Cable-CH6-02	2025/6/24	2026/6/23
Signal Analyzer R&S	FSV40	101544	2025/7/1	2026/6/30
Software BVADT	Radiated_V8.7.08	N/A	N/A	N/A
Tower ADT	AT100	0306	N/A	N/A
Turn Table ADT	TT100	0306	N/A	N/A

Notes:

1. The test was performed in Linkou 966 Chamber 6 (CH 6).
2. Tested Date: 2025/8/21

4.3 Radiated Emissions above 1 GHz

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Boresight antenna tower fixture BV	BAF-02	6	N/A	N/A
High Pass Filter Wainwright	WHK 3.1/18G-10SS	SN 8	2025/5/22	2026/5/21
Horn Antenna EMCO	3115	00028257	2024/11/10	2025/11/9
Horn Antenna ETS-Lindgren	3117-PA	00215857	2024/11/10	2025/11/9
Horn Antenna Schwarzbeck	BBHA 9170	212	2024/10/18	2025/10/17
		BBHA9170190	2024/11/10	2025/11/9
MXE EMI Receiver Agilent	N9038A	MY50010158	2024/10/11	2025/10/10
Notch Filter Micro-Tronics	BRC50703-01	010	2025/5/22	2026/5/21
	BRM17690	005	2025/5/22	2026/5/21
Preamplifier EMCI	EMC0126545	980076	2025/2/14	2026/2/13
	EMC184045B	980175	2024/8/25	2025/8/24
		980235	2025/2/14	2026/2/13
Preamplifier HP	8449B	3008A01201	2025/2/14	2026/2/13
RF Coaxial Cable EMCI	EMC104	190801	2025/7/4	2026/7/3
		190804	2025/7/4	2026/7/3
RF Coaxial Cable EMEC	EM102-KMKM-100	02	2025/7/4	2026/7/3
RF Coaxial Cable HUBER+SUHNER	SF-104	Cable-CH6-01	2025/7/4	2026/7/3
Signal Analyzer R&S	FSV40	101042	2024/9/12	2025/9/11
		101544	2025/7/1	2026/6/30
Software BVADT	Radiated_V7.7.1.1.1	N/A	N/A	N/A
Tower ADT	AT100	0306	N/A	N/A
Turn Table ADT	TT100	0306	N/A	N/A

Notes:

1. The test was performed in Linkou 966 Chamber 6 (CH 6).
2. Tested Date: 2025/8/21

4.4 20 dB Bandwidth

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Fixed Attenuator Woken	00800A1K01A-20	00800A1K01A-20-02	2025/5/23	2026/5/22
PXA Signal Analyzer Keysight	N9030A	MY54490260	2025/7/24	2026/7/23
Signal Analyzer R&S	FSV40	101544	2025/7/1	2026/6/30
Software	ADT_RF Test Software V6.6.5.4	N/A	N/A	N/A

Notes:

1. The test was performed in LK - Oven
2. Tested Date: 2025/9/17

5 Limits of Test Items

5.1 AC Power Conducted Emissions

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Notes:

The lower limit shall apply at the transition frequencies.

The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.

5.2 Radiated Emissions below 1 GHz

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table.

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

Notes:

1. The lower limit shall apply at the transition frequencies.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

5.3 Radiated Emissions above 1 GHz

The field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following.

Fundamental Frequency	Field Strength of Fundamental (millivolts/meter)	Field Strength of Harmonics (microvolts/meter)
2400 ~ 2483.5 MHz	50	500

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits as below table, whichever is the lesser attenuation.

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
Above 960	500	3

Notes:

1. The lower limit shall apply at the transition frequencies.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.


5.4 20 dB Bandwidth

The 20dB bandwidth shall be specified in operating frequency band.

6 Test Arrangements

6.1 AC Power Conducted Emissions

6.1.1 Test Setup



Note: 1. Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

6.1.2 Test Procedure


- Exploratory ac power-line conducted emission measurements: The EUT shall be operated on the mid channel and in the mode with highest output power unless the fundamental operates in the AC power-line emission test range then the EUT shall be operated in the range of typical modes of operation.
- The EUT was placed on a 0.8 meter to the top of table and placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50 uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150 kHz to 30 MHz was searched. Emission levels under (Limit – 20 dB) was not recorded.

Note: The resolution bandwidth and video bandwidth of test receiver is 9 kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15 MHz-30 MHz.


6.2 Radiated Emissions below 1 GHz

6.2.1 Test Setup

For Radiated emission below 30 MHz



For Radiated emission above 30 MHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

6.2.2 Test Procedure

For Radiated emission below 30 MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode, except for the frequency band (9 kHz to 90 kHz and 110 kHz to 490 kHz) set to average detect function and peak detect function.

Notes:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 200 Hz at frequency below 150 kHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9 kHz or 10 kHz at frequency (150 kHz to 30 MHz).
3. All modes of operation were investigated and the worst-case emissions are reported.

For Radiated emission above 30 MHz


- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-peak(QP) detect function, Average(AV) detect function, Peak(PK) detect function and specified bandwidth with maximum hold mode when the test frequencies less than or equal to 1 GHz.

Notes:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection (QP) at frequency below 1 GHz.
2. All modes of operation were investigated and the worst-case emissions are reported.

6.3 Radiated Emissions above 1 GHz

6.3.1 Test Setup



For the actual test configuration, please refer to the attached file (Test Setup Photo).

6.3.2 Test Procedure


- The EUT was placed on the top of a rotating table 1.5 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to peak and average detects function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Notes:

- The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) and Average detection (AV) at frequency above 1 GHz.
- According to ANSI C63.10 section 6.6.4 and 4.1.5.2.2. For fundamental and harmonic signal measurement, according to ANSI C63.10 section 7.5, the average value = peak value + duty cycle correction factor. For duty cycle correction factor values, see the Test Signal Duty Cycle section in this report.
- All modes of operation were investigated and the worst-case emissions are reported.

6.4 20 dB Bandwidth

6.4.1 Test Setup



6.4.2 Test Procedure

- Set resolution bandwidth (RBW) = 1% to 5% of the OBW.
- Set the video bandwidth (VBW) $\geq 3 \times$ RBW, Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 20 dB relative to the maximum level measured in the fundamental emission.

7 Test Results of Test Item


7.1 AC Power Conducted Emissions

RF Mode	GFSK	Channel	CH 1 : 2405 MHz
Frequency Range	150 kHz ~ 30 MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	25 °C, 75% RH
Tested By	Jed Wu		

Phase Of Power : Line (L)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15450	10.05	41.64	23.16	51.69	33.21	65.75	55.75	-14.06	-22.54
2	0.18150	10.05	39.50	20.50	49.55	30.55	64.42	54.42	-14.87	-23.87
3	0.54500	10.07	30.99	25.23	41.06	35.30	56.00	46.00	-14.94	-10.70
4	2.85275	10.16	21.33	10.17	31.49	20.33	56.00	46.00	-24.51	-25.67
5	3.60650	10.17	25.07	13.18	35.24	23.35	56.00	46.00	-20.76	-22.65
6	9.58775	10.36	19.77	13.45	30.13	23.81	60.00	50.00	-29.87	-26.19

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




RF Mode	GFSK	Channel	CH 1 : 2405 MHz
Frequency Range	150 kHz ~ 30 MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	25 °C, 75% RH
Tested By	Jed Wu		

Phase Of Power : Neutral (N)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15225	10.05	38.34	23.16	48.39	33.21	65.88	55.88	-17.49	-22.67
2	0.19500	10.04	37.67	24.89	47.71	34.93	63.82	53.82	-16.11	-18.89
3	0.54216	10.05	31.49	24.75	41.54	34.80	56.00	46.00	-14.46	-11.20
4	2.79200	10.17	23.98	13.90	34.15	24.07	56.00	46.00	-21.85	-21.93
5	4.02050	10.20	23.39	9.80	33.59	20.00	56.00	46.00	-22.41	-26.00
6	10.62950	10.39	17.24	11.72	27.63	22.11	60.00	50.00	-32.37	-27.89

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




7.2 Radiated Emissions below 1 GHz

RF Mode	GFSK	Channel	CH 1 : 2405 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	QP: RB=120 kHz, DET=Quasi-Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	25 °C, 75% RH
Tested By	Jed Wu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	30.60	34.3 QP	40.0	-5.7	1.13 H	41	44.9	-10.6
2	72.00	35.9 QP	40.0	-4.1	1.42 H	161	46.8	-10.9
3	180.20	29.9 QP	43.5	-13.6	1.25 H	215	39.1	-9.2
4	264.00	28.9 QP	46.0	-17.1	1.78 H	307	35.9	-7.0
5	416.80	26.3 QP	46.0	-19.7	1.63 H	161	29.5	-3.2
6	483.30	28.0 QP	46.0	-18.0	1.90 H	304	29.6	-1.6

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




RF Mode	GFSK	Channel	CH 1 : 2405 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	QP: RB=120 kHz, DET=Quasi-Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	25 °C, 75% RH
Tested By	Jed Wu		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	30.58	35.0 QP	40.0	-5.0	1.36 V	51	45.6	-10.6
2	72.00	35.8 QP	40.0	-4.2	1.24 V	205	46.7	-10.9
3	168.13	28.5 QP	43.5	-15.0	1.05 V	21	36.5	-8.0
4	328.47	23.7 QP	46.0	-22.3	1.78 V	58	28.4	-4.7
5	443.85	26.3 QP	46.0	-19.7	1.65 V	94	28.6	-2.3
6	553.61	29.1 QP	46.0	-16.9	1.93 V	202	29.6	-0.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.



7.3 Radiated Emissions above 1 GHz

RF Mode	GFSK	Channel	CH 1 : 2405 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=3 MHz, DET=RMS
Input Power	120 Vac, 60 Hz	Environmental Conditions	25.2 °C, 74.3% RH
Tested By	Jed Wu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	53.5 PK	74.0	-20.5	1.47 H	261	54.2	-0.7
2	2390.00	41.2 AV	54.0	-12.8	1.47 H	261	41.9	-0.7
3	2400.00	54.4 PK	74.0	-19.6	1.47 H	261	55.0	-0.6
4	2400.00	33.4 AV	54.0	-20.6	1.47 H	261	34.0	-0.6
5	*2405.00	89.4 PK	114.0	-24.6	1.47 H	261	90.0	-0.6
6	*2405.00	68.4 AV	94.0	-25.6	1.47 H	261	69.0	-0.6
7	4810.00	52.8 PK	74.0	-21.2	1.87 H	193	45.7	7.1
8	4810.00	31.8 AV	54.0	-22.2	1.87 H	193	24.7	7.1

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	53.8 PK	74.0	-20.2	3.18 V	170	54.5	-0.7
2	2390.00	41.4 AV	54.0	-12.6	3.18 V	170	42.1	-0.7
3	2400.00	54.7 PK	74.0	-19.3	3.18 V	170	55.3	-0.6
4	2400.00	33.7 AV	54.0	-20.3	3.18 V	170	34.3	-0.6
5	*2405.00	91.9 PK	114.0	-22.1	3.18 V	170	92.5	-0.6
6	*2405.00	70.9 AV	94.0	-23.1	3.18 V	170	71.5	-0.6
7	4810.00	50.5 PK	74.0	-23.5	1.05 V	230	43.4	7.1
8	4810.00	29.5 AV	54.0	-24.5	1.05 V	230	22.4	7.1

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle) Where the duty cycle correction factor is calculated from following formula:

$$20 \log(\text{Duty cycle}) = 20 \log(0.105 \text{ ms} / 1.177 \text{ ms}) = -21.0 \text{ dB}$$

RF Mode	GFSK	Channel	CH 2 : 2447 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=3 MHz, DET=RMS
Input Power	120 Vac, 60 Hz	Environmental Conditions	25.2 °C, 74.3% RH
Tested By	Jed Wu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2447.00	89.0 PK	114.0	-25.0	1.72 H	264	89.4	-0.4
2	*2447.00	68.0 AV	94.0	-26.0	1.72 H	264	68.4	-0.4
3	4894.00	52.7 PK	74.0	-21.3	2.12 H	190	45.1	7.6
4	4894.00	31.7 AV	54.0	-22.3	2.12 H	190	24.1	7.6
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2447.00	91.5 PK	114.0	-22.5	3.43 V	173	91.9	-0.4
2	*2447.00	70.5 AV	94.0	-23.5	3.43 V	173	70.9	-0.4
3	4894.00	50.4 PK	74.0	-23.6	1.30 V	227	42.8	7.6
4	4894.00	29.4 AV	54.0	-24.6	1.30 V	227	21.8	7.6

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle) Where the duty cycle correction factor is calculated from following formula:

$$20 \log(\text{Duty cycle}) = 20 \log(0.105 \text{ ms} / 1.177 \text{ ms}) = -21.0 \text{ dB}$$

RF Mode	GFSK	Channel	CH 12 : 2476 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=3 MHz, DET=RMS
Input Power	120 Vac, 60 Hz	Environmental Conditions	25.2 °C, 74.3% RH
Tested By	Jed Wu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2476.00	88.2 PK	114.0	-25.8	1.61 H	265	88.4	-0.2
2	*2476.00	67.2 AV	94.0	-26.8	1.61 H	265	67.4	-0.2
3	2483.50	53.4 PK	74.0	-20.6	1.61 H	265	53.5	-0.1
4	2483.50	32.4 AV	54.0	-21.6	1.61 H	265	32.5	-0.1
5	4952.00	51.7 PK	74.0	-22.3	2.01 H	190	44.2	7.5
6	4952.00	30.7 AV	54.0	-23.3	2.01 H	190	23.2	7.5
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2476.00	90.7 PK	114.0	-23.3	3.32 V	173	90.9	-0.2
2	*2476.00	69.7 AV	94.0	-24.3	3.32 V	173	69.9	-0.2
3	2483.50	53.8 PK	74.0	-20.2	3.32 V	173	53.9	-0.1
4	2483.50	32.8 AV	54.0	-21.2	3.32 V	173	32.9	-0.1
5	4952.00	49.4 PK	74.0	-24.6	1.19 V	226	41.9	7.5
6	4952.00	28.4 AV	54.0	-25.6	1.19 V	226	20.9	7.5


Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.
6. The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle) Where the duty cycle correction factor is calculated from following formula:
 $20 \log(\text{Duty cycle}) = 20 \log(0.105 \text{ ms} / 1.177 \text{ ms}) = -21.0 \text{ dB}$


Plot of Band Edge

Frequency Range	2.31 GHz ~ 2.5 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak
-----------------	--------------------	-------------------------------	----------------------------------

GFSK Channel 1



GFSK Channel 12




7.4 20 dB Bandwidth

Input Power:	120 Vac, 60 Hz	Environmental Conditions:	25°C, 76% RH	Tested By:	Dalen Dai
--------------	----------------	---------------------------	--------------	------------	-----------

Channel	Channel Frequency (MHz)	20 dB Bandwidth (MHz)	Measured Frequencies		Operating Frequency Band (MHz)	Test Result
			FL (MHz)	FH (MHz)		
1	2405	1.12	2404.44	2405.56	2400 ~ 2483.5	Pass
2	2447	1.11	2446.45	2447.56		Pass
12	2476	1.11	2475.45	2476.56		Pass

Notes:

1. FL is the lowest frequency of the 20 dB bandwidth of power envelope.
2. FH is the highest frequency of the 20 dB bandwidth of power envelope.



8 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo)

9 Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@bureauveritas.com

Web Site: <http://ee.bureauveritas.com.tw>

The address and road map of all our labs can be found in our web site also.

--- END ---