

COMPLIANCE ENGINEERING SERVICES, INC.												
Radiated Emissions								01/04/2000				
15.231 (B)								PETE KREBILL				
								C-SITE				
ADVANCED SECURITY												
433.92MHz TX M/N:6703												
All measurements were taken with EUT in X, Y, & Z axis orientations with measurement antenna in horizontal and vertical polarity. X axis with horizontal polarity produced highest emissions. P Readings shown are peak emissions which pass the average limits.												
F(MHz)	READING	AF	CL	AMP	DIST	HPF	TOTAL	LIMIT	MARGIN	NOTE		
	(dBuV)	(dB)	(dB)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)			
	Pk						Pk	Ave	Pk			
434.045	58.03	15.97	3.24	-27.46	0	0	49.78	80.8	-31	X, HOR		
868.05	30.22	21.31	4.82	-27.53	0	0	28.82	60.8	-32	X, HOR		
*1302	50.5	24.7	2.55	-35	-9.5	0	33.25	54	-20.8	HOR		
*1736	45.7	26.2	2.55	-35	-9.5	0	29.95	60.1	-30.2	HOR		
*2170	44.9	28.1	3.23	-35	-9.5	0	31.73	60.1	-28.4	HOR		
*2604	44.9	29.2	3.48	-35	-9.5	0	33.08	60.1	-27	HOR		
*3038	44.3	31	3.74	-35	-9.5	0	34.54	60.1	-25.6	HOR		
*3472	43.2	33	4.25	-35	-9.5	0	35.95	60.1	-24.2	HOR		
*3906	43.1	32	4.76	-35	-9.5	0	35.36	54	-18.6	HOR		
*4340	42.5	32.4	5	-35	-9.5	0	35.4	54	-18.6	HOR		
* Measured noise floor												
ANALYZER SETTINGS												
DIST: Correction to extrapolate reading to 3m specification distance								Res bw		Avg. bw		
1M measurement distance: -9.5dB								PEAK(Pk):		100KHz 100KHz BELOW 1GHz		
AF: Antenna Factor								AVERAGE(Avg):		100KHz 10Hz BELOW 1GHz		
AMP: Pre-amp gain								PEAK(Pk):		1MHz 1MHz ABOVE 1GHz		
CL: Cable loss (17ft)								AVERAGE(Avg):		1MHz 10Hz ABOVE 1GHz		
HPF: High pass filter insertion loss (1.8GHz)												