

**ELECTROMAGNETIC EMISSIONS COMPLIANCE REPORT
CERTIFICATION TO FCC PART 15 REQUIREMENTS**

for

INTENTIONAL RADIATOR

433.92 MHz THREE-BUTTON TRANSMITTER

MODEL NO: 6703

FCC ID NO: H5OT10

REPORT NO: 99T0752-1

ISSUE DATE: JANUARY 04, 2000

Prepared for

**ADVANCE SECURITY INC.
3F, 48 TA AN STREET, HSI CHIH
TAIPEI HSIEN, TAIWAN
R. O. C.**

Prepared by

COMPLIANCE ENGINEERING SERVICES, INC.

d.b.a.

**COMPLIANCE CERTIFICATION SERVICES
1366 BORDEAUX DRIVE
SUNNYVALE, CA 94089, USA
TEL: (408) 752-8166
FAX: (408) 752-8168**

TABLE OF CONTENTS	PAGE
1. VERIFICATION OF COMPLIANCE	1
2. Product Description.....	2
3. Test Facility.....	2
4. Measurement Standards	2
5. Test Methodology	2
6. Measurement Equipment Used.....	2
7. POWERLINE RFI LIMIT	3
8. RADIATED EMISSION LIMITS	3
9. SYSTEM TEST CONFIGURATION	4
10. Test Procedure	5
11. Equipment Modifications	6
12. TEST RESULT	7
12.1 Maximum Modulation Percentage (M%).....	7
12.2 The Emissions Bandwidth.....	7

TEST DATA

- Maximum Modulation Percentage Plot
- Emission Bandwidth Plot
- Radiated Emission Worksheet for Peak Measurement
- Radiated Emission Worksheet for Average Measurement

1. VERIFICATION OF COMPLIANCE

COMPANY NAME : ADVANCE SECURITY INC.
3F, 48 TA AN STREET, HSI CHIH
TAIPEI HSIEN, TAIWAN
R. O. C.

CONTACT PERSON : JESSE CHIU / SALES MANAGER

TELEPHONE NO. : (02) 2643-8192

EUT DESCRIPTION : 433.92 MHz THREE-BUTTON TRANSMITTER

MODEL NAME/NUMBER : 6703

FCC ID : H5OT10

DATE TESTED : JANUARY 04, 2000

REPORT NUMBER : 99T0752-1

TYPE OF EQUIPMENT	SECURITY EQUIPMENT (INTENTIONAL RADIATOR)
EQUIPMENT TYPE	433.92 MHz THREE-BUTTON TRANSMITTER
MEASUREMENT PROCEDURE	ANSI C63.4 / 1992
LIMIT TYPE	CERTIFICATION
FCC RULE	CFR 47, PART 15

The above equipment was tested by Compliance Engineering Services, Inc. for compliance with the requirements set forth in CFR 47, PART 15. This said equipment in the configuration described in this report shows that maximum emission levels emanating from equipment are within the compliance requirements.

MIKE C.I. KUO / VICE PRESIDENT
COMPLIANCE ENGINEERING SERVICES, INC.

2. Product Description

Fundamental Frequency	433.92 MHz
Power Source	12V Battery
Transmitting Time	Periodic $\leq$ 5 seconds
Associated Receiver	M/N: CS82 / FCC ID: H50R29

3. Test Facility

The 3/10/30 meter open area test site and conducted measurement facility used to collect the radiated data is located at 561F Monterey Road, Morgan Hill, California, U.S.A. A detailed description of the test facility was submitted to the Commission on May 27,1994.

4. Measurement Standards

The site is constructed and calibrated in conformance with the requirements of ANSI C63.4/1992.

5. Test Methodology

For an intentional radiator, the spectrum shall be investigated from the lowest radio frequency signal generated in the device, without going below 9 KHz, up to at least the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower. (CFR 47 Section 15.33)

6. Measurement Equipment Used

Manufacturer	Model Number	Description	Cal Due Date
H.P.	8568A	Spectrum Analyzer (100Hz – 1.5GHz)	02/00
H.P.	8566B	Spectrum Analyzer (100Hz – 22GHz)	09/00
EMCO	3146	Antenna (200-1000 MHz)	10/00
H.P.	8447D	Preamplifier (0.1 - 1300 MHz)	09/00
EMCO	3115	Antenna(1 - 18GHZ)	11/00

H.P.	8449B	Preamplifier (1-26.5GHZ)	03/00
------	-------	--------------------------	-------

7. POWERLINE RFI LIMIT

CONNECTED TO AC POWER LINE	SECTION 15.207
CARRIER CURRENT SYSTEM IN THE FREQUENCY RANGE OF 450 KHZ TO 30 MHz	SECTION 15.205 AND SECTION 15.209, 15.221, 15.223, 15.225 OR 15.227, AS APPROPRIATE.
BATTERY POWER	NO REQUIRED.

8. RADIATED EMISSION LIMITS

GENERAL REQUIREMENTS	SECTION 15.209.
RESTRICTED BANDS OF OPERATION	SECTION 15.205
PERIODIC OPERATION IN THE BAND 40.66 -40.70 MHz AND ABOVE 70 MHz.	SECTION 15.231

9. SYSTEM TEST CONFIGURATION



Radiated Open Site Test Set-up

10. Test Procedure

Radiated Emissions, 15.231(4)(b)




Fig. 1

1. The EUT was placed on a wooden table on the outdoor ground plane. The search antenna was placed 3-meters from the EUT.
2. The turntable was slowly rotated to locate the direction of maximum emission at each emission falling in the restricted bands of 15.205. The EUT was moved throughout the XY, XZ, and YZ planes to maximize emissions received by the search antenna.
3. Once maximum direction was determined, the search antenna was raised and lowered in both vertical and horizontal polarizations. The maximum readings so obtained are recorded in the data listed below.




FIG. 2

1. The EUT was placed on a wooden table on the outdoor ground plane. The search antenna was placed 1-meters from the EUT. The EUT antenna was mounted vertically as per normal installation.
2. The turntable was slowly rotated to locate the direction of maximum emission at each emission falling in the restricted bands of 15.205. The EUT was moved throughout the XY, XZ, and YZ planes to maximize emissions received by the search antenna.
3. Once maximum direction was determined, the search antenna was raised and lowered in both vertical and horizontal polarizations. The maximum readings so obtained are recorded in the data listed below.

11. Equipment Modifications

To achieve compliance to FCC Section 15.231 technical limits, the following change(s) were made during compliance testing:

NONE

12. TEST RESULT

Powerline RFI Class B	Eut	Radiated Emission Limits	Eut
SECTION 15.207		SECTION 15.209	x
SECTION 15.205, 15.209, 15.221, 15.223, x 15.225 OR 15.227		SECTION 15.205	
BATTERY POWER	X	SECTION 15.231 (b)	X
		SECTION 15.231 (e)	

12.1 Maximum Modulation Percentage (M%)

CALCULATION:

Average Reading = Peak Reading (dBuV/m)X 20log^(M%)

In order to determine possible Maximum Modulation percentage, alternations are made to the EUT. We measured:

WHERE T (1 period) = 100 mS

t1+t2+t3...+tn = 44.8 mS

Long: 1.7 msec

Short: 0.5 msec

19 Long in 100msec = 32.3

25 Short in 100msec = 12.5

44.8/100 = 0.448 Duty Cycle

$$M\% = ((t1 + t2 + t3 +tn) / T) \times 100\%$$

$$= 44.8\%$$

Maximum Modulation Percentage	44.8 %
-------------------------------	--------

12.2 The Emissions Bandwidth

The bandwidth of the emissions were investigated per 15.231(c)

Center Frequency	Measured	Limits
433.92 MHz	435KHz <	433MHz x 0.25%= 1082.5KHz