

FCC TEST REPORT

for

PART 15, SUBPART B CLASS B

Equipment : COLOR MONITOR

MODEL NO. : FFT995SKHK, FFT9905SKHKKW

TRADE : MITSUBISHI
NAME

F C C I D : H79DB-995

Filing Type : Original Grant

APPLICANT : **DELTA ELECTRONIES, INC.**

No. 3, Tung Yuan Road, Chungli Industrial Zone,
Taoyuan Hsien, Taiwan R.O.C.

- The test result refers exclusively to the test presented test model / sample.
- Without the written authorization of the test lab., the Test Report may not be copied.

SPORTON INTERNATIONAL INC.

6F, No. 106, Hsin Tai Wu Rd., Sec. 1, Hsi Chih, Taipei Hsien, Taiwan, R.O.C.

TABLE OF CONTENT

SECTION TITLE	PAGE
CERTIFICATE OF COMPLIANCE.....	3
1. GENERAL DESCRIPTION OF EQUIPMENT UNDER TEST.....	4
1.1. APPLICANT	4
1.2. MANUFACTURER	4
1.3. BASIC DESCRIPTION OF EQUIPMENT UNDER TEST	4
1.4. FEATURE OF EQUIPMENT UNDER TEST.....	4
2. TEST CONFIGURATION OF EQUIPMENT UNDER TEST	5
2.1. TEST MANNER	5
2.2. DESCRIPTION OF TEST SYSTEM	5
2.3. CONNECTION DIAGRAM OF TEST SYSTEM.....	7
3. TEST SOFTWARE.....	8
4. GENERAL INFORMATION OF TEST.....	9
4.1. TEST FACILITY	9
4.2. STANDARD FOR METHODS OF MEASUREMENT	9
4.3. TEST IN COMPLIANCE WITH.....	9
4.4. FREQUENCY RANGE INVESTIGATED	9
4.5. TEST DISTANCE.....	9
5. TEST OF CONDUCTED POWERLINE.....	10
5.1. MAJOR MEASURING INSTRUMENTS.....	10
5.2. TEST PROCEDURES	11
5.3. TYPICAL TEST SETUP LAYOUT OF CONDUCTED POWERLINE	12
5.4. TEST RESULT OF AC POWERLINE CONDUCTED EMISSION	13
5.4.1 TEST RESULT OF AC POWERLINE CONDUCTED EMISSION.....	14
5.5. PHOTOGRAPHS OF CONDUCTED POWERLINE TEST CONFIGURATION	15
6. TEST OF RADIATED EMISSION.....	17
6.1. MAJOR MEASURING INSTRUMENTS.....	17
6.2. TEST PROCEDURES	18
6.3. TYPICAL TEST SETUP LAYOUT OF RADIATED EMISSION	19
6.4. TEST RESULT OF RADIATED EMISSION	20
6.4.1 TEST RESULT OF RADIATED EMISSION	21
6.5. PHOTOGRAPHS OF RADIATED EMISSION TEST CONFIGURATION	22
7. ANTENNA FACTOR AND CABLE LOSS.....	23
8. LIST OF MEASURING INSTRUMENTS USED.....	24

CERTIFICATE OF COMPLIANCE

for

FCC PART 15, SUBPART B CLASS B

Equipment : COLOR MONITOR

MODEL NO. : FFT9905SKHK/FFT9905SKHKW

TRADE : MTISUBISHI
NAME


F C C I D : H79DB-995

APPLICANT : DELTA ELECTRONIES, INC.

No. 3, Tung Yuan Road, Chungli Industrial Zone,
Taoyuan Hsien, Taiwan R.O.C.

I HEREBY CERTIFY THAT :

The measurement shown in this report were made in accordance with the procedures given in **ANSI C63.4 -1992** and the energy emitted by this equipment was **passed** both radiated and conducted emissions CLASS B limits. Testing was carried out on MAR. 30, 1998 at **SPORTON International Inc.** in LIN KOU.

 Apr 22, 1998
W. L. Huang
General Manager

SPORTON International Inc.

6F, No. 106, Hsin Tai Wu Rd., Sec. 1, Hsi Chih, Taipei Hsien, Taiwan, R.O.C.

1. GENERAL DESCRIPTION OF EQUIPMENT UNDER TEST

1.1. APPLICANT

DELTA ELECTRONICS, INC.

No. 3, Tung Yuan Road, Chungli Industrial Zone,
Taoyuan Hsien, Taiwan R.O.C.

1.2. MANUFACTURER

Same as 1.1

1.3. BASIC DESCRIPTION OF EQUIPMENT UNDER TEST

EQUIPMENT : COLOR MONITOR

MODEL NO. : FFT9905SKHK, FFT9905SKHKW

FCC ID:H79DB-995

TRADE NAME : MITSUBISHI

15-pin DATA CABLE : Shielded

BNC DATA CABLE: Shielded

Serial DATA CABLE: Shielded

Remark: Two ferrite cores are added on the 15-pin video data cable at two end.

A ferrite core is added on the BNC data cable at PC end.

A ferrite core is added on the serial data cable at EUT end.

POWER SUPPLY TYPE : Switching

POWER CORD : Non-shielded

1.4. FEATURE OF EQUIPMENT UNDER TEST

- CRT: 19", 0.25mm, 90 degree
- Resolution: 1280x1024 NI
- Horizontal Sync.: 31.5 to 91KHz
- Vertical Sync.:60 to 85Hz
- Reponse video: 100Mhz nominal
- Signal cable: 15-pin D-type/BNC connector
- Power input voltage frequency: 100 to 240VAC, 60/50Hz

2. TEST CONFIGURATION OF EQUIPMENT UNDER TEST

2.1. TEST MANNER

- a. The EUT has been associated with personal computer and peripherals pursuant to ANSI C63.4-1992 and configuration operated in a manner which tended to maximize its emission characteristics in a typical application.
- b. The DELL keyboard, DELTA monitor, HP printer, PRIMAX mouse and ACEEX modem were connected to the LEO PC.
- c. The 15-PIN cable and BNC cable were tested in order to find the maximum emissions. Since the BNC cable generates the worst case, the mode was used as the final data.
- d. The following display resolution were investigated during the compliance test:
 1. Horizontal frequency (640x480 to 1280x1024, 31.5Khz to 91KHz)
 2. Vertical frequency (60Hz to 85Hz)
- e. According to the above tests, we listed the following display modes as the worst cases:
 1. 1024x768 (non-interlanced 69KHz), refresh rate 75Hz.
 2. 1280x1024 (non-interlanced 91KHz), refresh rate 85Hz.
- f. Frequency range investigated: Conduction 450 KHz to 30 MHz, Radiation 30 MHz to 2000 MHz.

2.2. DESCRIPTION OF TEST SYSTEM

Support Device 1. --- PERSONAL COMPUTER (LEO)

FCC ID	:N/A
Model No.	:P55T2P4
Serial No.	:SP1033
Data Cable	:Shielded, 360 degree via metal backshells
Power Cord	:Non-shielded
Power Supply Type	:Switching

Remark: This support device was tested to comply with FCC standards and authorized under a declaration of conformity.

FCC TEST REPORT

REPORT NO. : F832006

Support Device 2. --- MODEM (ACEEX)

FCC ID : IFAXDM1414
Model No. : DM1414
Serial No. : SP0016
Data Cable : Shielded, 360 degree via metal backshells
Power Supply Type : Linear

Support Device 3. --- PRINTER (HP)

FCC ID : B94C2642X
Model No. : DESKJET 400
Serial No. : SP0003
Data Cable : Shielded, 360 degree via metal backshells
Power Supply Type : Linear

Support Device 4. --- VGA CARD (JOYTECH)

FCC ID : JDF-765PCI-001
Model No. : 988
Serial No. : SP1046
Data Cable : Shielded, 360 degree via metal backshells

Support Device 5. --- KEYBOARD (DELL)

FCC ID : GYUM92SK
Model No. : AT101
Serial No. : SP1011
Data Cable : Shielded, 360 degree via metal backshells

Support Device 6. --- MOUSE (PRIMAX)

FCC ID : EMJMUJQ
Model No. : MUS9J
Serial No. : SP1036
Data Cable : Shielded, 360 degree via metal backshells

The diagram illustrates a computer system with the following components and connections:

- Printer**: Connected to the **PC** via connection 4.
- EUT**: Connected to the **PC** via connection 2.
- PC**: The central component, connected to the **Modem** (1), **KEYBOARD** (3), and **mouse** (5).
- Modem**: Connected to the **PC** via connection 1.
- KEYBOARD**: Connected to the **PC** via connection 3.
- mouse**: Connected to the **PC** via connection 5.

Connections 6 and 2 are also shown, but their specific paths are not clearly defined in the diagram.

1. The I/O cable is connected to the support device 2.
2. The I/O cable is connected to the EUT.
3. The I/O cable is connected to the support device 5.
4. The I/O cable is connected to the support device 3.
5. The I/O cable is connected to the support device 6.
6. The serial cable is connected to the support device 1.

3. TEST SOFTWARE

An executive program, FCC.EXE, which generates a complete line of continuously repeating " H " pattern is used as the test software.

The program was executed as follows :

- a. Turn on the power of all equipment.
- b. The PC reads the test program from the floppy disk drive and runs it.
- c. The PC sends " H " messages to the EUT, and the EUT displays " H " patterns on the screen.
- d. The PC sends " H " messages to the printer, then the printer prints them on the paper.
- e. The PC sends " H " messages to the modem.
- f. The PC sends " H " messages to the internal Hard Disk, then the hard disk reads and writes the message.
- g. Repeat the steps from b to f.

4. GENERAL INFORMATION OF TEST

4.1. TEST FACILITY

This test was carried out by SPORTON INTERNATIONAL INC. in an openarea test site.

Openarea Test Site Location : No. 30-1, Lin 6, Diing-Fwu Tsuen, Lin-Kou-Hsiang,
Taipei Hsien, Taiwan, R.O.C.

TEL : 886-2-2601-1640

FAX : 886-2-2601-1695

4.2. STANDARD FOR METHODS OF MEASUREMENT

ANSI C63.4-1992

4.3 .TEST IN COMPLIANCE WITH

FCC PART 15, SUBPART B CLASS B

4.4. FREQUENCY RANGE INVESTIGATED

- a. Conduction : from 450 KHz to 30 MHz
- b. Radiation : from 30 MHz to 2000 MHz

4.5. TEST DISTANCE

The test distance of radiated emission from antenna to EUT is 3M.

5. TEST OF CONDUCTED POWERLINE

Conducted Emissions were measured from 450 KHz to 30 MHz with a bandwidth of 9 KHz on the 115 VAC power and return leads of the EUT according to the methods defined in ANSI C63.4-1992 Section 3.1. The EUT was placed on a nonmetallic stand in a shielded room 0.8 meters above the ground plane as shown in Figure 5-3. The interface cables and equipment positioning were varied within limits of reasonable applications to determine the position produced maximum conducted emissions.


5.1. MAJOR MEASURING INSTRUMENTS

- Test Receiver HP85462A
 - Attenuation 0 dB
 - Start Frequency 0.45 MHz
 - Stop Frequency 30 MHz
 - Step MHz 0.007 MHz
 - IF Bandwidth 9 KHz

5.2. TEST PROCEDURES

- a. The EUT was placed 0.4 meter from the conducting wall of the shielding room and was kept at least 80 centimeters from any other grounded conducting surface.
- b. Connect EUT to the power mains through a line impedance stabilization network (LISN).
- c. All the support units are connect to the other LISN.
- d. The LISN provides 50 ohm coupling impedance for the measuring instrument.
- e. The FCC states that a 50 ohm , 50 microhenry LISN should be used.
- f. Both sides of AC line were checked for maximum conducted interference.
- g. The frequency range from 450 KHz to 30 MHz was searched.
- h. Set the test-receiver system (receiver HP85462A) to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- i. If the emission level of the EUT in peak mode was 6 dB lower than the limit specified, then testing will be stopped and peak values of EUT will be reported otherwise the emissions which do not have 6 dB margin will be retested on by one using the quasi-peak method and reported.

5.3. TYPICAL TEST SETUP LAYOUT OF CONDUCTED POWERLINE



5.4. TEST RESULT OF AC POWERLINE CONDUCTED EMISSION

- Frequency Range of Test : from 0.45 MHz to 30 MHz
- Temperature : 26 °C
- Relative Humidity :73% RH
- Measuring mode:1024x768 (non-interlaced 69Khz), 85Hz
- All emissions not reported here are more than 10 dB below the prescribed limit.
- Test Date : MAR. 30, 1998

The Conducted Emission test was passed at minimum margin

NEUTRAL 16.07MHz / 36.20dBuV.

Frequency (MHz)	Line / Neutral	Meter Reading		Limits		Margin (dB)
		(dBuV)	(uV)	(dBuV)	(uV)	
16.07	N	36.20	64.57	48.00	251.19	-11.80
18.20	N	32.80	43.65	48.00	251.19	-15.20
21.45	N	34.70	54.33	48.00	251.19	-13.30
10.07	L	33.30	46.24	48.00	251.19	-14.70
14.46	L	29.80	30.90	48.00	251.19	-18.20
20.77	L	32.10	40.27	48.00	251.19	-15.90

Test Engineer :

Jones Jam

5.4.1 TEST RESULT OF AC POWERLINE CONDUCTED EMISSION

- Frequency Range of Test : from 0.45 MHz to 30 MHz
- Temperature : 26 °C
- Relative Humidity : 73% RH
- Measuring mode: 1280x1024 (non-interlaced 91Khz), 85Hz
- All emissions not reported here are more than 10 dB below the prescribed limit.
- Test Date : MAR. 30, 1998

The Conducted Emission test was passed at minimum margin

LINE 21.24MHz / 38.60dBuV.

Frequency (MHz)	Line / Neutral	Meter Reading		Limits		Margin
		(dBuV)	(uV)	(dBuV)	(uV)	(dB)
16.23	N	38.00	79.43	48.00	251.19	-10.00
16.87	N	33.20	45.71	48.00	251.19	-14.80
21.24	N	37.70	76.74	48.00	251.19	-10.30
16.87	L	36.90	69.98	48.00	251.19	-11.10
19.42	L	36.50	66.83	48.00	251.19	-11.50
21.24	L	38.60	85.11	48.00	251.19	-9.40

Test Engineer :

6. TEST OF RADIATED EMISSION

Radiated emissions from 30 MHz to 2000MHz were measured with a bandwidth of 120 KHz according to the methods defines in ANSI C63.4-1992. The EUT was placed on a nonmetallic stand in the open-field site, 0.8 meter above the ground plane, as shown in Figure 6-3. The interface cables and equipment positions were varied within limits of reasonable applications to determine the positions producing maximum radiated emissions.

6.1. MAJOR MEASURING INSTRUMENTS

- RF Preselector
 - Attenuation 0 dB
 - RF Gain 20 dB
 - Signal Input Input 2 (for 20 MHz to 2 GHz)


- Spectrum Analyzer 8568B/8594A
 - Attenuation 0 dB
 - Start Frequency 30 MHz
 - Stop Frequency 2000MHz
 - Resolution Bandwidth 1 MHz
 - Video Bandwidth 1 MHz
 - Signal Input Input 1 (for 9KHz to 2.9 GHz)

- Quasi-Peak Adapter
 - Resolution Bandwidth 120 KHz
 - Frequency Band 30 MHz to 1 GHz
 - Quasi-Peak Detector ON for Quasi-Peak Mode
OFF for Peak Mode

6.2. TEST PROCEDURES

- a. The EUT was placed on a rotatable table top 0.8 meter above ground.
- b. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
- c. The table was rotated 360 degrees to determine the position of the highest radiation.
- d. The antenna is a half wave dipole and its height is varied between one meter and four meters above ground to find the maximum value of the field strength both horizontal polarization and vertical polarization of the antenna are set to make the measurement.
- e. For each suspected emission the EUT was arranged to its worst case and then tune the antenna tower (from 1 M to 4 M) and turn table (from 0 degree to 360 degrees) to find the maximum reading.
- f. Set the test-receiver system (HP 8568B/8594A) to Peak Detect Function and specified bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 6 dB lower than the limit specified, then testing will be stopped and peak values of EUT will be reported otherwise the emissions which do not have 6 dB margin will be repeated one by one using the quasi-peak method and reported.

6.3. TYPICAL TEST SETUP LAYOUT OF RADIATED EMISSION



6.4. TEST RESULT OF RADIATED EMISSION

- Equipment meets the technical specifications of 15.109
- Frequency Range of Test : from 30 MHz to 2000 MHz
- Test Distance : 3 M
- Temperature : 26 °C
- Relative Humidity : 74% RH
- Measuring mode: 1024x768 (non-interlaced 69Khz), 85Hz
- Test Date : MAR. 26, 1998
- Emission level (dBuV/m) = 20 log Emission level (uV/m)
- Sample Calculation at 330.66MHz
Corrected Reading = 18.65+ 3.15+ 10.98= 32.78(dBuV/m)

The Radiated Emission test was passed at minimum margin

Horizontal 36.27 MHz / 36.32dBuV

Antenna Height 4Meter , Turntable Degree 106°.

Frequency	Antenna	Cable	Reading	Limits	Emission	Level	Margin
(MHz)	Polarity	Factor (dB)	Loss (dB)	(dBuV)	(dBuV)	(uV)	(dB)
36.27	H	-0.39	0.85	35.86	40.00	100	36.32 65.46 -3.68
162.00	V	12.24	2.05	21.69	43.50	150	35.98 62.95 -7.52
39.97	V	0.50	0.94	34.20	40.00	100	35.64 60.53 -4.36
53.37	H	2.90	1.07	31.44	40.00	100	35.41 58.95 -4.59
197.01	V	13.89	2.37	18.57	43.50	150	34.83 55.14 -8.67
330.66	V	18.65	3.15	10.98	46.00	200	32.78 43.55 -13.22

Test Engineer :

Jade Day

6.4.1 TEST RESULT OF RADIATED EMISSION

- Equipment meets the technical specifications of 15.109
- Frequency Range of Test : from 30 MHz to 2000 MHz
- Test Distance : 3 M
- Temperature : 26 °C
- Relative Humidity :74% RH
- Measuring mode: 1280x1024 (non-interlaced 91Khz), 85Hz
- Test Date :MAR. 26, 1998
- Emission level (dBuV/m) = 20 log Emission level (uV/m)
- Sample Calculation at 160.53MHz
Corrected Reading = 12.25+ 2.02+ 20.95= 35.22(dBuV/m)


The Radiated Emission test was passed at minimum margin

Vertical 53.94 MHz / 36.59dBuV

Antenna Height 1 Meter , Turntable Degree 316°.

Frequency (MHz)	Polarity	Antenna Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Limits (dBuV)	(uV)	Emission (dBuV)	Level (uV)	Margin (dB)
117.49	V	10.33	1.67	24.72	43.50	150	36.73	68.63	-6.77
53.94	V	2.98	1.09	32.52	40.00	100	36.59	67.53	-3.41
65.91	V	5.22	1.20	30.06	40.00	100	36.48	66.68	-3.52
71.04	V	5.70	1.22	29.36	40.00	100	36.28	65.16	-3.72
132.31	V	10.90	1.83	23.33	43.50	150	36.05	63.46	-7.45
160.53	H	12.25	2.02	20.95	43.50	150	35.22	57.68	-8.28

Test Engineer :



7. ANTENNA FACTOR AND CABLE LOSS

Frequency (Mhz)	Antenna Factor (dB)	Cable Loss (dB)
30	-2.20	0.80
35	-0.70	0.82
40	0.51	0.94
45	1.30	1.00
50	2.39	1.00
55	3.14	1.11
60	4.40	1.20
65	5.14	1.20
70	5.59	1.20
75	6.11	1.30
80	7.10	1.40
85	7.53	1.40
90	8.22	1.40
95	8.80	1.40
100	9.36	1.50
110	10.11	1.60
120	10.41	1.70
130	10.74	1.80
140	11.42	1.91
150	11.91	2.01
160	12.25	2.01
170	12.22	2.21
180	13.02	2.30
190	13.50	2.30
200	14.05	2.40
220	14.31	2.40
240	15.11	2.50
260	17.11	2.61
280	17.50	2.70
300	17.99	3.11
320	18.10	3.10
340	19.13	3.20
360	20.14	3.30
380	21.81	3.40
400	22.29	3.60
450	22.40	3.80
500	22.31	4.10
550	23.42	4.40
600	24.01	4.60
650	25.11	5.00
700	26.00	5.30
750	26.51	5.51
800	27.10	5.70
850	27.51	5.90
900	27.90	6.20
950	30.01	6.30
1000	29.00	6.40

※ Remark: For frequency above 1000 MHz, we used low cable loss BNC cable to test.

8. LIST OF MEASURING INSTRUMENTS USED

INSTRUMENT	Manufacturer	Model No.	Serial No.	Characteristic	Calibration date	Remark
Receiver RF Section	HP	85462A	3325A00108	9 KHz - 6.5 GHz	Oct. 22, 1997	C
RF Section	HP	85460A	3308A00104	9 KHz - 6.5 GHz	Oct. 22, 1997	C
LISN	EMCO	3850/2	1035	50 ohm / 50 uH	Oct. 27, 1997	C
LISN	KYORITSU	KNW-407	8-693-10	50 ohm / 50 uH	Oct. 04, 1997	C
EMI Filter	CORCOM	MRI-2030	N/A	480 VAC / 30 A	N/A	C
EMI Filter	CORCOM	MRI-2030	N/A	480 VAC / 30 A	N/A	C
Spectrum Analyzer (Site 1)	HP	8568B	2732A04100	100Hz - 1500GHz	Jun 17, 1997	R
Quasi-peak Adapter (site 1)	HP	85650A	2811A01116	9KHz -1 GHz	Jun. 17, 1997	R
Amplifier (Site 1)	HP	8447D	2944A08291	0.1 MHz -1.3 GHz	Nov. 12, 1997	R
Bilog Antenna (Site 1)	CHASE	CBL6111	1378	30 MHz -1000 MHz	Aug. 11, 1997	R
Half-wave dipole antenna	EMCO	3121C	9705-1285	28M-1GHZ	May. 19, 1997	R
Turn Table (site 1)	EMCO	1060-1.211	9508-1805	0 ~ 360 degree	N/A	R
Antenna Mast (site 1)	EMCO	1051-1.2	9502-1868	1 m- 4 m	N/A	R

※ The column of Remark indicates that the instruments used for conduction ("C") or radiation ("R") test.