

TEST REPORT

CERTIFICATE OF CONFORMITY

Standard: 47 CFR FCC Part 15, Subpart E (Section 15.407)

Report No.: RFBCUN-WTW-P25070242-3

FCC ID: H8N-EAI2620P

Product: Indoor Wi-Fi 7 Enterprise Access Point

Brand: ASKEY

Model No.: EAI2620P, EAI2620P-FCC (refer to item 3.1 for more details)

Received Date: 2025/7/29

Test Date: 2025/8/12 ~ 2026/1/21

Issued Date: 2026/1/26

Applicant: Askey Computer Corp.

Address: 10F, No.119, JIANKANG RD., ZHONGHE DIST., NEW TAIPEI CITY, TAIWAN

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: (1) No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City 33383, Taiwan
(2) No. 70, Wenming Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)

FCC Registration / (1) 788550 / TW0003

Designation Number: (2) 281270 / TW0032

Approved by: Jeremy Lin, **Date:** 2026/1/26
Jeremy Lin / Project Engineer

This test report consists of 199 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The test results in the report only apply to the tested sample. The test results in this report are traceable to the national or international standards.

Prepared by : Vera Huang / Specialist



This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Table of Contents

Release Control Record	4
1 Certificate.....	5
2 Summary of Test Results	6
2.1 Measurement Uncertainty	6
2.2 Supplementary Information	6
3 General Information	7
3.1 General Description of EUT	7
3.2 Antenna Description of EUT	8
3.3 Channel List.....	9
3.4 Test Mode Applicability and Tested Channel Detail.....	13
3.5 Duty Cycle of Test Signal.....	15
3.6 Test Program Used and Operation Descriptions	18
3.7 Connection Diagram of EUT and Peripheral Devices	18
3.8 Configuration of Peripheral Devices and Cable Connections	18
4 Test Instruments	19
4.1 Maximum RF Output Power	19
4.2 Maximum Power Spectral Density	20
4.3 Emission Bandwidth	20
4.4 In-Band Emission Mask.....	20
4.5 Occupied Bandwidth.....	20
4.6 Contention-based Protocol.....	21
4.7 AC Power Conducted Emissions	21
4.8 Unwanted Emissions below 1 GHz	22
4.9 Unwanted Emissions above 1 GHz.....	23
5 Limits of Test Items.....	24
5.1 Maximum RF Output Power	24
5.2 Maximum Power Spectral Density	24
5.3 Emission Bandwidth	24
5.4 In-Band Emission Mask.....	24
5.5 Occupied Bandwidth.....	24
5.6 Contention-based Protocol.....	25
5.7 AC Power Conducted Emissions	25
5.8 Unwanted Emissions below 1 GHz	25
5.9 Unwanted Emissions above 1 GHz.....	26
6 Test Arrangements.....	27
6.1 Maximum RF Output Power	27
6.1.1 Test Setup	27
6.1.2 Test Procedure	27
6.2 Maximum Power Spectral Density	28
6.2.1 Test Setup	28
6.2.2 Test Procedure	28
6.3 Emission Bandwidth	29
6.3.1 Test Setup	29
6.3.2 Test Procedure	29
6.4 In-Band Emission Mask.....	29
6.4.1 Test Setup	29
6.4.2 Test Procedure	29
6.5 Occupied Bandwidth.....	30
6.5.1 Test Setup	30
6.5.2 Test Procedure	30
6.6 Contention-based Protocol.....	31
6.6.1 Test Setup	31
6.6.2 Test Procedure	31
6.7 AC Power Conducted Emissions	32

6.7.1	Test Setup	32
6.7.2	Test Procedure	32
6.8	Unwanted Emissions below 1 GHz	33
6.8.1	Test Setup	33
6.8.2	Test Procedure	34
6.9	Unwanted Emissions above 1 GHz	35
6.9.1	Test Setup	35
6.9.2	Test Procedure	35
7	Test Results of Test Item	36
7.1	Maximum RF Output Power	36
7.2	Maximum Power Spectral Density	47
7.3	Emission Bandwidth	54
7.4	In-Band Emission Mask	58
7.5	Occupied Bandwidth	97
7.6	Contention-based Protocol	101
7.7	AC Power Conducted Emissions	118
7.8	Unwanted Emissions below 1 GHz	120
7.9	Unwanted Emissions above 1 GHz	122
8	Pictures of Test Arrangements	198
9	Information of the Testing Laboratories	199

Release Control Record

Issue No.	Description	Date Issued
RFBCUN-WTW-P25070242-3	Original Release	2026/1/26

1 Certificate

Product: Indoor Wi-Fi 7 Enterprise Access Point

Brand: ASKEY

Test Model: EAI2620P, EAI2620P-FCC (refer to item 3.1 for more details)

Sample Status: Mass product

Applicant: Askey Computer Corp.

Test Date: 2025/8/12 ~ 2026/1/21

Standard: 47 CFR FCC Part 15, Subpart E (Section 15.407)

Measurement ANSI C63.10-2020

procedure: KDB 987594 D02 U-NII 6 GHz EMC Measurement v03

KDB 789033 D02 General UNII Test Procedure New Rules v02r01

KDB 662911 D01 Multiple Transmitter Output v02r01

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

2 Summary of Test Results

47 CFR FCC Part 15, Subpart E (Section 15.407)			
Clause	Test Item	Result	Remark
15.407(a)(5)	Maximum RF Output Power	Pass	Meet the requirement of limit.
15.407(a)(5)	Maximum Power Spectral Density	Pass	Meet the requirement of limit.
15.407(a)(11)	Emission Bandwidth	Pass	Meet the requirement of limit.
---	Occupied Bandwidth	-	Reference only.
15.407(b)(9)	AC Power Conducted Emissions	Pass	Minimum passing margin is -22.93 dB at 0.17400 MHz
15.407(b)(9)	Unwanted Emissions below 1 GHz	Pass	Minimum passing margin is -5.7 dB at 37.76 MHz
15.407(b)(6) 15.407(b)(10)	Unwanted Emissions above 1 GHz	Pass	Minimum passing margin is -0.3 dB at 7125.00 MHz
15.407(b)(7)	In-Band Emission Mask	Pass	Meet the requirement of limit.
15.407(d)(6)	Contention-based Protocol	Pass	Meet the requirement of limit.
15.203	Antenna Requirement	Pass	Antenna connector is ipex(MHF) not a standard connector.

Notes:

1. Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.
2. Per TCBC notice, FCC allows 99% BW measurements for Wi-Fi 320MHz BW mode instead of Emission Bandwidth.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Parameter	Specification	Uncertainty (±)
Occupied Bandwidth	-	72 Hz
AC Power Conducted Emissions	9 kHz ~ 30 MHz	2.88 dB
Unwanted Emissions below 1 GHz	9 kHz ~ 30 MHz	3 dB
	30 MHz ~ 1 GHz	2.93 dB
Unwanted Emissions above 1 GHz	1 GHz ~ 18 GHz	1.76 dB
	18 GHz ~ 40 GHz	1.77 dB

The other instruments specified are routine verified to remain within the calibrated levels, no measurement uncertainty is required to be calculated.

2.2 Supplementary Information

There is not any deviation from the test standards for the test method, and no modifications required for compliance.

3 General Information

3.1 General Description of EUT

Product	Indoor Wi-Fi 7 Enterprise Access Point
Brand	ASKEY
Test Model	EAI2620P, EAI2620P-FCC
Model Difference	for marketing purpose only
Status of EUT	Mass product
Power Supply Rating	12Vdc from Adapter 56Vdc from POE
Modulation Type	64QAM, 16QAM, QPSK, BPSK for OFDM 1024QAM for OFDMA in 11ax mode 4096QAM for OFDMA in 11be mode
Modulation Technology	OFDM, OFDMA
Transfer Rate	Up to 11528 Mbps
Operating Frequency	5.955 GHz ~ 6.415 GHz 6.425 GHz ~ 6.525 GHz 6.535 GHz ~ 6.865 GHz 6.875 GHz ~ 7.115 GHz
Number of Channel	802.11a, 802.11ax (HE20), 802.11be (EHT20):59 802.11ax (HE40), 802.11be (EHT40):29 802.11ax (HE80), 802.11be (EHT80):14 802.11ax (HE160), 802.11be (EHT160):7 802.11be (EHT320):6
Output Power	5.955 GHz ~ 6.415 GHz: EIRP: 410.204 mW (26.13 dBm) 6.425 GHz ~ 6.525 GHz: EIRP: 447.713 mW (26.51 dBm) 6.535 GHz ~ 6.865 GHz: EIRP: 442.588 mW (26.46 dBm) 6.875 GHz ~ 7.115 GHz: EIRP: 406.443 mW (26.09 dBm)
Equipment Class	6ID: 15E 6 GHz Low-power indoor access point

Note:

1. The EUT uses following accessories.

Item	Brand	Model	Specification
Adapter	Chenzhou Frecom Electronics Co. Ltd	F42L1-120350SPAV	Input : 100-240V ~ 50/60Hz, 1.4A Output : 12.0V, 3.5A, 42.0W Description : 1.5M w/o core
Wall Mount Kit	N/A	N/A	-

2. The EUT uses following support unit.

Item	Brand	Model	Specification
POE	PHIHONG	POE60U-BTA	AC Input : 100-240V ~ 1.5A 50-60Hz DC Output : 56V, 0.535A, 30W

3. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

3.2 Antenna Description of EUT

1. The antenna information is listed as below.

Antenna Type	Connector Type	Frequency (MHz)	Antenna Gain (dBi)			
			Ant. 11 (Chain 0)	Ant. 12 (Chain 1)	Ant. 13 (Chain 2)	Ant. 14 (Chain 3)
PIFA	ipex(MHF)	5925	5.5	5.9	5.7	5.9
		6000	5.5	6.1	5.4	7.1
		6100	4.9	6.4	5.4	6.2
		6200	4.7	5.8	6.3	5.8
		6300	5.4	5.5	6.3	5.9
		6400	5.3	5.9	7.6	6.4
		6500	5.3	6.2	7.4	6.7
		6600	4.5	6.1	6.8	6.7
		6700	5.0	6.2	6.6	6.2
		6800	5.2	6.5	7.6	6.7
		6900	4.9	5.7	7.5	6.8
		7125	4.9	5.8	7.0	6.4

* Detail antenna specification please refer to antenna datasheet and/or antenna measurement report.

2. The EUT incorporates a MIMO function:

6 GHz Band		
Modulation Mode	TX & RX Configuration	
802.11a	4TX	4RX
802.11ax (HE20)	4TX	4RX
802.11ax (HE40)	4TX	4RX
802.11ax (HE80)	4TX	4RX
802.11ax (HE160)	4TX	4RX
802.11be (EHT20)	4TX	4RX
802.11be (EHT40)	4TX	4RX
802.11be (EHT80)	4TX	4RX
802.11be (EHT160)	4TX	4RX
802.11be (EHT320)	4TX	4RX

Note:

1. All of modulation mode support beamforming function except 802.11a modulation mode.
2. The EUT support Beamforming and CDD mode, therefore both modes were investigated and the worst case scenario was identified. The worst case data were presented in test report.
3. The modulation and bandwidth of 802.11ax and 802.11be modes are similar at 20 MHz (40 MHz, 80 MHz, 160 MHz). Therefore, the investigated worst case is the representative mode in test report.
4. The EUT does not use channel puncturing and bandwidth reduction.

3.3 Channel List

U-NII-5:

24 channels are provided for 802.11a, 802.11ax (HE20), 802.11be (EHT20):

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	5955 MHz	5	5975 MHz	9	5995 MHz	13	6015 MHz
17	6035 MHz	21	6055 MHz	25	6075 MHz	29	6095 MHz
33	6115 MHz	37	6135 MHz	41	6155 MHz	45	6175 MHz
49	6195 MHz	53	6215 MHz	57	6235 MHz	61	6255 MHz
65	6275 MHz	69	6295 MHz	73	6315 MHz	77	6335 MHz
81	6355 MHz	85	6375 MHz	89	6395 MHz	93	6415 MHz

12 channels are provided for 802.11ax (HE40), 802.11be (EHT40):

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
3	5965 MHz	11	6005 MHz	19	6045 MHz	27	6085 MHz
35	6125 MHz	43	6165 MHz	51	6205 MHz	59	6245 MHz
67	6285 MHz	75	6325 MHz	83	6365 MHz	91	6405 MHz

6 channels are provided for 802.11ax (HE80), 802.11be (EHT80):

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
7	5985 MHz	23	6065 MHz	39	6145 MHz	55	6225 MHz
71	6305 MHz	87	6385 MHz				

3 channels are provided for 802.11ax (HE160), 802.11be (EHT160):

Channel	Frequency	Channel	Frequency	Channel	Frequency
15	6025 MHz	47	6185 MHz	79	6345 MHz

2 channels are provided for 802.11be (EHT320):

Channel	Frequency	Channel	Frequency
31	6105 MHz	63	6265 MHz

U-NII-6:

5 channels are provided for 802.11a, 802.11ax (HE20), 802.11be (EHT20):

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
97	6435 MHz	101	6455 MHz	105	6475 MHz	109	6495 MHz
113	6515 MHz						

3 channels are provided for 802.11ax (HE40), 802.11be (EHT40):

Channel	Frequency	Channel	Frequency	Channel	Frequency
99	6445 MHz	107	6485 MHz	*115	6525 MHz

1 channel is provided for 802.11ax (HE80), 802.11be (EHT80):

Channel	Frequency
103	6465 MHz

1 channel is provided for 802.11ax (HE160), 802.11be (EHT160):

Channel	Frequency
*111	6505 MHz

1 channel is provided for 802.11be (EHT320):

Channel	Frequency
*95	6425 MHz

U-NII-7:

17 channels are provided for 802.11a, 802.11ax (HE20), 802.11be (EHT20):

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
117	6535 MHz	121	6555 MHz	125	6575 MHz	129	6595 MHz
133	6615 MHz	137	6635 MHz	141	6655 MHz	145	6675 MHz
149	6695 MHz	153	6715 MHz	157	6735 MHz	161	6755 MHz
165	6775 MHz	169	6795 MHz	173	6815 MHz	177	6835 MHz
181	6855 MHz						

8 channels are provided for 802.11ax (HE40), 802.11be (EHT40):

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
123	6565 MHz	131	6605 MHz	139	6645 MHz	147	6685 MHz
155	6725 MHz	163	6765 MHz	171	6805 MHz	179	6845 MHz

5 channels are provided for 802.11ax (HE80), 802.11be (EHT80):

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
*119	6545 MHz	135	6625 MHz	151	6705 MHz	167	6785 MHz
*183	6865 MHz						

2 channels are provided for 802.11ax (HE160), 802.11be (EHT160):

Channel	Frequency	Channel	Frequency
143	6665 MHz	*175	6825 MHz

2 channels are provided for 802.11be (EHT320):

Channel	Frequency	Channel	Frequency
*127	6585 MHz	*159	6745 MHz

U-NII-8:

13 channels are provided for 802.11a, 802.11ax (HE20), 802.11be (EHT20):

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
*185	6875 MHz	189	6895 MHz	193	6915 MHz	197	6935 MHz
201	6955 MHz	205	6975 MHz	209	6995 MHz	213	7015 MHz
217	7035 MHz	221	7055 MHz	225	7075 MHz	229	7095 MHz
233	7115 MHz						

6 channels are provided for 802.11ax (HE40), 802.11be (EHT40):

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
*187	6885 MHz	195	6925 MHz	203	6965 MHz	211	7005 MHz
219	7045 MHz	227	7085 MHz				

2 channels are provided for 802.11ax (HE80), 802.11be (EHT80):

Channel	Frequency	Channel	Frequency
199	6945 MHz	215	7025 MHz

1 channel is provided for 802.11ax (HE160), 802.11be (EHT160):

Channel	Frequency
207	6985 MHz

1 channel is provided for 802.11be (EHT320):

Channel	Frequency
*191	6905 MHz

Note: * mean these are straddle channels.

3.4 Test Mode Applicability and Tested Channel Detail

Pre-Scan:	1. EUT has the following operations / usages: POE / Adapter. Pre-scan these operations / usages and find the worst case as a representative test condition. 2. EUT can be used in the following ways: X-axis / Y-axis / Z-axis. Pre-scan these ways and find the worst case as a representative test condition.
Worst Case:	1. POE / Adapter Worst Condition: Adapter 2. X-axis / Y-axis / Z-axis Worst Condition: X-axis

Following channel(s) was (were) selected for the final test as listed below:

Test Item	Mode	Signal Mode	Tested Channel	Modulation	Data Rate Parameter
Maximum RF Output Power	802.11a	CDD	1, 45, 93, 97, 105, 113, 117, 149, 181, 185, 209, 233	BPSK	6Mb/s
	802.11ax (HE20)	CDD & Beamforming	1, 45, 93, 97, 105, 113, 117, 149, 181, 185, 209, 233	BPSK	MCS0
	802.11ax (HE40)	CDD & Beamforming	3, 43, 91, 99, 107, 115, 123, 155, 179, 187, 211, 227	BPSK	MCS0
	802.11ax (HE80)	CDD & Beamforming	7, 39, 87, 103, 119, 151, 183, 199, 215	BPSK	MCS0
	802.11ax (HE160)	CDD & Beamforming	15, 47, 79, 111, 143, 175, 207	BPSK	MCS0
	802.11be (EHT20)	CDD & Beamforming	1, 45, 93, 97, 105, 113, 117, 149, 181, 185, 209, 233	BPSK	MCS0
	802.11be (EHT40)	CDD & Beamforming	3, 43, 91, 99, 107, 115, 123, 155, 179, 187, 211, 227	BPSK	MCS0
	802.11be (EHT80)	CDD & Beamforming	7, 39, 87, 103, 119, 151, 183, 199, 215	BPSK	MCS0
	802.11be (EHT160)	CDD & Beamforming	15, 47, 79, 111, 143, 175, 207	BPSK	MCS0
	802.11be (EHT320)	CDD & Beamforming	31, 63, 95, 127, 159, 191	BPSK	MCS0
Maximum Power Spectral Density	802.11a	CDD	1, 45, 93, 97, 105, 113, 117, 149, 181, 185, 209, 233	BPSK	6Mb/s
	802.11be (EHT20)	CDD & Beamforming	1, 45, 93, 97, 105, 113, 117, 149, 181, 185, 209, 233	BPSK	MCS0
	802.11be (EHT40)	CDD & Beamforming	3, 43, 91, 99, 107, 115, 123, 155, 179, 187, 211, 227	BPSK	MCS0
	802.11be (EHT80)	CDD & Beamforming	7, 39, 87, 103, 119, 151, 183, 199, 215	BPSK	MCS0
	802.11be (EHT160)	CDD & Beamforming	15, 47, 79, 111, 143, 175, 207	BPSK	MCS0
	802.11be (EHT320)	CDD & Beamforming	31, 63, 95, 127, 159, 191	BPSK	MCS0
Emission Bandwidth	802.11a	CDD	1, 45, 93, 97, 105, 113, 117, 149, 181, 185, 209, 233	BPSK	6Mb/s
	802.11be (EHT20)	CDD	1, 45, 93, 97, 105, 113, 117, 149, 181, 185, 209, 233	BPSK	MCS0
	802.11be (EHT40)	CDD	3, 43, 91, 99, 107, 115, 123, 155, 179, 187, 211, 227	BPSK	MCS0
	802.11be (EHT80)	CDD	7, 39, 87, 103, 119, 151, 183, 199, 215	BPSK	MCS0
	802.11be (EHT160)	CDD	15, 47, 79, 111, 143, 175, 207	BPSK	MCS0
	802.11be (EHT320)	CDD	31, 63, 95, 127, 159, 191	BPSK	MCS0

Test Item	Mode	Signal Mode	Tested Channel	Modulation	Data Rate Parameter
In-Band Emission Mask	802.11a	CDD	1, 45, 93, 97, 105, 113, 117, 149, 181, 185, 209, 233	BPSK	6Mb/s
	802.11be (EHT20)	CDD	1, 45, 93, 97, 105, 113, 117, 149, 181, 185, 209, 233	BPSK	MCS0
	802.11be (EHT40)	CDD	3, 43, 91, 99, 107, 115, 123, 155, 179, 187, 211, 227	BPSK	MCS0
	802.11be (EHT80)	CDD	7, 39, 87, 103, 119, 151, 183, 199, 215	BPSK	MCS0
	802.11be (EHT160)	CDD	15, 47, 79, 111, 143, 175, 207	BPSK	MCS0
	802.11be (EHT320)	CDD	31, 63, 95, 127, 159, 191	BPSK	MCS0
Occupied Bandwidth	802.11a	CDD	1, 45, 93, 97, 105, 113, 117, 149, 181, 185, 209, 233	BPSK	6Mb/s
	802.11be (EHT20)	CDD	1, 45, 93, 97, 105, 113, 117, 149, 181, 185, 209, 233	BPSK	MCS0
	802.11be (EHT40)	CDD	3, 43, 91, 99, 107, 115, 123, 155, 179, 187, 211, 227	BPSK	MCS0
	802.11be (EHT80)	CDD	7, 39, 87, 103, 119, 151, 183, 199, 215	BPSK	MCS0
	802.11be (EHT160)	CDD	15, 47, 79, 111, 143, 175, 207	BPSK	MCS0
	802.11be (EHT320)	CDD	31, 63, 95, 127, 159, 191	BPSK	MCS0
Contention-based Protocol	802.11be (EHT20)	CDD	45, 105, 161, 209	BPSK	MCS0
	802.11be (EHT320)	CDD	31, 95, 159, 191	BPSK	MCS0
AC Power Conducted Emissions	802.11be (EHT320)	CDD	95	BPSK	MCS0
Unwanted Emissions below 1 GHz	802.11be (EHT320)	CDD	95	BPSK	MCS0
Unwanted Emissions above 1 GHz	802.11a	CDD	1, 45, 93, 97, 105, 113, 117, 149, 181, 185, 209, 233	BPSK	6Mb/s
	802.11be (EHT20)	Beamforming	1, 45, 93, 97, 105, 113, 117, 149, 181, 185, 209, 233	BPSK	MCS0
	802.11be (EHT40)	Beamforming	3, 43, 91, 99, 107, 115, 123, 155, 179, 187, 211, 227	BPSK	MCS0
	802.11be (EHT80)	Beamforming	7, 39, 87, 103, 119, 151, 183, 199, 215	BPSK	MCS0
	802.11be (EHT160)	Beamforming	15, 47, 79, 111, 143, 175, 207	BPSK	MCS0
	802.11be (EHT320)	Beamforming	31, 63, 95, 127, 159, 191	BPSK	MCS0

3.5 Duty Cycle of Test Signal

802.11a: Duty cycle = 5.49 ms / 5.55 ms x 100% = 98.9%


802.11be (EHT20): Duty cycle = 5.49 ms / 5.58 ms x 100% = 98.4%

802.11be (EHT40): Duty cycle = 5.475 ms / 5.575 ms x 100% = 98.2%


802.11be (EHT80): Duty cycle = 5.475 ms / 5.575 ms x 100% = 98.2%

802.11be (EHT160): Duty cycle = 5.475 ms / 5.525 ms x 100% = 99.1%

802.11be (EHT320): Duty cycle = 5.465 ms / 5.54 ms x 100% = 98.6%




802.11a




802.11be (EHT20)

Duty Cycle Analysis




802.11be (EHT40)

Duty Cycle Analysis




802.11be (EHT80)

Duty Cycle Analysis




802.11be (EHT160)



3.6 Test Program Used and Operation Descriptions

Controlling software QSPR_Ver 5.0-00202 has been activated to set the EUT under transmission condition continuously at specific channel frequency.

3.7 Connection Diagram of EUT and Peripheral Devices



3.8 Configuration of Peripheral Devices and Cable Connections

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A	Notebook	Lenovo	L470	N/A	N/A	Provided by Lab
B	Load	N/A	N/A	N/A	N/A	Provided by Lab

ID	Cable Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1	RJ-45 Cable	1	1.5	No	0	Provided by Lab
2	DC Cable	1	1.5	No	0	Accessory of EUT
3	RJ-45 Cable	1	10	No	0	Provided by Lab

4 Test Instruments

The calibration interval of the all test instruments are 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.1 Maximum RF Output Power

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Antenna Tower Max-Full	MFA-515BSN	N/A	N/A	N/A
EXA Signal Analyzer Agilent	N9010A	MY52220207	2024/12/30	2025/12/29
Horn Antenna RFSPIN	DRH18-E	210104A18E	2024/11/10	2025/11/9
Horn Antenna Schwarzbeck	BBHA 9170	9170-1049	2024/11/10	2025/11/9
MXE EMI Receiver Keysight	N9038B	MY60180019	2025/1/15	2026/1/14
Preamplifier Agilent	83017A	MY39501357	2025/6/11	2026/6/10
Preamplifier EMCI	EMC184045SE	980788	2025/1/14	2026/1/13
RF Coaxial Cable EMCI	EMC101G-KM-KM-2000	201254	2025/1/14	2026/1/13
	EMC101G-KM-KM-3000	201258	2025/1/14	2026/1/13
	EMC101G-KM-KM-5000	201261	2025/1/14	2026/1/13
	EMC104-SM-SM-1000	210103	2025/1/14	2026/1/13
	EMC104-SM-SM-3000	201241	2025/1/14	2026/1/13
	EMC104-SM-SM-9000	201244	2025/1/14	2026/1/13
Software BV ADT	ADT_Radiated_ V7.6.15.9.5	N/A	N/A	N/A
Turn Table Max-Full	MFT-201SS	N/A	N/A	N/A
Turn Table Controller Max-Full	MF-7802BS	MF780208676	N/A	N/A

Notes:

1. The test was performed in WM - 966 chamber 9.
2. Tested Date: 2025/10/1 ~ 2025/10/23

4.2 Maximum Power Spectral Density

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Fixed Attenuator Woken	00800A1K01A-10	00800A1K01A-10-01	2025/5/23	2026/5/22
Signal & Spectrum Analyzer R&S	FSV3044	101504	2025/6/18	2026/6/17
Software BV	ADT_RF Test Software V7.6.5.4	N/A	N/A	N/A

Notes:

1. The test was performed in Oven room.
2. Tested Date: 2025/10/1 ~ 2025/10/23

4.3 Emission Bandwidth

Refer to section 4.2 to get the tested date and information of the instruments.

4.4 In-Band Emission Mask

Refer to section 4.2 to get the tested date and information of the instruments.

4.5 Occupied Bandwidth

Refer to section 4.2 to get the tested date and information of the instruments.

4.6 Contention-based Protocol

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
MXG Vector Signal Generator Agilent	N5182B	MY53050430	2024/11/29	2025/11/28
MXG Vector Signal Generator Keysight	N5182BU	MY59360189	2024/11/29	2025/11/28
Power Divider Woken	0120A02058001M	DCMD33WIK3	2025/4/27	2026/4/26
		DCMD33WIK7	2025/4/27	2026/4/26
Signal & Spectrum Analyzer R&S	FSW26	102023	2025/11/14	2026/11/13

Notes:

1. The test was performed in Adaptivity room.
2. Tested Date: 2025/11/26

4.7 AC Power Conducted Emissions

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
50 ohm terminal resistance	E1-011279	04	2024/11/28	2025/11/27
	E1-011280	05	2024/11/28	2025/11/27
	E1-011311	09	2024/11/28	2025/11/27
DC LISN Schwarzbeck	NNBM 8126G	8126G-069	2024/11/5	2025/11/4
Diode Pulse Limiter Schwarzbeck	VTSD 9561 F-N	01445	2025/4/27	2026/4/26
EMI Test Receiver R&S	ESCI	100613	2024/11/25	2025/11/24
LISN R&S	ENV216	101826	2025/3/24	2026/3/23
	ESH3-Z5	100311	2025/8/28	2026/8/27
RF Coaxial Cable Woken	5D-FB	Cable-cond1-01	2025/1/5	2026/1/4
Software BVADT	BVADT_Conc_ V7.4.1.0	N/A	N/A	N/A
V-LISN Schwarzbeck	NNBL 8226-2	8226-142	2025/8/27	2026/8/26

Notes:

1. The test was performed in HY - Conduction 1.
2. Tested Date: 2025/9/26

4.8 Unwanted Emissions below 1 GHz

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Antenna Tower Max-Full	MFA-515BSN	N/A	N/A	N/A
Bi_Log Antenna Schwarzbeck	VULB 9168	9168-1214	2025/9/18	2026/9/17
EXA Signal Analyzer Agilent	N9010A	MY52220207	2024/12/30	2025/12/29
Loop Antenna TESEQ	HLA 6121	45745	2025/9/1	2026/8/31
MXE EMI Receiver Keysight	N9038B	MY60180019	2025/1/15	2026/1/14
Preamplifier EMCI	EMC330N	980798	2025/1/14	2026/1/13
RF Coaxial Cable EMCI	EMCCFD400-NM-NM-500	201248	2025/1/14	2026/1/13
	EMCCFD400-NM-NM-3000	201249	2025/1/14	2026/1/13
	EMCCFD400-NM-NM-9000	201251(with PAD)	2025/1/14	2026/1/13
Software BV ADT	ADT_Radiated_ V7.6.15.9.5	N/A	N/A	N/A
Turn Table Max-Full	MFT-201SS	N/A	N/A	N/A
Turn Table Controller Max-Full	MF-7802BS	MF780208676	N/A	N/A

Notes:

1. The test was performed in WM - 966 chamber 9.
2. Tested Date: 2025/9/27

4.9 Unwanted Emissions above 1 GHz

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Antenna Tower Max-Full	MFA-515BSN	N/A	N/A	N/A
EXA Signal Analyzer Agilent	N9010A	MY52220207	2024/12/30	2025/12/29
		MY52220314	2025/12/22	2026/12/21
Horn Antenna RFSPIN	DRH18-E	210104A18E	2024/11/10 2025/11/9	2025/11/9 2026/11/8
Horn Antenna Schwarzbeck	BBHA 9170	9170-1049	2024/11/10 2025/11/9	2025/11/9 2026/11/8
MXE EMI Receiver Keysight	N9038B	MY60180019	2025/1/15 2026/1/14	2026/1/14 2027/1/13
Preamplifier Agilent	83017A	MY39501357	2025/6/11	2026/6/10
Preamplifier EMCI	EMC184045SE	980788	2025/1/14 2026/1/13	2026/1/13 2027/1/12
RF Coaxial Cable EMCI	EMC101G-KM-KM-2000	201254	2025/1/14 2026/1/13	2026/1/13 2027/1/12
	EMC101G-KM-KM-5000	201261	2025/1/14 2026/1/13	2026/1/13 2027/1/12
	EMC104-SM-SM-1000	210103	2025/1/14 2026/1/13	2026/1/13 2027/1/12
	EMC104-SM-SM-3000	201241	2025/1/14 2026/1/13	2026/1/13 2027/1/12
	EMC104-SM-SM-9000	201244	2025/1/14 2026/1/13	2026/1/13 2027/1/12
Software BV ADT	ADT_Radiated_ V7.6.15.9.5	N/A	N/A	N/A
Turn Table Max-Full	MFT-201SS	N/A	N/A	N/A
Turn Table Controller Max-Full	MF-7802BS	MF780208676	N/A	N/A

Notes:

1. The test was performed in WM - 966 chamber 9.
2. Tested Date: 2025/8/12 ~ 2026/1/21

5 Limits of Test Items

5.1 Maximum RF Output Power

Operation Band	Equipment Class	Limit
		Maximum Average Power
U-NII-5 U-NII-6 U-NII-7 U-NII-8	6ID: 15E 6 GHz Low-power indoor access point	EIRP 30 dBm

Per KDB 662911 Method of conducted output power measurement on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$;

Array Gain = 0 dB (i.e., no array gain) for channel widths ≥ 40 MHz for any N_{ANT} ;

Array Gain = $5 \log(N_{ANT}/N_{SS})$ dB or 3 dB, whichever is less for 20-MHz channel widths with $N_{ANT} \geq 5$.

For power measurements on all other devices: Array Gain = $10 \log(N_{ANT}/N_{SS})$ dB.

5.2 Maximum Power Spectral Density

Operation Band	Equipment Class	Limit
		Maximum Power Density
U-NII-5 U-NII-6 U-NII-7 U-NII-8	6ID: 15E 6 GHz Low-power indoor access point	EIRP 5 dBm/MHz

5.3 Emission Bandwidth

The maximum transmitter channel bandwidth for U-NII devices in the 5.925-7.125 GHz band is 320 MHz.

5.4 In-Band Emission Mask

Test Item	Frequencies (MHz)	(X) dBc ^{*1}
Emission Mask	At 1 MHz outside of channel edge	20
	At one channel bandwidth from the channel center ^{*2}	28
	At one- and one-half times the channel bandwidth away from channel center ^{*3}	40
	More than one- and one-half times the channel bandwidth	40

^{*1} : The power spectral density must be suppressed by "x" dB

^{*2} : At frequencies between one megahertz outside an unlicensed device's channel edge and one channel bandwidth from the center of the channel, the limits must be linearly interpolated between 20 dB and 28 dB suppression,

^{*3} : At frequencies between one and one- and one-half times an unlicensed device's channel bandwidth, the limits must be linearly interpolated between 28 dB and 40 dB suppression.

5.5 Occupied Bandwidth

The results are for reference only.

5.6 Contention-based Protocol

Unlicensed indoor low-power devices must detect co-channel radio frequency power that is at least -62 dBm (The threshold is referenced to a 0 dBi antenna gain.) or lower. Additionally, indoor low-power devices must detect co-channel energy with 90% or greater certainty.

5.7 AC Power Conducted Emissions

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Notes:

1. The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.

5.8 Unwanted Emissions below 1 GHz

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table.

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

Notes:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).

5.9 Unwanted Emissions above 1 GHz

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table.

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
Above 960	500	3

Notes:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

Limits of unwanted emission out of the restricted bands

Frequencies (MHz)	EIRP Limit	Equivalent Field Strength at 3 m
5925 MHz > F > 7125 MHz	Peak: -7 (dBm/MHz)	88.2 (dBuV/m)
	Average: -27 (dBm/MHz)	68.2 (dBuV/m)


Note: The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength:

$$E = \frac{1000000 \sqrt{30P}}{3} \quad \mu\text{V/m, where } P \text{ is the eirp (Watts).}$$

6 Test Arrangements

6.1 Maximum RF Output Power

6.1.1 Test Setup



6.1.2 Test Procedure

- The EUT was placed on the top of a rotating table 1.5 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- Perform a field strength measurement and record the worse read value, is the field strength value via a spectrum reading obtained corrected for antenna factor, cable loss and pre-amplifier factor and then mathematically convert the measured field strength level to EIRP level.
- Follow ANSI C63.10 section 12.7.3, $EIRP \text{ Value (dBm)} = \text{Field Strength Value (dBuV / m)} + \text{Correction Factor @ 3 m}$.
- $\text{Correction Factor (dB) @ 3 m} = 20\log(D) - 104.77 = -95.23 \text{ dB}$; where D is the measurement distance @3 m.

Spectrum analyzer setting as below:


Method SA-1

- Set span to encompass the entire emission bandwidth (EBW) of the signal.
- Set RBW = 1 MHz, Set VBW $\geq$ 3 MHz, Detector = RMS
- Sweep points $\geq [2 \times \text{span} / \text{RBW}]$. (This gives bin-to-bin spacing $\leq \text{RBW} / 2$, so that narrowband signals are not lost between frequency bins.)
- Sweep time = auto, trigger set to "free run".
- Trace average at least 100 traces in power averaging mode.
- Record the max value

Note: When measuring power, use compute power by integrating the spectrum across the 26 dB EBW or 99% OBW of the signal using the instrument's band power measurement function, with band limits set equal to the EBW or OBW band edges. If the instrument does not have a band power function, then sum the spectrum levels (in power units) at 1 MHz intervals extending across the 26 dB EBW or 99% OBW of the spectrum.

6.2 Maximum Power Spectral Density

6.2.1 Test Setup



6.2.2 Test Procedure

- The EUT was placed on the top of a rotating table 1.5 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- Perform a field strength measurement and record the worse read value, is the field strength value via a spectrum reading obtained corrected for antenna factor, cable loss and pre-amplifier factor and then mathematically convert the measured field strength level to EIRP level.
- Follow ANSI C63.10 section 12.7.3, $EIRP \text{ Value (dBm)} = \text{Field Strength Value (dBuV/m)} + \text{Correction Factor @ 3 m}$.
- $\text{Correction Factor (dB) @ 3 m} = 20\log(D) - 104.77$; where D is the measurement distance @3 m = -95.23 dB


Spectrum analyzer setting as below:

Method SA-1

- Set span to encompass the entire 99% OBW of the signal.
- Set RBW = 1 MHz, Set VBW $\geq$ 3 MHz, Detector = RMS.
- Sweep points $\geq [2 \times \text{span} / \text{RBW}]$. (This gives bin-to-bin spacing $\leq \text{RBW} / 2$, so that narrowband signals are not lost between frequency bins.)
- Sweep time = auto, trigger set to "free run".
- Trace average at least 100 traces in power averaging mode.
- Record the max value

6.3 Emission Bandwidth

6.3.1 Test Setup




6.3.2 Test Procedure

- Set RBW = shall be in the range of 1% to 5% of the emission bandwidth.
- Set the VBW > RBW.
- Detector = peak.
- Trace mode = max-hold.
- Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the instrument. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is in the range of 1% to 5%.

6.4 In-Band Emission Mask

6.4.1 Test Setup




6.4.2 Test Procedure

- Connect output of the antenna port to a spectrum analyzer and adjust appropriate attenuation.
- Measure the 26 dB EBW using the test procedure 12.5.2 of ANSI C63.10-2020. (This will be used to determine the channel edge.)
- Measure the power spectral density (for emissions mask reference) using the following procedure:
 - Set the span to encompass the entire 26 dB EBW of the signal.
 - Set RBW = same RBW used for 26 dB EBW measurement.
 - Set VBW $\geq 3 \times$ RBW
 - Number of points in sweep $\geq [2 \times \text{span} / \text{RBW}]$.
 - Sweep time = auto.
 - Detector = RMS (i.e., power averaging)
 - Trace average at least 100 traces in power averaging (rms) mode.
 - Use the peak search function on the instrument to find the peak of the spectrum.
- Using the measuring equipment limit line function, develop the emissions mask based on the following requirements. The emissions power spectral density must be reduced below the peak power spectral density (in dB) as follows:
 - Suppressed by 20 dB at 1 MHz outside of the channel edge. (The channel edge is defined as the 26-dB point on either side of the carrier center frequency.)
 - Suppressed by 28 dB at one channel bandwidth from the channel center.
 - Suppressed by 40 dB at one- and one-half times the channel bandwidth from the channel center.
- Adjust the span to encompass the entire mask as necessary and clear trace.
- Trace average at least 100 traces in power averaging (rms) mode.
- Adjust the reference level as necessary so that the crest of the channel touches the top of the emission mask.

6.5 Occupied Bandwidth

6.5.1 Test Setup




6.5.2 Test Procedure

The occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission. The following procedure shall be used for measuring 99% power bandwidth:

- The instrument center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be between 1.5 times and 5.0 times the OBW.
- The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW, and VBW shall be at least three times the RBW, unless otherwise specified by the applicable requirement.
- Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (OBW/RBW)]$ below the reference level.
- Step a) through step c) might require iteration to adjust within the specified range.
- Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max-hold mode (until the trace stabilizes) shall be used.
- Use the 99% power bandwidth function of the instrument and report the measured bandwidth.

6.6 Contention-based Protocol

6.6.1 Test Setup



6.6.2 Test Procedure


- Set the signal analyzer center frequency to the nominal EUT channel center frequency. The span range of the signal analyzer shall be between two times and five times the OBW of the EUT. Connect the output port of the EUT to the signal analyzer 2. Ensure that the attenuator 2 provides enough attenuation to not overload the signal analyzer 2 receiver.
- Monitoring the signal analyzer 2, verify the EUT is operating and transmitting with the parameters (set as following section 4.7.5 EUT operating condition).
- Determine number of times detection threshold test as following table,

If	Number of Tests	Placement of Incumbent Transmission
$BW_{EUT} \leq BW_{Inc}$	Once	Same as EUT transmission
$BW_{Inc} < BW_{EUT} \leq 2x BW_{Inc}$	Once	Contained within BW_{EUT}
$2x BW_{Inc} < BW_{EUT} \leq 4x BW_{Inc}$	Twice. (Incumbent transmission is contained within BW_{EUT})	Closely to the lower edge and upper edge of the EUT Channel
$BW_{EUT} > 4x BW_{Inc}$	Three times	Closely to the lower edge ,in the middle and upper edge of the EUT Channel

- The power measurement of AWGN signal refers to method SA-1 in section 12.4.2.2 of ANSI C63.10-2020.
- Using an AWGN signal source, generate (but do not transmit, i.e., RF OFF) a 10 MHz-wide AWGN signal. Use step c table to determine the center frequency of the 10 MHz AWGN signal relative to the EUT's channel bandwidth and center frequency.
- Set the AWGN signal power to an extremely low level (more than 20 dB below the -62 dBm threshold). Connect the AWGN signal source, via a 3-dB splitter, to the signal analyzer 1 and the EUT.
- Transmit the AWGN signal (RF ON) and verify its characteristics on the signal analyzer 1.
- Monitor the signal analyzer 2 to verify if the AWGN signal has been detected and the EUT has ceased transmission. If the EUT continues to transmit, then incrementally increase the AWGN signal power level until the EUT stops transmitting.
- (Including all losses in the RF paths) Determine and record the AWGN signal power level (at the EUT's antenna port) at which the EUT ceased transmission. Repeat the procedure at least 10 times to verify the EUT can detect an AWGN signal with 90% (or better) level of certainty.
- Refer to step c table to determine number of times the detection threshold testing needs to be repeated. If testing is required more than once, then go back to step d, choose a different center frequency for the AWGN signal and repeat the process.

6.7 AC Power Conducted Emissions

6.7.1 Test Setup



Note: 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

6.7.2 Test Procedure


- Exploratory ac power-line conducted emission measurements: The EUT shall be operated on the mid channel and in the mode with highest output power unless the fundamental operates in the AC power-line emission test range then the EUT shall be operated in the range of typical modes of operation.
- The EUT was placed on a 0.8 meter to the top of table and placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50 uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150 kHz to 30 MHz was searched. Emission levels under (Limit – 20 dB) was not recorded.

Note: The resolution bandwidth and video bandwidth of test receiver is 9 kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15 MHz-30 MHz.


6.8 Unwanted Emissions below 1 GHz

6.8.1 Test Setup

For Radiated emission below 30 MHz



For Radiated emission above 30 MHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

6.8.2 Test Procedure

For Radiated emission below 30 MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode, except for the frequency band (9 kHz to 90 kHz and 110 kHz to 490 kHz) set to average detect function and peak detect function.

Notes:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 200 Hz at frequency below 150 kHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9 kHz or 10 kHz at frequency (150 kHz to 30 MHz).
3. All modes of operation were investigated and the worst-case emissions are reported.

For Radiated emission above 30 MHz


- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-peak(QP) detect function, Average(AV) detect function, Peak(PK) detect function and specified bandwidth with maximum hold mode when the test frequencies less than or equal to 1 GHz.

Notes:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection (QP) at frequency below 1 GHz.
2. All modes of operation were investigated and the worst-case emissions are reported.

6.9 Unwanted Emissions above 1 GHz

6.9.1 Test Setup



For the actual test configuration, please refer to the attached file (Test Setup Photo).

6.9.2 Test Procedure

- The EUT was placed on the top of a rotating table 1.5 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to peak and average detects function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Notes:

- The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) and Average detection (AV) at frequency above 1 GHz.
- For fundamental and harmonic signal measurement, the resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is $\geq 1/T$ (Duty cycle $< 98\%$) or 10 Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1 GHz.
For 802.11be (EHT20) Channel 233: Integration method
 - For average emissions measurements:
 - Set RBW = 100 kHz.
 - Perform band-power integration across the 1 MHz bandwidth in which the band-edge emission level is to be measured.
- All modes of operation were investigated and the worst-case emissions are reported.

7 Test Results of Test Item

7.1 Maximum RF Output Power

Environmental Conditions:	25°C, 60% RH	Tested By:	Match Tsui
---------------------------	--------------	------------	------------

802.11a

Chan.	Chan. Freq. (MHz)	Field Strength (dBuV/m)	Correction Factor (dB)	EIRP (mW)	EIRP (dBm)	EIRP Limit (dBm)	Test Result
1	5955	108.68	-95.23	22.131	13.45	30	Pass
45	6175	109.06	-95.23	24.155	13.83	30	Pass
93	6415	108.53	-95.23	21.38	13.30	30	Pass
97	6435	108.25	-95.23	20.045	13.02	30	Pass
105	6475	108.72	-95.23	22.336	13.49	30	Pass
113	6515	108.49	-95.23	21.184	13.26	30	Pass
117	6535	108.46	-95.23	21.038	13.23	30	Pass
149	6695	108.45	-95.23	20.989	13.22	30	Pass
181	6855	108.38	-95.23	20.654	13.15	30	Pass
185	6875	108.43	-95.23	20.893	13.20	30	Pass
209	6995	108.46	-95.23	21.038	13.23	30	Pass
233	7115	108.58	-95.23	21.627	13.35	30	Pass

802.11ax (HE20)

Chan.	Chan. Freq. (MHz)	Field Strength (dBuV/m)	Correction Factor (dB)	EIRP (mW)	EIRP (dBm)	EIRP Limit (dBm)	Test Result
1	5955	108.54	-95.23	21.429	13.31	30	Pass
45	6175	108.38	-95.23	20.654	13.15	30	Pass
93	6415	108.27	-95.23	20.137	13.04	30	Pass
97	6435	108.20	-95.23	19.815	12.97	30	Pass
105	6475	108.23	-95.23	19.953	13.00	30	Pass
113	6515	107.85	-95.23	18.281	12.62	30	Pass
117	6535	107.90	-95.23	18.493	12.67	30	Pass
149	6695	108.55	-95.23	21.478	13.32	30	Pass
181	6855	107.93	-95.23	18.621	12.70	30	Pass
185	6875	107.91	-95.23	18.535	12.68	30	Pass
209	6995	107.88	-95.23	18.408	12.65	30	Pass
233	7115	106.40	-95.23	13.092	11.17	30	Pass

802.11ax (HE40)

Chan.	Chan. Freq. (MHz)	Field Strength (dBuV/m)	Correction Factor (dB)	EIRP (mW)	EIRP (dBm)	EIRP Limit (dBm)	Test Result
3	5965	111.61	-95.23	43.451	16.38	30	Pass
43	6165	111.20	-95.23	39.537	15.97	30	Pass
91	6405	111.26	-95.23	40.087	16.03	30	Pass
99	6445	111.23	-95.23	39.811	16.00	30	Pass
107	6485	111.32	-95.23	40.644	16.09	30	Pass
115	6525	111.34	-95.23	40.832	16.11	30	Pass
123	6565	111.22	-95.23	39.719	15.99	30	Pass
155	6725	111.54	-95.23	42.756	16.31	30	Pass
179	6845	111.53	-95.23	42.658	16.30	30	Pass
187	6885	111.44	-95.23	41.783	16.21	30	Pass
211	7005	111.52	-95.23	42.56	16.29	30	Pass
227	7085	111.51	-95.23	42.462	16.28	30	Pass

802.11ax (HE80)

Chan.	Chan. Freq. (MHz)	Field Strength (dBuV/m)	Correction Factor (dB)	EIRP (mW)	EIRP (dBm)	EIRP Limit (dBm)	Test Result
7	5985	114.53	-95.23	85.114	19.30	30	Pass
39	6145	114.55	-95.23	85.507	19.32	30	Pass
87	6385	114.58	-95.23	86.099	19.35	30	Pass
103	6465	114.51	-95.23	84.723	19.28	30	Pass
119	6545	114.40	-95.23	82.604	19.17	30	Pass
151	6705	114.39	-95.23	82.414	19.16	30	Pass
183	6865	114.53	-95.23	85.114	19.30	30	Pass
199	6945	114.31	-95.23	80.91	19.08	30	Pass
215	7025	114.43	-95.23	83.176	19.20	30	Pass

802.11ax (HE160)

Chan.	Chan. Freq. (MHz)	Field Strength (dBuV/m)	Correction Factor (dB)	EIRP (mW)	EIRP (dBm)	EIRP Limit (dBm)	Test Result
15	6025	116.34	-95.23	129.122	21.11	30	Pass
47	6185	116.39	-95.23	130.617	21.16	30	Pass
79	6345	116.88	-95.23	146.218	21.65	30	Pass
111	6505	116.89	-95.23	146.555	21.66	30	Pass
143	6665	116.40	-95.23	130.918	21.17	30	Pass
175	6825	116.64	-95.23	138.357	21.41	30	Pass
207	6985	116.45	-95.23	132.434	21.22	30	Pass

802.11be (EHT20)

Chan.	Chan. Freq. (MHz)	Field Strength (dBuV/m)	Correction Factor (dB)	EIRP (mW)	EIRP (dBm)	EIRP Limit (dBm)	Test Result
1	5955	108.59	-95.23	21.677	13.36	30	Pass
45	6175	108.42	-95.23	20.845	13.19	30	Pass
93	6415	108.32	-95.23	20.37	13.09	30	Pass
97	6435	108.24	-95.23	19.999	13.01	30	Pass
105	6475	108.28	-95.23	20.184	13.05	30	Pass
113	6515	107.89	-95.23	18.45	12.66	30	Pass
117	6535	107.93	-95.23	18.621	12.70	30	Pass
149	6695	108.60	-95.23	21.827	13.39	30	Pass
181	6855	107.96	-95.23	18.75	12.73	30	Pass
185	6875	107.94	-95.23	18.664	12.71	30	Pass
209	6995	107.91	-95.23	18.535	12.68	30	Pass
233	7115	106.43	-95.23	13.183	11.20	30	Pass

802.11be (EHT40)

Chan.	Chan. Freq. (MHz)	Field Strength (dBuV/m)	Correction Factor (dB)	EIRP (mW)	EIRP (dBm)	EIRP Limit (dBm)	Test Result
3	5965	111.64	-95.23	43.752	16.41	30	Pass
43	6165	111.24	-95.23	39.902	16.01	30	Pass
91	6405	111.31	-95.23	40.551	16.08	30	Pass
99	6445	111.28	-95.23	40.272	16.05	30	Pass
107	6485	111.36	-95.23	41.02	16.13	30	Pass
115	6525	111.39	-95.23	41.305	16.16	30	Pass
123	6565	111.25	-95.23	39.994	16.02	30	Pass
155	6725	111.58	-95.23	43.152	16.35	30	Pass
179	6845	111.56	-95.23	42.954	16.33	30	Pass
187	6885	111.47	-95.23	42.073	16.24	30	Pass
211	7005	111.55	-95.23	42.855	16.32	30	Pass
227	7085	111.54	-95.23	42.756	16.31	30	Pass

802.11be (EHT80)

Chan.	Chan. Freq. (MHz)	Field Strength (dBuV/m)	Correction Factor (dB)	EIRP (mW)	EIRP (dBm)	EIRP Limit (dBm)	Test Result
7	5985	114.56	-95.23	85.704	19.33	30	Pass
39	6145	114.59	-95.23	86.298	19.36	30	Pass
87	6385	114.63	-95.23	87.096	19.40	30	Pass
103	6465	114.57	-95.23	85.901	19.34	30	Pass
119	6545	114.43	-95.23	83.176	19.20	30	Pass
151	6705	114.44	-95.23	83.368	19.21	30	Pass
183	6865	114.56	-95.23	85.704	19.33	30	Pass
199	6945	114.34	-95.23	81.47	19.11	30	Pass
215	7025	114.47	-95.23	83.946	19.24	30	Pass


802.11be (EHT160)

Chan.	Chan. Freq. (MHz)	Field Strength (dBuV/m)	Correction Factor (dB)	EIRP (mW)	EIRP (dBm)	EIRP Limit (dBm)	Test Result
15	6025	116.37	-95.23	130.017	21.14	30	Pass
47	6185	116.42	-95.23	131.522	21.19	30	Pass
79	6345	116.91	-95.23	147.231	21.68	30	Pass
111	6505	116.93	-95.23	147.911	21.70	30	Pass
143	6665	116.43	-95.23	131.826	21.20	30	Pass
175	6825	116.67	-95.23	139.316	21.44	30	Pass
207	6985	116.48	-95.23	133.352	21.25	30	Pass

802.11be (EHT320)

Chan.	Chan. Freq. (MHz)	Field Strength (dBuV/m)	Correction Factor (dB)	EIRP (mW)	EIRP (dBm)	EIRP Limit (dBm)	Test Result
31	6105	119.14	-95.23	246.037	23.91	30	Pass
63	6265	119.13	-95.23	245.471	23.90	30	Pass
95	6425	119.29	-95.23	254.683	24.06	30	Pass
127	6585	119.26	-95.23	252.93	24.03	30	Pass
159	6745	119.73	-95.23	281.838	24.50	30	Pass
191	6905	119.27	-95.23	253.513	24.04	30	Pass

Spectrum Plot of Maximum Value



802.11ax (HE20) Beamforming

Chan.	Chan. Freq. (MHz)	Field Strength (dBuV/m)	Correction Factor (dB)	EIRP (mW)	EIRP (dBm)	EIRP Limit (dBm)	Test Result
1	5955	110.37	-95.23	32.659	15.14	30	Pass
45	6175	110.21	-95.23	31.477	14.98	30	Pass
93	6415	110.51	-95.23	33.729	15.28	30	Pass
97	6435	110.07	-95.23	30.479	14.84	30	Pass
105	6475	110.24	-95.23	31.696	15.01	30	Pass
113	6515	109.86	-95.23	29.04	14.63	30	Pass
117	6535	109.95	-95.23	29.648	14.72	30	Pass
149	6695	110.22	-95.23	31.55	14.99	30	Pass
181	6855	110.06	-95.23	30.409	14.83	30	Pass
185	6875	110.26	-95.23	31.842	15.03	30	Pass
209	6995	110.29	-95.23	32.063	15.06	30	Pass
233	7115	101.63	-95.23	4.365	6.40	30	Pass

802.11ax (HE40) Beamforming

Chan.	Chan. Freq. (MHz)	Field Strength (dBuV/m)	Correction Factor (dB)	EIRP (mW)	EIRP (dBm)	EIRP Limit (dBm)	Test Result
3	5965	113.54	-95.23	67.764	18.31	30	Pass
43	6165	113.40	-95.23	65.615	18.17	30	Pass
91	6405	113.54	-95.23	67.764	18.31	30	Pass
99	6445	113.82	-95.23	72.277	18.59	30	Pass
107	6485	113.14	-95.23	61.802	17.91	30	Pass
115	6525	113.49	-95.23	66.988	18.26	30	Pass
123	6565	113.25	-95.23	63.387	18.02	30	Pass
155	6725	113.54	-95.23	67.764	18.31	30	Pass
179	6845	113.14	-95.23	61.802	17.91	30	Pass
187	6885	113.29	-95.23	63.973	18.06	30	Pass
211	7005	113.19	-95.23	62.517	17.96	30	Pass
227	7085	113.20	-95.23	62.661	17.97	30	Pass

802.11ax (HE80) Beamforming

Chan.	Chan. Freq. (MHz)	Field Strength (dBuV/m)	Correction Factor (dB)	EIRP (mW)	EIRP (dBm)	EIRP Limit (dBm)	Test Result
7	5985	116.32	-95.23	128.529	21.09	30	Pass
39	6145	116.44	-95.23	132.13	21.21	30	Pass
87	6385	116.44	-95.23	132.13	21.21	30	Pass
103	6465	116.71	-95.23	140.605	21.48	30	Pass
119	6545	116.70	-95.23	140.281	21.47	30	Pass
151	6705	116.60	-95.23	137.088	21.37	30	Pass
183	6865	116.35	-95.23	129.42	21.12	30	Pass
199	6945	116.50	-95.23	133.968	21.27	30	Pass
215	7025	116.67	-95.23	139.316	21.44	30	Pass

802.11ax (HE160) Beamforming

Chan.	Chan. Freq. (MHz)	Field Strength (dBuV/m)	Correction Factor (dB)	EIRP (mW)	EIRP (dBm)	EIRP Limit (dBm)	Test Result
15	6025	118.56	-95.23	215.278	23.33	30	Pass
47	6185	118.59	-95.23	216.77	23.36	30	Pass
79	6345	118.67	-95.23	220.8	23.44	30	Pass
111	6505	118.75	-95.23	224.905	23.52	30	Pass
143	6665	118.30	-95.23	202.768	23.07	30	Pass
175	6825	118.72	-95.23	223.357	23.49	30	Pass
207	6985	118.42	-95.23	208.449	23.19	30	Pass

802.11be (EHT20) Beamforming

Chan.	Chan. Freq. (MHz)	Field Strength (dBuV/m)	Correction Factor (dB)	EIRP (mW)	EIRP (dBm)	EIRP Limit (dBm)	Test Result
1	5955	110.43	-95.23	33.113	15.20	30	Pass
45	6175	110.26	-95.23	31.842	15.03	30	Pass
93	6415	110.57	-95.23	34.198	15.34	30	Pass
97	6435	110.12	-95.23	30.832	14.89	30	Pass
105	6475	110.26	-95.23	31.842	15.03	30	Pass
113	6515	109.89	-95.23	29.242	14.66	30	Pass
117	6535	109.97	-95.23	29.785	14.74	30	Pass
149	6695	110.24	-95.23	31.696	15.01	30	Pass
181	6855	110.12	-95.23	30.832	14.89	30	Pass
185	6875	110.28	-95.23	31.989	15.05	30	Pass
209	6995	110.34	-95.23	32.434	15.11	30	Pass
233	7115	101.65	-95.23	4.385	6.42	30	Pass

802.11be (EHT40) Beamforming

Chan.	Chan. Freq. (MHz)	Field Strength (dBuV/m)	Correction Factor (dB)	EIRP (mW)	EIRP (dBm)	EIRP Limit (dBm)	Test Result
3	5965	113.57	-95.23	68.234	18.34	30	Pass
43	6165	113.42	-95.23	65.917	18.19	30	Pass
91	6405	113.56	-95.23	68.077	18.33	30	Pass
99	6445	113.85	-95.23	72.778	18.62	30	Pass
107	6485	113.16	-95.23	62.087	17.93	30	Pass
115	6525	113.51	-95.23	67.298	18.28	30	Pass
123	6565	113.31	-95.23	64.269	18.08	30	Pass
155	6725	113.59	-95.23	68.549	18.36	30	Pass
179	6845	113.19	-95.23	62.517	17.96	30	Pass
187	6885	113.34	-95.23	64.714	18.11	30	Pass
211	7005	113.22	-95.23	62.951	17.99	30	Pass
227	7085	113.22	-95.23	62.951	17.99	30	Pass

802.11be (EHT80) Beamforming

Chan.	Chan. Freq. (MHz)	Field Strength (dBuV/m)	Correction Factor (dB)	EIRP (mW)	EIRP (dBm)	EIRP Limit (dBm)	Test Result
7	5985	116.34	-95.23	129.122	21.11	30	Pass
39	6145	116.47	-95.23	133.045	21.24	30	Pass
87	6385	116.46	-95.23	132.739	21.23	30	Pass
103	6465	116.76	-95.23	142.233	21.53	30	Pass
119	6545	116.73	-95.23	141.254	21.50	30	Pass
151	6705	116.65	-95.23	138.676	21.42	30	Pass
183	6865	116.40	-95.23	130.918	21.17	30	Pass
199	6945	116.52	-95.23	134.586	21.29	30	Pass
215	7025	116.73	-95.23	141.254	21.50	30	Pass


802.11be (EHT160) Beamforming

Chan.	Chan. Freq. (MHz)	Field Strength (dBuV/m)	Correction Factor (dB)	EIRP (mW)	EIRP (dBm)	EIRP Limit (dBm)	Test Result
15	6025	118.58	-95.23	216.272	23.35	30	Pass
47	6185	118.62	-95.23	218.273	23.39	30	Pass
79	6345	118.69	-95.23	221.82	23.46	30	Pass
111	6505	118.77	-95.23	227.51	23.57	30	Pass
143	6665	118.32	-95.23	203.704	23.09	30	Pass
175	6825	118.78	-95.23	226.464	23.55	30	Pass
207	6985	118.48	-95.23	211.349	23.25	30	Pass

802.11be (EHT320) Beamforming


Chan.	Chan. Freq. (MHz)	Field Strength (dBuV/m)	Correction Factor (dB)	EIRP (mW)	EIRP (dBm)	EIRP Limit (dBm)	Test Result
31	6105	121.27	-95.23	401.791	26.04	30	Pass
63	6265	121.36	-95.23	410.204	26.13	30	Pass
95	6425	121.74	-95.23	447.713	26.51	30	Pass
127	6585	121.31	-95.23	405.509	26.08	30	Pass
159	6745	121.69	-95.23	442.588	26.46	30	Pass
191	6905	121.32	-95.23	406.443	26.09	30	Pass

Spectrum Plot of Maximum Value




802.11be (EHT20) Beamforming : CH 93

802.11be (EHT40) Beamforming : CH 99



802.11be (EHT80) Beamforming : CH 103

802.11be (EHT160) Beamforming : CH 175



802.11be (EHT320) Beamforming : CH 95

7.2 Maximum Power Spectral Density

Environmental Conditions:	25°C, 60% RH	Tested By:	Match Tsui
---------------------------	--------------	------------	------------

802.11a

Chan.	Chan. Freq. (MHz)	Field Strength (dBuV/m)	Correction Factor (dB)	EIRP PSD (dBm/MHz)	EIRP PSD Limit (dBm/MHz)	Test Result
1	5955	100.07	-95.23	4.84	5	Pass
45	6175	100.18	-95.23	4.95	5	Pass
93	6415	100.13	-95.23	4.90	5	Pass
97	6435	100.15	-95.23	4.92	5	Pass
105	6475	100.08	-95.23	4.85	5	Pass
113	6515	100.03	-95.23	4.80	5	Pass
117	6535	100.04	-95.23	4.81	5	Pass
149	6695	100.16	-95.23	4.93	5	Pass
181	6855	100.08	-95.23	4.85	5	Pass
185	6875	100.13	-95.23	4.90	5	Pass
209	6995	100.04	-95.23	4.81	5	Pass
233	7115	100.09	-95.23	4.86	5	Pass

802.11be (EHT20)

Chan.	Chan. Freq. (MHz)	Field Strength (dBuV/m)	Correction Factor (dB)	EIRP PSD (dBm/MHz)	EIRP PSD Limit (dBm/MHz)	Test Result
1	5955	100.11	-95.23	4.88	5	Pass
45	6175	100.08	-95.23	4.85	5	Pass
93	6415	100.06	-95.23	4.83	5	Pass
97	6435	100.03	-95.23	4.80	5	Pass
105	6475	100.08	-95.23	4.85	5	Pass
113	6515	100.07	-95.23	4.84	5	Pass
117	6535	100.05	-95.23	4.82	5	Pass
149	6695	100.15	-95.23	4.92	5	Pass
181	6855	100.04	-95.23	4.81	5	Pass
185	6875	100.03	-95.23	4.80	5	Pass
209	6995	100.09	-95.23	4.86	5	Pass
233	7115	98.33	-95.23	3.10	5	Pass

802.11be (EHT40)

Chan.	Chan. Freq. (MHz)	Field Strength (dBuV/m)	Correction Factor (dB)	EIRP PSD (dBm/MHz)	EIRP PSD Limit (dBm/MHz)	Test Result
3	5965	100.18	-95.23	4.95	5	Pass
43	6165	100.04	-95.23	4.81	5	Pass
91	6405	100.03	-95.23	4.80	5	Pass
99	6445	100.08	-95.23	4.85	5	Pass
107	6485	100.09	-95.23	4.86	5	Pass
115	6525	100.11	-95.23	4.88	5	Pass
123	6565	100.14	-95.23	4.91	5	Pass
155	6725	100.13	-95.23	4.90	5	Pass
179	6845	100.09	-95.23	4.86	5	Pass
187	6885	100.07	-95.23	4.84	5	Pass
211	7005	100.12	-95.23	4.89	5	Pass
227	7085	100.07	-95.23	4.84	5	Pass

802.11be (EHT80)

Chan.	Chan. Freq. (MHz)	Field Strength (dBuV/m)	Correction Factor (dB)	EIRP PSD (dBm/MHz)	EIRP PSD Limit (dBm/MHz)	Test Result
7	5985	100.03	-95.23	4.80	5	Pass
39	6145	100.11	-95.23	4.88	5	Pass
87	6385	100.15	-95.23	4.92	5	Pass
103	6465	100.08	-95.23	4.85	5	Pass
119	6545	100.04	-95.23	4.81	5	Pass
151	6705	100.05	-95.23	4.82	5	Pass
183	6865	100.07	-95.23	4.84	5	Pass
199	6945	100.04	-95.23	4.81	5	Pass
215	7025	100.06	-95.23	4.83	5	Pass


802.11be (EHT160)

Chan.	Chan. Freq. (MHz)	Field Strength (dBuV/m)	Correction Factor (dB)	EIRP PSD (dBm/MHz)	EIRP PSD Limit (dBm/MHz)	Test Result
15	6025	100.10	-95.23	4.87	5	Pass
47	6185	100.04	-95.23	4.81	5	Pass
79	6345	100.07	-95.23	4.84	5	Pass
111	6505	100.15	-95.23	4.92	5	Pass
143	6665	100.05	-95.23	4.82	5	Pass
175	6825	100.02	-95.23	4.79	5	Pass
207	6985	100.03	-95.23	4.80	5	Pass

802.11be (EHT320)

Chan.	Chan. Freq. (MHz)	Field Strength (dBuV/m)	Correction Factor (dB)	EIRP PSD (dBm/MHz)	EIRP PSD Limit (dBm/MHz)	Test Result
31	6105	100.01	-95.23	4.78	5	Pass
63	6265	100.08	-95.23	4.85	5	Pass
95	6425	100.06	-95.23	4.83	5	Pass
127	6585	100.16	-95.23	4.93	5	Pass
159	6745	100.18	-95.23	4.95	5	Pass
191	6905	100.11	-95.23	4.88	5	Pass

Spectrum Plot of Maximum Value



802.11be (EHT20) Beamforming

Chan.	Chan. Freq. (MHz)	Field Strength (dBuV/m)	Correction Factor (dB)	EIRP PSD (dBm/MHz)	EIRP PSD Limit (dBm/MHz)	Test Result
1	5955	100.07	-95.23	4.84	5	Pass
45	6175	100.04	-95.23	4.81	5	Pass
93	6415	100.14	-95.23	4.91	5	Pass
97	6435	100.02	-95.23	4.79	5	Pass
105	6475	100.05	-95.23	4.82	5	Pass
113	6515	100.01	-95.23	4.78	5	Pass
117	6535	100.05	-95.23	4.82	5	Pass
149	6695	100.12	-95.23	4.89	5	Pass
181	6855	100.04	-95.23	4.81	5	Pass
185	6875	100.03	-95.23	4.80	5	Pass
209	6995	100.08	-95.23	4.85	5	Pass
233	7115	91.95	-95.23	-3.28	5	Pass

802.11be (EHT40) Beamforming

Chan.	Chan. Freq. (MHz)	Field Strength (dBuV/m)	Correction Factor (dB)	EIRP PSD (dBm/MHz)	EIRP PSD Limit (dBm/MHz)	Test Result
3	5965	100.07	-95.23	4.84	5	Pass
43	6165	100.06	-95.23	4.83	5	Pass
91	6405	100.12	-95.23	4.89	5	Pass
99	6445	100.16	-95.23	4.93	5	Pass
107	6485	100.03	-95.23	4.80	5	Pass
115	6525	100.11	-95.23	4.88	5	Pass
123	6565	100.07	-95.23	4.84	5	Pass
155	6725	100.10	-95.23	4.87	5	Pass
179	6845	100.01	-95.23	4.78	5	Pass
187	6885	100.02	-95.23	4.79	5	Pass
211	7005	100.01	-95.23	4.78	5	Pass
227	7085	100.02	-95.23	4.79	5	Pass

802.11be (EHT80) Beamforming

Chan.	Chan. Freq. (MHz)	Field Strength (dBuV/m)	Correction Factor (dB)	EIRP PSD (dBm/MHz)	EIRP PSD Limit (dBm/MHz)	Test Result
7	5985	100.06	-95.23	4.83	5	Pass
39	6145	100.10	-95.23	4.87	5	Pass
87	6385	100.08	-95.23	4.85	5	Pass
103	6465	100.14	-95.23	4.91	5	Pass
119	6545	100.09	-95.23	4.86	5	Pass
151	6705	100.06	-95.23	4.83	5	Pass
183	6865	100.05	-95.23	4.82	5	Pass
199	6945	100.07	-95.23	4.84	5	Pass
215	7025	100.11	-95.23	4.88	5	Pass


802.11be (EHT160) Beamforming

Chan.	Chan. Freq. (MHz)	Field Strength (dBuV/m)	Correction Factor (dB)	EIRP PSD (dBm/MHz)	EIRP PSD Limit (dBm/MHz)	Test Result
15	6025	100.02	-95.23	4.79	5	Pass
47	6185	100.10	-95.23	4.87	5	Pass
79	6345	100.17	-95.23	4.94	5	Pass
111	6505	100.12	-95.23	4.89	5	Pass
143	6665	100.14	-95.23	4.91	5	Pass
175	6825	100.19	-95.23	4.96	5	Pass
207	6985	100.17	-95.23	4.94	5	Pass


802.11be (EHT320) Beamforming

Chan.	Chan. Freq. (MHz)	Field Strength (dBuV/m)	Correction Factor (dB)	EIRP PSD (dBm/MHz)	EIRP PSD Limit (dBm/MHz)	Test Result
31	6105	100.03	-95.23	4.80	5	Pass
63	6265	100.10	-95.23	4.87	5	Pass
95	6425	100.17	-95.23	4.94	5	Pass
127	6585	100.07	-95.23	4.84	5	Pass
159	6745	100.12	-95.23	4.89	5	Pass
191	6905	100.04	-95.23	4.81	5	Pass


Spectrum Plot of Maximum Value




802.11be (EHT20) Beamforming : CH 93




802.11be (EHT40) Beamforming : CH 99



802.11be (EHT80) Beamforming : CH 103



802.11be (EHT160) Beamforming : CH 175



802.11be (EHT320) Beamforming : CH 95

7.3 Emission Bandwidth

Environmental Conditions:	25°C, 60% RH	Tested By:	Match Tsui
---------------------------	--------------	------------	------------

802.11a

Channel	Frequency (MHz)	26dB Bandwidth (MHz)				Maximum Limit (MHz)	Test Result
		Chain 0	Chain 1	Chain 2	Chain 3		
1	5955	22.74	23.04	23.02	22.90	320	Pass
45	6175	22.76	22.99	23.23	22.71	320	Pass
93	6415	22.69	22.99	23.13	22.74	320	Pass
97	6435	22.69	22.99	23.29	22.79	320	Pass
105	6475	22.96	23.24	23.36	22.69	320	Pass
113	6515	22.73	22.93	23.11	22.76	320	Pass
117	6535	22.99	23.03	22.51	22.88	320	Pass
149	6695	22.75	23.26	23.24	22.82	320	Pass
181	6855	22.75	23.16	22.78	23.19	320	Pass
185	6875	22.71	23.05	23.09	23.01	320	Pass
209	6995	22.76	23.04	23.31	22.72	320	Pass
233	7115	23.15	23.52	22.89	22.74	320	Pass

802.11be (EHT20)

Channel	Frequency (MHz)	26dB Bandwidth (MHz)				Maximum Limit (MHz)	Test Result
		Chain 0	Chain 1	Chain 2	Chain 3		
1	5955	23.51	22.92	24.06	22.74	320	Pass
45	6175	23.33	23.03	23.92	22.72	320	Pass
93	6415	23.37	23.05	24.03	22.68	320	Pass
97	6435	23.44	22.96	24.00	22.69	320	Pass
105	6475	23.52	23.04	24.31	22.69	320	Pass
113	6515	23.65	22.90	23.89	22.89	320	Pass
117	6535	23.58	23.02	23.87	22.74	320	Pass
149	6695	23.49	23.10	24.11	22.55	320	Pass
181	6855	23.42	23.09	23.63	22.93	320	Pass
185	6875	23.15	23.00	24.09	22.70	320	Pass
209	6995	23.37	22.92	24.28	22.92	320	Pass
233	7115	23.16	23.15	24.05	22.74	320	Pass

802.11be (EHT40)

Channel	Frequency (MHz)	26dB Bandwidth (MHz)				Maximum Limit (MHz)	Test Result
		Chain 0	Chain 1	Chain 2	Chain 3		
3	5965	45.53	44.87	45.46	45.25	320	Pass
43	6165	44.73	44.60	44.87	45.29	320	Pass
91	6405	45.33	45.28	45.46	45.14	320	Pass
99	6445	44.80	45.30	45.00	45.39	320	Pass
107	6485	45.29	44.66	44.85	45.18	320	Pass
115	6525	45.12	44.79	44.92	44.67	320	Pass
123	6565	44.86	45.09	44.94	45.03	320	Pass
155	6725	45.05	45.21	44.83	44.59	320	Pass
179	6845	45.65	44.59	45.03	45.06	320	Pass
187	6885	44.77	44.93	45.17	45.04	320	Pass
211	7005	44.92	45.08	44.34	45.44	320	Pass
227	7085	45.15	45.17	44.97	44.92	320	Pass

802.11be (EHT80)

Channel	Frequency (MHz)	26dB Bandwidth (MHz)				Maximum Limit (MHz)	Test Result
		Chain 0	Chain 1	Chain 2	Chain 3		
7	5985	91.39	89.96	93.53	92.11	320	Pass
39	6145	91.34	90.58	91.86	91.40	320	Pass
87	6385	90.10	91.32	91.31	89.91	320	Pass
103	6465	91.58	91.46	91.28	89.97	320	Pass
119	6545	89.79	90.16	91.68	91.16	320	Pass
151	6705	90.42	91.56	91.15	90.95	320	Pass
183	6865	91.32	90.48	90.75	90.69	320	Pass
199	6945	90.48	90.64	91.77	90.58	320	Pass
215	7025	90.74	91.57	91.10	90.44	320	Pass

802.11be (EHT160)


Channel	Frequency (MHz)	26dB Bandwidth (MHz)				Maximum Limit (MHz)	Test Result
		Chain 0	Chain 1	Chain 2	Chain 3		
15	6025	175.17	176.02	172.72	175.44	320	Pass
47	6185	176.59	174.75	172.59	176.56	320	Pass
79	6345	175.61	175.99	173.55	177.24	320	Pass
111	6505	174.97	176.28	173.81	175.65	320	Pass
143	6665	176.29	176.61	175.41	175.37	320	Pass
175	6825	177.62	177.13	172.75	176.64	320	Pass
207	6985	176.80	176.59	171.97	175.77	320	Pass

802.11be (EHT320)


Channel	Frequency (MHz)	26dB Bandwidth (MHz)				Maximum Limit (MHz)	Test Result
		Chain 0	Chain 1	Chain 2	Chain 3		
31	6105	344.59	344.62	341.77	341.38	320	Note
63	6265	345.29	347.36	346.34	348.31	320	Note
95	6425	343.30	345.17	343.47	345.51	320	Note
127	6585	343.79	345.17	345.33	345.82	320	Note
159	6745	346.29	345.84	343.97	349.12	320	Note
191	6905	347.29	346.51	344.66	345.36	320	Note

Note: For channels with a nominal bandwidth of 320 MHz, compliance is demonstrated by way of the 99% BW.


Spectrum Plot of Maximum Value




802.11a / Chain 1 : CH 233




802.11be (EHT20) / Chain 2 : CH 105




802.11be (EHT40) / Chain 0 : CH 179



802.11be (EHT80) / Chain 2 : CH 7



802.11be (EHT160) / Chain 0 : CH 175




802.11be (EHT320) / Chain 3 : CH 159







7.4 In-Band Emission Mask

Environmental Conditions:	25°C, 60% RH	Tested By:	Match Tsui
---------------------------	--------------	------------	------------







802.11a









Spectrum Plot









Spectrum Plot









Spectrum Plot









Spectrum Plot









Spectrum Plot



Spectrum Plot




Spectrum Plot




802.11be (EHT20)


Spectrum Plot




802.11be (EHT20) / Chain 0 : CH 1




802.11be (EHT20) / Chain 0 : CH 45




802.11be (EHT20) / Chain 0 : CH 93



802.11be (EHT20) / Chain 0 : CH 97




802.11be (EHT20) / Chain 0 : CH 105




802.11be (EHT20) / Chain 0 : CH 113


Spectrum Plot




802.11be (EHT20) / Chain 0 : CH 117




802.11be (EHT20) / Chain 0 : CH 149




802.11be (EHT20) / Chain 0 : CH 181



802.11be (EHT20) / Chain 0 : CH 185




802.11be (EHT20) / Chain 0 : CH 209




802.11be (EHT20) / Chain 0 : CH 233


Spectrum Plot




802.11be (EHT20) / Chain 1 : CH 1




802.11be (EHT20) / Chain 1 : CH 45




802.11be (EHT20) / Chain 1 : CH 93



802.11be (EHT20) / Chain 1 : CH 97




802.11be (EHT20) / Chain 1 : CH 105




802.11be (EHT20) / Chain 1 : CH 113


Spectrum Plot




802.11be (EHT20) / Chain 1 : CH 117




802.11be (EHT20) / Chain 1 : CH 149




802.11be (EHT20) / Chain 1 : CH 181



802.11be (EHT20) / Chain 1 : CH 185




802.11be (EHT20) / Chain 1 : CH 209




802.11be (EHT20) / Chain 1 : CH 233


Spectrum Plot




802.11be (EHT20) / Chain 2 : CH 1




802.11be (EHT20) / Chain 2 : CH 45




802.11be (EHT20) / Chain 2 : CH 93



802.11be (EHT20) / Chain 2 : CH 97









802.11be (EHT20) / Chain 2 : CH 105









802.11be (EHT20) / Chain 2 : CH 113


Spectrum Plot




Spectrum Plot




Spectrum Plot




802.11be (EHT20) / Chain 3 : CH 117




802.11be (EHT20) / Chain 3 : CH 149




802.11be (EHT20) / Chain 3 : CH 181



802.11be (EHT20) / Chain 3 : CH 185



802.11be (EHT20) / Chain 3 : CH 209



802.11be (EHT20) / Chain 3 : CH 233