



## RF Exposure Evaluation Declaration

---

**FCC ID:** H8N-RG8000W

**APPLICANT:** ASKEY COMPUTER CORP

**Application Type:** Certification

**Product:** Gateway

**Model No.:** QB-GW-TAC

**Trademark:** ASKEY

**FCC Classification:** Digital Transmission System (DTS)  
Unlicensed National Information Infrastructure (UNII)  
FCC Part 15 Spread Spectrum Transmitter(DSS)  
KDB 447498 D01v06

Reviewed By : Robin Wu  
( Robin Wu )

Approved By : Marlin Chen  
( Marlin Chen )



The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standards through the calibration of the equipment and evaluated measurement uncertainty herein.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

---

## Revision History

| Report No.   | Version | Description                   | Issue Date |
|--------------|---------|-------------------------------|------------|
| 1512RSU00309 | Rev. 01 | Initial report                | 01-19-2016 |
| 1512RSU00309 | Rev. 02 | Added MPE of Bluetooth module | 01-29-2016 |
| 1512RSU00309 | Rev. 03 | Measure the MPE               | 02-04-2016 |
| 1512RSU00309 | Rev. 04 | Revised the FCC ID            | 02-17-2016 |

## 1. PRODUCT INFORMATION

### 1.1. Equipment Description

|                                       |                                                                                                                                                                                                                                                                                                                                                                              |
|---------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product Name                          | Gateway                                                                                                                                                                                                                                                                                                                                                                      |
| Model No.                             | QB-GW-TAC                                                                                                                                                                                                                                                                                                                                                                    |
| Brand Name                            | ASKEY                                                                                                                                                                                                                                                                                                                                                                        |
| Wi-Fi Specification                   | 802.11a/b/g/n/ac                                                                                                                                                                                                                                                                                                                                                             |
| Frequency Range                       | <p><b><u>2.4GHz:</u></b></p> <p>For 802.11b/g/n-HT20:<br/>2412 ~ 2462 MHz</p> <p>For 802.11n-HT40:<br/>2422 ~ 2452 MHz</p> <p><b><u>5GHz:</u></b></p> <p>For 802.11a/n-HT20/ac-VHT20:<br/>5180~5240MHz, 5745~5825MHz</p> <p>For 802.11n-HT40/ac-VHT40:<br/>5190~5230MHz, 5755~5795MHz</p> <p>For 802.11ac-VHT80:<br/>5210MHz, 5775MHz</p>                                    |
| Type of Modulation                    | <p>802.11b: DSSS</p> <p>802.11g/a/n/ac: OFDM</p>                                                                                                                                                                                                                                                                                                                             |
| Maximum Average Output Power          | <p><b><u>For 2.4GHz Band:</u></b></p> <p>802.11b: 26.60dBm</p> <p>802.11g: 25.80dBm</p> <p>802.11n-HT20: 25.44dBm</p> <p>802.11n-HT40: 26.72dBm</p> <p><b><u>For 5GHz Band:</u></b></p> <p>802.11a: 24.91dBm</p> <p>802.11n-HT20: 25.00dBm</p> <p>802.11n-HT40: 24.57dBm</p> <p>802.11ac-VHT20: 24.93dBm</p> <p>802.11ac-VHT40: 25.03dBm</p> <p>802.11ac-VHT80: 24.22dBm</p> |
| Bluetooth Module Maximum Output Power | <p>Bluetooth v3.0+HS: 6.90(Peak)</p> <p>Bluetooth v4.0: 8.83(Average)</p>                                                                                                                                                                                                                                                                                                    |

## 1.2. Antenna Description

| Antenna Type | Frequency Band (MHz) | Tx Paths | Per Chain Max Antenna Gain (dBi) |       |       | Beam Forming & CDD Directional Gain (dBi) |
|--------------|----------------------|----------|----------------------------------|-------|-------|-------------------------------------------|
|              |                      |          | Ant 0                            | Ant 1 | Ant 2 |                                           |
| PCB Antenna  | 2412 ~2462           | 3        | 5.41                             | 2.62  | 1.99  | 8.24                                      |

| Antenna Type | Frequency Band (MHz) | Tx Paths | Per Chain Max Antenna Gain (dBi) |       |       |       | Beam Forming & CDD Directional Gain (dBi) |
|--------------|----------------------|----------|----------------------------------|-------|-------|-------|-------------------------------------------|
|              |                      |          | Ant 0                            | Ant 1 | Ant 2 | Ant 3 |                                           |
| PCB Antenna  | 5150 ~ 5250          | 4        | 4.84                             | 5.12  | 4.34  | 5.41  | 10.96                                     |
|              | 5725 ~ 5850          | 4        | 4.28                             | 5.14  | 3.48  | 5.11  | 10.55                                     |

1. The EUT supports Cyclic Delay Diversity (CDD) technology, and that CDD technology is correlated.
  - (1) Correlated *signals include, but are not limited to, signals transmitted in any of the following modes:*
    - Unequal Antenna gains, with equal transmit powers. For Antenna gains given by  $G_1, G_2, \dots, G_N$  dBi transmit signals are correlated, then
    - Directional gain =  $10 \cdot \log[(10^{G_1/20} + 10^{G_2/20} + \dots + 10^{G_N/20})^2 / N_{\text{ANT}}]$  dBi [Note the “20”s in the denominator of each exponent and the square of the sum of terms; the object is to combine the signal levels coherently.]

For example: 2.4GHz Directional Gain =  $10 \cdot \log[(10^{5.41/20} + 10^{2.62/20} + 10^{1.99/20})^2 / 2] = 8.24$  dBi

5150 ~ 5250MHz Directional Gain =  $10 \cdot \log[(10^{4.84/20} + 10^{5.12/20} + 10^{4.34/20} + 10^{5.41/20})^2 / 4] = 10.96$  dBi

## 2. RF Exposure Evaluation

### 2.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

#### LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

| Frequency Range (MHz)                                     | Electric Field Strength (V/m) | Magnetic Field Strength (A/m) | Power Density (mW/cm <sup>2</sup> ) | Average Time (Minutes) |
|-----------------------------------------------------------|-------------------------------|-------------------------------|-------------------------------------|------------------------|
| (A) Limits for Occupational/ Control Exposures            |                               |                               |                                     |                        |
| 300-1500                                                  | --                            | --                            | f/300                               | 6                      |
| 1500-100,000                                              | --                            | --                            | 5                                   | 6                      |
| (B) Limits for General Population/ Uncontrolled Exposures |                               |                               |                                     |                        |
| 300-1500                                                  | --                            | --                            | f/1500                              | 6                      |
| 1500-100,000                                              | --                            | --                            | 1                                   | 30                     |

f= Frequency in MHz

Calculation Formula:  $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

$P_d$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

G = gain of antenna in linear scale

$\pi$  = 3.1416

r = distance between observation point and center of the radiator in cm

$P_d$  is the limit of MPE, 1mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

### 2.2. Test Procedure Used

1. Setup the EUT and simulators as shown in the test setup photo;
2. Make the EUT transmit at Max Power(refer section 1.1) in each band;
3. Move the Field Strength Meter to find position of each face which the Max Field Strength, and keep distance 20cm between the probe with EUT;
4. Rotating the Field Strength Meter to X, Y, Z axial, and record the Max Field Strength in each position of each face.

| Instrument           | Manufacturer | Type No. | Measurement Range | Cali. Interval | Cali. Due Date |
|----------------------|--------------|----------|-------------------|----------------|----------------|
| Field Strength Meter | AR           | FL7006   | 100kHz ~ 6GHz     | 1 year         | 2016/09/09     |

### 2.3. Test Result of RF Exposure Evaluation

|           |                        |
|-----------|------------------------|
| Product   | Gateway                |
| Test Item | RF Exposure Evaluation |

Antenna Gain: refer to the section 1.2; the maximum Gain measured in fully anechoic chamber is 1dBi for Bluetooth Module.

#### For 2.4GHz ISM Band:

| Test Mode                   | Frequency Band (MHz) | Maximum Average Output Power (dBm) |
|-----------------------------|----------------------|------------------------------------|
| 802.11b/g/n-HT20/<br>n-HT40 | 2412 ~ 2462          | 26.72                              |

#### For 5GHz UNII Band:

| Test Mode                                              | Frequency Band (MHz) | Maximum Average Output Power (dBm) |
|--------------------------------------------------------|----------------------|------------------------------------|
| 802.11a/n-HT20/<br>n-H40/ac-VHT20<br>ac-VHT40/ac-VHT80 | 5180 ~ 5240          | 24.62                              |
|                                                        | 5745 ~ 5825          | 25.03                              |

#### Bluetooth Module

| Test Mode      | Frequency Band (MHz) | Maximum Average Output Power (dBm) | Power Density at R = 20 cm (mW/cm <sup>2</sup> ) | Limit (mW/cm <sup>2</sup> ) |
|----------------|----------------------|------------------------------------|--------------------------------------------------|-----------------------------|
| Bluetooth v4.0 | 2402 ~ 2480          | 8.83                               | 0.0019                                           | 1                           |

### MPE Measurement Result

| Test Mode                   | Frequency Band (MHz) | Position | Field Strength (V/m) |
|-----------------------------|----------------------|----------|----------------------|
| 802.11b/g/n-HT20/<br>n-HT40 | 2412 ~ 2462          | Front    | 15.84                |
|                             |                      | Back     | 20.17                |
|                             |                      | Left     | 14.97                |
|                             |                      | Right    | 22.47                |
|                             |                      | Top      | 24.78                |

| Test Mode                                              | Frequency Band (MHz) | Position | Field Strength (V/m) |
|--------------------------------------------------------|----------------------|----------|----------------------|
| 802.11a/n-HT20/<br>n-H40/ac-VHT20<br>ac-VHT40/ac-VHT80 | 5180 ~ 5240          | Front    | 21.88                |
|                                                        |                      | Back     | 21.34                |
|                                                        |                      | Left     | 26.17                |
|                                                        |                      | Right    | 16.74                |
|                                                        |                      | Top      | 22.06                |

| Test Mode                                              | Frequency Band (MHz) | Position | Field Strength (V/m) |
|--------------------------------------------------------|----------------------|----------|----------------------|
| 802.11a/n-HT20/<br>n-H40/ac-VHT20<br>ac-VHT40/ac-VHT80 | 5745 ~ 5825          | Front    | 17.79                |
|                                                        |                      | Back     | 16.03                |
|                                                        |                      | Left     | 24.07                |
|                                                        |                      | Right    | 18.40                |
|                                                        |                      | Top      | 18.99                |

Both of the WLAN 2.4GHz Band, WLAN 5GHz Band & Bluetooth Module can transmit simultaneously.

**Therefore,  $\text{Max } P_d = (V/m)^2 / 3770 \text{ mW/cm}^2$**

$\text{Max } P_d = \{(2.4\text{GHz Max Field Strength})^2 + (5\text{GHz Max Field Strength})^2\} / 3770 + P_d(\text{Bluetooth Module}) = (24.78^2 + 26.17^2) / 377 + 0.0019 = 0.3464 \text{ mW/cm}^2 < 1 \text{ mW/cm}^2$

Note: The detail Measurement result can refer to the Test Setup Photos.

The End