



FCC 47 CFR PART 15 SUBPART C

TEST REPORT

For

Wireless Lan Cardbus Card

Model: Gigaset PC Card 108

Trade Name: SIEMENS

Issued to

**ASKEY COMPUTER CORP.
10F, No.119, CHIENKANG RD., CHUNG-HO,
TAIPEI, TAIWAN, R.O.C.**

Issued by



**Compliance Certification Services Inc.
No. 81-1, Lane 210, Bade Rd. 2, Luchu Hsiang,
Taoyuan Hsien, (338) Taiwan, R.O.C.
<http://www.ccsemc.com.tw>
service@tw.ccsemc.com**



Note: This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document.



TABLE OF CONTENTS

1. TEST RESULT CERTIFICATION.....	3
2. EUT DESCRIPTION	4
3. TEST METHODOLOGY	5
3.1 EUT CONFIGURATION	5
3.2 EUT EXERCISE.....	5
3.3 GENERAL TEST PROCEDURES.....	5
3.4 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS.....	6
3.5 DESCRIPTION OF TEST MODES	7
4. INSTRUMENT CALIBRATION.....	8
4.1 MEASURING INSTRUMENT CALIBRATION.....	8
4.2 MEASUREMENT EQUIPMENT USED.....	8
5. FACILITIES AND ACCREDITATIONS	9
5.1 FACILITIES	9
5.2 EQUIPMENT.....	9
5.3 TABLE OF ACCREDITATIONS AND LISTINGS.....	10
6. SETUP OF EQUIPMENT UNDER TEST	11
6.1 SETUP CONFIGURATION OF EUT.....	11
6.2 SUPPORT EQUIPMENT	11
7. FCC PART 15.247 REQUIREMENTS.....	12
7.1 6DB BANDWIDTH.....	12
7.2 PEAK POWER.....	17
7.3 AVERAGE POWER	22
7.4 BAND EDGES MEASUREMENT	27
7.5 PEAK POWER SPECTRAL DENSITY	40
7.6 SPURIOUS EMISSIONS	46
7.7 POWERLINE CONDUCTED EMISSIONS.....	62
APPENDIX I RADIO FREQUENCY EXPOSURE	65
APPENDIX II PHOTOGRAPHS OF TEST SETUP	66



1. TEST RESULT CERTIFICATION

Applicant: ASKEY COMPUTER CORP.
10F, No.119, CHIENKANG RD., CHUNG-HO,
TAIPEI, TAIWAN, R.O.C.

Equipment Under Test: Wireless Lan Cardbus Card

Trade Name: SIEMENS

Model: Gigaset PC Card 108

Date of Test: April 24 ~ May 4, 2006

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
FCC 47 CFR Part 15 Subpart C	No non-compliance noted

We hereby certify that:

The above equipment was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4: 2003 and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 15.207, 15.209, 15.247.

The test results of this report relate only to the tested sample EUT identified in this report.

Approved by:

Reviewed by:

Gavin Lim
Section Manager
Compliance Certification Services Inc.

Amanda Wu
Section Manager
Compliance Certification Services Inc.



2. EUT DESCRIPTION

Product	Wireless Lan Cardbus Card
Trade Name	SIEMENS
Model Number	Gigaset PC Card 108
Model Discrepancy	N/A
Power Supply	Powered from host device.
Frequency Range	IEEE 802.11b/g Base mode: 2.412~2.462 GHz IEEE 802.11g Turbo mode: 2.437 GHz
Transmit Power	IEEE 802.11b mode: 19.08 dBm IEEE 802.11g Base mode: 18.91 dBm IEEE 802.11g Turbo mode: 18.95 dBm
Modulation Technique	IEEE 802.11b mode: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g Base mode: DSSS (CCK, DQPSK, DBPSK) + OFDM (QPSK, BPSK, 16-QAM, 64-QAM) IEEE 802.11g Turbo mode: OFDM (QPSK, BPSK, 16-QAM, 64-QAM)
Transmit Data Rate	IEEE 802.11b mode: 11, 5.5, 2, 1 Mbps IEEE 802.11g Base mode: 54, 48, 36, 24, 18, 12, 9, 6 Mbps IEEE 802.11g Turbo mode: 108, 96, 72Mbps
Number of Channels	IEEE 802.11b/g Base mode: 11 Channels IEEE 802.11g Turbo mode: 1 Channel
Antenna Specification	Left: Printed Antenna / Gain: 1.66 dBi Right: Printed Antenna / Gain: 0.83 dBi

Remark:

1. The sample selected for test was engineering sample that approximated to production product and was provided by manufacturer.
2. This submittal(s) (test report) is intended for FCC ID: H8NWLC3070 filing to comply with Section 15.207, 15.209 and 15.247 of the FCC Part 15, Subpart C Rules.



3. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.4 and FCC CFR 47 2.1046, 2.1047, 2.1049, 2.1051, 2.1053, 2.1055, 2.1057, 15.207, 15.209 and 15.247.

3.1 EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

3.2 EUT EXERCISE

The EUT was operated in the engineering mode to fix the TX frequency that was for the purpose of the measurements.

According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C.

3.3 GENERAL TEST PROCEDURES

Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.4 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 13.1.4.1 of ANSI C63.4.



3.4 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS

- (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 -	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.52525	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	156.7 - 156.9	3260 - 3267	23.6 - 24.0
12.29 - 12.293	162.0125 - 167.17	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	167.72 - 173.2	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	240 - 285	3600 - 4400	(²)
13.36 - 13.41	322 - 335.4		

¹ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

² Above 38.6

- (b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.



3.5 DESCRIPTION OF TEST MODES

The EUT (model: Gigaset PC Card 108) with 1.66 dBi Printed Antenna had been tested under operating condition.

Software used to control the EUT for staying in continuous transmitting mode was programmed.

After verification, all tests were carried out with the worst case test modes as shown below except radiated spurious emission below 1GHz, which worst case was in normal link mode only.

IEEE802.11b mode: Channel Low, Channel Mid and Channel High with 11Mbps data rate were chosen for full testing.

IEEE802.11g mode:

Channel Low Channel Low, Channel Mid and Channel High with 54Mbps data rate were chosen for full testing.

IEEE802.11g Turbo mode:

Channel Mid (2437MHz) with 108Mbps data rate was chosen for full testing.



4. INSTRUMENT CALIBRATION

4.1 MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

4.2 MEASUREMENT EQUIPMENT USED

Equipment Used for Emissions Measurement

Remark: Each piece of equipment is scheduled for calibration once a year.

Conducted Emissions Test Site				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY43360131	01/18/2007

3M Semi Anechoic Chamber				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	US42510252	07/25/2006
Test Receiver	Rohde&Schwarz	ESCI	100064	11/05/2006
Switch Controller	TRC	Switch Controller	SC94050010	05/05/2007
4 Port Switch	TRC	4 Port Switch	SC94050020	05/05/2007
Horn-Antenna	TRC	HA-0502	06	06/02/2006
Horn-Antenna	TRC	HA-0801	04	05/05/2007
Horn-Antenna	TRC	HA-1201A	01	07/04/2006
Horn-Antenna	TRC	HA-1301A	01	07/04/2006
Bilog- Antenna	Sunol Sciences	JB3	A030205	03/09/2007
Turn Table	Max-Full	MFT-120S	T120S940302	N.C.R.
Antenna Tower	Max-Full	MFA-430	A440940302	N.C.R.
Controller	Max-Full	MF-CM886	CC-C-1F-13	N.C.R.
Site NSA	CCS	N/A	FCC: 965860 IC: IC 6106	09/26/2008
Test S/W	LABVIEW (V 6.1)			

Remark: The measurement uncertainty is less than +/-2.0065dB (30MHz ~ 1GHz), +/-3.0958dB (Above 1GHz) which is evaluated as per the NAMAS NIS 81 and CISPR/A/291/CDV.

Powerline Conducted Emissions Test Site				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
EMI TEST RECEIVER 9kHz-30MHz	ROHDE & SCHWARZ	ESHS30	828144/003	09/27/2006
TWO-LINE V-NETWORK 9kHz-30MHz	SCHAFFNER	NNB41	03/10013	06/12/2006
LISN 10kHz-100MHz	EMCO	3825/2	9106-1809	03/20/2007
Test S/W	LABVIEW (V 6.1)			

Remark: The measurement uncertainty is less than +/- 2.81dB, which is evaluated as per the NAMAS NIS 81 and CISPR/A/291/CDV.



5. FACILITIES AND ACCREDITATIONS

5.1 FACILITIES

All measurement facilities used to collect the measurement data are located at

☐ No.199, Chunghsen Road, Hsintien City, Taipei Hsien, Taiwan, R.O.C.

Tel: 886-2-2217-0894 / Fax: 886-2-2217-1029

☒ No.11, Wugong 6th Rd., Wugu Industrial Park, Taipei Hsien 248, Taiwan

Tel: 886-2-2299-9720 / Fax: 886-2-2298-4045

☒ No.81-1, Lane 210, Bade 2nd Rd., Luchu Hsiang, Taoyuan Hsien 338, Taiwan

Tel: 886-3-324-0332 / Fax: 886-3-324-5235

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22.

5.2 EQUIPMENT

Radiated emissions are measured with one or more of the following types of linearly polarized antennas: tuned dipole, biconical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers.

Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

5.3 TABLE OF ACCREDITATIONS AND LISTINGS

Country	Agency	Scope of Accreditation	Logo
USA	A2LA	EN 55011, EN 55014-1/2, CISPR 11, CISPR 14-1/2, EN 55022, EN 55015, CISPR 22, CISPR 15, AS/NZS 3548, VCCI V3 (2001), CFR 47, FCC Part 15/18, CNS 13783-1, CNS 13439, CNS 13438, CNS 13803, CNS 14115, EN 55024, IEC 801-2, IEC 801-3, IEC 801-4, IEC/EN 61000-3-2, EIC/EN 61000-3-3, IEC/EN 61000-4-2/3/4/5/6/8/11, EN 50081-1/ EN 61000-6-3, EN 50081-2/EN 61000-6-4, EN 50081-2/EN 61000-6-1: 2001	 0824-01
USA	FCC	3/10 meter Open Area Test Sites (93105, 90471) / 3M Semi Anechoic Chamber (965860) to perform FCC Part 15/18 measurements	 93105, 90471 965860
Japan	VCCI	3/10 meter Open Area Test Sites to perform conducted/radiated measurements	 R-393/1066/725/879 C-402/747/912
Norway	NEMKO	EN 50081-1/2, EN 50082-1/2, IEC 61000-6-1/2, EN 50091-2, EN 50130-4, EN 55011, EN 55013, EN 55014-1/2, EN 55015, EN 55022, EN 55024, EN 61000-3-2/3, EN 61326-1, IEC 61000-4-2/3/4/5/6/8/11, EN 60601-1-2, EN 300 328, EN 300 422-2, EN 301 419-1, EN 301 489-01/03/07/08/09/17, EN 301 419-2/3, EN 300 454-2, EN 301 357-2	 ELA 124a ELA 124b ELA 124c
Taiwan	TAF	EN 300 328, EN 300 220-1, EN 300 220-2, EN 300 220-3, 47 CFR FCC Part 15 Subpart C, EN 61000-3-2, EN 61000-3-3, CNS 13439, CNS 13783-1, CNS 14115, CNS 13438, AS/NZS CISPR 22, CNS 13022-1, IEC 61000-4-2/3/4/5/6/8/11, CNS 13022-2/3	
Taiwan	BSMI	CNS 13438, CNS 13783-1, CNS 13439, CNS 14115	 SL2-IS-E-0014 SL2-IN-E-0014 SL2-A1-E-0014 SL2-R1-E-0014 SL2-R2-E-0014 SL2-L1-E-0014
Canada	Industry Canada	3/10 meter Open Area Test Sites (IC 3991-3, IC 3991-4) / 3M Semi Anechoic Chamber (IC 6106) to perform RSS 212 Issue 1	 IC 3991-3 IC 3991-4 IC 6106

* No part of this report may be used to claim or imply product endorsement by A2LA or any agency of the US Government.



6. SETUP OF EQUIPMENT UNDER TEST

6.1 SETUP CONFIGURATION OF EUT

See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

6.2 SUPPORT EQUIPMENT

No.	Device Type	Brand	Model	Series No.	FCC ID	Data Cable	Power Cord
1.	Notebook PC	IBM	2672(X31)	99PBTKB	WLAN: ANO20030400LEG Bluetooth: ANO20020100MTN	N/A	AC I/P: Unshielded, 1.8m DC O/P: Unshielded, 1.8m with a core
2.	Notebook PC	Dell	PP05L	7T390 A03	E2K5HCKT	N/A	AC I/P: Unshielded, 1.8m DC O/P: Unshielded, 1.8m with a core

Remark:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.




7. FCC PART 15.247 REQUIREMENTS

7.1 6DB BANDWIDTH

LIMIT

According to §15.247(a)(2), systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6dB bandwidth shall be at least 500 kHz.

Test Configuration



TEST PROCEDURE

1. Place the EUT on the table and set it in the transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as RBW = 100 kHz, VBW = RBW, Span = 50 MHz, Sweep = auto.
4. Mark the peak frequency and -6dB (upper and lower) frequency.
5. Repeat until all the rest channels are investigated.

TEST RESULTS

No non-compliance noted

Test Data

Test mode: IEEE 802.11b mode

Channel	Frequency (MHz)	Bandwidth (kHz)	Limit (kHz)	Result
Low	2412	10420	>500	PASS
Mid	2437	12500		PASS
High	2462	12080		PASS

Test mode: IEEE 802.11g mode


Channel	Frequency (MHz)		Bandwidth (kHz)	Limit (kHz)	Test Result
Low	Base mode	2412	16500	>500	PASS
Mid		2437	16420		PASS
High		2462	16330		PASS
Mid	Turbo mode	2437	32670		PASS




Test Plot

IEEE 802.11b mode

6dB Bandwidth (CH Low)



6dB Bandwidth (CH Mid)





6dB Bandwidth (CH High)

Agilent 18:44:04 May 2, 2006

R T

6dB BW, b Mode High Ch.

Δ Mkr1 12.08 MHz

Ref 20 dBm

Atten 20 dB

1.47 dB

#Peak

Log

10

dB/

Offst

16

dB

DI

1.0

dBm

LgAv


V1 S2

S3 FC

$\alpha(f)$:

FTun

Swp



Center 2.462 00 GHz

Span 50 MHz

#Res BW 100 kHz

#VBW 100 kHz

Sweep 6.04 ms (601 pts)

IEEE 802.11g Base mode

6dB Bandwidth (CH Low)

Agilent 18:51:12 May 2, 2006

R T

6dB BW, g Mode Low Ch.

Δ Mkr1 16.50 MHz

Ref 20 dBm

Atten 20 dB

1.79 dB

#Peak

Log

10

dB/

Offst

16

dB

DI

-0.6

dBm

LgAv


V1 S2

S3 FC

$\alpha(f)$:

FTun

Swp



Center 2.412 00 GHz

Span 50 MHz

#Res BW 100 kHz

#VBW 100 kHz

Sweep 6.04 ms (601 pts)



6dB Bandwidth (CH Mid)

Agilent 10:30:11 May 3, 2006

R T

6dB BW, g Mode Mid Ch.

Δ Mkr1 16.42 MHz

Ref 20 dBm

Atten 20 dB

-1.34 dB

#Peak

Log

10

dB/

Offst

16

dB

DI

-0.3

dBm

LgAv


V1 S2

S3 FC

$\alpha(f)$:

FTun

Swp



Center 2.437 00 GHz

Span 50 MHz

#Res BW 100 kHz

#VBW 100 kHz

Sweep 6.04 ms (601 pts)

6dB Bandwidth (CH High)

Agilent 10:55:26 May 3, 2006

R T

6dB BW, g Mode High Ch.

Δ Mkr1 16.33 MHz

Ref 20 dBm

Atten 20 dB

-1.40 dB

#Peak

Log

10

dB/

Offst

16

dB

DI

-2.3

dBm

LgAv


V1 S2

S3 FC

$\alpha(f)$:

FTun

Swp



Center 2.462 00 GHz

Span 50 MHz

#Res BW 100 kHz

#VBW 100 kHz

Sweep 6.04 ms (601 pts)



IEEE 802.11g Turbo mode

CH Mid

Agilent 11:23:57 May 3, 2006

R L

6dB BW, g turbo Mode Mid Ch.

Δ Mkr1 32.67 MHz

Ref 20 dBm

Atten 20 dB

-2.23 dB

#Peak

Log

10

dB/

Offst

16

dB

DI

-3.5

dBm

LgAv

V1 S2

S3 FC

$\alpha(f)$:

FTun

Swp


Center 2.437 00 GHz

#Res BW 100 kHz

#VBW 100 kHz

Span 50 MHz

Sweep 6.04 ms (601 pts)






7.2 PEAK POWER

LIMIT

The maximum peak output power of the intentional radiator shall not exceed the following:

1. According to §15.247(b)(3), for systems using digital modulation in the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz: 1 Watt.
2. According to §15.247(b)(4), the conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Test Configuration



TEST PROCEDURE

The transmitter output is connected to the Spectrum analyzer. The Spectrum analyzer is set to the peak power detection.

TEST RESULTS

No non-compliance noted

Test Data

Test mode: IEEE 802.11b mode

Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)	Limit (W)	Result
Low	2412	18.82	0.0762	1.00	PASS
Mid	2437	19.08	0.0809		PASS
High	2462	18.85	0.0767		PASS

Test mode: IEEE 802.11g mode

Channel	Frequency (MHz)		Output Power (dBm)	Output Power (W)	Limit (W)	Result
Low	Base mode	2412	18.74	0.0748	1.00	PASS
Mid		2437	18.91	0.0778		PASS
High		2462	18.64	0.0731		PASS
Mid	Turbo mode	2437	18.95	0.0785		PASS




Test Plot

IEEE 802.11b mode

Peak Power (CH Low)

Agilent 11:47:54 May 3, 2006
Peak Output Power, b Mode Low Ch.

R L



Channel Power

18.82 dBm / 15.3140 MHz


Power Spectral Density

-53.03 dBm/Hz

Peak Power (CH Mid)

Agilent 12:16:32 May 3, 2006
Peak Output Power (DTS), b Mode Mid Ch.

R L



Channel Power

19.08 dBm / 15.2970 MHz

Power Spectral Density

-52.77 dBm/Hz



Peak Power (CH High)


Agilent 11:58:32 May 3, 2006

L

Peak Output Power , b Mode High Ch.

Ref 20 dBm

Atten 20 dB



Channel Power

18.85 dBm / 15.3410 MHz

Power Spectral Density

-53.01 dBm/Hz

IEEE 802.11g Base mode

Peak Power (CH Low)


Agilent 12:21:34 May 3, 2006

R L

Peak Output Power , g Mode Low Ch.

Ref 20 dBm

Atten 20 dB



Channel Power

18.74 dBm / 16.6020 MHz

Power Spectral Density

-53.46 dBm/Hz

**Peak Power (CH Mid)**


* Agilent 12:23:57 May 3, 2006

R L

Peak Output Power , g Mode Mid Ch.

Ref 20 dBm

Atten 20 dB



Channel Power

Power Spectral Density

18.91 dBm / 16.5990 MHz

-53.29 dBm/Hz

Peak Power (CH High)


* Agilent 12:18:06 May 3, 2006

R T

Peak Output Power , g Mode High Ch.

Ref 20 dBm

Atten 20 dB



Channel Power

Power Spectral Density

18.64 dBm / 16.5660 MHz

-53.56 dBm/Hz



IEEE 802.11g Turbo mode

CH Mid


Agilent 11:17:23 May 3, 2006

R L

Peak Output Power , g turbo Mode Mid Ch.

Ref 20 dBm

Atten 20 dB



Channel Power

Power Spectral Density

18.95 dBm / 33.0310 MHz

-56.24 dBm/Hz




7.3 AVERAGE POWER

LIMIT

None; for reporting purposes only.

Test Configuration



TEST PROCEDURE

The transmitter output is connected to the Spectrum analyzer. The Spectrum analyzer is set to the average power detection.

TEST RESULTS

No non-compliance noted.

Test Data

Test mode: IEEE 802.11b mode

Channel	Frequency (MHz)	Output Power (dBm)
Low	2412	16.28
Mid	2437	16.58
High	2462	16.27

Test mode: IEEE 802.11g mode

Channel	Frequency (MHz)		Output Power (dBm)
Low	Base mode	2412	16.09
Mid		2437	16.19
High		2462	15.99
Mid	Turbo mode	2437	15.17



Test Plot

IEEE 802.11b mode

CH Low


Agilent 11:48:43 May 3, 2006

R L

AVG Output Power, b Mode Low Ch.

Ref 30 dBm

Atten 30 dB



Center 2.412 00 GHz

Span 22.97 MHz

#Res BW 1 MHz

#VBW 3 MHz

Sweep 1 ms (601 pts)

Channel Power

Power Spectral Density

16.28 dBm / 15.3140 MHz

-55.57 dBm/Hz

CH Mid


Agilent 12:14:53 May 3, 2006

R L

AVG Output Power, b Mode Mid Ch.

Ref 30 dBm

Atten 30 dB



Center 2.437 00 GHz

Span 22.95 MHz

#Res BW 1 MHz

#VBW 3 MHz

Sweep 1 ms (601 pts)

Channel Power

Power Spectral Density

16.58 dBm / 15.2970 MHz

-55.27 dBm/Hz



CH High


Agilent 11:59:04 May 3, 2006

L

AVG Output Power, b Mode High Ch.

Ref 30 dBm

Atten 30 dB



Center 2.462 00 GHz

Span 23.01 MHz

#Res BW 1 MHz

#VBW 3 MHz

Sweep 1 ms (601 pts)

Channel Power

Power Spectral Density

16.27 dBm / 15.3410 MHz

-55.59 dBm/Hz

IEEE 802.11g Base mode

CH Low


Agilent 12:34:17 May 3, 2006

R L

AVG Output Power, g Mode Low Ch.

Ref 30 dBm

Atten 30 dB



Center 2.412 00 GHz

Span 30 MHz

#Res BW 1 MHz

#VBW 3 MHz

Sweep 1 ms (601 pts)

Channel Power

Power Spectral Density

16.09 dBm / 20.0000 MHz

-56.92 dBm/Hz



CH Mid


Agilent 12:25:05 May 3, 2006

R L

AVG Output Power , g Mode Mid Ch.

Ref 30 dBm

Atten 30 dB



#PAvg

100

V1 S2

Center 2.437 00 GHz

#Res BW 1 MHz

#VBW 3 MHz

Span 24.9 MHz
Sweep 1 ms (601 pts)

Channel Power

Power Spectral Density

16.19 dBm / 16.5990 MHz

-56.01 dBm/Hz

CH High


Agilent 12:20:17 May 3, 2006

R L

AVG Output Power , g Mode High Ch.

Ref 30 dBm

Atten 30 dB



#PAvg

100

V1 S2

Center 2.462 00 GHz

#Res BW 1 MHz

#VBW 3 MHz

Span 24.85 MHz
Sweep 1 ms (601 pts)

Channel Power

Power Spectral Density

15.99 dBm / 16.5660 MHz

-56.20 dBm/Hz



IEEE 802.11g Turbo mode

CH Mid


Agilent 11:17:55 May 3, 2006

R L

avg Output Power , g turbo Mode Mid Ch.

Ref 30 dBm

Atten 30 dB



Channel Power

Power Spectral Density

15.17 dBm / 33.0310 MHz


-60.02 dBm/Hz

7.4 BAND EDGES MEASUREMENT

LIMIT

According to §15.247(d), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a) (see Section 15.205(c)).

Test Configuration



TEST PROCEDURE

1. The EUT is placed on a turntable, which is 0.8m above the ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
4. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:
 - (a) PEAK: RBW=VBW=1MHz / Sweep=AUTO
 - (b) AVERAGE: RBW=1MHz / VBW=10Hz / Sweep=AUTO
5. Repeat the procedures until all the PEAK and AVERAGE versus POLARIZATION are measured.


TEST RESULTS

Refer to attach spectrum analyzer data chart.

**Band Edges (IEEE 802.11b mode / CH Low)****Detector mode: Peak****Polarity: Vertical**


* Agilent 16:24:32 Apr 24, 2006

R T

**Detector mode: Average****Polarity: Vertical**

* Agilent 16:24:09 Apr 24, 2006

R T






Detector mode: Peak

Polarity: Horizontal

Agilent 16:29:29 Apr 24, 2006

R T




Detector mode: Average

Polarity: Horizontal

Agilent 16:29:09 Apr 24, 2006

R T






Band Edges (IEEE 802.11b mode / CH High)

Detector mode: Peak

Polarity: Vertical

Agilent 16:16:33 Apr 24, 2006

R T




Detector mode: Average

Polarity: Vertical

Agilent 16:16:06 Apr 24, 2006

R T






Detector mode: Peak

Polarity: Horizontal

Agilent 16:14:03 Apr 24, 2006

R T




Detector mode: Average

Polarity: Horizontal

Agilent 16:13:38 Apr 24, 2006

R T






Band Edges (IEEE 802.11g Base mode / CH Low)

Detector mode: Peak

Polarity: Vertical

Agilent 16:43:16 Apr 24, 2006

R T




Detector mode: Average

Polarity: Vertical

Agilent 16:42:56 Apr 24, 2006

R T






Detector mode: Peak

Polarity: Horizontal

Agilent 16:35:11 Apr 24, 2006

R T




Detector mode: Average

Polarity: Horizontal

Agilent 16:34:49 Apr 24, 2006

R T






Band Edges (IEEE 802.11g Base mode / CH High)

Detector mode: Peak

Polarity: Vertical

Agilent 16:59:55 Apr 24, 2006

R T




Detector mode: Average

Polarity: Vertical

Agilent 16:59:33 Apr 24, 2006

R T






Detector mode: Peak

Polarity: Horizontal

Agilent 16:50:31 Apr 24, 2006

R T




Detector mode: Average

Polarity: Horizontal

Agilent 16:49:01 Apr 24, 2006

R T





Band Edges (IEEE 802.11g Turbo mode / CH Mid)

Detector mode: Peak

Polarity: Vertical

Agilent 20:50:52 Apr 24, 2006

R T

Mkr1 2.390 0 GHz

56.19 dB μ V

Ref 133 dB μ V

#Atten 20 dB

#Peak

Log

10

dB/

Offst

16

dB

DI

74.0

dB μ V

LgAv

M1 S2

S3 FC

A AA

*(f):

FTun

Swp

Start 2.310 0 GHz

#Res BW 1 MHz

VBW 1 MHz

Stop 2.445 0 GHz

#Sweep 100 ms (601 pts)

Detector mode: Average

Polarity: Vertical

Agilent 20:49:56 Apr 24, 2006

R T

Mkr1 2.390 0 GHz

43.30 dB μ V

Ref 133 dB μ V

#Atten 20 dB

#Peak

Log

10

dB/

Offst

16

dB

DI

54.0

dB μ V

LgAv

M1 S2

S3 FC

A AA

*(f):

FTun

Swp

Start 2.310 0 GHz

#Res BW 1 MHz

#VBW 10 Hz

Stop 2.445 0 GHz

Sweep 10.53 s (601 pts)




Detector mode: Peak

Polarity: Horizontal

Agilent 20:43:45 Apr 24, 2006

R T



Detector mode: Average

Polarity: Horizontal

Agilent 20:43:22 Apr 24, 2006

R T






Band Edges (IEEE 802.11g Turbo mode / CH Mid)

Detector mode: Peak

Polarity: Vertical

Agilent 21:01:15 Apr 24, 2006

R T




Detector mode: Average

Polarity: Vertical

Agilent 21:00:53 Apr 24, 2006

R T






Detector mode: Peak

Polarity: Horizontal

Agilent 20:55:02 Apr 24, 2006

R T

Mkr1 2.483 50 GHz
65.63 dB μ V



Detector mode: Average

Polarity: Horizontal

Agilent 20:54:38 Apr 24, 2006

R T

Mkr1 2.483 50 GHz
49.32 dB μ V






7.5 PEAK POWER SPECTRAL DENSITY

LIMIT

1. According to §15.247(e), for digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.
2. According to §15.247(f), the digital modulation operation of the hybrid system, with the frequency hopping turned off, shall comply with the power density requirements of paragraph (d) of this section.

Test Configuration



TEST PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.
Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
2. Set the spectrum analyzer as RBW = 3 kHz, VBW = 10 kHz, Span = 300 kHz, Sweep = 100 s
3. Record the max reading.
4. Repeat the above procedure until the measurements for all frequencies are completed.



TEST RESULTS

No non-compliance noted

Test Data

Test mode: IEEE 802.11b mode

Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Result
Low	2412	-5.89	8.00	PASS
Mid	2437	-5.75		PASS
High	2462	-3.92		PASS

Test mode: IEEE 802.11g mode


Channel	Frequency (MHz)		PPSD (dBm)	Limit (dBm)	Result
Low	Base mode	2412	-8.20	8.00	PASS
Mid		2437	-7.82		PASS
High		2462	-8.06		PASS
Mid	Turbo mode	2437	-10.22		PASS




Test Plot

IEEE 802.11b mode

PPSD (CH Low)



PPSD (CH Mid)



**PPSD (CH High)**

* Agilent 18:48:22 May 2, 2006

R T


Peak Power Spectral Density, b Mode High Ch.

Mkr1 2.464 998 4 GHz

Ref 20 dBm

Atten 20 dB

-3.92 dBm



Center 2.465 050 0 GHz

Span 300 kHz

#Res BW 3 kHz

#VBW 10 kHz

#Sweep 100 s (601 pts)

IEEE 802.11g Base mode**PPSD (CH Low)**

* Agilent 19:25:41 May 2, 2006

R T


Peak Power Spectral Density, g Mode Low Ch.

Mkr1 2.405 059 3 GHz

Ref 20 dBm

Atten 20 dB

-8.20 dBm



Center 2.405 100 0 GHz

Span 300 kHz

#Res BW 3 kHz

#VBW 10 kHz

#Sweep 100 s (601 pts)



PPSD (CH Mid)

Agilent 10:35:31 May 3, 2006

R T


Peak Power Spectral Density, g Mode Mid Ch.

Mkr1 2.438 581 2 GHz

Ref 20 dBm

Atten 20 dB

-7.82 dBm



Center 2.438 500 0 GHz

Span 300 kHz

#Res BW 3 kHz

#VBW 10 kHz

#Sweep 100 s (601 pts)

PPSD (CH High)

Agilent 11:04:03 May 3, 2006

R L


Peak Power Spectral Density, g Mode High Ch.

Mkr1 2.464 472 4 GHz

Ref 20 dBm

Atten 20 dB

-8.06 dBm



Center 2.464 500 0 GHz

Span 300 kHz

#Res BW 3 kHz

#VBW 10 kHz

#Sweep 100 s (601 pts)



IEEE 802.11g Turbo mode

CH Mid

Agilent 11:20:43 May 3, 2006

R L

Mkr1 2.441 954 5 GHz

-10.22 dBm

Ref 20 dBm

Atten 20 dB

#Peak

Log

10

dB/

Offst

16

dB

DI

8.0

dBm

LgAv

W1 S2

S3 FS

$\alpha(f)$:

f>50k

Swp


Center 2.441 950 0 GHz

#Res BW 3 kHz

#VBW 10 kHz

Span 300 kHz

#Sweep 100 s (601 pts)






7.6 SPURIOUS EMISSIONS

7.6.1 Conducted Measurement

LIMIT

According to §15.247(d), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a) (see Section 15.205(c)).

Test Configuration



TEST PROCEDURE

Conducted RF measurements of the transmitter output were made to confirm that the EUT antenna port conducted emissions meet the specified limit and to identify any spurious signals that require further investigation or measurements on the radiated emissions site.

The transmitter output is connected to the spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 100 kHz.

Measurements are made over the 30MHz to 26GHz range with the transmitter set to the lowest, middle, and highest channels.

TEST RESULTS

No non-compliance noted

**Test Plot****IEEE 802.11b mode****CH Low**

* Agilent 18:33:51 May 2, 2006

R T


Spurious, b Mode Low Ch.

Mkr2 340 MHz

Ref 20 dBm

Atten 20 dB

-51.41 dBm



Center 13.02 GHz

Span 25.97 GHz

#Res BW 100 kHz

#VBW 100 kHz

Sweep 3.131 s (1001 pts)

Marker	Trace	Type	X Axis	Amplitude
1	(1)	Freq	2.42 GHz	7.39 dBm
2	(1)	Freq	340 MHz	-51.41 dBm

CH Mid

* Agilent 18:40:54 May 2, 2006

R T


Spurious, b Mode Mid Ch.

Mkr2 340 MHz

Ref 20 dBm

Atten 20 dB

-52.97 dBm



Center 13.02 GHz

Span 25.97 GHz

#Res BW 100 kHz

#VBW 100 kHz

Sweep 3.131 s (1001 pts)

Marker	Trace	Type	X Axis	Amplitude
1	(1)	Freq	2.45 GHz	6.81 dBm
2	(1)	Freq	340 MHz	-52.97 dBm

**CH High**

* Agilent 18:49:46 May 2, 2006

R T


Spurious, b Mode High Ch.

Mkr2 340 MHz

Ref 20 dBm

Atten 20 dB

-51.01 dBm



Center 13.02 GHz

Span 25.97 GHz

#Res BW 100 kHz

#VBW 100 kHz

Sweep 3.131 s (1001 pts)

Marker	Trace	Type	X Axis	Amplitude
1	(1)	Freq	2.47 GHz	7.56 dBm
2	(1)	Freq	340 MHz	-51.01 dBm

IEEE 802.11g Base mode**CH Low**

* Agilent 19:26:39 May 2, 2006

L


Spurious, g Mode Low Ch.

Mkr1 2.42 GHz

Ref 20 dBm

Atten 20 dB

4.13 dBm



Center 13.02 GHz

Span 25.97 GHz

#Res BW 100 kHz

#VBW 100 kHz


Sweep 3.131 s (1001 pts)



CH Mid

Agilent 10:44:16 May 3, 2006

R L




CH High

Agilent 11:04:59 May 3, 2006

L

Spurious, g Mode High Ch.





IEEE 802.11g Turbo mode

CH Mid

Agilent 11:22:37 May 3, 2006

L


Spurious, g turbo Mode Mid Ch.

Mkr1 2.45 GHz

Ref 20 dBm

Atten 20 dB

3.00 dBm



Center 13.02 GHz

Span 25.97 GHz

#Res BW 100 kHz

#VBW 100 kHz

Sweep 3.131 s (1001 pts)



7.6.2 RADIATED EMISSIONS

LIMIT

1. According to §15.209(a), except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V/m}$)	Measurement Distance (m)
30-88	100*	3
88-216	150*	3
216-960	200*	3
Above 960	500	3


Remark: Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

2. In the emission table above, the tighter limit applies at the band edges.


Frequency (MHz)	Field Strength ($\mu\text{V/m}$ at 3-meter)	Field Strength (dB $\mu\text{V/m}$ at 3-meter)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

Test Configuration

Below 1 GHz



Above 1 GHz





TEST PROCEDURE

1. The EUT is placed on a turntable, which is 0.8m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Set the spectrum analyzer in the following setting as:
Below 1GHz:
RBW=100kHz / VBW=300kHz / Sweep=AUTO
Above 1GHz:
(a) PEAK: RBW=VBW=1MHz / Sweep=AUTO
(b) AVERAGE: RBW=1MHz / VBW=10Hz / Sweep=AUTO
7. Repeat above procedures until the measurements for all frequencies are complete.



TEST RESULTS

Below 1GHz

Operation Mode: Normal Link**Test Date:** April 25, 2006**Temperature:** 23°C**Tested by:** Rex Lai**Humidity:** 56% RH**Polarity:** Ver. / Hor.

Frequency (MHz)	Ant.Pol. (H/V)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
125.38	V	61.02	-27.99	33.04	43.50	-10.46	Peak
498.83	V	58.01	-24.43	33.58	46.00	-12.42	Peak
600.68	V	62.30	-22.93	39.37	46.00	-6.63	Peak
749.42	V	58.35	-21.08	37.28	46.00	-8.72	Peak
799.53	V	58.99	-20.54	38.45	46.00	-7.55	Peak
998.38	V	60.49	-18.14	42.35	54.00	-11.65	Peak
128.62	H	58.31	-27.54	30.77	43.50	-12.73	Peak
165.80	H	60.19	-29.49	30.70	43.50	-12.80	Peak
233.70	H	64.90	-31.00	33.90	46.00	-12.10	Peak
364.65	H	61.64	-28.11	33.52	46.00	-12.48	Peak
600.68	H	58.78	-22.93	35.85	46.00	-10.15	Peak
799.53	H	55.46	-20.54	34.92	46.00	-11.08	Peak

Remark:

1. Measuring frequencies from 30 MHz to the 1GHz.
2. Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using peak/quasi-peak detector mode.
3. Quasi-peak test would be performed if the peak result were greater than the quasi-peak limit or as required by the applicant.
4. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
5. Margin (dB) = Remark result (dBuV/m) – Quasi-peak limit (dBuV/m).

**Above 1 GHz****Operation Mode:** TX / IEEE 802.11b mode / CH Low**Test Date:** April 24, 2006**Temperature:** 24°C**Tested by:** Skyman Tsai**Humidity:** 57 % RH**Polarity:** Ver. / Hor.

Frequency (MHz)	Ant. Pol. (H/V)	Reading (Peak) (dBuV)	Reading (Average) (dBuV)	Correction Factor (dB/m)	Result (Peak) (dBuV/m)	Result (Average) (dBuV/m)	Limit (Peak) (dBuV/m)	Limit (Average) (dBuV/m)	Margin (dB)	Remark
1503.33	V	64.33	---	-13.90	50.43	---	74.00	54.00	-3.57	Peak
3616.67	V	53.84	---	-9.05	44.79	---	74.00	54.00	-9.21	Peak
4825.00	V	53.21	---	-7.80	45.41	---	74.00	54.00	-8.59	Peak
7241.67	V	61.41	52.02	-5.69	55.72	46.33	74.00	54.00	-7.67	AVG
N/A										
1203.33	H	71.09	50.15	-14.51	56.58	35.64	74.00	54.00	-18.36	AVG
4825.00	H	52.32	---	-7.80	44.52	---	74.00	54.00	-9.48	Peak
7233.33	H	57.73	---	-5.70	52.03	---	74.00	54.00	-1.97	Peak
N/A										

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).

**Operation Mode:** TX / IEEE 802.11b mode / CH Mid**Test Date:** April 24, 2006**Temperature:** 24°C**Tested by:** Skyman Tsai**Humidity:** 57 % RH**Polarity:** Ver. / Hor.

Frequency (MHz)	Ant. Pol. (H/V)	Reading (Peak) (dBuV)	Reading (Average) (dBuV)	Correction Factor (dB/m)	Result (Peak) (dBuV/m)	Result (Average) (dBuV/m)	Limit (Peak) (dBuV/m)	Limit (Average) (dBuV/m)	Margin (dB)	Remark
1220.00	V	73.58	50.32	-14.47	59.11	35.85	74.00	54.00	-18.15	AVG
7316.67	V	59.44	51.67	-5.64	53.80	46.03	74.00	54.00	-7.97	AVG
N/A										
1230.00	H	75.84	50.46	-14.45	61.39	36.01	74.00	54.00	-17.99	AVG
3666.67	H	61.95	35.09	-8.98	52.97	26.11	74.00	54.00	-27.89	AVG
7316.67	H	59.92	49.50	-5.64	54.28	43.86	74.00	54.00	-10.14	AVG
N/A										

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser; with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).

**Operation Mode:** TX / IEEE 802.11b mode / CH High**Test Date:** April 24, 2006**Temperature:** 24°C**Tested by:** Skyman Tsai**Humidity:** 57 % RH**Polarity:** Ver. / Hor.

Frequency (MHz)	Ant. Pol. (H/V)	Reading (Peak) (dBuV)	Reading (Average) (dBuV)	Correction Factor (dB/m)	Result (Peak) (dBuV/m)	Result (Average) (dBuV/m)	Limit (Peak) (dBuV/m)	Limit (Average) (dBuV/m)	Margin (dB)	Remark
1236.67	V	74.89	50.27	-14.44	60.45	35.83	74.00	54.00	-18.17	AVG
3691.67	V	68.33	35.15	-8.94	59.39	26.21	74.00	54.00	-27.79	AVG
4925.00	V	58.09	---	-7.78	50.31	---	74.00	54.00	-3.69	Peak
7383.33	V	57.46	---	-5.59	51.87	---	74.00	54.00	-2.13	Peak
N/A										
1243.33	H	77.35	50.47	-14.43	62.92	36.04	74.00	54.00	-17.96	AVG
3691.67	H	66.96	35.09	-8.94	58.02	26.15	74.00	54.00	-27.85	AVG
4925.00	H	54.75	---	-7.78	46.97	---	74.00	54.00	-7.03	Peak
7391.67	H	60.39	50.91	-5.58	54.81	45.33	74.00	54.00	-8.67	AVG
N/A										

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).

**Operation Mode:** TX / IEEE 802.11g Base mode / CH Low **Test Date:** April 24, 2006**Temperature:** 24°C**Tested by:** Skyman Tsai**Humidity:** 57 % RH**Polarity:** Ver. / Hor.

Frequency (MHz)	Ant. Pol. (H/V)	Reading (Peak) (dBuV)	Reading (Average) (dBuV)	Correction Factor (dB/m)	Result (Peak) (dBuV/m)	Result (Average) (dBuV/m)	Limit (Peak) (dBuV/m)	Limit (Average) (dBuV/m)	Margin (dB)	Remark
1213.33	V	69.67	50.73	-14.49	55.18	36.24	74.00	54.00	-17.76	AVG
3625.00	V	68.92	37.02	-9.04	59.88	27.98	74.00	54.00	-26.02	AVG
4816.67	V	52.34	---	-7.80	44.55	---	74.00	54.00	-9.45	Peak
7241.67	V	65.76	51.67	-5.69	60.07	45.98	74.00	54.00	-8.02	AVG
N/A										
1210.00	H	75.99	52.04	-14.49	61.50	37.55	74.00	54.00	-16.45	AVG
3616.67	H	69.89	36.99	-9.05	60.84	27.94	74.00	54.00	-26.06	AVG
7241.67	H	58.33	44.94	-5.69	52.64	39.25	74.00	54.00	-14.75	AVG
N/A										

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).

**Operation Mode:** TX / IEEE 802.11g Base mode / CH Mid **Test Date:** April 24, 2006**Temperature:** 24°C**Tested by:** Skyman Tsai**Humidity:** 57 % RH**Polarity:** Ver. / Hor.

Frequency (MHz)	Ant. Pol. (H/V)	Reading (Peak) (dBuV)	Reading (Average) (dBuV)	Correction Factor (dB/m)	Result (Peak) (dBuV/m)	Result (Average) (dBuV/m)	Limit (Peak) (dBuV/m)	Limit (Average) (dBuV/m)	Margin (dB)	Remark
1223.33	V	74.92	53.21	-14.47	60.45	38.74	74.00	54.00	-15.26	AVG
3658.33	V	69.27	41.67	-8.99	60.28	32.68	74.00	54.00	-21.32	AVG
7316.67	V	59.59	45.92	-5.64	53.95	40.28	74.00	54.00	-13.72	AVG
N/A										
1223.33	H	78.64	54.24	-14.47	64.17	39.77	74.00	54.00	-14.23	AVG
3650.00	H	67.96	41.04	-9.00	58.96	32.04	74.00	54.00	-21.96	AVG
7316.67	H	60.50	46.86	-5.64	54.86	41.22	74.00	54.00	-12.78	AVG
N/A										

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser; with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).

**Operation Mode:** TX / IEEE 802.11g Base mode / CH High **Test Date:** April 24, 2006**Temperature:** 24°C**Tested by:** Skyman Tsai**Humidity:** 57 % RH**Polarity:** Ver. / Hor.

Frequency (MHz)	Ant. Pol. (H/V)	Reading (Peak) (dBuV)	Reading (Average) (dBuV)	Correction Factor (dB/m)	Result (Peak) (dBuV/m)	Result (Average) (dBuV/m)	Limit (Peak) (dBuV/m)	Limit (Average) (dBuV/m)	Margin (dB)	Remark
1230.00	V	71.64	51.62	-14.45	57.19	37.17	74.00	54.00	-16.83	AVG
3691.67	V	69.10	40.14	-8.94	60.16	31.20	74.00	54.00	-22.80	AVG
7383.33	V	55.49	41.42	-5.59	49.90	35.83	74.00	54.00	-18.17	AVG
N/A										
1230.00	H	77.02	52.46	-14.45	62.57	38.01	74.00	54.00	-15.99	AVG
3691.67	H	69.27	40.08	-8.94	60.33	31.14	74.00	54.00	-22.86	AVG
7391.67	H	58.95	45.34	-5.58	53.37	39.76	74.00	54.00	-14.24	AVG
N/A										

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser; with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).

**Operation Mode:** Tx / IEEE 802.11g Turbo mode / CH Mid **Test Date:** April 24, 2006**Temperature:** 24°C**Tested by:** Skyman Tsai**Humidity:** 57% RH**Polarity:** Ver. / Hor.

Frequency (MHz)	Ant.Pol. (H/V)	Reading (Peak) (dBuV)	Reading (Average) (dBuV)	Correction Factor (dB/m)	Result (Peak) (dBuV/m)	Result (Average) (dBuV/m)	Limit (Peak) (dBuV/m)	Limit (Average) (dBuV/m)	Margin (dB)	Remark
1226.67	V	69.27	50.60	-14.46	54.81	36.14	74.00	54.00	-17.86	AVG
3658.33	V	65.91	36.66	-8.99	56.92	27.67	74.00	54.00	-26.33	AVG
7308.33	V	57.12	---	-5.64	51.48	---	74.00	54.00	-2.52	Peak
N/A										
1236.67	H	75.06	50.95	-14.44	60.62	36.51	74.00	54.00	-17.49	AVG
3675.00	H	68.82	37.01	-8.96	59.86	28.05	74.00	54.00	-25.95	AVG
7300.00	H	57.57	---	-5.65	51.92	---	74.00	54.00	-2.08	Peak
N/A										

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser; with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



7.7 POWERLINE CONDUCTED EMISSIONS

LIMIT

According to §15.207(a), except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency Range (MHz)	Limits (dB μ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56*	56 to 46*
0.50 to 5	56	46
5 to 30	60	50

* Decreases with the logarithm of the frequency.

Test Configuration

See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

TEST PROCEDURE

1. The EUT was placed on a table, which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured were complete.

**TEST RESULTS**

The initial step in collecting conducted data is a spectrum analyzer peak scan of the measurement range. Significant peaks are then marked as shown on the following data page, and these signals are then quasi-peaked.

Test Data

Operation Mode: Normal Link **Test Date:** May 4, 2006
Temperature: 25°C **Tested by:** Ivan Tsai
Humidity: 55% RH

Freq. (MHz)	QP Reading (dBuV)	AV Reading (dBuV)	Corr. factor (dB)	QP Result (dBuV)	AV Result (dBuV)	QP Limit (dBuV)	AV Limit (dBuV)	QP Margin (dB)	AV Margin (dB)	Note
0.246	45.010	41.150	0.100	45.110	41.250	61.891	51.891	-16.781	-10.641	L1
0.369	45.840	41.150	0.100	45.940	41.250	58.523	48.523	-12.583	-7.273	L1
0.491	42.890	36.910	0.100	42.990	37.010	56.158	46.158	-13.168	-9.148	L1
0.732	47.510	39.790	0.100	47.610	39.890	56.000	46.000	-8.390	-6.110	L1
0.885	42.020	31.200	0.100	42.120	31.300	56.000	46.000	-13.880	-14.700	L1
10.503	49.490	42.320	0.710	50.200	43.030	60.000	50.000	-9.800	-6.970	L1
0.248	44.060	40.550	0.100	44.160	40.650	61.824	51.824	-17.664	-11.174	L2
0.372	42.500	38.010	0.100	42.600	38.110	58.456	48.456	-15.856	-10.346	L2
0.496	42.180	35.510	0.100	42.280	35.610	56.067	46.067	-13.787	-10.457	L2
0.738	49.090	42.320	0.100	49.190	42.420	56.000	46.000	-6.810	-3.580	L2
0.856	48.550	40.270	0.100	48.650	40.370	56.000	46.000	-7.350	-5.630	L2
7.985	46.720	39.720	0.498	47.218	40.218	60.000	50.000	-12.782	-9.782	L2


Remark:

1. Measuring frequencies from 0.15 MHz to 30MHz.
2. The emissions measured in frequency range from 0.15 MHz to 30MHz were made with an instrument using Quasi-peak detector and average detector.
3. The IF bandwidth of SPA between 0.15MHz and 30MHz was 10 kHz; the IF bandwidth of Test Receiver between 0.15MHz and 30MHz was 9 kHz;
4. L1 = Line One (Live Line) / L2 = Line Two (Neutral Line)




Test Plots

Conducted emissions (Line 1)



Conducted emissions (Line 2)





APPENDIX I

RADIO FREQUENCY EXPOSURE

LIMIT

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this chapter.

EUT Specification

EUT	Wireless Lan Cardbus Card
Frequency band (Operating)	☒ WLAN: 2.412GHz ~ 2.462GHz ☐ WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz ☐ WLAN: 5.745GHz ~ 5.825GHz ☐ Others
Device category	☒ Portable (<20cm separation) ☐ Mobile (>20cm separation) ☐ Others
Exposure classification	☐ Occupational/Controlled exposure ($S = 5\text{mW}/\text{cm}^2$) ☒ General Population/Uncontrolled exposure ($S=1\text{mW}/\text{cm}^2$)
Antenna diversity	☐ Single antenna ☒ Multiple antennas ☐ Tx diversity ☐ Rx diversity ☒ Tx/Rx diversity
Max. output power	IEEE 802.11b mode: 19.08 dBm (80.91mW) IEEE 802.11g mode: 18.95 dBm (78.52mW)
Antenna gain (Max)	1.66 dBi (Numeric gain: 1.47)
Evaluation applied	☐ MPE Evaluation ☒ SAR Evaluation*

Remark:

1. The maximum output power is 19.08dBm (80.91mW) at 2437MHz (with 1.47 numeric antenna gain.)
2. DTS device is not subject to routine RF evaluation; MPE estimate is used to justify the compliance.
3. For mobile or fixed location transmitters, no SAR consideration applied. The maximum power density is $1.0\text{ mW}/\text{cm}^2$ even if the calculation indicates that the power density would be larger.

TEST RESULTS

No non-compliance noted.

Remark: Please refer to the separated SAR report.

MPE evaluation

Not applicable.