

Test Method:	FCC Part 15 Subpart C Radiated Emissions, Fundamental & Harmonic Emissions						
Customer:	Symbol Technologies				Job No.	R-8427-1	
Test Sample:	Continuous 2.4GHz RF Transmitter				Paragraph:	15.209(a)	
Model No.:	PDT6844				FCC ID:	H9P	
Operating Mode:	Continuously Transmitting a 2.4 GHz Signal						
Technician:	P.Lananna				Date:	March 2, 2000	
Notes:	Test Distance: 3 Meters Detector: Peak, Unless otherwise specified						
Test Freq.	Antenna Pol./Height	EUT Orientation	Meter Reading	Correction Factor	Corrected Reading	Converted Reading	Average Limit
GHz	(V/H)/Meters	X / Y / Z	DBuV	dB	dBuV/m	uV/m	uV/m
2.4819	H / 1.7	X	40.8	31.5	72.3	4121.0	50000
	H / 1.0	Y	47.3	31.5	78.8	8709.6	
	H / 1.5	Z	42.3	31.5	73.8	4897.8	
	V / 1.0	X	39.7	31.5	71.2	3630.8	
	V / 1.5	Y	44.7	31.5	76.2	6456.5	
2.4819	V / 1.5	Z	45.2	31.5	76.7	6839.1	50000
4.963	H / 1.0	X	45.1	-6.5	38.6	85.1	500
	H / 1.0	Y	42.6	-6.5	36.1	63.8	
	H / 1.0	Z	44.6	-6.5	38.1	80.3	
	V / 1.0	X	44.1	-6.5	37.6	75.9	
	V / 1.0	Y	48.7	-6.5	42.2	128.8	
4.963	V / 1.0	Z	43.8	-6.5	37.3	73.3	500
7.445	H /	X	30.9	-5.4	25.5	18.8*	500
	H /	Y	30.9	-5.4	25.5	18.8*	
	H /	Z	30.9	-5.4	25.5	18.8*	
	V /	X	30.9	-5.4	25.5	18.8*	
	V /	Y	30.9	-5.4	25.5	18.8*	
7.445	V /	Z	30.9	-5.4	25.5	18.8*	500
9.927	H /	X	35.0	-2.6	32.4	41.7*	500
	H /	Y	35.0	-2.6	32.4	41.7*	
	H /	Z	35.0	-2.6	32.4	41.7*	
	V /	X	35.0	-2.6	32.4	41.7*	
	V /	Y	35.0	-2.6	32.4	41.7*	
9.927	V /	Z	35.0	-2.6	32.4	41.7*	500
12.409	H /	X	35.0	0	35	56.2*	500
	H /	Y	35.0	0	35	56.2*	
	H /	Z	35.0	0	35	56.2*	
	V /	X	35.0	0	35	56.2*	
	V /	Y	35.0	0	35	56.2*	
12.409	V /	Z	35.0	0	35	56.2*	500
	The frequency range was scanned from 30 MHz to25GHz. All emissions not recorded were more						
	Than 10 dB below the specified limit. Emissions from the EUT do not exceed the specified limits.						
	*=Noise Floor Measurements (Minimum system sensitivity)						



Retlif Testing Laboratories

Retlif Job Number R-8427-1

Test Method:		FCC Part 15 Subpart C Radiated Emissions, Fundamental & Harmonic Emissions					
Customer:		Symbol Technologies			Job No.		R-8427-1
Test Sample:		Continuos 2.4GHz RF Transmitter			Paragraph:		15.209(a)
Model No.:		PDT6844			FCC ID:		H9P
Operating Mode:		Continuously Transmitting a 2.4 GHz Signal					
Technician:		P. Lananna			Date:		March 2, 2000
Notes: Test Distance: 3 Meters, **= Readings taken @ 1 meter correction factor includes test distance correction. Detector: Peak, unless otherwise specified							
Test Freq.	Antenna Pol./Height	EUT Orientation	Meter Reading	Correction Factor	Corrected Reading	Converted Reading	Average Limit
GHz	(V/H)-Meters	X / Y / Z	dBuV	dB	dBuV/m	uV/m	uV/m
14.891	H /	X	30.2	1.5	31.7	38.5*	500
	H /	Y	30.2	1.5	31.7	38.5*	
	H /	Z	30.2	1.5	31.7	38.5*	
	V /	X	30.2	1.5	31.7	38.5*	
	V /	Y	30.2	1.5	31.7	38.5*	
14.891	V /	Z	30.2	1.5	31.7	38.5*	500
17.373	H /	X	25.0	5.9	30.9	35.1*	500
	H /	Y	25.0	5.9	30.9	35.1*	
	H /	Z	25.0	5.9	30.9	35.1*	
	V /	X	25.0	5.9	30.9	35.1*	
	V /	Y	25.0	5.9	30.9	35.1*	
17.373	V /	Z	25.0	5.9	30.9	35.1*	500
19.855	H /	X	29.0	22.9**	51.9	393.6*	500
	H /	Y	29.0	22.9**	51.9	393.6*	
	H /	Z	29.0	22.9**	51.9	393.6*	
	V /	X	29.0	22.9**	51.9	393.6*	
	V /	Y	29.0	22.9**	51.9	393.6*	
19.855	V /	Z	29.0	22.9**	51.9	393.6*	500
22.337	H /	X	26.0	23.2**	49.2	288.4*	500
	H /	Y	26.0	23.2**	49.2	288.4*	
	H /	Z	26.0	23.2**	49.2	288.4*	
	V /	X	26.0	23.2**	49.2	288.4*	
	V /	Y	26.0	23.2**	49.2	288.4*	
22.337	V /	Z	26.0	23.2**	49.2	288.4*	500
24.818	H /	X	25.0	23.4**	48.4	263.0*	500
	H /	Y	25.0	23.4**	48.4	263.0*	
	H /	Z	25.0	23.4**	48.4	263.0*	
	V /	X	25.0	23.4**	48.4	263.0*	
	V /	Y	25.0	23.4**	48.4	263.0*	
24.818	V /	Z	25.0	23.4**	48.4	263.0*	500
	The frequency range was scanned from 30 MHz to 25 GHz. All emissions not recorded were more						
	Than 10 dB below the specified limit. Emissions from the EUT do not exceed the specified limits.						
	*=Noise Floor Measurements (Minimum system sensitivity)						



Retlif Testing Laboratories

Retlif Job Number R-8427-1


Test Method:	FCC Part 15 Subpart C Radiated Emissions, Fundamental & Harmonic Emissions						
Customer:				Job No.			
Test Sample:				Paragraph:			
Model No.:				FCC ID:			
Operating Mode:	Continuously Transmitting a MHz Signal						
Technician:				Date:			
Notes:	Test Distance: 3 Meters			Duty Cycle:			
	Detector: Peak, unless otherwise specified			Duty Cycle Correction: - dB			
Test Freq.	Antenna Pol./Height	EUT Orientation	Peak Reading	Correction Factor	Corrected Reading	Converted Reading	Avg. Limit
MHz	(V/H)-Meters	X / Y / Z	dBuV	dB	dBuV/m	uV/m	uV/m
	H /	X					
	H /	Y					
	H /	Z					
	V /	X					
	V /	Y					
	V /	Z					
	H /	X					
	H /	Y					
	H /	Z					
	V /	X					
	V /	Y					
	V /	Z					
	H /	X					
	H /	Y					
	H /	Z					
	V /	X					
	V /	Y					
	V /	Z					
	H /	X					
	H /	Y					
	H /	Z					
	V /	X					
	V /	Y					
	V /	Z					
	H /	X					
	H /	Y					
	H /	Z					
	V /	X					
	V /	Y					
	V /	Z					
	H /	X					
	H /	Y					
	H /	Z					
	V /	X					
	V /	Y					
	V /	Z					
The frequency range was scanned from 30 MHz to XX GHz. All emissions not recorded were more							
Than 10 dB below the specified limit. Emissions from the EUT do not exceed the specified limits.							
*=Noise Floor Measurements (Minimum system sensitivity)							



Retlif Testing Laboratories

Retlif Job Number R-

Test Method:	FCC Part 15 Subpart C Radiated Emissions, Fundamental & Harmonic Emissions						
Customer:				Job No.			
Test Sample:				Paragraph:			
Model No.:				FCC ID:	N/A		
Operating Mode:	Continuously Transmitting a MHz Signal						
Technician:				Date:			
Notes:	Test Distance: 3 Meters			Duty Cycle:			
	Detector: Peak, unless otherwise specified			Duty Cycle Correction: - dB			
Test Freq.	Antenna Pol./Height	EUT Orientation	Peak Reading	Correction Factor	Corrected Reading	Converted Reading	Avg. Limit
MHz	(V/H)-Meters	X / Y / Z	dBuV	dB	dBuV/m	uV/m	uV/m
	H /	X					
	H /	Y					
	H /	Z					
	V /	X					
	V /	Y					
	V /	Z					
	H /	X					
	H /	Y					
	H /	Z					
	V /	X					
	V /	Y					
	V /	Z					
	H /	X					
	H /	Y					
	H /	Z					
	V /	X					
	V /	Y					
	V /	Z					
	H /	X					
	H /	Y					
	H /	Z					
	V /	X					
	V /	Y					
	V /	Z					
	H /	X					
	H /	Y					
	H /	Z					
	V /	X					
	V /	Y					
	V /	Z					
	H /	X					
	H /	Y					
	H /	Z					
	V /	X					
	V /	Y					
	V /	Z					
The frequency range was scanned from 30 MHz to XX GHz. All emissions not recorded were more							
Than 10 dB below the specified limit. Emissions from the EUT do not exceed the specified limits.							
*=Noise Floor Measurements (Minimum system sensitivity)							



Retlif Testing Laboratories

Retlif Job Number R-