

Prüfbericht-Nr.: <i>Test report no.:</i>	CN26I79B 003	Auftrags-Nr.: <i>Order no.:</i>	168588505	Seite 1 von 7 Page 1 of 7
Kunden-Referenz-Nr.: <i>Client reference no.:</i>	N/A	Auftragsdatum: <i>Order date:</i>	2025-12-11	
Auftraggeber: <i>Client:</i>	SHENZHEN FENDA TECHNOLOGY CO., LTD. Fenda Hi-Tech Park, Zhoushi Road, Shiyao Town, Baoan District, Shenzhen City, Guangdong, China.			
Prüfgegenstand: <i>Test item:</i>	Portable Bluetooth Speaker			
Bezeichnung / Typ-Nr.: <i>Identification / Type no.:</i>	WEBOOM, WeBOOM (Trademark: Hisense)			
Auftrags-Inhalt: <i>Order content:</i>	Test Report			
Prüfgrundlage: <i>Test specification:</i>	CFR Title 47 FCC Part 2: Section 2.1093 FCC KDB Publication 447498 D01 IC RSS-102 Issue 6: December 2023			
Wareneingangsdatum: <i>Date of sample receipt:</i>	2025-12-08	Please refer to photo documents		
Prüfmuster-Nr.: <i>Test sample no.:</i>	A004156484-005			
Prüfzeitraum: <i>Testing period:</i>	2026-01-16			
Ort der Prüfung: <i>Place of testing:</i>	TÜV Rheinland (Shenzhen) Co., Ltd.			
Prüflaboratorium: <i>Testing laboratory:</i>	TÜV Rheinland (Shenzhen) Co., Ltd.			
Prüfergebnis*: <i>Test result*:</i>	Pass			
geprüft von: <i>tested by:</i>	genehmigt von: <i>authorized by:</i>			
Datum: <i>Date:</i>	Ausstellungsdatum: <i>Issue date:</i>			
Stellung / Position:	Stellung / Position:			
Sonstiges / <i>Other:</i>	FCC ID: HBOBS2622 IC: 10550A-BS2622 HVIN: WEBOOM			
Zustand des Prüfgegenstandes bei Anlieferung: <i>Condition of the test item at delivery:</i>		Prüfmuster vollständig und unbeschädigt <i>Test item complete and undamaged</i>		
* Legende: P(ass) = entspricht o.g. Prüfgrundlage(n) F(ail) = entspricht nicht o.g. Prüfgrundlage(n) N/A = nicht anwendbar N/T = nicht getestet * Legend: P(ass) = passed a.m. test specification(s) F(ail) = failed a.m. test specification(s) N/A = not applicable N/T = not tested				
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report only relates to the above mentioned test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>				

Prüfbericht-Nr.: CN26I79B 003
Test report no.:

Seite 2 von 7
Page 2 of 7

Anmerkungen
Remarks

1	Alle eingesetzten Prüfmittel waren zum angegebenen Prüfzeitraum gemäß eines festgelegten Kalibrierungsprogramms unseres Prüfhauses kalibriert. Sie entsprechen den in den Prüfprogrammen hinterlegten Anforderungen. Die Rückverfolgbarkeit der eingesetzten Prüfmittel ist durch die Einhaltung der Regelungen unseres Managementsystems gegeben. Detaillierte Informationen bezüglich Prüfkonditionen, Prüfequipment und Messunsicherheiten sind im Prüflabor vorhanden und können auf Wunsch bereitgestellt werden. <i>The equipment used during the specified testing period was calibrated according to our test laboratory calibration program. The equipment fulfils the requirements included in the relevant standards. The traceability of the test equipment used is ensured by compliance with the regulations of our management system. Detailed information regarding test conditions, equipment and measurement uncertainty is available in the test laboratory and could be provided on request.</i>
2	Wie vertraglich vereinbart, wurde dieses Dokument nur digital unterzeichnet. Der TÜV Rheinland hat nicht überprüft, welche rechtlichen oder sonstigen diesbezüglichen Anforderungen für dieses Dokument gelten. Diese Überprüfung liegt in der Verantwortung des Benutzers dieses Dokuments. Auf Verlangen des Kunden kann der TÜV Rheinland die Gültigkeit der digitalen Signatur durch ein gesondertes Dokument bestätigen. Diese Anfrage ist an unseren Vertrieb zu richten. Eine Umweltgebühr für einen solchen zusätzlichen Service wird erhoben. Informationen zur Verifizierung der Authentizität unserer Dokumente erhalten Sie auf folgender Webseite: go.tuv.com/digital-signature <i>As contractually agreed, this document has been signed digitally only. TUV Rheinland has not verified and unable to verify which legal or other pertaining requirements are applicable for this document. Such verification is within the responsibility of the user of this document. Upon request by its client, TUV Rheinland can confirm the validity of the digital signature by a separate document. Such request shall be addressed to our Sales department. An environmental fee for such additional service will be charged. For information on verifying the authenticity of our documents, please visit the following website: go.tuv.com/digital-signature</i>
3	Prüfklausel mit der Note * wurden an qualifizierte Unterauftragnehmer vergeben und sind unter der jeweiligen Prüfklausel des Berichts beschrieben. Abweichungen von Prüfspezifikation(en) oder Kundenanforderungen sind in der jeweiligen Prüfklausel im Bericht aufgeführt. <i>Test clauses with remark of * are subcontracted to qualified subcontractors and described under the respective test clause in the report.</i> <i>Deviations of testing specification(s) or customer requirements are listed in specific test clause in the report.</i>
4	Die Entscheidungsregel für Konformitätserklärungen basierend auf numerischen Messergebnissen in diesem Prüfbericht basiert auf der "Null-Grenzwert-Regel" und der "Einfachen Akzeptanz" gemäß ILAC G8:2019 und IEC Guide 115:2023, es sei denn, in der auf Seite 1 dieses Berichts genannten angewandten Norm ist etwas anderes festgelegt oder vom Kunden gewünscht. Dies bedeutet, dass die Messunsicherheit nicht berücksichtigt wird und daher auch nicht im Prüfbericht angegeben wird. Zu weiteren Informationen bezüglich des Risikos durch diese Entscheidungsregel siehe ILAC G8:2019. <i>The decision rule for statements of conformity, based on numerical measurement results, in this test report is based on the "Zero Guard Band Rule" and "Simple Acceptance" in accordance with ILAC G8:2019 and IEC Guide 115:2023, unless otherwise specified in the applied standard mentioned on Page 1 of this report or requested by the customer. This means that measurement uncertainty is not taken in account and hence also not declared in the test report. For additional information to the resulting risk based of this decision rule please refer to ILAC G8:2019.</i>

Prüfbericht - Nr.: CN26I79B 003
Test Report No.:

Seite 3 von 7
Page 3 of 7

Test Summary

3.1.1 RF EXPOSURE COMPLIANCE
RESULT: Pass

Contents

1.	TEST SITES	5
1.1	TEST FACILITIES	5
1.2	TRACEABILITY	5
1.3	CALIBRATION	5
1.4	LOCATION OF ORIGINAL DATA.....	5
1.5	STATUS OF FACILITY USED FOR TESTING	5
2.	GENERAL PRODUCT INFORMATION	6
2.1	GENERAL DESCRIPTION.....	6
2.2	RATING AND SYSTEM DETAILS	6
3.	TEST RESULTS	7
3.1	TRANSMITTER REQUIREMENTS & TEST SUITES	7
3.1.1	RF Exposure Compliance	7

1. Test Sites

1.1 Test Facilities

TÜV Rheinland (Shenzhen) Co., Ltd.

2-3F, 101 & 102, No.2, Nuclear Power Industrial Park, Fuming Community, Fucheng Street, Longhua District, Shenzhen 518000, China

A2LA Certificate Number: 5162.01

FCC Accreditation Designation No.: CN1260

ISED wireless device testing laboratory: 25069

1.2 Traceability

All measurement equipment calibrations are traceable to NIST or where calibration is performed outside the United States, to equivalent nationally recognized standards organizations.

1.3 Calibration

Equipment requiring calibration is calibrated periodically by the manufacturer or according to manufacturer's specifications. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

1.4 Location of Original Data

The original copies of all test data taken during actual testing were attached at Appendixes of this report and delivered to the applicant. A copy has been retained in the TÜV Rheinland (Shenzhen) file for certification follow-up purposes.

1.5 Status of Facility Used for Testing

The TÜV Rheinland (Shenzhen) Co., Ltd. facility located at 2-3F, 101 & 102, No.2, Nuclear Power Industrial Park, Fuming Community, Fucheng Street, Longhua District, Shenzhen 518000, China is listed on the US Federal Communications Commission list of facilities approved to perform measurements.

2. General Product Information

2.1 General Description

The EUT is Portable Bluetooth Speaker which supports Bluetooth and FM wireless technology.

For details refer to the User Manual, Technical Description and Circuit Diagram.

2.2 Rating and System Details

Table 1: Technical Specification of EUT

General Information of EUT	Value
Kind of Equipment:	Portable Bluetooth Speaker
Type Designation:	WEBOOM, WeBOOM Note: only the model name is different.
Trademark:	Hisense
FCC ID:	HBOBS2622
IC:	10550A-BS2622
HVIN:	WEBOOM
Operating Voltage:	Battery operated (Li ion Battery:7.4Vdc, 10000mAh) Type-C Input: DC 15V/2A Type-C Output: DC 15V/1.4A USB-A Output: DC 5V/1A
Operating Temperature Range:	0 °C ~ +45 °C
Technical Specification of Bluetooth (dual mode)	
Operating Frequency:	2402 MHz to 2480 MHz
Type of Modulation:	GFSK, $\pi/4$ -DQPSK, 8DPSK
Channel Number:	BR & EDR mode:79 channels, Low Energy mode:40 channels
Channel Separation:	BR & EDR mode:1MHz, Low Energy mode:2MHz
Data Rate:	BR & EDR mode: 1Mbps, 2Mbps, 3Mbps Low Energy mode: 1Mbps, 2Mbps
Antenna Type:	PCB Antenna
Antenna Gain:	2.36 dBi (Provided by the Client)

Note: The correctness of all data provided by customer in the test report is ensured and responsible of the customer. Any misjudgment of the test results caused by the use of incorrect data provided by customer shall be borne by the customer.

3. Test Results

3.1 Transmitter Requirements & Test Suites

3.1.1 RF Exposure Compliance

RESULT:**Pass**

Test standard : CFR Title 47 FCC Part 2: Section 2.1093
FCC KDB 447498 D01 General RF Exposure Guidance v06
RSS-102 Issue 6 December 2023

Measurement Record:

The minimum distance for the EUT is less than 30mm.

The separation distance for antenna to edge:

Antenna	To Front Face (mm)	To Rear Face (mm)	To Left Side (mm)	To Right Side (mm)	To Top Side (mm)	To Bottom Side (mm)
BT	80	30	93	229	65	50

For FCC:

Since maximum peak output power of the transmitter is 9.20 dBm $\approx 8.32 \text{ mW}$ $< \frac{3 \cdot d}{\sqrt{f}} = 57.15 \text{ mW}$.

Note: The maximum peak output power test data refer to test report CN26I79B 002.

Hence the EUT is excluded from SAR evaluation according to FCC KDB Publication 447498 D01 General RF Exposure Guidance v06.

For IC:

The maximum e.i.r.p. of the transmitter is 11.56 dBm $\approx 14.32 \text{ mW}$, which is below the SAR exclusion threshold level 89 mW $\approx 19.49 \text{ dBm}$.

The EUT is exempted from routine evaluation limits (SAR Evaluation) according to clause 6.3 of RSS-102 Issue 6.