

FCC 47 CFR MPE REPORT

SHENZHEN FENDA TECHNOLOGY CO., LTD.

3.1 Channel Soundbar with Built-in Subwoofer

Model Number: AX3000

Additional Model: AX3000S, AX3000N, HS3000, HS3000N, Q3000, E3000, Q700, E800,

Q3100, E3100, Q3000DE, E3000DE, AX3000DE, Q700DE, E800DE

FCC ID: HBOHS3000

Applicant:	SHENZHEN FENDA TECHNOLOGY CO., LTD.
Address:	Fenda Hi-Tech Park, Zhoushi Road, Shiyan Town, Baoan District,
	Shenzhen City, Guangdong, China
Prepared By:	EST Technology Co., Ltd.
	Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China
Tel: 86-769-83081888-808	

Report Number:	ESTE-R2607085
Date of Test:	Jun. 11, 2026 to Jul. 03, 2026
Date of Report:	Jul. 07, 2026

Maximum Permissible Exposure

1. Applicable Standards

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 & KDB 447498 D04 V01 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

1.1. Limits for Maximum Permissible Exposure (MPE)

(a) Limits for Occupational/Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-10000			5	6

(b) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-10000			1.0	30

Note: f=frequency in MHz; *Plane-wave equivalent power density

1.2. MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

From the peak EUT RF output power, the minimum mobile separation distance, $d=0.2\text{m}$, as well as the gain of the used antenna, the RF power density can be obtained

2. Conducted Power Result

Mode	Frequency (MHz)	Peak output power (dBm)	Peak output power (mW)
GFSK	2402	4.88	3.076
	2441	5.08	3.221
	2480	4.85	3.055
$\pi/4$ -DQPSK	2402	5.55	3.589
	2441	5.57	3.606
	2480	5.29	3.381
8-DPSK	2402	5.99	3.972
	2441	6.06	4.036
	2480	5.83	3.828
BLE 1M	2402	4.81	3.027
	2440	4.84	3.048
	2480	4.59	2.877
BLE 2M	2402	4.79	3.013
	2440	4.90	3.090
	2480	4.62	2.897

3. Calculated Result and Limit

Mode	Peak output power (dBm)	Target power (dBm)	MAX Target power (dBm)	Antenna gain		Power Density (S) (mW /cm ²)	Limited of Power Density (S) (mW /cm ²)	Test Result
				(dBi)	(Linear)			
2.4G Band								
GFSK	5.08	5±1	6	1.6	1.445	0.00114	1	Complies
π/4-DQPSK	5.57	5±1	6	1.6	1.445	0.00114	1	Complies
8-DPSK	6.06	6±1	7	1.6	1.445	0.00144	1	Complies
BLE 1M	4.84	4±1	5	1.6	1.445	0.00091	1	Complies
BLE 2M	4.90	4±1	5	1.6	1.445	0.00091	1	Complies

End of Test Report