

FCC/IC Label Artwork

Labels for both LiftMaster/Chamberlain model and also the Raynor Brand Name model equivalent

LiftMaster	
POWERED BY myQ	
Model:	JHDC12X1N4XMC
SN.:	xxxxxxx001
myQ	
MAC Address:	
Input:	120/240Vac, x/xA, 1PH 240Vac, xA, 3PH
Mfg Date:	2023/04/01
Max Door Weight:	1200 lbs.
Cycle Rate:	30/hr; 150/day
Freq:	60 Hz
FCC ID:	HBW083743
IC: 2666A-	083743
HVIN:63-083743	
IFT#: (PENDING)	
Country of Origin: MEXICO	
	 May be patent protected. See www.LiftMaster.com/patents.
	132-3457-010

Raynor Garage Door	
POWERED BY myQ	
Model:	2125041
SN.:	xxxxxxx001
myQ	
MAC Address:	
Input:	120/240Vac, x/xA, 1PH 240Vac, xA, 3PH
Mfg Date:	2023/04/01
Max Door Weight:	1200 lbs.
Cycle Rate:	30/hr; 150/day
Freq:	60 Hz
FCC ID:	HBW083743
IC: 2666A-	083743
HVIN:63-083743	
IFT#: (PENDING)	
Country of Origin: MEXICO	
	 May be patent protected. See www.LiftMaster.com/patents.
	132-3457-010

⚠ WARNING Mount Operator 8 ft. or more above floor level. Locate control station within clear sight of door. For indoor use only. DISCONNECT power BEFORE installing or servicing operator. ⚠ ADVERTENCIA Instalar l'opérateur à au moins 8 pi du sol. Aménager la station de commande de façon à ce qu'elle soit visible de la porte. Pour utilisation intérieure seulement. DÉBRANCHER le courant AVANT d'installer ou de faire l'entretien de l'actionneur. ⚠ AVERTISSEMENT Monte el operador 8 pies o más por encima del piso. Localice la estación de control a la vista de la puerta. Para uso en interiores solamente. DESCONECTE la energía eléctrica ANTES de instalar o dar servicio al operador. This device complies with part 15 of the FCC rules and Innovation, Science and Economic Development Canada's license - exempt RSS standard(s). Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. This Class B digital apparatus complies with Canadian ICES-003. This device must be installed in a way where a minimum 8' (20 cm) distance is maintained between users/bystanders and device. Ce dispositif est conforme à la partie 15 du règlement de la FCC et de l'exemption de licence RSS d'Innovation, Sciences et Développement économique Canada. L'utilisation est assuétie aux deux conditions suivantes : (1) ce dispositif ne peut causer de brouillage nuisible, et (2) ce dispositif doit accepter tout brouillage reçu, y compris tout brouillage pouvant causer un fonctionnement indésirable. Cet appareil numérique de classe B est conforme à la norme ICES-003 du Canada. Cet appareil doit être installé de manière à laisser une distance d'au moins 20 cm (8 po) entre celui-ci et l'utilisateur ou toute personne. Este dispositivo cumple con la parte 15 de la reglamentación de la FCC y los estándares RSS exentos de licencia de Innovación, Ciencia y Desarrollo Económico de Canadá. La operación está sujeta a las dos siguientes condiciones: (1) este dispositivo no puede causar interferencias perjudiciales y (2) este dispositivo debe aceptar cualquier interferencia recibida, incluyendo la interferencia que puede causar una operación no deseable. Este aparato digital de Clase B cumple con las normas canadienses ICES-003. Instalar este dispositivo de manera que quede una distancia mínima de 20 cm (8 pulg.) entre el dispositivo y los usuarios/transentes.	132-3434-000
---	--------------