



1516 Centre Circle, Downers Grove IL 60515

RF EXPOSURE EXHIBIT

Manufacturer Name	The Chamberlain Group LLC	
Manufacturer Address	300 Windsor Dr Oak Brook, IL 60523	
Model No.	L993LT	
Specifications	FCC "Code of Federal Regulations" Title 47 Part 1.1307(b) FCC "Code of Federal Regulations" Title 47 Part 2.1093	
Test Facility	Elite Electronic Engineering, Inc. 1516 Centre Circle, Downers Grove, IL 60515	FCC Reg. Number: 269750 IC Reg. Number: 2987A CAB Identifier: US0107
Test Procedure	FCC KDB 447498 D01 General RF Exposure Guidance v06	
Limits	<p>The 1-g and 10-g SAR test exclusion thresholds for 100MHz to 6GHz at test separation distances ≤ 50 mm are determined by the following:</p> $[(\text{max. power of chan., inc. tune-up tol., mW})/(\text{min. test separation distance, mm})][\sqrt{f(\text{GHz})}]$ <p>$f(\text{GHz})$ = RF channel transmit frequency in GHz.</p> <p>power is rounded to the nearest mW distance is rounded to the nearest mm result is rounded to 1 decimal place for comparison</p>	

This is a portable device.

The maximum peak EIRP output power measured 10.55dBm.

This device meets the SAR exclusions FCC 1.1307(b)(3)(i)

Radio Access Technology	f Transmit Frequency (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	P Conducted Output Power (mW)	ERP (mW)	EIRP (mW)	Duty Cycle
BLE	2480	---	---	5.49540874	11.3501082	18.6208714	0.344

Radio Access Technology	f Transmit Frequency (MHz)	Time-Averaged Output Power (mW)	ERP (mW)	Pth (mW)	Exemption Rule	Exemption Results
BLE	2480	1.89042061	11.3501082	10.1747717	FCC 1.1307(b)(3)(i)(B)	Exempt