



Measurement of RF Emissions from an Door State Sensor Transmitter

For	Chamberlain Group, Inc. 845 Larch Ave Elmhurst, IL 60126-2850
P.O. Number	4900053890
Date Tested	June 27- 30, 2017
Test Personnel	Javier Cardenas
Test Specification	FCC "Code of Federal Regulations" Title 47 Part15, Subpart C Industry Canada RSS-Gen Industry Canada RSS-210

Test Report By:




Javier Cardenas
EMC Engineer

Requested By:

Cindy Shaaf
Chamberlain Group, Inc.

Approved By:



Raymond J. Klouda
Registered Professional
Engineer of Illinois - 44894

Elite Electronic Engineering Inc.

1516 CENTRE CIRCLE
DOWNERS GROVE, IL 60515

TEL: 630 - 495 - 9770

FAX: 630 - 495 - 9785

www.elltetest.com

TABLE OF CONTENTS

PARAGRAPH	DESCRIPTION OF CONTENTS	PAGE NO.
1.	Introduction.....	4
1.1.	Scope of Tests.....	4
1.2.	Purpose	4
1.3.	Deviations, Additions and Exclusions.....	4
1.4.	EMC Laboratory Identification	4
1.5.	Laboratory Conditions.....	4
2.	Applicable Documents.....	4
3.	EUT Setup and Operation	5
3.1.	General Description	5
3.1.1.	Power Input.....	5
3.1.2.	Peripheral Equipment	5
3.1.3.	Signal Input/Output Leads	5
3.1.4.	Grounding	5
3.2.	Operational Mode	5
3.3.	EUT Modifications.....	5
4.	Test Facility and Test Instrumentation	5
4.1.	Shielded Enclosure.....	5
4.2.	Test Instrumentation.....	5
4.3.	Calibration Traceability	6
4.4.	Measurement Uncertainty	6
5.	Test Procedures	6
5.1.	Duty Cycle Factor Measurements	6
5.1.1.	Results	6
5.2.	Radiated Measurements	6
5.2.1.	Requirements.....	6
5.2.2.	Procedures.....	7
5.2.3.	Results	7
5.3.	Occupied Bandwidth Measurements.....	7
5.3.1.	Requirement.....	7
5.3.2.	Procedures.....	7
5.3.3.	Results	8
6.	Other Test Conditions	8
6.1.	Test Personnel and Witnesses.....	8
6.2.	Disposition of the EUT	8
7.	Conclusions.....	8
8.	Certification.....	8
9.	Equipment List.....	9

THIS REPORT SHALL NOT BE REPRODUCED, EXCEPT IN FULL, WITHOUT THE
WRITTEN APPROVAL OF ELITE ELECTRONIC ENGINEERING INCORPORATED.

REVISION HISTORY

Revision	Date	Description
—	29 June 2018	Initial
A	10 July 2018 By JCJ	- Added Rev A to the report number on the cover and throughout the report. - Updated device name from “OOK ACCEL Door Sensor” to “Door State Sensor”
B	18 July 2018 By JCJ	- Changed Rev A to Rev B on the report number on the cover and throughout the report. - Added the FCC/IC ID of the product in the Scope of Tests section 1.1

Measurement of RF Emissions from a Door State Sensor Transmitter

1. INTRODUCTION

1.1. Scope of Tests

This report presents the results of the RF emissions measurements performed on a Door State Sensor, FCC/IC ID: HBW8628R2, 2666A-8628R2 (hereinafter referred to as the Equipment Under Test (EUT)). The EUT was designed to transmit at approximately 311.88MHz, 312.5MHz, and 313.12MHz using an internal antenna. The EUT was manufactured and submitted for testing by Chamberlain Group, Inc. located in Elmhurst, IL.

The EUT was originally tested in June 2017. The original test results were presented in Elite Electronic Engineering Test Report No. 1702798-01.

Since it was last tested, the EUT has been modified to include an accelerometer mechanism.

1.2. Purpose

The test series was performed to determine if the EUT meets the Class II Permissive Change requirements of the FCC "Code of Federal Regulations" Title 47, Part 2, Subpart J, Section 2.1043(b)(2) and the Class II Permissive Change requirements of the Innovation, Science, and Economic Development Canada RSP-100, Section 7.3.

Testing was performed to the requirements of the FCC "Code of Federal Regulations" Title 47, Part 15, Subpart C, Section 15.231 for Intentional Radiators, Innovation, Science, and Economic Development Canada RSS-210, Annex A, and ANSI C63.4-2014.

1.3. Deviations, Additions and Exclusions

There were no deviations, additions to, or exclusions from the test specification during this test series.

1.4. EMC Laboratory Identification

This series of tests was performed by Elite Electronic Engineering Incorporated of Downers Grove, Illinois. The laboratory is accredited by The American Association for Laboratory Accreditation (A2LA). A2LA Certificate Number: 1786.01.

1.5. Laboratory Conditions

The temperature at the time of the test was 25°C and the relative humidity was 30%.

2. APPLICABLE DOCUMENTS

The following documents of the exact issue designated form part of this document to the extent specified herein:

- Federal Communications Commission "Code of Federal Regulations", Title 47, Part 15, Subpart C, dated 1 October 2016
- ANSI C63.4-2014, "American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz"
- Industry Canada Radio Standards Specification, RSS-Gen, "General Requirements for Compliance of Radio Apparatus", Issue 4, November 2014
- Industry Canada Radio Standards Specification, RSS-210, "License-Exempt Radio Apparatus: Category I Equipment", Issue 9, August 2016

3. EUT SETUP AND OPERATION

3.1. General Description

The EUT is a Chamberlain Group, Inc. Door State Sensor. This sensor is attached to a garage door and works together with the garage door opener to allow the owner to monitor their garage doors, as well as open and close them through the use of a mobile application. The EUT also ensures the security of the garage door. It will send supervisory transmissions to the garage door opener to ensure the integrity of the system. It will also include the state of the door itself and the battery voltage of the transmitter in this transmission. A block diagram of the EUT setup is shown as Figure 1.

3.1.1. Power Input

The EUT was powered with a 3 VDC coin cell battery.

3.1.2. Peripheral Equipment

There was no peripheral equipment submitted with the EUT.

3.1.3. Signal Input/Output Leads

There were no interconnect cables submitted with the EUT.

3.1.4. Grounding

The EUT was ungrounded during the tests.

3.2. Operational Mode

For all tests the EUT and all peripheral equipment were placed on an 80cm high non-conductive stand. The EUT and all peripheral equipment were energized.

Tx - When powered up and switched between 'open' and 'close', the EUT will send out a full powered transmit signal for 4 seconds, followed by a less than 1 second transmission 40 seconds later. The EUT will then send out a transmission 30 minutes later and repeat that transmission until it is powered off.

It was programmed to continuously transmit three frequencies separately: 311.88MHz, 312.5MHz, and 313.12MHz.

3.3. EUT Modifications

No modifications were required for compliance to FCC Title 47, Part 15, Subpart C, Section 15.231.

4. TEST FACILITY AND TEST INSTRUMENTATION

4.1. Shielded Enclosure

All tests were performed in a 32ft. x 20ft. x 18ft. hybrid ferrite-tile/anechoic absorber lined test chamber. With the exception of the floor, the reflective surfaces of the shielded chamber are lined with ferrite tiles on the walls and ceiling. Anechoic absorber material is installed over the ferrite tile. The floor of the chamber is used as the ground plane. The chamber complies with ANSI C63.4-2014 for site attenuation.

4.2. Test Instrumentation

The test instrumentation and auxiliary equipment used during the tests are listed in Table 9-1.

Conducted and radiated emission measurements were performed with a spectrum analyzer. This receiver allows measurements with the bandwidths and detector functions specified by the FCC. The receiver bandwidth was 120kHz for the 30MHz to 1000MHz radiated emissions data and 1MHz for the 1000MHz to 5000MHz radiated emissions data.

4.3. Calibration Traceability

Test equipment is maintained and calibrated on a regular basis with a calibration interval not greater than two years. All calibrations are traceable to the National Institute of Standards and Technology (NIST).

4.4. Measurement Uncertainty

All measurements are an estimate of their true value. The measurement uncertainty characterizes, with a specified confidence level, the spread of values which may be possible for a given measurement system.

The measurement uncertainty for these tests is presented below:

Conducted Emissions Measurements		
Combined Standard Uncertainty	1.06	-1.06
Expanded Uncertainty (95% confidence)	2.12	-2.12

Radiated Emissions Measurements		
Combined Standard Uncertainty	2.09	-2.09
Expanded Uncertainty (95% confidence)	4.19	-4.19

5. TEST PROCEDURES

5.1. Duty Cycle Factor Measurements

5.1.1. Results

The manufacturer provided following information to calculate the duty cycle for the Rolling Code:

The rolling code consists of the following: 50 short pulses (0.246msec) and 18 long pulses (0.494msec).

A worst case situation is used when computing the rolling code modulation factor.

Worst Case = 21.2msec on-time over 100msec word period

Duty Cycle Factor = $20\log(21.2/100) = -13.5\text{dB}$.

5.2. Radiated Measurements

5.2.1. Requirements

The EUT must comply with the requirements of FCC "Code of Federal Regulations Title 47", Part 15, Subpart C, Section 15.231 et seq.

Fundamental Frequency MHz	Field Intensity uV/m @ 3 meters	Field Strength Harmonics and Spurious @ 3 meters
260 to 470	3,750 to 12,500*	375 to 1,250*

* - Linear Interpolation

In addition, emissions appearing in the Restricted Bands of Operation listed in paragraph 15.231(b) shall not exceed the general requirements shown in paragraph 15.231.

5.2.2.Procedures

All tests were performed in a 32ft. x 20ft. x 18ft. hybrid ferrite-tile/anechoic absorber lined test chamber. The walls and ceiling of the shielded chamber are lined with ferrite tiles. Anechoic absorber material is installed over the ferrite tile. The floor of the chamber is used as the ground plane. The chamber complies with ANSI C63.4-2014 for site attenuation.

The shielded enclosure prevents emissions from other sources, such as radio and TV stations from interfering with the measurements. All powerlines and signal lines entering the enclosure pass through filters on the enclosure wall. The powerline filters prevent extraneous signals from entering the enclosure on these leads.

A preliminary radiated emissions test was performed to determine the emission characteristics of the EUT. For the preliminary test, a broadband measuring antenna was positioned at a 3 meter distance from the EUT. The entire frequency range from 30MHz to 4.5GHz was investigated using a peak detector function. The data was then processed by the computer to calculate equivalent field intensity.

The final open field emission tests were then manually performed over the frequency range of 30MHz to 4500MHz. Between 30MHz and 1000MHz, a BiLog antenna was used as the pick-up device. A broadband double ridged waveguide antenna was used as the pick-up device for all frequencies above 1GHz. All significant broadband and narrowband signals were measured and recorded. The peak detected levels were converted to average levels using a duty cycle factor which was computed from the pulse train.

To ensure that maximum or worst case, emission levels were measured, the following steps were taken:

- 1) The EUT was set to transmit at 311.88MHz.
- 2) The EUT was rotated so that all of its sides were exposed to the receiving antenna.
- 3) Since the measuring antenna is linearly polarized, both horizontal and vertical field components were measured.
- 4) The measuring antenna was raised and lowered from 1 to 4 meters for each antenna polarization to maximize the readings.
- 5) Steps (1) through (4) were repeated with the EUT set to transmit at 312.5MHz.
- 6) Steps (1) through (4) were repeated with the EUT set to transmit at 313.12MHz.

5.2.3.Results

The preliminary plots, with the EUT transmitting at 311.88MHz, 312.5MHz, and 313.12MHz, are presented on data pages 14 and 25. The plots are presented for a reference only, and are not used to determine compliance.

The final open area radiated levels, with the EUT transmitting at 311.88MHz, 312.5MHz, and 313.12MHz, are presented on data pages 26 through 28. As can be seen from the data, all emissions measured from the EUT were within the specification limits. The emissions level closest to the limit (worst case) occurred at 313.12MHz. The emissions level at this frequency was -2.3dB within the limit. Photographs of the test configuration which yielded the highest (or worst case) radiated emission levels are shown in Figures 2 through 5.

5.3. Occupied Bandwidth Measurements

5.3.1.Requirement

In accordance with paragraph 15.231(c), all emissions within 20dB of the peak amplitude level of the center frequency are required to be within a band less than 0.25% of the center frequency wide.

5.3.2.Procedures

The EUT was placed on an 80cm high non-conductive stand. The unit was set to transmit continuously. With an antenna positioned nearby, occupied bandwidth emissions were displayed on the spectrum analyzer. The resolution bandwidth was set to 30kHz and span was set to 2MHz. The frequency spectrum near the fundamental was plotted for all frequencies.

5.3.3.Results

The plot of the emissions near the fundamental frequency is presented on data pages 29 through 34. As can be seen from this data page, the transmitter met the occupied bandwidth requirements. The 99% bandwidth was measured to be 383.62kHz for 311.88MHz.

6. OTHER TEST CONDITIONS

6.1. Test Personnel and Witnesses

All tests were performed by qualified personnel from Elite Electronic Engineering Incorporated.

6.2. Disposition of the EUT

The EUT and all associated equipment were returned to Chamberlain Group, Inc. upon completion of the tests.

7. CONCLUSIONS

It was determined that the Chamberlain Group, Inc. Door State Sensor did fully meet the technical requirements of the FCC "Code of Federal Regulations" Title 47, Part 15, Subpart C, Section 15.231 et seq. for Intentional Radiators, when tested per ANSI C63.4-2014.

It was determined that the Chamberlain Group, Inc. Door State Sensor did fully meet the technical requirements of the Industry Canada Radio Standards Specification, Radio Standards Specification RSS-210 for transmitters, when tested per ANSI C63.4-2014.

8. CERTIFICATION

Elite Electronic Engineering Incorporated certifies that the information contained in this report was obtained under conditions which meet or exceed those specified in the test specifications.

The data presented in this test report pertains to the EUT at the test date. Any electrical or mechanical modification made to the EUT subsequent to the specified test date will serve to invalidate the data and void this certification.

This report must not be used to claim product certification, approval, or endorsement by A2LA, NIST or any agency of the Federal Government.



9. EQUIPMENT LIST


Table 9-1 Equipment List

Eq ID	Equipment Description	Manufacturer	Model No.	Serial No.	Frequency Range	Cal Date	Due Date
NTA4	BILOG ANTENNA	TESEQ	6112D	46660	20-2000GHZ	8/18/2017	8/18/2018
NWQ1	DOUBLE RIDGED WAVEGUIDE ANTENNA	ETS-LINDGREN	3117	66655	1GHZ-18GHZ	4/10/2018	4/10/2020
PHA0	MAGNETIC FIELD PROBE	ELECTRO-METRICS	EM-6882	134	22-230MHZ	NOTE 1	
RBG3	EMI ANALYZER	ROHDE & SCHWARZ	ESW44	101592	2HZ-44GHZ	2/20/2018	2/20/2019

I/O: Initial Only

N/A: Not Applicable

Note 1: For the purpose of this test, the equipment was calibrated over the specified frequency range, pulse rate, or modulation prior to the test or monitored by a calibrated instrument.








Figure 2 - Test Setup for Radiated Emissions, 30MHz to 1GHz – Horizontal Polarization



Figure 3 - Test Setup for Radiated Emissions, 30MHz to 1GHz – Vertical Polarization







Figure 4 - Test Setup for Radiated Emissions, 1GHz to 4.5GHz – Horizontal Polarization





Figure 5 - Test Setup for Radiated Emissions, 1GHz to 4.5GHz – Vertical Polarization


































MANUFACTURER Chamberlain Group, Inc.
EUT Door State Sensor
SPECIFICATION FCC 15 C, Section 15.231
TEST Radiated Emissions
MODE Tx – 311.88MHz
DATE TESTED 06/22/2018

Freq. (MHz)	Ant Pol	Meter Reading (dBuV)	CBL Fac (dB)	Ant Fac (dB)	Pre Amp (dB)	Duty Cycle (dB)	Total (dBuV/m)	Total (uV/m)	Limit (uV/m)	Margin (dB)
311.880	H	63.8	1.2	19.2	0.0	-13.5	70.7	3437.4	5911.7	-4.7
311.880	V	45.9	1.2	19.2	0.0	-13.5	52.8	435.7	5911.7	-22.6
623.760	H	25.6	1.7	24.7	0.0	-13.5	38.4	83.6	591.2	-17.0
623.760	V	26.1	1.7	24.7	0.0	-13.5	39.0	88.8	591.2	-16.5
935.640	H	27.1	2.1	26.7	0.0	-13.5	42.4	131.4	591.2	-13.1
935.640	V	24.8	2.1	26.7	0.0	-13.5	40.1	100.8	591.2	-15.4
1247.520	H	33.0	2.4	29.1	0.0	-13.5	51.0	356.3	591.2	-4.4
1247.520	V	32.3	2.4	29.1	0.0	-13.5	50.3	328.0	591.2	-5.1

Tested By:

Javier Cardenas



MANUFACTURER Chamberlain Group, Inc.
EUT Door State Sensor
SPECIFICATION FCC 15 C, Section 15.231
TEST Radiated Emissions
MODE Tx – 312.5MHz
DATE TESTED 02/23/2017

Freq. (MHz)	Ant Pol	Meter Reading (dBuV)	CBL Fac (dB)	Ant Fac (dB)	Pre Amp (dB)	Duty Cycle (dB)	Total (dBuV/m)	Total (uV/m)	Limit (uV/m)	Margin (dB)
312.500	H	63.9	1.2	19.2	0.0	-13.5	70.8	3473.6	5937.5	-4.7
312.500	V	45.8	1.2	19.2	0.0	-13.5	52.8	434.3	5937.5	-22.7
625.000	H	25.7	1.7	24.7	0.0	-13.5	38.6	85.5	593.7	-16.8
625.000	V	25.9	1.7	24.7	0.0	-13.5	38.8	87.3	593.7	-16.6
937.500	H	28.0	2.1	26.7	0.0	-13.5	43.2	144.3	593.7	-12.3
937.500	V	24.6	2.1	26.7	0.0	-13.5	39.8	97.7	593.7	-15.7
1250.000	H	33.6	2.4	29.1	0.0	-13.5	51.6	381.5	593.7	-3.8
1250.000	V	33.8	2.4	29.1	0.0	-13.5	51.8	389.9	593.7	-3.7

Tested By:

Javier Cardenas



MANUFACTURER Chamberlain Group, Inc.
EUT Door State Sensor
SPECIFICATION FCC 15 C, Section 15.231
TEST Radiated Emissions
MODE Tx – 313.12MHz
DATE TESTED 02/23/2017


Freq. (MHz)	Ant Pol	Meter Reading (dBuV)	CBL Fac (dB)	Ant Fac (dB)	Pre Amp (dB)	Duty Cycle (dB)	Total (dBuV/m)	Total (uV/m)	Limit (uV/m)	Margin (dB)
313.120	H	64.3	1.2	19.2	0.0	-13.5	71.3	3667.1	5963.3	-4.2
313.120	V	40.3	1.2	19.2	0.0	-13.5	47.3	231.4	5963.3	-28.2
626.240	H	25.7	1.7	24.8	0.0	-13.5	38.7	85.9	596.3	-16.8
626.240	V	26.1	1.7	24.8	0.0	-13.5	39.1	90.5	596.3	-16.4
939.360	H	28.4	2.1	26.7	0.0	-13.5	43.6	151.3	596.3	-11.9
939.360	V	24.9	2.1	26.7	0.0	-13.5	40.2	102.0	596.3	-15.3
1252.480	H	33.7	2.4	29.1	0.0	-13.5	51.8	387.5	596.3	-3.7
1252.480	V	33.4	2.4	29.1	0.0	-13.5	51.5	374.4	596.3	-4.0

Tested By:

Javier Cardenas




Manufacturer : Chamberlain Group, Inc.
Test Item : Door State Sensor
Serial No. : N
Mode : Transmit at 311.88MHz
Test : Occupied Bandwidth
Test Limits : 15.231 (c)
Date : March 5, 2018



Date: 22 JUN 2018 21:19:05




Manufacturer : Chamberlain Group, Inc.
Test Item : Door State Sensor
Serial No. : N
Mode : Transmit at 312.5MHz
Test : Occupied Bandwidth
Test Limits : 15.231 (c)
Date : March 5, 2018



Date: 22 JUN 2018 21:21:24




Manufacturer : Chamberlain Group, Inc.
Test Item : Door State Sensor
Serial No. : N
Mode : Transmit at 313.12MHz
Test : Occupied Bandwidth
Test Limits : 15.231 (c)
Date : March 5, 2018



Date: 22 JUN 2018 21:16:27



Manufacturer : Chamberlain Group, Inc.
Test Item : Door State Sensor
Serial No. : N
Mode : Transmit at 311.88MHz
Test : 99% Bandwidth
Test Limits : 15.231
Date : March 5, 2018



Date: 22 JUN 2018 21:45:22




Manufacturer : Chamberlain Group, Inc.
Test Item : Door State Sensor
Serial No. : N
Mode : Transmit at 311.88MHz
Test : 99% Bandwidth
Test Limits : 15.231
Date : March 5, 2018



Date: 22 JUN 2018 21:34:36



Manufacturer : Chamberlain Group, Inc.
Test Item : Door State Sensor
Serial No. : N
Mode : Transmit at 311.88MHz
Test : 99% Bandwidth
Test Limits : 15.231
Date : March 5, 2018



Date: 22 JUN 2018 21:39:38