ncee labs
Product Compliance Solutions

4740 Discovery Drive | Lincoln, NE 68521
tel- 402.323.6233 | tel -888.657.6860 | fax - 402.323.6238
info@nceelabs.com | http://nceelabs.com

Test Report

Prepared for: **Inovonics**

Address: **11000 Westmoor Circle**
Building 10, Suite 250
Westminster, CO 80021

Product: **E1501v3, Battery Powered DSS Transmitter**

Test Report No: **R20220713-00-E1**

Approved by:

Nic Johnson, NCE
Technical Manager
iNARTE Certified EMC Engineer #EMC-003337-NE

DATE: **16 September 2022**

Total Pages: **34**

The Nebraska Center for Excellence in Electronics (NCEE) authorizes the above named company to reproduce this report provided it is reproduced in its entirety for use by the company's employees only. Any use that a third party makes of this report, or any reliance on or decisions made based on it, are the responsibility of such third parties. NCEE accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report. This report applies only to the items tested.

ilac-MRA
ACCREDITED
TESTING LABORATORY
CERTIFICATE NO. 1953.01

REVISION PAGE

Rev. No.	Date	Description
Original	15 September 2022	Reviewed – FLane Prepared by BWinter

CONTENTS

Revision Page **2**

1.0 Summary of test results **4**

2.0 EUT Description **5**

2.1 Equipment under test 5

2.2 Description of test modes 6

2.3 Description of support units 6

3.0 Laboratory description **7**

3.1 Laboratory description 7

3.2 Test personnel 7

3.3 Test equipment 8

3.4 GENERAL TEST PROCEDURE AND SETUP FOR RADIO MEASUREMENTS 9

4.0 Detailed results **10**

4.1 Duty Cycle 11

4.2 Radiated emissions 12

4.3 Peak Output Power 19

4.4 Bandwidth 20

4.5 Bandedges 21

4.6 Carrier frequency separation, number of hopping channels, time of occupancy 22

Appendix A: Sample Calculation **23**

Appendix B – Measurement Uncertainty **25**

Appendix C – Graphs and Tables **26**

REPORT END **34**

1.0 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

(1) US Code of Federal Regulations, Title 47, Part 15
(2) ISED RSS-Gen, Issue 5
(3) ISED RSS-247, Issue 2

SUMMARY			
Standard Section	**Test Type and Limit**	**Result**	**Remark**
FCC 15.203	Unique Antenna Requirement	Pass	PCB antenna
FCC 15.35 RSS-Gen, 6.10	Duty cycle of pulsed emissions	Pass	Pulsed emissions duty cycle was applied
FCC 15.209 RSS-Gen, 7.1	Receiver Radiated Emissions	Pass	Meets the requirement of the limit.
FCC 15.247(a)(1)(i) RSS-247, 5.1(c)	Minimum Bandwidth, Limit: Min. 250kHz, Frequency Separation	Pass	Meets the requirement of the limit.
FCC 15.247(b)(1) RSS-247, 5.1	Maximum Peak Output Power, Limit: Max. 24 dBm	Pass	Meets the requirement of the limit.
FCC 15.209 RSS-Gen, 8.9 RSS-247, 5.5	Transmitter Radiated Emissions	Pass	Meets the requirement of the limit.
FCC 15.247(a) (1) (i) RSS-247, 5.1(c)	Frequency hopping system, Limit: Max. 0.4 Seconds in 10 Second Period	Pass	Meets the requirement of the limit.
FCC 15.209, 15.205,15.247 RSS-Gen, 8.9 RSS-247, 5.5	Band Edge Measurement, Limit: 20dB less than the peak value of fundamental frequency	Pass	Meets the requirement of the limit.
FCC 15.207 RSS-Gen. 8.8	Conducted AC Emissions	NA	Battery powered only.

2.0 EUT DESCRIPTION

2.1 EQUIPMENT UNDER TEST

The Equipment Under Test (EUT) was a wireless FHSS transmitter, E1501v3 module.

EUT	E1501v3
EUT Received	8/9/2022; 8/19/22
EUT Tested	8/9/2022- 8/25/2022
Serial No./ Tx ID	NCEE 010566 -> Unit 1; NCEE 010567 -> Unit 2; NCEE 010607 -> Unit 3
Operating Band	902.0 – 928.0 MHz
Device Type	FHSS
Power Supply	3VDC Battery (CR123A Lithium).

NOTE: For more detailed features description, please refer to the manufacturer's specifications or user's manual.

2.2 DESCRIPTION OF TEST MODES

The EUT operates on, and was tested at the frequencies below:

Channel	Frequency
Low	902.4
Middle	914.8
High	927.6

These are the only three representative channels tested in the frequency range according to FCC Part 15.31 and RSS-Gen Table A1. See the operational description for a list of all channel frequency and designations.

EUT was modified to transmit at the highest practical duty cycle on the lowest, highest and one channel in the middle that was used for all RF tests.

2.3 DESCRIPTION OF SUPPORT UNITS

N/A

3.0 LABORATORY DESCRIPTION

3.1 LABORATORY DESCRIPTION

All testing was performed at the following Facility:

The Nebraska Center for Excellence in Electronics (NCEE Labs)
4740 Discovery Drive
Lincoln, NE 68521

A2LA Certificate Number:	1953.01
FCC Accredited Test Site Designation No:	US1060
Industry Canada Test Site Registration No:	4294A-1
CAB MRA Recognition Identification No:	US0177

Environmental conditions varied slightly throughout the tests.

3.2 TEST PERSONNEL

No.	PERSONNEL	TITLE	ROLE
1	Fox Lane	EMC Test Engineer	Review
2	Blake Winter	EMC Test Engineer	Testing and Report

Notes:
All personnel are permanent staff members of NCEE Labs. No testing or review was sub-contracted or performed by sub-contracted personnel.

3.3 TEST EQUIPMENT

DESCRIPTION AND MANUFACTURER	MODEL NO.	SERIAL NO.	LAST CALIBRATION DATE	CALIBRATION DUE DATE
Keysight MXE Signal Analyzer (26.5GHz)	N9038A	MY56400083	July 19, 2022	July 19, 2024
Keysight MXE Signal Analyzer (44GHz)	N9038A	MY59050109	July 19, 2022	July 19, 2024
SunAR RF Motion**	JB1	A082918-1	July 26, 2022	July 26, 2024
EMCO Horn Antenna	3115	6416	July 28, 2021	July 28, 2023
Rohde & Schwarz Preamplifier*	TS-PR18	3545700803	April 4, 2022	April 4, 2024
Trilithic High Pass Filter*	6HC330	23042	April 22, 2022	April 22, 2024
MiniCircuits High Pass Filter*	VHF-1320+	15542	April 4, 2022	April 4, 2024
ETS – Lindgren- VSWR on 10m Chamber	10m Semi-anechoic chamber-VSWR	4740 Discovery Drive	July 30, 2020	July 30, 2023
NCEE Labs-NSA on 10m Chamber	10m Semi-anechoic chamber-NSA	NCEE-001	May 24, 2022	May 24, 2025
TDK Emissions Lab Software	V11.25	700307	NA	NA
RF Cable (preamplifier to antenna)*	MFR-57500	01-07-002	April 4, 2022	April 4, 2024
RF Cable (antenna to 10m chamber bulkhead)*	FSCM 64639	01E3872	September 24, 2021	September 24, 2023
RF Cable (10m chamber bulkhead to control room bulkhead)*	FSCM 64639	01E3864	September 24, 2021	September 24, 2023
RF Cable (control room bulkhead to test receiver)*	FSCM 64639	01F1206	September 24, 2021	September 24, 2023
N connector bulkhead (10m chamber)**	PE9128	NCEEBH1	September 24, 2021	September 24, 2023
N connector bulkhead (control room)**	PE9128	NCEEBH2	September 24, 2021	September 24, 2023

*Internal Characterization

**2-year calibration cycle

Notes:

All equipment is owned by NCEE Labs and stored permanently at NCEE Labs facilities. All equipment were in Cal during testing. However, latest calibration dates were provided.

3.4 GENERAL TEST PROCEDURE AND SETUP FOR RADIO MEASUREMENTS

Measurement type presented in this report (Please see the checked box below):

Conducted ☐

The conducted measurements were performed by connecting the output of the transmitter directly into a spectrum analyzer using an impedance matched cable and connector soldered to the EUT in place of the antenna. The information regarding resolution bandwidth, video bandwidth, span and the detector used can be found in the graphs provided in the Appendix C. All the radio measurements were performed using the sections from ANSI C63.10, details about the section used can be found in the spectrum analyzer titles on the graph.



Figure 1 - Bandwidth Measurements Test Setup

Radiated ☒

All the radiated measurements were taken at a distance of 3m from the EUT. The information regarding resolution bandwidth, video bandwidth, span and the detector used can be found in the graphs provided in the Appendix C. All the radio measurements were performed using the sections from ANSI C63.10, details about the section used can be found in the spectrum analyzer titles on the graph.



Figure 2 - Radiated Emissions Test Setup

4.0 DETAILED RESULTS

DSS Radiated Radio Measurements								
CHANNEL	Transmitter	99% Occupied Bandwidth (kHz)	20 dB Bandwidth (kHz)	PEAK Radiated EIRP (dBm)	PEAK Radiated EIRP (mW)	RESULT	No. of Hopping Channels	Time of Occupancy*
							25	0.0650s*
Low	Hopping	287.42	304.4	20.47	111.43	PASS	Min Frequency Separation	Duty Cycle Correction
Mid	Hopping	295.82	303.5	19.46	88.31	PASS		
High	Hopping	297.00	304.4	18.77	75.34	PASS	774 kHz	-13.2
Occupied Bandwidth = N/A; 20 dB Bandwidth Limit 250 kHz ≤ BW ≤ 500 kHz. *EIRP = dBm(Raw) + Correction Level Offset. See table below. See Plots for dBm(Raw) in Appendix C				Peak Output Power Limit = 24 dBm; corrections can be found in the last table of this section and in the graphs in Appendix C. Time of Occupancy<0.4 S in 10 S				

Unrestricted Band-Edge							
CHANNEL	Mode	Band edge /Measurement Frequency (MHz)	Relative Highest out of band level (dBm)	Relative Fundamental (dBm)	Delta (dB)	Min Delta (dB)	Result
Low	Hopping	902.00	-66.12	-23.44	42.68	20.00	PASS
High	Hopping	928.00	-67.65	-25.08	42.57	20.00	PASS

Peak Restricted Band-Edge							
CHANNEL	Mode	Band edge /Measurement Frequency (MHz)	Highest out of band level (dBuV/m @ 3m)	Measurement Type	Limit (dBuV/m @ 3m)*	Margin	Result
Low**	Hopping	613.994	33.18	Radiated	46.02	12.84	PASS
High**	Hopping	988.520	39.50	Radiated	53.98	14.44	PASS

*Limit shown is the peak limit taken from FCC Part 15.209
**Measurement was corrected using:
Highest out of band level = Highest out of band level(Raw) + Correction Level offset. See table below
See tables below for Antenna Factor and Cable Corrections

Corrections and Raw Values for Restricted Band Edges and Output Power				
Channel, MHz	Antenna Factor (dB)	Cable Loss (dB)	dBm to dBuV	Correction/Reference level offset
614.0	23.0	4.44	N/A	27.44**
902.4	26.6	5.30	107	138.9*
914.8	26.5	5.37	107	138.87*
927.6	26.6	5.43	107	139.03*
988.5	27.3	5.60	N/A	32.9**
Correction level offset =dBm to dBuV + Antenna Factor + Cable				
Correction level offset = Antenna Factor + Cable				

4.1 DUTY CYCLE

NCEE measured 22 ms in a given 100 ms period. So, Duty cycle correction factor for spurious emissions related to the transmitter is 20 log 22/100 = -13.2 dB.

4.2 RADIATED EMISSIONS

Test Method: ANSI C63.10-2013, Section 6.5, 6.6

Limits for radiated emissions measurements:

Emissions radiated outside of the specified bands shall be applied to the limits in 15.209 as followed:

FREQUENCIES (MHz)	FIELD STRENGTH (µV/m)	MEASUREMENT DISTANCE (m)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	3
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

NOTE:
1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 * log * Emission level (µV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits by more than 20dB under any condition of modulation.

Test procedures:

a. The EUT was placed on the top of a rotating table above the ground plane in a 10-meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. The table was 0.8m high for measurements form 30MHz-1GHz and 1.5m for measurements from 1GHz to 10 GHz.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. The antenna was a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are used to make the measurement.

d. For each suspected emission, the EUT was arranged to maximize its emissions and then the antenna height was varied from 1 meter to 4 meters and the rotating table was turned from 0 degrees to 360 degrees to find the maximum emission reading.

e. The test-receiver system was set to use a peak detector with a specified resolution bandwidth. For spectrum analyzer measurements, the composite maximum of several analyzer sweeps was used for final measurements.

f. If the emission level of the EUT in peak mode was 6dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise, the emissions that did not have 6 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

g. The EUT was maximized in all 3 orthogonal positions. The results are presented for the axis that had the highest emissions.

NOTE:
1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Peak detection (PK) and Quasi-peak detection (QP) at frequencies below 1GHz.

2. The resolution bandwidth 1 MHz for all measurements and at frequencies above 1GHz, A peak detector was used for all measurements above 1GHz. Measurements were made with an EMI Receiver.

Deviations from test standard:

No deviation.

Test setup:



Figure 3 - Radiated Emissions Test Setup

EUT operating conditions
Details can be found in section 2.1 of this report.

Test results:



Figure 4 - Radiated Emissions Plot, Low Channel, 30 MHz-1GHz

*Noise floor on this plot looks higher than the other plots because of the receiver settings during the test to avoid saturation. The worst-case measurements are listed in the tables below, all other measurements were found to be at least 6 dB below the limit.



Figure 5 - Radiated Emissions Plot, Mid Channel, 30 MHz-1GHz

*Noise floor on this plot looks higher than the other plots because of the receiver settings during the test to avoid saturation. The worst-case measurements are listed in the tables below, all other measurements were found to be at least 6 dB below the limit.



Figure 6 - Radiated Emissions Plot, High Channel, 30 MHz-1GHz

*Noise floor on this plot looks higher than the other plots because of the receiver settings during the test to avoid saturation. The worst-case measurements are listed in the tables below, all other measurements were found to be at least 6 dB below the limit.

Peak Measurements, 900 MHz Radio,								
Frequency	**Level**	**Limit**	**Margin**	**Pol**	**Height**	**Angle**	**Channel**	**Radio Band**
MHz	**dBµV/m**	**dBµV/m**	**dB**		**cm.**	**deg.**		**MHz**
1804.82	53.40	73.98	20.58	H	207.00	20.00	Low	900 -928
2707.23	48.84	73.98	25.14	H	559.00	243.00	Low	900 -928
3609.59	57.71	73.98	16.27	H	300.00	181.00	Low	900 -928
4512.03	58.70	73.98	15.28	H	99.00	186.00	Low	900 -928
5414.35	66.68	73.98	7.30	H	200.00	192.00	Low	900 -928
6316.90	52.48	73.98	21.50	H	200.00	175.00	Low	900 -928
7218.93	52.95	73.98	21.03	H	99.00	169.00	Low	900 -928
1829.62	56.48	73.98	17.50	H	251.00	196.00	Mid	900 -928
2744.40	47.20	73.98	26.78	H	170.00	95.00	Mid	900 -928
3659.25	55.59	73.98	18.39	H	300.00	172.00	Mid	900 -928
4574.01	60.67	73.98	13.31	H	99.00	177.00	Mid	900 -928
5488.78	65.56	73.98	8.42	H	200.00	175.00	Mid	900 -928
6403.58	52.77	73.98	21.21	H	200.00	165.00	Mid	900 -928
7318.26	54.05	73.98	19.93	H	200.00	162.00	Mid	900 -928
1855.20	53.45	73.98	20.53	H	368.00	197.00	High	900 -928
2782.83	46.04	73.98	27.94	V	245.00	314.00	High	900 -928
3710.54	51.26	73.98	22.72	H	300.00	177.00	High	900 -928
4637.99	57.31	73.98	16.67	H	199.00	173.00	High	900 -928
5565.51	56.95	73.98	17.03	H	99.00	180.00	High	900 -928
7420.68	53.34	73.98	20.64	H	99.00	190.00	High	900 -928
All other measurements were found to be at least 6dB below the limit line. EUT was maximized on 3 orthogonal angles, worst case was reported								

Average Measurements, 900 MHz Radio,								
Frequency	**Level**	**Limit**	**Margin**	**Height**	**Angle**	**Pol**	**Channel**	**Radio Band**
MHz	**dBµV/m**	**dBµV/m**	**dB**	**cm.**	**deg.**			**MHz**
1804.82	40.20	53.98	13.78	H	207.00	20.00	Low	900 -928
2707.23	35.64	53.98	18.34	H	559.00	243.00	Low	900 -928
3609.59	44.51	53.98	9.47	H	300.00	181.00	Low	900 -928
4512.03	45.50	53.98	8.48	H	99.00	186.00	Low	900 -928
5414.35	53.48	53.98	0.50	H	200.00	192.00	Low	900 -928
6316.90	39.28	53.98	14.7	H	200.00	175.00	Low	900 -928
7218.93	39.75	53.98	13.23	H	99.00	169.00	Low	900 -928
1829.62	43.28	53.98	10.7	H	251.00	196.00	Mid	900 -928
2744.40	34.00	53.98	19.98	H	170.00	95.00	Mid	900 -928
3659.25	42.39	53.98	11.59	H	300.00	172.00	Mid	900 -928
4574.01	47.47	53.98	6.51	H	99.00	177.00	Mid	900 -928
5488.78	52.36	53.98	1.62	H	200.00	175.00	Mid	900 -928
6403.58	39.57	53.98	14.41	H	200.00	165.00	Mid	900 -928
7318.26	40.85	53.98	13.13	H	200.00	162.00	Mid	900 -928
1855.20	53.45	53.98	40.25	H	368.00	197.00	High	900 -928
2782.83	32.84	53.98	21.14	V	245.00	314.00	High	900 -928
3710.54	38.06	53.98	15.92	H	300.00	177.00	High	900 -928
4637.99	44.11	53.98	9.87	H	199.00	173.00	High	900 -928
5565.51	43.75	53.98	10.23	H	99.00	180.00	High	900 -928
7420.68	40.14	53.98	13.84	H	99.00	190.00	High	900 -928
Average Level is obtained by adding the duty cycle correction factor found in section 4.1 to the Peak level. All the measurements were compared to general limits from FCC part 15.209 to show compliance. All other measurements were found to be at least 6dB below the limit line.								

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB)
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Limit Value – Emission Level.
5. The EUT was measured in all 3 orthogonal axes. See the test setup photo exhibit for details on the orientations.

4.3 PEAK OUTPUT POWER

Test Method: ANSI C63.10, Section(s) 7.8.5

Limits of bandwidth measurements:
Per FCC Part 15
For an FHSS system with 25 channels, the output power is required to be less than 250 mW or 24 dBm.

Test procedures:
Spectrum analyzer was set with a resolution bandwidth greater than occupied bandwidth and centered on the operating channel. Output power was measured by radiated emissions at a distance of 3 meters.

Deviations from test standard:
No deviation.

Test setup:
Details can be found in section 3.4 of this report.

EUT operating conditions:
Details can be found in section 2.1 of this report.

Test results:
Pass
Comments:
1. All the output power plots can be found in the Appendix C.
2. All data is in the table in results section 4.0.
3. All the measurements were found to be compliant.

4.4 BANDWIDTH

Test Method: ANSI C63.10, Section(s) 6.9.2

Limits of bandwidth measurements:
The allowed 20 dB bandwidth of the hopping channel is 250 kHz ≤ BW ≤ 500 kHz.

Test procedures:
The bandwidth of the fundamental frequency was measured by spectrum analyzer with 3 kHz RBW and 30 kHz VBW.

The 20 dB bandwidth is defined as the bandwidth of which is higher than peak power minus 20dB.
The 99% bandwidth is defined as the bandwidth that contains 99% of the power.

Deviations from test standard:
No deviation.

Test setup:
Details can be found in section 3.4 of this report.

EUT operating conditions:
Details can be found in section 2.1 of this report.

Test results:

Pass

Comments:
1. All the bandwidth plots can be found in the Appendix C.
2. All data is in the table in results section 4.0.
3. All the measurements were found to be compliant.

4.5 BANDEDGES

Test Method: ANSI C63.10, Section(s) 6.10.6

Limits of band edge measurements:
For emissions outside of the allowed band of operation (902 – 928MHz), the emission level needs to be 20dB under the maximum fundamental field strength. However, if the emissions fall within one of the restricted bands from 15.205 the field strength levels need to be under that of the limits in 15.209.

Test procedures:
The resolution bandwidth was set to 100kHz and the EMI receiver was used to scan from the band edge to the fundamental frequency with a Peak detector. The highest emissions level beyond the band edge was measured and recorded. For restricted band edge measurements, the unit was tested to the same method as section 4.2 of this report.

Deviations from test standard:
No deviation.

Test setup:
Details can be found in section 3.4 of this report.

EUT operating conditions:
Details can be found in section 2.1 of this report.

Test results:

Pass

Comments:

1. All the band edge plots can be found in the Appendix C.
2. All data is in the table in results section 4.0.
3. If the device falls under FCC Part 15.247 (Details can be found in summary of test results), compliance is shown in the unrestricted band edges by showing minimum delta of 20 dB between peak and the band edge.
4. The restricted band edge compliance is shown by comparing to the general limit defined in Part 15.209. The limit shown in the graph accounts for the antenna gain of the device.

4.6 CARRIER FREQUENCY SEPARATION, NUMBER OF HOPPING CHANNELS, TIME OF OCCUPANCY

Test Method: ANSI C63.10, Section 7.8.2, 7.8.3, 7.8.4

Limits for Time of Occupancy

Average time of occupancy on any frequency, not to exceed 0.4 seconds within a 10 second period.

Test procedures:
The method from KDB 558074 D01 v05;

Test setup:
Details can be found in section 3.4 of this report.

EUT operating conditions:
Details can be found in section 2.1 of this report.

.

Test results:

Pass

Comments:

1. All the plots can be found in the Appendix C.
2. All the measurements were found to be compliant.
3. The measurements are reported on the graph.
4. **Declaration from manufacturer:** The EchoStream protocol defines 64 channels spaced 400 kHz apart. Manufacturer uses only 25 channels from the set of 64. The minimum spacing between channels is ~ 800 kHz with some channels space ~1.2 MHz apart. The entire channel map uses a spacing of 400 kHz, but the used channels are either 800 kHz or 1.2 MHz apart.

APPENDIX A: SAMPLE CALCULATION

Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any) from the measured reading. The basic equation with a sample calculation is as follows:
FS = RA + AF – (-CF + AG) + AV

where FS = Field Strength

RA = Receiver Amplitude

AF = Antenna Factor

CF = Cable Attenuation Factor

AG = Amplifier Gain

AV = Averaging Factor (if applicable)

Assume a receiver reading of 55 dBμV is obtained. The Antenna Factor of 12 and a Cable Factor of 1.1 is added. The Amplifier Gain of 20 dB is subtracted, giving a field strength of 48.1 dBμV/m.

FS = 55 + 12 – (-1.1 + 20) + 0 = 48.1 dBμV/m

The 48.1 dBμV/m value can be mathematically converted to its corresponding level in μV/m.

Level in μV/m = Common Antilogarithm [(48.1 dBμV/m)/20]= 254.1 μV/m

AV is calculated by the taking the 20*log(T_{on}/100) where T_{on} is the maximum transmission time in any 100ms window.

EIRP Calculations

In cases where direct antenna port measurement is not possible or would be inaccurate, output power is measured in EIRP. The maximum field strength is measured at a specified distance and the EIRP is calculated using the following equation;

EIRP (Watts) = [Field Strength (V/m) x antenna distance (m)]^2 / 30

Power (watts) = 10^[Power (dBm)/10] / 1000

Voltage (dBµV) = Power (dBm) + 107 (for 50Ω measurement systems)

Field Strength (V/m) = 10^[Field Strength (dBµV/m) / 20] / 10^6

Gain = 1 (numeric gain for isotropic radiator)

Conversion from 3m field strength to EIRP (d=3):

EIRP = [FS(V/m) x d^2]/30 = FS [0.3] for d = 3

EIRP(dBm) = FS(dBµV/m) – 10(log 10^9)+ 10log[0.3] = FS(dBµV/m) - 95.23

10log(10^9) is the conversion from micro to milli

APPENDIX B – MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been for tests performed in this test report:

Test	Frequency Range	Uncertainty Value (dB)
Radiated Emissions, 3m	30MHz - 1GHz	±4.31
Radiated Emissions, 3m	1GHz - 18GHz	±5.08
Emissions limits, conducted	30MHz – 18GHz	±3.03

Expanded uncertainty values are calculated to a confidence level of 95%.

APPENDIX C – GRAPHS AND TABLES



01 Uncorrected EIRP, Hopping Mode



04 Bandwidth Low Channel



05. Bandwidth Mid Channel



06 Bandwidth High Channel



07 Bandedge Unrestricted Low Channel Hopping, Relative



08 Bandedge Restricted Low Channel without Corrections Hopping

Corrections and Raw Values for Restricted Band Edges				
Channel, MHz	Antenna Factor (dB)	Cable Loss (dB)	dBm to dBuV	Correction/Reference level offset
614.0	23.00	4.44	NA	27.44
dBuV = Uncorrected Level (dBuV) + Antenna Factor + Cable				



09 Bandedge Unrestricted High Channel Hopping, Relative



10 Bandedge Restricted High Channel Without Corrections Hopping

Corrections and Raw Values for Restricted Band Edges				
Channel, MHz	Antenna Factor (dB)	Cable Loss (dB)	dBm to dBuV	Correction/Reference level offset
988.5	27.3	5.60	NA	32.90
dBuV = Uncorrected Level (dBuV) + Antenna Factor + Cable				



11 Hop Count, 25 Hops



12 Minimum Frequency Separation



13 Channel Occupancy, On time*

***Measured in hopping mode provided by the manufacturer.**



14 Channel Occupancy in 20 s window, 3 Hops possible*

***Measured in hopping mode provided by the manufacturer. 21.68 ms x 3=65.0 ms=0.0650 s.**

REPORT END