

VARIANT EMC TEST REPORT


Applicant:	Honeywell International Inc
Address:	9680 Old Bailes Road, Fort Mill, SC 29707 United States

Manufacturer or Supplier:	Honeywell International Inc
Address:	9680 Old Bailes Road, Fort Mill, SC 29707 United States
Product:	Mobile Computer
Brand Name:	Honeywell
Model Name:	CT45P-X0N
FCC ID:	HD5-CT45PX0N
Date of tests:	Oct, 09, 2025 ~ Dec. 17, 2025

The submitted sample of the above equipment has been tested for according to the requirements of the following standards:

- ☐ FCC Part 15, Subpart B, Class A
☒ FCC Part 15, Subpart B, Class B
☒ ANSI C63.4:2014

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Prepared by Hanwen Xu Engineer / Mobile Department	Approved by Luke Lu Manager / Mobile Department
	
Date: Dec. 17, 2025	Date: Dec. 17, 2025

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

TABLE OF CONTENTS

TABLE OF CONTENTS	2
RELEASE CONTROL RECORD	3
1 GENERAL INFORMATION.....	4
1.1 GENERAL DESCRIPTION OF EUT	4
1.2 SUMMARY OF TEST RESULTS	6
1.3 MEASUREMENT UNCERTAINTY	7
1.4 DESCRIPTION OF TEST MODES	8
1.5 DESCRIPTION OF SUPPORT UNITS	9
2 EMISSION TEST.....	10
2.1 CONDUCTED EMISSION MEASUREMENT	10
2.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT	10
2.1.2 TEST INSTRUMENTS.....	10
2.1.3 TEST PROCEDURES	11
2.1.4 DEVIATION FROM TEST STANDARD	11
2.1.5 TEST SETUP	12
2.1.6 EUT OPERATING CONDITIONS	12
2.1.7 TEST RESULTS	13
2.2 RADIATED EMISSION MEASUREMENT	15
2.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT	15
2.2.2 TEST INSTRUMENTS.....	16
2.2.3 TEST PROCEDURE.....	17
2.2.4 DEVIATION FROM TEST STANDARD	18
2.2.5 TEST SETUP	19
2.2.6 EUT OPERATING CONDITIONS	19
2.2.7 TEST RESULTS	20
3 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB	24



RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
W7L-P21080021EM03	Original release	Sep. 06, 2021
PSU-QBJ2512030414EM03	Based on the original report, the new product add alternate parts, the electrical specs of the alternate part is equivalent to the current part. In this report update the SW version, verify CE and RE worst case, So this report updates CE and RE worst case data.	Dec. 17, 2025



1 GENERAL INFORMATION

1.1 GENERAL DESCRIPTION OF EUT

PRODUCT*	Mobile Computer	
BRAND NAME*	Honeywell	
MODEL NAME*	CT45P-X0N	
NOMINAL VOLTAGE*	5Vdc (adapter) 3.85Vdc (Lithium-ion cell, battery)	
MODULATION TYPE*	BT_LE	GFSK
	Bluetooth	GFSK, $\pi/4$ -DQPSK, 8DPSK
	NFC	ASK
	WLAN	DSSS, OFDM
OPERATING FREQUENCY*	Bluetooth/ BT_LE	2402MHz ~ 2480MHz
	NFC	13.56 MHz
	WLAN	11b/g/n(HT20) /ax(HE20) 5180 ~ 5240MHz, 5260 ~ 5320 MHz, 5500 ~ 5720MHz, 5745 ~ 5825 MHz for 11a/n(HT20)/n(HT40)/ac(VHT20)/ac(VHT40)/ac(VHT80) / ax(HE20)/ ax(HE40) / ax(HE80)
HW VERSION*	V1.0	
SW VERSION*	OS.11.003	
I/O PORTS*	Refer to user's manual	
CABLE SUPPLIED*	USB cable: shielded without ferrite, 1.25 meter Earphone cable: unshielded without ferrite, 1.27 meter	
ACCESSORY DEVICES*	Refer to note as below	

NOTE:

1. *Since the above data and/or information is provided by the client relevant results or conclusions of this report are only made for these data and/or information, Test Lab is not responsible for the authenticity, integrity and results of the data and information and/or the validity of the conclusion.
2. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
3. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in the test report.



4. This product includes the following two SKU which hardware is exactly same, the difference is described as following, Sample 1 was full test, sample 2 verify the worst case, check worst case Radiated emission:

SAMPLE	EUT CONFIGURATION INFORMATION
1	SKU ID:CT45P-X0N-37D100G ,Assembled with Scanner Imager: S0703
2	SKU ID:CT45P-X0N-38D100G ,Assembled with Scanner Imager: N6803/S0803

5. List of Accessory:

ACCESSORIES	BRAND	MODEL	SPECIFICATION
Battery	Honeywell	CT50-BTSC	Capacity: 3.85vdc 4020mAh
AC Adapter 1	HONOR	ADS-65LSI-12-1 12036E	I/P:100-240Vac, 1.5A O/P: 12Vdc, 3A
AC Adapter 2	HONOR	ADS-110DL-12-1 120084E	I/P:100-240Vac, 1.5A O/P: 12Vdc, 7A
Earphone	Honeywell	PTE-300N	Shielded, 1.27meter
LCD Panel 1	CASIL	CTM10801920T01	5.0" FHD(1928*1080)

1.2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart B			
Standard Section	Test Item	Result	Test lab*
FCC Part 15, Subpart B, Class B ANSI C63.4:2014	Conducted Test	Compliance	A
	Radiated Emission Test (30MHz ~ 1GHz)	Compliance	A
	Radiated Emission Test (Above 1GHz)	Compliance	A

*Test Lab Information Reference

Lab A:

Huarui 7Layers High Technology (Suzhou) Co., Ltd.

Lab Address:

Tower N, Innovation Center, 88 Zuyi Road, High-tech District, Suzhou City, Anhui Province, China

Accredited Test Lab Cert 6613.01


The FCC Site Registration No. is 434559; The Designation No. is CN1325.

1.3 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	150kHz ~ 30MHz	±2.70dB
Radiated emissions	30MHz~1GHz	±4.98dB
	1GHz ~6GHz	±4.70dB
	6GHz ~18GHz	±4.60dB
	18GHz ~40GHz	±4.12dB



The verdicts in this test report are given according the above diagram:

Case	Measured Value	Uncertainty Range	Verdict
1	below pass mark	below pass mark	Passed
2	below pass mark	within pass mark	Passed
3	above pass mark	within pass mark	Failed
4	above pass mark	above pass mark	Failed

That means, the laboratory applies, as decision rule (see ISO/IEC 17025:2017), the so-called shared risk principle.

1.4 DESCRIPTION OF TEST MODES

Test Mode	Test Condition
Radiated emission test	
1	Adapter + USB cable + Earphone + Front Camera On
2	Adapter + USB cable + Earphone + Back Camera On
3	Adapter + USB cable + Earphone + MPG4 + Scanning
4	USB Link + Data Transmission + USB Cable + Earphone + PC to EUT
5	USB Link + Data Transmission + USB Cable + Earphone + PC to SD
6	Adapter + Charger + Back Camera On
7	Adapter + Charger + Front Camera On
8	Adapter + Charger + MPG4 + Scanning
9	Charger + Data Transmission + EUT to PC
10	Charger + Data Transmission + SD to PC

Test Mode	Test Condition
Conducted emission test	
1	Adapter + USB cable + Earphone + Front Camera On
2	Adapter + USB cable + Earphone + Back Camera On
3	Adapter + USB cable + Earphone + MPG4 + Scanning
4	USB Link + Data Transmission + USB Cable + Earphone + PC to EUT
5	USB Link + Data Transmission + USB Cable + Earphone + PC to SD
6	Adapter + Charger + Back Camera On
7	Adapter + Charger + Front Camera On
8	Adapter + Charger + MPG4 + Scanning
9	Charger + Data Transmission + EUT to PC
10	Charger + Data Transmission + SD to PC
NOTE: - For radiated emission test, Pre-scan all mode, test mode 1 was the worst case and only this mode was presented in this report - For conducted emission test, Pre-scan all mode, mode 9 was the worst case and only this mode was presented in this report.	



1.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

FOR ALL TESTS

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	Laptop	Lenovo	Thinkpad E14	SL10W47313	N/A
2	Micro SD	SAM SUNG	N/A	N/A	N/A
3	Bluetooth	Rohde&Schwarz	SMBV100B	102176	N/A
4	WIFI Router	HUAWEI	N/A	N/A	N/A
5	Adapter	N/A	N/A	N/A	N/A
6	NFC Card	N/A	N/A	N/A	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	USB Line: Shielded, Detachable 1.25m;



2 EMISSION TEST

2.1 CONDUCTED EMISSION MEASUREMENT

2.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

TEST STANDARD: FCC Part 15, Subpart B (Section: 15.107 a CLASS B)

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB μ V)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

TEST STANDARD: FCC Part 15, Subpart B (Section: 15.107 b CLASS A)

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB μ V)	
	Quasi-peak	Average
0.15 ~ 0.5	79	66
0.5 ~ 30	73	60

NOTE: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

3. All emanations from a class A/B digital device or system, including any network of conductors

and apparatus connected thereto, shall not exceed the level of field strengths specified above.

2.1.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESR3	102749	Mar.28,24	Mar.27,26
ELEKTRA test software	Rohde&Schwarz	ELEKTRA	NA	N/A	N/A
LISN network	Rohde&Schwarz	ENV216	102640	Mar.28,24	Mar.27,26
CABLE	Rohde&Schwarz	W61.01	N/A	Apr.26,25	Apr.25,26
CABLE	Rohde&Schwarz	W601	N/A	Apr.26,25	Apr.25,26

NOTE: 1. The test was performed in CE shielded room.



2.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150 kHz to 30MHz was searched. Emission levels under (Limit - 20dB) were not recorded.


NOTE: All modes of operation were investigated and the worst-case emissions are reported.

2.1.4 DEVIATION FROM TEST STANDARD

No deviation.



2.1.5 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

2.1.6 EUT OPERATING CONDITIONS

- Turned on the power and connected of all equipment.
- EUT was operated according to the use type described in the manufacturer's specifications or the user's manual.



2.1.7 TEST RESULTS

TEST VOLTAGE	Input 120 Vac, 60 Hz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
ENVIRONMENTAL CONDITIONS	26deg. C, 51%RH	TESTED BY	Hanwen Xu

Rg	Frequency [MHz]	QPK Level [dBμV]	QPK Limit [dBμV]	QPK Margin [dB]	CAV Level [dBμV]	CAV: AVG Limit [dBμV]	CAV Margin [dB]	Correction [dB]	Line	Meas. BW [kHz]
1	0.159	41.65	65.52	23.87	31.29	55.52	24.23	9.79	L1	9.000
1	0.533	39.38	56.00	16.62	29.45	46.00	16.55	9.75	L1	9.000
1	1.563	34.27	56.00	21.73	25.07	46.00	20.93	9.79	L1	9.000
1	8.021	37.15	60.00	22.85	26.45	50.00	23.55	10.63	L1	9.000
1	11.558	33.12	60.00	26.88	25.44	50.00	24.56	11.39	L1	9.000
1	16.989	32.29	60.00	27.71	18.46	50.00	31.54	12.75	L1	9.000

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Limit value- Emission level
4. Correction factor = Insertion loss + Cable loss + Attenuate
5. Emission Level = Correction Factor + Reading Value.






TEST VOLTAGE	Input 120 Vac, 60 Hz	DETECTOR FUNCTION & RESOLUTION BANDWIDTH	Quasi-Peak (QP) / Average (AV), 9 kHz
ENVIRONMENTAL CONDITIONS	26deg. C, 51%RH	TESTED BY	Hanwen Xu

Rg	Frequency [MHz]	QPK Level [dBμV]	QPK Limit [dBμV]	QPK Margin [dB]	CAV Level [dBμV]	CAV: AVG Limit [dBμV]	CAV Margin [dB]	Correction [dB]	Line	Meas. BW [kHz]
1	0.168	38.35	65.06	26.71	15.13	55.06	39.93	9.79	N	9.000
1	0.519	38.20	56.00	17.80	22.80	46.00	23.20	9.75	N	9.000
1	1.347	34.76	56.00	21.24	21.33	46.00	24.67	9.79	N	9.000
1	8.070	41.38	60.00	18.62	30.73	50.00	19.27	10.64	N	9.000
1	10.896	39.99	60.00	20.01	30.60	50.00	19.40	11.22	N	9.000
1	18.785	30.77	60.00	29.23	21.65	50.00	28.35	13.23	N	9.000

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Limit value- Emission level
4. Correction factor = Insertion loss + Cable loss + Attenuate
5. Emission Level = Correction Factor + Reading Value.





2.2 RADIATED EMISSION MEASUREMENT

2.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

TEST STANDARD: FCC Part 15, Subpart B (Section: 15.109)

Emissions radiated outside of the specified bands, shall be according to the general radiated limits as following:

Radiated Emissions Limits at 3 meters (dB μ V/m)		
Frequencies (MHz)	FCC 15B Class A	FCC 15B Class B
30-88	49.54	40
88-216	53.98	43.5
216-960	56.9	46
960-1000	60	54
Above 1000	Avg: 60 Peak: 80	Avg: 54 Peak: 74

Frequency Range (For unintentional radiators)

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705-108	1000
108-500	2000
500-1000	5000
Above 1000	5 th harmonic of the highest frequency or 40GHz, whichever is lower

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
 2. Emission level (dB μ V/m) = 20 log Emission level (μ V/m).
 3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.
 4. QP detector shall be applied if not specified.



2.2.2 TEST INSTRUMENTS

Frequency range below 1GHz

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
3m Semi-anechoic Chamber	TDK	9m*6m*6m	HRSW-SZ-EMC-02Chamber	Aug.20,25	Aug.19,28
Bilog Antenna	SCHWARZBECK	VULB 9163	1264	Jul.04,25	Jul.03,27
EMI Test Receiver	R&S	ESW44	101973	Mar.28,24	Mar.27,26
Measurement Software	R&S	ELEKTRA	N/A	N/A	N/A
6DB attenuator	Tonscend Technology Co., Ltd	N/A	23062787	N/A	N/A
Pre-Amplifier	R&S	SCU08F1	101028	Jan.22,24	Jan.21,26
CABLE	R&S	W13.01	N/A	Apr.26,25	Apr.25,26
CABLE	R&S	W13.02	N/A	Apr.26,25	Apr.25,26
CABLE	R&S	W12.14	N/A	Apr.26,25	Apr.25,26

Frequency range above 1GHz

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
3m Fully-anechoic Chamber	TDK	9m*6m*6m	HRSW-SZ-EMC-01Chamber	Nov.24,22	Nov.23,25
3m Fully-anechoic Chamber	TDK	9m*6m*6m	HRSW-SZ-EMC-01Chamber	Nov.23,25	Nov.22,28
Horn Antenna	ETS-LINDGREN	3117	227836	Aug.20,25	Aug.19,27
EMI Test Receiver	R&S	ESW44	101973	Mar.28,24	Mar.27,26
Pre-Amplifier	R&S	SCU08F1	101028	Jan.22,24	Jan.21,26
Measurement Software	R&S	ELEKTRA	N/A	N/A	N/A
CABLE	R&S	W13.01	N/A	Apr.26,25	Apr.25,26
CABLE	R&S	W13.02	N/A	Apr.26,25	Apr.25,26
CABLE	R&S	W12.14	N/A	Apr.26,25	Apr.25,26

NOTE: 1. The calibration interval of the above test instruments is 12/ 24/ 36 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
2. The test was performed in 3m Chamber.



2.2.3 TEST PROCEDURE

<Frequency Range below 1GHz>

The basic test procedure was in accordance with ANSI C63.4:2014 (section 12).

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from 1 meter to 4 meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1GHz.

NOTE:

1. The resolution bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. $\text{Emission level(dBuV/m)} = \text{Raw Value(dBuV)} + \text{Correction Factor(dB/m)}$
3. $\text{Correction Factor(dB/m)} = \text{Antenna Factor (dB/m)} + \text{Cable Factor (dB)}$ (if the raw value not contains the amplifier);
4. $\text{Correction Factor(dB/m)} = \text{Antenna Factor (dB/m)} + \text{Cable Factor (dB)} - \text{Amplifier Gain(dB)}$ (if the raw value contains the amplifier).
5. $\text{Margin value} = \text{Limit value} - \text{Emission level}$.



<Frequency Range above 1GHz>

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter fully-anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. The bore sight should be used during the test above 1GHz.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz

NOTE:

1. The resolution bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth is 1MHz and video bandwidth of test receiver/spectrum analyzer is 3MHz for Peak detection at frequency above 1GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth of test receiver/spectrum analyzer is 1Hz for Average detection (AV) at frequency above 1GHz.
3. For measurement of frequency above 1000 MHz, the EUT was set 3 meters away from the receiver antenna.
4. $\text{Emission level(dBuV/m)} = \text{Raw Value(dBuV)} + \text{Correction Factor(dB/m)}$
5. $\text{Correction Factor(dB/m)} = \text{Antenna Factor (dB/m)} + \text{Cable Factor (dB)}$ (if the raw value not contains the amplifier);
6. $\text{Correction Factor(dB/m)} = \text{Antenna Factor (dB/m)} + \text{Cable Factor (dB)} - \text{Amplifier Gain(dB)}$ (if the raw value contains the amplifier)
7. $\text{Margin value} = \text{Limit value} - \text{Emission level}$.


2.2.4 DEVIATION FROM TEST STANDARD

No deviation.




2.2.5 TEST SETUP

<Frequency Range below 1GHz>



<Frequency Range above 1GHz>



Note: Above 1G is a directional antenna depends on the EUT height and the antenna 3dB bandwidth both, refer to section 7.3 of CISPR 16-2-3.

2.2.6 EUT OPERATING CONDITIONS

Same as item 2.1.6.



2.2.7 TEST RESULTS


TEST VOLTAGE	Input 120 Vac, 60 Hz	FREQUENCY RANGE	30-1000 MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	DETECTOR FUNCTION & RESOLUTION BANDWIDTH	Quasi-Peak, 120 kHz
TESTED BY	Hanwen Xu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	QPK Level [dBμV/m]	QPK Limit [dBμV/m]	QPK Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]	Meas. BW [kHz]
1	47.676	25.04	40.00	14.96	-10.16	H	4.9	1.00	120.000
1	99.948	19.52	43.50	23.98	-12.20	H	0.9	2.00	120.000
1	215.054	15.57	43.50	27.93	-11.27	H	0.9	2.00	120.000
1	401.348	19.24	46.00	26.76	-4.09	H	287.9	2.00	120.000
1	626.227	23.40	46.00	22.60	-2.29	H	359.1	1.00	120.000
1	889.689	40.49	46.00	5.51	1.57	H	2.6	2.00	120.000

REMARKS:

1. Emission level(dBuV/m)=Read Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) -Amplifier Gain
3. The other emission levels were very low against the limit.
4. Margin value = Limit value –. Emission level.






TEST VOLTAGE	Input 120 Vac, 60 Hz	FREQUENCY RANGE	30-1000 MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70 %RH	DETECTOR FUNCTION & RESOLUTION BANDWIDTH	Quasi-Peak, 120 kHz
TESTED BY	Hanwen Xu		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	QPK Level [dBμV/m]	QPK Limit [dBμV/m]	QPK Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]	Meas. BW [kHz]
1	33.179	31.17	40.00	8.83	-13.03	V	226.4	1.00	120.000
1	46.652	25.32	40.00	14.68	-10.21	V	2.4	2.00	120.000
1	75.806	19.37	40.00	20.63	-16.13	V	133.6	2.00	120.000
1	171.243	21.99	43.50	21.51	-13.89	V	149.8	1.00	120.000
1	341.316	18.21	46.00	27.79	-5.67	V	226.4	1.00	120.000
1	633.987	23.42	46.00	22.58	-2.35	V	0.9	2.00	120.000

REMARKS:

1. Emission level(dBuV/m)=Read Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) -Amplifier Gain
3. The other emission levels were very low against the limit.
4. Margin value = Limit value – Emission level.






TEST VOLTAGE	Input 120 Vac, 60 Hz	FREQUENCY RANGE	1-18 GHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70 %RH	DETECTOR FUNCTION & RESOLUTION BANDWIDTH	Peak/Average, 1 MHz
TESTED BY	Hanwen Xu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,036.500	44.20	74.00	29.80	32.32	54.00	21.68	5.97	H	176.1	1.00
1	3,839.000	48.24	74.00	25.76	35.31	54.00	18.69	9.09	H	1	1.00
1	7,455.000	58.98	74.00	15.02	47.42	54.00	6.58	16.20	H	359	1.00

REMARKS:

1. Peak detector quick scan is shown on the graph and final quasi-peak detector data is measured corresponding to relevant limit and recorded in the data table.
2. Negative sign (-) in the margin column signify levels below the limit.
3. Frequency range scanned: 1GHz to 5th harmonic of the highest frequency or 40GHz, whichever is lower. For frequency above 18GHz, the emission was tested 20db below the limit so the data not recorded in the sheet.
4. Only emissions significantly above the equipment noise floor are reported.






TEST VOLTAGE	Input 120 Vac, 60 Hz	FREQUENCY RANGE	1-18 GHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70 %RH	DETECTOR FUNCTION & RESOLUTION BANDWIDTH	Peak/Average, 1 MHz
TESTED BY	Hanwen Xu		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	1,961.500	42.30	74.00	31.70	30.55	54.00	23.45	4.96	V	173.8	1.00
1	3,814.000	45.50	74.00	28.50	33.58	54.00	20.42	8.97	V	359.1	1.00
1	7,515.000	51.83	74.00	22.17	39.03	54.00	14.97	16.18	V	316	1.00

REMARKS:

1. Peak detector quick scan is shown on the graph and final quasi-peak detector data is measured corresponding to relevant limit and recorded in the data table.
2. Negative sign (-) in the margin column signify levels below the limit.
3. Frequency range scanned: 1GHz to 5th harmonic of the highest frequency or 40GHz, whichever is lower. For frequency above 18GHz, the emission was tested 20db below the limit so the data not recorded in the sheet.
4. Only emissions significantly above the equipment noise floor are reported.





3 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications were made to the EUT by the lab during the test.

---END---