FCC Test Report (BT-EDR)

Report No.: RF170908C01-2

FCC ID: HD5CT60L0N

Test Model: CT60L0N

Received Date: Sep. 08, 2017

Test Date: Oct. 06 to 18, 2017

Issued Date: Oct. 27, 2017

Applicant: Honeywell International Inc.

Address: 9680 Old Bailes Road, Fort Mill, SC 29707 USA

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300, Taiwan R.O.C.

Test Location : E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300, Taiwan R.O.C.

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

Release Control Record **4**

1 Certificate of Conformity **5**

2 Summary of Test Results **6**

2.1 Measurement Uncertainty 6
2.2 Modification Record 6

3 General Information **7**

3.1 General Description of EUT (BT-EDR) 7
3.2 Description of Test Modes 9
3.2.1 Test Mode Applicability and Tested Channel Detail 10
3.3 Description of Support Units 12
3.3.1 Configuration of System under Test 13
3.4 General Description of Applied Standards 14

4 Test Types and Results **15**

4.1 Radiated Emission and Bandedge Measurement 15
4.1.1 Limits of Radiated Emission and Bandedge Measurement 15
4.1.2 Test Instruments 16
4.1.3 Test Procedures 17
4.1.4 Deviation from Test Standard 17
4.1.5 Test Setup 18
4.1.6 EUT Operating Conditions 19
4.1.7 Test Results 20
4.2 Conducted Emission Measurement 27
4.2.1 Limits of Conducted Emission Measurement 27
4.2.2 Test Instruments 27
4.2.3 Test Procedures 28
4.2.4 Deviation from Test Standard 28
4.2.5 Test Setup 28
4.2.6 EUT Operating Condition 28
4.2.7 Test Results (Mode 1) 29
4.2.8 Test Results (Mode 2) 31
4.3 Number of Hopping Frequency Used 33
4.3.1 Limits of Hopping Frequency Used Measurement 33
4.3.2 Test Setup 33
4.3.3 Test Instruments 33
4.3.4 Test Procedure 33
4.3.5 Deviation from Test Standard 33
4.3.6 Test Results 34
4.4 Dwell Time on Each Channel 35
4.4.1 Limits of Dwell Time on Each Channel Measurement 35
4.4.2 Test Setup 35
4.4.3 Test Instruments 35
4.4.4 Test Procedures 35
4.4.5 Deviation from Test Standard 35
4.4.6 Test Results 36
4.5 Channel Bandwidth 40
4.5.1 Limits of Channel Bandwidth Measurement 40
4.5.2 Test Setup 40
4.5.3 Test Instruments 40
4.5.4 Test Procedure 40
4.5.5 Deviation from Test Standard 40
4.5.6 EUT Operating Condition 40
4.5.7 Test Results 41
4.6 Hopping Channel Separation 42

4.6.1 Limits of Hopping Channel Separation Measurement 42
4.6.2 Test Setup 42
4.6.3 Test Instruments 42
4.6.4 Test Procedure 42
4.6.5 Deviation from Test Standard 42
4.6.6 Test Results 43
4.7 Maximum Output Power 44
4.7.1 Limits of Maximum Output Power Measurement 44
4.7.2 Test Setup 44
4.7.3 Test Instruments 44
4.7.4 Test Procedure 44
4.7.5 Deviation from Test Standard 44
4.7.6 EUT Operating Condition 44
4.7.7 Test Results 45
4.8 Conducted Out of Band Emission Measurement 46
4.8.1 Limits of Conducted Out of Band Emission Measurement 46
4.8.2 Test Instruments 46
4.8.3 Test Procedure 46
4.8.4 Deviation from Test Standard 46
4.8.5 EUT Operating Condition 46
4.8.6 Test Results 46

5 Pictures of Test Arrangements 49

Appendix – Information on the Testing Laboratories 50

Release Control Record

Issue No.	Description	Date Issued
RF170908C01-2	Original release.	Oct. 27, 2017

1 Certificate of Conformity

Product: Dolphin CT60

Brand: Honeywell

Test Model: CT60L0N

Sample Status: ENGINEERING SAMPLE

Applicant: Honeywell International Inc.

Test Date: Oct. 06 to 18, 2017

Standards: 47 CFR FCC Part 15, Subpart C (Section 15.247)
ANSI C63.10: 2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

:

Prepared by _____ , **Date:** Oct. 27, 2017
Wendy Wu / Specialist

Approved by : _____ , **Date:** Oct. 27, 2017
May Chen / Manager

2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (SECTION 15.247)			
FCC Clause	Test Item	Result	Remarks
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -12.79dB at 0.56016MHz.
15.247(a)(1)(iii)	Number of Hopping Frequency Used	PASS	Meet the requirement of limit.
15.247(a)(1)(iii)	Dwell Time on Each Channel	PASS	Meet the requirement of limit.
15.247(a)(1)	1. Hopping Channel Separation 2. Spectrum Bandwidth of a Frequency Hopping Sequence Spread Spectrum System	PASS	Meet the requirement of limit.
15.247(b)	Maximum Peak Output Power	PASS	Meet the requirement of limit.
15.205 & 209 & 15.247(d)	Radiated Emissions & Band Edge Measurement	PASS	Meet the requirement of limit. Minimum passing margin is -10.0dB at 2390.00MHz.
15.247(d)	Antenna Port Emission	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	No antenna connector is used.

NOTE: If The Frequency Hopping System operating in 2400-2483.5MHz band and the output power less than 125mW. The hopping channel carrier frequencies separated by a minimum of 25kHz or two-thirds of the 20dB bandwidth of hopping channel whichever is greater.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) (±)
Conducted Emissions at mains ports	150kHz ~ 30MHz	1.84 dB
Radiated Emissions up to 1 GHz	30MHz ~ 1GHz	5.30 dB
Radiated Emissions above 1 GHz	1GHz ~ 6GHz	5.16 dB
	6GHz ~ 18GHz	4.91 dB
	18GHz ~ 40GHz	5.30 dB

2.2 Modification Record

There were no modifications required for compliance.

3 General Information

3.1 General Description of EUT (BT-EDR)

Product	Dolphin CT60
Brand	Honeywell
Test Model	CT60L0N
Status of EUT	ENGINEERING SAMPLE
HW Version	V1.0
SW Version	0179D
Power Supply Rating	3.6Vdc from battery 5Vdc from USB interface
Modulation Type	GFSK, π/4-DQPSK, 8DPSK
Modulation Technology	FHSS
Transfer Rate	Up to 3Mbps
Operating Frequency	2402MHz ~ 2480MHz
Number of Channel	79
Output Power	5.176mW
Antenna Type	Refer to Note
Antenna Connector	Refer to Note
Accessory Device	Battery x 1
Data Cable Supplied	USB snap-on adapter x 1 (1.25m, Shielded with two cores)

Note:

1. There are WLAN, Bluetooth and NFC technology used for the EUT.
2. Simultaneously transmission condition.

Condition	Technology	
1	WLAN 2.4GHz	NFC
2	WLAN 5GHz	NFC
3	Bluetooth	NFC
Note: The emission of the simultaneous operation has been evaluated and no non-compliance was found.		

3. The EUT needs to be supplied from battery, the information is as below table:

Brand	Model No.	Spec.
Inventus	CT50-BTSC	3.6Vdc, 4040mAh, 14.6Wh

4. The antennas provided to the EUT, please refer to the following table:

WLAN / Bluetooth Antenna Spec.				
Antenna No.	Antenna Gain include path loss (dBi)	Frequency rang (GHz)	Antenna type	Connector type
1	0.62	2.4~2.4835	PIFA	UFL
	1.14	5.15~5.25		
	1.14	5.25~5.35		
	1.14	5.47~5.725		
	1.14	5.725~5.85		

NFC Antenna Spec.			
Antenna No.	Frequency rang (MHz)	Antenna type	Connector type
1	13~14	Loop	NA
Note: 1. The antenna has path loss. 2.4GHz: 1dB; 5GHz: 1.7dB			

5. For the radiated emissions, the EUT was pre-tested under the following modes:

Test Mode	Description
Mode A	**Power from laptop**
Mode B	Power from adapter

From the above modes, the worst case was found in **Mode A**. Therefore only the test data of the mode was recorded in this report.

6. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

3.2 Description of Test Modes

79 channels are provided for BT-EDR mode:

Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		

3.2.1 Test Mode Applicability and Tested Channel Detail

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE≥1G	RE<1G	PLC	APCM	
1	√	√	√	√	Power from Laptop
2	-	-	√	-	Power from Adapter

Where **RE≥1G:** Radiated Emission above 1GHz **RE<1G:** Radiated Emission below 1GHz
PLC: Power Line Conducted Emission **APCM:** Antenna Port Conducted Measurement

NOTE: The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on **Z-plane (below 1GHz) & X-plane (Above 1GHz).**

NOTE: "-"means no effect.

Radiated Emission Test (Above 1GHz):

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
0 to 78	0, 39, 78	FHSS	GFSK	DH5
0 to 78	0, 39, 78	FHSS	8DPSK	3DH5

Radiated Emission Test (Below 1GHz):

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
0 to 78	0	FHSS	GFSK	DH5

Power Line Conducted Emission Test:

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
0 to 78	0	FHSS	GFSK	DH5

Antenna Port Conducted Measurement:

☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
0 to 78	0, 39, 78	FHSS	GFSK	DH5
0 to 78	0, 39, 78	FHSS	8DPSK	3DH5

Test Condition:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER (System)	TESTED BY
RE≥1G	24deg. C, 64%RH	120Vac, 60Hz	Jyunchun Lin
RE<1G	24deg. C, 62%RH	120Vac, 60Hz	Jyunchun Lin
PLC	26deg. C, 73%RH	120Vac, 60Hz	Andy Ho
APCM	25deg. C, 60%RH	120Vac, 60Hz	Anderson Chen

3.3 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A.	Laptop	HP	Pavilion 14-ab023TU	5CD5340WXZ	FCC DoC	Provided by Lab
		DELL	E6440	F9LYQ32	FCC DoC	Provided by Lab (For Conducted Emission)
B.	Micro SD Card	Transcend	16GB	NA	NA	Provided by Lab
C.	USB Adapter	ASUS	EXA1205UA	NA	NA	Provided by Lab

Note:

1. All power cords of the above support units are non-shielded (1.8m).

ID	Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1.	USB Charging Cable	1	1.25	Yes	2	Supplied by client(for RF Setup)

Note: The core(s) is(are) originally attached to the cable(s).

3.3.1 Configuration of System under Test

Mode 1



Mode 2



3.4 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C (15.247)
ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

Note: The EUT has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.

4 Test Types and Results

4.1 Radiated Emission and Bandedge Measurement

4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.1.2 Test Instruments

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver Keysight	N9038A	MY54450088	July 08, 2017	July 07, 2018
Pre-Amplifier(*) EMCI	EMC001340	980142	Jan. 20, 2016	Jan. 19, 2018
Loop Antenna(*) Electro-Metrics	EM-6879	264	Dec. 16, 2016	Dec. 15, 2018
RF Cable	NA	LOOPCAB-001 LOOPCAB-002	Jan. 17, 2017	Jan. 16, 2018
Pre-Amplifier Mini-Circuits	ZFL-1000VH2B	AMP-ZFL-01	Nov. 10, 2016	Nov. 09, 2017
Trilog Broadband Antenna SCHWARZBECK	VULB 9168	9168-406	Dec. 13, 2016	Dec. 12, 2017
RF Cable	8D	966-4-1 966-4-2 966-4-3	Apr. 01, 2017	Mar. 31, 2018
Fixed attenuator Mini-Circuits	UNAT-5+	PAD-3m-4-01	Oct. 03, 2017	Oct. 02, 2018
Horn_Antenna SCHWARZBECK	BBHA 9120D	9120D-783	Dec. 27, 2016	Dec. 26, 2017
Pre-Amplifier EMCI	EMC12630SE	980385	Feb. 02, 2017	Feb. 01, 2018
RF Cable	EMC104-SM-SM-1200 EMC104-SM-SM-2000 EMC104-SM-SM-5000	160923 150318 150321	Feb. 02, 2017 Mar. 29, 2017 Mar. 29, 2017	Feb. 01, 2018 Mar. 28, 2018 Mar. 28, 2018
Pre-Amplifier EMCI	EMC184045SE	980387	Feb. 02, 2017	Feb. 01, 2018
Horn_Antenna SCHWARZBECK	BBHA 9170	BBHA9170608	Dec. 15, 2016	Dec. 14, 2017
RF Cable	SUCOFLEX 102	36432/2 36433/2	Jan. 15, 2017	Jan. 14, 2018
Software	ADT_Radiated_V8.7.08	NA	NA	NA
Antenna Tower & Turn Table Max-Full	MF-7802	MF780208410	NA	NA
Boresight Antenna Fixture	FBA-01	FBA-SIP02	NA	NA
Spectrum Analyzer R&S	FSv40	100964	July 1, 2017	June 30, 2018
Power meter Anritsu	ML2495A	1014008	May 11, 2017	May 10, 2018
Power sensor Anritsu	MA2411B	0917122	May 11, 2017	May 10, 2018

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. *The calibration interval of the above test instruments is 24 months and the calibrations are traceable to NML/ROC and NIST/USA.
3. The test was performed in 966 Chamber No. 4.
4. The FCC Designation Number is TW2020.
5 Loop antenna was used for all emissions below 30 MHz.
6. The CANADA Site Registration No. is 20331-2
7. Tested Date: Oct. 06 to 12, 2017

4.1.3 Test Procedures

For Radiated emission below 30MHz

a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. Both X and Y axes of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

For Radiated emission above 30MHz

a. The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.

f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 Deviation from Test Standard

No deviation.

4.1.5 Test Setup

For Radiated emission below 30MHz



For Radiated emission 30MHz to 1GHz



For Radiated emission above 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT Operating Conditions

a. Connected the EUT with the Laptop.

b. Controlling software (QRCT_Version3.0.268.0) has been activated to set the EUT on specific status.

4.1.7 Test Results

Above 1GHz Data:

BT_GFSK

CHANNEL	TX Channel 0	**DETECTOR FUNCTION**	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	**FREQ. (MHz)**	**EMISSION LEVEL (dBuV/m)**	**LIMIT (dBuV/m)**	**MARGIN (dB)**	**ANTENNA HEIGHT (m)**	**TABLE ANGLE (Degree)**	**RAW VALUE (dBuV)**	**CORRECTION FACTOR (dB/m)**
1	2390.00	56.8 PK	74.0	-17.2	1.00 H	171	58.1	-1.3
2	2390.00	43.9 AV	54.0	-10.1	1.00 H	171	45.2	-1.3
3	*2402.00	107.6 PK			1.00 H	171	108.7	-1.1
4	*2402.00	77.5 AV			1.00 H	171	78.6	-1.1
5	4804.00	39.8 PK	74.0	-34.2	1.01 H	243	36.6	3.2
6	4804.00	9.7 AV	54.0	-44.3	1.01 H	243	6.5	3.2
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	**FREQ. (MHz)**	**EMISSION LEVEL (dBuV/m)**	**LIMIT (dBuV/m)**	**MARGIN (dB)**	**ANTENNA HEIGHT (m)**	**TABLE ANGLE (Degree)**	**RAW VALUE (dBuV)**	**CORRECTION FACTOR (dB/m)**
1	2390.00	54.6 PK	74.0	-19.4	1.53 V	259	55.9	-1.3
2	2390.00	41.7 AV	54.0	-12.3	1.53 V	259	43.0	-1.3
3	*2402.00	103.5 PK			1.53 V	259	104.6	-1.1
4	*2402.00	73.4 AV			1.53 V	259	74.5	-1.1
5	4804.00	40.3 PK	74.0	-33.7	1.07 V	51	37.1	3.2
6	4804.00	10.2 AV	54.0	-43.8	1.07 V	51	7.0	3.2

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: 20log(3.125 / 100)= -30.1 dB
7. The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle)

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	107.5 PK			1.06 H	156	108.7	-1.2
2	*2441.00	77.4 AV			1.06 H	156	78.6	-1.2
3	4882.00	39.4 PK	74.0	-34.6	1.02 H	245	36.0	3.4
4	4882.00	9.3 AV	54.0	-44.7	1.02 H	245	5.9	3.4
5	7323.00	43.9 PK	74.0	-30.1	3.15 H	240	34.1	9.8
6	7323.00	13.8 AV	54.0	-40.2	3.15 H	240	4.0	9.8
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	103.6 PK			1.55 V	247	104.8	-1.2
2	*2441.00	73.5 AV			1.55 V	247	74.7	-1.2
3	4882.00	40.1 PK	74.0	-33.9	1.13 V	67	36.7	3.4
4	4882.00	10.0 AV	54.0	-44.0	1.13 V	67	6.6	3.4
5	7323.00	43.7 PK	74.0	-30.3	2.11 V	288	33.9	9.8
6	7323.00	13.6 AV	54.0	-40.4	2.11 V	288	3.8	9.8

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: 20log(3.125 / 100)= -30.1 dB
7. The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle)

CHANNEL	TX Channel 78	DETECTOR FUNCTION	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	107.5 PK			1.50 H	354	108.5	-1.0
2	*2480.00	77.4 AV			1.50 H	354	78.4	-1.0
3	2483.50	56.6 PK	74.0	-17.4	1.50 H	354	57.6	-1.0
4	2483.50	26.5 AV	54.0	-27.5	1.50 H	354	27.5	-1.0
5	4960.00	39.8 PK	74.0	-34.2	1.01 H	258	36.2	3.6
6	4960.00	9.7 AV	54.0	-44.3	1.01 H	258	6.1	3.6
7	7440.00	43.8 PK	74.0	-30.2	3.12 H	243	33.7	10.1
8	7440.00	13.7 AV	54.0	-40.3	3.12 H	243	3.6	10.1
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	103.4 PK			1.20 V	197	104.4	-1.0
2	*2480.00	73.3 AV			1.20 V	197	74.3	-1.0
3	2483.50	54.5 PK	74.0	-19.5	1.20 V	197	55.5	-1.0
4	2483.50	24.4 AV	54.0	-29.6	1.20 V	197	25.4	-1.0
5	4960.00	40.0 PK	74.0	-34.0	1.09 V	66	36.4	3.6
6	4960.00	9.9 AV	54.0	-44.1	1.09 V	66	6.3	3.6
7	7440.00	44.3 PK	74.0	-29.7	2.14 V	302	34.2	10.1
8	7440.00	14.2 AV	54.0	-39.8	2.14 V	302	4.1	10.1

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: 20log(3.125 / 100)= -30.1 dB
7. The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle)

BT_8DPSK

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	56.9 PK	74.0	-17.1	1.00 H	159	58.2	-1.3
2	**2390.00**	**44.0 AV**	**54.0**	**-10.0**	**1.00 H**	**159**	**45.3**	**-1.3**
3	*2402.00	106.7 PK			1.00 H	159	107.8	-1.1
4	*2402.00	76.6 AV			1.00 H	159	77.7	-1.1
5	4804.00	40.4 PK	74.0	-33.6	1.00 H	246	37.2	3.2
6	4804.00	10.3 AV	54.0	-43.7	1.00 H	246	7.1	3.2
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	54.8 PK	74.0	-19.2	1.14 V	257	56.1	-1.3
2	2390.00	41.9 AV	54.0	-12.1	1.14 V	257	43.2	-1.3
3	*2402.00	102.0 PK			1.14 V	257	103.1	-1.1
4	*2402.00	71.9 AV			1.14 V	257	73.0	-1.1
5	4804.00	39.9 PK	74.0	-34.1	1.12 V	74	36.7	3.2
6	4804.00	9.8 AV	54.0	-44.2	1.12 V	74	6.6	3.2

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: 20log(3.125 / 100)= -30.1 dB
7. The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle)

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	106.6 PK			1.04 H	154	107.8	-1.2
2	*2441.00	76.5 AV			1.04 H	154	77.7	-1.2
3	4882.00	39.4 PK	74.0	-34.6	1.00 H	254	36.0	3.4
4	4882.00	9.3 AV	54.0	-44.7	1.00 H	254	5.9	3.4
5	7323.00	44.1 PK	74.0	-29.9	3.14 H	232	34.3	9.8
6	7323.00	14.0 AV	54.0	-40.0	3.14 H	232	4.2	9.8
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	101.9 PK			1.19 V	269	103.1	-1.2
2	*2441.00	71.8 AV			1.19 V	269	73.0	-1.2
3	4882.00	40.1 PK	74.0	-33.9	1.15 V	68	36.7	3.4
4	4882.00	10.0 AV	54.0	-44.0	1.15 V	68	6.6	3.4
5	7323.00	44.6 PK	74.0	-29.4	2.14 V	294	34.8	9.8
6	7323.00	14.5 AV	54.0	-39.5	2.14 V	294	4.7	9.8

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: 20log(3.125 / 100)= -30.1 dB
7. The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle)

CHANNEL	TX Channel 78	DETECTOR FUNCTION	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	106.9 PK			1.02 H	165	107.9	-1.0
2	*2480.00	76.8 AV			1.02 H	165	77.8	-1.0
3	2483.50	57.2 PK	74.0	-16.8	1.02 H	165	58.2	-1.0
4	2483.50	27.1 AV	54.0	-26.9	1.02 H	165	28.1	-1.0
5	4960.00	39.6 PK	74.0	-34.4	1.01 H	270	36.0	3.6
6	4960.00	9.5 AV	54.0	-44.5	1.01 H	270	5.9	3.6
7	7440.00	43.6 PK	74.0	-30.4	3.06 H	238	33.5	10.1
8	7440.00	13.5 AV	54.0	-40.5	3.06 H	238	3.4	10.1

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	102.0 PK			1.16 V	260	103.0	-1.0
2	*2480.00	71.9 AV			1.16 V	260	72.9	-1.0
3	2483.50	55.1 PK	74.0	-18.9	1.16 V	260	56.1	-1.0
4	2483.50	25.0 AV	54.0	-29.0	1.16 V	260	26.0	-1.0
5	4960.00	40.6 PK	74.0	-33.4	1.04 V	76	37.0	3.6
6	4960.00	10.5 AV	54.0	-43.5	1.04 V	76	6.9	3.6
7	7440.00	44.3 PK	74.0	-29.7	2.08 V	317	34.2	10.1
8	7440.00	14.2 AV	54.0	-39.8	2.08 V	317	4.1	10.1

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: 20log(3.125 / 100)= -30.1 dB
7. The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle)

Below 1GHz Data:

BT_GFSK

CHANNEL	TX Channel 0	**DETECTOR FUNCTION**	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	**FREQ. (MHz)**	**EMISSION LEVEL (dBuV/m)**	**LIMIT (dBuV/m)**	**MARGIN (dB)**	**ANTENNA HEIGHT (m)**	**TABLE ANGLE (Degree)**	**RAW VALUE (dBuV)**	**CORRECTION FACTOR (dB/m)**
1	102.34	24.2 QP	43.5	-19.3	2.00 H	255	36.3	-12.1
2	165.92	24.6 QP	43.5	-18.9	2.00 H	104	32.9	-8.3
3	233.92	32.1 QP	46.0	-13.9	1.50 H	360	42.4	-10.3
4	525.28	26.0 QP	46.0	-20.0	2.00 H	167	28.4	-2.4
5	718.43	31.3 QP	46.0	-14.7	1.00 H	96	30.2	1.1
6	916.73	33.3 QP	46.0	-12.7	2.50 H	360	28.9	4.4
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	**FREQ. (MHz)**	**EMISSION LEVEL (dBuV/m)**	**LIMIT (dBuV/m)**	**MARGIN (dB)**	**ANTENNA HEIGHT (m)**	**TABLE ANGLE (Degree)**	**RAW VALUE (dBuV)**	**CORRECTION FACTOR (dB/m)**
1	30.17	27.5 QP	40.0	-12.5	1.00 V	360	37.0	-9.5
2	127.61	24.3 QP	43.5	-19.2	1.00 V	285	33.7	-9.4
3	240.88	23.6 QP	46.0	-22.4	1.50 V	239	33.5	-9.9
4	606.52	28.2 QP	46.0	-17.8	2.00 V	360	28.5	-0.3
5	721.59	31.1 QP	46.0	-14.9	2.00 V	353	30.0	1.1
6	914.08	32.5 QP	46.0	-13.5	2.00 V	360	28.2	4.3

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

4.2 Conducted Emission Measurement

4.2.1 Limits of Conducted Emission Measurement

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

4.2.2 Test Instruments

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver R&S	ESCS 30	847124/029	Oct. 24, 2016	Oct. 23, 2017
Line-Impedance Stabilization Network (for EUT) R&S	ESH3-Z5	848773/004	Oct. 26, 2016	Oct. 25, 2017
Line-Impedance Stabilization Network (for Peripheral) R&S	ENV216	100072	June 03, 2017	June 02, 2018
50 ohms Terminator	N/A	EMC-02	Sep. 22, 2017	Sep. 21, 2018
RF Cable	5D-FB	COCCAB-001	Sep. 29, 2017	Sep. 28, 2018
10 dB PAD Mini-Circuits	HAT-10+	CONATT-004	June 18, 2017	June 17, 2018
Software BVADT	BVADT_Cond_ V7.3.7.4	NA	NA	NA

Note:

1. The calibration interval of the above test instruments are 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in Shielded Room No. 1.
3 Tested Date: Oct. 17 to 18, 2017

4.2.3 Test Procedures

a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.

b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.

c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

NOTE: The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.

4.2.4 Deviation from Test Standard

No deviation.

4.2.5 Test Setup



Note: 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT Operating Condition

Controlling software (QRCT_Version3.0.268.0) has been activated to set the EUT on specific status.

4.2.7 Test Results (Mode 1)

Phase	Line (L)	Detector Function	Quasi-Peak (QP) / Average (AV)

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.24766	10.07	34.36	24.38	44.43	34.45	61.84	51.84	-17.41	-17.39
2	0.45859	10.11	28.97	21.94	39.08	32.05	56.72	46.72	-17.64	-14.67
3	0.57578	10.12	28.88	17.65	39.00	27.77	56.00	46.00	-17.00	-18.23
4	0.67344	10.12	28.76	20.70	38.88	30.82	56.00	46.00	-17.12	-15.18
5	0.79844	10.13	24.34	14.66	34.47	24.79	56.00	46.00	-21.53	-21.21
6	3.71094	10.28	18.93	12.14	29.21	22.42	56.00	46.00	-26.79	-23.58

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.



Phase	Neutral (N)	Detector Function	Quasi-Peak (QP) / Average (AV)

No	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
		Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15000	10.06	24.14	14.52	34.20	24.58	66.00	56.00	-31.80	-31.42
2	0.25547	10.05	28.96	14.51	39.01	24.56	61.58	51.58	-22.57	-27.02
3	0.45078	10.10	28.54	23.16	38.64	33.26	56.86	46.86	-18.22	-13.60
4	0.57578	10.10	29.00	16.78	39.10	26.88	56.00	46.00	-16.90	-19.12
5	0.67344	10.10	28.52	20.68	38.62	30.78	56.00	46.00	-17.38	-15.22
6	3.41797	10.21	24.63	18.56	34.84	28.77	56.00	46.00	-21.16	-17.23

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.



4.2.8 Test Results (Mode 2)

Phase	Line (L)	Detector Function	Quasi-Peak (QP) / Average (AV)

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16172	10.08	34.64	22.59	44.72	32.67	65.38	55.38	-20.66	-22.71
2	0.18125	10.07	34.47	23.84	44.54	33.91	64.43	54.43	-19.89	-20.52
3	0.20859	10.07	31.00	21.29	41.07	31.36	63.26	53.26	-22.19	-21.90
4	**0.56016**	**10.13**	**32.39**	**23.08**	**42.52**	**33.21**	**56.00**	**46.00**	**-13.48**	**-12.79**
5	0.91172	10.15	23.56	14.30	33.71	24.45	56.00	46.00	-22.29	-21.55
6	30.00000	11.75	14.83	9.30	26.58	21.05	60.00	50.00	-33.42	-28.95

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.



Phase	Neutral (N)	Detector Function	Quasi-Peak (QP) / Average (AV)

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15000	10.07	36.23	21.99	46.30	32.06	66.00	56.00	-19.70	-23.94
2	0.19297	10.04	30.67	16.85	40.71	26.89	63.91	53.91	-23.20	-27.02
3	0.55234	10.12	26.58	19.75	36.70	29.87	56.00	46.00	-19.30	-16.13
4	0.91953	10.12	19.77	12.67	29.89	22.79	56.00	46.00	-26.11	-23.21
5	2.07813	10.21	21.19	11.25	31.40	21.46	56.00	46.00	-24.60	-24.54
6	14.10547	10.95	14.39	9.24	25.34	20.19	60.00	50.00	-34.66	-29.81

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.



4.3 Number of Hopping Frequency Used

4.3.1 Limits of Hopping Frequency Used Measurement

At least 15 channels frequencies, and should be equally spaced.

4.3.2 Test Setup



4.3.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.3.4 Test Procedure

a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.

b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.

c. Set the SA on MaxHold Mode, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been recorded.

d. Set the SA on View mode and then plot the result on SA screen.

e. Repeat above procedures until all frequencies measured were complete.

4.3.5 Deviation from Test Standard

No deviation.

4.3.6 Test Results

There are 79 hopping frequencies in the hopping mode. Please refer to next page for the test result. On the plots, it shows that the hopping frequencies are equally spaced.

GFSK





8DPSK





4.4 Dwell Time on Each Channel

4.4.1 Limits of Dwell Time on Each Channel Measurement

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

4.4.2 Test Setup



4.4.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.4.4 Test Procedures

a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
c. Adjust the center frequency of SA on any frequency be measured and set SA to zero span mode. And then, set RBW and VBW of spectrum analyzer to proper value.
d. Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.
e. Repeat above procedures until all different time-slot modes have been completed.

.

4.4.5 Deviation from Test Standard

No deviation.

4.4.6 Test Results

GFSK

Mode	Number of transmission in a 31.6 (79Hopping*0.4)	Length of transmission time (msec)	Result (msec)	Limit (msec)
DH1	50 (times / 5 sec) * 6.32 = 316 times	0.438	138.41	400
DH3	27 (times / 5 sec) * 6.32 = 170.64 times	1.72	293.5	400
DH5	18 (times / 5 sec) * 6.32 = 344.01 times	3.024	344.01	400

NOTE: Test plots of the transmitting time slot are shown on next page.

DH1


RBW 100 kHz
VBW 300 kHz
SWT 5 s
[T1] MP CLRWR
[T2] MP VIEW
Ref 22 dBm
Att 20 dB
Offset 12 dB
Center 2.441 GHz
500 ms/


RBW 100 kHz
VBW 300 kHz
SWT 3 ms
[T1] MP VIEW
[T2] MP VIEW
Marker 1 [T1]
-57.63 dBm
1.278000 ms
Delta 2 [T1]
0.54 dB
438.000000 us
Ref 22 dBm
Att 20 dB
Offset 12 dB
Center 2.441 GHz
300 us/

DH3


RBW 100 kHz
VBW 300 kHz
SWT 5 s
[T1] MP CLRWR
[T2] MP VIEW
Ref 22 dBm
Att 20 dB
Offset 12 dB
Center 2.441 GHz
500 ms/


RBW 100 kHz
VBW 300 kHz
SWT 5 ms
[T1] MP VIEW
[T2] MP VIEW
Marker 1 [T1]
-59.29 dBm
1.620000 ms
Delta 2 [T1]
6.64 dB
1.720000 ms
Ref 22 dBm
Att 20 dB
Offset 12 dB
Center 2.441 GHz
500 us/

DH5


RBW 100 kHz
VBW 300 kHz
SWT 5 s
[T1] MP CLRWR
[T2] MP VIEW
Ref 22 dBm
Att 20 dB
Offset 12 dB
Center 2.441 GHz
500 ms/


RBW 100 kHz
VBW 300 kHz
SWT 8 ms
[T1] MP VIEW
[T2] MP VIEW
Marker 1 [T1]
-57.64 dBm
2.480000 ms
Delta 2 [T1]
1.28 dB
3.024000 ms
Ref 22 dBm
Att 20 dB
Offset 12 dB
Center 2.441 GHz
800 us/

8DPSK

Mode	Number of transmission in a 31.6 (79Hopping*0.4)	Length of transmission time (msec)	Result (msec)	Limit (msec)
3DH1	51 (times / 5 sec) * 6.32 = 322.32 times	0.432	139.24	400
3DH3	26 (times / 5 sec) * 6.32 = 164.32 times	1.74	285.92	400
3DH5	18 (times / 5 sec) * 6.32 = 113.76 times	3.024	344.01	400

NOTE: Test plots of the transmitting time slot are shown on next page.

3DH1





3DH3





3DH5





4.5 Channel Bandwidth

4.5.1 Limits of Channel Bandwidth Measurement

For frequency hopping system operating in the 2400-2483.5MHz, If the 20dB bandwidth of hopping channel is greater than 25kHz, two-thirds 20dBbandwidth of hopping channel shell be a minimum limit for the hopping channel separation.

4.5.2 Test Setup



4.5.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.5.4 Test Procedure

a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
c. Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.
d. Repeat above procedures until all frequencies measured were complete.

4.5.5 Deviation from Test Standard

No deviation.

4.5.6 EUT Operating Condition

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

4.5.7 Test Results

Channel	Frequency (MHz)	20dB Bandwidth (MHz)	
		GFSK	8DPSK
0	2402	0.94	1.29
39	2441	0.94	1.29
78	2480	0.94	1.30

Spectrum Plot of Worst Value

GFSK / CH 78



8DPSK / CH 78



4.6 Hopping Channel Separation

4.6.1 Limits of Hopping Channel Separation Measurement

At least 25kHz or two-third of 20dB hopping channel bandwidth (whichever is greater).

4.6.2 Test Setup



4.6.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.6.4 Test Procedure

Measurement Procedure REF

a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.

b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range.

c. By using the MaxHold function record the separation of two adjacent channels.

d. Measure the frequency difference of these two adjacent channels by SA MARK function. And then plot the result on SA screen.

e. Repeat above procedures until all frequencies measured were complete.

4.6.5 Deviation from Test Standard

No deviation.

4.6.6 Test Results

Channel	Frequency (MHz)	Adjacent Channel Separation (MHz)		20dB Bandwidth (MHz)		Minimum Limit (MHz)		Pass / Fail
		GFSK	8DPSK	GFSK	8DPSK	GFSK	8DPSK	
0	2402	1.00	1.00	0.94	1.29	0.63	0.86	Pass
39	2441	1.00	1.00	0.94	1.29	0.63	0.86	Pass
78	2480	1.00	1.00	0.94	1.30	0.63	0.87	Pass

NOTE: The minimum limit is two-third 20dB bandwidth.

Spectrum Plot of Worst Value

GFSK / CH0



8DPSK / CH0



4.7 Maximum Output Power

4.7.1 Limits of Maximum Output Power Measurement

The Maximum Output Power Measurement is 125mW.

4.7.2 Test Setup



4.7.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.7.4 Test Procedure

a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.

b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.

c. The center frequency of the spectrum analyzer is set to the fundamental frequency and using 3MHz RBW and 10 MHz VBW.

d. Measure the captured power within the band and recording the plot.

e. Repeat above procedures until all frequencies required were complete.

4.7.5 Deviation from Test Standard

No deviation.

4.7.6 EUT Operating Condition

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

4.7.7 Test Results

FOR PEAK POWER

Channel	Frequency (MHZ)	Output Power (mW)		Output Power (dBm)		Power Limit (mW)	Pass / Fail
		GFSK	8DPSK	GFSK	8DPSK		
0	2402	5.176	3.013	7.14	4.79	125	Pass
39	2441	4.55	2.831	6.58	4.52	125	Pass
78	2480	4.977	2.904	6.97	4.63	125	Pass

FOR AVERAGE POWER - reference only

Channel	Frequency (MHZ)	Output Power (mW)		Output Power (dBm)	
		GFSK	8DPSK	GFSK	8DPSK
0	2402	4.624	2.168	6.65	3.36
39	2441	4.009	2.023	6.03	3.06
78	2480	4.355	2.032	6.39	3.08

Spectrum Plot of Worst Value

GFSK / CH0



8DPSK / CH0



4.8 Conducted Out of Band Emission Measurement

4.8.1 Limits of Conducted Out of Band Emission Measurement

Below –20dB of the highest emission level of operating band (in 100kHz RBW).

4.8.2 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.8.3 Test Procedure

The transmitter output was connected to the spectrum analyzer via a low lose cable. Set both RBW and VBW of spectrum analyzer to 100 kHz and 300 kHz with suitable frequency span including 100 MHz bandwidth from band edge. The band edges was measured and recorded.

4.8.4 Deviation from Test Standard

No deviation.

4.8.5 EUT Operating Condition

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

4.8.6 Test Results

The spectrum plots are attached on the following images. D1 line indicates the highest level, D2 line indicates the 20dB offset below D1. It shows compliance with the requirement.

GFSK

Hopping disabled_ Low Channel





Hopping disabled_ High Channel





Hopping enabled_ Low Channel





Hopping enabled_ High Channel





8DPSK

Hopping disabled_ Low Channel





Hopping disabled_ High Channel





Hopping enabled_ Low Channel





Hopping enabled_ High Channel





5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

Appendix – Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab
Tel: 886-2-26052180
Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab
Tel: 886-3-6668565
Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab
Tel: 886-3-3183232
Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com
Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---