



FCC Test Report

Test report no.: EMC_826FCC22-24_2004

FCC Part 22, 24 / RSS 132, 133

Model: D9500LUP

FCC ID: HD59500LUP



TTI-P-G 081/94-A0

Accredited according to ISO/IEC 17025



Bluetooth Qualification
Test Facility
(BQTF)



FCC listed # 101450

IC recognized # 3925

CETECOM Inc.

411 Dixon Landing Road • Milpitas, CA 95035 • U.S.A.

Phone: + 1 (408) 586 6200 • Fax: + 1 (408) 586 6299 • E-mail: info@cetecomusa.com • <http://www.cetecom.com>

CETECOM Inc. is a Delaware Corporation with Corporation number: 2113686

Board of Directors: Dr. Harald Ansorge, Dr. Klaus Matkey, Hans Peter May

Table of Contents

1	General information
1.1	Notes
1.2	Testing laboratory
1.3	Details of applicant
1.4	Application details
1.5	Test item
1.6	Test standards
2	Technical test
2.1	Summary of test results
2.2	Test report
1	General information
1.1	Notes

The test results of this test report relate exclusively to the test item specified in 1.5. The CETECOM Inc. does not assume responsibility for any conclusions and generalisations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item. The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of the CETECOM Inc.

TEST REPORT PREPARED BY:**EMC Engineer: Harpreet Sidhu****1.2 Testing laboratory**

CETECOM Inc.

411 Dixon Landing Road, Milpitas, CA-95035, USA

Phone: +1 408 586 6200

Fax: +1 408 586 6299

E-mail: lothar.schmidt@cetecomusa.comInternet: www.cetecom.com

1.3 Details of applicant

Name : Hand Held Products, Inc.
Street : 700 Vision Drive
City / Zip Code : Skaneateles Falls, NY 13153
Country : U.S.A
Contact : Naveen Velagapudi
Telephone : +1 315 685 2931
Tele-fax : +1 315 685 1210
e-mail : velagapudin@hhp.com

1.4 Application details

Date of receipt test item : 2004-12-15
Date of test : 2004-12-15/16

1.5 Test item

Manufacturer : Applicant
Marketing Name : Dolphin 9500LUP
Model No. : **D9500LUP**
Description : [Dolphin 9500 is a ruggedized handheld computer which can read barcodes and other auto ID codes. It contains three different transmitters \(BT, WLAN and GSM\) to send and receive data.](#)
FCC-ID : D9500LUP

Additional information

Frequency : 824.2MHz – 848.8MHz for GSM 850,
1850.2MHz – 1909.8MHz for PCS 1900
Type of modulation : GMSK
Number of channels : 124 for GSM-850, 299 for PCS-1900
Antenna : External
Power supply : 12VDC Nominal voltage (10-24VDC)
Output power : 25.22dBm (332.66mW) max. ERP measured in GSM-850
31.58dBm (1.44W) max. EIRP measured in PCS-1900
Extreme temp. Tolerance : Lower: -20°C Upper: +60°C

1.6 Test standards

FCC Part 22,24 / RSS132,133 r1

Note: All radiated measurements were made in all three orthogonal planes. The values reported are the maximum values.

The EUT (D9500LUP) carries pre-certified Siemens GSM module model# MC46 with FCC ID: QIPMC46

This test report covers full radiated testing as per FCC 22/24 on EUT with GSM module. All conducted measurements for GSM 1900 are covered under *test report# 2-205420436/02* and for GSM850 are covered under *test report# 2_3350-01-01/03*.

2 Technical test**2.1 Summary of test results**

No deviations from the technical specification(s) were ascertained in the course of the tests
Performed

Final Verdict:
(only “passed” if all single measurements are “passed”)

Passed

Technical responsibility for area of testing:

2004-12-20 EMC & Radio Lothar Schmidt
(Technical Manager)

Date

Section

Name

Signature

Responsible for test report and project leader:

2004-12-20 EMC & Radio Harpreet Sidhu (EMC Engineer)

Date

Section

Name

Signature

2.2 Test report

TEST REPORT

Test report no.: EMC_826FCC22-24_2004

TEST REPORT REFERENCE

PARAMETER TO BE MEASURED	PARAGRAPH	PAGE
POWER OUTPUT	§22.913(a) / § 24.232 (b)	8
EMISSION LIMITS TRANSMITTER	§2.1051 / §24.238	17
COLLOCATION BT & GSM:		43
CONDUCTED EMISSIONS	§15.107/207	45
TEST EQUIPMENT AND ANCILLARIES USED FOR TESTS		46
BLOCK DIAGRAMS		47

POWER OUTPUT**§ 22.913(a) / § 24.232 (b)****Summary:**

During the process of testing, the EUT was controlled via Rhode & Schwarz Universal Radio Communication tester (CMU 200) to ensure max. Power transmission and proper modulation.

This paragraph contains average output power, peak output power, EIRP & ERP measurements for the EUT. In all cases, the peak output power is within the specified limits.

Method of Measurements:

The EUT was set up for the max. Output power with pseudo random data modulation.

The power was measured with R&S Spectrum Analyzer ESIB 40 (peak)

These measurements were done at 3 frequencies,

824.2 MHz, 836.6 MHz and 848.8 MHz (bottom, middle and top of operational frequency range) for GSM-850

1850.2 MHz, 1880.0 MHz and 1909.8 MHz (bottom, middle and top of operational frequency range) for PCS-1900

ERP (GSM-850)**§22.913(a)****Limits:**

Power Control Level	Burst Peak ERP
5	≤38.45dBm (7W)


EIRP

Frequency (MHz)	Power Control Level	Burst Peak (dBm)	
		EIRP	ERP
824.2	5	22.54	20.40
836.6	5	24.65	22.51
848.8	5	27.36	25.22
Measurement uncertainty	±0.5 dB		


ANALYZER SETTINGS: RBW = VBW = 3MHz

EIRP (GSM-850)
CHANNEL 128**§22.913(a)**


Marker: 824.330261 MHz 22.54 dBm



EIRP (GSM-850) §22.913(a)
CHANNEL 190



EIRP (GSM-850) §22.913(a)
CHANNEL 251




EIRP (PCS-1900) §24.232(b)**Limits:**

Power Control Level	Burst Peak EIRP
0	≤33dBm (1W)


EIRP

Frequency (MHz)	Power Control Level	Burst Peak (dBm)
		EIRP
1850.2	0	29.74
1880.0	0	30.81
1909.8	0	31.58
Measurement uncertainty	±0.5 dB	


ANALYZER SETTINGS: RBW = VBW = 3MHz

EIRP (PCS-1900)
CHANNEL 512**§24.232(b)**

EIRP (PCS-1900) §24.232(b)
CHANNEL 661



EIRP (PCS-1900) §24.232(b)
CHANNEL 810



EMISSION LIMITS TRANSMITTER**§2.1051 / §24.238****Measurement Procedure:**

The following steps outline the procedure used to measure the radiated emissions from the EUT. The site is constructed in accordance with ANSI C63.4 – 2003 requirements and is recognised by the FCC. The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment, which is the transmitted carrier that can be as high as 848.8MHz for GSM-850 & 1910 MHz for PCS-1900. The resolution bandwidth is set as outlined in Part 24.238. The spectrum was scanned with the mobile station transmitting at carrier frequencies that pertain to low, mid and high channels of the GSM-850 & PCS-1900 bands.

The final Radiated emission test procedure is as follows:

- a) The test item was placed on a 0.8 meter high non-conductive stand at a 3 meter test distance from the receive antenna.
- b) The antenna output was terminated in a 50-ohm load.
- c) A double-ridged wave guide antenna was placed on an adjustable height antenna mast 3 meters from the test item for emission measurements.
- d) Detected emissions were maximized at each frequency by rotating the test item and adjusting the receive antenna height and polarization. The maximum meter reading was recorded. The radiated emission measurements of all non-harmonic and harmonics of the transmit frequency through the 10th harmonic were measured with peak detector and 1MHz bandwidth. If the harmonic could not be detected above the noise floor, the ambient level was recorded. The equivalent power into a dipole antenna was determined by the substitution method described for ERP measurements.

Measurement Limit:

Sec. 24.238 Emission Limits.

(a) On any frequency outside a licensee's frequency block (e.g. A, D, B, etc.) within the USPCS spectrum, the power of any emission shall be attenuated below the transmitter power (P, in Watts) by at least $43 + 10 \log(P)$ dB. The specification that emissions shall be attenuated below the transmitter power (P) by at least $43 + 10 \log(P)$ dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

Measurement Results:

Radiated emissions measurements were made only at the upper, middle, and lower carrier frequencies of the GSM-850 & PCS-1900 bands. It was decided that measurements at these three carrier frequencies would be sufficient to demonstrate compliance with emissions limits because it was seen that all the significant spurs occur well outside the band and no radiation was seen from a carrier in one block of the GSM-850 & PCS-1900 band into any of the other blocks respectively. The equipment must still, however, meet emissions requirements with the carrier at all frequencies over which it is capable of operating and it is the manufacturer's responsibility to verify this.

RESULTS OF RADIATED TESTS GSM-850:

Harmonics	Tx ch-128 Freq. (MHz)	Level (dBm)	Tx ch-190 Freq. (MHz)	Level (dBm)	Tx ch-251 Freq. (MHz)	Level (dBm)
2	1648.4	-30.94	1673.2	-36.64	1697.6	Nf
3	2472.6	Nf	2509.8	Nf	2546.4	Nf
4	3296.8	-52.61	3346.4	-55.66	3395.2	-58.24
5	4121	-39.04	4183	-51.42	4244	-43.55
6	4945.2	-39.36	5019.6	-40.67	5092.8	-43.45
7	5769.4	Nf	5856.2	-47.97	5941.6	Nf
8	6593.6	-39.37	6692.8	-43.03	6790.4	-45.02
9	7417.8	-42.91	7529.4	-40.78	7639.2	-43.13
10	8242	nf	8366	nf	8488	nf

RADIATED SPURIOUS EMISSIONS (GSM-850)**30MHz - 1GHz**


Spurious emission limit -13dBm

Antenna: vertical**SWEEP TABLE: "FCC 22 Spur 30M-1G"**

Start	Stop	Detector	Meas.	RBW/VBW
Frequency	Frequency		Time	
30MHz	1GHz	Max Peak	Coupled	1 MHz

Note:

- 1.The peak above the limit line is the carrier freq.
- 2.This plot is valid for low, mid & high channels (worst-case plot)




RADIATED SPURIOUS EMISSIONS (GSM-850)**Tx @ 824.2MHz: 1GHz – 1.58GHz**

Spurious emission limit –13dBm

SWEEP TABLE: "FCC 22 Spur 1-1.58G"

Start	Stop	Detector	Meas.	RBW/VBW
Frequency	Frequency		Time	
1GHz	1.58GHz	Max Peak	Coupled	1 MHz




RADIATED SPURIOUS EMISSIONS (GSM-850)**Tx @ 824.2MHz: 1.58GHz – 3GHz**

Spurious emission limit –13dBm

SWEEP TABLE: "FCC 22 Spur 1.58-3G"

Start	Stop	Detector	Meas.	RBW/VBW
Frequency	Frequency		Time	
1.58GHz	3GHz	Max Peak	Coupled	1 MHz




RADIATED SPURIOUS EMISSIONS (GSM-850)

Tx @ 824.2MHz: 3GHz – 9GHz

Spurious emission limit –13dBm

SWEEP TABLE: "FCC 22 Spur 3-9G"

Start	Stop	Detector	Meas.	RBW/VBW
Frequency	Frequency		Time	
3GHz	9GHz	Max Peak	Coupled	1 MHz




RADIATED SPURIOUS EMISSIONS (GSM-850)

Tx @ 836.6MHz: 1GHz – 1.58GHz

Spurious emission limit –13dBm

SWEEP TABLE: "FCC 22 Spur 1-1.58G"

Start	Stop	Detector	Meas.	RBW/VBW
Frequency	Frequency		Time	
1GHz	1.58GHz	Max Peak	Coupled	1 MHz




RADIATED SPURIOUS EMISSIONS (GSM-850)

Tx @ 836.6MHz: 1.58GHz – 3GHz

Spurious emission limit –13dBm

SWEEP TABLE: "FCC 22 Spur 1.58-3G"

Start	Stop	Detector	Meas.	RBW/VBW
Frequency	Frequency	Time		
1.58GHz	3GHz	Max Peak	Coupled	1 MHz




RADIATED SPURIOUS EMISSIONS (GSM-850)

Tx @ 836.6MHz: 3GHz – 9GHz

Spurious emission limit –13dBm

SWEEP TABLE: "FCC 22 Spur 3-9G"

Start	Stop	Detector	Meas.	RBW/VBW
Frequency	Frequency		Time	
3GHz	9GHz	Max Peak	Coupled	1 MHz




RADIATED SPURIOUS EMISSIONS (GSM-850)

Tx @ 848.8MHz: 1GHz – 1.58GHz

Spurious emission limit –13dBm

SWEEP TABLE: "FCC 22 Spur 1-1.58G"

Start	Stop	Detector	Meas.	RBW/VBW
Frequency	Frequency		Time	
1GHz	1.58GHz	Max Peak	Coupled	1 MHz




RADIATED SPURIOUS EMISSIONS (GSM-850)**Tx @ 848.8MHz: 1.58GHz – 3GHz**

Spurious emission limit –13dBm

SWEEP TABLE: "FCC 22 Spur 1.58-3G"

Start	Stop	Detector	Meas.	RBW/VBW
Frequency	Frequency		Time	
1.58GHz	3GHz	Max Peak	Coupled	1 MHz




RADIATED SPURIOUS EMISSIONS (GSM-850)**Tx @ 848.8MHz: 3GHz – 9GHz**

Spurious emission limit –13dBm

SWEEP TABLE: "FCC 22 Spur 3-9G"

Start	Stop	Detector	Meas.	RBW/VBW
Frequency	Frequency		Time	
3GHz	9GHz	Max Peak	Coupled	1 MHz



RESULTS OF RADIATED TESTS PCS-1900:

nf=noise floor


Harmonic	Tx ch-512 Freq.(MHz)	Level (dBm)	Tx ch-661 Freq. (MHz)	Level (dBm)	Tx ch-810 Freq. (MHz)	Level (dBm)
2	3700.4	-34.98	3760	-40.39	3819.6	-38.23
3	5550.6	-37	5640	-38.25	5729.4	-42.20
4	7400.8	-43.39	7520	-38.79	7639.2	-36.34
5	9251	-36.61	9400	-38.83	9549	-31.95
6	11101.2	-34.40	11280	-29.62	11458.8	-29.24
7	12951.4	nf	13160	nf	13368.6	nf
8	14801.6	nf	15040	nf	15278.4	nf
9	16651.8	nf	16920	nf	17188.2	nf
10	18502	nf	18800	nf	19098	nf

RADIATED SPURIOUS EMISSIONS**30MHz - 1GHz**

Spurious emission limit -13dBm

Antenna: vertical**SWEEP TABLE: "FCC 24 Spur 30M-1G"**

Start	Stop	Detector	Meas.	RBW/VBW
Frequency	Frequency		Time	
30MHz	1GHz	Max Peak	Coupled	1 MHz

Note: This plot is valid for low, mid & high channels (worst-case plot)

RADIATED SPURIOUS EMISSIONS

30MHz - 1GHz


Spurious emission limit -13dBm

Antenna: horizontal

SWEEP TABLE: "FCC 24 Spur 30M-1G"

Start	Stop	Detector	Meas.	RBW/VBW
Frequency	Frequency	Time		
30MHz	1GHz	Max Peak	Coupled	1 MHz

Note: This plot is valid for low, mid & high channels (worst-case plot)



RADIATED SPURIOUS EMISSIONS


Tx @ 1850.2MHz: 1GHz – 3GHz

Spurious emission limit -13dBm

SWEEP TABLE: "FCC Spuri 1-3G"

Start	Stop	Detector	Meas.	RBW/VBW
Frequency	Frequency		Time	
1GHz	3GHz	Max Peak	Coupled	1 MHz

Note: The peak above the limit line is the carrier freq. at ch-512.




RADIATED SPURIOUS EMISSIONS

Tx @ 1850.2MHz: 3GHz – 18GHz

Spurious emission limit -13dBm

SWEEP TABLE: "FCC Spuri 3-18G"

Start	Stop	Detector	Meas.	RBW/VBW
Frequency	Frequency		Time	
3GHz	18GHz	Max Peak	Coupled	1 MHz



RADIATED SPURIOUS EMISSIONS


Tx @ 1880.0MHz: 1GHz – 3GHz

Spurious emission limit –13dBm

SWEEP TABLE: "FCC Spuri 1-3G"

Start	Stop	Detector	Meas.	RBW/VBW
Frequency	Frequency		Time	
1GHz	3GHz	Max Peak	Coupled	1 MHz

Note: The peak above the limit line is the carrier freq. at ch-661.




RADIATED SPURIOUS EMISSIONS

Tx @ 1880.0MHz: 3GHz – 18GHz

Spurious emission limit –13dBm

SWEEP TABLE: "FCC Spuri 3-18G"

Start	Stop	Detector	Meas.	RBW/VBW
Frequency	Frequency		Time	
3GHz	18GHz	Max Peak	Coupled	1 MHz




RADIATED SPURIOUS EMISSIONS**Tx @ 1909.8MHz: 1GHz – 3GHz**

Spurious emission limit –13dBm

SWEEP TABLE: "FCC Spuri 1-3G"

Start	Stop	Detector	Meas.	RBW/VBW
Frequency	Frequency		Time	
1GHz	3GHz	Max Peak	Coupled	1 MHz

Note: The peak above the limit line is the carrier freq. at ch-810.




RADIATED SPURIOUS EMISSIONS

Tx @ 1909.8MHz: 3GHz – 18GHz

Spurious emission limit –13dBm

SWEEP TABLE: "FCC Spuri 3-18G"

Start	Stop	Detector	Meas.	RBW/VBW
Frequency	Frequency		Time	
3GHz	18GHz	Max Peak	Coupled	1 MHz



RADIATED SPURIOUS EMISSIONS


18GHz – 19.1GHz

Spurious emission limit –13dBm

SWEEP TABLE: "FCC 24 spuri 18-19.1G"

Start Frequency	Stop Frequency	Detector	Meas. Time	RBW/VBW
18GHz	19.1GHz	Max Peak	Coupled	1 MHz

Note: This plot is valid for low, mid & high channels (worst-case plot)



RADIATED SPURIOUS EMISSIONS (IDLE MODE)


EUT in Idle Mode: 30MHz – 1GHz

Spurious emission limit –13dBm

Note: This plot is valid for both polarities (worst-case plot)

SWEEP TABLE: "FCC 22 Spur 30M-1G"

Start	Stop	Detector	Meas.	RBW/VBW
Frequency	Frequency		Time	
30MHz	1GHz	Max Peak	Coupled	1 MHz




RADIATED SPURIOUS EMISSIONS (IDLE MODE)

EUT in Idle Mode: 1GHz – 3GHz

Spurious emission limit –13dBm

SWEEP TABLE: "FCC Spuri 1-3G"

Start	Stop	Detector	Meas.	RBW/VBW
Frequency	Frequency	Time		
1GHz	3GHz	Max Peak	Coupled	1 MHz




RADIATED SPURIOUS EMISSIONS (IDLE MODE)

EUT in Idle Mode: 3GHz – 18GHz

Spurious emission limit –13dBm

SWEEP TABLE: "FCC 24 spuri 3-18G"

Start	Stop	Detector	Meas.	RBW/VBW
Frequency	Frequency		Time	
3GHz	18GHz	Max Peak	Coupled	1 MHz




RADIATED SPURIOUS EMISSIONS (IDLE MODE)

EUT in Idle Mode: 18GHz – 19.1GHz

Spurious emission limit –13dBm

SWEEP TABLE: "FCC 24 spuri 18-19.1G"

Start	Stop	Detector	Meas.	RBW/VBW
Frequency	Frequency	Time		
18GHz	19.1GHz	Max Peak	Coupled	1 MHz



COLLOCATION BT & GSM:

EMISSION LIMITATIONS - Radiated (Transmitter)

§ 15.247 (c) (1)

1-3GHz

BT Tx @ 2441MHz

GSM Tx @ 1880MHz

NOTE: The peaks above the limit are above mentioned carrier frequencies.


SWEEP TABLE:

"Spuri hi 1-3G"

Short Description:

Bluetooth Spurious 1-3GHz

Start	Stop	Detector	Meas.	RBW	Transducer
Frequency	Frequency	Time	Bandw.	VBW	
1.0 GHz	3.0 GHz	MaxPeak	Coupled	1 MHz	#326 horn (dBi)



EMISSION LIMITATIONS - Radiated (Transmitter)

§ 15.247 (c) (1)

3-18GHz

BT Tx @ 2441MHz

GSM Tx @ 1880MHz

SWEEP TABLE:

"Spuri hi 3-18G"

Short Description:

Bluetooth Spurious 3-18 GHz

Start

Stop

Detector

Meas.

RBW

Transducer

Frequency

Frequency

Time

Bandw.

VBW

3.0 GHz

18.0 GHz

MaxPeak

Coupled

1 MHz

10Hz


#326 horn (dBi)

Marker:

11.296593186 GHz

42.35 dBμV/m

Level [dBμV/m]



CONDUCTED EMISSIONS

§ 15.107/207

Measured with AC/DC power adapter

SWEEP TABLE: "55022 cond"

Short Description: EN 55022 for 150KHz-30MHz
 Start Stop Detector Meas IF Transducer
 Frequency Frequency Time Bandw.
 150.0 kHz 30.0 MHz MaxPeak Coupled 10 kHz None

Technical specification: 15.107 / 15.207 (Revised as of August 20, 2002)

Limit


Frequency of Emission (MHz)	Conducted Limit (dBµV)	
	Quasi-Peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50

* Decreases with logarithm of the frequency

ANALYZER SETTINGS: RBW = 10KHz VBW = 10KHz

MEASUREMENT RESULT: "test_fin AV"

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Line	PE
0.675000	35.70	0.0	46	10.3	N	GND



TEST EQUIPMENT AND ANCILLARIES USED FOR TESTS

No	Instrument/Ancillary	Type	Manufacturer	Serial No.
01	Spectrum Analyzer	ESIB 40	Rohde & Schwarz	100107
02	Spectrum Analyzer	FSEM 30	Rohde & Schwarz	826880/010
03	Signal Generator	SMY02	Rohde & Schwarz	836878/011
04	Power-Meter	NRVD	Rohde & Schwarz	0857.8008.02
05	Biconilog Antenna	3141	EMCO	0005-1186
06	Horn Antenna (1-18GHz)	SAS-200/571	AH Systems	325
07	Horn Antenna (18-26.5GHz)	3160-09	EMCO	1240
08	Power Splitter	11667B	Hewlett Packard	645348
09	Climatic Chamber	VT4004	Voltsch	G1115
10	High Pass Filter	5HC2700	Trilithic Inc.	9926013
11	High Pass Filter	4HC1600	Trilithic Inc.	9922307
12	Pre-Amplifier	JS4-00102600	Miteq	00616
13	Power Sensor	URV5-Z2	Rohde & Schwarz	DE30807
14	Digital Radio Comm. Tester	CMD-55	Rohde & Schwarz	847958/008
15	Universal Radio Comm. Tester	CMU 200	Rohde & Schwarz	832221/06

BLOCK DIAGRAMS
Radiated Testing**ANECHOIC CHAMBER**