



RF Exposure Evaluation Declaration

FCC ID: HDC17600031F1

Applicant: Adtran Inc.

Application Type: Certification

Product: WiFi 5 Mesh AP

Model No.: 831-t5

FCC Classification: Digital Transmission System (DTS)
Unlicensed National Information Infrastructure (NII)

FCC Rule Part(s) FCC Part 2.1091

Test Procedure(s): KDB 447498 D01v06

Reviewed By:

Vincent Yu

Vincent Yu

Approved By:

Robin Wu

Robin Wu



The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standards through the calibration of the equipment and evaluated measurement uncertainty herein.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

Revision History

Report No.	Version	Description	Issue Date	Note
2108RSU047-U3	Rev. 01	Initial Report	11-20-2021	Valid

CONTENTS

Description	Page
1. General Information	4
1.1. Applicant.....	4
1.2. Manufacturer	4
1.3. Testing Facility.....	4
1.4. Product Information	5
1.5. Antenna Details	5
2. RF Exposure Evaluation.....	6
2.1. Test Limits	6
2.2. Test Result.....	7
Appendix - EUT Photograph.....	8

1. General Information

1.1. Applicant

Adtran Inc.

901 Explorer Blvd NW Huntsville, AL 35806, USA

1.2. Manufacturer

Adtran Inc.

901 Explorer Blvd NW Huntsville, AL 35806, USA

1.3. Testing Facility

☐	Test Site – MRT Suzhou Laboratory
	Laboratory Location (Suzhou - Wuzhong) D8 Building, No.2 Tian'edang Rd., Wuzhong Economic Development Zone, Suzhou, China
	Laboratory Location (Suzhou - SIP) 4b Building, Liando U Valley, No.200 Xingpu Rd., Shengpu Town, Suzhou Industrial Park, China
	Laboratory Accreditations
	A2LA: 3628.01 FCC: CN1166 VCCI:
	CNAS: L10551 ISED: CN0001 ☐R-20025 ☐G-20034 ☐C-20020 ☐T-20020 ☐R-20141 ☐G-20134 ☐C-20103 ☐T-20104
☒	Test Site – MRT Shenzhen Laboratory
	Laboratory Location (Shenzhen) 1G, Building A, Junxiangda Building, Zhongshanyuan Road West, Nanshan District, Shenzhen, China
	Laboratory Accreditations
	A2LA: 3628.02 FCC: CN1284
	CNAS: L10551 ISED: CN0105
☐	Test Site – MRT Taiwan Laboratory
	Laboratory Location (Taiwan) No. 38, Fuxing 2nd Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)
	Laboratory Accreditations
	TAF: L3261-190725 FCC: 291082, TW3261
	ISED: TW3261

1.4. Product Information

Product Name	WiFi 5 Mesh AP
Model No.	831-t5
Serial No.	831t5A0719000001
Wi-Fi Specification	802.11a/b/g/n/ac, VHT
Antenna Information	Refer to section 1.5
Power Supply	AC/DC Adapter
Accessories	
Adapter	MODEL: S36B52-120A300-C4-6 INPUT: 100-240V~50/60Hz 1.0A OUTPUT: 12.0V DC, 3A, 36.0W
Remark: The information of EUT was provided by the manufacturer, and the accuracy of the information shall be the responsibility of the manufacturer.	

1.5. Antenna Details

Antenna Type	Frequency Band (MHz)	Tx Paths	Max. Antenna Gain (dBi)	Beamforming Directional Gain (dBi)	CDD Directional Gain (dBi)	
					For Power	For PSD
PCB Antenna	2.4GHz Band	2	3.5	6.51	3.5	6.51
	5GHz Low Band	2	4.9	7.91	4.9	7.91
	5GHz High Band	4	5.5	11.52	5.5	11.52
Remark: - The EUT supports Cyclic Delay Diversity (CDD) mode, and CDD signals are correlated. If all antennas have the same gain, G_{ANT}, Directional gain = $G_{ANT} + \text{Array Gain}$, where Array Gain is as follows. - For power spectral density (PSD) measurements on all devices, Array Gain = $10 \log (N_{ANT} / N_{SS})$ dB; - For power measurements on IEEE 802.11 devices, Array Gain = 0 dB for $N_{ANT} \leq 4$; - The EUT also supports Beam Forming mode, and the Beam Forming support 802.11n/ac and VHT, not include 802.11a/b/g. The conducted output power in the beamforming mode will be reduced below the conducted output power in the CDD mode by the amount in dB that the beamforming gain exceeds the maximum antenna gain.						

2. RF Exposure Evaluation

2.1. Test Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	f/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	f/1500	6
1500-100,000	--	--	1	30

f= Frequency in MHz

Calculation Formula: $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

r = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

2.2. Test Result

Product	WiFi 5 Mesh AP
Test Item	RF Exposure Evaluation

Test Mode	Frequency Band (MHz)	Conducted Power (dBm)	Max. Antenna Gain (dBi)	Max. EIRP (dBm)	Compliance Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
802.11b/g/n	2412 ~ 2462	26.51	3.5	30.01	20	0.1994	1
802.11a/n/ac	5180 ~ 5240 (Low Band)	28.24	4.9	33.14	20	0.4099	1
802.11a/n/ac	5725 ~ 5825 (High Band)	29.82	5.5	35.32	20	0.6772	1

CONCLUSION:

WLAN 2.4GHz Band and WLAN 5GHz can transmit simultaneously.

The Max. Power Density at R (20 cm) = $0.1994\text{mW/cm}^2 + 0.6772\text{mW/cm}^2 = 0.8766\text{mW/cm}^2 < 1\text{mW/cm}^2$.

So the compliance distance is 20cm for device installed without any other radio equipment.

Appendix - EUT Photograph

Refer to “2108RSU047-UE” file.