

## FCC Test Report

**Report No.:** RF160726C12

**FCC ID:** HDCBSAP304X

**Test Model:** BSAP-3045

**Series Model:** BSAP-3040

**Received Date:** Jul. 26, 2016

**Test Date:** Jul. 29 ~ Sep. 09, 2016

**Issued Date:** Nov. 04, 2016

**Applicant:** Adtran

**Address:** 901 Explorer Boulevard Huntsville Alabama United States

**Issued By:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

**Lab Address:** No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan, R.O.C.

**Test Location:** No.19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City 33383, TAIWAN (R.O.C.)



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. This report should not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

## Table of Contents

|                                                            |           |
|------------------------------------------------------------|-----------|
| <b>Release Control Record</b>                              | <b>4</b>  |
| <b>1 Certificate of Conformity</b>                         | <b>5</b>  |
| <b>2 Summary of Test Results</b>                           | <b>6</b>  |
| 2.1 Measurement Uncertainty                                | 6         |
| 2.2 Modification Record                                    | 6         |
| <b>3 General Information</b>                               | <b>7</b>  |
| 3.1 General Description of EUT                             | 7         |
| 3.2 Description of Test Modes                              | 9         |
| 3.2.1 Test Mode Applicability and Tested Channel Detail    | 10        |
| 3.3 Duty Cycle of Test Signal                              | 12        |
| 3.4 Description of Support Units                           | 14        |
| 3.4.1 Configuration of System under Test                   | 15        |
| 3.5 General Description of Applied Standards               | 17        |
| <b>4 Test Types and Results</b>                            | <b>18</b> |
| 4.1 Radiated Emission and Bandedge Measurement             | 18        |
| 4.1.1 Limits of Radiated Emission and Bandedge Measurement | 18        |
| 4.1.2 Test Instruments                                     | 19        |
| 4.1.3 Test Procedures                                      | 20        |
| 4.1.4 Deviation from Test Standard                         | 20        |
| 4.1.5 Test Set Up                                          | 21        |
| 4.1.6 EUT Operating Conditions                             | 22        |
| 4.1.7 Test Results                                         | 23        |
| 4.2 Conducted Emission Measurement                         | 79        |
| 4.2.1 Limits of Conducted Emission Measurement             | 79        |
| 4.2.2 Test Instruments                                     | 79        |
| 4.2.3 Test Procedures                                      | 80        |
| 4.2.4 Deviation from Test Standard                         | 80        |
| 4.2.5 Test Setup                                           | 80        |
| 4.2.6 EUT Operating Conditions                             | 80        |
| 4.2.7 Test Results                                         | 81        |
| 4.3 6dB Bandwidth Measurement                              | 97        |
| 4.3.1 Limits of 6dB Bandwidth Measurement                  | 97        |
| 4.3.2 Test Setup                                           | 97        |
| 4.3.3 Test Instruments                                     | 97        |
| 4.3.4 Test Procedure                                       | 97        |
| 4.3.5 Deviation from Test Standard                         | 97        |
| 4.3.6 EUT Operating Conditions                             | 97        |
| 4.3.7 Test Result                                          | 98        |
| 4.4 Conducted Output Power Measurement                     | 102       |
| 4.4.1 Limits of Conducted Output Power Measurement         | 102       |
| 4.4.2 Test Setup                                           | 102       |
| 4.4.3 Test Instruments                                     | 102       |
| 4.4.4 Test Procedures                                      | 102       |
| 4.4.5 Deviation from Test Standard                         | 102       |
| 4.4.6 EUT Operating Conditions                             | 102       |
| 4.4.7 Test Results                                         | 103       |
| 4.5 Power Spectral Density Measurement                     | 106       |
| 4.5.1 Limits of Power Spectral Density Measurement         | 106       |
| 4.5.2 Test Setup                                           | 106       |
| 4.5.3 Test Instruments                                     | 106       |
| 4.5.4 Test Procedure                                       | 106       |
| 4.5.5 Deviation from Test Standard                         | 107       |
| 4.5.6 EUT Operating Condition                              | 107       |

|                                                                  |            |
|------------------------------------------------------------------|------------|
| 4.5.7 Test Results .....                                         | 108        |
| 4.6 Conducted Out of Band Emission Measurement.....              | 115        |
| 4.6.1 Limits of Conducted Out of Band Emission Measurement ..... | 115        |
| 4.6.2 Test Setup.....                                            | 115        |
| 4.6.3 Test Instruments .....                                     | 115        |
| 4.6.4 Test Procedure .....                                       | 115        |
| 4.6.5 Deviation from Test Standard .....                         | 116        |
| 4.6.6 EUT Operating Condition .....                              | 116        |
| 4.6.7 Test Results .....                                         | 116        |
| <b>5 Pictures of Test Arrangements.....</b>                      | <b>137</b> |
| <b>Appendix – Information on the Testing Laboratories .....</b>  | <b>138</b> |

### Release Control Record

| Issue No.   | Description      | Date Issued   |
|-------------|------------------|---------------|
| RF160726C12 | Original release | Nov. 04, 2016 |

## 1 Certificate of Conformity

**Product:** Wireless 802.11abgn/ac Access Point

**Brand:** Adtran

**Test Model:** BSAP-3045

**Series Model:** BSAP-3040

**Sample Status:** Engineering sample

**Applicant:** Adtran

**Test Date:** Jul. 29 ~ Sep. 09, 2016

**Standards:** 47 CFR FCC Part 15, Subpart C (Section 15.247)  
ANSI C63.10:2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**Prepared by :** Celine Chou , **Date:** Nov. 04, 2016  
Celine Chou / Specialist

**Approved by :** Ken Liu , **Date:** Nov. 04, 2016  
Ken Liu / Senior Manager

## 2 Summary of Test Results

| 47 CFR FCC Part 15, Subpart C (Section 15.247) |                                              |        |                                                                                                  |
|------------------------------------------------|----------------------------------------------|--------|--------------------------------------------------------------------------------------------------|
| FCC Clause                                     | Test Item                                    | Result | Remarks                                                                                          |
| 15.207                                         | AC Power Conducted Emission                  | Pass   | Meet the requirement of limit.<br>Minimum passing margin is -5.56dB at 0.52130MHz                |
| 15.205 /<br>15.209 /<br>15.247(d)              | Radiated Emissions and Band Edge Measurement | Pass   | Meet the requirement of limit.<br>Minimum passing margin is -1.1dB at 2488.00MHz and 4874.00MHz. |
| 15.247(d)                                      | Antenna Port Emission                        | Pass   | Meet the requirement of limit.                                                                   |
| 15.247(a)(2)                                   | 6dB bandwidth                                | Pass   | Meet the requirement of limit.                                                                   |
| 15.247(b)                                      | Conducted power                              | Pass   | Meet the requirement of limit.                                                                   |
| 15.247(e)                                      | Power Spectral Density                       | Pass   | Meet the requirement of limit.                                                                   |
| 15.203                                         | Antenna Requirement                          | Pass   | Antenna connector is IPEX not a standard connector.                                              |

### 2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

| Measurement                        | Frequency        | Expanded Uncertainty (k=2) ( $\pm$ ) |
|------------------------------------|------------------|--------------------------------------|
| Conducted Emissions at mains ports | 150kHz ~ 30MHz   | 2.44 dB                              |
| Radiated Emissions up to 1 GHz     | 30MHz ~ 200MHz   | 3.86 dB                              |
|                                    | 200MHz ~ 1000MHz | 3.87 dB                              |
| Radiated Emissions above 1 GHz     | 1GHz ~ 18GHz     | 2.29 dB                              |
|                                    | 18GHz ~ 40GHz    | 2.29 dB                              |

### 2.2 Modification Record

There were no modifications required for compliance.

### 3 General Information

#### 3.1 General Description of EUT

|                       |                                                                                                                         |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------|
| Product               | Wireless 802.11abgn/ac Access Point                                                                                     |
| Brand                 | Adtran                                                                                                                  |
| Test Model            | BSAP-3045                                                                                                               |
| Series Model          | BSAP-3040                                                                                                               |
| Model Difference      | Refer to note for more details                                                                                          |
| Sample Status         | Engineering sample                                                                                                      |
| Power Supply Rating   | 12Vdc from adapter<br>48Vdc from POE                                                                                    |
| Modulation Type       | CCK, DQPSK, DBPSK for DSSS<br>64QAM, 16QAM, QPSK, BPSK for OFDM                                                         |
| Modulation Technology | DSSS, OFDM                                                                                                              |
| Transfer Rate         | 802.11b: 11.0/ 5.5/ 2.0/ 1.0Mbps<br>802.11g: 54.0/ 48.0/ 36.0/ 24.0/ 18.0/ 12.0/ 9.0/ 6.0Mbps<br>802.11n: up to 600Mbps |
| Operating Frequency   | 2412 ~ 2462MHz                                                                                                          |
| Number of Channel     | 11 for 802.11b, 802.11g, 802.11n (HT20)<br>7 for 802.11n (HT40)                                                         |
| Output Power          | Radio 1:<br>CDD Mode: 315.359mW<br>Beamforming Mode: 75.262mW<br>Radio 3:<br>CDD Mode: 20.091mW                         |
| Antenna Type          | Refer to note                                                                                                           |
| Antenna Connector     | Refer to note                                                                                                           |
| Accessory Device      | NA                                                                                                                      |
| Data Cable Supplied   | NA                                                                                                                      |

Note:

1. The following models are provided to this EUT.

| Brand  | Model     | Difference       |
|--------|-----------|------------------|
| Adtran | BSAP-3040 | Internal antenna |
|        | BSAP-3045 | External antenna |

2. There are four radios for the EUT.

| Radio   | Model         | Function                      |
|---------|---------------|-------------------------------|
| Radio 1 | QCA9994       | WLAN 2.4G                     |
| Radio 2 | QCA9994       | WLAN 5G                       |
| Radio 3 | QCA9889       | WLAN 2.4GHz (TX/RX)+5GHz (RX) |
| Radio 4 | MKW40Z160 MCU | BT LE                         |

3. The EUT incorporates a MIMO function. Physically, the EUT provides 4 completed transmitters and 4 receivers.

| Modulation Mode | TX Function | Beamforming | Remark  |
|-----------------|-------------|-------------|---------|
| 802.11b         | 4TX         | Not Support | Radio 1 |
| 802.11g         | 4TX         | Not Support |         |
| 802.11n (HT20)  | 4TX         | Support     |         |
| 802.11n (HT40)  | 4TX         | Support     |         |
| 802.11b         | 1TX         | Not Support | Radio 3 |
| 802.11g         | 1TX         | Not Support |         |
| 802.11n (HT20)  | 1TX         | Not Support |         |
| 802.11n (HT40)  | 1TX         | Not Support |         |

\* For 2.4GHz band, CDD mode is the worst case for final tests except RF output power test after pretesting CDD mode and beamforming mode.

4. The EUT uses following antennas.

**For Model: BSAP-3040 (Internal antenna)**

| Ant. No.        | 1         | 2    | 3    | 4    | 5         | 6    | 7    | 8    | 9 (Scan)<br>Individual  | 10 (BLE)<br>Individual |
|-----------------|-----------|------|------|------|-----------|------|------|------|-------------------------|------------------------|
| Ant. Type       | PIFA      |      |      |      |           |      |      |      | PIFA                    | Dipole                 |
| Frequency (MHz) | 2400-2500 |      |      |      | 5150-5850 |      |      |      | 2400-2500/<br>5150-5850 | 2400-2500              |
| Gain (dBi)      | 3.81      | 3.98 | 3.47 | 3.75 | 5.65      | 5.50 | 5.84 | 5.84 | 2.9/5.1                 | 3.93                   |
| Connector       | IPEX      |      |      |      |           |      |      |      | IPEX                    | IPEX                   |

**For Model: BSAP-3045 (External antenna)**

|                    |        |      |      |      |      |      |                         |                       |
|--------------------|--------|------|------|------|------|------|-------------------------|-----------------------|
| Ant. No.           | -      |      |      | -    |      |      | 9 (Scan)<br>Individual  | 1 (BLE)<br>Individual |
| Ant. Type          | Dipole |      |      |      |      |      | PIFA                    | PIFA                  |
| Frequency<br>(MHz) | 2400   | 2450 | 2500 | 5150 | 5550 | 5850 | 2400-2500/<br>5150-5850 | 2400-2500             |
| Gain (dBi)         | 4.66   | 4.47 | 4.49 | 3.34 | 4.67 | 4.52 | 2.9/5.1                 | 3.81                  |
| Connector          | IPEX   |      |      |      |      |      | IPEX                    | IPEX                  |

5. The EUT consumes power from the following adapter and POE. (Support units only)

| Adapter      |                                              |
|--------------|----------------------------------------------|
| Brand        | AOEM                                         |
| Model        | ADS036T-W120300                              |
| Input Power  | 100-240Vac, 50-60Hz, 1.0A                    |
| Output Power | 12Vdc, 3.0A                                  |
| Power Line   | 1.5m cable with one core attached on adapter |

| POE          |                      |
|--------------|----------------------|
| Brand        | EnGenius             |
| Model        | EPE-48GR             |
| Output Power | 48Vdc, 0.5A, 24W Max |

|               |                                               |
|---------------|-----------------------------------------------|
| POE's adapter |                                               |
| Brand         | Powertron Electronics Corp.                   |
| Model         | PA1040-480IB080                               |
| Input Power   | 100-240Vac, 50-60Hz, 1.5A                     |
| Output Power  | 48Vdc, 0.8A, 38.4W Max                        |
| Power Line    | 1.55m cable with one core attached on adapter |

6. 2.4GHz, 5GHz and BT LE technology can transmit at same time.
7. Spurious emission of the simultaneous operation (2.4GHz, 5GHz and BT LE) has been evaluated and no non-compliance was found.

### 3.2 Description of Test Modes

11 channels are provided for 802.11b, 802.11g and 802.11n (HT20):

| Channel | Frequency | Channel | Frequency |
|---------|-----------|---------|-----------|
| 1       | 2412MHz   | 7       | 2442MHz   |
| 2       | 2417MHz   | 8       | 2447MHz   |
| 3       | 2422MHz   | 9       | 2452MHz   |
| 4       | 2427MHz   | 10      | 2457MHz   |
| 5       | 2432MHz   | 11      | 2462MHz   |
| 6       | 2437MHz   |         |           |

7 channels are provided for 802.11n (HT40):

| Channel | Frequency | Channel | Frequency |
|---------|-----------|---------|-----------|
| 3       | 2422MHz   | 7       | 2442MHz   |
| 4       | 2427MHz   | 8       | 2447MHz   |
| 5       | 2432MHz   | 9       | 2452MHz   |
| 6       | 2437MHz   |         |           |

### 3.2.1 Test Mode Applicability and Tested Channel Detail

| EUT CONFIGURE MODE | APPLICABLE TO |           |     |      | DESCRIPTION                         |
|--------------------|---------------|-----------|-----|------|-------------------------------------|
|                    | RE $\geq$ 1G  | RE $<$ 1G | PLC | APCM |                                     |
| A                  | √             | √         | √   | √    | Model: BSAP-3045 Power from adapter |
| B                  | -             | √         | √   | -    | Model: BSAP-3045 Power from POE     |
| C                  | √             | √         | √   | -    | Model: BSAP-3040 Power from adapter |
| D                  | -             | √         | √   | -    | Model: BSAP-3040 Power from POE     |

Where **RE $\geq$ 1G**: Radiated Emission above 1GHz & Bandedge Measurement  
**RE $<$ 1G**: Radiated Emission below 1GHz  
**PLC**: Power Line Conducted Emission  
**APCM**: Antenna Port Conducted Measurement

Note:

- The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on **Z-plane for test mode B (Radio 1), Y-plane for test mode B (Radio 3) and test mode C (Radio 1 and 3)**.
- "-" means no effect.

#### Radiated Emission Test (Above 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

- ☒ Following channel(s) was (were) selected for the final test as listed below.

| EUT CONFIGURE MODE | MODE           | AVAILABLE CHANNEL | TESTED CHANNEL | MODULATION TECHNOLOGY | MODULATION TYPE | DATA RATE (Mbps) | REMARK        |
|--------------------|----------------|-------------------|----------------|-----------------------|-----------------|------------------|---------------|
| A, C               | 802.11b        | 1 to 11           | 1, 6, 11       | DSSS                  | DBPSK           | 1.0              | Radio 1 (4TX) |
|                    |                | 1 to 11           | 1, 6, 11       | DSSS                  | DBPSK           | 1.0              | Radio 3 (1TX) |
| A, C               | 802.11g        | 1 to 11           | 1, 6, 11       | OFDM                  | BPSK            | 6.0              | Radio 1 (4TX) |
|                    |                | 1 to 11           | 1, 6, 11       | OFDM                  | BPSK            | 6.0              | Radio 3 (1TX) |
| A, C               | 802.11n (HT20) | 1 to 11           | 1, 6, 11       | OFDM                  | BPSK            | 6.5              | Radio 1 (4TX) |
|                    |                | 1 to 11           | 1, 6, 11       | OFDM                  | BPSK            | 6.5              | Radio 3 (1TX) |
| A, C               | 802.11n (HT40) | 3 to 9            | 3, 6, 9        | OFDM                  | BPSK            | 13.5             | Radio 1 (4TX) |
|                    |                | 3 to 9            | 3, 6, 9        | OFDM                  | BPSK            | 13.5             | Radio 3 (1TX) |

#### Radiated Emission Test (Below 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

- ☒ Following channel(s) was (were) selected for the final test as listed below.

| EUT CONFIGURE MODE | MODE    | AVAILABLE CHANNEL | TESTED CHANNEL | MODULATION TECHNOLOGY | MODULATION TYPE | DATA RATE (Mbps) | REMARK        |
|--------------------|---------|-------------------|----------------|-----------------------|-----------------|------------------|---------------|
| A, B, C, D         | 802.11b | 1 to 11           | 1              | DSSS                  | DBPSK           | 1.0              | Radio 1 (4TX) |
|                    |         | 1 to 11           |                | DSSS                  | DBPSK           | 1.0              | Radio 3 (1TX) |

### Power Line Conducted Emission Test:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

| EUT CONFIGURE MODE | MODE    | AVAILABLE CHANNEL | TESTED CHANNEL | MODULATION TECHNOLOGY | MODULATION TYPE | DATA RATE (Mbps) | REMARK        |
|--------------------|---------|-------------------|----------------|-----------------------|-----------------|------------------|---------------|
| A, B, C, D         | 802.11b | 1 to 11           | 1              | DSSS                  | DBPSK           | 1.0              | Radio 1 (4TX) |
|                    |         | 1 to 11           |                | DSSS                  | DBPSK           | 1.0              | Radio 3 (1TX) |

### Antenna Port Conducted Measurement:

- ☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

| EUT CONFIGURE MODE | MODE           | AVAILABLE CHANNEL | TESTED CHANNEL | MODULATION TECHNOLOGY | MODULATION TYPE | DATA RATE (Mbps) | REMARK        |
|--------------------|----------------|-------------------|----------------|-----------------------|-----------------|------------------|---------------|
| CDD Mode           |                |                   |                |                       |                 |                  |               |
| A                  | 802.11b        | 1 to 11           | 1, 6, 11       | DSSS                  | DBPSK           | 1.0              | Radio 1 (4TX) |
|                    |                | 1 to 11           | 1, 6, 11       | DSSS                  | DBPSK           | 1.0              | Radio 3 (1TX) |
| A                  | 802.11g        | 1 to 11           | 1, 6, 11       | OFDM                  | BPSK            | 6.0              | Radio 1 (4TX) |
|                    |                | 1 to 11           | 1, 6, 11       | OFDM                  | BPSK            | 6.0              | Radio 3 (1TX) |
| A                  | 802.11n (HT20) | 1 to 11           | 1, 6, 11       | OFDM                  | BPSK            | 6.5              | Radio 1 (4TX) |
|                    |                | 1 to 11           | 1, 6, 11       | OFDM                  | BPSK            | 6.5              | Radio 3 (1TX) |
| A                  | 802.11n (HT40) | 3 to 9            | 3, 6, 9        | OFDM                  | BPSK            | 13.5             | Radio 1 (4TX) |
|                    |                | 3 to 9            | 3, 6, 9        | OFDM                  | BPSK            | 13.5             | Radio 3 (1TX) |
| Beamforming Mode   |                |                   |                |                       |                 |                  |               |
| A                  | 802.11n (HT20) | 1 to 11           | 1, 6, 11       | OFDM                  | BPSK            | 6.5              | Radio 1 (4TX) |
| A                  | 802.11n (HT40) | 3 to 9            | 3, 6, 9        | OFDM                  | BPSK            | 13.5             | Radio 1 (4TX) |

### Test Condition:

| APPLICABLE TO         | ENVIRONMENTAL CONDITIONS           | INPUT POWER           | TESTED BY   |
|-----------------------|------------------------------------|-----------------------|-------------|
| RE <sub>≥</sub> 1G    | 19deg. C, 70%RH<br>18deg. C, 70%RH | 120Vac, 60Hz          | James Yang  |
| RE <sub>&lt;</sub> 1G | 19deg. C, 70%RH<br>18deg. C, 70%RH | 120Vac, 60Hz<br>48Vdc | Jones Chang |
| PLC                   | 20deg. C, 70%RH                    | 120Vac, 60Hz<br>48Vdc | Jones Chang |
| APCM                  | 25deg. C, 60%RH                    | 120Vac, 60Hz          | Leo Tsai    |

### 3.3 Duty Cycle of Test Signal

#### Radio 1

802.11b, 802.11n (HT20): Duty cycle of test signal is > 98%, duty factor is not required.


802.11g, 802.11n (HT40): Duty cycle of test signal is < 98%, duty factor shall be considered.

802.11b: Duty cycle =  $12.437/12.499 = 0.995$

802.11g: Duty cycle =  $2.060/2.150 = 0.958$ , Duty factor =  $10 * \log(1/0.958) = 0.19$

802.11n (HT20): Duty cycle =  $4.997/5.090 = 0.982$

802.11n (HT40): Duty cycle =  $2.422/2.497 = 0.970$ , Duty factor =  $10 * \log(1/0.970) = 0.13$



### Radio 3

802.11b: Duty cycle of test signal is > 98%.


802.11g, 802.11n (HT20), 802.11n (HT40): Duty cycle of test signal is < 98%.

802.11g: Duty cycle =  $13.150/13.287 = 0.990$

802.11g: Duty cycle =  $2.197/2.282 = 0.963$ , Duty factor =  $10 * \log(1/0.963) = 0.16$

802.11n (HT20): Duty cycle =  $2.043/2.148 = 0.951$ , Duty factor =  $10 * \log(1/0.951) = 0.22$

802.11n (HT40): Duty cycle =  $0.994/1.099 = 0.904$ , Duty factor =  $10 * \log(1/0.904) = 0.44$



### 3.4 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| ID | Product     | Brand                          | Model No.       | Serial No. | FCC ID           | Remarks                                                |
|----|-------------|--------------------------------|-----------------|------------|------------------|--------------------------------------------------------|
| A. | Notebook    | DELL                           | E5410           | 1HC2XM1    | FCC DoC Approved | -                                                      |
| B. | Adapter     | AOEM                           | ADS036T-W120300 | N/A        | N/A              | Provided by manufacturer<br>For test mode A and C only |
| C. | POE         | EnGenius                       | EPE-48GR        | N/A        | N/A              | Provided by manufacturer<br>For test mode B and D only |
| D. | POE adapter | Powertron<br>Electronics Corp. | PA1040-480IB080 | N/A        | N/A              | Provided by manufacturer<br>For test mode B and D only |
| E. | Load        | N/A                            | N/A             | N/A        | N/A              | -                                                      |
| F. | USB Flash   | HP                             | v250W           | 01         | FCC DoC Approved | -                                                      |


Note:

1. All power cords of the above support units are non-shielded (1.8m).
2. Item A acted as communication partner to transfer data.


| ID | Descriptions         | Qty. | Length (m) | Shielding<br>(Yes/No) | Cores (Qty.) | Remarks                    |
|----|----------------------|------|------------|-----------------------|--------------|----------------------------|
| 1. | RJ45 Cable           | 1    | 3          | N                     | 0            | Cat5e                      |
| 2. | Power Cable          | 1    | 1.5        | -                     | 1            | For test mode A and C only |
| 3. | Power Cable          | 1    | 1.55       | -                     | 1            | For test mode B and D only |
| 4. | RJ45 Cable           | 1    | 1.8        | N                     | 0            | Cat5e                      |
| 5. | RJ45 to RS-232 Cable | 1    | 1.8        | N                     | 0            | -                          |
| 6. | RJ45 Cable           | 1    | 1.8        | N                     | 0            | Cat5e                      |

### 3.4.1 Configuration of System under Test


#### Test Mode A




#### Test Mode B



### Test Mode C



### Test Mode D



### 3.5 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC Part 15, Subpart C (15.247)**

**KDB 558074 D01 DTS Meas Guidance v03r05**

**KDB 662911 D01 Multiple Transmitter Output v02r01**

**ANSI C63.10-2013**

All test items have been performed and recorded as per the above standards.

Note: The EUT has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC).  
The test report has been issued separately.

## 4 Test Types and Results

### 4.1 Radiated Emission and Bandedge Measurement

#### 4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 30dB below the highest level of the desired power:

| Frequencies (MHz) | Field Strength (microvolts/meter) | Measurement Distance (meters) |
|-------------------|-----------------------------------|-------------------------------|
| 0.009 ~ 0.490     | 2400/F(kHz)                       | 300                           |
| 0.490 ~ 1.705     | 24000/F(kHz)                      | 30                            |
| 1.705 ~ 30.0      | 30                                | 30                            |
| 30 ~ 88           | 100                               | 3                             |
| 88 ~ 216          | 150                               | 3                             |
| 216 ~ 960         | 200                               | 3                             |
| Above 960         | 500                               | 3                             |

**Note:**

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 30dB under any condition of modulation.

#### 4.1.2 Test Instruments

| Description & Manufacturer           | Model No.                    | Serial No.                     | Cal. Date     | Cal. Due      |
|--------------------------------------|------------------------------|--------------------------------|---------------|---------------|
| Test Receiver<br>ROHDE & SCHWARZ     | ESIB7                        | 100187                         | Apr. 18, 2016 | Apr. 17, 2017 |
| Spectrum Analyzer<br>ROHDE & SCHWARZ | FSP40                        | 100041                         | Sep. 02, 2015 | Sep. 01, 2016 |
|                                      |                              |                                | Sep. 02, 2016 | Sep. 01, 2017 |
| BILOG Antenna<br>SCHWARZBECK         | VULB9168                     | 9168-171                       | Jan. 07, 2016 | Jan. 06, 2017 |
| HORN Antenna<br>SCHWARZBECK          | 9120D                        | 209                            | Jan. 20, 2016 | Jan. 19, 2017 |
| HORN Antenna<br>SCHWARZBECK          | BBHA 9170                    | BBHA9170241                    | Jan. 18, 2016 | Jan. 17, 2017 |
| Loop Antenna                         | EM-6879                      | 269                            | Aug. 11, 2015 | Aug. 10, 2016 |
|                                      |                              |                                | Aug. 11, 2016 | Aug. 10, 2017 |
| Preamplifier<br>Agilent              | 8447D                        | 2944A10738                     | Aug. 22, 2015 | Aug. 21, 2016 |
|                                      |                              |                                | Aug. 22, 2016 | Aug. 21, 2017 |
| Preamplifier<br>Agilent              | 8449B                        | 3008A01964                     | Aug. 22, 2015 | Aug. 21, 2016 |
|                                      |                              |                                | Aug. 22, 2016 | Aug. 21, 2017 |
| RF signal cable<br>HUBER+SUHNER      | SUCOFLEX 104                 | Cable-CH3-03 (214378)          | Aug. 22, 2015 | Aug. 21, 2016 |
|                                      |                              |                                | Aug. 22, 2016 | Aug. 21, 2017 |
| RF signal cable<br>HUBER+SUHNER      | SUCOFLEX 106                 | Cable-CH3-03<br>(309224+12738) | Aug. 22, 2015 | Aug. 21, 2016 |
|                                      |                              |                                | Aug. 22, 2016 | Aug. 21, 2017 |
| Software<br>BV ADT                   | ADT_Radiated_<br>V7.6.15.9.4 | NA                             | NA            | NA            |
| Antenna Tower<br>inn-co GmbH         | MA 4000                      | 013303                         | NA            | NA            |
| Antenna Tower Controller<br>BV ADT   | AT100                        | AT93021702                     | NA            | NA            |
| Turn Table<br>BV ADT                 | TT100                        | TT93021702                     | NA            | NA            |
| Turn Table Controller<br>BV ADT      | SC100                        | SC93021702                     | NA            | NA            |
| High Speed Peak Power<br>Meter       | ML2495A                      | 0824011                        | Jul. 09, 2016 | Jul. 08, 2017 |
| Power Sensor                         | MA2411B                      | 0738171                        | Aug. 11, 2015 | Aug. 10, 2016 |
|                                      |                              |                                | Aug. 11, 2016 | Aug. 10, 2017 |

- Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in HwaYa Chamber 3.
3. The horn antenna and preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
4. The FCC Site Registration No. is 988962.
5. The IC Site Registration No. is IC 7450F-3.

### 4.1.3 Test Procedures

#### For Radiated emission below 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Both X and Y axes of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

#### Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

#### For Radiated emission above 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

#### Note:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is  $\geq 1/T$  (Duty cycle < 98%) or 10Hz (Duty cycle  $\geq 98\%$ ) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

### 4.1.4 Deviation from Test Standard


No deviation.

#### 4.1.5 Test Set Up


##### For Radiated emission below 30MHz



##### For Radiated emission 30MHz to 1GHz



### For Radiated emission above 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.1.6 EUT Operating Conditions

- Placed the EUT on the testing table.
- Prepared a notebook to act as a communication partner and placed it outside of testing area.
- The communication partner connected with EUT via a RJ45 cable and ran a test program (provided by manufacturer) to enable EUT under transmission condition continuously at specific channel frequency.
- The communication partner sent data to EUT by command "PING".

#### 4.1.7 Test Results

Above 1GHz worst-Case data:

Test Mode A

Radio 1: CDD Mode

802.11b

|                 |              |                   |              |
|-----------------|--------------|-------------------|--------------|
| CHANNEL         | TX Channel 1 | DETECTOR FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                   | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |             |                         |                |             |                    |                      |                  |                          |
|-----------------------------------------------------|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO.                                                 | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1                                                   | 2370.00     | 62.2 PK                 | 74.0           | -11.8       | 1.66 H             | 342                  | 29.5             | 32.7                     |
| 2                                                   | 2370.00     | 52.3 AV                 | 54.0           | -1.7        | 1.66 H             | 342                  | 19.6             | 32.7                     |
| 3                                                   | *2412.00    | 120.8 PK                |                |             | 1.78 H             | 347                  | 87.9             | 32.9                     |
| 4                                                   | *2412.00    | 117.3 AV                |                |             | 1.78 H             | 347                  | 84.4             | 32.9                     |
| 5                                                   | 4824.00     | 50.3 PK                 | 74.0           | -23.7       | 2.10 H             | 258                  | 44.4             | 5.9                      |
| 6                                                   | 4824.00     | 40.6 AV                 | 54.0           | -13.4       | 2.10 H             | 258                  | 34.7             | 5.9                      |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |             |                         |                |             |                    |                      |                  |                          |
| NO.                                                 | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1                                                   | 2390.00     | 57.3 PK                 | 74.0           | -16.7       | 2.52 V             | 240                  | 24.5             | 32.8                     |
| 2                                                   | 2390.00     | 46.0 AV                 | 54.0           | -8.0        | 2.52 V             | 240                  | 13.2             | 32.8                     |
| 3                                                   | *2412.00    | 109.8 PK                |                |             | 2.82 V             | 300                  | 76.9             | 32.9                     |
| 4                                                   | *2412.00    | 107.6 AV                |                |             | 2.82 V             | 300                  | 74.7             | 32.9                     |
| 5                                                   | 4824.00     | 51.2 PK                 | 74.0           | -22.8       | 1.34 V             | 327                  | 45.3             | 5.9                      |
| 6                                                   | 4824.00     | 45.5 AV                 | 54.0           | -8.5        | 1.34 V             | 327                  | 39.6             | 5.9                      |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

|                 |              |                      |              |
|-----------------|--------------|----------------------|--------------|
| CHANNEL         | TX Channel 6 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2437.00       | 120.9 PK                      |                   |                | 1.86 H                   | 347                        | 88.0                   | 32.9                           |
| 2                                                   | *2437.00       | 117.5 AV                      |                   |                | 1.86 H                   | 347                        | 84.6                   | 32.9                           |
| 3                                                   | 2483.50        | 62.1 PK                       | 74.0              | -11.9          | 1.50 H                   | 346                        | 29.1                   | 33.0                           |
| 4                                                   | 2483.50        | 51.5 AV                       | 54.0              | -2.5           | 1.50 H                   | 346                        | 18.5                   | 33.0                           |
| 5                                                   | 4874.00        | 53.4 PK                       | 74.0              | -20.6          | 2.03 H                   | 19                         | 47.4                   | 6.0                            |
| 6                                                   | 4874.00        | 50.5 AV                       | 54.0              | -3.5           | 2.03 H                   | 19                         | 44.5                   | 6.0                            |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2437.00       | 108.4 PK                      |                   |                | 2.68 V                   | 303                        | 75.5                   | 32.9                           |
| 2                                                   | *2437.00       | 105.0 AV                      |                   |                | 2.68 V                   | 303                        | 72.1                   | 32.9                           |
| 3                                                   | 2483.50        | 58.1 PK                       | 74.0              | -15.9          | 2.45 V                   | 346                        | 25.1                   | 33.0                           |
| 4                                                   | 2483.50        | 47.0 AV                       | 54.0              | -7.0           | 2.45 V                   | 346                        | 14.0                   | 33.0                           |
| 5                                                   | 4874.00        | 56.6 PK                       | 74.0              | -17.4          | 1.81 V                   | 322                        | 50.6                   | 6.0                            |
| 6                                                   | 4874.00        | 52.5 AV                       | 54.0              | -1.5           | 1.81 V                   | 322                        | 46.5                   | 6.0                            |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* " : Fundamental frequency.

|                 |               |          |              |
|-----------------|---------------|----------|--------------|
| CHANNEL         | TX Channel 11 | DETECTOR | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz  | FUNCTION | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2462.00       | 117.0 PK                      |                   |                | 1.57 H                   | 327                        | 84.1                   | 32.9                           |
| 2                                                   | *2462.00       | 113.2 AV                      |                   |                | 1.57 H                   | 327                        | 80.3                   | 32.9                           |
| 3                                                   | 2483.50        | 60.6 PK                       | 74.0              | -13.4          | 1.72 H                   | 19                         | 27.6                   | 33.0                           |
| 4                                                   | 2483.50        | 51.5 AV                       | 54.0              | -2.5           | 1.72 H                   | 19                         | 18.5                   | 33.0                           |
| 5                                                   | 4924.00        | 55.0 PK                       | 74.0              | -19.0          | 1.50 H                   | 37                         | 49.0                   | 6.0                            |
| 6                                                   | 4924.00        | 52.0 AV                       | 54.0              | -2.0           | 1.50 H                   | 37                         | 46.0                   | 6.0                            |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2462.00       | 106.9 PK                      |                   |                | 2.84 V                   | 304                        | 74.0                   | 32.9                           |
| 2                                                   | *2462.00       | 103.2 AV                      |                   |                | 2.84 V                   | 304                        | 70.3                   | 32.9                           |
| 3                                                   | 2483.50        | 57.5 PK                       | 74.0              | -16.5          | 2.50 V                   | 311                        | 24.5                   | 33.0                           |
| 4                                                   | 2483.50        | 46.1 AV                       | 54.0              | -7.9           | 2.50 V                   | 311                        | 13.1                   | 33.0                           |
| 5                                                   | 4924.00        | 57.3 PK                       | 74.0              | -16.7          | 1.42 V                   | 324                        | 51.3                   | 6.0                            |
| 6                                                   | 4924.00        | 52.6 AV                       | 54.0              | -1.4           | 1.42 V                   | 324                        | 46.6                   | 6.0                            |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

802.11g

|                 |              |                      |              |
|-----------------|--------------|----------------------|--------------|
| CHANNEL         | TX Channel 1 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 66.1 PK                       | 74.0              | -7.9           | 1.63 H                   | 316                        | 33.3                   | 32.8                           |
| 2                                                   | 2390.00        | 52.7 AV                       | 54.0              | -1.3           | 1.63 H                   | 316                        | 19.9                   | 32.8                           |
| 3                                                   | *2412.00       | 124.8 PK                      |                   |                | 1.61 H                   | 353                        | 91.9                   | 32.9                           |
| 4                                                   | *2412.00       | 114.3 AV                      |                   |                | 1.61 H                   | 353                        | 81.4                   | 32.9                           |
| 5                                                   | 4824.00        | 48.4 PK                       | 74.0              | -25.6          | 1.94 H                   | 201                        | 42.5                   | 5.9                            |
| 6                                                   | 4824.00        | 38.5 AV                       | 54.0              | -15.5          | 1.94 H                   | 201                        | 32.6                   | 5.9                            |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 61.0 PK                       | 74.0              | -13.0          | 3.23 V                   | 7                          | 28.2                   | 32.8                           |
| 2                                                   | 2390.00        | 47.3 AV                       | 54.0              | -6.7           | 3.23 V                   | 7                          | 14.5                   | 32.8                           |
| 3                                                   | *2412.00       | 107.4 PK                      |                   |                | 3.45 V                   | 5                          | 74.5                   | 32.9                           |
| 4                                                   | *2412.00       | 97.4 AV                       |                   |                | 3.45 V                   | 5                          | 64.5                   | 32.9                           |
| 5                                                   | 4824.00        | 47.0 PK                       | 74.0              | -27.0          | 2.63 V                   | 181                        | 41.1                   | 5.9                            |
| 6                                                   | 4824.00        | 34.5 AV                       | 54.0              | -19.5          | 2.63 V                   | 181                        | 28.6                   | 5.9                            |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

|                 |              |                      |              |
|-----------------|--------------|----------------------|--------------|
| CHANNEL         | TX Channel 6 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 71.5 PK                       | 74.0              | -2.5           | 1.40 H                   | 346                        | 38.7                   | 32.8                           |
| 2                                                   | 2390.00        | 51.8 AV                       | 54.0              | -2.2           | 1.40 H                   | 346                        | 19.0                   | 32.8                           |
| 3                                                   | *2437.00       | 123.0 PK                      |                   |                | 1.88 H                   | 347                        | 90.1                   | 32.9                           |
| 4                                                   | *2437.00       | 113.3 AV                      |                   |                | 1.88 H                   | 347                        | 80.4                   | 32.9                           |
| 5                                                   | 2483.50        | 69.7 PK                       | 74.0              | -4.3           | 1.33 H                   | 358                        | 36.7                   | 33.0                           |
| 6                                                   | 2483.50        | 52.8 AV                       | 54.0              | -1.2           | 1.33 H                   | 358                        | 19.8                   | 33.0                           |
| 7                                                   | 4874.00        | 50.5 PK                       | 74.0              | -23.5          | 2.00 H                   | 289                        | 44.5                   | 6.0                            |
| 8                                                   | 4874.00        | 39.6 AV                       | 54.0              | -14.4          | 2.00 H                   | 289                        | 33.6                   | 6.0                            |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 56.3 PK                       | 74.0              | -17.7          | 1.98 V                   | 184                        | 23.5                   | 32.8                           |
| 2                                                   | 2390.00        | 44.7 AV                       | 54.0              | -9.3           | 1.98 V                   | 184                        | 11.9                   | 32.8                           |
| 3                                                   | *2437.00       | 111.4 PK                      |                   |                | 3.45 V                   | 7                          | 78.5                   | 32.9                           |
| 4                                                   | *2437.00       | 101.2 AV                      |                   |                | 3.45 V                   | 7                          | 68.3                   | 32.9                           |
| 5                                                   | 2483.50        | 56.5 PK                       | 74.0              | -17.5          | 2.37 V                   | 309                        | 23.5                   | 33.0                           |
| 6                                                   | 2483.50        | 45.6 AV                       | 54.0              | -8.4           | 2.37 V                   | 309                        | 12.6                   | 33.0                           |
| 7                                                   | 4874.00        | 59.3 PK                       | 74.0              | -14.7          | 1.49 V                   | 323                        | 53.3                   | 6.0                            |
| 8                                                   | 4874.00        | 44.7 AV                       | 54.0              | -9.3           | 1.49 V                   | 323                        | 38.7                   | 6.0                            |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

|                 |               |                   |              |
|-----------------|---------------|-------------------|--------------|
| CHANNEL         | TX Channel 11 | DETECTOR FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz  |                   | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |             |                         |                |             |                    |                      |                  |                          |
|-----------------------------------------------------|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO.                                                 | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1                                                   | *2462.00    | 119.0 PK                |                |             | 1.73 H             | 345                  | 86.1             | 32.9                     |
| 2                                                   | *2462.00    | 108.6 AV                |                |             | 1.73 H             | 345                  | 75.7             | 32.9                     |
| 3                                                   | 2483.50     | 66.0 PK                 | 74.0           | -8.0        | 1.53 H             | 5                    | 33.0             | 33.0                     |
| 4                                                   | 2483.50     | 52.3 AV                 | 54.0           | -1.7        | 1.53 H             | 5                    | 19.3             | 33.0                     |
| 5                                                   | 4924.00     | 47.4 PK                 | 74.0           | -26.6       | 2.33 H             | 322                  | 41.4             | 6.0                      |
| 6                                                   | 4924.00     | 36.6 AV                 | 54.0           | -17.4       | 2.33 H             | 322                  | 30.6             | 6.0                      |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |             |                         |                |             |                    |                      |                  |                          |
| NO.                                                 | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1                                                   | *2462.00    | 107.1 PK                |                |             | 3.37 V             | 10                   | 74.2             | 32.9                     |
| 2                                                   | *2462.00    | 96.4 AV                 |                |             | 3.37 V             | 10                   | 63.5             | 32.9                     |
| 3                                                   | 2483.50     | 57.8 PK                 | 74.0           | -16.2       | 2.82 V             | 259                  | 24.8             | 33.0                     |
| 4                                                   | 2483.50     | 46.1 AV                 | 54.0           | -7.9        | 2.82 V             | 259                  | 13.1             | 33.0                     |
| 5                                                   | 4924.00     | 48.0 PK                 | 74.0           | -26.0       | 2.91 V             | 96                   | 42.0             | 6.0                      |
| 6                                                   | 4924.00     | 34.7 AV                 | 54.0           | -19.3       | 2.91 V             | 96                   | 28.7             | 6.0                      |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

### 802.11n (HT20)

|                 |              |                      |              |
|-----------------|--------------|----------------------|--------------|
| CHANNEL         | TX Channel 1 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 68.8 PK                       | 74.0              | -5.2           | 1.53 H                   | 189                        | 36.0                   | 32.8                           |
| 2                                                   | 2390.00        | 52.8 AV                       | 54.0              | -1.2           | 1.53 H                   | 189                        | 20.0                   | 32.8                           |
| 3                                                   | *2412.00       | 118.3 PK                      |                   |                | 2.35 H                   | 340                        | 85.4                   | 32.9                           |
| 4                                                   | *2412.00       | 107.9 AV                      |                   |                | 2.35 H                   | 340                        | 75.0                   | 32.9                           |
| 5                                                   | 4824.00        | 47.0 PK                       | 74.0              | -27.0          | 2.34 H                   | 91                         | 41.1                   | 5.9                            |
| 6                                                   | 4824.00        | 34.8 AV                       | 54.0              | -19.2          | 2.34 H                   | 91                         | 28.9                   | 5.9                            |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 56.5 PK                       | 74.0              | -17.5          | 2.85 V                   | 307                        | 23.7                   | 32.8                           |
| 2                                                   | 2390.00        | 45.4 AV                       | 54.0              | -8.6           | 2.85 V                   | 307                        | 12.6                   | 32.8                           |
| 3                                                   | *2412.00       | 108.3 PK                      |                   |                | 3.46 V                   | 5                          | 75.4                   | 32.9                           |
| 4                                                   | *2412.00       | 97.8 AV                       |                   |                | 3.46 V                   | 5                          | 64.9                   | 32.9                           |
| 5                                                   | 4824.00        | 46.5 PK                       | 74.0              | -27.5          | 2.69 V                   | 210                        | 40.6                   | 5.9                            |
| 6                                                   | 4824.00        | 34.2 AV                       | 54.0              | -19.8          | 2.69 V                   | 210                        | 28.3                   | 5.9                            |

#### Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

|                 |              |                      |              |
|-----------------|--------------|----------------------|--------------|
| CHANNEL         | TX Channel 6 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 68.1 PK                       | 74.0              | -5.9           | 2.66 H                   | 351                        | 35.3                   | 32.8                           |
| 2                                                   | 2390.00        | 51.8 AV                       | 54.0              | -2.2           | 2.66 H                   | 351                        | 19.0                   | 32.8                           |
| 3                                                   | *2437.00       | 122.5 PK                      |                   |                | 2.34 H                   | 339                        | 89.6                   | 32.9                           |
| 4                                                   | *2437.00       | 112.3 AV                      |                   |                | 2.34 H                   | 339                        | 79.4                   | 32.9                           |
| 5                                                   | 2483.50        | 68.6 PK                       | 74.0              | -5.4           | 2.54 H                   | 325                        | 35.6                   | 33.0                           |
| 6                                                   | 2483.50        | 52.5 AV                       | 54.0              | -1.5           | 2.54 H                   | 325                        | 19.5                   | 33.0                           |
| 7                                                   | 4874.00        | 57.0 PK                       | 74.0              | -17.0          | 2.38 H                   | 296                        | 51.0                   | 6.0                            |
| 8                                                   | 4874.00        | 42.3 AV                       | 54.0              | -11.7          | 2.38 H                   | 296                        | 36.3                   | 6.0                            |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 56.1 PK                       | 74.0              | -17.9          | 2.80 V                   | 342                        | 23.3                   | 32.8                           |
| 2                                                   | 2390.00        | 45.1 AV                       | 54.0              | -8.9           | 2.80 V                   | 342                        | 12.3                   | 32.8                           |
| 3                                                   | *2437.00       | 111.5 PK                      |                   |                | 3.43 V                   | 6                          | 78.6                   | 32.9                           |
| 4                                                   | *2437.00       | 101.1 AV                      |                   |                | 3.43 V                   | 6                          | 68.2                   | 32.9                           |
| 5                                                   | 2483.50        | 56.9 PK                       | 74.0              | -17.1          | 2.93 V                   | 298                        | 23.9                   | 33.0                           |
| 6                                                   | 2483.50        | 45.2 AV                       | 54.0              | -8.8           | 2.93 V                   | 298                        | 12.2                   | 33.0                           |
| 7                                                   | 4874.00        | 53.4 PK                       | 74.0              | -20.6          | 3.49 V                   | 179                        | 47.4                   | 6.0                            |
| 8                                                   | 4874.00        | 38.8 AV                       | 54.0              | -15.2          | 3.49 V                   | 179                        | 32.8                   | 6.0                            |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

|                 |               |          |              |
|-----------------|---------------|----------|--------------|
| CHANNEL         | TX Channel 11 | DETECTOR | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz  | FUNCTION | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2462.00       | 117.5 PK                      |                   |                | 2.23 H                   | 340                        | 84.6                   | 32.9                           |
| 2                                                   | *2462.00       | 107.3 AV                      |                   |                | 2.23 H                   | 340                        | 74.4                   | 32.9                           |
| 3                                                   | 2483.50        | 65.0 PK                       | 74.0              | -9.0           | 1.97 H                   | 4                          | 32.0                   | 33.0                           |
| 4                                                   | 2483.50        | 52.6 AV                       | 54.0              | -1.4           | 1.97 H                   | 4                          | 19.6                   | 33.0                           |
| 5                                                   | 4924.00        | 47.7 PK                       | 74.0              | -26.3          | 2.07 H                   | 270                        | 41.7                   | 6.0                            |
| 6                                                   | 4924.00        | 34.9 AV                       | 54.0              | -19.1          | 2.07 H                   | 270                        | 28.9                   | 6.0                            |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2462.00       | 106.3 PK                      |                   |                | 3.36 V                   | 9                          | 73.4                   | 32.9                           |
| 2                                                   | *2462.00       | 95.7 AV                       |                   |                | 3.36 V                   | 9                          | 62.8                   | 32.9                           |
| 3                                                   | 2483.50        | 56.9 PK                       | 74.0              | -17.1          | 2.81 V                   | 303                        | 23.9                   | 33.0                           |
| 4                                                   | 2483.50        | 45.7 AV                       | 54.0              | -8.3           | 2.81 V                   | 303                        | 12.7                   | 33.0                           |
| 5                                                   | 4924.00        | 47.0 PK                       | 74.0              | -27.0          | 2.41 V                   | 223                        | 41.0                   | 6.0                            |
| 6                                                   | 4924.00        | 34.6 AV                       | 54.0              | -19.4          | 2.41 V                   | 223                        | 28.6                   | 6.0                            |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

### 802.11n (HT40)

|                 |              |                      |              |
|-----------------|--------------|----------------------|--------------|
| CHANNEL         | TX Channel 3 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 65.4 PK                       | 74.0              | -8.6           | 1.38 H                   | 355                        | 32.6                   | 32.8                           |
| 2                                                   | 2390.00        | 52.3 AV                       | 54.0              | -1.7           | 1.38 H                   | 355                        | 19.5                   | 32.8                           |
| 3                                                   | *2422.00       | 113.0 PK                      |                   |                | 1.35 H                   | 355                        | 80.1                   | 32.9                           |
| 4                                                   | *2422.00       | 103.4 AV                      |                   |                | 1.35 H                   | 355                        | 70.5                   | 32.9                           |
| 5                                                   | 4844.00        | 48.7 PK                       | 74.0              | -25.3          | 1.50 H                   | 249                        | 42.9                   | 5.8                            |
| 6                                                   | 4844.00        | 37.4 AV                       | 54.0              | -16.6          | 1.50 H                   | 249                        | 31.6                   | 5.8                            |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 56.7 PK                       | 74.0              | -17.3          | 2.46 V                   | 215                        | 23.9                   | 32.8                           |
| 2                                                   | 2390.00        | 45.0 AV                       | 54.0              | -9.0           | 2.46 V                   | 215                        | 12.2                   | 32.8                           |
| 3                                                   | *2422.00       | 100.4 PK                      |                   |                | 3.14 V                   | 11                         | 67.5                   | 32.9                           |
| 4                                                   | *2422.00       | 90.9 AV                       |                   |                | 3.14 V                   | 11                         | 58.0                   | 32.9                           |
| 5                                                   | 4844.00        | 47.0 PK                       | 74.0              | -27.0          | 2.20 V                   | 165                        | 41.2                   | 5.8                            |
| 6                                                   | 4844.00        | 33.9 AV                       | 54.0              | -20.1          | 2.20 V                   | 165                        | 28.1                   | 5.8                            |

#### Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

|                 |              |          |              |
|-----------------|--------------|----------|--------------|
| CHANNEL         | TX Channel 6 | DETECTOR | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz | FUNCTION | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 62.5 PK                       | 74.0              | -11.5          | 1.31 H                   | 344                        | 29.7                   | 32.8                           |
| 2                                                   | 2390.00        | 49.9 AV                       | 54.0              | -4.1           | 1.31 H                   | 344                        | 17.1                   | 32.8                           |
| 3                                                   | *2437.00       | 115.0 PK                      |                   |                | 1.70 H                   | 345                        | 82.1                   | 32.9                           |
| 4                                                   | *2437.00       | 105.6 AV                      |                   |                | 1.70 H                   | 345                        | 72.7                   | 32.9                           |
| 5                                                   | 2483.50        | 66.7 PK                       | 74.0              | -7.3           | 1.30 H                   | 245                        | 33.7                   | 33.0                           |
| 6                                                   | 2483.50        | 52.7 AV                       | 54.0              | -1.3           | 1.30 H                   | 245                        | 19.7                   | 33.0                           |
| 7                                                   | 4874.00        | 49.2 PK                       | 74.0              | -24.8          | 1.50 H                   | 272                        | 43.2                   | 6.0                            |
| 8                                                   | 4874.00        | 38.2 AV                       | 54.0              | -15.8          | 1.50 H                   | 272                        | 32.2                   | 6.0                            |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 56.3 PK                       | 74.0              | -17.7          | 2.74 V                   | 33                         | 23.5                   | 32.8                           |
| 2                                                   | 2390.00        | 44.9 AV                       | 54.0              | -9.1           | 2.74 V                   | 33                         | 12.1                   | 32.8                           |
| 3                                                   | *2437.00       | 102.3 PK                      |                   |                | 3.18 V                   | 26                         | 69.4                   | 32.9                           |
| 4                                                   | *2437.00       | 92.7 AV                       |                   |                | 3.18 V                   | 26                         | 59.8                   | 32.9                           |
| 5                                                   | 2483.50        | 57.5 PK                       | 74.0              | -16.5          | 3.08 V                   | 322                        | 24.5                   | 33.0                           |
| 6                                                   | 2483.50        | 45.3 AV                       | 54.0              | -8.7           | 3.08 V                   | 322                        | 12.3                   | 33.0                           |
| 7                                                   | 4874.00        | 47.2 PK                       | 74.0              | -26.8          | 2.75 V                   | 322                        | 41.2                   | 6.0                            |
| 8                                                   | 4874.00        | 34.4 AV                       | 54.0              | -19.6          | 2.75 V                   | 322                        | 28.4                   | 6.0                            |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

|                 |              |                      |              |
|-----------------|--------------|----------------------|--------------|
| CHANNEL         | TX Channel 9 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2452.00       | 113.0 PK                      |                   |                | 1.74 H                   | 342                        | 80.0                   | 33.0                           |
| 2                                                   | *2452.00       | 103.8 AV                      |                   |                | 1.74 H                   | 342                        | 70.8                   | 33.0                           |
| 3                                                   | 2488.00        | 72.6 PK                       | 74.0              | -1.4           | 1.88 H                   | 345                        | 39.6                   | 33.0                           |
| 4                                                   | <b>2488.00</b> | <b>52.9 AV</b>                | <b>54.0</b>       | <b>-1.1</b>    | <b>1.88 H</b>            | <b>345</b>                 | <b>19.9</b>            | <b>33.0</b>                    |
| 5                                                   | 4904.00        | 47.0 PK                       | 74.0              | -27.0          | 2.23 H                   | 359                        | 41.1                   | 5.9                            |
| 6                                                   | 4904.00        | 35.8 AV                       | 54.0              | -18.2          | 2.23 H                   | 359                        | 29.9                   | 5.9                            |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2452.00       | 101.8 PK                      |                   |                | 3.50 V                   | 27                         | 68.8                   | 33.0                           |
| 2                                                   | *2452.00       | 91.5 AV                       |                   |                | 3.50 V                   | 27                         | 58.5                   | 33.0                           |
| 3                                                   | 2483.50        | 57.6 PK                       | 74.0              | -16.4          | 2.85 V                   | 301                        | 24.6                   | 33.0                           |
| 4                                                   | 2483.50        | 46.2 AV                       | 54.0              | -7.8           | 2.85 V                   | 301                        | 13.2                   | 33.0                           |
| 5                                                   | 4904.00        | 47.3 PK                       | 74.0              | -26.7          | 2.66 V                   | 198                        | 41.4                   | 5.9                            |
| 6                                                   | 4904.00        | 34.5 AV                       | 54.0              | -19.5          | 2.66 V                   | 198                        | 28.6                   | 5.9                            |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

### Radio 3: CDD Mode

802.11b

|                 |              |          |              |
|-----------------|--------------|----------|--------------|
| CHANNEL         | TX Channel 1 | DETECTOR | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz | FUNCTION | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2356.00        | 56.5 PK                       | 74.0              | -17.5          | 1.72 H                   | 41                         | 23.8                   | 32.7                           |
| 2                                                   | 2356.00        | 45.9 AV                       | 54.0              | -8.1           | 1.72 H                   | 41                         | 13.2                   | 32.7                           |
| 3                                                   | *2412.00       | 97.2 PK                       |                   |                | 1.84 H                   | 39                         | 64.3                   | 32.9                           |
| 4                                                   | *2412.00       | 95.1 AV                       |                   |                | 1.84 H                   | 39                         | 62.2                   | 32.9                           |
| 5                                                   | 4824.00        | 55.0 PK                       | 74.0              | -19.0          | 1.20 H                   | 41                         | 49.1                   | 5.9                            |
| 6                                                   | 4824.00        | 51.5 AV                       | 54.0              | -2.5           | 1.20 H                   | 41                         | 45.6                   | 5.9                            |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2356.00        | 56.6 PK                       | 74.0              | -17.4          | 3.28 V                   | 345                        | 23.9                   | 32.7                           |
| 2                                                   | 2356.00        | 44.7 AV                       | 54.0              | -9.3           | 3.28 V                   | 345                        | 12.0                   | 32.7                           |
| 3                                                   | *2412.00       | 92.7 PK                       |                   |                | 3.31 V                   | 331                        | 59.8                   | 32.9                           |
| 4                                                   | *2412.00       | 90.4 AV                       |                   |                | 3.31 V                   | 331                        | 57.5                   | 32.9                           |
| 5                                                   | 4824.00        | 55.7 PK                       | 74.0              | -18.3          | 1.11 V                   | 307                        | 49.8                   | 5.9                            |
| 6                                                   | 4824.00        | 52.6 AV                       | 54.0              | -1.4           | 1.11 V                   | 307                        | 46.7                   | 5.9                            |

#### Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

|                 |              |                      |              |
|-----------------|--------------|----------------------|--------------|
| CHANNEL         | TX Channel 6 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2437.00       | 98.1 PK                       |                   |                | 1.69 H                   | 41                         | 65.2                   | 32.9                           |
| 2                                                   | *2437.00       | 96.0 AV                       |                   |                | 1.69 H                   | 41                         | 63.1                   | 32.9                           |
| 3                                                   | 4874.00        | 52.8 PK                       | 74.0              | -21.2          | 1.30 H                   | 43                         | 46.8                   | 6.0                            |
| 4                                                   | 4874.00        | 48.2 AV                       | 54.0              | -5.8           | 1.30 H                   | 43                         | 42.2                   | 6.0                            |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2437.00       | 94.9 PK                       |                   |                | 3.60 V                   | 306                        | 62.0                   | 32.9                           |
| 2                                                   | *2437.00       | 92.1 AV                       |                   |                | 3.60 V                   | 306                        | 59.2                   | 32.9                           |
| 3                                                   | 4874.00        | 56.7 PK                       | 74.0              | -17.3          | 1.06 V                   | 306                        | 50.7                   | 6.0                            |
| 4                                                   | 4874.00        | 52.6 AV                       | 54.0              | -1.4           | 1.06 V                   | 306                        | 46.6                   | 6.0                            |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

|                 |               |                      |              |
|-----------------|---------------|----------------------|--------------|
| CHANNEL         | TX Channel 11 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz  |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2462.00       | 99.7 PK                       |                   |                | 1.80 H                   | 36                         | 66.8                   | 32.9                           |
| 2                                                   | *2462.00       | 96.1 AV                       |                   |                | 1.80 H                   | 36                         | 63.2                   | 32.9                           |
| 3                                                   | 2483.50        | 56.6 PK                       | 74.0              | -17.4          | 1.77 H                   | 42                         | 23.6                   | 33.0                           |
| 4                                                   | 2483.50        | 45.1 AV                       | 54.0              | -8.9           | 1.77 H                   | 42                         | 12.1                   | 33.0                           |
| 5                                                   | 4924.00        | 54.1 PK                       | 74.0              | -19.9          | 1.20 H                   | 46                         | 48.1                   | 6.0                            |
| 6                                                   | 4924.00        | 50.2 AV                       | 54.0              | -3.8           | 1.20 H                   | 46                         | 44.2                   | 6.0                            |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2462.00       | 94.4 PK                       |                   |                | 3.49 V                   | 311                        | 61.5                   | 32.9                           |
| 2                                                   | *2462.00       | 92.3 AV                       |                   |                | 3.49 V                   | 311                        | 59.4                   | 32.9                           |
| 3                                                   | 2483.50        | 57.4 PK                       | 74.0              | -16.6          | 3.51 V                   | 308                        | 24.4                   | 33.0                           |
| 4                                                   | 2483.50        | 44.7 AV                       | 54.0              | -9.3           | 3.51 V                   | 308                        | 11.7                   | 33.0                           |
| 5                                                   | 4924.00        | 55.3 PK                       | 74.0              | -18.7          | 1.10 V                   | 307                        | 49.3                   | 6.0                            |
| 6                                                   | 4924.00        | 52.6 AV                       | 54.0              | -1.4           | 1.10 V                   | 307                        | 46.6                   | 6.0                            |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

802.11g

|                 |              |                      |              |
|-----------------|--------------|----------------------|--------------|
| CHANNEL         | TX Channel 1 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 67.2 PK                       | 74.0              | -6.8           | 1.78 H                   | 35                         | 34.4                   | 32.8                           |
| 2                                                   | 2390.00        | 52.7 AV                       | 54.0              | -1.3           | 1.78 H                   | 35                         | 19.9                   | 32.8                           |
| 3                                                   | *2412.00       | 100.5 PK                      |                   |                | 1.66 H                   | 38                         | 67.6                   | 32.9                           |
| 4                                                   | *2412.00       | 90.2 AV                       |                   |                | 1.66 H                   | 38                         | 57.3                   | 32.9                           |
| 5                                                   | 4824.00        | 54.2 PK                       | 74.0              | -19.8          | 1.24 H                   | 43                         | 48.3                   | 5.9                            |
| 6                                                   | 4824.00        | 41.3 AV                       | 54.0              | -12.7          | 1.24 H                   | 43                         | 35.4                   | 5.9                            |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 58.4 PK                       | 74.0              | -15.6          | 3.23 V                   | 174                        | 25.6                   | 32.8                           |
| 2                                                   | 2390.00        | 45.8 AV                       | 54.0              | -8.2           | 3.23 V                   | 174                        | 13.0                   | 32.8                           |
| 3                                                   | *2412.00       | 94.5 PK                       |                   |                | 3.18 V                   | 172                        | 61.6                   | 32.9                           |
| 4                                                   | *2412.00       | 84.5 AV                       |                   |                | 3.18 V                   | 172                        | 51.6                   | 32.9                           |
| 5                                                   | 4824.00        | 55.0 PK                       | 74.0              | -19.0          | 3.42 V                   | 322                        | 49.1                   | 5.9                            |
| 6                                                   | 4824.00        | 42.0 AV                       | 54.0              | -12.0          | 3.42 V                   | 322                        | 36.1                   | 5.9                            |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

|                 |              |                      |              |
|-----------------|--------------|----------------------|--------------|
| CHANNEL         | TX Channel 6 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2437.00       | 103.0 PK                      |                   |                | 1.63 H                   | 35                         | 70.1                   | 32.9                           |
| 2                                                   | *2437.00       | 92.5 AV                       |                   |                | 1.63 H                   | 35                         | 59.6                   | 32.9                           |
| 3                                                   | 4874.00        | 64.5 PK                       | 74.0              | -9.5           | 1.15 H                   | 41                         | 58.5                   | 6.0                            |
| 4                                                   | 4874.00        | 50.7 AV                       | 54.0              | -3.3           | 1.15 H                   | 41                         | 44.7                   | 6.0                            |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2437.00       | 95.1 PK                       |                   |                | 3.01 V                   | 171                        | 62.2                   | 32.9                           |
| 2                                                   | *2437.00       | 85.2 AV                       |                   |                | 3.01 V                   | 171                        | 52.3                   | 32.9                           |
| 3                                                   | 4874.00        | 65.0 PK                       | 74.0              | -9.0           | 1.05 V                   | 308                        | 59.0                   | 6.0                            |
| 4                                                   | 4874.00        | 52.5 AV                       | 54.0              | -1.5           | 1.05 V                   | 308                        | 46.5                   | 6.0                            |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

|                 |               |                      |              |
|-----------------|---------------|----------------------|--------------|
| CHANNEL         | TX Channel 11 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz  |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2462.00       | 102.3 PK                      |                   |                | 1.82 H                   | 35                         | 69.4                   | 32.9                           |
| 2                                                   | *2462.00       | 92.2 AV                       |                   |                | 1.82 H                   | 35                         | 59.3                   | 32.9                           |
| 3                                                   | 2483.50        | 66.8 PK                       | 74.0              | -7.2           | 1.79 H                   | 42                         | 33.8                   | 33.0                           |
| 4                                                   | 2483.50        | 52.5 AV                       | 54.0              | -1.5           | 1.79 H                   | 42                         | 19.5                   | 33.0                           |
| 5                                                   | 4924.00        | 53.1 PK                       | 74.0              | -20.9          | 1.20 H                   | 45                         | 47.1                   | 6.0                            |
| 6                                                   | 4924.00        | 40.3 AV                       | 54.0              | -13.7          | 1.20 H                   | 45                         | 34.3                   | 6.0                            |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2462.00       | 92.5 PK                       |                   |                | 2.92 V                   | 174                        | 59.6                   | 32.9                           |
| 2                                                   | *2462.00       | 82.5 AV                       |                   |                | 2.92 V                   | 174                        | 49.6                   | 32.9                           |
| 3                                                   | 2483.50        | 61.0 PK                       | 74.0              | -13.0          | 2.87 V                   | 174                        | 28.0                   | 33.0                           |
| 4                                                   | 2483.50        | 48.1 AV                       | 54.0              | -5.9           | 2.87 V                   | 174                        | 15.1                   | 33.0                           |
| 5                                                   | 4924.00        | 55.7 PK                       | 74.0              | -18.3          | 1.08 V                   | 310                        | 49.7                   | 6.0                            |
| 6                                                   | 4924.00        | 42.3 AV                       | 54.0              | -11.7          | 1.08 V                   | 310                        | 36.3                   | 6.0                            |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

### 802.11n (HT20)

|                 |              |                      |              |
|-----------------|--------------|----------------------|--------------|
| CHANNEL         | TX Channel 1 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 66.4 PK                       | 74.0              | -7.6           | 1.44 H                   | 44                         | 33.6                   | 32.8                           |
| 2                                                   | 2390.00        | 52.5 AV                       | 54.0              | -1.5           | 1.44 H                   | 44                         | 19.7                   | 32.8                           |
| 3                                                   | *2412.00       | 99.5 PK                       |                   |                | 1.64 H                   | 45                         | 66.6                   | 32.9                           |
| 4                                                   | *2412.00       | 89.5 AV                       |                   |                | 1.64 H                   | 45                         | 56.6                   | 32.9                           |
| 5                                                   | 4824.00        | 51.9 PK                       | 74.0              | -22.1          | 1.27 H                   | 38                         | 46.0                   | 5.9                            |
| 6                                                   | 4824.00        | 37.9 AV                       | 54.0              | -16.1          | 1.27 H                   | 38                         | 32.0                   | 5.9                            |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 57.0 PK                       | 74.0              | -17.0          | 3.00 V                   | 170                        | 24.2                   | 32.8                           |
| 2                                                   | 2390.00        | 45.1 AV                       | 54.0              | -8.9           | 3.00 V                   | 170                        | 12.3                   | 32.8                           |
| 3                                                   | *2412.00       | 92.8 PK                       |                   |                | 3.06 V                   | 174                        | 59.9                   | 32.9                           |
| 4                                                   | *2412.00       | 82.8 AV                       |                   |                | 3.06 V                   | 174                        | 49.9                   | 32.9                           |
| 5                                                   | 4824.00        | 55.5 PK                       | 74.0              | -18.5          | 1.07 V                   | 312                        | 49.6                   | 5.9                            |
| 6                                                   | 4824.00        | 40.9 AV                       | 54.0              | -13.1          | 1.07 V                   | 312                        | 35.0                   | 5.9                            |

#### Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

|                 |              |                      |              |
|-----------------|--------------|----------------------|--------------|
| CHANNEL         | TX Channel 6 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2437.00       | 103.4 PK                      |                   |                | 1.62 H                   | 39                         | 70.5                   | 32.9                           |
| 2                                                   | *2437.00       | 93.1 AV                       |                   |                | 1.62 H                   | 39                         | 60.2                   | 32.9                           |
| 3                                                   | 4874.00        | 67.2 PK                       | 74.0              | -6.8           | 1.30 H                   | 47                         | 61.2                   | 6.0                            |
| 4                                                   | 4874.00        | 51.6 AV                       | 54.0              | -2.4           | 1.30 H                   | 47                         | 45.6                   | 6.0                            |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2437.00       | 95.3 PK                       |                   |                | 1.09 V                   | 313                        | 62.4                   | 32.9                           |
| 2                                                   | *2437.00       | 85.2 AV                       |                   |                | 1.09 V                   | 313                        | 52.3                   | 32.9                           |
| 3                                                   | 4874.00        | 68.0 PK                       | 74.0              | -6.0           | 1.03 V                   | 312                        | 62.0                   | 6.0                            |
| 4                                                   | 4874.00        | 52.5 AV                       | 54.0              | -1.5           | 1.03 V                   | 312                        | 46.5                   | 6.0                            |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

|                 |               |          |              |
|-----------------|---------------|----------|--------------|
| CHANNEL         | TX Channel 11 | DETECTOR | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz  | FUNCTION | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2462.00       | 100.6 PK                      |                   |                | 1.77 H                   | 40                         | 67.7                   | 32.9                           |
| 2                                                   | *2462.00       | 90.5 AV                       |                   |                | 1.77 H                   | 40                         | 57.6                   | 32.9                           |
| 3                                                   | 2483.50        | 67.3 PK                       | 74.0              | -6.7           | 1.96 H                   | 38                         | 34.3                   | 33.0                           |
| 4                                                   | 2483.50        | 52.6 AV                       | 54.0              | -1.4           | 1.96 H                   | 38                         | 19.6                   | 33.0                           |
| 5                                                   | 4924.00        | 52.9 PK                       | 74.0              | -21.1          | 1.19 H                   | 43                         | 46.9                   | 6.0                            |
| 6                                                   | 4924.00        | 38.5 AV                       | 54.0              | -15.5          | 1.19 H                   | 43                         | 32.5                   | 6.0                            |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2462.00       | 92.1 PK                       |                   |                | 1.06 V                   | 171                        | 59.2                   | 32.9                           |
| 2                                                   | *2462.00       | 82.1 AV                       |                   |                | 1.06 V                   | 171                        | 49.2                   | 32.9                           |
| 3                                                   | 2483.50        | 57.6 PK                       | 74.0              | -16.4          | 1.08 V                   | 174                        | 24.6                   | 33.0                           |
| 4                                                   | 2483.50        | 46.3 AV                       | 54.0              | -7.7           | 1.08 V                   | 174                        | 13.3                   | 33.0                           |
| 5                                                   | 4924.00        | 54.0 PK                       | 74.0              | -20.0          | 1.09 V                   | 311                        | 48.0                   | 6.0                            |
| 6                                                   | 4924.00        | 39.7 AV                       | 54.0              | -14.3          | 1.09 V                   | 311                        | 33.7                   | 6.0                            |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

### 802.11n (HT40)

|                 |              |                      |              |
|-----------------|--------------|----------------------|--------------|
| CHANNEL         | TX Channel 3 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 64.3 PK                       | 74.0              | -9.7           | 1.75 H                   | 36                         | 31.5                   | 32.8                           |
| 2                                                   | 2390.00        | 52.6 AV                       | 54.0              | -1.4           | 1.75 H                   | 36                         | 19.8                   | 32.8                           |
| 3                                                   | *2422.00       | 95.2 PK                       |                   |                | 1.64 H                   | 36                         | 62.3                   | 32.9                           |
| 4                                                   | *2422.00       | 85.3 AV                       |                   |                | 1.64 H                   | 36                         | 52.4                   | 32.9                           |
| 5                                                   | 4844.00        | 47.2 PK                       | 74.0              | -26.8          | 1.42 H                   | 46                         | 41.4                   | 5.8                            |
| 6                                                   | 4844.00        | 34.5 AV                       | 54.0              | -19.5          | 1.42 H                   | 46                         | 28.7                   | 5.8                            |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 56.9 PK                       | 74.0              | -17.1          | 2.99 V                   | 166                        | 24.1                   | 32.8                           |
| 2                                                   | 2390.00        | 45.9 AV                       | 54.0              | -8.1           | 2.99 V                   | 166                        | 13.1                   | 32.8                           |
| 3                                                   | *2422.00       | 88.1 PK                       |                   |                | 3.04 V                   | 171                        | 55.2                   | 32.9                           |
| 4                                                   | *2422.00       | 78.5 AV                       |                   |                | 3.04 V                   | 171                        | 45.6                   | 32.9                           |
| 5                                                   | 4844.00        | 48.1 PK                       | 74.0              | -25.9          | 1.54 V                   | 328                        | 42.3                   | 5.8                            |
| 6                                                   | 4844.00        | 35.1 AV                       | 54.0              | -18.9          | 1.54 V                   | 328                        | 29.3                   | 5.8                            |

#### Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

|                 |              |          |              |
|-----------------|--------------|----------|--------------|
| CHANNEL         | TX Channel 6 | DETECTOR | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz | FUNCTION | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2437.00       | 98.1 PK                       |                   |                | 2.06 H                   | 40                         | 65.2                   | 32.9                           |
| 2                                                   | *2437.00       | 88.9 AV                       |                   |                | 2.06 H                   | 40                         | 56.0                   | 32.9                           |
| 3                                                   | 2483.50        | 65.3 PK                       | 74.0              | -8.7           | 2.00 H                   | 37                         | 32.3                   | 33.0                           |
| 4                                                   | 2483.50        | 52.6 AV                       | 54.0              | -1.4           | 2.00 H                   | 37                         | 19.6                   | 33.0                           |
| 5                                                   | 4874.00        | 50.9 PK                       | 74.0              | -23.1          | 1.20 H                   | 48                         | 44.9                   | 6.0                            |
| 6                                                   | 4874.00        | 38.6 AV                       | 54.0              | -15.4          | 1.20 H                   | 48                         | 32.6                   | 6.0                            |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2437.00       | 89.8 PK                       |                   |                | 3.02 V                   | 170                        | 56.9                   | 32.9                           |
| 2                                                   | *2437.00       | 80.1 AV                       |                   |                | 3.02 V                   | 170                        | 47.2                   | 32.9                           |
| 3                                                   | 2483.50        | 58.1 PK                       | 74.0              | -15.9          | 3.00 V                   | 175                        | 25.1                   | 33.0                           |
| 4                                                   | 2483.50        | 45.9 AV                       | 54.0              | -8.1           | 3.00 V                   | 175                        | 12.9                   | 33.0                           |
| 5                                                   | 4874.00        | 53.3 PK                       | 74.0              | -20.7          | 1.04 V                   | 311                        | 47.3                   | 6.0                            |
| 6                                                   | 4874.00        | 41.0 AV                       | 54.0              | -13.0          | 1.04 V                   | 311                        | 35.0                   | 6.0                            |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

|                 |              |          |              |
|-----------------|--------------|----------|--------------|
| CHANNEL         | TX Channel 9 | DETECTOR | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz | FUNCTION | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2452.00       | 94.8 PK                       |                   |                | 1.83 H                   | 35                         | 61.8                   | 33.0                           |
| 2                                                   | *2452.00       | 85.7 AV                       |                   |                | 1.83 H                   | 35                         | 52.7                   | 33.0                           |
| 3                                                   | 2483.50        | 63.8 PK                       | 74.0              | -10.2          | 1.80 H                   | 38                         | 30.8                   | 33.0                           |
| 4                                                   | 2483.50        | 52.8 AV                       | 54.0              | -1.2           | 1.80 H                   | 38                         | 19.8                   | 33.0                           |
| 5                                                   | 4904.00        | 47.3 PK                       | 74.0              | -26.7          | 1.59 H                   | 63                         | 41.4                   | 5.9                            |
| 6                                                   | 4904.00        | 34.4 AV                       | 54.0              | -19.6          | 1.59 H                   | 63                         | 28.5                   | 5.9                            |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2452.00       | 86.5 PK                       |                   |                | 1.05 V                   | 170                        | 53.5                   | 33.0                           |
| 2                                                   | *2452.00       | 76.5 AV                       |                   |                | 1.05 V                   | 170                        | 43.5                   | 33.0                           |
| 3                                                   | 2483.50        | 58.0 PK                       | 74.0              | -16.0          | 1.07 V                   | 168                        | 25.0                   | 33.0                           |
| 4                                                   | 2483.50        | 47.2 AV                       | 54.0              | -6.8           | 1.07 V                   | 168                        | 14.2                   | 33.0                           |
| 5                                                   | 4904.00        | 47.9 PK                       | 74.0              | -26.1          | 1.58 V                   | 325                        | 42.0                   | 5.9                            |
| 6                                                   | 4904.00        | 34.9 AV                       | 54.0              | -19.1          | 1.58 V                   | 325                        | 29.0                   | 5.9                            |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

# Test Mode C

## Radio 1: CDD Mode

### 802.11b

|                 |              |                      |                           |
|-----------------|--------------|----------------------|---------------------------|
| CHANNEL         | TX Channel 1 | DETECTOR<br>FUNCTION | Peak (PK)<br>Average (AV) |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                      |                           |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 58.1 PK                       | 74.0              | -15.9          | 2.34 H                   | 3                          | 25.3                   | 32.8                           |
| 2                                                   | 2390.00        | 48.5 AV                       | 54.0              | -5.5           | 2.34 H                   | 3                          | 15.7                   | 32.8                           |
| 3                                                   | *2412.00       | 115.1 PK                      |                   |                | 1.94 H                   | 53                         | 82.2                   | 32.9                           |
| 4                                                   | *2412.00       | 111.4 AV                      |                   |                | 1.94 H                   | 53                         | 78.5                   | 32.9                           |
| 5                                                   | 4824.00        | 51.7 PK                       | 74.0              | -22.3          | 1.94 H                   | 279                        | 45.8                   | 5.9                            |
| 6                                                   | 4824.00        | 47.0 AV                       | 54.0              | -7.0           | 1.94 H                   | 279                        | 41.1                   | 5.9                            |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 56.3 PK                       | 74.0              | -17.7          | 1.96 V                   | 256                        | 23.5                   | 32.8                           |
| 2                                                   | 2390.00        | 45.4 AV                       | 54.0              | -8.6           | 1.96 V                   | 256                        | 12.6                   | 32.8                           |
| 3                                                   | *2412.00       | 114.1 PK                      |                   |                | 2.55 V                   | 326                        | 81.2                   | 32.9                           |
| 4                                                   | *2412.00       | 110.3 AV                      |                   |                | 2.55 V                   | 326                        | 77.4                   | 32.9                           |
| 5                                                   | 4824.00        | 49.0 PK                       | 74.0              | -25.0          | 2.19 V                   | 302                        | 43.1                   | 5.9                            |
| 6                                                   | 4824.00        | 39.5 AV                       | 54.0              | -14.5          | 2.19 V                   | 302                        | 33.6                   | 5.9                            |

#### Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

|                 |              |                      |              |
|-----------------|--------------|----------------------|--------------|
| CHANNEL         | TX Channel 6 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2437.00       | 116.1 PK                      |                   |                | 2.33 H                   | 285                        | 83.2                   | 32.9                           |
| 2                                                   | *2437.00       | 112.2 AV                      |                   |                | 2.33 H                   | 285                        | 79.3                   | 32.9                           |
| 3                                                   | 4874.00        | 55.6 PK                       | 74.0              | -18.4          | 2.04 H                   | 284                        | 49.6                   | 6.0                            |
| 4                                                   | 4874.00        | 52.4 AV                       | 54.0              | -1.6           | 2.04 H                   | 284                        | 46.4                   | 6.0                            |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2437.00       | 114.9 PK                      |                   |                | 2.48 V                   | 353                        | 82.0                   | 32.9                           |
| 2                                                   | *2437.00       | 111.2 AV                      |                   |                | 2.48 V                   | 353                        | 78.3                   | 32.9                           |
| 3                                                   | 4874.00        | 48.7 PK                       | 74.0              | -25.3          | 1.95 V                   | 356                        | 42.7                   | 6.0                            |
| 4                                                   | 4874.00        | 39.4 AV                       | 54.0              | -14.6          | 1.95 V                   | 356                        | 33.4                   | 6.0                            |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

|                 |               |          |              |
|-----------------|---------------|----------|--------------|
| CHANNEL         | TX Channel 11 | DETECTOR | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz  | FUNCTION | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2462.00       | 115.8 PK                      |                   |                | 2.71 H                   | 27                         | 82.9                   | 32.9                           |
| 2                                                   | *2462.00       | 112.1 AV                      |                   |                | 2.71 H                   | 27                         | 79.2                   | 32.9                           |
| 3                                                   | 2483.50        | 61.0 PK                       | 74.0              | -13.0          | 2.41 H                   | 303                        | 28.0                   | 33.0                           |
| 4                                                   | 2483.50        | 52.8 AV                       | 54.0              | -1.2           | 2.41 H                   | 303                        | 19.8                   | 33.0                           |
| 5                                                   | 4924.00        | 56.1 PK                       | 74.0              | -17.9          | 2.34 H                   | 341                        | 50.1                   | 6.0                            |
| 6                                                   | 4924.00        | 52.7 AV                       | 54.0              | -1.3           | 2.34 H                   | 341                        | 46.7                   | 6.0                            |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2462.00       | 114.8 PK                      |                   |                | 2.67 V                   | 15                         | 81.9                   | 32.9                           |
| 2                                                   | *2462.00       | 110.9 AV                      |                   |                | 2.67 V                   | 15                         | 78.0                   | 32.9                           |
| 3                                                   | 2483.50        | 60.5 PK                       | 74.0              | -13.5          | 2.88 V                   | 10                         | 27.5                   | 33.0                           |
| 4                                                   | 2483.50        | 48.6 AV                       | 54.0              | -5.4           | 2.88 V                   | 10                         | 15.6                   | 33.0                           |
| 5                                                   | 4924.00        | 49.2 PK                       | 74.0              | -24.8          | 2.65 V                   | 18                         | 43.2                   | 6.0                            |
| 6                                                   | 4924.00        | 42.5 AV                       | 54.0              | -11.5          | 2.65 V                   | 18                         | 36.5                   | 6.0                            |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

802.11g

|                 |              |                      |              |
|-----------------|--------------|----------------------|--------------|
| CHANNEL         | TX Channel 1 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 67.0 PK                       | 74.0              | -7.0           | 2.11 H                   | 301                        | 34.2                   | 32.8                           |
| 2                                                   | 2390.00        | 52.7 AV                       | 54.0              | -1.3           | 2.11 H                   | 301                        | 19.9                   | 32.8                           |
| 3                                                   | *2412.00       | 114.0 PK                      |                   |                | 1.78 H                   | 38                         | 81.1                   | 32.9                           |
| 4                                                   | *2412.00       | 103.3 AV                      |                   |                | 1.78 H                   | 38                         | 70.4                   | 32.9                           |
| 5                                                   | 4824.00        | 47.6 PK                       | 74.0              | -26.4          | 1.83 H                   | 281                        | 41.7                   | 5.9                            |
| 6                                                   | 4824.00        | 35.5 AV                       | 54.0              | -18.5          | 1.83 H                   | 281                        | 29.6                   | 5.9                            |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 65.7 PK                       | 74.0              | -8.3           | 2.50 V                   | 316                        | 32.9                   | 32.8                           |
| 2                                                   | 2390.00        | 49.5 AV                       | 54.0              | -4.5           | 2.50 V                   | 316                        | 16.7                   | 32.8                           |
| 3                                                   | *2412.00       | 113.6 PK                      |                   |                | 2.41 V                   | 314                        | 80.7                   | 32.9                           |
| 4                                                   | *2412.00       | 102.5 AV                      |                   |                | 2.41 V                   | 314                        | 69.6                   | 32.9                           |
| 5                                                   | 4824.00        | 47.1 PK                       | 74.0              | -26.9          | 2.12 V                   | 147                        | 41.2                   | 5.9                            |
| 6                                                   | 4824.00        | 34.4 AV                       | 54.0              | -19.6          | 2.12 V                   | 147                        | 28.5                   | 5.9                            |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

|                 |              |                      |              |
|-----------------|--------------|----------------------|--------------|
| CHANNEL         | TX Channel 6 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2437.00       | 119.4 PK                      |                   |                | 1.87 H                   | 36                         | 86.5                   | 32.9                           |
| 2                                                   | *2437.00       | 108.9 AV                      |                   |                | 1.87 H                   | 36                         | 76.0                   | 32.9                           |
| 3                                                   | 4874.00        | 52.4 PK                       | 74.0              | -21.6          | 2.00 H                   | 343                        | 46.4                   | 6.0                            |
| 4                                                   | 4874.00        | 39.2 AV                       | 54.0              | -14.8          | 2.00 H                   | 343                        | 33.2                   | 6.0                            |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2437.00       | 117.7 PK                      |                   |                | 2.99 V                   | 359                        | 84.8                   | 32.9                           |
| 2                                                   | *2437.00       | 107.5 AV                      |                   |                | 2.99 V                   | 359                        | 74.6                   | 32.9                           |
| 3                                                   | 4874.00        | 50.0 PK                       | 74.0              | -24.0          | 3.01 V                   | 32                         | 44.0                   | 6.0                            |
| 4                                                   | 4874.00        | 36.8 AV                       | 54.0              | -17.2          | 3.01 V                   | 32                         | 30.8                   | 6.0                            |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

|                 |               |                      |              |
|-----------------|---------------|----------------------|--------------|
| CHANNEL         | TX Channel 11 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz  |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2462.00       | 115.0 PK                      |                   |                | 1.98 H                   | 39                         | 82.1                   | 32.9                           |
| 2                                                   | *2462.00       | 104.8 AV                      |                   |                | 1.98 H                   | 39                         | 71.9                   | 32.9                           |
| 3                                                   | 2483.50        | 67.2 PK                       | 74.0              | -6.8           | 2.39 H                   | 303                        | 34.2                   | 33.0                           |
| 4                                                   | 2483.50        | 52.6 AV                       | 54.0              | -1.4           | 2.39 H                   | 303                        | 19.6                   | 33.0                           |
| 5                                                   | 4924.00        | 50.5 PK                       | 74.0              | -23.5          | 2.18 H                   | 340                        | 44.5                   | 6.0                            |
| 6                                                   | 4924.00        | 37.5 AV                       | 54.0              | -16.5          | 2.18 H                   | 340                        | 31.5                   | 6.0                            |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2462.00       | 112.5 PK                      |                   |                | 2.43 V                   | 357                        | 79.6                   | 32.9                           |
| 2                                                   | *2462.00       | 101.9 AV                      |                   |                | 2.43 V                   | 357                        | 69.0                   | 32.9                           |
| 3                                                   | 2483.50        | 59.4 PK                       | 74.0              | -14.6          | 2.59 V                   | 4                          | 26.4                   | 33.0                           |
| 4                                                   | 2483.50        | 47.3 AV                       | 54.0              | -6.7           | 2.59 V                   | 4                          | 14.3                   | 33.0                           |
| 5                                                   | 4924.00        | 46.0 PK                       | 74.0              | -28.0          | 2.36 V                   | 227                        | 40.0                   | 6.0                            |
| 6                                                   | 4924.00        | 34.3 AV                       | 54.0              | -19.7          | 2.36 V                   | 227                        | 28.3                   | 6.0                            |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

### 802.11n (HT20)

|                 |              |                      |              |
|-----------------|--------------|----------------------|--------------|
| CHANNEL         | TX Channel 1 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 66.4 PK                       | 74.0              | -7.6           | 2.33 H                   | 302                        | 33.6                   | 32.8                           |
| 2                                                   | 2390.00        | 52.6 AV                       | 54.0              | -1.4           | 2.33 H                   | 302                        | 19.8                   | 32.8                           |
| 3                                                   | *2412.00       | 114.8 PK                      |                   |                | 1.57 H                   | 37                         | 81.9                   | 32.9                           |
| 4                                                   | *2412.00       | 104.2 AV                      |                   |                | 1.57 H                   | 37                         | 71.3                   | 32.9                           |
| 5                                                   | 4824.00        | 47.3 PK                       | 74.0              | -26.7          | 2.11 H                   | 293                        | 41.4                   | 5.9                            |
| 6                                                   | 4824.00        | 34.2 AV                       | 54.0              | -19.8          | 2.11 H                   | 293                        | 28.3                   | 5.9                            |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 65.7 PK                       | 74.0              | -8.3           | 3.50 V                   | 8                          | 32.9                   | 32.8                           |
| 2                                                   | 2390.00        | 50.5 AV                       | 54.0              | -3.5           | 3.50 V                   | 8                          | 17.7                   | 32.8                           |
| 3                                                   | *2412.00       | 115.8 PK                      |                   |                | 3.45 V                   | 351                        | 82.9                   | 32.9                           |
| 4                                                   | *2412.00       | 105.4 AV                      |                   |                | 3.45 V                   | 351                        | 72.5                   | 32.9                           |
| 5                                                   | 4824.00        | 47.6 PK                       | 74.0              | -26.4          | 2.58 V                   | 175                        | 41.7                   | 5.9                            |
| 6                                                   | 4824.00        | 34.8 AV                       | 54.0              | -19.2          | 2.58 V                   | 175                        | 28.9                   | 5.9                            |

#### Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

|                 |              |                      |              |
|-----------------|--------------|----------------------|--------------|
| CHANNEL         | TX Channel 6 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 63.1 PK                       | 74.0              | -10.9          | 1.87 H                   | 37                         | 30.3                   | 32.8                           |
| 2                                                   | 2390.00        | 48.8 AV                       | 54.0              | -5.2           | 1.87 H                   | 37                         | 16.0                   | 32.8                           |
| 3                                                   | *2437.00       | 119.4 PK                      |                   |                | 1.84 H                   | 39                         | 86.5                   | 32.9                           |
| 4                                                   | *2437.00       | 109.5 AV                      |                   |                | 1.84 H                   | 39                         | 76.6                   | 32.9                           |
| 5                                                   | 4874.00        | 56.3 PK                       | 74.0              | -17.7          | 1.84 H                   | 282                        | 50.3                   | 6.0                            |
| 6                                                   | 4874.00        | 40.6 AV                       | 54.0              | -13.4          | 1.84 H                   | 282                        | 34.6                   | 6.0                            |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 66.3 PK                       | 74.0              | -7.7           | 3.46 V                   | 353                        | 33.5                   | 32.8                           |
| 2                                                   | 2390.00        | 50.7 AV                       | 54.0              | -3.3           | 3.46 V                   | 353                        | 17.9                   | 32.8                           |
| 3                                                   | *2437.00       | 118.8 PK                      |                   |                | 3.42 V                   | 355                        | 85.9                   | 32.9                           |
| 4                                                   | *2437.00       | 107.9 AV                      |                   |                | 3.42 V                   | 355                        | 75.0                   | 32.9                           |
| 5                                                   | 4874.00        | 50.6 PK                       | 74.0              | -23.4          | 2.15 V                   | 305                        | 44.6                   | 6.0                            |
| 6                                                   | 4874.00        | 35.7 AV                       | 54.0              | -18.3          | 2.15 V                   | 305                        | 29.7                   | 6.0                            |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

|                 |               |          |              |
|-----------------|---------------|----------|--------------|
| CHANNEL         | TX Channel 11 | DETECTOR | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz  | FUNCTION | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2462.00       | 115.6 PK                      |                   |                | 1.72 H                   | 36                         | 82.7                   | 32.9                           |
| 2                                                   | *2462.00       | 105.3 AV                      |                   |                | 1.72 H                   | 36                         | 72.4                   | 32.9                           |
| 3                                                   | 2483.50        | 67.5 PK                       | 74.0              | -6.5           | 2.44 H                   | 301                        | 34.5                   | 33.0                           |
| 4                                                   | 2483.50        | 52.2 AV                       | 54.0              | -1.8           | 2.44 H                   | 301                        | 19.2                   | 33.0                           |
| 5                                                   | 4924.00        | 48.1 PK                       | 74.0              | -25.9          | 1.73 H                   | 310                        | 42.1                   | 6.0                            |
| 6                                                   | 4924.00        | 36.0 AV                       | 54.0              | -18.0          | 1.73 H                   | 310                        | 30.0                   | 6.0                            |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2462.00       | 114.6 PK                      |                   |                | 2.91 V                   | 349                        | 81.7                   | 32.9                           |
| 2                                                   | *2462.00       | 103.9 AV                      |                   |                | 2.91 V                   | 349                        | 71.0                   | 32.9                           |
| 3                                                   | 2483.50        | 62.2 PK                       | 74.0              | -11.8          | 2.86 V                   | 320                        | 29.2                   | 33.0                           |
| 4                                                   | 2483.50        | 49.9 AV                       | 54.0              | -4.1           | 2.86 V                   | 320                        | 16.9                   | 33.0                           |
| 5                                                   | 4924.00        | 47.3 PK                       | 74.0              | -26.7          | 2.00 V                   | 252                        | 41.3                   | 6.0                            |
| 6                                                   | 4924.00        | 35.1 AV                       | 54.0              | -18.9          | 2.00 V                   | 252                        | 29.1                   | 6.0                            |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

### 802.11n (HT40)

|                 |              |                      |              |
|-----------------|--------------|----------------------|--------------|
| CHANNEL         | TX Channel 3 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 66.5 PK                       | 74.0              | -7.5           | 3.14 H                   | 307                        | 33.7                   | 32.8                           |
| 2                                                   | 2390.00        | 52.6 AV                       | 54.0              | -1.4           | 3.14 H                   | 307                        | 19.8                   | 32.8                           |
| 3                                                   | *2422.00       | 109.4 PK                      |                   |                | 1.90 H                   | 39                         | 76.5                   | 32.9                           |
| 4                                                   | *2422.00       | 99.5 AV                       |                   |                | 1.90 H                   | 39                         | 66.6                   | 32.9                           |
| 5                                                   | 4844.00        | 46.7 PK                       | 74.0              | -27.3          | 2.28 H                   | 145                        | 40.9                   | 5.8                            |
| 6                                                   | 4844.00        | 33.5 AV                       | 54.0              | -20.5          | 2.28 H                   | 145                        | 27.7                   | 5.8                            |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 61.7 PK                       | 74.0              | -12.3          | 2.80 V                   | 327                        | 28.9                   | 32.8                           |
| 2                                                   | 2390.00        | 47.7 AV                       | 54.0              | -6.3           | 2.80 V                   | 327                        | 14.9                   | 32.8                           |
| 3                                                   | *2422.00       | 106.3 PK                      |                   |                | 2.40 V                   | 313                        | 73.4                   | 32.9                           |
| 4                                                   | *2422.00       | 96.6 AV                       |                   |                | 2.40 V                   | 313                        | 63.7                   | 32.9                           |
| 5                                                   | 4844.00        | 46.1 PK                       | 74.0              | -27.9          | 2.41 V                   | 195                        | 40.3                   | 5.8                            |
| 6                                                   | 4844.00        | 33.5 AV                       | 54.0              | -20.5          | 2.41 V                   | 195                        | 27.7                   | 5.8                            |

#### Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

|                 |              |          |              |
|-----------------|--------------|----------|--------------|
| CHANNEL         | TX Channel 6 | DETECTOR | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz | FUNCTION | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 65.5 PK                       | 74.0              | -8.5           | 1.31 H                   | 28                         | 32.7                   | 32.8                           |
| 2                                                   | 2390.00        | 52.5 AV                       | 54.0              | -1.5           | 1.31 H                   | 28                         | 19.7                   | 32.8                           |
| 3                                                   | *2437.00       | 112.2 PK                      |                   |                | 1.85 H                   | 38                         | 79.3                   | 32.9                           |
| 4                                                   | *2437.00       | 102.0 AV                      |                   |                | 1.85 H                   | 38                         | 69.1                   | 32.9                           |
| 5                                                   | 2483.50        | 64.9 PK                       | 74.0              | -9.1           | 1.86 H                   | 333                        | 31.9                   | 33.0                           |
| 6                                                   | 2483.50        | 51.7 AV                       | 54.0              | -2.3           | 1.86 H                   | 333                        | 18.7                   | 33.0                           |
| 7                                                   | 4874.00        | 47.1 PK                       | 74.0              | -26.9          | 2.03 H                   | 283                        | 41.1                   | 6.0                            |
| 8                                                   | 4874.00        | 35.9 AV                       | 54.0              | -18.1          | 2.03 H                   | 283                        | 29.9                   | 6.0                            |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 64.3 PK                       | 74.0              | -9.7           | 3.10 V                   | 352                        | 31.5                   | 32.8                           |
| 2                                                   | 2390.00        | 49.2 AV                       | 54.0              | -4.8           | 3.10 V                   | 352                        | 16.4                   | 32.8                           |
| 3                                                   | *2437.00       | 109.9 PK                      |                   |                | 2.40 V                   | 316                        | 77.0                   | 32.9                           |
| 4                                                   | *2437.00       | 100.4 AV                      |                   |                | 2.40 V                   | 316                        | 67.5                   | 32.9                           |
| 5                                                   | 2483.50        | 64.2 PK                       | 74.0              | -9.8           | 3.07 V                   | 309                        | 31.2                   | 33.0                           |
| 6                                                   | 2483.50        | 50.4 AV                       | 54.0              | -3.6           | 3.07 V                   | 309                        | 17.4                   | 33.0                           |
| 7                                                   | 4874.00        | 47.5 PK                       | 74.0              | -26.5          | 2.71 V                   | 201                        | 41.5                   | 6.0                            |
| 8                                                   | 4874.00        | 33.9 AV                       | 54.0              | -20.1          | 2.71 V                   | 201                        | 27.9                   | 6.0                            |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

|                 |              |          |              |
|-----------------|--------------|----------|--------------|
| CHANNEL         | TX Channel 9 | DETECTOR | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz | FUNCTION | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2452.00       | 110.6 PK                      |                   |                | 1.78 H                   | 38                         | 77.6                   | 33.0                           |
| 2                                                   | *2452.00       | 101.2 AV                      |                   |                | 1.78 H                   | 38                         | 68.2                   | 33.0                           |
| 3                                                   | 2483.50        | 67.5 PK                       | 74.0              | -6.5           | 1.79 H                   | 40                         | 34.5                   | 33.0                           |
| 4                                                   | 2483.50        | 52.5 AV                       | 54.0              | -1.5           | 1.79 H                   | 40                         | 19.5                   | 33.0                           |
| 5                                                   | 4904.00        | 46.8 PK                       | 74.0              | -27.2          | 1.86 H                   | 180                        | 40.9                   | 5.9                            |
| 6                                                   | 4904.00        | 34.6 AV                       | 54.0              | -19.4          | 1.86 H                   | 180                        | 28.7                   | 5.9                            |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2452.00       | 107.5 PK                      |                   |                | 2.46 V                   | 357                        | 74.5                   | 33.0                           |
| 2                                                   | *2452.00       | 98.1 AV                       |                   |                | 2.46 V                   | 357                        | 65.1                   | 33.0                           |
| 3                                                   | 2483.50        | 66.6 PK                       | 74.0              | -7.4           | 1.89 V                   | 353                        | 33.6                   | 33.0                           |
| 4                                                   | 2483.50        | 50.5 AV                       | 54.0              | -3.5           | 1.89 V                   | 353                        | 17.5                   | 33.0                           |
| 5                                                   | 4904.00        | 46.6 PK                       | 74.0              | -27.4          | 1.96 V                   | 279                        | 40.7                   | 5.9                            |
| 6                                                   | 4904.00        | 34.3 AV                       | 54.0              | -19.7          | 1.96 V                   | 279                        | 28.4                   | 5.9                            |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

### Radio 3: CDD Mode

802.11b

|                 |              |          |              |
|-----------------|--------------|----------|--------------|
| CHANNEL         | TX Channel 1 | DETECTOR | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz | FUNCTION | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 58.7 PK                       | 74.0              | -15.3          | 2.19 H                   | 45                         | 25.9                   | 32.8                           |
| 2                                                   | 2390.00        | 47.5 AV                       | 54.0              | -6.5           | 2.19 H                   | 45                         | 14.7                   | 32.8                           |
| 3                                                   | *2412.00       | 101.5 PK                      |                   |                | 2.13 H                   | 38                         | 68.6                   | 32.9                           |
| 4                                                   | *2412.00       | 97.9 AV                       |                   |                | 2.13 H                   | 38                         | 65.0                   | 32.9                           |
| 5                                                   | 4824.00        | 56.3 PK                       | 74.0              | -17.7          | 1.35 H                   | 39                         | 50.4                   | 5.9                            |
| 6                                                   | 4824.00        | 52.4 AV                       | 54.0              | -1.6           | 1.35 H                   | 39                         | 46.5                   | 5.9                            |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 58.6 PK                       | 74.0              | -15.4          | 2.88 V                   | 22                         | 25.8                   | 32.8                           |
| 2                                                   | 2390.00        | 46.3 AV                       | 54.0              | -7.7           | 2.88 V                   | 22                         | 13.5                   | 32.8                           |
| 3                                                   | *2412.00       | 94.9 PK                       |                   |                | 2.86 V                   | 24                         | 62.0                   | 32.9                           |
| 4                                                   | *2412.00       | 91.1 AV                       |                   |                | 2.86 V                   | 24                         | 58.2                   | 32.9                           |
| 5                                                   | 4824.00        | 57.7 PK                       | 74.0              | -16.3          | 2.54 V                   | 321                        | 51.8                   | 5.9                            |
| 6                                                   | 4824.00        | 52.6 AV                       | 54.0              | -1.4           | 2.54 V                   | 321                        | 46.7                   | 5.9                            |

#### Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

|                 |              |                      |              |
|-----------------|--------------|----------------------|--------------|
| CHANNEL         | TX Channel 6 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2437.00       | 101.1 PK                      |                   |                | 2.31 H                   | 33                         | 68.2                   | 32.9                           |
| 2                                                   | *2437.00       | 96.7 AV                       |                   |                | 2.31 H                   | 33                         | 63.8                   | 32.9                           |
| 3                                                   | 4874.00        | 57.6 PK                       | 74.0              | -16.4          | 1.39 H                   | 42                         | 51.6                   | 6.0                            |
| 4                                                   | 4874.00        | 52.6 AV                       | 54.0              | -1.4           | 1.39 H                   | 42                         | 46.6                   | 6.0                            |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2437.00       | 95.9 PK                       |                   |                | 2.96 V                   | 16                         | 63.0                   | 32.9                           |
| 2                                                   | *2437.00       | 91.7 AV                       |                   |                | 2.96 V                   | 16                         | 58.8                   | 32.9                           |
| 3                                                   | 4874.00        | 57.2 PK                       | 74.0              | -16.8          | 2.36 V                   | 318                        | 51.2                   | 6.0                            |
| 4                                                   | 4874.00        | 52.3 AV                       | 54.0              | -1.7           | 2.36 V                   | 318                        | 46.3                   | 6.0                            |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

|                 |               |          |              |
|-----------------|---------------|----------|--------------|
| CHANNEL         | TX Channel 11 | DETECTOR | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz  | FUNCTION | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2462.00       | 102.7 PK                      |                   |                | 1.82 H                   | 37                         | 69.8                   | 32.9                           |
| 2                                                   | *2462.00       | 98.3 AV                       |                   |                | 1.82 H                   | 37                         | 65.4                   | 32.9                           |
| 3                                                   | 2483.50        | 58.7 PK                       | 74.0              | -15.3          | 1.78 H                   | 45                         | 25.7                   | 33.0                           |
| 4                                                   | 2483.50        | 46.4 AV                       | 54.0              | -7.6           | 1.78 H                   | 45                         | 13.4                   | 33.0                           |
| 5                                                   | 4924.00        | 56.2 PK                       | 74.0              | -17.8          | 1.57 H                   | 39                         | 50.2                   | 6.0                            |
| 6                                                   | 4924.00        | 52.8 AV                       | 54.0              | -1.2           | 1.57 H                   | 39                         | 46.8                   | 6.0                            |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2462.00       | 96.6 PK                       |                   |                | 2.84 V                   | 16                         | 63.7                   | 32.9                           |
| 2                                                   | *2462.00       | 92.3 AV                       |                   |                | 2.84 V                   | 16                         | 59.4                   | 32.9                           |
| 3                                                   | 2483.50        | 58.4 PK                       | 74.0              | -15.6          | 2.66 V                   | 37                         | 25.4                   | 33.0                           |
| 4                                                   | 2483.50        | 46.1 AV                       | 54.0              | -7.9           | 2.66 V                   | 37                         | 13.1                   | 33.0                           |
| 5                                                   | 4924.00        | 56.4 PK                       | 74.0              | -17.6          | 2.35 V                   | 321                        | 50.4                   | 6.0                            |
| 6                                                   | 4924.00        | 51.6 AV                       | 54.0              | -2.4           | 2.35 V                   | 321                        | 45.6                   | 6.0                            |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

802.11g

|                 |              |                      |              |
|-----------------|--------------|----------------------|--------------|
| CHANNEL         | TX Channel 1 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 68.5 PK                       | 74.0              | -5.5           | 2.68 H                   | 37                         | 35.7                   | 32.8                           |
| 2                                                   | 2390.00        | 52.6 AV                       | 54.0              | -1.4           | 2.68 H                   | 37                         | 19.8                   | 32.8                           |
| 3                                                   | *2412.00       | 101.2 PK                      |                   |                | 2.56 H                   | 37                         | 68.3                   | 32.9                           |
| 4                                                   | *2412.00       | 90.7 AV                       |                   |                | 2.56 H                   | 37                         | 57.8                   | 32.9                           |
| 5                                                   | 4824.00        | 54.0 PK                       | 74.0              | -20.0          | 1.23 H                   | 38                         | 48.1                   | 5.9                            |
| 6                                                   | 4824.00        | 40.6 AV                       | 54.0              | -13.4          | 1.23 H                   | 38                         | 34.7                   | 5.9                            |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 57.8 PK                       | 74.0              | -16.2          | 1.35 V                   | 340                        | 25.0                   | 32.8                           |
| 2                                                   | 2390.00        | 46.2 AV                       | 54.0              | -7.8           | 1.35 V                   | 340                        | 13.4                   | 32.8                           |
| 3                                                   | *2412.00       | 94.1 PK                       |                   |                | 1.37 V                   | 346                        | 61.2                   | 32.9                           |
| 4                                                   | *2412.00       | 83.5 AV                       |                   |                | 1.37 V                   | 346                        | 50.6                   | 32.9                           |
| 5                                                   | 4824.00        | 55.6 PK                       | 74.0              | -18.4          | 2.66 V                   | 319                        | 49.7                   | 5.9                            |
| 6                                                   | 4824.00        | 40.9 AV                       | 54.0              | -13.1          | 2.66 V                   | 319                        | 35.0                   | 5.9                            |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

|                 |              |                      |              |
|-----------------|--------------|----------------------|--------------|
| CHANNEL         | TX Channel 6 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2437.00       | 106.6 PK                      |                   |                | 1.64 H                   | 34                         | 73.7                   | 32.9                           |
| 2                                                   | *2437.00       | 95.6 AV                       |                   |                | 1.64 H                   | 34                         | 62.7                   | 32.9                           |
| 3                                                   | 4874.00        | 66.6 PK                       | 74.0              | -7.4           | 1.36 H                   | 40                         | 60.6                   | 6.0                            |
| 4                                                   | 4874.00        | 52.6 AV                       | 54.0              | -1.4           | 1.36 H                   | 40                         | 46.6                   | 6.0                            |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2437.00       | 97.9 PK                       |                   |                | 2.64 V                   | 19                         | 65.0                   | 32.9                           |
| 2                                                   | *2437.00       | 88.2 AV                       |                   |                | 2.64 V                   | 19                         | 55.3                   | 32.9                           |
| 3                                                   | 4874.00        | 62.7 PK                       | 74.0              | -11.3          | 1.39 V                   | 324                        | 56.7                   | 6.0                            |
| 4                                                   | 4874.00        | 49.1 AV                       | 54.0              | -4.9           | 1.39 V                   | 324                        | 43.1                   | 6.0                            |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

|                 |               |          |              |
|-----------------|---------------|----------|--------------|
| CHANNEL         | TX Channel 11 | DETECTOR | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz  | FUNCTION | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2462.00       | 104.5 PK                      |                   |                | 1.82 H                   | 33                         | 71.6                   | 32.9                           |
| 2                                                   | *2462.00       | 93.7 AV                       |                   |                | 1.82 H                   | 33                         | 60.8                   | 32.9                           |
| 3                                                   | 2483.50        | 66.3 PK                       | 74.0              | -7.7           | 1.83 H                   | 31                         | 33.3                   | 33.0                           |
| 4                                                   | 2483.50        | 52.7 AV                       | 54.0              | -1.3           | 1.83 H                   | 31                         | 19.7                   | 33.0                           |
| 5                                                   | 4924.00        | 54.7 PK                       | 74.0              | -19.3          | 1.39 H                   | 41                         | 48.7                   | 6.0                            |
| 6                                                   | 4924.00        | 40.8 AV                       | 54.0              | -13.2          | 1.39 H                   | 41                         | 34.8                   | 6.0                            |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2462.00       | 95.2 PK                       |                   |                | 2.64 V                   | 19                         | 62.3                   | 32.9                           |
| 2                                                   | *2462.00       | 85.3 AV                       |                   |                | 2.64 V                   | 19                         | 52.4                   | 32.9                           |
| 3                                                   | 2483.50        | 60.5 PK                       | 74.0              | -13.5          | 2.53 V                   | 20                         | 27.5                   | 33.0                           |
| 4                                                   | 2483.50        | 48.6 AV                       | 54.0              | -5.4           | 2.53 V                   | 20                         | 15.6                   | 33.0                           |
| 5                                                   | 4924.00        | 51.9 PK                       | 74.0              | -22.1          | 1.57 V                   | 325                        | 45.9                   | 6.0                            |
| 6                                                   | 4924.00        | 38.4 AV                       | 54.0              | -15.6          | 1.57 V                   | 325                        | 32.4                   | 6.0                            |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

### 802.11n (HT20)

|                 |              |                      |              |
|-----------------|--------------|----------------------|--------------|
| CHANNEL         | TX Channel 1 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 68.2 PK                       | 74.0              | -5.8           | 1.90 H                   | 36                         | 35.4                   | 32.8                           |
| 2                                                   | 2390.00        | 52.8 AV                       | 54.0              | -1.2           | 1.90 H                   | 36                         | 20.0                   | 32.8                           |
| 3                                                   | *2412.00       | 99.3 PK                       |                   |                | 2.62 H                   | 42                         | 66.4                   | 32.9                           |
| 4                                                   | *2412.00       | 89.7 AV                       |                   |                | 2.62 H                   | 42                         | 56.8                   | 32.9                           |
| 5                                                   | 4824.00        | 51.0 PK                       | 74.0              | -23.0          | 1.33 H                   | 54                         | 45.1                   | 5.9                            |
| 6                                                   | 4824.00        | 37.9 AV                       | 54.0              | -16.1          | 1.33 H                   | 54                         | 32.0                   | 5.9                            |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 61.4 PK                       | 74.0              | -12.6          | 2.56 V                   | 22                         | 28.6                   | 32.8                           |
| 2                                                   | 2390.00        | 47.5 AV                       | 54.0              | -6.5           | 2.56 V                   | 22                         | 14.7                   | 32.8                           |
| 3                                                   | *2412.00       | 92.5 PK                       |                   |                | 2.66 V                   | 17                         | 59.6                   | 32.9                           |
| 4                                                   | *2412.00       | 83.1 AV                       |                   |                | 2.66 V                   | 17                         | 50.2                   | 32.9                           |
| 5                                                   | 4824.00        | 51.3 PK                       | 74.0              | -22.7          | 2.50 V                   | 321                        | 45.4                   | 5.9                            |
| 6                                                   | 4824.00        | 37.4 AV                       | 54.0              | -16.6          | 2.50 V                   | 321                        | 31.5                   | 5.9                            |

#### Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

|                 |              |                      |              |
|-----------------|--------------|----------------------|--------------|
| CHANNEL         | TX Channel 6 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2437.00       | 105.2 PK                      |                   |                | 1.63 H                   | 31                         | 72.3                   | 32.9                           |
| 2                                                   | *2437.00       | 96.0 AV                       |                   |                | 1.63 H                   | 31                         | 63.1                   | 32.9                           |
| 3                                                   | 4874.00        | 66.9 PK                       | 74.0              | -7.1           | 1.30 H                   | 44                         | 60.9                   | 6.0                            |
| 4                                                   | 4874.00        | 52.3 AV                       | 54.0              | -1.7           | 1.30 H                   | 44                         | 46.3                   | 6.0                            |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2437.00       | 100.6 PK                      |                   |                | 3.22 V                   | 26                         | 67.7                   | 32.9                           |
| 2                                                   | *2437.00       | 90.6 AV                       |                   |                | 3.22 V                   | 26                         | 57.7                   | 32.9                           |
| 3                                                   | 4874.00        | 68.0 PK                       | 74.0              | -6.0           | 2.52 V                   | 319                        | 62.0                   | 6.0                            |
| 4                                                   | 4874.00        | 52.9 AV                       | 54.0              | -1.1           | 2.52 V                   | 319                        | 46.9                   | 6.0                            |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

|                 |               |          |              |
|-----------------|---------------|----------|--------------|
| CHANNEL         | TX Channel 11 | DETECTOR | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz  | FUNCTION | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2462.00       | 100.1 PK                      |                   |                | 2.30 H                   | 40                         | 67.2                   | 32.9                           |
| 2                                                   | *2462.00       | 90.1 AV                       |                   |                | 2.30 H                   | 40                         | 57.2                   | 32.9                           |
| 3                                                   | 2483.50        | 65.3 PK                       | 74.0              | -8.7           | 2.03 H                   | 34                         | 32.3                   | 33.0                           |
| 4                                                   | 2483.50        | 52.5 AV                       | 54.0              | -1.5           | 2.03 H                   | 34                         | 19.5                   | 33.0                           |
| 5                                                   | 4924.00        | 52.6 PK                       | 74.0              | -21.4          | 1.40 H                   | 56                         | 46.6                   | 6.0                            |
| 6                                                   | 4924.00        | 39.6 AV                       | 54.0              | -14.4          | 1.40 H                   | 56                         | 33.6                   | 6.0                            |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2462.00       | 95.0 PK                       |                   |                | 2.63 V                   | 27                         | 62.1                   | 32.9                           |
| 2                                                   | *2462.00       | 85.5 AV                       |                   |                | 2.63 V                   | 27                         | 52.6                   | 32.9                           |
| 3                                                   | 2483.50        | 60.9 PK                       | 74.0              | -13.1          | 2.63 V                   | 27                         | 27.9                   | 33.0                           |
| 4                                                   | 2483.50        | 49.0 AV                       | 54.0              | -5.0           | 2.63 V                   | 27                         | 16.0                   | 33.0                           |
| 5                                                   | 4924.00        | 50.7 PK                       | 74.0              | -23.3          | 2.56 V                   | 315                        | 44.7                   | 6.0                            |
| 6                                                   | 4924.00        | 37.0 AV                       | 54.0              | -17.0          | 2.56 V                   | 315                        | 31.0                   | 6.0                            |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* " : Fundamental frequency.

# 802.11n (HT40)

|                 |              |                      |              |
|-----------------|--------------|----------------------|--------------|
| CHANNEL         | TX Channel 3 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 64.4 PK                       | 74.0              | -9.6           | 2.28 H                   | 35                         | 31.6                   | 32.8                           |
| 2                                                   | 2390.00        | 52.6 AV                       | 54.0              | -1.4           | 2.28 H                   | 35                         | 19.8                   | 32.8                           |
| 3                                                   | *2422.00       | 95.8 PK                       |                   |                | 2.31 H                   | 36                         | 62.9                   | 32.9                           |
| 4                                                   | *2422.00       | 85.3 AV                       |                   |                | 2.31 H                   | 36                         | 52.4                   | 32.9                           |
| 5                                                   | 4844.00        | 49.2 PK                       | 74.0              | -24.8          | 2.07 H                   | 269                        | 43.4                   | 5.8                            |
| 6                                                   | 4844.00        | 35.6 AV                       | 54.0              | -18.4          | 2.07 H                   | 269                        | 29.8                   | 5.8                            |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 59.2 PK                       | 74.0              | -14.8          | 2.72 V                   | 306                        | 26.4                   | 32.8                           |
| 2                                                   | 2390.00        | 47.8 AV                       | 54.0              | -6.2           | 2.72 V                   | 306                        | 15.0                   | 32.8                           |
| 3                                                   | *2422.00       | 87.7 PK                       |                   |                | 3.68 V                   | 312                        | 54.8                   | 32.9                           |
| 4                                                   | *2422.00       | 78.3 AV                       |                   |                | 3.68 V                   | 312                        | 45.4                   | 32.9                           |
| 5                                                   | 4844.00        | 46.8 PK                       | 74.0              | -27.2          | 2.01 V                   | 44                         | 41.0                   | 5.8                            |
| 6                                                   | 4844.00        | 34.1 AV                       | 54.0              | -19.9          | 2.01 V                   | 44                         | 28.3                   | 5.8                            |

## Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

|                 |              |          |              |
|-----------------|--------------|----------|--------------|
| CHANNEL         | TX Channel 6 | DETECTOR | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz | FUNCTION | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 63.5 PK                       | 74.0              | -10.5          | 1.96 H                   | 37                         | 30.7                   | 32.8                           |
| 2                                                   | 2390.00        | 49.7 AV                       | 54.0              | -4.3           | 1.96 H                   | 37                         | 16.9                   | 32.8                           |
| 3                                                   | *2437.00       | 101.2 PK                      |                   |                | 1.87 H                   | 29                         | 68.3                   | 32.9                           |
| 4                                                   | *2437.00       | 90.1 AV                       |                   |                | 1.87 H                   | 29                         | 57.2                   | 32.9                           |
| 5                                                   | 2483.50        | 66.9 PK                       | 74.0              | -7.1           | 2.05 H                   | 34                         | 33.9                   | 33.0                           |
| 6                                                   | 2483.50        | 52.7 AV                       | 54.0              | -1.3           | 2.05 H                   | 34                         | 19.7                   | 33.0                           |
| 7                                                   | 4874.00        | 52.0 PK                       | 74.0              | -22.0          | 1.68 H                   | 33                         | 46.0                   | 6.0                            |
| 8                                                   | 4874.00        | 39.5 AV                       | 54.0              | -14.5          | 1.68 H                   | 33                         | 33.5                   | 6.0                            |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 58.4 PK                       | 74.0              | -15.6          | 2.41 V                   | 19                         | 25.6                   | 32.8                           |
| 2                                                   | 2390.00        | 47.9 AV                       | 54.0              | -6.1           | 2.41 V                   | 19                         | 15.1                   | 32.8                           |
| 3                                                   | *2437.00       | 91.3 PK                       |                   |                | 3.62 V                   | 342                        | 58.4                   | 32.9                           |
| 4                                                   | *2437.00       | 82.0 AV                       |                   |                | 3.62 V                   | 342                        | 49.1                   | 32.9                           |
| 5                                                   | 2483.50        | 59.2 PK                       | 74.0              | -14.8          | 3.62 V                   | 342                        | 26.2                   | 33.0                           |
| 6                                                   | 2483.50        | 47.5 AV                       | 54.0              | -6.5           | 3.62 V                   | 342                        | 14.5                   | 33.0                           |
| 7                                                   | 4874.00        | 51.0 PK                       | 74.0              | -23.0          | 1.69 V                   | 228                        | 45.0                   | 6.0                            |
| 8                                                   | 4874.00        | 38.1 AV                       | 54.0              | -15.9          | 1.69 V                   | 228                        | 32.1                   | 6.0                            |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

|                 |              |                      |              |
|-----------------|--------------|----------------------|--------------|
| CHANNEL         | TX Channel 9 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2452.00       | 97.5 PK                       |                   |                | 1.83 H                   | 33                         | 64.5                   | 33.0                           |
| 2                                                   | *2452.00       | 86.3 AV                       |                   |                | 1.83 H                   | 33                         | 53.3                   | 33.0                           |
| 3                                                   | 2483.50        | 65.0 PK                       | 74.0              | -9.0           | 1.38 H                   | 35                         | 32.0                   | 33.0                           |
| 4                                                   | 2483.50        | 52.6 AV                       | 54.0              | -1.4           | 1.38 H                   | 35                         | 19.6                   | 33.0                           |
| 5                                                   | 4904.00        | 48.8 PK                       | 74.0              | -25.2          | 2.22 H                   | 127                        | 42.9                   | 5.9                            |
| 6                                                   | 4904.00        | 36.3 AV                       | 54.0              | -17.7          | 2.22 H                   | 127                        | 30.4                   | 5.9                            |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2452.00       | 88.0 PK                       |                   |                | 3.62 V                   | 357                        | 55.0                   | 33.0                           |
| 2                                                   | *2452.00       | 78.8 AV                       |                   |                | 3.62 V                   | 357                        | 45.8                   | 33.0                           |
| 3                                                   | 2483.50        | 59.1 PK                       | 74.0              | -14.9          | 3.28 V                   | 359                        | 26.1                   | 33.0                           |
| 4                                                   | 2483.50        | 48.1 AV                       | 54.0              | -5.9           | 3.28 V                   | 359                        | 15.1                   | 33.0                           |
| 5                                                   | 4904.00        | 46.8 PK                       | 74.0              | -27.2          | 2.56 V                   | 333                        | 40.9                   | 5.9                            |
| 6                                                   | 4904.00        | 34.1 AV                       | 54.0              | -19.9          | 2.56 V                   | 333                        | 28.2                   | 5.9                            |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

Below 1GHz worst-case data:

Radio 1: CDD Mode

802.11b

|                 |              |                   |                 |
|-----------------|--------------|-------------------|-----------------|
| CHANNEL         | TX Channel 1 | DETECTOR FUNCTION | Quasi-Peak (QP) |
| FREQUENCY RANGE | 9kHz ~ 1GHz  |                   |                 |
| TEST MODE       | A            |                   |                 |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |             |                         |                |             |                    |                      |                  |                          |
|-----------------------------------------------------|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO.                                                 | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1                                                   | 57.12       | 30.8 QP                 | 40.0           | -9.2        | 2.00 H             | 116                  | 45.4             | -14.6                    |
| 2                                                   | 199.05      | 40.1 QP                 | 43.5           | -3.4        | 1.00 H             | 239                  | 56.6             | -16.5                    |
| 3                                                   | 354.60      | 37.0 QP                 | 46.0           | -9.0        | 2.00 H             | 178                  | 48.1             | -11.1                    |
| 4                                                   | 500.42      | 32.9 QP                 | 46.0           | -13.1       | 1.50 H             | 186                  | 40.8             | -7.9                     |
| 5                                                   | 700.68      | 32.5 QP                 | 46.0           | -13.5       | 1.00 H             | 111                  | 36.1             | -3.6                     |
| 6                                                   | 799.84      | 35.7 QP                 | 46.0           | -10.3       | 1.50 H             | 98                   | 37.2             | -1.5                     |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |             |                         |                |             |                    |                      |                  |                          |
| NO.                                                 | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1                                                   | 35.73       | 35.1 QP                 | 40.0           | -4.9        | 1.00 V             | 157                  | 50.7             | -15.6                    |
| 2                                                   | 70.73       | 35.4 QP                 | 40.0           | -4.6        | 1.00 V             | 207                  | 51.9             | -16.5                    |
| 3                                                   | 199.05      | 36.2 QP                 | 43.5           | -7.3        | 1.00 V             | 55                   | 52.7             | -16.5                    |
| 4                                                   | 348.76      | 33.8 QP                 | 46.0           | -12.2       | 1.49 V             | 272                  | 45.1             | -11.3                    |
| 5                                                   | 599.58      | 30.1 QP                 | 46.0           | -15.9       | 1.00 V             | 159                  | 35.5             | -5.4                     |
| 6                                                   | 799.84      | 35.4 QP                 | 46.0           | -10.6       | 1.00 V             | 336                  | 36.9             | -1.5                     |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

|                 |              |                   |                 |
|-----------------|--------------|-------------------|-----------------|
| CHANNEL         | TX Channel 1 | DETECTOR FUNCTION | Quasi-Peak (QP) |
| FREQUENCY RANGE | 9kHz ~ 1GHz  |                   |                 |
| TEST MODE       | B            |                   |                 |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |             |                         |                |             |                    |                      |                  |                          |
|-----------------------------------------------------|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO.                                                 | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1                                                   | 57.12       | 28.8 QP                 | 40.0           | -11.2       | 1.50 H             | 7                    | 43.4             | -14.6                    |
| 2                                                   | 119.34      | 31.8 QP                 | 43.5           | -11.7       | 1.50 H             | 272                  | 48.2             | -16.4                    |
| 3                                                   | 199.05      | 39.4 QP                 | 43.5           | -4.1        | 1.00 H             | 238                  | 55.9             | -16.5                    |
| 4                                                   | 239.88      | 36.7 QP                 | 46.0           | -9.3        | 1.50 H             | 114                  | 51.2             | -14.5                    |
| 5                                                   | 292.38      | 38.2 QP                 | 46.0           | -7.8        | 1.00 H             | 154                  | 50.5             | -12.3                    |
| 6                                                   | 700.68      | 32.9 QP                 | 46.0           | -13.1       | 2.00 H             | 112                  | 36.5             | -3.6                     |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |             |                         |                |             |                    |                      |                  |                          |
| NO.                                                 | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1                                                   | 43.51       | 34.8 QP                 | 40.0           | -5.2        | 1.49 V             | 207                  | 49.6             | -14.8                    |
| 2                                                   | 199.05      | 38.7 QP                 | 43.5           | -4.8        | 1.00 V             | 50                   | 55.2             | -16.5                    |
| 3                                                   | 234.05      | 36.5 QP                 | 46.0           | -9.5        | 1.00 V             | 200                  | 51.8             | -15.3                    |
| 4                                                   | 284.60      | 34.5 QP                 | 46.0           | -11.5       | 1.00 V             | 62                   | 46.9             | -12.4                    |
| 5                                                   | 342.93      | 32.7 QP                 | 46.0           | -13.3       | 1.49 V             | 139                  | 44.0             | -11.3                    |
| 6                                                   | 799.84      | 34.1 QP                 | 46.0           | -11.9       | 1.00 V             | 12                   | 35.6             | -1.5                     |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

|                 |              |                   |                 |
|-----------------|--------------|-------------------|-----------------|
| CHANNEL         | TX Channel 1 | DETECTOR FUNCTION | Quasi-Peak (QP) |
| FREQUENCY RANGE | 9kHz ~ 1GHz  |                   |                 |
| TEST MODE       | C            |                   |                 |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 57.12          | 31.1 QP                       | 40.0              | -8.9           | 1.99 H                   | 238                        | 45.7                   | -14.6                          |
| 2                                                   | 119.34         | 32.5 QP                       | 43.5              | -11.0          | 1.49 H                   | 111                        | 48.9                   | -16.4                          |
| 3                                                   | 199.05         | 38.7 QP                       | 43.5              | -4.8           | 1.49 H                   | 115                        | 55.2                   | -16.5                          |
| 4                                                   | 249.60         | 34.6 QP                       | 46.0              | -11.4          | 1.00 H                   | 9                          | 48.6                   | -14.0                          |
| 5                                                   | 374.04         | 30.7 QP                       | 46.0              | -15.3          | 1.99 H                   | 139                        | 41.2                   | -10.5                          |
| 6                                                   | 500.42         | 30.8 QP                       | 46.0              | -15.2          | 1.49 H                   | 270                        | 38.7                   | -7.9                           |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 45.45          | 36.7 QP                       | 40.0              | -3.3           | 1.00 V                   | 105                        | 51.4                   | -14.7                          |
| 2                                                   | 70.73          | 37.7 QP                       | 40.0              | -2.3           | 1.49 V                   | 239                        | 54.2                   | -16.5                          |
| 3                                                   | 199.05         | 34.7 QP                       | 43.5              | -8.8           | 1.00 V                   | 342                        | 51.2                   | -16.5                          |
| 4                                                   | 249.60         | 32.8 QP                       | 46.0              | -13.2          | 1.00 V                   | 354                        | 46.8                   | -14.0                          |
| 5                                                   | 374.04         | 30.0 QP                       | 46.0              | -16.0          | 1.00 V                   | 176                        | 40.5                   | -10.5                          |
| 6                                                   | 500.42         | 30.1 QP                       | 46.0              | -15.9          | 1.00 V                   | 247                        | 38.0                   | -7.9                           |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

|                 |              |                   |                 |
|-----------------|--------------|-------------------|-----------------|
| CHANNEL         | TX Channel 1 | DETECTOR FUNCTION | Quasi-Peak (QP) |
| FREQUENCY RANGE | 9kHz ~ 1GHz  |                   |                 |
| TEST MODE       | D            |                   |                 |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |             |                         |                |             |                    |                      |                  |                          |
|-----------------------------------------------------|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO.                                                 | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1                                                   | 70.73       | 33.3 QP                 | 40.0           | -6.7        | 1.50 H             | 274                  | 49.8             | -16.5                    |
| 2                                                   | 119.34      | 34.1 QP                 | 43.5           | -9.4        | 1.99 H             | 122                  | 50.5             | -16.4                    |
| 3                                                   | 199.05      | 35.8 QP                 | 43.5           | -7.7        | 1.50 H             | 145                  | 52.3             | -16.5                    |
| 4                                                   | 249.60      | 35.3 QP                 | 46.0           | -10.7       | 1.00 H             | 263                  | 49.3             | -14.0                    |
| 5                                                   | 500.42      | 31.0 QP                 | 46.0           | -15.0       | 1.50 H             | 16                   | 38.9             | -7.9                     |
| 6                                                   | 700.68      | 32.7 QP                 | 46.0           | -13.3       | 1.00 H             | 148                  | 36.3             | -3.6                     |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |             |                         |                |             |                    |                      |                  |                          |
| NO.                                                 | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1                                                   | 45.45       | 34.5 QP                 | 40.0           | -5.5        | 1.00 V             | 305                  | 49.2             | -14.7                    |
| 2                                                   | 55.18       | 35.0 QP                 | 40.0           | -5.0        | 1.00 V             | 69                   | 49.4             | -14.4                    |
| 3                                                   | 199.05      | 32.0 QP                 | 43.5           | -11.5       | 1.00 V             | 9                    | 48.5             | -16.5                    |
| 4                                                   | 249.60      | 34.3 QP                 | 46.0           | -11.7       | 1.00 V             | 223                  | 48.3             | -14.0                    |
| 5                                                   | 374.04      | 31.8 QP                 | 46.0           | -14.2       | 1.00 V             | 174                  | 42.3             | -10.5                    |
| 6                                                   | 500.42      | 32.9 QP                 | 46.0           | -13.1       | 1.00 V             | 265                  | 40.8             | -7.9                     |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

### Radio 3: CDD Mode

#### 802.11b

|                 |              |                      |                 |
|-----------------|--------------|----------------------|-----------------|
| CHANNEL         | TX Channel 1 | DETECTOR<br>FUNCTION | Quasi-Peak (QP) |
| FREQUENCY RANGE | 9kHz ~ 1GHz  |                      |                 |
| TEST MODE       | A            |                      |                 |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 57.12          | 29.7 QP                       | 40.0              | -10.3          | 1.50 H                   | 224                        | 44.3                   | -14.6                          |
| 2                                                   | 199.05         | 40.2 QP                       | 43.5              | -3.3           | 1.00 H                   | 14                         | 56.7                   | -16.5                          |
| 3                                                   | 249.60         | 39.6 QP                       | 46.0              | -6.4           | 1.00 H                   | 124                        | 53.6                   | -14.0                          |
| 4                                                   | 348.76         | 34.7 QP                       | 46.0              | -11.3          | 1.00 H                   | 154                        | 46.0                   | -11.3                          |
| 5                                                   | 500.42         | 32.3 QP                       | 46.0              | -13.7          | 1.50 H                   | 127                        | 40.2                   | -7.9                           |
| 6                                                   | 799.84         | 36.5 QP                       | 46.0              | -9.5           | 1.50 H                   | 108                        | 38.0                   | -1.5                           |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 35.73          | 34.9 QP                       | 40.0              | -5.1           | 1.00 V                   | 108                        | 50.5                   | -15.6                          |
| 2                                                   | 140.72         | 31.6 QP                       | 43.5              | -11.9          | 1.00 V                   | 139                        | 46.1                   | -14.5                          |
| 3                                                   | 199.05         | 32.8 QP                       | 43.5              | -10.7          | 1.50 V                   | 13                         | 49.3                   | -16.5                          |
| 4                                                   | 249.60         | 35.0 QP                       | 46.0              | -11.0          | 1.00 V                   | 64                         | 49.0                   | -14.0                          |
| 5                                                   | 352.65         | 36.9 QP                       | 46.0              | -9.1           | 1.50 V                   | 275                        | 48.0                   | -11.1                          |
| 6                                                   | 399.31         | 32.1 QP                       | 46.0              | -13.9          | 1.00 V                   | 148                        | 42.2                   | -10.1                          |

#### Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

|                 |              |                   |                 |
|-----------------|--------------|-------------------|-----------------|
| CHANNEL         | TX Channel 1 | DETECTOR FUNCTION | Quasi-Peak (QP) |
| FREQUENCY RANGE | 9kHz ~ 1GHz  |                   |                 |
| TEST MODE       | B            |                   |                 |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |             |                         |                |             |                    |                      |                  |                          |
|-----------------------------------------------------|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO.                                                 | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1                                                   | 57.12       | 26.1 QP                 | 40.0           | -13.9       | 1.50 H             | 102                  | 40.7             | -14.6                    |
| 2                                                   | 199.05      | 38.1 QP                 | 43.5           | -5.4        | 1.00 H             | 240                  | 54.6             | -16.5                    |
| 3                                                   | 249.60      | 38.4 QP                 | 46.0           | -7.6        | 2.00 H             | 247                  | 52.4             | -14.0                    |
| 4                                                   | 292.38      | 37.2 QP                 | 46.0           | -8.8        | 1.00 H             | 148                  | 49.5             | -12.3                    |
| 5                                                   | 700.68      | 33.2 QP                 | 46.0           | -12.8       | 1.00 H             | 198                  | 36.8             | -3.6                     |
| 6                                                   | 799.84      | 34.4 QP                 | 46.0           | -11.6       | 1.50 H             | 205                  | 35.9             | -1.5                     |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |             |                         |                |             |                    |                      |                  |                          |
| NO.                                                 | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1                                                   | 43.51       | 34.8 QP                 | 40.0           | -5.2        | 1.00 V             | 81                   | 49.6             | -14.8                    |
| 2                                                   | 199.05      | 38.9 QP                 | 43.5           | -4.6        | 1.00 V             | 55                   | 55.4             | -16.5                    |
| 3                                                   | 232.11      | 36.5 QP                 | 46.0           | -9.5        | 1.00 V             | 291                  | 52.0             | -15.5                    |
| 4                                                   | 350.71      | 32.9 QP                 | 46.0           | -13.1       | 1.49 V             | 143                  | 44.1             | -11.2                    |
| 5                                                   | 500.42      | 30.1 QP                 | 46.0           | -15.9       | 1.00 V             | 189                  | 38.0             | -7.9                     |
| 6                                                   | 799.84      | 35.6 QP                 | 46.0           | -10.4       | 1.49 V             | 7                    | 37.1             | -1.5                     |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

|                 |              |                   |                 |
|-----------------|--------------|-------------------|-----------------|
| CHANNEL         | TX Channel 1 | DETECTOR FUNCTION | Quasi-Peak (QP) |
| FREQUENCY RANGE | 9kHz ~ 1GHz  |                   |                 |
| TEST MODE       | C            |                   |                 |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |             |                         |                |             |                    |                      |                  |                          |
|-----------------------------------------------------|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO.                                                 | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1                                                   | 57.12       | 30.1 QP                 | 40.0           | -9.9        | 2.00 H             | 235                  | 44.7             | -14.6                    |
| 2                                                   | 199.05      | 36.3 QP                 | 43.5           | -7.2        | 1.50 H             | 103                  | 52.8             | -16.5                    |
| 3                                                   | 249.60      | 36.5 QP                 | 46.0           | -9.5        | 1.01 H             | 4                    | 50.5             | -14.0                    |
| 4                                                   | 374.04      | 31.8 QP                 | 46.0           | -14.2       | 2.00 H             | 152                  | 42.3             | -10.5                    |
| 5                                                   | 500.42      | 31.7 QP                 | 46.0           | -14.3       | 1.50 H             | 246                  | 39.6             | -7.9                     |
| 6                                                   | 700.68      | 30.9 QP                 | 46.0           | -15.1       | 1.01 H             | 203                  | 34.5             | -3.6                     |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |             |                         |                |             |                    |                      |                  |                          |
| NO.                                                 | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1                                                   | 45.45       | 36.8 QP                 | 40.0           | -3.2        | 1.50 V             | 146                  | 51.5             | -14.7                    |
| 2                                                   | 62.95       | 36.2 QP                 | 40.0           | -3.8        | 1.50 V             | 16                   | 51.3             | -15.1                    |
| 3                                                   | 199.05      | 33.3 QP                 | 43.5           | -10.2       | 1.00 V             | 12                   | 49.8             | -16.5                    |
| 4                                                   | 249.60      | 32.8 QP                 | 46.0           | -13.2       | 1.00 V             | 338                  | 46.8             | -14.0                    |
| 5                                                   | 374.04      | 30.4 QP                 | 46.0           | -15.6       | 1.00 V             | 162                  | 40.9             | -10.5                    |
| 6                                                   | 500.42      | 30.4 QP                 | 46.0           | -15.6       | 1.00 V             | 251                  | 38.3             | -7.9                     |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

|                 |              |                      |                 |
|-----------------|--------------|----------------------|-----------------|
| CHANNEL         | TX Channel 1 | DETECTOR<br>FUNCTION | Quasi-Peak (QP) |
| FREQUENCY RANGE | 9kHz ~ 1GHz  |                      |                 |
| TEST MODE       | D            |                      |                 |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 57.12          | 29.5 QP                       | 40.0              | -10.5          | 2.00 H                   | 127                        | 44.1                   | -14.6                          |
| 2                                                   | 125.17         | 30.0 QP                       | 43.5              | -13.5          | 1.50 H                   | 294                        | 46.1                   | -16.1                          |
| 3                                                   | 199.05         | 35.7 QP                       | 43.5              | -7.8           | 1.50 H                   | 153                        | 52.2                   | -16.5                          |
| 4                                                   | 249.60         | 34.4 QP                       | 46.0              | -11.6          | 1.01 H                   | 264                        | 48.4                   | -14.0                          |
| 5                                                   | 500.42         | 30.0 QP                       | 46.0              | -16.0          | 1.50 H                   | 6                          | 37.9                   | -7.9                           |
| 6                                                   | 700.68         | 32.3 QP                       | 46.0              | -13.7          | 1.01 H                   | 147                        | 35.9                   | -3.6                           |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 45.45          | 35.5 QP                       | 40.0              | -4.5           | 1.00 V                   | 15                         | 50.2                   | -14.7                          |
| 2                                                   | 55.18          | 34.5 QP                       | 40.0              | -5.5           | 1.49 V                   | 10                         | 48.9                   | -14.4                          |
| 3                                                   | 199.05         | 32.3 QP                       | 43.5              | -11.2          | 1.00 V                   | 27                         | 48.8                   | -16.5                          |
| 4                                                   | 249.60         | 32.7 QP                       | 46.0              | -13.3          | 1.00 V                   | 234                        | 46.7                   | -14.0                          |
| 5                                                   | 374.04         | 31.0 QP                       | 46.0              | -15.0          | 1.49 V                   | 171                        | 41.5                   | -10.5                          |
| 6                                                   | 500.42         | 33.0 QP                       | 46.0              | -13.0          | 1.00 V                   | 259                        | 40.9                   | -7.9                           |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

## 4.2 Conducted Emission Measurement

### 4.2.1 Limits of Conducted Emission Measurement

| Frequency (MHz) | Conducted Limit (dBuV) |         |
|-----------------|------------------------|---------|
|                 | Quasi-peak             | Average |
| 0.15 - 0.5      | 66 - 56                | 56 - 46 |
| 0.50 - 5.0      | 56                     | 46      |
| 5.0 - 30.0      | 60                     | 50      |

**Note:** 1. The lower limit shall apply at the transition frequencies.  
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

### 4.2.2 Test Instruments

| Description & Manufacturer                  | Model No.                | Serial No.     | Cal. Date     | Cal. Due      |
|---------------------------------------------|--------------------------|----------------|---------------|---------------|
| Test Receiver<br>ROHDE & SCHWARZ            | ESCI                     | 100613         | Nov. 16, 2015 | Nov. 15, 2016 |
| RF signal cable (with 10dB PAD)<br>Woken    | 5D-FB                    | Cable-cond1-01 | Dec. 26, 2015 | Dec. 25, 2016 |
| LISN/AMN<br>ROHDE & SCHWARZ<br>(EUT)        | ESH3-Z5                  | 835239/001     | Feb. 26, 2016 | Feb. 25, 2017 |
| LISN/AMN<br>ROHDE & SCHWARZ<br>(Peripheral) | ESH3-Z5                  | 100220         | Nov. 13, 2015 | Nov. 12, 2016 |
| Software<br>ADT                             | BV ADT_Cond_<br>V7.3.7.3 | NA             | NA            | NA            |

**Note:** 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.  
2. The test was performed in HwaYa Shielded Room 1.  
3. The VCCI Site Registration No. is C-2040.

### 4.2.3 Test Procedures


- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

Note: The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.

### 4.2.4 Deviation from Test Standard

No deviation.

### 4.2.5 Test Setup



Note: 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

### 4.2.6 EUT Operating Conditions

Same as 4.1.6.

## 4.2.7 Test Results


### Radio 1: CDD Mode

| Phase     | Line (L) | Detector Function | Quasi-Peak (QP) / Average (AV) |
|-----------|----------|-------------------|--------------------------------|
| Test Mode | A        |                   |                                |

| No | Freq.<br>[MHz] | Corr.<br>Factor<br>(dB) | Reading Value |       | Emission Level |       | Limit     |       | Margin |        |
|----|----------------|-------------------------|---------------|-------|----------------|-------|-----------|-------|--------|--------|
|    |                |                         | [dB (uV)]     |       | [dB (uV)]      |       | [dB (uV)] |       | (dB)   |        |
|    |                |                         | Q.P.          | AV.   | Q.P.           | AV.   | Q.P.      | AV.   | Q.P.   | AV.    |
| 1  | 0.18128        | 10.08                   | 38.25         | 28.01 | 48.33          | 38.09 | 64.43     | 54.43 | -16.10 | -16.34 |
| 2  | 0.20865        | 10.08                   | 35.89         | 25.53 | 45.97          | 35.61 | 63.26     | 53.26 | -17.29 | -17.65 |
| 3  | 0.32204        | 10.13                   | 33.77         | 26.37 | 43.90          | 36.50 | 59.65     | 49.65 | -15.75 | -13.15 |
| 4  | 0.47453        | 10.18                   | 27.80         | 12.61 | 37.98          | 22.79 | 56.43     | 46.43 | -18.45 | -23.64 |
| 5  | 0.53318        | 10.20                   | 32.03         | 22.69 | 42.23          | 32.89 | 56.00     | 46.00 | -13.77 | -13.11 |
| 6  | 19.22298       | 11.36                   | 21.22         | 16.57 | 32.58          | 27.93 | 60.00     | 50.00 | -27.42 | -22.07 |

#### Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




|           |             |                   |                                |
|-----------|-------------|-------------------|--------------------------------|
| Phase     | Neutral (N) | Detector Function | Quasi-Peak (QP) / Average (AV) |
| Test Mode | A           |                   |                                |

| No | Freq.<br>[MHz] | Corr.<br>Factor<br>(dB) | Reading Value<br>[dB (uV)] |       | Emission Level<br>[dB (uV)] |       | Limit<br>[dB (uV)] |       | Margin<br>(dB) |        |
|----|----------------|-------------------------|----------------------------|-------|-----------------------------|-------|--------------------|-------|----------------|--------|
|    |                |                         |                            |       |                             |       |                    |       |                |        |
|    |                |                         | Q.P.                       | AV.   | Q.P.                        | AV.   | Q.P.               | AV.   | Q.P.           | AV.    |
| 1  | 0.17737        | 10.08                   | 38.21                      | 29.54 | 48.29                       | 39.62 | 64.61              | 54.61 | -16.32         | -14.99 |
| 2  | 0.22038        | 10.10                   | 35.48                      | 26.91 | 45.58                       | 37.01 | 62.80              | 52.80 | -17.22         | -15.79 |
| 3  | 0.29076        | 10.15                   | 23.28                      | 15.57 | 33.43                       | 25.72 | 60.50              | 50.50 | -27.07         | -24.78 |
| 4  | 0.31849        | 10.17                   | 33.45                      | 26.02 | 43.62                       | 36.19 | 59.75              | 49.75 | -16.13         | -13.56 |
| 5  | 0.51993        | 10.25                   | 34.95                      | 29.51 | 45.20                       | 39.76 | 56.00              | 46.00 | -10.80         | -6.24  |
| 6  | 15.04319       | 11.19                   | 21.68                      | 17.03 | 32.87                       | 28.22 | 60.00              | 50.00 | -27.13         | -21.78 |

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




|           |          |                   |                                |
|-----------|----------|-------------------|--------------------------------|
| Phase     | Line (L) | Detector Function | Quasi-Peak (QP) / Average (AV) |
| Test Mode | B        |                   |                                |

| No | Freq.<br>[MHz] | Corr.<br>Factor<br>(dB) | Reading Value<br>[dB (uV)] |       | Emission Level<br>[dB (uV)] |       | Limit<br>[dB (uV)] |       | Margin<br>(dB) |        |
|----|----------------|-------------------------|----------------------------|-------|-----------------------------|-------|--------------------|-------|----------------|--------|
|    |                |                         |                            |       |                             |       |                    |       |                |        |
|    |                |                         | Q.P.                       | AV.   | Q.P.                        | AV.   | Q.P.               | AV.   | Q.P.           | AV.    |
| 1  | 0.17744        | 10.08                   | 24.01                      | 17.09 | 34.09                       | 27.17 | 64.60              | 54.60 | -30.51         | -27.43 |
| 2  | 0.42761        | 10.18                   | 25.46                      | 20.81 | 35.64                       | 30.99 | 57.30              | 47.30 | -21.66         | -16.31 |
| 3  | 0.49799        | 10.19                   | 34.25                      | 28.62 | 44.44                       | 38.81 | 56.03              | 46.03 | -11.59         | -7.22  |
| 4  | 0.52544        | 10.20                   | 33.30                      | 27.30 | 43.50                       | 37.50 | 56.00              | 46.00 | -12.50         | -8.50  |
| 5  | 0.89290        | 10.27                   | 22.07                      | 12.76 | 32.34                       | 23.03 | 56.00              | 46.00 | -23.66         | -22.97 |
| 6  | 19.50450       | 11.38                   | 23.89                      | 18.06 | 35.27                       | 29.44 | 60.00              | 50.00 | -24.73         | -20.56 |

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




|           |             |                   |                                |
|-----------|-------------|-------------------|--------------------------------|
| Phase     | Neutral (N) | Detector Function | Quasi-Peak (QP) / Average (AV) |
| Test Mode | B           |                   |                                |

| No | Freq.<br>[MHz] | Corr.<br>Factor<br>(dB) | Reading Value<br>[dB (uV)] |       | Emission Level<br>[dB (uV)] |       | Limit<br>[dB (uV)] |       | Margin<br>(dB) |        |
|----|----------------|-------------------------|----------------------------|-------|-----------------------------|-------|--------------------|-------|----------------|--------|
|    |                |                         |                            |       |                             |       |                    |       |                |        |
|    |                |                         | Q.P.                       | AV.   | Q.P.                        | AV.   | Q.P.               | AV.   | Q.P.           | AV.    |
| 1  | 0.18075        | 10.08                   | 25.89                      | 17.22 | 35.97                       | 27.30 | 64.45              | 54.45 | -28.48         | -27.15 |
| 2  | 0.34926        | 10.20                   | 25.52                      | 17.11 | 35.72                       | 27.31 | 58.98              | 48.98 | -23.26         | -21.67 |
| 3  | 0.49064        | 10.25                   | 32.71                      | 26.74 | 42.96                       | 36.99 | 56.16              | 46.16 | -13.20         | -9.17  |
| 4  | 0.52544        | 10.25                   | 34.52                      | 28.26 | 44.77                       | 38.51 | 56.00              | 46.00 | -11.23         | -7.49  |
| 5  | 0.63856        | 10.26                   | 27.36                      | 18.50 | 37.62                       | 28.76 | 56.00              | 46.00 | -18.38         | -17.24 |
| 6  | 19.04312       | 11.50                   | 20.72                      | 14.40 | 32.22                       | 25.90 | 60.00              | 50.00 | -27.78         | -24.10 |

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




|           |          |                   |                                |
|-----------|----------|-------------------|--------------------------------|
| Phase     | Line (L) | Detector Function | Quasi-Peak (QP) / Average (AV) |
| Test Mode | C        |                   |                                |

| No | Freq.<br>[MHz] | Corr.<br>Factor<br>(dB) | Reading Value<br>[dB (uV)] |       | Emission Level<br>[dB (uV)] |       | Limit<br>[dB (uV)] |       | Margin<br>(dB) |        |
|----|----------------|-------------------------|----------------------------|-------|-----------------------------|-------|--------------------|-------|----------------|--------|
|    |                |                         |                            |       |                             |       |                    |       |                |        |
|    |                |                         | Q.P.                       | AV.   | Q.P.                        | AV.   | Q.P.               | AV.   | Q.P.           | AV.    |
| 1  | 0.15391        | 10.08                   | 38.81                      | 21.17 | 48.89                       | 31.25 | 65.79              | 55.79 | -16.90         | -24.54 |
| 2  | 0.18122        | 10.08                   | 36.05                      | 21.08 | 46.13                       | 31.16 | 64.43              | 54.43 | -18.30         | -23.27 |
| 3  | 0.29076        | 10.12                   | 35.23                      | 26.35 | 45.35                       | 36.47 | 60.50              | 50.50 | -15.15         | -14.03 |
| 4  | 0.32187        | 10.13                   | 31.28                      | 19.29 | 41.41                       | 29.42 | 59.66              | 49.66 | -18.25         | -20.24 |
| 5  | 0.51856        | 10.19                   | 32.35                      | 26.12 | 42.54                       | 36.31 | 56.00              | 46.00 | -13.46         | -9.69  |
| 6  | 15.86429       | 11.13                   | 21.77                      | 17.12 | 32.90                       | 28.25 | 60.00              | 50.00 | -27.10         | -21.75 |

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




|           |             |                   |                                |
|-----------|-------------|-------------------|--------------------------------|
| Phase     | Neutral (N) | Detector Function | Quasi-Peak (QP) / Average (AV) |
| Test Mode | C           |                   |                                |

| No | Freq.<br>[MHz] | Corr.<br>Factor<br>(dB) | Reading Value<br>[dB (uV)] |       | Emission Level<br>[dB (uV)] |       | Limit<br>[dB (uV)] |       | Margin<br>(dB) |        |
|----|----------------|-------------------------|----------------------------|-------|-----------------------------|-------|--------------------|-------|----------------|--------|
|    |                |                         |                            |       |                             |       |                    |       |                |        |
|    |                |                         | Q.P.                       | AV.   | Q.P.                        | AV.   | Q.P.               | AV.   | Q.P.           | AV.    |
| 1  | 0.15000        | 10.08                   | 33.96                      | 14.13 | 44.04                       | 24.21 | 66.00              | 56.00 | -21.96         | -31.79 |
| 2  | 0.18754        | 10.08                   | 29.72                      | 14.15 | 39.80                       | 24.23 | 64.14              | 54.14 | -24.34         | -29.91 |
| 3  | 0.22434        | 10.10                   | 34.32                      | 20.08 | 44.42                       | 30.18 | 62.66              | 52.66 | -18.24         | -22.48 |
| 4  | 0.29858        | 10.16                   | 29.78                      | 12.61 | 39.94                       | 22.77 | 60.28              | 50.28 | -20.34         | -27.51 |
| 5  | 0.53318        | 10.25                   | 30.97                      | 20.35 | 41.22                       | 30.60 | 56.00              | 46.00 | -14.78         | -15.40 |
| 6  | 18.01870       | 11.42                   | 20.18                      | 15.52 | 31.60                       | 26.94 | 60.00              | 50.00 | -28.40         | -23.06 |

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




|           |          |                   |                                |
|-----------|----------|-------------------|--------------------------------|
| Phase     | Line (L) | Detector Function | Quasi-Peak (QP) / Average (AV) |
| Test Mode | D        |                   |                                |

| No | Freq.<br>[MHz] | Corr.<br>Factor<br>(dB) | Reading Value<br>[dB (uV)] |       | Emission Level<br>[dB (uV)] |       | Limit<br>[dB (uV)] |       | Margin<br>(dB) |        |
|----|----------------|-------------------------|----------------------------|-------|-----------------------------|-------|--------------------|-------|----------------|--------|
|    |                |                         |                            |       |                             |       |                    |       |                |        |
|    |                |                         | Q.P.                       | AV.   | Q.P.                        | AV.   | Q.P.               | AV.   | Q.P.           | AV.    |
| 1  | 0.16181        | 10.08                   | 25.31                      | 16.44 | 35.39                       | 26.52 | 65.37              | 55.37 | -29.98         | -28.85 |
| 2  | 0.50000        | 10.19                   | 33.58                      | 26.81 | 43.77                       | 37.00 | 56.00              | 46.00 | -12.23         | -9.00  |
| 3  | 0.52544        | 10.20                   | 33.16                      | 26.57 | 43.36                       | 36.77 | 56.00              | 46.00 | -12.64         | -9.23  |
| 4  | 1.02975        | 10.29                   | 21.98                      | 15.03 | 32.27                       | 25.32 | 56.00              | 46.00 | -23.73         | -20.68 |
| 5  | 1.32300        | 10.32                   | 21.27                      | 13.61 | 31.59                       | 23.93 | 56.00              | 46.00 | -24.41         | -22.07 |
| 6  | 20.16529       | 11.43                   | 22.76                      | 17.19 | 34.19                       | 28.62 | 60.00              | 50.00 | -25.81         | -21.38 |

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




|           |             |                   |                                |
|-----------|-------------|-------------------|--------------------------------|
| Phase     | Neutral (N) | Detector Function | Quasi-Peak (QP) / Average (AV) |
| Test Mode | D           |                   |                                |

| No | Freq.<br>[MHz] | Corr.<br>Factor<br>(dB) | Reading Value<br>[dB (uV)] |       | Emission Level<br>[dB (uV)] |       | Limit<br>[dB (uV)] |       | Margin<br>(dB) |        |
|----|----------------|-------------------------|----------------------------|-------|-----------------------------|-------|--------------------|-------|----------------|--------|
|    |                |                         |                            |       |                             |       |                    |       |                |        |
|    |                |                         | Q.P.                       | AV.   | Q.P.                        | AV.   | Q.P.               | AV.   | Q.P.           | AV.    |
| 1  | 0.16955        | 10.08                   | 25.65                      | 17.89 | 35.73                       | 27.97 | 64.98              | 54.98 | -29.25         | -27.01 |
| 2  | 0.30939        | 10.17                   | 21.96                      | 9.81  | 32.13                       | 19.98 | 59.99              | 49.99 | -27.86         | -30.01 |
| 3  | 0.52130        | 10.25                   | 34.15                      | 24.92 | 44.40                       | 35.17 | 56.00              | 46.00 | -11.60         | -10.83 |
| 4  | 0.61543        | 10.26                   | 25.25                      | 14.15 | 35.51                       | 24.41 | 56.00              | 46.00 | -20.49         | -21.59 |
| 5  | 0.91636        | 10.28                   | 23.40                      | 15.37 | 33.68                       | 25.65 | 56.00              | 46.00 | -22.32         | -20.35 |
| 6  | 19.78602       | 11.56                   | 20.76                      | 15.06 | 32.32                       | 26.62 | 60.00              | 50.00 | -27.68         | -23.38 |

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




### Radio 3: CDD Mode

| Phase     | Line (L) | Detector Function | Quasi-Peak (QP) / Average (AV) |
|-----------|----------|-------------------|--------------------------------|
| Test Mode | A        |                   |                                |

| No | Freq.<br>[MHz] | Corr.<br>Factor<br>(dB) | Reading Value |              | Emission Level |              | Limit        |              | Margin        |              |
|----|----------------|-------------------------|---------------|--------------|----------------|--------------|--------------|--------------|---------------|--------------|
|    |                |                         | [dB (uV)]     |              | [dB (uV)]      |              | [dB (uV)]    |              | (dB)          |              |
|    |                |                         | Q.P.          | AV.          | Q.P.           | AV.          | Q.P.         | AV.          | Q.P.          | AV.          |
| 1  | 0.17737        | 10.08                   | 35.86         | 25.89        | 45.94          | 35.97        | 64.61        | 54.61        | -18.67        | -18.64       |
| 2  | 0.24025        | 10.10                   | 32.16         | 24.37        | 42.26          | 34.47        | 62.09        | 52.09        | -19.83        | -17.62       |
| 3  | 0.32204        | 10.13                   | 33.78         | 25.35        | 43.91          | 35.48        | 59.65        | 49.65        | -15.74        | -14.17       |
| 4  | 0.46301        | 10.18                   | 28.40         | 16.71        | 38.58          | 26.89        | 56.64        | 46.64        | -18.06        | -19.75       |
| 5  | <b>0.52130</b> | <b>10.19</b>            | <b>34.71</b>  | <b>30.25</b> | <b>44.90</b>   | <b>40.44</b> | <b>56.00</b> | <b>46.00</b> | <b>-11.10</b> | <b>-5.56</b> |
| 6  | 19.47713       | 11.38                   | 21.25         | 16.64        | 32.63          | 28.02        | 60.00        | 50.00        | -27.37        | -21.98       |

#### Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




|           |             |                   |                                |
|-----------|-------------|-------------------|--------------------------------|
| Phase     | Neutral (N) | Detector Function | Quasi-Peak (QP) / Average (AV) |
| Test Mode | A           |                   |                                |

| No | Freq.<br>[MHz] | Corr.<br>Factor<br>(dB) | Reading Value<br>[dB (uV)] |       | Emission Level<br>[dB (uV)] |       | Limit<br>[dB (uV)] |       | Margin<br>(dB) |        |
|----|----------------|-------------------------|----------------------------|-------|-----------------------------|-------|--------------------|-------|----------------|--------|
|    |                |                         |                            |       |                             |       |                    |       |                |        |
|    |                |                         | Q.P.                       | AV.   | Q.P.                        | AV.   | Q.P.               | AV.   | Q.P.           | AV.    |
| 1  | 0.15391        | 10.08                   | 26.14                      | 11.22 | 36.22                       | 21.30 | 65.79              | 55.79 | -29.57         | -34.49 |
| 2  | 0.22429        | 10.10                   | 21.34                      | 16.76 | 31.44                       | 26.86 | 62.66              | 52.66 | -31.22         | -25.80 |
| 3  | 0.33750        | 10.19                   | 29.01                      | 14.10 | 39.20                       | 24.29 | 59.26              | 49.26 | -20.06         | -24.97 |
| 4  | 0.47537        | 10.25                   | 32.73                      | 26.35 | 42.98                       | 36.60 | 56.42              | 46.42 | -13.44         | -9.82  |
| 5  | 0.51312        | 10.25                   | 34.51                      | 25.36 | 44.76                       | 35.61 | 56.00              | 46.00 | -11.24         | -10.39 |
| 6  | 14.58963       | 11.16                   | 21.72                      | 17.00 | 32.88                       | 28.16 | 60.00              | 50.00 | -27.12         | -21.84 |

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




|           |          |                   |                                |
|-----------|----------|-------------------|--------------------------------|
| Phase     | Line (L) | Detector Function | Quasi-Peak (QP) / Average (AV) |
| Test Mode | B        |                   |                                |

| No | Freq.<br>[MHz] | Corr.<br>Factor<br>(dB) | Reading Value<br>[dB (uV)] |       | Emission Level<br>[dB (uV)] |       | Limit<br>[dB (uV)] |       | Margin<br>(dB) |        |
|----|----------------|-------------------------|----------------------------|-------|-----------------------------|-------|--------------------|-------|----------------|--------|
|    |                |                         |                            |       |                             |       |                    |       |                |        |
|    |                |                         | Q.P.                       | AV.   | Q.P.                        | AV.   | Q.P.               | AV.   | Q.P.           | AV.    |
| 1  | 0.17698        | 10.08                   | 24.00                      | 17.20 | 34.08                       | 27.28 | 64.63              | 54.63 | -30.55         | -27.35 |
| 2  | 0.50000        | 10.19                   | 34.15                      | 27.60 | 44.34                       | 37.79 | 56.00              | 46.00 | -11.66         | -8.21  |
| 3  | 0.52536        | 10.20                   | 33.45                      | 26.77 | 43.65                       | 36.97 | 56.00              | 46.00 | -12.35         | -9.03  |
| 4  | 0.63484        | 10.22                   | 24.03                      | 16.16 | 34.25                       | 26.38 | 56.00              | 46.00 | -21.75         | -19.62 |
| 5  | 1.01799        | 10.29                   | 21.83                      | 13.10 | 32.12                       | 23.39 | 56.00              | 46.00 | -23.88         | -22.61 |
| 6  | 19.84467       | 11.41                   | 24.42                      | 18.68 | 35.83                       | 30.09 | 60.00              | 50.00 | -24.17         | -19.91 |

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




|           |             |                   |                                |
|-----------|-------------|-------------------|--------------------------------|
| Phase     | Neutral (N) | Detector Function | Quasi-Peak (QP) / Average (AV) |
| Test Mode | B           |                   |                                |

| No | Freq.<br>[MHz] | Corr.<br>Factor<br>(dB) | Reading Value<br>[dB (uV)] |       | Emission Level<br>[dB (uV)] |       | Limit<br>[dB (uV)] |       | Margin<br>(dB) |        |
|----|----------------|-------------------------|----------------------------|-------|-----------------------------|-------|--------------------|-------|----------------|--------|
|    |                |                         |                            |       |                             |       |                    |       |                |        |
|    |                |                         | Q.P.                       | AV.   | Q.P.                        | AV.   | Q.P.               | AV.   | Q.P.           | AV.    |
| 1  | 0.17374        | 10.08                   | 27.67                      | 21.54 | 37.75                       | 31.62 | 64.78              | 54.78 | -27.03         | -23.16 |
| 2  | 0.43152        | 10.24                   | 27.68                      | 21.42 | 37.92                       | 31.66 | 57.22              | 47.22 | -19.30         | -15.56 |
| 3  | 0.49017        | 10.25                   | 32.34                      | 26.03 | 42.59                       | 36.28 | 56.16              | 46.16 | -13.57         | -9.88  |
| 4  | 0.53240        | 10.25                   | 33.02                      | 26.75 | 43.27                       | 37.00 | 56.00              | 46.00 | -12.73         | -9.00  |
| 5  | 0.63093        | 10.26                   | 27.45                      | 20.58 | 37.71                       | 30.84 | 56.00              | 46.00 | -18.29         | -15.16 |
| 6  | 19.17997       | 11.52                   | 20.54                      | 14.33 | 32.06                       | 25.85 | 60.00              | 50.00 | -27.94         | -24.15 |

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




|           |          |                   |                                |
|-----------|----------|-------------------|--------------------------------|
| Phase     | Line (L) | Detector Function | Quasi-Peak (QP) / Average (AV) |
| Test Mode | C        |                   |                                |

| No | Freq.<br>[MHz] | Corr.<br>Factor<br>(dB) | Reading Value<br>[dB (uV)] |       | Emission Level<br>[dB (uV)] |       | Limit<br>[dB (uV)] |       | Margin<br>(dB) |        |
|----|----------------|-------------------------|----------------------------|-------|-----------------------------|-------|--------------------|-------|----------------|--------|
|    |                |                         |                            |       |                             |       |                    |       |                |        |
|    |                |                         | Q.P.                       | AV.   | Q.P.                        | AV.   | Q.P.               | AV.   | Q.P.           | AV.    |
| 1  | 0.17346        | 10.08                   | 38.35                      | 29.85 | 48.43                       | 39.93 | 64.79              | 54.79 | -16.36         | -14.86 |
| 2  | 0.20084        | 10.08                   | 34.52                      | 21.52 | 44.60                       | 31.60 | 63.58              | 53.58 | -18.98         | -21.98 |
| 3  | 0.31031        | 10.13                   | 34.90                      | 28.54 | 45.03                       | 38.67 | 59.96              | 49.96 | -14.93         | -11.29 |
| 4  | 0.34159        | 10.14                   | 31.76                      | 23.60 | 41.90                       | 33.74 | 59.16              | 49.16 | -17.26         | -15.42 |
| 5  | 0.52821        | 10.20                   | 32.77                      | 20.68 | 42.97                       | 30.88 | 56.00              | 46.00 | -13.03         | -15.12 |
| 6  | 15.49284       | 11.10                   | 21.33                      | 16.61 | 32.43                       | 27.71 | 60.00              | 50.00 | -27.57         | -22.29 |

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




|           |             |                   |                                |
|-----------|-------------|-------------------|--------------------------------|
| Phase     | Neutral (N) | Detector Function | Quasi-Peak (QP) / Average (AV) |
| Test Mode | C           |                   |                                |

| No | Freq.<br>[MHz] | Corr.<br>Factor<br>(dB) | Reading Value<br>[dB (uV)] |       | Emission Level<br>[dB (uV)] |       | Limit<br>[dB (uV)] |       | Margin<br>(dB) |        |
|----|----------------|-------------------------|----------------------------|-------|-----------------------------|-------|--------------------|-------|----------------|--------|
|    |                |                         |                            |       |                             |       |                    |       |                |        |
|    |                |                         | Q.P.                       | AV.   | Q.P.                        | AV.   | Q.P.               | AV.   | Q.P.           | AV.    |
| 1  | 0.16955        | 10.08                   | 39.03                      | 28.80 | 49.11                       | 38.88 | 64.98              | 54.98 | -15.87         | -16.10 |
| 2  | 0.20865        | 10.09                   | 34.91                      | 22.12 | 45.00                       | 32.21 | 63.26              | 53.26 | -18.26         | -21.05 |
| 3  | 0.23602        | 10.11                   | 32.63                      | 22.23 | 42.74                       | 32.34 | 62.24              | 52.24 | -19.50         | -19.90 |
| 4  | 0.31813        | 10.17                   | 30.19                      | 17.30 | 40.36                       | 27.47 | 59.76              | 49.76 | -19.40         | -22.29 |
| 5  | 0.52544        | 10.25                   | 32.83                      | 23.23 | 43.08                       | 33.48 | 56.00              | 46.00 | -12.92         | -12.52 |
| 6  | 19.04703       | 11.50                   | 19.71                      | 15.13 | 31.21                       | 26.63 | 60.00              | 50.00 | -28.79         | -23.37 |

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




|           |          |                   |                                |
|-----------|----------|-------------------|--------------------------------|
| Phase     | Line (L) | Detector Function | Quasi-Peak (QP) / Average (AV) |
| Test Mode | D        |                   |                                |

| No | Freq.<br>[MHz] | Corr.<br>Factor<br>(dB) | Reading Value<br>[dB (uV)] |       | Emission Level<br>[dB (uV)] |       | Limit<br>[dB (uV)] |       | Margin<br>(dB) |        |
|----|----------------|-------------------------|----------------------------|-------|-----------------------------|-------|--------------------|-------|----------------|--------|
|    |                |                         |                            |       |                             |       |                    |       |                |        |
|    |                |                         | Q.P.                       | AV.   | Q.P.                        | AV.   | Q.P.               | AV.   | Q.P.           | AV.    |
| 1  | 0.15000        | 10.07                   | 23.66                      | 8.67  | 33.73                       | 18.74 | 66.00              | 56.00 | -32.27         | -37.26 |
| 2  | 0.34108        | 10.14                   | 20.08                      | 10.09 | 30.22                       | 20.23 | 59.18              | 49.18 | -28.96         | -28.95 |
| 3  | 0.50000        | 10.19                   | 34.13                      | 26.90 | 44.32                       | 37.09 | 56.00              | 46.00 | -11.68         | -8.91  |
| 4  | 0.52927        | 10.20                   | 32.70                      | 26.82 | 42.90                       | 37.02 | 56.00              | 46.00 | -13.10         | -8.98  |
| 5  | 0.59627        | 10.21                   | 24.05                      | 16.11 | 34.26                       | 26.32 | 56.00              | 46.00 | -21.74         | -19.68 |
| 6  | 19.90723       | 11.41                   | 21.77                      | 16.15 | 33.18                       | 27.56 | 60.00              | 50.00 | -26.82         | -22.44 |

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




|           |             |                   |                                |
|-----------|-------------|-------------------|--------------------------------|
| Phase     | Neutral (N) | Detector Function | Quasi-Peak (QP) / Average (AV) |
| Test Mode | D           |                   |                                |

| No | Freq.<br>[MHz] | Corr.<br>Factor<br>(dB) | Reading Value<br>[dB (uV)] |       | Emission Level<br>[dB (uV)] |       | Limit<br>[dB (uV)] |       | Margin<br>(dB) |        |
|----|----------------|-------------------------|----------------------------|-------|-----------------------------|-------|--------------------|-------|----------------|--------|
|    |                |                         |                            |       |                             |       |                    |       |                |        |
|    |                |                         | Q.P.                       | AV.   | Q.P.                        | AV.   | Q.P.               | AV.   | Q.P.           | AV.    |
| 1  | 0.16569        | 10.08                   | 27.94                      | 21.87 | 38.02                       | 31.95 | 65.17              | 55.17 | -27.15         | -23.22 |
| 2  | 0.48935        | 10.25                   | 32.43                      | 25.44 | 42.68                       | 35.69 | 56.18              | 46.18 | -13.50         | -10.49 |
| 3  | 0.52544        | 10.25                   | 34.47                      | 28.05 | 44.72                       | 38.30 | 56.00              | 46.00 | -11.28         | -7.70  |
| 4  | 0.64266        | 10.26                   | 26.75                      | 15.70 | 37.01                       | 25.96 | 56.00              | 46.00 | -18.99         | -20.04 |
| 5  | 0.87335        | 10.28                   | 25.93                      | 18.46 | 36.21                       | 28.74 | 56.00              | 46.00 | -19.79         | -17.26 |
| 6  | 20.32560       | 11.60                   | 20.75                      | 15.17 | 32.35                       | 26.77 | 60.00              | 50.00 | -27.65         | -23.23 |

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




### 4.3 6dB Bandwidth Measurement

#### 4.3.1 Limits of 6dB Bandwidth Measurement

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

#### 4.3.2 Test Setup



#### 4.3.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

#### 4.3.4 Test Procedure

- Set resolution bandwidth (RBW) = 100kHz
- Set the video bandwidth (VBW)  $\geq 3 \times$  RBW, Detector = average.
- Trace mode = max hold.
- Sweep = auto couple.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

#### 4.3.5 Deviation from Test Standard

No deviation.

#### 4.3.6 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

#### 4.3.7 Test Result

Radio1: CDD Mode

##### 802.11b

| Channel | Frequency (MHz) | 6dB Bandwidth (MHz) |         |         |         | Minimum Limit (MHz) | Pass / Fail |
|---------|-----------------|---------------------|---------|---------|---------|---------------------|-------------|
|         |                 | Chain 0             | Chain 1 | Chain 2 | Chain 3 |                     |             |
| 1       | 2412            | 8.11                | 8.11    | 8.08    | 8.12    | 0.5                 | Pass        |
| 6       | 2437            | 8.11                | 8.11    | 8.09    | 8.07    | 0.5                 | Pass        |
| 11      | 2462            | 8.11                | 6.60    | 7.12    | 8.10    | 0.5                 | Pass        |

##### 802.11g

| Channel | Frequency (MHz) | 6dB Bandwidth (MHz) |         |         |         | Minimum Limit (MHz) | Pass / Fail |
|---------|-----------------|---------------------|---------|---------|---------|---------------------|-------------|
|         |                 | Chain 0             | Chain 1 | Chain 2 | Chain 3 |                     |             |
| 1       | 2412            | 16.37               | 16.31   | 16.39   | 16.39   | 0.5                 | Pass        |
| 6       | 2437            | 16.36               | 15.68   | 16.34   | 16.40   | 0.5                 | Pass        |
| 11      | 2462            | 16.38               | 15.29   | 15.77   | 16.39   | 0.5                 | Pass        |

##### 802.11n (HT20)


| Channel | Frequency (MHz) | 6dB Bandwidth (MHz) |         |         |         | Minimum Limit (MHz) | Pass / Fail |
|---------|-----------------|---------------------|---------|---------|---------|---------------------|-------------|
|         |                 | Chain 0             | Chain 1 | Chain 2 | Chain 3 |                     |             |
| 1       | 2412            | 17.60               | 16.33   | 17.21   | 17.62   | 0.5                 | Pass        |
| 6       | 2437            | 17.60               | 15.59   | 17.18   | 17.62   | 0.5                 | Pass        |
| 11      | 2462            | 17.57               | 15.95   | 16.92   | 17.61   | 0.5                 | Pass        |

##### 802.11n (HT40)


| Channel | Frequency (MHz) | 6dB Bandwidth (MHz) |         |         |         | Minimum Limit (MHz) | Pass / Fail |
|---------|-----------------|---------------------|---------|---------|---------|---------------------|-------------|
|         |                 | Chain 0             | Chain 1 | Chain 2 | Chain 3 |                     |             |
| 3       | 2422            | 35.89               | 35.83   | 35.87   | 35.83   | 0.5                 | Pass        |
| 6       | 2437            | 35.80               | 35.81   | 35.77   | 35.29   | 0.5                 | Pass        |
| 9       | 2452            | 35.81               | 35.82   | 35.78   | 35.24   | 0.5                 | Pass        |

## Spectrum Plot of Worst Value


### 802.11b




### 802.11g



### 802.11n (HT20)



### 802.11n (HT40)



Radio3: CDD Mode

802.11b

| Channel | Frequency (MHz) | 6dB Bandwidth (MHz) | Minimum Limit (MHz) | Pass / Fail |
|---------|-----------------|---------------------|---------------------|-------------|
| 1       | 2412            | 6.13                | 0.5                 | Pass        |
| 6       | 2437            | 6.14                | 0.5                 | Pass        |
| 11      | 2462            | 6.08                | 0.5                 | Pass        |

802.11g

| Channel | Frequency (MHz) | 6dB Bandwidth (MHz) | Minimum Limit (MHz) | Pass / Fail |
|---------|-----------------|---------------------|---------------------|-------------|
| 1       | 2412            | 16.31               | 0.5                 | Pass        |
| 6       | 2437            | 16.08               | 0.5                 | Pass        |
| 11      | 2462            | 16.09               | 0.5                 | Pass        |

802.11n (HT20)


| Channel | Frequency (MHz) | 6dB Bandwidth (MHz) | Minimum Limit (MHz) | Pass / Fail |
|---------|-----------------|---------------------|---------------------|-------------|
| 1       | 2412            | 16.90               | 0.5                 | Pass        |
| 6       | 2437            | 16.86               | 0.5                 | Pass        |
| 11      | 2462            | 16.85               | 0.5                 | Pass        |

802.11n (HT40)


| Channel | Frequency (MHz) | 6dB Bandwidth (MHz) | Minimum Limit (MHz) | Pass / Fail |
|---------|-----------------|---------------------|---------------------|-------------|
| 3       | 2422            | 35.35               | 0.5                 | Pass        |
| 6       | 2437            | 35.28               | 0.5                 | Pass        |
| 9       | 2452            | 35.27               | 0.5                 | Pass        |

## Spectrum Plot of Worst Value


### 802.11b




### 802.11g



### 802.11n (HT20)



### 802.11n (HT40)



## 4.4 Conducted Output Power Measurement

### 4.4.1 Limits of Conducted Output Power Measurement

For systems using digital modulation in the 2400–2483.5 MHz bands: 1 Watt (30dBm)

Per KDB 662911 D01 Multiple Transmitter Output Method of conducted output power measurement on IEEE 802.11 devices,


Array Gain = 0 dB (i.e., no array gain) for  $NANT \leq 4$ ;

Array Gain = 0 dB (i.e., no array gain) for channel widths  $\geq 40$  MHz for any NANT;

Array Gain =  $5 \log(NANT/NSS)$  dB or 3 dB, whichever is less for 20-MHz channel widths with  $NANT \geq 5$ .

For power measurements on all other devices: Array Gain =  $10 \log(NANT/NSS)$  dB.

### 4.4.2 Test Setup



### 4.4.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

### 4.4.4 Test Procedures

An average power sensor was used on the output port of the EUT. A power meter was used to read the response of the average power sensor. Record the power level.

### 4.4.5 Deviation from Test Standard

No deviation.

### 4.4.6 EUT Operating Conditions

Same as Item 4.3.6.

#### 4.4.7 Test Results

Radio 1: CDD Mode

802.11b

| Channel | Frequency (MHz) | Average Power (dBm) |         |         |         | Total Power (mW) | Total Power (dBm) | Limit (dBm) | Pass / Fail |
|---------|-----------------|---------------------|---------|---------|---------|------------------|-------------------|-------------|-------------|
|         |                 | Chain 0             | Chain 1 | Chain 2 | Chain 3 |                  |                   |             |             |
| 1       | 2412            | 18.58               | 19.46   | 19.12   | 18.65   | <b>315.359</b>   | 24.99             | 30          | Pass        |
| 6       | 2437            | 18.73               | 19.39   | 18.40   | 18.61   | 303.335          | 24.82             | 30          | Pass        |
| 11      | 2462            | 16.11               | 16.83   | 15.84   | 15.96   | 166.844          | 22.22             | 30          | Pass        |

802.11g

| Channel | Frequency (MHz) | Average Power (dBm) |         |         |         | Total Power (mW) | Total Power (dBm) | Limit (dBm) | Pass / Fail |
|---------|-----------------|---------------------|---------|---------|---------|------------------|-------------------|-------------|-------------|
|         |                 | Chain 0             | Chain 1 | Chain 2 | Chain 3 |                  |                   |             |             |
| 1       | 2412            | 15.03               | 14.90   | 14.80   | 14.91   | 123.919          | 20.93             | 30          | Pass        |
| 6       | 2437            | 18.85               | 19.05   | 18.38   | 18.55   | 297.568          | 24.74             | 30          | Pass        |
| 11      | 2462            | 13.26               | 13.65   | 13.11   | 13.12   | 85.334           | 19.31             | 30          | Pass        |

802.11n (HT20)

| Channel | Frequency (MHz) | Average Power (dBm) |         |         |         | Total Power (mW) | Total Power (dBm) | Limit (dBm) | Pass / Fail |
|---------|-----------------|---------------------|---------|---------|---------|------------------|-------------------|-------------|-------------|
|         |                 | Chain 0             | Chain 1 | Chain 2 | Chain 3 |                  |                   |             |             |
| 1       | 2412            | 15.06               | 15.10   | 14.92   | 14.96   | 126.801          | 21.03             | 30          | Pass        |
| 6       | 2437            | 18.82               | 18.98   | 18.66   | 18.59   | 301.004          | 24.79             | 30          | Pass        |
| 11      | 2462            | 13.25               | 13.54   | 13.29   | 13.28   | 86.340           | 19.36             | 30          | Pass        |

802.11n (HT40)

| Channel | Frequency (MHz) | Average Power (dBm) |         |         |         | Total Power (mW) | Total Power (dBm) | Limit (dBm) | Pass / Fail |
|---------|-----------------|---------------------|---------|---------|---------|------------------|-------------------|-------------|-------------|
|         |                 | Chain 0             | Chain 1 | Chain 2 | Chain 3 |                  |                   |             |             |
| 3       | 2422            | 11.79               | 11.63   | 11.35   | 11.21   | 56.515           | 17.52             | 30          | Pass        |
| 6       | 2437            | 13.67               | 13.67   | 13.45   | 13.34   | 90.270           | 19.56             | 30          | Pass        |
| 9       | 2452            | 11.10               | 11.00   | 10.89   | 10.72   | 49.548           | 16.95             | 30          | Pass        |

## Radio 1: Beamforming Mode

### 802.11n (HT20)

| Channel | Frequency (MHz) | Average Power (dBm) |         |         |         | Total Power (mW) | Total Power (dBm) | Limit (dBm) | Pass / Fail |
|---------|-----------------|---------------------|---------|---------|---------|------------------|-------------------|-------------|-------------|
|         |                 | Chain 0             | Chain 1 | Chain 2 | Chain 3 |                  |                   |             |             |
| 1       | 2412            | 9.04                | 9.08    | 8.90    | 8.94    | 31.704           | 15.01             | 25.32       | Pass        |
| 6       | 2437            | 12.80               | 12.96   | 12.64   | 12.57   | <b>75.262</b>    | 18.77             | 25.32       | Pass        |
| 11      | 2462            | 7.23                | 7.52    | 7.27    | 7.26    | 21.587           | 13.34             | 25.32       | Pass        |

Note: Directional gain = 4.66dBi + 10log(4) = 10.68dBi > 6dBi, so the power limit shall be reduced to 30-(10.68-6) = 25.32dBm.

### 802.11n (HT40)

| Channel | Frequency (MHz) | Average Power (dBm) |         |         |         | Total Power (mW) | Total Power (dBm) | Limit (dBm) | Pass / Fail |
|---------|-----------------|---------------------|---------|---------|---------|------------------|-------------------|-------------|-------------|
|         |                 | Chain 0             | Chain 1 | Chain 2 | Chain 3 |                  |                   |             |             |
| 3       | 2422            | 5.77                | 5.61    | 5.33    | 5.19    | 14.131           | 11.50             | 25.32       | Pass        |
| 6       | 2437            | 7.65                | 7.65    | 7.43    | 7.32    | 22.571           | 13.54             | 25.32       | Pass        |
| 9       | 2452            | 5.08                | 4.98    | 4.87    | 4.70    | 12.389           | 10.93             | 25.32       | Pass        |

Note: Directional gain = 4.66dBi + 10log(4) = 10.68dBi > 6dBi, so the power limit shall be reduced to 30-(10.68-6) = 25.32dBm.

### Radio 3: CDD Mode

#### 802.11b

| Channel | Frequency (MHz) | Average Power (mW) | Average Power (dBm) | Limit (dBm) | Pass / Fail |
|---------|-----------------|--------------------|---------------------|-------------|-------------|
| 1       | 2412            | 6.281              | 7.98                | 30          | Pass        |
| 6       | 2437            | 6.427              | 8.08                | 30          | Pass        |
| 11      | 2462            | 5.768              | 7.61                | 30          | Pass        |

#### 802.11g

| Channel | Frequency (MHz) | Average Power (mW) | Average Power (dBm) | Limit (dBm) | Pass / Fail |
|---------|-----------------|--------------------|---------------------|-------------|-------------|
| 1       | 2412            | 8.299              | 9.19                | 30          | Pass        |
| 6       | 2437            | 17.865             | 12.52               | 30          | Pass        |
| 11      | 2462            | 7.031              | 8.47                | 30          | Pass        |

#### 802.11n (HT20)

| Channel | Frequency (MHz) | Average Power (mW) | Average Power (dBm) | Limit (dBm) | Pass / Fail |
|---------|-----------------|--------------------|---------------------|-------------|-------------|
| 1       | 2412            | 6.577              | 8.18                | 30          | Pass        |
| 6       | 2437            | <b>20.091</b>      | 13.03               | 30          | Pass        |
| 11      | 2462            | 5.929              | 7.73                | 30          | Pass        |

#### 802.11n (HT40)


| Channel | Frequency (MHz) | Average Power (mW) | Average Power (dBm) | Limit (dBm) | Pass / Fail |
|---------|-----------------|--------------------|---------------------|-------------|-------------|
| 3       | 2422            | 3.062              | 4.86                | 30          | Pass        |
| 6       | 2437            | 7.638              | 8.83                | 30          | Pass        |
| 9       | 2452            | 2.812              | 4.49                | 30          | Pass        |

## 4.5 Power Spectral Density Measurement

### 4.5.1 Limits of Power Spectral Density Measurement

The Maximum of Power Spectral Density Measurement is 8dBm.

### 4.5.2 Test Setup



### 4.5.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

### 4.5.4 Test Procedure

Duty cycle  $\geq 98\%$

- Set instrument center frequency to DTS channel center frequency.
- Set span to at least 1.5 times the OBW.
- Set RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
- Set VBW  $\geq 3 \times \text{RBW}$ .
- Detector = power averaging (RMS) or sample detector (when RMS not available).
- Ensure that the number of measurement points in the sweep  $\geq 2 \times \text{span/RBW}$ .
- Sweep time = auto couple.
- Employ trace averaging (RMS) mode over a minimum of 100 traces.
- Use the peak marker function to determine the maximum amplitude level.

Duty cycle  $< 98\%$

- Measure the duty cycle (x).
- Set instrument center frequency to DTS channel center frequency.
- Set span to at least 1.5 times the OBW.
- Set RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
- Set VBW  $\geq 3 \times \text{RBW}$ .
- Detector = power averaging (RMS) or sample detector (when RMS not available).
- Ensure that the number of measurement points in the sweep  $\geq 2 \times \text{span/RBW}$ .
- Sweep time = auto couple.
- Do not use sweep triggering. Allow sweep to "free run".
- Employ trace averaging (RMS) mode over a minimum of 100 traces.
- Use the peak marker function to determine the maximum amplitude level.
- Add  $10 \log (1/x)$ , where x is the duty cycle measured in step (a), to the measured PSD to compute the average PSD during the actual transmission time.

#### **4.5.5 Deviation from Test Standard**

No deviation.

#### **4.5.6 EUT Operating Condition**

Same as Item 4.3.6

#### 4.5.7 Test Results

Radio 1: CDD Mode

802.11b

| TX chain | Channel | Frequency (MHz) | PSD (dBm/3kHz) | 10 log (N=4) dB | Total PSD (dBm/3kHz) | Limit (dBm/3kHz) | Pass / Fail |
|----------|---------|-----------------|----------------|-----------------|----------------------|------------------|-------------|
| 0        | 1       | 2412            | -14.11         | 6.02            | -8.09                | 3.32             | Pass        |
|          | 6       | 2437            | -13.72         | 6.02            | -7.70                | 3.32             | Pass        |
|          | 11      | 2462            | -16.60         | 6.02            | -10.58               | 3.32             | Pass        |
| 1        | 1       | 2412            | -14.81         | 6.02            | -8.79                | 3.32             | Pass        |
|          | 6       | 2437            | -14.23         | 6.02            | -8.21                | 3.32             | Pass        |
|          | 11      | 2462            | -15.31         | 6.02            | -9.29                | 3.32             | Pass        |
| 2        | 1       | 2412            | -13.05         | 6.02            | -7.03                | 3.32             | Pass        |
|          | 6       | 2437            | -13.59         | 6.02            | -7.57                | 3.32             | Pass        |
|          | 11      | 2462            | -15.80         | 6.02            | -9.78                | 3.32             | Pass        |
| 3        | 1       | 2412            | -14.12         | 6.02            | -8.10                | 3.32             | Pass        |
|          | 6       | 2437            | -14.50         | 6.02            | -8.48                | 3.32             | Pass        |
|          | 11      | 2462            | -16.54         | 6.02            | -10.52               | 3.32             | Pass        |

Note:

1. Method 1 of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
2. Directional gain =  $4.66\text{dBi} + 10\log(4) = 10.68\text{dBi} > 6\text{dBi}$ , so the power density limit shall be reduced to  $8 - (10.68 - 6) = 3.32\text{dBm}$

### 802.11g

| TX chain | Channel | Freq. (MHz) | PSD w/o Duty Factor (dBm/3kHz) | 10 log (N=4) dB | Duty Factor (dB) | Total PSD With Duty Factor (dBm/3kHz) | Limit (dBm/3kHz) | Pass / Fail |
|----------|---------|-------------|--------------------------------|-----------------|------------------|---------------------------------------|------------------|-------------|
| 0        | 1       | 2412        | -21.54                         | 6.02            | 0.19             | -15.33                                | 3.32             | Pass        |
|          | 6       | 2437        | -17.77                         | 6.02            | 0.19             | -11.56                                | 3.32             | Pass        |
|          | 11      | 2462        | -23.13                         | 6.02            | 0.19             | -16.92                                | 3.32             | Pass        |
| 1        | 1       | 2412        | -21.55                         | 6.02            | 0.19             | -15.34                                | 3.32             | Pass        |
|          | 6       | 2437        | -16.77                         | 6.02            | 0.19             | -10.56                                | 3.32             | Pass        |
|          | 11      | 2462        | -22.02                         | 6.02            | 0.19             | -15.81                                | 3.32             | Pass        |
| 2        | 1       | 2412        | -22.06                         | 6.02            | 0.19             | -15.85                                | 3.32             | Pass        |
|          | 6       | 2437        | -17.87                         | 6.02            | 0.19             | -11.66                                | 3.32             | Pass        |
|          | 11      | 2462        | -23.02                         | 6.02            | 0.19             | -16.81                                | 3.32             | Pass        |
| 3        | 1       | 2412        | -21.94                         | 6.02            | 0.19             | -15.73                                | 3.32             | Pass        |
|          | 6       | 2437        | -18.00                         | 6.02            | 0.19             | -11.79                                | 3.32             | Pass        |
|          | 11      | 2462        | -22.97                         | 6.02            | 0.19             | -16.76                                | 3.32             | Pass        |

#### Note:

1. Method 1 of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
2. Directional gain =  $4.66\text{dBi} + 10\log(4) = 10.68\text{dBi} > 6\text{dBi}$ , so the power density limit shall be reduced to  $8 - (10.68 - 6) = 3.32\text{dBm}$
3. Refer to section 3.3 for duty cycle spectrum plot.

### 802.11n (HT20)

| TX chain | Channel | Frequency (MHz) | PSD (dBm/3kHz) | 10 log (N=4) dB | Total PSD (dBm/3kHz) | Limit (dBm/3kHz) | Pass / Fail |
|----------|---------|-----------------|----------------|-----------------|----------------------|------------------|-------------|
| 0        | 1       | 2412            | -21.97         | 6.02            | -15.95               | 3.32             | Pass        |
|          | 6       | 2437            | -17.68         | 6.02            | -11.66               | 3.32             | Pass        |
|          | 11      | 2462            | -23.53         | 6.02            | -17.51               | 3.32             | Pass        |
| 1        | 1       | 2412            | -21.21         | 6.02            | -15.19               | 3.32             | Pass        |
|          | 6       | 2437            | -16.98         | 6.02            | -10.96               | 3.32             | Pass        |
|          | 11      | 2462            | -22.33         | 6.02            | -16.31               | 3.32             | Pass        |
| 2        | 1       | 2412            | -22.38         | 6.02            | -16.36               | 3.32             | Pass        |
|          | 6       | 2437            | -17.62         | 6.02            | -11.60               | 3.32             | Pass        |
|          | 11      | 2462            | -22.64         | 6.02            | -16.62               | 3.32             | Pass        |
| 3        | 1       | 2412            | -21.57         | 6.02            | -15.55               | 3.32             | Pass        |
|          | 6       | 2437            | -17.36         | 6.02            | -11.34               | 3.32             | Pass        |
|          | 11      | 2462            | -23.29         | 6.02            | -17.27               | 3.32             | Pass        |

Note:

1. Method 1 of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
2. Directional gain =  $4.66\text{dBi} + 10\log(4) = 10.68\text{dBi} > 6\text{dBi}$ , so the power density limit shall be reduced to  $8 - (10.68 - 6) = 3.32\text{dBm}$

#### 802.11n (HT40)


| TX chain | Channel | Freq. (MHz) | PSD w/o Duty Factor (dBm/3kHz) | 10 log (N=4) dB | Duty Factor (dB) | Total PSD With Duty Factor (dBm/3kHz) | Limit (dBm/3kHz) | Pass / Fail |
|----------|---------|-------------|--------------------------------|-----------------|------------------|---------------------------------------|------------------|-------------|
| 0        | 3       | 2422        | -28.47                         | 6.02            | 0.13             | -22.32                                | 3.32             | Pass        |
|          | 6       | 2437        | -26.67                         | 6.02            | 0.13             | -20.52                                | 3.32             | Pass        |
|          | 9       | 2452        | -29.15                         | 6.02            | 0.13             | -23.00                                | 3.32             | Pass        |
| 1        | 3       | 2422        | -28.60                         | 6.02            | 0.13             | -22.45                                | 3.32             | Pass        |
|          | 6       | 2437        | -25.37                         | 6.02            | 0.13             | -19.22                                | 3.32             | Pass        |
|          | 9       | 2452        | -28.98                         | 6.02            | 0.13             | -22.83                                | 3.32             | Pass        |
| 2        | 3       | 2422        | -28.97                         | 6.02            | 0.13             | -22.82                                | 3.32             | Pass        |
|          | 6       | 2437        | -26.58                         | 6.02            | 0.13             | -20.43                                | 3.32             | Pass        |
|          | 9       | 2452        | -28.51                         | 6.02            | 0.13             | -22.36                                | 3.32             | Pass        |
| 3        | 3       | 2422        | -28.65                         | 6.02            | 0.13             | -22.50                                | 3.32             | Pass        |
|          | 6       | 2437        | -26.84                         | 6.02            | 0.13             | -20.69                                | 3.32             | Pass        |
|          | 9       | 2452        | -29.41                         | 6.02            | 0.13             | -23.26                                | 3.32             | Pass        |

#### Note:


1. Method 1 of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
2. Directional gain =  $4.66\text{dBi} + 10\log(4) = 10.68\text{dBi} > 6\text{dBi}$ , so the power density limit shall be reduced to  $8 - (10.68 - 6) = 3.32\text{dBm}$
3. Refer to section 3.3 for duty cycle spectrum plot.

## Spectrum Plot of Worst Value


### 802.11b




### 802.11g



### 802.11n (HT20)



### 802.11n (HT40)



### Radio 3: CDD Mode

#### 802.11b

| Channel | Freq. (MHz) | PSD (dBm/3kHz) | Limit (dBm/3kHz) | Pass / Fail |
|---------|-------------|----------------|------------------|-------------|
| 1       | 2412        | -22.03         | 8.00             | Pass        |
| 6       | 2437        | -22.54         | 8.00             | Pass        |
| 11      | 2462        | -22.28         | 8.00             | Pass        |

#### 802.11g

| Channel | Frequency (MHz) | PSD w/o Duty Factor (dBm/3kHz) | Duty Factor (dB) | Total PSD With Duty Factor (dBm/3kHz) | Limit (dBm/3kHz) | Pass / Fail |
|---------|-----------------|--------------------------------|------------------|---------------------------------------|------------------|-------------|
| 1       | 2412            | -25.58                         | 0.16             | -25.42                                | 8.00             | Pass        |
| 6       | 2437            | -21.14                         | 0.16             | -20.98                                | 8.00             | Pass        |
| 11      | 2462            | -25.35                         | 0.16             | -25.19                                | 8.00             | Pass        |

Note: Refer to section 3.3 for duty cycle spectrum plot.

#### 802.11n (HT20)

| Channel | Frequency (MHz) | PSD w/o Duty Factor (dBm/3kHz) | Duty Factor (dB) | Total PSD With Duty Factor (dBm/3kHz) | Limit (dBm/3kHz) | Pass / Fail |
|---------|-----------------|--------------------------------|------------------|---------------------------------------|------------------|-------------|
| 1       | 2412            | -26.16                         | 0.22             | -25.94                                | 8.00             | Pass        |
| 6       | 2437            | -20.95                         | 0.22             | -20.73                                | 8.00             | Pass        |
| 11      | 2462            | -26.61                         | 0.22             | -26.39                                | 8.00             | Pass        |

Note: Refer to section 3.3 for duty cycle spectrum plot.


#### 802.11n (HT40)

| Channel | Frequency (MHz) | PSD w/o Duty Factor (dBm/3kHz) | Duty Factor (dB) | Total PSD With Duty Factor (dBm/3kHz) | Limit (dBm/3kHz) | Pass / Fail |
|---------|-----------------|--------------------------------|------------------|---------------------------------------|------------------|-------------|
| 3       | 2422            | -33.93                         | 0.44             | -33.49                                | 8.00             | Pass        |
| 6       | 2437            | -29.16                         | 0.44             | -28.72                                | 8.00             | Pass        |
| 9       | 2452            | -33.96                         | 0.44             | -33.52                                | 8.00             | Pass        |


Note: Refer to section 3.3 for duty cycle spectrum plot.

## Spectrum Plot of Worst Value


### 802.11b




### 802.11g



### 802.11n (HT20)



### 802.11n (HT40)




## 4.6 Conducted Out of Band Emission Measurement

### 4.6.1 Limits of Conducted Out of Band Emission Measurement

Below 30dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

### 4.6.2 Test Setup



### 4.6.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

### 4.6.4 Test Procedure

#### MEASUREMENT PROCEDURE REF

- Set the RBW = 100 kHz.
- Set the VBW  $\geq$  300 kHz.
- Detector = average.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

#### MEASUREMENT PROCEDURE OOB

- Set RBW = 100 kHz.
- Set VBW  $\geq$  300 kHz.
- Ensure that the number of measurement points  $\geq$  span/RBW
- According to measurement points to set differ measurement span.
- Detector = average.
- Trace Mode = max hold.
- Sweep = auto couple.

#### **4.6.5 Deviation from Test Standard**

No deviation.

#### **4.6.6 EUT Operating Condition**

Same as Item 4.3.6



#### **4.6.7 Test Results**

The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 30dB offset below D1. It shows compliance with the requirement.



Radio 1: CDD Mode

802.11b\_Chain 0



CH 1




CH 6




CH 11



CH 1 Band edge





CH 11 Band edge





## 802.11b\_Chain 1



### CH 1




### CH 6




### CH 11



### CH 1 Band edge





### CH 11 Band edge





## 802.11b\_Chain 2



### CH 1




### CH 6




### CH 11



### CH 1 Band edge





### CH 11 Band edge





## 802.11b\_Chain 3



### CH 1




### CH 6




### CH 11



### CH 1 Band edge





### CH 11 Band edge





## 802.11g\_Chain 0



### CH 1




### CH 6




### CH 11



### CH 1 Band edge





### CH 11 Band edge





## 802.11g\_Chain 1



### CH 1




### CH 6




### CH 11



### CH 1 Band edge





### CH 11 Band edge





## 802.11g\_Chain 2



### CH 1




### CH 6




### CH 11



### CH 1 Band edge




### CH 11 Band edge




## 802.11g\_Chain 3


### CH 1




### CH 6




### CH 11



### CH 1 Band edge





### CH 11 Band edge





## 802.11n (HT20)\_Chain 0



### CH 1




### CH 6




### CH 11



### CH 1 Band edge





### CH 11 Band edge





## 802.11n (HT20)\_Chain 1



### CH 1




### CH 6




### CH 11



### CH 1 Band edge





### CH 11 Band edge





## 802.11n (HT20)\_Chain 2



### CH 1




### CH 6




### CH 11



### CH 1 Band edge





### CH 11 Band edge





## 802.11n (HT20)\_Chain 3



### CH 1




### CH 6




### CH 11



### CH 1 Band edge





### CH 11 Band edge







## 802.11n (HT40)\_Chain 1



### CH 3




### CH 6




### CH 9



### CH 3 Band edge




### CH 9 Band edge




## 802.11n (HT40)\_Chain 2


### CH 3




### CH 6




### CH 9



### CH 3 Band edge





### CH 9 Band edge





## 802.11n (HT40)\_Chain 3



### CH 3




### CH 6




### CH 9



### CH 3 Band edge





### CH 9 Band edge





## Radio 3: CDD Mode

802.11b



### CH 1




### CH 6




### CH 11



### CH 1 Band edge




### CH 11 Band edge




Note: Chosen the worst reference level for band edge limit.

802.11g


### CH 1




### CH 6




### CH 11



### CH 1 Band edge





### CH 11 Band edge





Note: Chosen the worst reference level for band edge limit.

## 802.11n (HT20)



### CH 1




### CH 6




### CH 11



### CH 1 Band edge





### CH 11 Band edge





Note: Chosen the worst reference level for band edge limit.

802.11n (HT40)



### CH 3




### CH 6




### CH 9



### CH 3 Band edge



### CH 9 Band edge



Note: Chosen the worst reference level for band edge limit.

## 5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

## Appendix – Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

**Linko EMC/RF Lab**

Tel: 886-2-26052180

Fax: 886-2-26051924

**Hsin Chu EMC/RF/Telecom Lab**

Tel: 886-3-6668565

Fax: 886-3-6668323

**Hwa Ya EMC/RF/Safety Lab**

Tel: 886-3-3183232

Fax: 886-3-3270892

**Email:** [service.adt@tw.bureauveritas.com](mailto:service.adt@tw.bureauveritas.com)

**Web Site:** [www.bureauveritas-adt.com](http://www.bureauveritas-adt.com)

The address and road map of all our labs can be found in our web site also.

--- END ---