

## FCC Test Report

**Report No.:** RF160726C12-1

**FCC ID:** HDCBSAP304X

**Test Model:** BSAP-3045

**Series Model:** BSAP-3040

**Received Date:** Jul. 26, 2016

**Test Date:** Jul. 30 ~ Sep. 09, 2016

**Issued Date:** Nov. 04, 2016

**Applicant:** Adtran

**Address:** 901 Explorer Boulevard Huntsville Alabama United States

**Issued By:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

**Lab Address:** No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan (R.O.C.)

**Test Location:** No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City 33383, TAIWAN (R.O.C.)



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

## Table of Contents

|                                                            |           |
|------------------------------------------------------------|-----------|
| <b>Release Control Record</b>                              | <b>4</b>  |
| <b>1 Certificate of Conformity</b>                         | <b>5</b>  |
| <b>2 Summary of Test Results</b>                           | <b>6</b>  |
| 2.1 Measurement Uncertainty                                | 6         |
| 2.2 Modification Record                                    | 6         |
| <b>3 General Information</b>                               | <b>7</b>  |
| 3.1 General Description of EUT                             | 7         |
| 3.2 Description of Test Modes                              | 10        |
| 3.2.1 Test Mode Applicability and Tested Channel Detail    | 11        |
| 3.3 Duty Cycle of Test Signal                              | 13        |
| 3.4 Description of Support Units                           | 14        |
| 3.4.1 Configuration of System under Test                   | 14        |
| 3.5 General Description of Applied Standard                | 16        |
| <b>4 Test Types and Results</b>                            | <b>17</b> |
| 4.1 Radiated Emission and Bandedge Measurement             | 17        |
| 4.1.1 Limits of Radiated Emission and Bandedge Measurement | 17        |
| 4.1.2 Test Instruments                                     | 18        |
| 4.1.3 Test Procedure                                       | 19        |
| 4.1.4 Deviation from Test Standard                         | 19        |
| 4.1.5 Test Setup                                           | 20        |
| 4.1.6 EUT Operating Conditions                             | 21        |
| 4.1.7 Test Results                                         | 22        |
| 4.2 Conducted Emission Measurement                         | 64        |
| 4.2.1 Limits of Conducted Emission Measurement             | 64        |
| 4.2.2 Test Instruments                                     | 64        |
| 4.2.3 Test Procedure                                       | 65        |
| 4.2.4 Deviation from Test Standard                         | 65        |
| 4.2.5 Test Setup                                           | 65        |
| 4.2.6 EUT Operating Conditions                             | 65        |
| 4.2.7 Test Results                                         | 66        |
| 4.3 Transmit Power Measurement                             | 74        |
| 4.3.1 Limits of Transmit Power Measurement                 | 74        |
| 4.3.2 Test Setup                                           | 74        |
| 4.3.3 Test Instruments                                     | 75        |
| 4.3.4 Test Procedure                                       | 75        |
| 4.3.5 Deviation from Test Standard                         | 75        |
| 4.3.6 EUT Operating Conditions                             | 75        |
| 4.3.7 Test Result                                          | 76        |
| 4.4 Occupied Bandwidth Measurement                         | 81        |
| 4.4.1 Test Setup                                           | 81        |
| 4.4.2 Test Instruments                                     | 81        |
| 4.4.3 Test Procedure                                       | 81        |
| 4.4.4 Test Result                                          | 82        |
| 4.5 Peak Power Spectral Density Measurement                | 84        |
| 4.5.1 Limits of Peak Power Spectral Density Measurement    | 84        |
| 4.5.2 Test Setup                                           | 84        |
| 4.5.3 Test Instruments                                     | 84        |
| 4.5.4 Test Procedure                                       | 85        |
| 4.5.5 Deviation from Test Standard                         | 85        |
| 4.5.6 EUT Operating Condition                              | 85        |
| 4.5.7 Test Results                                         | 86        |
| 4.6 Frequency Stability                                    | 92        |
| 4.6.1 Limits of Frequency Stability Measurement            | 92        |

|          |                                                                                           |            |
|----------|-------------------------------------------------------------------------------------------|------------|
| 4.6.2    | Test Setup .....                                                                          | 92         |
| 4.6.3    | Test Instruments .....                                                                    | 92         |
| 4.6.4    | Test Procedure .....                                                                      | 92         |
| 4.6.5    | Deviation from Test Standard .....                                                        | 92         |
| 4.6.6    | EUT Operating Condition .....                                                             | 92         |
| 4.6.7    | Test Results .....                                                                        | 93         |
| 4.7      | 6dB Bandwidth Measurement .....                                                           | 94         |
| 4.7.1    | Limits of 6dB Bandwidth Measurement .....                                                 | 94         |
| 4.7.2    | Test Setup .....                                                                          | 94         |
| 4.7.3    | Test Instruments .....                                                                    | 94         |
| 4.7.4    | Test Procedure .....                                                                      | 94         |
| 4.7.5    | Deviation from Test Standard .....                                                        | 94         |
| 4.7.6    | EUT Operating Condition .....                                                             | 94         |
| 4.7.7    | Test Results .....                                                                        | 95         |
| <b>5</b> | <b>Pictures of Test Arrangements .....</b>                                                | <b>97</b>  |
|          | <b>Annex A- Radiated Out of Band Emission (OOBE) Measurement (For U-NII-3 band) .....</b> | <b>98</b>  |
|          | <b>Appendix – Information on the Testing Laboratories .....</b>                           | <b>104</b> |

### Release Control Record

| Issue No.     | Description       | Date Issued   |
|---------------|-------------------|---------------|
| RF160726C12-1 | Original release. | Nov. 04, 2016 |

## 1 Certificate of Conformity

**Product:** Wireless 802.11abgn/ac Access Point

**Brand:** Adtran

**Test Model:** BSAP-3045

**Series Model:** BSAP-3040

**Sample Status:** Engineering sample

**Applicant:** Adtran

**Test Date:** Jul. 30 ~ Sep. 09, 2016

**Standard:** 47 CFR FCC Part 15, Subpart E (Section 15.407)  
ANSI C63.10:2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the Conditions specified in this report.

**Prepared by :** Polly Chien, **Date:** Nov. 04, 2016  
Polly Chien / Specialist

**Approved by :** Ken Liu, **Date:** Nov. 04, 2016  
Ken Liu / Senior Manager

## 2 Summary of Test Results

| 47 CFR FCC Part 15, Subpart E (Section 15.407) |                                            |        |                                                                                              |
|------------------------------------------------|--------------------------------------------|--------|----------------------------------------------------------------------------------------------|
| FCC Clause                                     | Test Item                                  | Result | Remarks                                                                                      |
| 15.407(b)(6)                                   | AC Power Conducted Emissions               | Pass   | Meet the requirement of limit.<br>Minimum passing margin is -5.74dB at 0.52544MHz.           |
| 15.407(b)<br>(1/2/3/4(i/ii)/6)                 | Radiated Emissions & Band Edge Measurement | Pass   | Meet the requirement of limit.<br>Minimum passing margin is -1.0dB at 11490MHz, 11570.00MHz. |
| 15.407(a)(1/2/3)                               | Max Average Transmit Power                 | Pass   | Meet the requirement of limit.                                                               |
| 15.407(a)(1/2/3)                               | Peak Power Spectral Density                | Pass   | Meet the requirement of limit.                                                               |
| 15.407(e)                                      | 6dB bandwidth                              | Pass   | Meet the requirement of limit.<br>(U-NII-3 Band only)                                        |
| 15.407(g)                                      | Frequency Stability                        | Pass   | Meet the requirement of limit.                                                               |
| 15.203                                         | Antenna Requirement                        | Pass   | Antenna connector is IPEX not a standard connector.                                          |

\*For U-NII-3 band compliance with rule part 15.407(b)(4)(i), the OOB test plots were recorded in Annex A.

### 2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

| Measurement                        | Frequency        | Expanded Uncertainty<br>(k=2) (±) |
|------------------------------------|------------------|-----------------------------------|
| Conducted Emissions at mains ports | 150kHz ~ 30MHz   | 2.44 dB                           |
| Radiated Emissions up to 1 GHz     | 30MHz ~ 200MHz   | 3.86 dB                           |
|                                    | 200MHz ~ 1000MHz | 3.87 dB                           |
| Radiated Emissions above 1 GHz     | 1GHz ~ 18GHz     | 2.29 dB                           |
|                                    | 18GHz ~ 40GHz    | 2.29 dB                           |

### 2.2 Modification Record

There were no modifications required for compliance.

### 3 General Information

#### 3.1 General Description of EUT

|                       |                                                                                                                                                                                                                                                                                                            |
|-----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product               | Wireless 802.11abgn/ac Access Point                                                                                                                                                                                                                                                                        |
| Brand                 | Adtran                                                                                                                                                                                                                                                                                                     |
| Test Model            | BSAP-3045                                                                                                                                                                                                                                                                                                  |
| Series Model          | BSAP-3040                                                                                                                                                                                                                                                                                                  |
| Model Difference      | Refer to note for more details                                                                                                                                                                                                                                                                             |
| Sample Status         | Engineering sample                                                                                                                                                                                                                                                                                         |
| Power Supply Rating   | 12Vdc from adapter<br>48Vdc from POE                                                                                                                                                                                                                                                                       |
| Modulation Type       | 256QAM, 64QAM, 16QAM, QPSK, BPSK                                                                                                                                                                                                                                                                           |
| Modulation Technology | OFDM                                                                                                                                                                                                                                                                                                       |
| Transfer Rate         | 802.11a: 54/48/36/24/18/12/9/6Mbps<br>802.11n: up to 600Mbps<br>802.11ac: up to 1733Mbps                                                                                                                                                                                                                   |
| Operating Frequency   | 5180~5240MHz, 5745~5825MHz                                                                                                                                                                                                                                                                                 |
| Number of Channel     | 5180~5240MHz:<br>802.11a, 802.11n (HT20), 802.11ac (VHT20): 4<br>802.11n (HT40), 802.11ac (VHT40): 2<br>802.11ac (VHT80), 802.11ac (VHT80+VHT80): 1<br>5745~5825MHz:<br>802.11a, 802.11n (HT20), 802.11ac (VHT20): 5<br>802.11n (HT40), 802.11ac (VHT40): 2<br>802.11ac (VHT80), 802.11ac (VHT80+VHT80): 1 |
| Output Power          | Radio 2:<br>CDD Mode<br>5180 ~ 5240MHz: 267.841mW<br>5745 ~ 5825MHz: 351.314mW<br>Beamforming Mode<br>5180 ~ 5240MHz: 66.970mW<br>5745 ~ 5825MHz: 87.810mW                                                                                                                                                 |
| Antenna Type          | Refer to Note                                                                                                                                                                                                                                                                                              |
| Antenna Connector     | Refer to Note                                                                                                                                                                                                                                                                                              |
| Accessory Device      | NA                                                                                                                                                                                                                                                                                                         |
| Data Cable Supplied   | NA                                                                                                                                                                                                                                                                                                         |

Note:

1. The following models are provided to this EUT.

| Brand  | Model     | Difference       |
|--------|-----------|------------------|
| Adtran | BSAP-3040 | Internal antenna |
|        | BSAP-3045 | External antenna |

2. There are four radios for the EUT.

| Radio   | Model         | Function                      |
|---------|---------------|-------------------------------|
| Radio 1 | QCA9994       | WLAN 2.4G                     |
| Radio 2 | QCA9994       | WLAN 5G                       |
| Radio 3 | QCA9889       | WLAN 2.4GHz (TX/RX)+5GHz (RX) |
| Radio 4 | MKW40Z160 MCU | BT LE                         |

3. The EUT incorporates a MIMO function. Physically, the EUT provides 4 completed transmitters and 4 receivers.

| Band                      | Modulation Mode            | Beamforming Mode | TX/RX Function | Available Channel | Remark  |
|---------------------------|----------------------------|------------------|----------------|-------------------|---------|
| 5GHz<br>(U-NII-1<br>band) | 802.11a                    | Not Support      | 4TX            | 36 ~ 48           | Radio 2 |
|                           | 802.11ac (VHT20)           | Support          | 4TX            | 36 ~ 48           |         |
|                           | 802.11ac (VHT40)           | Support          | 4TX            | 38 ~ 46           |         |
|                           | 802.11ac (VHT80)           | Support          | 4TX            | 42                |         |
|                           | 802.11ac<br>(VHT80+ VHT80) | Support          | 2TX+2TX        | 42 + 155          |         |
|                           | 802.11a                    | Not Support      | RX only        | 36 ~ 48           | Radio 3 |
|                           | 802.11ac (VHT20)           | Not Support      | RX only        | 36 ~ 48           |         |
|                           | 802.11ac (VHT40)           | Not Support      | RX only        | 38 ~ 46           |         |
|                           | 802.11ac (VHT80)           | Not Support      | RX only        | 42                |         |
| 5GHz<br>(U-NII-3<br>band) | 802.11a                    | Not Support      | 4TX            | 149 ~ 165         | Radio 2 |
|                           | 802.11ac (VHT20)           | Support          | 4TX            | 149 ~ 165         |         |
|                           | 802.11ac (VHT40)           | Support          | 4TX            | 151 ~ 159         |         |
|                           | 802.11ac (VHT80)           | Support          | 4TX            | 155               |         |
|                           | 802.11ac<br>(VHT80+ VHT80) | Support          | 2TX+2TX        | 42 + 155          |         |
|                           | 802.11a                    | Not Support      | RX only        | 149 ~ 165         | Radio 3 |
|                           | 802.11ac (VHT20)           | Not Support      | RX only        | 149 ~ 165         |         |
|                           | 802.11ac (VHT40)           | Not Support      | RX only        | 151 ~ 159         |         |
|                           | 802.11ac (VHT80)           | Not Support      | RX only        | 155               |         |

\* The modulation and bandwidth are similar for 802.11n mode for HT20/HT40 and 802.11ac mode for VHT20/VHT40, therefore investigated worst case to representative mode in test report. (Final test mode refer section 3.2.1)

\* For 802.11n & 802.11ac, after pre-tested two modes(with beamforming mode and CDD mode) found CDD mode was the worst, therefore chosen for final test except power output test and presented in the test report.

4. The EUT uses following antennas.

**For Model: BSAP-3040 (Internal antenna)**

| Ant. No.        | 1         | 2    | 3    | 4    | 5         | 6    | 7    | 8    | 9 (Scan)<br>Individual  | 10 (BLE)<br>Individual |
|-----------------|-----------|------|------|------|-----------|------|------|------|-------------------------|------------------------|
| Ant. Type       | PIFA      |      |      |      |           |      |      |      | PIFA                    | Dipole                 |
| Frequency (MHz) | 2400-2500 |      |      |      | 5150-5850 |      |      |      | 2400-2500/<br>5150-5850 | 2400-2500              |
| CDD Gain (dBi)  | 3.81      | 3.98 | 3.47 | 3.75 | 5.65      | 5.50 | 5.84 | 5.84 | 2.9/5.1                 | 3.93                   |
| Connector       | IPEX      |      |      |      |           |      |      |      | IPEX                    | IPEX                   |

**For Model: BSAP-3045 (External antenna)**

|                 |        |      |      |      |      |      |                         |                       |
|-----------------|--------|------|------|------|------|------|-------------------------|-----------------------|
| Ant. No.        | -      |      |      | -    |      |      | 9 (Scan)<br>Individual  | 1 (BLE)<br>Individual |
| Ant. Type       | Dipole |      |      |      |      |      | PIFA                    | PIFA                  |
| Frequency (MHz) | 2400   | 2450 | 2500 | 5150 | 5550 | 5850 | 2400-2500/<br>5150-5850 | 2400-2500             |
| CDD Gain (dBi)  | 4.66   | 4.47 | 4.49 | 3.34 | 4.67 | 4.52 | 2.9/5.1                 | 3.81                  |
| Connector       | IPEX   |      |      |      |      |      | IPEX                    | IPEX                  |

5. The EUT consumes power from the following adapter and POE. (Support units only)

| Adapter      |                                              |
|--------------|----------------------------------------------|
| Brand        | AOEM                                         |
| Model        | ADS036T-W120300                              |
| Input Power  | 100-240Vac, 50-60Hz, 1.0A                    |
| Output Power | 12Vdc, 3.0A                                  |
| Power Line   | 1.5m cable with one core attached on adapter |

| POE          |                      |
|--------------|----------------------|
| Brand        | EnGenius             |
| Model        | EPE-48GR             |
| Output Power | 48Vdc, 0.5A, 24W Max |

| POE's adapter |                                               |
|---------------|-----------------------------------------------|
| Brand         | Powertron Electronics Corp.                   |
| Model         | PA1040-480IB080                               |
| Input Power   | 100-240Vac, 50-60Hz, 1.5A                     |
| Output Power  | 48Vdc, 0.8A, 38.4W Max                        |
| Power Line    | 1.55m cable with one core attached on adapter |

6. WLAN 2.4GHz, WLAN 5GHz and BT LE technologies can transmit at same time.

7. Spurious emission of the simultaneous operation (2.4GHz, 5GHz and BT LE) has been evaluated and no non-compliance was found.

### 3.2 Description of Test Modes

#### 5180 ~ 5240MHz:

4 channels are provided for 802.11a, 802.11n (HT20), 802.11ac (VHT20):

| Channel | Frequency | Channel | Frequency |
|---------|-----------|---------|-----------|
| 36      | 5180 MHz  | 44      | 5220 MHz  |
| 40      | 5200 MHz  | 48      | 5240 MHz  |

2 channels are provided for 802.11n (HT40), 802.11ac (VHT40):

| Channel | Frequency | Channel | Frequency |
|---------|-----------|---------|-----------|
| 38      | 5190 MHz  | 46      | 5230 MHz  |

1 channel is provided for 802.11ac (VHT80), 802.11ac (VHT80+VHT80):

| Channel | Frequency |
|---------|-----------|
| 42      | 5210MHz   |

#### 5745 ~ 5825MHz:

5 channels are provided for 802.11a, 802.11n (HT20), 802.11ac (VHT20):

| Channel | Frequency | Channel | Frequency |
|---------|-----------|---------|-----------|
| 149     | 5745MHz   | 161     | 5805MHz   |
| 153     | 5765MHz   | 165     | 5825MHz   |
| 157     | 5785MHz   |         |           |

2 channels are provided for 802.11n (HT40), 802.11ac (VHT40):

| Channel | Frequency | Channel | Frequency |
|---------|-----------|---------|-----------|
| 151     | 5755MHz   | 159     | 5795MHz   |

1 channel is provided for 802.11ac (VHT80), 802.11ac (VHT80+VHT80):

| Channel | Frequency |
|---------|-----------|
| 155     | 5775MHz   |

802.11ac (VHT80+VHT80) only support channel as below:

| Channel | Frequency       |
|---------|-----------------|
| 42+155  | 5210MHz+5775MHz |

### 3.2.1 Test Mode Applicability and Tested Channel Detail

| EUT Configure Mode | Applicable to |       |     |      | Description                            |
|--------------------|---------------|-------|-----|------|----------------------------------------|
|                    | RE $\geq$ 1G  | RE<1G | PLC | APCM |                                        |
| A                  | √             | √     | √   | -    | Model: BSAP-3045<br>Power from adapter |
| B                  | -             | √     | √   | -    | Model: BSAP-3045<br>Power from POE     |
| C                  | √             | √     | √   | √    | Model: BSAP-3040<br>Power from adapter |
| D                  | -             | √     | √   | -    | Model: BSAP-3040<br>Power from POE     |

Where RE $\geq$ 1G: Radiated Emission above 1GHz & Bandedge Measurement  
PLC: Power Line Conducted Emission

RE<1G: Radiated Emission below 1GHz  
APCM: Antenna Port Conducted Measurement

Note:

- The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on **Z-plane for test mode A, B (Radio 2), Y-plane for test mode C, D (Radio 2)**.
- "-" means no effect.

#### Radiated Emission Test (Above 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

| EUT CONFIGURE MODE | MODE                   | FREQ. BAND (MHz) | AVAILABLE CHANNEL | TESTED CHANNEL | MODULATION TECHNOLOGY | MODULATION TYPE | DATA RATE (Mbps) | REMARK        |
|--------------------|------------------------|------------------|-------------------|----------------|-----------------------|-----------------|------------------|---------------|
| A, C               | 802.11a                | 5180-5240        | 36 to 48          | 36, 40, 48     | OFDM                  | BPSK            | 6.0              | Radio 2 (4TX) |
| A, C               | 802.11n (HT20)         |                  | 36 to 48          | 36, 40, 48     | OFDM                  | BPSK            | 7.2              | Radio 2 (4TX) |
| A, C               | 802.11n (HT40)         |                  | 38 to 46          | 38, 46         | OFDM                  | BPSK            | 15.0             | Radio 2 (4TX) |
| A, C               | 802.11ac (VHT80)       |                  | 42                | 42             | OFDM                  | BPSK            | 130.0            | Radio 2 (4TX) |
| A, C               | 802.11a                | 5745-5825        | 149 to 165        | 149, 157, 165  | OFDM                  | BPSK            | 6.0              | Radio 2 (4TX) |
| A, C               | 802.11n (HT20)         |                  | 149 to 165        | 149, 157, 165  | OFDM                  | BPSK            | 7.2              | Radio 2 (4TX) |
| A, C               | 802.11n (HT40)         |                  | 151 to 159        | 151, 159       | OFDM                  | BPSK            | 15.0             | Radio 2 (4TX) |
| A, C               | 802.11ac (VHT80)       |                  | 155               | 155            | OFDM                  | BPSK            | 130.0            | Radio 2 (4TX) |
| A, C               | 802.11ac (VHT80+VHT80) | 5180-5240        | 42                | 42+155         | OFDM                  | BPSK            | 130.0            | Radio 2 (2TX) |
|                    |                        | 5745-5825        | 155               |                | OFDM                  | BPSK            | 130.0            | Radio 2 (2TX) |

#### Radiated Emission Test (Below 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

| EUT CONFIGURE MODE | MODE           | FREQ. BAND (MHz) | AVAILABLE CHANNEL | TESTED CHANNEL | MODULATION TECHNOLOGY | MODULATION TYPE | DATA RATE (Mbps) | REMARK        |
|--------------------|----------------|------------------|-------------------|----------------|-----------------------|-----------------|------------------|---------------|
| A, B, C, D         | 802.11n (HT20) | 5180-5240        | 36 to 48          | 149            | OFDM                  | BPSK            | 7.2              | Radio 2 (4TX) |
|                    | 802.11n (HT20) | 5745-5825        | 149 to 165        |                | OFDM                  | BPSK            | 7.2              | Radio 2 (4TX) |

#### Power Line Conducted Emission Test:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

| EUT CONFIGURE MODE | MODE           | FREQ. BAND (MHz) | AVAILABLE CHANNEL | TESTED CHANNEL | MODULATION TECHNOLOGY | MODULATION TYPE | DATA RATE (Mbps) | REMARK        |
|--------------------|----------------|------------------|-------------------|----------------|-----------------------|-----------------|------------------|---------------|
| A, B, C, D         | 802.11n (HT20) | 5180-5240        | 36 to 48          | 149            | OFDM                  | BPSK            | 7.2              | Radio 2 (4TX) |
|                    | 802.11n (HT20) | 5745-5825        | 149 to 165        |                | OFDM                  | BPSK            | 7.2              | Radio 2 (4TX) |

#### Antenna Port Conducted Measurement:

- ☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

| EUT CONFIGURE MODE | MODE                   | FREQ. BAND (MHz) | AVAILABLE CHANNEL | TESTED CHANNEL | MODULATION TECHNOLOGY | MODULATION TYPE | DATA RATE (Mbps) | REMARK        |
|--------------------|------------------------|------------------|-------------------|----------------|-----------------------|-----------------|------------------|---------------|
| C                  | 802.11a                | 5180-5240        | 36 to 48          | 36, 40, 48     | OFDM                  | BPSK            | 6.0              | Radio 2 (4TX) |
| C                  | 802.11n (HT20)         |                  | 36 to 48          | 36, 40, 48     | OFDM                  | BPSK            | 7.2              | Radio 2 (4TX) |
| C                  | 802.11n (HT40)         |                  | 38 to 46          | 38, 46         | OFDM                  | BPSK            | 15.0             | Radio 2 (4TX) |
| C                  | 802.11ac (VHT80)       |                  | 42                | 42             | OFDM                  | BPSK            | 130.0            | Radio 2 (4TX) |
| C                  | 802.11a                | 5745-5825        | 149 to 165        | 149, 157, 165  | OFDM                  | BPSK            | 6.0              | Radio 2 (4TX) |
| C                  | 802.11n (HT20)         |                  | 149 to 165        | 149, 157, 165  | OFDM                  | BPSK            | 7.2              | Radio 2 (4TX) |
| C                  | 802.11n (HT40)         |                  | 151 to 159        | 151, 159       | OFDM                  | BPSK            | 15.0             | Radio 2 (4TX) |
| C                  | 802.11ac (VHT80)       |                  | 155               | 155            | OFDM                  | BPSK            | 130.0            | Radio 2 (4TX) |
| C                  | 802.11ac (VHT80+VHT80) | 5180-5240        | 42                | 42+155         | OFDM                  | BPSK            | 130.0            | Radio 2 (2TX) |
|                    |                        | 5745-5825        | 155               |                | OFDM                  | BPSK            | 130.0            | Radio 2 (2TX) |

#### Test Condition:

| Applicable to | Environmental Conditions | Input Power         | Tested by                         |
|---------------|--------------------------|---------------------|-----------------------------------|
| RE≥1G         | 18 deg. C, 70% RH        | 120Vac, 60Hz        | Nick Hsu, James Yang, Jones Chang |
|               | 19 deg. C, 70% RH        |                     | James Yang, Jones Chang           |
| RE<1G         | 18 deg. C, 70% RH        | 120Vac, 60Hz, 48Vdc | Jones Chang                       |
| PLC           | 20 deg. C, 70% RH        | 120Vac, 60Hz, 48Vdc | Jones Chang                       |
| APCM          | 25 deg. C, 60% RH        | 120Vac, 60Hz        | Leo Tsai, Ted Chang               |

### 3.3 Duty Cycle of Test Signal

Duty cycle of test signal is > 98%, duty factor is not required

Duty cycle of test signal is < 98 %, duty factor is required

Radio 2: CDD Mode


802.11a: Duty cycle =  $2.052/2.132 = 0.962$ , Duty factor =  $10 * \log(1/0.962) = 0.17$

802.11n (HT20): Duty cycle =  $4.995/5.065 = 0.986$

802.11n (HT40): Duty cycle =  $2.425/2.492 = 0.973$ , Duty factor =  $10 * \log(1/0.973) = 0.12$

802.11ac (VHT80): Duty cycle =  $1.145/1.215 = 0.942$ , Duty factor =  $10 * \log(1/0.942) = 0.26$

802.11ac (VHT80+VHT80): Duty cycle =  $1.145/1.222 = 0.937$ , Duty factor =  $10 * \log(1/0.937) = 0.28$



### 3.4 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| ID | Product     | Brand                       | Model No.       | Serial No. | FCC ID           | Remarks                                                |
|----|-------------|-----------------------------|-----------------|------------|------------------|--------------------------------------------------------|
| A. | Notebook    | DELL                        | E5410           | 1HC2XM1    | FCC DoC Approved | -                                                      |
| B. | Adapter     | AOEM                        | ADS036T-W120300 | N/A        | N/A              | Provided by manufacturer<br>For test mode A and C only |
| C. | POE         | EnGenius                    | EPE-48GR        | N/A        | N/A              | Provided by manufacturer<br>For test mode B and D only |
| D. | POE adapter | Powertron Electronics Corp. | PA1040-480IB080 | N/A        | N/A              | Provided by manufacturer<br>For test mode B and D only |
| E. | Load        | N/A                         | N/A             | N/A        | N/A              | -                                                      |
| F. | USB Flash   | HP                          | v250W           | 01         | FCC DoC Approved | -                                                      |


Note:

1. All power cords of the above support units are non-shielded (1.8m).
2. Item A acted as communication partner to transfer data.


| ID | Descriptions         | Qty. | Length (m) | Shielding (Yes/No) | Cores (Qty.) | Remarks                    |
|----|----------------------|------|------------|--------------------|--------------|----------------------------|
| 1. | RJ45 Cable           | 1    | 3          | N                  | 0            | Cat5e                      |
| 2. | Power Cable          | 1    | 1.5        | -                  | 1            | For test mode A and C only |
| 3. | Power Cable          | 1    | 1.55       | -                  | 1            | For test mode B and D only |
| 4. | RJ45 Cable           | 1    | 1.8        | N                  | 0            | Cat5e                      |
| 5. | RJ45 to RS-232 Cable | 1    | 1.8        | N                  | 0            | -                          |
| 6. | RJ45 Cable           | 1    | 1.8        | N                  | 0            | Cat5e                      |

#### 3.4.1 Configuration of System under Test


Test Mode A




## Test Mode B



## Test Mode C



## Test Mode D



### 3.5 General Description of Applied Standard

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC Part 15, Subpart E (15.407)**

**789033 D02 General UNII Test Procedures New Rules v01r03**

**662911 D01 Multiple Transmitter Output v02r01**

ANSI C63.10:2013

All test items have been performed and recorded as per the above standards.

Note: The EUT has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC).  
The test report has been issued separately.

## 4 Test Types and Results

### 4.1 Radiated Emission and Bandedge Measurement

#### 4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table.

| Frequencies (MHz) | Field Strength (microvolts/meter) | Measurement Distance (meters) |
|-------------------|-----------------------------------|-------------------------------|
| 0.009 ~ 0.490     | 2400/F(kHz)                       | 300                           |
| 0.490 ~ 1.705     | 24000/F(kHz)                      | 30                            |
| 1.705 ~ 30.0      | 30                                | 30                            |
| 30 ~ 88           | 100                               | 3                             |
| 88 ~ 216          | 150                               | 3                             |
| 216 ~ 960         | 200                               | 3                             |
| Above 960         | 500                               | 3                             |

#### NOTE:

- The lower limit shall apply at the transition frequencies.
- Emission level (dBuV/m) = 20 log Emission level (uV/m).
- For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

#### Limits of unwanted emission out of the restricted bands

| Applicable To                                                                                    |                                     |                  | Limit                                                                                                                               |                                                                                                                                         |
|--------------------------------------------------------------------------------------------------|-------------------------------------|------------------|-------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| 789033 D02 General UNII Test Procedure<br>New Rules v01r03                                       |                                     |                  | Field Strength at 3m                                                                                                                |                                                                                                                                         |
|                                                                                                  |                                     |                  | PK:74 (dBµV/m)                                                                                                                      | AV:54 (dBµV/m)                                                                                                                          |
| Frequency Band                                                                                   | Applicable To                       |                  | EIRP Limit                                                                                                                          | Equivalent Field Strength at 3m                                                                                                         |
| 5150~5250 MHz                                                                                    | 15.407(b)(1)                        |                  | PK:-27 (dBm/MHz)                                                                                                                    | PK:68.2(dBµV/m)                                                                                                                         |
| 5250~5350 MHz                                                                                    | 15.407(b)(2)                        |                  |                                                                                                                                     |                                                                                                                                         |
| 5470~5725 MHz                                                                                    | 15.407(b)(3)                        |                  |                                                                                                                                     |                                                                                                                                         |
| 5725~5850 MHz                                                                                    | <input checked="" type="checkbox"/> | 15.407(b)(4)(i)  | PK:-27 (dBm/MHz) <sup>*1</sup><br>PK:10 (dBm/MHz) <sup>*2</sup><br>PK:15.6 (dBm/MHz) <sup>*3</sup><br>PK:27 (dBm/MHz) <sup>*4</sup> | PK: 68.2(dBµV/m) <sup>*1</sup><br>PK:105.2 (dBµV/m) <sup>*2</sup><br>PK: 110.8(dBµV/m) <sup>*3</sup><br>PK:122.2 (dBµV/m) <sup>*4</sup> |
|                                                                                                  | <input type="checkbox"/>            | 15.407(b)(4)(ii) | Emission limits in section 15.247(d)                                                                                                |                                                                                                                                         |
| <sup>*1</sup> beyond 75 MHz or more above of the band edge.                                      |                                     |                  | <sup>*2</sup> below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above.                                                |                                                                                                                                         |
| <sup>*3</sup> below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above. |                                     |                  | <sup>*4</sup> from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.                |                                                                                                                                         |

#### Note:

The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength:

$$E = \frac{1000000 \sqrt{30P}}{3} \text{ } \mu\text{V/m, where P is the eirp (Watts).}$$

#### 4.1.2 Test Instruments

| Description & Manufacturer                          | Model No.                    | Serial No.                     | Cal. Date                      | Cal. Due                       |
|-----------------------------------------------------|------------------------------|--------------------------------|--------------------------------|--------------------------------|
| Test Receiver<br>ROHDE & SCHWARZ                    | ESIB7                        | 100187                         | Apr. 18, 2016                  | Apr. 17, 2017                  |
| Spectrum Analyzer<br>ROHDE & SCHWARZ                | FSP40                        | 100041                         | Sep. 02, 2015<br>Sep. 02, 2016 | Sep. 01, 2016<br>Sep. 01, 2017 |
| BILOG Antenna<br>SCHWARZBECK                        | VULB9168                     | 9168-171                       | Jan. 07, 2016                  | Jan. 06, 2017                  |
| HORN Antenna<br>SCHWARZBECK                         | 9120D                        | 209                            | Jan. 20, 2016                  | Jan. 19, 2017                  |
| HORN Antenna<br>SCHWARZBECK                         | BBHA 9170                    | BBHA9170241                    | Jan. 18, 2016                  | Jan. 17, 2017                  |
| Loop Antenna                                        | EM-6879                      | 269                            | Aug. 11, 2016<br>Aug. 11, 2016 | Aug. 10, 2017<br>Aug. 10, 2017 |
| Preamplifier<br>Agilent                             | 8447D                        | 2944A10738                     | Oct. 18, 2015                  | Oct. 17, 2016                  |
| Preamplifier<br>Agilent                             | 8449B                        | 3008A01964                     | Aug. 22, 2015<br>Aug. 22, 2016 | Aug. 21, 2016<br>Aug. 21, 2017 |
| RF signal cable<br>HUBER+SUHNER                     | SUCOFLEX 104                 | Cable-CH3-03 (214378)          | Aug. 22, 2015<br>Aug. 22, 2016 | Aug. 21, 2016<br>Aug. 21, 2017 |
| RF signal cable<br>HUBER+SUHNER                     | SUCOFLEX 106                 | Cable-CH3-03<br>(309224+12738) | Aug. 22, 2015<br>Aug. 22, 2016 | Aug. 21, 2016<br>Aug. 21, 2017 |
| Software<br>BV ADT                                  | ADT_Radiated_<br>V7.6.15.9.4 | NA                             | NA                             | NA                             |
| Antenna Tower<br>inn-co GmbH                        | MA 4000                      | 013303                         | NA                             | NA                             |
| Antenna Tower Controller<br>BV ADT                  | AT100                        | AT93021702                     | NA                             | NA                             |
| Turn Table<br>BV ADT                                | TT100                        | TT93021702                     | NA                             | NA                             |
| Turn Table Controller<br>BV ADT                     | SC100                        | SC93021702                     | NA                             | NA                             |
| 26GHz ~ 40GHz Amplifier                             | EM26400                      | 815221                         | Oct. 18, 2015                  | Oct. 17, 2016                  |
| High Speed Peak Power<br>Meter                      | ML2495A                      | 0824011                        | Jul. 09, 2015<br>Jul. 09, 2016 | Jul. 08, 2016<br>Jul. 08, 2017 |
| Power Sensor                                        | MA2411B                      | 0738171                        | Jul. 09, 2015<br>Jul. 09, 2016 | Jul. 08, 2016<br>Jul. 08, 2017 |
| WIT Standard<br>Temperature And Humidity<br>Chamber | TH-4S-C                      | W981030                        | Jun. 08, 2016                  | Jun. 07, 2017                  |

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.  
2. The test was performed in HwaYa Chamber 3.  
3. The horn antenna and preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.  
4. The FCC Site Registration No. is 988962.  
5. The IC Site Registration No. is IC 7450F-3.

#### 4.1.3 Test Procedure

##### For Radiated emission below 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Both X and Y axes of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

##### Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

##### For Radiated emission above 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

##### Note:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is  $\geq 1/T$  (Duty cycle < 98%) or 10Hz (Duty cycle  $\geq 98\%$ ) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

#### 4.1.4 Deviation from Test Standard


No deviation.

#### 4.1.5 Test Setup


##### For Radiated emission below 30MHz



##### For Radiated emission 30MHz to 1GHz



### For Radiated emission above 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.1.6 EUT Operating Conditions

- Placed the EUT on the testing table.
- Prepared a notebook to act as a communication partner and placed it outside of testing area.
- The communication partner connected with EUT via a RJ45 cable and ran a test program (provided by manufacturer) to enable EUT under transmission condition continuously at specific channel frequency.
- The communication partner sent data to EUT by command "PING".

#### 4.1.7 Test Results

Above 1GHz Data:

Radio 2: CDD Mode

Test Mode A

802.11a

|                 |               |          |              |
|-----------------|---------------|----------|--------------|
| CHANNEL         | TX Channel 36 | DETECTOR | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 40GHz  | FUNCTION | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | #3480.00       | 51.6 PK                       | 74.0              | -22.4          | 1.05 H                   | 344                        | 49.70                  | 1.90                           |
| 2                                                   | #3480.00       | 47.8 AV                       | 54.0              | -6.2           | 1.05 H                   | 344                        | 45.90                  | 1.90                           |
| 3                                                   | 5150.00        | 66.6 PK                       | 74.0              | -7.4           | 1.58 H                   | 157                        | 60.60                  | 6.00                           |
| 4                                                   | 5150.00        | 52.3 AV                       | 54.0              | -1.7           | 1.58 H                   | 157                        | 46.30                  | 6.00                           |
| 5                                                   | *5180.00       | 119.6 PK                      |                   |                | 1.59 H                   | 154                        | 80.20                  | 39.40                          |
| 6                                                   | *5180.00       | 108.4 AV                      |                   |                | 1.59 H                   | 154                        | 69.00                  | 39.40                          |
| 7                                                   | #6904.00       | 59.7 PK                       | 68.2              | -8.5           | 1.51 H                   | 340                        | 46.80                  | 12.90                          |
| 8                                                   | #10360.00      | 60.8 PK                       | 74.0              | -13.2          | 3.30 H                   | 156                        | 43.00                  | 17.80                          |
| 9                                                   | #10360.00      | 48.1 AV                       | 54.0              | -5.9           | 3.30 H                   | 156                        | 30.30                  | 17.80                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | #3480.00       | 47.6 PK                       | 74.0              | -26.4          | 1.52 V                   | 36                         | 45.70                  | 1.90                           |
| 2                                                   | #3480.00       | 40.7 AV                       | 54.0              | -13.3          | 1.52 V                   | 36                         | 38.80                  | 1.90                           |
| 3                                                   | 5150.00        | 57.7 PK                       | 74.0              | -16.3          | 1.34 V                   | 29                         | 51.70                  | 6.00                           |
| 4                                                   | 5150.00        | 45.5 AV                       | 54.0              | -8.5           | 1.34 V                   | 29                         | 39.50                  | 6.00                           |
| 5                                                   | *5180.00       | 112.3 PK                      |                   |                | 1.46 V                   | 23                         | 72.90                  | 39.40                          |
| 6                                                   | *5180.00       | 101.8 AV                      |                   |                | 1.46 V                   | 23                         | 62.40                  | 39.40                          |
| 7                                                   | #6906.00       | 56.0 PK                       | 68.2              | -12.2          | 2.52 V                   | 303                        | 43.10                  | 12.90                          |
| 8                                                   | #10360.00      | 58.8 PK                       | 74.0              | -15.2          | 2.21 V                   | 213                        | 41.00                  | 17.80                          |
| 9                                                   | #10360.00      | 47.0 AV                       | 54.0              | -7.0           | 2.21 V                   | 213                        | 29.20                  | 17.80                          |

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)  
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

|                 |               |                      |              |
|-----------------|---------------|----------------------|--------------|
| CHANNEL         | TX Channel 40 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 40GHz  |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 5150.00        | 67.8 PK                       | 74.0              | -6.2           | 1.82 H                   | 170                        | 61.80                  | 6.00                           |
| 2                                                   | 5150.00        | 50.1 AV                       | 54.0              | -3.9           | 1.82 H                   | 170                        | 44.10                  | 6.00                           |
| 3                                                   | *5200.00       | 123.6 PK                      |                   |                | 1.77 H                   | 135                        | 84.10                  | 39.50                          |
| 4                                                   | *5200.00       | 113.0 AV                      |                   |                | 1.77 H                   | 135                        | 73.50                  | 39.50                          |
| 5                                                   | #6933.00       | 58.7 PK                       | 68.2              | -9.5           | 2.25 H                   | 145                        | 45.60                  | 13.10                          |
| 6                                                   | #10400.00      | 60.3 PK                       | 74.0              | -13.7          | 1.80 H                   | 162                        | 42.60                  | 17.70                          |
| 7                                                   | #10400.00      | 47.9 AV                       | 54.0              | -6.1           | 1.80 H                   | 162                        | 30.20                  | 17.70                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 5150.00        | 60.8 PK                       | 74.0              | -13.2          | 1.95 V                   | 38                         | 54.80                  | 6.00                           |
| 2                                                   | 5150.00        | 45.1 AV                       | 54.0              | -8.9           | 1.95 V                   | 38                         | 39.10                  | 6.00                           |
| 3                                                   | *5200.00       | 116.0 PK                      |                   |                | 1.96 V                   | 348                        | 76.50                  | 39.50                          |
| 4                                                   | *5200.00       | 105.6 AV                      |                   |                | 1.96 V                   | 348                        | 66.10                  | 39.50                          |
| 5                                                   | #6933.00       | 54.7 PK                       | 68.2              | -13.5          | 1.68 V                   | 58                         | 41.60                  | 13.10                          |
| 6                                                   | #10400.00      | 59.7 PK                       | 74.0              | -14.3          | 2.41 V                   | 85                         | 42.00                  | 17.70                          |
| 7                                                   | #10400.00      | 46.3 AV                       | 54.0              | -7.7           | 2.41 V                   | 85                         | 28.60                  | 17.70                          |

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)  
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

|                 |               |                      |              |
|-----------------|---------------|----------------------|--------------|
| CHANNEL         | TX Channel 48 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 40GHz  |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *5240.00       | 124.5 PK                      |                   |                | 1.66 H                   | 147                        | 84.90                  | 39.60                          |
| 2                                                   | *5240.00       | 113.4 AV                      |                   |                | 1.66 H                   | 147                        | 73.80                  | 39.60                          |
| 3                                                   | 5350.00        | 57.6 PK                       | 74.0              | -16.4          | 1.74 H                   | 238                        | 51.10                  | 6.50                           |
| 4                                                   | 5350.00        | 45.1 AV                       | 54.0              | -8.9           | 1.74 H                   | 238                        | 38.60                  | 6.50                           |
| 5                                                   | #6986.00       | 57.0 PK                       | 68.2              | -11.2          | 2.26 H                   | 151                        | 43.50                  | 13.50                          |
| 6                                                   | #10480.00      | 64.1 PK                       | 74.0              | -9.9           | 1.65 H                   | 307                        | 45.40                  | 18.70                          |
| 7                                                   | #10480.00      | 51.2 AV                       | 54.0              | -2.8           | 1.65 H                   | 307                        | 32.50                  | 18.70                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *5240.00       | 115.5 PK                      |                   |                | 1.96 V                   | 349                        | 75.90                  | 39.60                          |
| 2                                                   | *5240.00       | 104.8 AV                      |                   |                | 1.96 V                   | 349                        | 65.20                  | 39.60                          |
| 3                                                   | 5350.00        | 57.6 PK                       | 74.0              | -16.4          | 2.05 V                   | 331                        | 51.10                  | 6.50                           |
| 4                                                   | 5350.00        | 44.7 AV                       | 54.0              | -9.3           | 2.05 V                   | 331                        | 38.20                  | 6.50                           |
| 5                                                   | #6986.00       | 55.7 PK                       | 68.2              | -12.5          | 1.78 V                   | 99                         | 42.20                  | 13.50                          |
| 6                                                   | #10480.00      | 60.0 PK                       | 74.0              | -14.0          | 1.88 V                   | 320                        | 41.30                  | 18.70                          |
| 7                                                   | #10480.00      | 47.8 AV                       | 54.0              | -6.2           | 1.88 V                   | 320                        | 29.10                  | 18.70                          |

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)  
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

|                 |                |                      |              |
|-----------------|----------------|----------------------|--------------|
| CHANNEL         | TX Channel 149 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 40GHz   |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | #5651.20       | 57.9 PK                       | 69.1              | -11.2          | 1.56 H                   | 150                        | 50.80                  | 7.10                           |
| 2                                                   | *5745.00       | 124.1 PK                      |                   |                | 1.56 H                   | 150                        | 83.60                  | 40.50                          |
| 3                                                   | *5745.00       | 113.6 AV                      |                   |                | 1.56 H                   | 150                        | 73.10                  | 40.50                          |
| 4                                                   | #5980.00       | 59.2 PK                       | 68.2              | -9.0           | 1.56 H                   | 150                        | 51.30                  | 7.90                           |
| 5                                                   | 11490.00       | 61.9 PK                       | 74.0              | -12.1          | 2.36 H                   | 354                        | 43.20                  | 18.70                          |
| 6                                                   | 11490.00       | 49.4 AV                       | 54.0              | -4.6           | 2.36 H                   | 354                        | 30.70                  | 18.70                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | #5630.40       | 59.0 PK                       | 68.2              | -9.2           | 3.32 V                   | 237                        | 51.90                  | 7.10                           |
| 2                                                   | *5745.00       | 115.2 PK                      |                   |                | 3.32 V                   | 292                        | 74.70                  | 40.50                          |
| 3                                                   | *5745.00       | 105.0 AV                      |                   |                | 3.32 V                   | 292                        | 64.50                  | 40.50                          |
| 4                                                   | #5994.40       | 61.0 PK                       | 68.2              | -7.2           | 3.32 V                   | 237                        | 53.10                  | 7.90                           |
| 5                                                   | 11490.00       | 58.6 PK                       | 74.0              | -15.4          | 2.84 V                   | 49                         | 39.90                  | 18.70                          |
| 6                                                   | 11490.00       | 46.2 AV                       | 54.0              | -7.8           | 2.84 V                   | 49                         | 27.50                  | 18.70                          |

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)  
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

|                 |                |                      |              |
|-----------------|----------------|----------------------|--------------|
| CHANNEL         | TX Channel 157 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 40GHz   |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | #5617.60       | 59.2 PK                       | 68.2              | -9.0           | 1.49 H                   | 143                        | 52.10                  | 7.10                           |
| 2                                                   | *5785.00       | 122.2 PK                      |                   |                | 1.49 H                   | 143                        | 81.60                  | 40.60                          |
| 3                                                   | *5785.00       | 111.9 AV                      |                   |                | 1.49 H                   | 143                        | 71.30                  | 40.60                          |
| 4                                                   | #5965.60       | 60.3 PK                       | 68.2              | -7.9           | 1.49 H                   | 143                        | 52.50                  | 7.80                           |
| 5                                                   | 11570.00       | 61.8 PK                       | 74.0              | -12.2          | 2.63 H                   | 307                        | 43.10                  | 18.70                          |
| 6                                                   | 11570.00       | 49.0 AV                       | 54.0              | -5.0           | 2.63 H                   | 307                        | 30.30                  | 18.70                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | #5617.60       | 59.7 PK                       | 68.2              | -8.5           | 3.37 V                   | 306                        | 52.60                  | 7.10                           |
| 2                                                   | *5785.00       | 114.5 PK                      |                   |                | 3.37 V                   | 306                        | 73.90                  | 40.60                          |
| 3                                                   | *5785.00       | 104.0 AV                      |                   |                | 3.37 V                   | 306                        | 63.40                  | 40.60                          |
| 4                                                   | #5930.40       | 60.7 PK                       | 68.2              | -7.5           | 3.37 V                   | 306                        | 53.00                  | 7.70                           |
| 5                                                   | 11570.00       | 59.6 PK                       | 74.0              | -14.4          | 2.98 V                   | 254                        | 40.90                  | 18.70                          |
| 6                                                   | 11570.00       | 46.9 AV                       | 54.0              | -7.1           | 2.98 V                   | 254                        | 28.20                  | 18.70                          |

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)  
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

|                 |                |                      |              |
|-----------------|----------------|----------------------|--------------|
| CHANNEL         | TX Channel 165 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 40GHz   |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | #5608.80       | 59.4 PK                       | 68.2              | -8.8           | 2.46 H                   | 175                        | 52.30                  | 7.10                           |
| 2                                                   | *5825.00       | 121.2 PK                      |                   |                | 2.46 H                   | 175                        | 80.60                  | 40.60                          |
| 3                                                   | *5825.00       | 111.1 AV                      |                   |                | 2.46 H                   | 175                        | 70.50                  | 40.60                          |
| 4                                                   | #5969.60       | 60.8 PK                       | 68.2              | -7.4           | 2.46 H                   | 175                        | 53.00                  | 7.80                           |
| 5                                                   | 11650.00       | 66.9 PK                       | 74.0              | -7.1           | 2.41 H                   | 338                        | 47.70                  | 19.20                          |
| 6                                                   | 11650.00       | 52.7 AV                       | 54.0              | -1.3           | 2.41 H                   | 338                        | 33.50                  | 19.20                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | #5632.80       | 59.4 PK                       | 68.2              | -8.8           | 3.38 V                   | 71                         | 52.30                  | 7.10                           |
| 2                                                   | *5825.00       | 112.8 PK                      |                   |                | 3.38 V                   | 71                         | 72.20                  | 40.60                          |
| 3                                                   | *5825.00       | 102.2 AV                      |                   |                | 3.38 V                   | 71                         | 61.60                  | 40.60                          |
| 4                                                   | #5933.60       | 60.9 PK                       | 68.2              | -7.3           | 3.38 V                   | 71                         | 53.20                  | 7.70                           |
| 5                                                   | 11650.00       | 62.2 PK                       | 74.0              | -11.8          | 3.00 V                   | 254                        | 43.00                  | 19.20                          |
| 6                                                   | 11650.00       | 48.6 AV                       | 54.0              | -5.4           | 3.00 V                   | 254                        | 29.40                  | 19.20                          |

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)  
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

# 802.11n (HT20)

|                 |               |          |              |
|-----------------|---------------|----------|--------------|
| CHANNEL         | TX Channel 36 | DETECTOR | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 40GHz  | FUNCTION | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |             |                         |                |             |                    |                      |                  |                          |
|-----------------------------------------------------|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO.                                                 | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1                                                   | 5150.00     | 64.5 PK                 | 74.0           | -9.5        | 1.70 H             | 172                  | 58.50            | 6.00                     |
| 2                                                   | 5150.00     | 52.5 AV                 | 54.0           | -1.5        | 1.70 H             | 172                  | 46.50            | 6.00                     |
| 3                                                   | *5180.00    | 119.3 PK                |                |             | 1.63 H             | 145                  | 79.90            | 39.40                    |
| 4                                                   | *5180.00    | 108.9 AV                |                |             | 1.63 H             | 145                  | 69.50            | 39.40                    |
| 5                                                   | #6906.00    | 58.0 PK                 | 68.2           | -10.2       | 2.30 H             | 146                  | 45.10            | 12.90                    |
| 6                                                   | #10360.00   | 59.7 PK                 | 74.0           | -14.3       | 1.45 H             | 224                  | 41.90            | 17.80                    |
| 7                                                   | #10360.00   | 47.1 AV                 | 54.0           | -6.9        | 1.45 H             | 224                  | 29.30            | 17.80                    |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |             |                         |                |             |                    |                      |                  |                          |
| NO.                                                 | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1                                                   | 5150.00     | 60.3 PK                 | 74.0           | -13.7       | 1.72 V             | 313                  | 54.30            | 6.00                     |
| 2                                                   | 5150.00     | 46.5 AV                 | 54.0           | -7.5        | 1.72 V             | 313                  | 40.50            | 6.00                     |
| 3                                                   | *5180.00    | 109.9 PK                |                |             | 2.44 V             | 269                  | 70.50            | 39.40                    |
| 4                                                   | *5180.00    | 98.9 AV                 |                |             | 2.44 V             | 269                  | 59.50            | 39.40                    |
| 5                                                   | #6906.00    | 55.9 PK                 | 68.2           | -12.3       | 2.51 V             | 235                  | 43.00            | 12.90                    |
| 6                                                   | #10360.00   | 59.7 PK                 | 74.0           | -14.3       | 2.24 V             | 325                  | 41.90            | 17.80                    |
| 7                                                   | #10360.00   | 46.6 AV                 | 54.0           | -7.4        | 2.24 V             | 325                  | 28.80            | 17.80                    |

## REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)  
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

|                 |               |                      |              |
|-----------------|---------------|----------------------|--------------|
| CHANNEL         | TX Channel 40 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 40GHz  |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 5150.00        | 68.2 PK                       | 74.0              | -5.8           | 1.63 H                   | 156                        | 62.20                  | 6.00                           |
| 2                                                   | 5150.00        | 51.0 AV                       | 54.0              | -3.0           | 1.63 H                   | 156                        | 45.00                  | 6.00                           |
| 3                                                   | *5200.00       | 123.0 PK                      |                   |                | 1.68 H                   | 148                        | 83.50                  | 39.50                          |
| 4                                                   | *5200.00       | 112.8 AV                      |                   |                | 1.68 H                   | 148                        | 73.30                  | 39.50                          |
| 5                                                   | #6933.00       | 58.4 PK                       | 68.2              | -9.8           | 2.29 H                   | 144                        | 45.30                  | 13.10                          |
| 6                                                   | #10400.00      | 60.0 PK                       | 74.0              | -14.0          | 1.68 H                   | 173                        | 42.30                  | 17.70                          |
| 7                                                   | #10400.00      | 47.3 AV                       | 54.0              | -6.7           | 1.68 H                   | 173                        | 29.60                  | 17.70                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 5150.00        | 60.4 PK                       | 74.0              | -13.6          | 1.87 V                   | 315                        | 54.40                  | 6.00                           |
| 2                                                   | 5150.00        | 45.7 AV                       | 54.0              | -8.3           | 1.87 V                   | 315                        | 39.70                  | 6.00                           |
| 3                                                   | *5200.00       | 116.5 PK                      |                   |                | 1.66 V                   | 128                        | 77.00                  | 39.50                          |
| 4                                                   | *5200.00       | 105.7 AV                      |                   |                | 1.66 V                   | 128                        | 66.20                  | 39.50                          |
| 5                                                   | #6933.00       | 54.6 PK                       | 68.2              | -13.6          | 2.10 V                   | 168                        | 41.50                  | 13.10                          |
| 6                                                   | #10400.00      | 59.5 PK                       | 74.0              | -14.5          | 1.68 V                   | 62                         | 41.80                  | 17.70                          |
| 7                                                   | #10400.00      | 46.2 AV                       | 54.0              | -7.8           | 1.68 V                   | 62                         | 28.50                  | 17.70                          |

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)  
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

|                 |               |                      |              |
|-----------------|---------------|----------------------|--------------|
| CHANNEL         | TX Channel 48 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 40GHz  |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *5240.00       | 123.7 PK                      |                   |                | 1.76 H                   | 135                        | 84.10                  | 39.60                          |
| 2                                                   | *5240.00       | 112.9 AV                      |                   |                | 1.76 H                   | 135                        | 73.30                  | 39.60                          |
| 3                                                   | 5350.00        | 57.7 PK                       | 74.0              | -16.3          | 1.65 H                   | 222                        | 51.20                  | 6.50                           |
| 4                                                   | 5350.00        | 44.8 AV                       | 54.0              | -9.2           | 1.65 H                   | 222                        | 38.30                  | 6.50                           |
| 5                                                   | #6986.00       | 57.7 PK                       | 68.2              | -10.5          | 2.27 H                   | 10                         | 44.20                  | 13.50                          |
| 6                                                   | #10480.00      | 62.8 PK                       | 74.0              | -11.2          | 1.75 H                   | 217                        | 44.10                  | 18.70                          |
| 7                                                   | #10480.00      | 49.9 AV                       | 54.0              | -4.1           | 1.75 H                   | 217                        | 31.20                  | 18.70                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *5240.00       | 112.2 PK                      |                   |                | 2.55 V                   | 311                        | 72.60                  | 39.60                          |
| 2                                                   | *5240.00       | 102.5 AV                      |                   |                | 2.55 V                   | 311                        | 62.90                  | 39.60                          |
| 3                                                   | 5350.00        | 57.2 PK                       | 74.0              | -16.8          | 1.97 V                   | 85                         | 50.70                  | 6.50                           |
| 4                                                   | 5350.00        | 44.5 AV                       | 54.0              | -9.5           | 1.97 V                   | 85                         | 38.00                  | 6.50                           |
| 5                                                   | #6986.00       | 55.5 PK                       | 68.2              | -12.7          | 2.84 V                   | 193                        | 42.00                  | 13.50                          |
| 6                                                   | #10480.00      | 60.5 PK                       | 74.0              | -13.5          | 1.75 V                   | 117                        | 41.80                  | 18.70                          |
| 7                                                   | #10480.00      | 47.7 AV                       | 54.0              | -6.3           | 1.75 V                   | 117                        | 29.00                  | 18.70                          |

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)  
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

|                 |                |                      |              |
|-----------------|----------------|----------------------|--------------|
| CHANNEL         | TX Channel 149 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 40GHz   |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | #5641.60       | 58.6 PK                       | 68.2              | -9.6           | 2.55 H                   | 165                        | 51.50                  | 7.10                           |
| 2                                                   | *5745.00       | 123.0 PK                      |                   |                | 2.55 H                   | 165                        | 82.50                  | 40.50                          |
| 3                                                   | *5745.00       | 112.2 AV                      |                   |                | 2.55 H                   | 165                        | 71.70                  | 40.50                          |
| 4                                                   | #5999.20       | 60.5 PK                       | 68.2              | -7.7           | 2.55 H                   | 165                        | 52.60                  | 7.90                           |
| 5                                                   | 11490.00       | 61.0 PK                       | 74.0              | -13.0          | 2.53 H                   | 346                        | 42.30                  | 18.70                          |
| 6                                                   | 11490.00       | 48.8 AV                       | 54.0              | -5.2           | 2.53 H                   | 346                        | 30.10                  | 18.70                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | #5601.60       | 59.4 PK                       | 68.2              | -8.8           | 3.33 V                   | 292                        | 52.30                  | 7.10                           |
| 2                                                   | *5745.00       | 116.0 PK                      |                   |                | 3.33 V                   | 292                        | 75.50                  | 40.50                          |
| 3                                                   | *5745.00       | 104.8 AV                      |                   |                | 3.33 V                   | 292                        | 64.30                  | 40.50                          |
| 4                                                   | #5979.20       | 59.9 PK                       | 68.2              | -8.3           | 3.33 V                   | 292                        | 52.00                  | 7.90                           |
| 5                                                   | 11490.00       | 59.9 PK                       | 74.0              | -14.1          | 2.56 V                   | 142                        | 41.20                  | 18.70                          |
| 6                                                   | 11490.00       | 47.1 AV                       | 54.0              | -6.9           | 2.56 V                   | 142                        | 28.40                  | 18.70                          |

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)  
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

|                 |                |                      |              |
|-----------------|----------------|----------------------|--------------|
| CHANNEL         | TX Channel 157 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 40GHz   |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | #5615.20       | 59.4 PK                       | 68.2              | -8.8           | 2.08 H                   | 164                        | 52.30                  | 7.10                           |
| 2                                                   | *5785.00       | 122.8 PK                      |                   |                | 2.08 H                   | 164                        | 82.20                  | 40.60                          |
| 3                                                   | *5785.00       | 112.7 AV                      |                   |                | 2.08 H                   | 164                        | 72.10                  | 40.60                          |
| 4                                                   | #5976.00       | 60.5 PK                       | 68.2              | -7.7           | 2.08 H                   | 164                        | 52.60                  | 7.90                           |
| 5                                                   | 11570.00       | 62.9 PK                       | 74.0              | -11.1          | 2.55 H                   | 346                        | 44.20                  | 18.70                          |
| 6                                                   | 11570.00       | 49.8 AV                       | 54.0              | -4.2           | 2.55 H                   | 346                        | 31.10                  | 18.70                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | #5629.60       | 59.3 PK                       | 68.2              | -8.9           | 3.36 V                   | 289                        | 52.20                  | 7.10                           |
| 2                                                   | *5785.00       | 113.9 PK                      |                   |                | 3.36 V                   | 289                        | 73.30                  | 40.60                          |
| 3                                                   | *5785.00       | 103.3 AV                      |                   |                | 3.36 V                   | 289                        | 62.70                  | 40.60                          |
| 4                                                   | #5960.80       | 60.7 PK                       | 68.2              | -7.5           | 3.36 V                   | 289                        | 53.00                  | 7.70                           |
| 5                                                   | 11570.00       | 60.5 PK                       | 74.0              | -13.5          | 2.05 V                   | 157                        | 41.80                  | 18.70                          |
| 6                                                   | 11570.00       | 47.6 AV                       | 54.0              | -6.4           | 2.05 V                   | 157                        | 28.90                  | 18.70                          |

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)  
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

|                 |                |                      |              |
|-----------------|----------------|----------------------|--------------|
| CHANNEL         | TX Channel 165 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 40GHz   |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | #5600.80       | 59.9 PK                       | 68.2              | -8.3           | 2.45 H                   | 174                        | 52.80                  | 7.10                           |
| 2                                                   | *5825.00       | 121.6 PK                      |                   |                | 2.45 H                   | 174                        | 81.00                  | 40.60                          |
| 3                                                   | *5825.00       | 111.2 AV                      |                   |                | 2.45 H                   | 174                        | 70.60                  | 40.60                          |
| 4                                                   | #5998.40       | 61.3 PK                       | 68.2              | -6.9           | 2.45 H                   | 174                        | 53.40                  | 7.90                           |
| 5                                                   | 11650.00       | 66.5 PK                       | 74.0              | -7.5           | 2.41 H                   | 339                        | 47.30                  | 19.20                          |
| 6                                                   | 11650.00       | 52.7 AV                       | 54.0              | -1.3           | 2.41 H                   | 339                        | 33.50                  | 19.20                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | #5620.00       | 59.7 PK                       | 68.2              | -8.5           | 3.23 V                   | 64                         | 52.60                  | 7.10                           |
| 2                                                   | *5825.00       | 112.3 PK                      |                   |                | 3.23 V                   | 64                         | 71.70                  | 40.60                          |
| 3                                                   | *5825.00       | 101.2 AV                      |                   |                | 3.23 V                   | 64                         | 60.60                  | 40.60                          |
| 4                                                   | #5950.40       | 61.0 PK                       | 68.2              | -7.2           | 3.23 V                   | 64                         | 53.30                  | 7.70                           |
| 5                                                   | 11650.00       | 60.8 PK                       | 74.0              | -13.2          | 2.74 V                   | 168                        | 41.60                  | 19.20                          |
| 6                                                   | 11650.00       | 47.9 AV                       | 54.0              | -6.1           | 2.74 V                   | 168                        | 28.70                  | 19.20                          |

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)  
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

# 802.11n (HT40)

|                 |               |                   |              |
|-----------------|---------------|-------------------|--------------|
| CHANNEL         | TX Channel 38 | DETECTOR FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 40GHz  |                   | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |             |                         |                |             |                    |                      |                  |                          |
|-----------------------------------------------------|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO.                                                 | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1                                                   | 5150.00     | 65.2 PK                 | 74.0           | -8.8        | 1.66 H             | 148                  | 59.20            | 6.00                     |
| 2                                                   | 5150.00     | 52.2 AV                 | 54.0           | -1.8        | 1.66 H             | 148                  | 46.20            | 6.00                     |
| 3                                                   | *5190.00    | 112.9 PK                |                |             | 1.51 H             | 153                  | 73.50            | 39.40                    |
| 4                                                   | *5190.00    | 103.1 AV                |                |             | 1.51 H             | 153                  | 63.70            | 39.40                    |
| 5                                                   | #6920.00    | 57.4 PK                 | 68.2           | -10.8       | 1.56 H             | 339                  | 44.40            | 13.00                    |
| 6                                                   | #10380.00   | 59.3 PK                 | 74.0           | -14.7       | 1.77 H             | 86                   | 41.60            | 17.70                    |
| 7                                                   | #10380.00   | 46.3 AV                 | 54.0           | -7.7        | 1.77 H             | 86                   | 28.60            | 17.70                    |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |             |                         |                |             |                    |                      |                  |                          |
| NO.                                                 | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1                                                   | 5150.00     | 65.2 PK                 | 74.0           | -8.8        | 2.56 V             | 357                  | 59.20            | 6.00                     |
| 2                                                   | 5150.00     | 51.2 AV                 | 54.0           | -2.8        | 2.56 V             | 357                  | 45.20            | 6.00                     |
| 3                                                   | *5190.00    | 103.6 PK                |                |             | 2.56 V             | 262                  | 64.20            | 39.40                    |
| 4                                                   | *5190.00    | 93.7 AV                 |                |             | 2.56 V             | 262                  | 54.30            | 39.40                    |
| 5                                                   | #6920.00    | 55.4 PK                 | 68.2           | -12.8       | 2.87 V             | 119                  | 42.40            | 13.00                    |
| 6                                                   | #10380.00   | 59.3 PK                 | 74.0           | -14.7       | 2.54 V             | 211                  | 41.60            | 17.70                    |
| 7                                                   | #10380.00   | 46.3 AV                 | 54.0           | -7.7        | 2.54 V             | 211                  | 28.60            | 17.70                    |

## REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)  
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

|                 |               |                      |              |
|-----------------|---------------|----------------------|--------------|
| CHANNEL         | TX Channel 46 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 40GHz  |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 5150.00        | 65.7 PK                       | 74.0              | -8.3           | 1.78 H                   | 148                        | 59.70                  | 6.00                           |
| 2                                                   | 5150.00        | 52.6 AV                       | 54.0              | -1.4           | 1.78 H                   | 148                        | 46.60                  | 6.00                           |
| 3                                                   | *5230.00       | 119.5 PK                      |                   |                | 1.68 H                   | 169                        | 79.90                  | 39.60                          |
| 4                                                   | *5230.00       | 109.1 AV                      |                   |                | 1.68 H                   | 169                        | 69.50                  | 39.60                          |
| 5                                                   | #6973.00       | 58.4 PK                       | 68.2              | -9.8           | 1.59 H                   | 13                         | 44.90                  | 13.50                          |
| 6                                                   | #10460.00      | 60.6 PK                       | 74.0              | -13.4          | 2.35 H                   | 165                        | 42.10                  | 18.50                          |
| 7                                                   | #10460.00      | 48.5 AV                       | 54.0              | -5.5           | 2.35 H                   | 165                        | 30.00                  | 18.50                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 5150.00        | 61.4 PK                       | 74.0              | -12.6          | 2.99 V                   | 297                        | 55.40                  | 6.00                           |
| 2                                                   | 5150.00        | 46.5 AV                       | 54.0              | -7.5           | 2.99 V                   | 297                        | 40.50                  | 6.00                           |
| 3                                                   | *5230.00       | 111.5 PK                      |                   |                | 3.17 V                   | 71                         | 71.90                  | 39.60                          |
| 4                                                   | *5230.00       | 101.4 AV                      |                   |                | 3.17 V                   | 71                         | 61.80                  | 39.60                          |
| 5                                                   | #6973.00       | 55.8 PK                       | 68.2              | -12.4          | 2.63 V                   | 154                        | 42.30                  | 13.50                          |
| 6                                                   | #10460.00      | 59.9 PK                       | 74.0              | -14.1          | 2.21 V                   | 73                         | 41.40                  | 18.50                          |
| 7                                                   | #10460.00      | 46.6 AV                       | 54.0              | -7.4           | 2.21 V                   | 73                         | 28.10                  | 18.50                          |

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)  
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

|                 |                |                      |              |
|-----------------|----------------|----------------------|--------------|
| CHANNEL         | TX Channel 151 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 40GHz   |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | #5641.60       | 61.7 PK                       | 68.2              | -6.5           | 1.58 H                   | 150                        | 54.60                  | 7.10                           |
| 2                                                   | #5650.00       | 66.6 PK                       | 68.2              | -1.6           | 1.61 H                   | 182                        | 59.50                  | 7.10                           |
| 3                                                   | *5755.00       | 120.3 PK                      |                   |                | 1.58 H                   | 150                        | 79.70                  | 40.60                          |
| 4                                                   | *5755.00       | 110.7 AV                      |                   |                | 1.58 H                   | 150                        | 70.10                  | 40.60                          |
| 5                                                   | #5930.40       | 59.9 PK                       | 68.2              | -8.3           | 1.58 H                   | 150                        | 52.20                  | 7.70                           |
| 6                                                   | 11510.00       | 61.8 PK                       | 74.0              | -12.2          | 2.46 H                   | 289                        | 43.10                  | 18.70                          |
| 7                                                   | 11510.00       | 49.0 AV                       | 54.0              | -5.0           | 2.46 H                   | 289                        | 30.30                  | 18.70                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | #5615.20       | 59.4 PK                       | 68.2              | -8.8           | 3.16 V                   | 296                        | 52.30                  | 7.10                           |
| 2                                                   | *5755.00       | 111.1 PK                      |                   |                | 3.16 V                   | 296                        | 70.50                  | 40.60                          |
| 3                                                   | *5755.00       | 101.6 AV                      |                   |                | 3.16 V                   | 296                        | 61.00                  | 40.60                          |
| 4                                                   | #5979.20       | 60.7 PK                       | 68.2              | -7.5           | 3.16 V                   | 296                        | 52.80                  | 7.90                           |
| 5                                                   | 11510.00       | 60.1 PK                       | 74.0              | -13.9          | 2.96 V                   | 54                         | 41.40                  | 18.70                          |
| 6                                                   | 11510.00       | 47.2 AV                       | 54.0              | -6.8           | 2.96 V                   | 54                         | 28.50                  | 18.70                          |

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)  
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

|                 |                |                      |              |
|-----------------|----------------|----------------------|--------------|
| CHANNEL         | TX Channel 159 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 40GHz   |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | #5616.00       | 60.5 PK                       | 68.2              | -7.7           | 2.37 H                   | 173                        | 53.40                  | 7.10                           |
| 2                                                   | *5795.00       | 121.6 PK                      |                   |                | 2.37 H                   | 173                        | 81.00                  | 40.60                          |
| 3                                                   | *5795.00       | 111.6 AV                      |                   |                | 2.37 H                   | 173                        | 71.00                  | 40.60                          |
| 4                                                   | #5931.20       | 61.9 PK                       | 68.2              | -6.3           | 2.37 H                   | 173                        | 54.20                  | 7.70                           |
| 5                                                   | 11590.00       | 60.8 PK                       | 74.0              | -13.2          | 2.45 H                   | 337                        | 42.00                  | 18.80                          |
| 6                                                   | 11590.00       | 50.7 AV                       | 54.0              | -3.3           | 2.45 H                   | 337                        | 31.90                  | 18.80                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | #5603.20       | 60.1 PK                       | 68.2              | -8.1           | 3.14 V                   | 294                        | 53.00                  | 7.10                           |
| 2                                                   | *5795.00       | 112.6 PK                      |                   |                | 3.14 V                   | 294                        | 72.00                  | 40.60                          |
| 3                                                   | *5795.00       | 102.9 AV                      |                   |                | 3.14 V                   | 294                        | 62.30                  | 40.60                          |
| 4                                                   | #5981.60       | 60.2 PK                       | 68.2              | -8.0           | 3.14 V                   | 294                        | 52.30                  | 7.90                           |
| 5                                                   | 11590.00       | 60.3 PK                       | 74.0              | -13.7          | 2.74 V                   | 105                        | 41.50                  | 18.80                          |
| 6                                                   | 11590.00       | 47.6 AV                       | 54.0              | -6.4           | 2.74 V                   | 105                        | 28.80                  | 18.80                          |

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)  
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

## 802.11ac (VHT80)

|                 |               |          |              |
|-----------------|---------------|----------|--------------|
| CHANNEL         | TX Channel 42 | DETECTOR | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 40GHz  | FUNCTION | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 5150.00        | 65.2 PK                       | 74.0              | -8.8           | 2.16 H                   | 154                        | 59.20                  | 6.00                           |
| 2                                                   | 5150.00        | 52.5 AV                       | 54.0              | -1.5           | 2.16 H                   | 154                        | 46.50                  | 6.00                           |
| 3                                                   | *5210.00       | 107.0 PK                      |                   |                | 1.50 H                   | 153                        | 67.50                  | 39.50                          |
| 4                                                   | *5210.00       | 97.4 AV                       |                   |                | 1.50 H                   | 153                        | 57.90                  | 39.50                          |
| 5                                                   | #6946.00       | 57.5 PK                       | 68.2              | -10.7          | 1.67 H                   | 336                        | 44.20                  | 13.30                          |
| 6                                                   | #10420.00      | 59.0 PK                       | 74.0              | -15.0          | 1.75 H                   | 228                        | 41.10                  | 17.90                          |
| 7                                                   | #10420.00      | 46.6 AV                       | 54.0              | -7.4           | 1.75 H                   | 228                        | 28.70                  | 17.90                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 5150.00        | 62.2 PK                       | 74.0              | -11.8          | 1.88 V                   | 25                         | 56.20                  | 6.00                           |
| 2                                                   | 5150.00        | 49.0 AV                       | 54.0              | -5.0           | 1.88 V                   | 25                         | 43.00                  | 6.00                           |
| 3                                                   | *5210.00       | 99.3 PK                       |                   |                | 2.97 V                   | 293                        | 59.80                  | 39.50                          |
| 4                                                   | *5210.00       | 89.7 AV                       |                   |                | 2.97 V                   | 293                        | 50.20                  | 39.50                          |
| 5                                                   | #6946.00       | 55.6 PK                       | 68.2              | -12.6          | 2.05 V                   | 146                        | 42.30                  | 13.30                          |
| 6                                                   | #10420.00      | 59.5 PK                       | 74.0              | -14.5          | 2.65 V                   | 333                        | 41.60                  | 17.90                          |
| 7                                                   | #10420.00      | 46.3 AV                       | 54.0              | -7.7           | 2.65 V                   | 333                        | 28.40                  | 17.90                          |

## REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)  
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

|                 |                |                      |              |
|-----------------|----------------|----------------------|--------------|
| CHANNEL         | TX Channel 155 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 40GHz   |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | #5647.20       | 65.2 PK                       | 68.2              | -3.0           | 1.62 H                   | 151                        | 58.10                  | 7.10                           |
| 2                                                   | #5650.00       | 67.0 PK                       | 68.2              | -1.2           | 1.61 H                   | 148                        | 59.90                  | 7.10                           |
| 3                                                   | *5775.00       | 114.5 PK                      |                   |                | 1.62 H                   | 151                        | 73.90                  | 40.60                          |
| 4                                                   | *5775.00       | 104.5 AV                      |                   |                | 1.62 H                   | 151                        | 63.90                  | 40.60                          |
| 5                                                   | #5935.20       | 63.1 PK                       | 68.2              | -5.1           | 1.62 H                   | 151                        | 55.40                  | 7.70                           |
| 6                                                   | 11550.00       | 60.5 PK                       | 74.0              | -13.5          | 3.03 H                   | 206                        | 41.90                  | 18.60                          |
| 7                                                   | 11550.00       | 47.3 AV                       | 54.0              | -6.7           | 3.03 H                   | 206                        | 28.70                  | 18.60                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | #5648.00       | 61.6 PK                       | 68.2              | -6.6           | 3.40 V                   | 288                        | 54.50                  | 7.10                           |
| 2                                                   | *5775.00       | 104.7 PK                      |                   |                | 3.40 V                   | 288                        | 64.10                  | 40.60                          |
| 3                                                   | *5775.00       | 95.3 AV                       |                   |                | 3.40 V                   | 288                        | 54.70                  | 40.60                          |
| 4                                                   | #5964.80       | 60.5 PK                       | 68.2              | -7.7           | 3.40 V                   | 288                        | 52.70                  | 7.80                           |
| 5                                                   | 11550.00       | 60.7 PK                       | 74.0              | -13.3          | 1.85 V                   | 252                        | 42.10                  | 18.60                          |
| 6                                                   | 11550.00       | 47.6 AV                       | 54.0              | -6.4           | 1.85 V                   | 252                        | 29.00                  | 18.60                          |

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)  
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

# 802.11ac (VHT80+VHT80)

|                 |                   |                      |              |
|-----------------|-------------------|----------------------|--------------|
| CHANNEL         | TX Channel 42+155 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 40GHz      |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 5150.00        | 64.2 PK                       | 74.0              | -9.8           | 1.49 H                   | 175                        | 58.20                  | 6.00                           |
| 2                                                   | 5150.00        | 52.6 AV                       | 54.0              | -1.4           | 1.49 H                   | 175                        | 46.60                  | 6.00                           |
| 3                                                   | *5210.00       | 103.1 PK                      |                   |                | 1.49 H                   | 169                        | 63.60                  | 39.50                          |
| 4                                                   | *5210.00       | 93.2 AV                       |                   |                | 1.49 H                   | 169                        | 53.70                  | 39.50                          |
| 5                                                   | 5350.00        | 57.9 PK                       | 74.0              | -16.1          | 1.65 H                   | 182                        | 51.40                  | 6.50                           |
| 6                                                   | 5350.00        | 45.3 AV                       | 54.0              | -8.7           | 1.65 H                   | 182                        | 38.80                  | 6.50                           |
| 7                                                   | #5648.00       | 59.2 PK                       | 68.2              | -9.0           | 1.06 H                   | 20                         | 52.10                  | 7.10                           |
| 8                                                   | *5775.00       | 104.6 PK                      |                   |                | 1.06 H                   | 20                         | 64.00                  | 40.60                          |
| 9                                                   | *5775.00       | 94.3 AV                       |                   |                | 1.06 H                   | 20                         | 53.70                  | 40.60                          |
| 10                                                  | #5944.00       | 59.7 PK                       | 68.2              | -8.5           | 1.06 H                   | 20                         | 52.00                  | 7.70                           |
| 11                                                  | #10420.00      | 60.1 PK                       | 74.0              | -13.9          | 1.76 H                   | 331                        | 42.20                  | 17.90                          |
| 12                                                  | #10420.00      | 47.0 AV                       | 54.0              | -7.0           | 1.76 H                   | 331                        | 29.10                  | 17.90                          |
| 13                                                  | 11550.00       | 60.7 PK                       | 74.0              | -13.3          | 2.48 H                   | 256                        | 42.10                  | 18.60                          |
| 14                                                  | 11550.00       | 47.5 AV                       | 54.0              | -6.5           | 2.48 H                   | 256                        | 28.90                  | 18.60                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 5150.00        | 60.1 PK                       | 74.0              | -13.9          | 1.24 V                   | 41                         | 54.10                  | 6.00                           |
| 2                                                   | 5150.00        | 47.5 AV                       | 54.0              | -6.5           | 1.24 V                   | 41                         | 41.50                  | 6.00                           |
| 3                                                   | *5210.00       | 96.5 PK                       |                   |                | 1.24 V                   | 342                        | 57.00                  | 39.50                          |
| 4                                                   | *5210.00       | 86.8 AV                       |                   |                | 1.24 V                   | 342                        | 47.30                  | 39.50                          |
| 5                                                   | 5350.00        | 58.2 PK                       | 74.0              | -15.8          | 1.38 V                   | 49                         | 51.70                  | 6.50                           |
| 6                                                   | 5350.00        | 44.8 AV                       | 54.0              | -9.2           | 1.38 V                   | 49                         | 38.30                  | 6.50                           |
| 7                                                   | #5611.20       | 59.0 PK                       | 68.2              | -9.2           | 2.93 V                   | 111                        | 51.90                  | 7.10                           |
| 8                                                   | *5775.00       | 96.3 PK                       |                   |                | 2.93 V                   | 111                        | 55.70                  | 40.60                          |
| 9                                                   | *5775.00       | 85.9 AV                       |                   |                | 2.93 V                   | 111                        | 45.30                  | 40.60                          |
| 10                                                  | #5944.80       | 60.1 PK                       | 68.2              | -8.1           | 2.93 V                   | 111                        | 52.40                  | 7.70                           |
| 11                                                  | #10420.00      | 59.6 PK                       | 74.0              | -14.4          | 2.33 V                   | 281                        | 41.70                  | 17.90                          |
| 12                                                  | #10420.00      | 46.9 AV                       | 54.0              | -7.1           | 2.33 V                   | 281                        | 29.00                  | 17.90                          |
| 13                                                  | 11550.00       | 59.9 PK                       | 74.0              | -14.1          | 2.72 V                   | 150                        | 41.30                  | 18.60                          |
| 14                                                  | 11550.00       | 46.9 AV                       | 54.0              | -7.1           | 2.72 V                   | 150                        | 28.30                  | 18.60                          |

## REMARKS:

- Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)  
– Pre-Amplifier Factor(dB)
- The other emission levels were very low against the limit.
- Margin value = Emission Level – Limit value
- " \* ": Fundamental frequency.
- " # ": The radiated frequency is out of the restricted band.

# Test Mode C

802.11a

|                 |               |                      |              |
|-----------------|---------------|----------------------|--------------|
| CHANNEL         | TX Channel 36 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 40GHz  |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 5150.00        | 68.6 PK                       | 74.0              | -5.4           | 1.79 H                   | 286                        | 62.60                  | 6.00                           |
| 2                                                   | 5150.00        | 52.7 AV                       | 54.0              | -1.3           | 1.79 H                   | 286                        | 46.70                  | 6.00                           |
| 3                                                   | *5180.00       | 120.8 PK                      |                   |                | 1.77 H                   | 289                        | 81.40                  | 39.40                          |
| 4                                                   | *5180.00       | 110.3 AV                      |                   |                | 1.77 H                   | 289                        | 70.90                  | 39.40                          |
| 5                                                   | #10360.00      | 61.8 PK                       | 74.0              | -12.2          | 1.79 H                   | 279                        | 44.00                  | 17.80                          |
| 6                                                   | #10360.00      | 48.8 AV                       | 54.0              | -5.2           | 1.79 H                   | 279                        | 31.00                  | 17.80                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 5150.00        | 63.4 PK                       | 74.0              | -10.6          | 2.13 V                   | 352                        | 57.40                  | 6.00                           |
| 2                                                   | 5150.00        | 49.6 AV                       | 54.0              | -4.4           | 2.13 V                   | 352                        | 43.60                  | 6.00                           |
| 3                                                   | *5180.00       | 117.9 PK                      |                   |                | 3.73 V                   | 19                         | 78.50                  | 39.40                          |
| 4                                                   | *5180.00       | 107.5 AV                      |                   |                | 3.73 V                   | 19                         | 68.10                  | 39.40                          |
| 5                                                   | #10360.00      | 61.1 PK                       | 74.0              | -12.9          | 2.22 V                   | 0                          | 43.30                  | 17.80                          |
| 6                                                   | #10360.00      | 47.9 AV                       | 54.0              | -6.1           | 2.22 V                   | 0                          | 30.10                  | 17.80                          |

## REMARKS:

- Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)  
– Pre-Amplifier Factor(dB)
- The other emission levels were very low against the limit.
- Margin value = Emission Level – Limit value
- " \* ": Fundamental frequency.
- " # ": The radiated frequency is out of the restricted band.

|                 |               |                      |              |
|-----------------|---------------|----------------------|--------------|
| CHANNEL         | TX Channel 40 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 40GHz  |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *5200.00       | 124.1 PK                      |                   |                | 1.62 H                   | 291                        | 84.60                  | 39.50                          |
| 2                                                   | *5200.00       | 113.5 AV                      |                   |                | 1.62 H                   | 291                        | 74.00                  | 39.50                          |
| 3                                                   | #10400.00      | 65.5 PK                       | 74.0              | -8.5           | 1.45 H                   | 284                        | 47.80                  | 17.70                          |
| 4                                                   | #10400.00      | 52.5 AV                       | 54.0              | -1.5           | 1.45 H                   | 284                        | 34.80                  | 17.70                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *5200.00       | 121.8 PK                      |                   |                | 3.24 V                   | 358                        | 82.30                  | 39.50                          |
| 2                                                   | *5200.00       | 111.1 AV                      |                   |                | 3.24 V                   | 358                        | 71.60                  | 39.50                          |
| 3                                                   | #10400.00      | 61.0 PK                       | 74.0              | -13.0          | 3.31 V                   | 315                        | 43.30                  | 17.70                          |
| 4                                                   | #10400.00      | 48.3 AV                       | 54.0              | -5.7           | 3.31 V                   | 315                        | 30.60                  | 17.70                          |

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)  
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

|                 |               |                      |              |
|-----------------|---------------|----------------------|--------------|
| CHANNEL         | TX Channel 48 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 40GHz  |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *5240.00       | 121.0 PK                      |                   |                | 1.68 H                   | 289                        | 81.40                  | 39.60                          |
| 2                                                   | *5240.00       | 110.4 AV                      |                   |                | 1.68 H                   | 289                        | 70.80                  | 39.60                          |
| 3                                                   | 5350.00        | 48.0 PK                       | 74.0              | -26.0          | 2.01 H                   | 210                        | 41.50                  | 6.50                           |
| 4                                                   | 5350.00        | 45.9 AV                       | 54.0              | -8.1           | 2.01 H                   | 210                        | 39.40                  | 6.50                           |
| 5                                                   | #10480.00      | 67.7 PK                       | 74.0              | -6.3           | 1.61 H                   | 306                        | 49.00                  | 18.70                          |
| 6                                                   | #10480.00      | 52.8 AV                       | 54.0              | -1.2           | 1.61 H                   | 306                        | 34.10                  | 18.70                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *5240.00       | 117.1 PK                      |                   |                | 3.62 V                   | 15                         | 77.50                  | 39.60                          |
| 2                                                   | *5240.00       | 106.8 AV                      |                   |                | 3.62 V                   | 15                         | 67.20                  | 39.60                          |
| 3                                                   | 5350.00        | 59.0 PK                       | 74.0              | -15.0          | 2.85 V                   | 223                        | 52.50                  | 6.50                           |
| 4                                                   | 5350.00        | 46.1 AV                       | 54.0              | -7.9           | 2.85 V                   | 223                        | 39.60                  | 6.50                           |
| 5                                                   | #10480.00      | 60.5 PK                       | 74.0              | -13.5          | 2.01 V                   | 194                        | 41.80                  | 18.70                          |
| 6                                                   | #10480.00      | 47.8 AV                       | 54.0              | -6.2           | 2.01 V                   | 194                        | 29.10                  | 18.70                          |

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)  
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

|                 |                |                      |              |
|-----------------|----------------|----------------------|--------------|
| CHANNEL         | TX Channel 149 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 40GHz   |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | #5620.00       | 58.9 PK                       | 68.2              | -9.3           | 2.09 H                   | 54                         | 51.80                  | 7.10                           |
| 2                                                   | *5745.00       | 124.4 PK                      |                   |                | 2.09 H                   | 54                         | 83.90                  | 40.50                          |
| 3                                                   | *5745.00       | 114.1 AV                      |                   |                | 2.09 H                   | 54                         | 73.60                  | 40.50                          |
| 4                                                   | #5997.60       | 60.3 PK                       | 68.2              | -7.9           | 2.09 H                   | 54                         | 52.40                  | 7.90                           |
| 5                                                   | 11490.00       | 63.6 PK                       | 74.0              | -10.4          | 2.16 H                   | 274                        | 44.90                  | 18.70                          |
| 6                                                   | 11490.00       | 50.2 AV                       | 54.0              | -3.8           | 2.16 H                   | 274                        | 31.50                  | 18.70                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | #5619.20       | 58.4 PK                       | 68.2              | -9.8           | 2.83 V                   | 346                        | 51.30                  | 7.10                           |
| 2                                                   | *5745.00       | 117.1 PK                      |                   |                | 2.83 V                   | 346                        | 76.60                  | 40.50                          |
| 3                                                   | *5745.00       | 106.9 AV                      |                   |                | 2.83 V                   | 346                        | 66.40                  | 40.50                          |
| 4                                                   | #5963.20       | 59.4 PK                       | 68.2              | -8.8           | 2.83 V                   | 346                        | 51.60                  | 7.80                           |
| 5                                                   | 11490.00       | 61.2 PK                       | 74.0              | -12.8          | 2.31 V                   | 300                        | 42.50                  | 18.70                          |
| 6                                                   | 11490.00       | 47.8 AV                       | 54.0              | -6.2           | 2.31 V                   | 300                        | 29.10                  | 18.70                          |

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)  
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

|                 |                |                      |              |
|-----------------|----------------|----------------------|--------------|
| CHANNEL         | TX Channel 157 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 40GHz   |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | #5632.00       | 58.7 PK                       | 68.2              | -9.5           | 2.06 H                   | 52                         | 51.60                  | 7.10                           |
| 2                                                   | *5785.00       | 124.4 PK                      |                   |                | 2.06 H                   | 52                         | 83.80                  | 40.60                          |
| 3                                                   | *5785.00       | 114.3 AV                      |                   |                | 2.06 H                   | 52                         | 73.70                  | 40.60                          |
| 4                                                   | #5960.00       | 59.2 PK                       | 68.2              | -9.0           | 2.06 H                   | 52                         | 51.50                  | 7.70                           |
| 5                                                   | 11570.00       | 61.8 PK                       | 74.0              | -12.2          | 2.72 H                   | 305                        | 43.10                  | 18.70                          |
| 6                                                   | 11570.00       | 49.1 AV                       | 54.0              | -4.9           | 2.72 H                   | 305                        | 30.40                  | 18.70                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | #5624.00       | 59.1 PK                       | 68.2              | -9.1           | 3.20 V                   | 22                         | 52.00                  | 7.10                           |
| 2                                                   | *5785.00       | 117.6 PK                      |                   |                | 3.20 V                   | 22                         | 77.00                  | 40.60                          |
| 3                                                   | *5785.00       | 107.5 AV                      |                   |                | 3.20 V                   | 22                         | 66.90                  | 40.60                          |
| 4                                                   | #5996.00       | 60.5 PK                       | 68.2              | -7.7           | 3.20 V                   | 22                         | 52.60                  | 7.90                           |
| 5                                                   | 11570.00       | 61.3 PK                       | 74.0              | -12.7          | 2.56 V                   | 254                        | 42.60                  | 18.70                          |
| 6                                                   | 11570.00       | 48.1 AV                       | 54.0              | -5.9           | 2.56 V                   | 254                        | 29.40                  | 18.70                          |

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)  
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

|                 |                |                      |              |
|-----------------|----------------|----------------------|--------------|
| CHANNEL         | TX Channel 165 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 40GHz   |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | #5616.00       | 57.9 PK                       | 68.2              | -10.3          | 1.93 H                   | 60                         | 50.80                  | 7.10                           |
| 2                                                   | *5825.00       | 124.1 PK                      |                   |                | 1.93 H                   | 60                         | 83.50                  | 40.60                          |
| 3                                                   | *5825.00       | 114.1 AV                      |                   |                | 1.93 H                   | 60                         | 73.50                  | 40.60                          |
| 4                                                   | #5941.60       | 60.1 PK                       | 68.2              | -8.1           | 1.93 H                   | 60                         | 52.40                  | 7.70                           |
| 5                                                   | 11650.00       | 62.0 PK                       | 74.0              | -12.0          | 2.65 H                   | 300                        | 42.80                  | 19.20                          |
| 6                                                   | 11650.00       | 49.0 AV                       | 54.0              | -5.0           | 2.65 H                   | 300                        | 29.80                  | 19.20                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | #5632.80       | 59.4 PK                       | 68.2              | -8.8           | 3.15 V                   | 19                         | 52.30                  | 7.10                           |
| 2                                                   | *5825.00       | 118.4 PK                      |                   |                | 3.15 V                   | 19                         | 77.80                  | 40.60                          |
| 3                                                   | *5825.00       | 108.4 AV                      |                   |                | 3.15 V                   | 19                         | 67.80                  | 40.60                          |
| 4                                                   | #5971.20       | 60.3 PK                       | 68.2              | -7.9           | 3.15 V                   | 19                         | 52.50                  | 7.80                           |
| 5                                                   | 11650.00       | 62.3 PK                       | 74.0              | -11.7          | 2.33 V                   | 270                        | 43.10                  | 19.20                          |
| 6                                                   | 11650.00       | 49.2 AV                       | 54.0              | -4.8           | 2.33 V                   | 270                        | 30.00                  | 19.20                          |

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)  
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

# 802.11n (HT20)

|                 |               |          |              |
|-----------------|---------------|----------|--------------|
| CHANNEL         | TX Channel 36 | DETECTOR | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 40GHz  | FUNCTION | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |             |                         |                |             |                    |                      |                  |                          |
|-----------------------------------------------------|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO.                                                 | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1                                                   | 5150.00     | 66.8 PK                 | 74.0           | -7.2        | 2.20 H             | 280                  | 60.80            | 6.00                     |
| 2                                                   | 5150.00     | 52.5 AV                 | 54.0           | -1.5        | 2.20 H             | 280                  | 46.50            | 6.00                     |
| 3                                                   | *5180.00    | 121.9 PK                |                |             | 2.02 H             | 51                   | 82.50            | 39.40                    |
| 4                                                   | *5180.00    | 111.6 AV                |                |             | 2.02 H             | 51                   | 72.20            | 39.40                    |
| 5                                                   | #10360.00   | 63.2 PK                 | 74.0           | -10.8       | 2.17 H             | 278                  | 45.40            | 17.80                    |
| 6                                                   | #10360.00   | 49.7 AV                 | 54.0           | -4.3        | 2.17 H             | 278                  | 31.90            | 17.80                    |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |             |                         |                |             |                    |                      |                  |                          |
| NO.                                                 | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1                                                   | 5150.00     | 63.2 PK                 | 74.0           | -10.8       | 3.15 V             | 1                    | 57.20            | 6.00                     |
| 2                                                   | 5150.00     | 49.2 AV                 | 54.0           | -4.8        | 3.15 V             | 1                    | 43.20            | 6.00                     |
| 3                                                   | *5180.00    | 118.0 PK                |                |             | 3.12 V             | 1                    | 78.60            | 39.40                    |
| 4                                                   | *5180.00    | 107.5 AV                |                |             | 3.12 V             | 1                    | 68.10            | 39.40                    |
| 5                                                   | #10360.00   | 61.4 PK                 | 74.0           | -12.6       | 2.98 V             | 342                  | 43.60            | 17.80                    |
| 6                                                   | #10360.00   | 47.8 AV                 | 54.0           | -6.2        | 2.98 V             | 342                  | 30.00            | 17.80                    |

## REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

|                 |               |                      |              |
|-----------------|---------------|----------------------|--------------|
| CHANNEL         | TX Channel 40 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 40GHz  |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *5200.00       | 123.3 PK                      |                   |                | 1.59 H                   | 292                        | 83.80                  | 39.50                          |
| 2                                                   | *5200.00       | 112.5 AV                      |                   |                | 1.59 H                   | 292                        | 73.00                  | 39.50                          |
| 3                                                   | #10400.00      | 66.2 PK                       | 74.0              | -7.8           | 1.52 H                   | 285                        | 48.50                  | 17.70                          |
| 4                                                   | #10400.00      | 52.5 AV                       | 54.0              | -1.5           | 1.52 H                   | 285                        | 34.80                  | 17.70                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *5200.00       | 120.9 PK                      |                   |                | 3.23 V                   | 356                        | 81.40                  | 39.50                          |
| 2                                                   | *5200.00       | 110.4 AV                      |                   |                | 3.23 V                   | 356                        | 70.90                  | 39.50                          |
| 3                                                   | #10400.00      | 60.5 PK                       | 74.0              | -13.5          | 3.23 V                   | 21                         | 42.80                  | 17.70                          |
| 4                                                   | #10400.00      | 47.7 AV                       | 54.0              | -6.3           | 3.23 V                   | 21                         | 30.00                  | 17.70                          |

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)  
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

|                 |               |                      |              |
|-----------------|---------------|----------------------|--------------|
| CHANNEL         | TX Channel 48 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 40GHz  |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *5240.00       | 120.7 PK                      |                   |                | 1.56 H                   | 294                        | 81.10                  | 39.60                          |
| 2                                                   | *5240.00       | 110.1 AV                      |                   |                | 1.56 H                   | 294                        | 70.50                  | 39.60                          |
| 3                                                   | 5350.00        | 59.0 PK                       | 74.0              | -15.0          | 1.67 H                   | 302                        | 52.50                  | 6.50                           |
| 4                                                   | 5350.00        | 46.1 AV                       | 54.0              | -7.9           | 1.67 H                   | 302                        | 39.60                  | 6.50                           |
| 5                                                   | #10480.00      | 66.9 PK                       | 74.0              | -7.1           | 1.62 H                   | 307                        | 48.20                  | 18.70                          |
| 6                                                   | #10480.00      | 52.7 AV                       | 54.0              | -1.3           | 1.62 H                   | 307                        | 34.00                  | 18.70                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *5240.00       | 117.0 PK                      |                   |                | 2.94 V                   | 330                        | 77.40                  | 39.60                          |
| 2                                                   | *5240.00       | 106.5 AV                      |                   |                | 2.94 V                   | 330                        | 66.90                  | 39.60                          |
| 3                                                   | 5350.00        | 58.2 PK                       | 74.0              | -15.8          | 2.47 V                   | 149                        | 51.70                  | 6.50                           |
| 4                                                   | 5350.00        | 45.8 AV                       | 54.0              | -8.2           | 2.47 V                   | 149                        | 39.30                  | 6.50                           |
| 5                                                   | #10480.00      | 61.7 PK                       | 74.0              | -12.3          | 2.79 V                   | 315                        | 43.00                  | 18.70                          |
| 6                                                   | #10480.00      | 49.1 AV                       | 54.0              | -4.9           | 2.79 V                   | 315                        | 30.40                  | 18.70                          |

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)  
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

|                 |                |                      |              |
|-----------------|----------------|----------------------|--------------|
| CHANNEL         | TX Channel 149 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 40GHz   |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | #5644.80       | 59.9 PK                       | 68.2              | -8.3           | 2.20 H                   | 54                         | 52.80                  | 7.10                           |
| 2                                                   | *5745.00       | 124.0 PK                      |                   |                | 2.20 H                   | 54                         | 83.50                  | 40.50                          |
| 3                                                   | *5745.00       | 113.8 AV                      |                   |                | 2.20 H                   | 54                         | 73.30                  | 40.50                          |
| 4                                                   | #5978.40       | 61.0 PK                       | 68.2              | -7.2           | 2.20 H                   | 54                         | 53.10                  | 7.90                           |
| 5                                                   | 11490.00       | 61.3 PK                       | 74.0              | -12.7          | 2.21 H                   | 275                        | 42.60                  | 18.70                          |
| 6                                                   | 11490.00       | 48.5 AV                       | 54.0              | -5.5           | 2.21 H                   | 275                        | 29.80                  | 18.70                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | #5618.40       | 58.6 PK                       | 68.2              | -9.6           | 3.04 V                   | 0                          | 51.50                  | 7.10                           |
| 2                                                   | *5745.00       | 119.7 PK                      |                   |                | 3.49 V                   | 0                          | 79.20                  | 40.50                          |
| 3                                                   | *5745.00       | 109.2 AV                      |                   |                | 3.49 V                   | 0                          | 68.70                  | 40.50                          |
| 4                                                   | #5975.20       | 59.1 PK                       | 68.2              | -9.1           | 3.04 V                   | 0                          | 51.20                  | 7.90                           |
| 5                                                   | 11490.00       | 62.1 PK                       | 74.0              | -11.9          | 2.43 V                   | 344                        | 43.40                  | 18.70                          |
| 6                                                   | 11490.00       | 49.2 AV                       | 54.0              | -4.8           | 2.43 V                   | 344                        | 30.50                  | 18.70                          |

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)  
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

|                 |                |                      |              |
|-----------------|----------------|----------------------|--------------|
| CHANNEL         | TX Channel 157 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 40GHz   |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | #5625.60       | 59.4 PK                       | 68.2              | -8.8           | 2.12 H                   | 54                         | 52.30                  | 7.10                           |
| 2                                                   | *5785.00       | 123.5 PK                      |                   |                | 2.12 H                   | 54                         | 82.90                  | 40.60                          |
| 3                                                   | *5785.00       | 113.9 AV                      |                   |                | 2.12 H                   | 54                         | 73.30                  | 40.60                          |
| 4                                                   | #5980.80       | 60.6 PK                       | 68.2              | -7.6           | 2.12 H                   | 54                         | 52.70                  | 7.90                           |
| 5                                                   | 11570.00       | 61.4 PK                       | 74.0              | -12.6          | 2.22 H                   | 291                        | 42.70                  | 18.70                          |
| 6                                                   | 11570.00       | 48.5 AV                       | 54.0              | -5.5           | 2.22 H                   | 291                        | 29.80                  | 18.70                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | #5618.40       | 59.6 PK                       | 68.2              | -8.6           | 2.98 V                   | 322                        | 52.50                  | 7.10                           |
| 2                                                   | *5785.00       | 117.8 PK                      |                   |                | 2.98 V                   | 322                        | 77.20                  | 40.60                          |
| 3                                                   | *5785.00       | 107.1 AV                      |                   |                | 2.98 V                   | 322                        | 66.50                  | 40.60                          |
| 4                                                   | #5963.20       | 60.4 PK                       | 68.2              | -7.8           | 2.98 V                   | 322                        | 52.60                  | 7.80                           |
| 5                                                   | 11570.00       | 61.4 PK                       | 74.0              | -12.6          | 2.44 V                   | 357                        | 42.70                  | 18.70                          |
| 6                                                   | 11570.00       | 48.5 AV                       | 54.0              | -5.5           | 2.44 V                   | 357                        | 29.80                  | 18.70                          |

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)  
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

|                 |                |                      |              |
|-----------------|----------------|----------------------|--------------|
| CHANNEL         | TX Channel 165 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 40GHz   |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | #5608.00       | 59.6 PK                       | 68.2              | -8.6           | 2.09 H                   | 50                         | 52.50                  | 7.10                           |
| 2                                                   | *5825.00       | 123.5 PK                      |                   |                | 2.09 H                   | 50                         | 82.90                  | 40.60                          |
| 3                                                   | *5825.00       | 113.4 AV                      |                   |                | 2.09 H                   | 50                         | 72.80                  | 40.60                          |
| 4                                                   | #5948.00       | 60.7 PK                       | 68.2              | -7.5           | 2.09 H                   | 50                         | 53.00                  | 7.70                           |
| 5                                                   | 11650.00       | 62.2 PK                       | 74.0              | -11.8          | 2.66 H                   | 310                        | 43.00                  | 19.20                          |
| 6                                                   | 11650.00       | 49.1 AV                       | 54.0              | -4.9           | 2.66 H                   | 310                        | 29.90                  | 19.20                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | #5636.80       | 58.0 PK                       | 68.2              | -10.2          | 3.15 V                   | 345                        | 50.90                  | 7.10                           |
| 2                                                   | *5825.00       | 116.9 PK                      |                   |                | 3.15 V                   | 345                        | 76.30                  | 40.60                          |
| 3                                                   | *5825.00       | 106.8 AV                      |                   |                | 3.15 V                   | 345                        | 66.20                  | 40.60                          |
| 4                                                   | #5927.20       | 60.3 PK                       | 68.2              | -7.9           | 3.15 V                   | 345                        | 52.60                  | 7.70                           |
| 5                                                   | 11650.00       | 61.8 PK                       | 74.0              | -12.2          | 2.40 V                   | 278                        | 42.60                  | 19.20                          |
| 6                                                   | 11650.00       | 48.7 AV                       | 54.0              | -5.3           | 2.40 V                   | 278                        | 29.50                  | 19.20                          |

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)  
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

# 802.11n (HT40)

|                 |               |                      |              |
|-----------------|---------------|----------------------|--------------|
| CHANNEL         | TX Channel 38 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 40GHz  |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 5150.00        | 67.2 PK                       | 74.0              | -6.8           | 2.23 H                   | 302                        | 61.20                  | 6.00                           |
| 2                                                   | 5150.00        | 52.4 AV                       | 54.0              | -1.6           | 2.23 H                   | 302                        | 46.40                  | 6.00                           |
| 3                                                   | *5190.00       | 114.7 PK                      |                   |                | 1.70 H                   | 290                        | 75.30                  | 39.40                          |
| 4                                                   | *5190.00       | 104.7 AV                      |                   |                | 1.70 H                   | 290                        | 65.30                  | 39.40                          |
| 5                                                   | #10380.00      | 60.0 PK                       | 74.0              | -14.0          | 1.88 H                   | 290                        | 42.30                  | 17.70                          |
| 6                                                   | #10380.00      | 46.9 AV                       | 54.0              | -7.1           | 1.88 H                   | 290                        | 29.20                  | 17.70                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 5150.00        | 61.4 PK                       | 74.0              | -12.6          | 3.21 V                   | 26                         | 55.40                  | 6.00                           |
| 2                                                   | 5150.00        | 48.2 AV                       | 54.0              | -5.8           | 3.21 V                   | 26                         | 42.20                  | 6.00                           |
| 3                                                   | *5190.00       | 112.1 PK                      |                   |                | 3.23 V                   | 359                        | 72.70                  | 39.40                          |
| 4                                                   | *5190.00       | 102.7 AV                      |                   |                | 3.23 V                   | 359                        | 63.30                  | 39.40                          |
| 5                                                   | #10380.00      | 59.2 PK                       | 74.0              | -14.8          | 2.64 V                   | 291                        | 41.50                  | 17.70                          |
| 6                                                   | #10380.00      | 46.1 AV                       | 54.0              | -7.9           | 2.64 V                   | 291                        | 28.40                  | 17.70                          |

## REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)  
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

|                 |               |                      |              |
|-----------------|---------------|----------------------|--------------|
| CHANNEL         | TX Channel 46 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 40GHz  |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 5150.00        | 64.8 PK                       | 74.0              | -9.2           | 2.57 H                   | 287                        | 58.80                  | 6.00                           |
| 2                                                   | 5150.00        | 52.6 AV                       | 54.0              | -1.4           | 2.57 H                   | 287                        | 46.60                  | 6.00                           |
| 3                                                   | *5230.00       | 119.9 PK                      |                   |                | 1.49 H                   | 297                        | 80.30                  | 39.60                          |
| 4                                                   | *5230.00       | 110.4 AV                      |                   |                | 1.49 H                   | 297                        | 70.80                  | 39.60                          |
| 5                                                   | #10460.00      | 63.4 PK                       | 74.0              | -10.6          | 1.62 H                   | 308                        | 44.90                  | 18.50                          |
| 6                                                   | #10460.00      | 51.2 AV                       | 54.0              | -2.8           | 1.62 H                   | 308                        | 32.70                  | 18.50                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 5150.00        | 62.5 PK                       | 74.0              | -11.5          | 3.16 V                   | 0                          | 56.50                  | 6.00                           |
| 2                                                   | 5150.00        | 48.1 AV                       | 54.0              | -5.9           | 3.16 V                   | 0                          | 42.10                  | 6.00                           |
| 3                                                   | *5230.00       | 117.5 PK                      |                   |                | 3.21 V                   | 357                        | 77.90                  | 39.60                          |
| 4                                                   | *5230.00       | 107.8 AV                      |                   |                | 3.21 V                   | 357                        | 68.20                  | 39.60                          |
| 5                                                   | #10460.00      | 59.9 PK                       | 74.0              | -14.1          | 2.43 V                   | 282                        | 41.40                  | 18.50                          |
| 6                                                   | #10460.00      | 48.6 AV                       | 54.0              | -5.4           | 2.43 V                   | 282                        | 30.10                  | 18.50                          |

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)  
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

|                 |                |                      |              |
|-----------------|----------------|----------------------|--------------|
| CHANNEL         | TX Channel 151 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 40GHz   |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | #5651.20       | 61.9 PK                       | 69.1              | -7.2           | 2.10 H                   | 59                         | 54.80                  | 7.10                           |
| 2                                                   | *5755.00       | 120.6 PK                      |                   |                | 2.10 H                   | 59                         | 80.00                  | 40.60                          |
| 3                                                   | *5755.00       | 111.0 AV                      |                   |                | 2.10 H                   | 59                         | 70.40                  | 40.60                          |
| 4                                                   | #5978.40       | 60.7 PK                       | 68.2              | -7.5           | 2.10 H                   | 59                         | 52.80                  | 7.90                           |
| 5                                                   | 11510.00       | 62.2 PK                       | 74.0              | -11.8          | 2.23 H                   | 244                        | 43.50                  | 18.70                          |
| 6                                                   | 11510.00       | 48.9 AV                       | 54.0              | -5.1           | 2.23 H                   | 244                        | 30.20                  | 18.70                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | #5608.80       | 59.4 PK                       | 68.2              | -8.8           | 2.89 V                   | 345                        | 52.30                  | 7.10                           |
| 2                                                   | *5755.00       | 114.6 PK                      |                   |                | 2.89 V                   | 345                        | 74.00                  | 40.60                          |
| 3                                                   | *5755.00       | 106.4 AV                      |                   |                | 2.89 V                   | 345                        | 65.80                  | 40.60                          |
| 4                                                   | #5944.00       | 59.7 PK                       | 68.2              | -8.5           | 2.89 V                   | 345                        | 52.00                  | 7.70                           |
| 5                                                   | 11510.00       | 61.0 PK                       | 74.0              | -13.0          | 2.45 V                   | 293                        | 42.30                  | 18.70                          |
| 6                                                   | 11510.00       | 48.0 AV                       | 54.0              | -6.0           | 2.45 V                   | 293                        | 29.30                  | 18.70                          |

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)  
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

|                 |                |                      |              |
|-----------------|----------------|----------------------|--------------|
| CHANNEL         | TX Channel 159 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 40GHz   |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | #5633.60       | 59.2 PK                       | 68.2              | -9.0           | 2.01 H                   | 52                         | 52.10                  | 7.10                           |
| 2                                                   | *5795.00       | 120.5 PK                      |                   |                | 2.01 H                   | 52                         | 79.90                  | 40.60                          |
| 3                                                   | *5795.00       | 111.0 AV                      |                   |                | 2.01 H                   | 52                         | 70.40                  | 40.60                          |
| 4                                                   | #5944.00       | 60.0 PK                       | 68.2              | -8.2           | 2.01 H                   | 52                         | 52.30                  | 7.70                           |
| 5                                                   | 11590.00       | 61.2 PK                       | 74.0              | -12.8          | 2.28 H                   | 269                        | 42.40                  | 18.80                          |
| 6                                                   | 11590.00       | 48.5 AV                       | 54.0              | -5.5           | 2.28 H                   | 269                        | 29.70                  | 18.80                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | #5641.60       | 58.7 PK                       | 68.2              | -9.5           | 3.48 V                   | 355                        | 51.60                  | 7.10                           |
| 2                                                   | *5795.00       | 115.2 PK                      |                   |                | 3.48 V                   | 355                        | 74.60                  | 40.60                          |
| 3                                                   | *5795.00       | 105.6 AV                      |                   |                | 3.48 V                   | 355                        | 65.00                  | 40.60                          |
| 4                                                   | #5986.40       | 60.2 PK                       | 68.2              | -8.0           | 3.48 V                   | 355                        | 52.30                  | 7.90                           |
| 5                                                   | 11590.00       | 61.5 PK                       | 74.0              | -12.5          | 2.48 V                   | 266                        | 42.70                  | 18.80                          |
| 6                                                   | 11590.00       | 48.4 AV                       | 54.0              | -5.6           | 2.48 V                   | 266                        | 29.60                  | 18.80                          |

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)  
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

## 802.11ac (VHT80)

|                 |               |                      |              |
|-----------------|---------------|----------------------|--------------|
| CHANNEL         | TX Channel 42 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 40GHz  |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 5150.00        | 65.2 PK                       | 74.0              | -8.8           | 2.15 H                   | 52                         | 59.20                  | 6.00                           |
| 2                                                   | 5150.00        | 52.5 AV                       | 54.0              | -1.5           | 2.15 H                   | 52                         | 46.50                  | 6.00                           |
| 3                                                   | *5210.00       | 107.5 PK                      |                   |                | 2.44 H                   | 304                        | 68.00                  | 39.50                          |
| 4                                                   | *5210.00       | 97.6 AV                       |                   |                | 2.44 H                   | 304                        | 58.10                  | 39.50                          |
| 5                                                   | 5350.00        | 58.1 PK                       | 74.0              | -15.9          | 1.68 H                   | 284                        | 51.60                  | 6.50                           |
| 6                                                   | 5350.00        | 46.9 AV                       | 54.0              | -7.1           | 1.68 H                   | 284                        | 40.40                  | 6.50                           |
| 7                                                   | #10420.00      | 59.5 PK                       | 74.0              | -14.5          | 2.01 H                   | 111                        | 41.60                  | 17.90                          |
| 8                                                   | #10420.00      | 46.6 AV                       | 54.0              | -7.4           | 2.01 H                   | 111                        | 28.70                  | 17.90                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 5150.00        | 62.1 PK                       | 74.0              | -11.9          | 3.20 V                   | 2                          | 56.10                  | 6.00                           |
| 2                                                   | 5150.00        | 49.7 AV                       | 54.0              | -4.3           | 3.20 V                   | 2                          | 43.70                  | 6.00                           |
| 3                                                   | *5210.00       | 105.0 PK                      |                   |                | 3.07 V                   | 0                          | 65.50                  | 39.50                          |
| 4                                                   | *5210.00       | 95.1 AV                       |                   |                | 3.07 V                   | 0                          | 55.60                  | 39.50                          |
| 5                                                   | 5350.00        | 58.5 PK                       | 74.0              | -15.5          | 2.28 V                   | 156                        | 52.00                  | 6.50                           |
| 6                                                   | 5350.00        | 45.6 AV                       | 54.0              | -8.4           | 2.28 V                   | 156                        | 39.10                  | 6.50                           |
| 7                                                   | #10420.00      | 59.9 PK                       | 74.0              | -14.1          | 2.32 V                   | 121                        | 42.00                  | 17.90                          |
| 8                                                   | #10420.00      | 46.4 AV                       | 54.0              | -7.6           | 2.32 V                   | 121                        | 28.50                  | 17.90                          |

## REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)  
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

|                 |                |                      |              |
|-----------------|----------------|----------------------|--------------|
| CHANNEL         | TX Channel 155 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 40GHz   |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | #5648.80       | 64.7 PK                       | 68.2              | -3.5           | 2.25 H                   | 41                         | 57.60                  | 7.10                           |
| 2                                                   | #5650.00       | 66.7 PK                       | 68.2              | -1.5           | 2.11 H                   | 39                         | 59.60                  | 7.10                           |
| 3                                                   | *5775.00       | 113.7 PK                      |                   |                | 2.12 H                   | 43                         | 73.10                  | 40.60                          |
| 4                                                   | *5775.00       | 104.1 AV                      |                   |                | 2.12 H                   | 43                         | 63.50                  | 40.60                          |
| 5                                                   | #5932.80       | 61.3 PK                       | 68.2              | -6.9           | 2.25 H                   | 41                         | 53.60                  | 7.70                           |
| 6                                                   | 11550.00       | 59.9 PK                       | 74.0              | -14.1          | 2.34 H                   | 302                        | 41.30                  | 18.60                          |
| 7                                                   | 11550.00       | 47.2 AV                       | 54.0              | -6.8           | 2.34 H                   | 302                        | 28.60                  | 18.60                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | #5640.00       | 62.3 PK                       | 68.2              | -5.9           | 3.60 V                   | 359                        | 55.20                  | 7.10                           |
| 2                                                   | *5775.00       | 111.3 PK                      |                   |                | 3.60 V                   | 359                        | 70.70                  | 40.60                          |
| 3                                                   | *5775.00       | 101.5 AV                      |                   |                | 3.60 V                   | 359                        | 60.90                  | 40.60                          |
| 4                                                   | #5995.20       | 59.9 PK                       | 68.2              | -8.3           | 3.60 V                   | 359                        | 52.00                  | 7.90                           |
| 5                                                   | 11550.00       | 59.6 PK                       | 74.0              | -14.4          | 2.23 V                   | 290                        | 41.00                  | 18.60                          |
| 6                                                   | 11550.00       | 46.7 AV                       | 54.0              | -7.3           | 2.23 V                   | 290                        | 28.10                  | 18.60                          |

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)  
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

# 802.11ac (VHT80+VHT80)

|                 |                   |                      |              |
|-----------------|-------------------|----------------------|--------------|
| CHANNEL         | TX Channel 42+155 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 40GHz      |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 5150.00        | 64.2 PK                       | 74.0              | -9.8           | 2.14 H                   | 48                         | 58.20                  | 6.00                           |
| 2                                                   | 5150.00        | 52.5 AV                       | 54.0              | -1.5           | 2.14 H                   | 48                         | 46.50                  | 6.00                           |
| 3                                                   | *5210.00       | 104.0 PK                      |                   |                | 2.06 H                   | 42                         | 64.50                  | 39.50                          |
| 4                                                   | *5210.00       | 93.8 AV                       |                   |                | 2.06 H                   | 42                         | 54.30                  | 39.50                          |
| 5                                                   | 5350.00        | 57.8 PK                       | 74.0              | -16.2          | 2.20 H                   | 55                         | 51.30                  | 6.50                           |
| 6                                                   | 5350.00        | 44.7 AV                       | 54.0              | -9.3           | 2.20 H                   | 55                         | 38.20                  | 6.50                           |
| 7                                                   | #5623.20       | 58.8 PK                       | 68.2              | -9.4           | 1.70 H                   | 48                         | 51.70                  | 7.10                           |
| 8                                                   | *5775.00       | 104.0 PK                      |                   |                | 1.70 H                   | 48                         | 63.40                  | 40.60                          |
| 9                                                   | *5775.00       | 93.9 AV                       |                   |                | 1.70 H                   | 48                         | 53.30                  | 40.60                          |
| 10                                                  | #5954.40       | 60.0 PK                       | 68.2              | -8.2           | 1.70 H                   | 48                         | 52.30                  | 7.70                           |
| 11                                                  | #10420.00      | 59.9 PK                       | 74.0              | -14.1          | 2.00 H                   | 110                        | 42.00                  | 17.90                          |
| 12                                                  | #10420.00      | 46.7 AV                       | 54.0              | -7.3           | 2.00 H                   | 110                        | 28.80                  | 17.90                          |
| 13                                                  | 11550.00       | 60.2 PK                       | 74.0              | -13.8          | 1.77 H                   | 301                        | 41.60                  | 18.60                          |
| 14                                                  | 11550.00       | 47.0 AV                       | 54.0              | -7.0           | 1.77 H                   | 301                        | 28.40                  | 18.60                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 5150.00        | 61.6 PK                       | 74.0              | -12.4          | 3.25 V                   | 7                          | 55.60                  | 6.00                           |
| 2                                                   | 5150.00        | 48.0 AV                       | 54.0              | -6.0           | 3.25 V                   | 7                          | 42.00                  | 6.00                           |
| 3                                                   | *5210.00       | 100.2 PK                      |                   |                | 3.13 V                   | 3                          | 60.70                  | 39.50                          |
| 4                                                   | *5210.00       | 89.7 AV                       |                   |                | 3.13 V                   | 3                          | 50.20                  | 39.50                          |
| 5                                                   | 5350.00        | 57.7 PK                       | 74.0              | -16.3          | 3.00 V                   | 1                          | 51.20                  | 6.50                           |
| 6                                                   | 5350.00        | 44.3 AV                       | 54.0              | -9.7           | 3.00 V                   | 1                          | 37.80                  | 6.50                           |
| 7                                                   | #5616.80       | 58.3 PK                       | 68.2              | -9.9           | 3.12 V                   | 346                        | 51.20                  | 7.10                           |
| 8                                                   | *5775.00       | 96.6 PK                       |                   |                | 3.12 V                   | 346                        | 56.00                  | 40.60                          |
| 9                                                   | *5775.00       | 86.6 AV                       |                   |                | 3.12 V                   | 346                        | 46.00                  | 40.60                          |
| 10                                                  | #5959.20       | 59.6 PK                       | 68.2              | -8.6           | 3.12 V                   | 346                        | 51.90                  | 7.70                           |
| 11                                                  | #10420.00      | 59.4 PK                       | 74.0              | -14.6          | 2.87 V                   | 289                        | 41.50                  | 17.90                          |
| 12                                                  | #10420.00      | 46.3 AV                       | 54.0              | -7.7           | 2.87 V                   | 289                        | 28.40                  | 17.90                          |
| 13                                                  | 11550.00       | 59.6 PK                       | 74.0              | -14.4          | 1.76 V                   | 88                         | 41.00                  | 18.60                          |
| 14                                                  | 11550.00       | 46.7 AV                       | 54.0              | -7.3           | 1.76 V                   | 88                         | 28.10                  | 18.60                          |

## REMARKS:

- Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)  
– Pre-Amplifier Factor(dB)
- The other emission levels were very low against the limit.
- Margin value = Emission Level – Limit value
- " \* ": Fundamental frequency.
- " # ": The radiated frequency is out of the restricted band.

Below 1GHz Worst-Case Data:

Radio 2: CDD Mode

802.11n (HT20)

|                 |                |                   |                 |
|-----------------|----------------|-------------------|-----------------|
| CHANNEL         | TX Channel 149 | DETECTOR FUNCTION | Quasi-Peak (QP) |
| FREQUENCY RANGE | 9kHz ~ 1GHz    |                   |                 |
| TEST MODE       | A              |                   |                 |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |             |                         |                |             |                    |                      |                  |                          |
|-----------------------------------------------------|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO.                                                 | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1                                                   | 57.12       | 29.2 QP                 | 40.0           | -10.8       | 1.50 H             | 81                   | 43.80            | -14.60                   |
| 2                                                   | 199.05      | 39.3 QP                 | 43.5           | -4.2        | 1.50 H             | 24                   | 55.80            | -16.50                   |
| 3                                                   | 352.65      | 36.7 QP                 | 46.0           | -9.3        | 1.00 H             | 169                  | 47.80            | -11.10                   |
| 4                                                   | 500.42      | 31.6 QP                 | 46.0           | -14.4       | 1.50 H             | 176                  | 39.50            | -7.90                    |
| 5                                                   | 700.68      | 33.0 QP                 | 46.0           | -13.0       | 1.00 H             | 99                   | 36.60            | -3.60                    |
| 6                                                   | 799.84      | 36.2 QP                 | 46.0           | -9.8        | 1.00 H             | 110                  | 37.70            | -1.50                    |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |             |                         |                |             |                    |                      |                  |                          |
| NO.                                                 | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1                                                   | 35.73       | 34.0 QP                 | 40.0           | -6.0        | 1.00 V             | 107                  | 49.60            | -15.60                   |
| 2                                                   | 199.05      | 33.8 QP                 | 43.5           | -9.7        | 1.49 V             | 171                  | 50.30            | -16.50                   |
| 3                                                   | 249.60      | 34.6 QP                 | 46.0           | -11.4       | 1.00 V             | 65                   | 48.60            | -14.00                   |
| 4                                                   | 350.71      | 36.8 QP                 | 46.0           | -9.2        | 1.49 V             | 283                  | 48.00            | -11.20                   |
| 5                                                   | 799.84      | 33.0 QP                 | 46.0           | -13.0       | 1.49 V             | 72                   | 34.50            | -1.50                    |
| 6                                                   | 897.05      | 41.1 QP                 | 46.0           | -4.9        | 1.49 V             | 16                   | 40.30            | 0.80                     |

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)  
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

|                 |                |                      |                 |
|-----------------|----------------|----------------------|-----------------|
| CHANNEL         | TX Channel 149 | DETECTOR<br>FUNCTION | Quasi-Peak (QP) |
| FREQUENCY RANGE | 9kHz ~ 1GHz    |                      |                 |
| TEST MODE       | B              |                      |                 |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 119.34         | 28.1 QP                       | 43.5              | -15.4          | 2.00 H                   | 81                         | 44.50                  | -16.40                         |
| 2                                                   | 199.05         | 38.0 QP                       | 43.5              | -5.5           | 1.00 H                   | 241                        | 54.50                  | -16.50                         |
| 3                                                   | 249.60         | 38.6 QP                       | 46.0              | -7.4           | 1.50 H                   | 143                        | 52.60                  | -14.00                         |
| 4                                                   | 290.43         | 36.7 QP                       | 46.0              | -9.3           | 1.00 H                   | 148                        | 49.00                  | -12.30                         |
| 5                                                   | 374.04         | 31.5 QP                       | 46.0              | -14.5          | 1.50 H                   | 181                        | 42.00                  | -10.50                         |
| 6                                                   | 799.84         | 35.3 QP                       | 46.0              | -10.7          | 1.00 H                   | 217                        | 36.80                  | -1.50                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 43.51          | 34.8 QP                       | 40.0              | -5.2           | 1.00 V                   | 105                        | 49.60                  | -14.80                         |
| 2                                                   | 199.05         | 39.0 QP                       | 43.5              | -4.5           | 1.00 V                   | 44                         | 55.50                  | -16.50                         |
| 3                                                   | 232.11         | 36.2 QP                       | 46.0              | -9.8           | 1.00 V                   | 318                        | 51.70                  | -15.50                         |
| 4                                                   | 348.76         | 33.2 QP                       | 46.0              | -12.8          | 1.50 V                   | 125                        | 44.50                  | -11.30                         |
| 5                                                   | 500.42         | 30.2 QP                       | 46.0              | -15.8          | 1.00 V                   | 197                        | 38.10                  | -7.90                          |
| 6                                                   | 799.84         | 35.9 QP                       | 46.0              | -10.1          | 1.00 V                   | 5                          | 37.40                  | -1.50                          |

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)  
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

|                 |                |                      |                 |
|-----------------|----------------|----------------------|-----------------|
| CHANNEL         | TX Channel 149 | DETECTOR<br>FUNCTION | Quasi-Peak (QP) |
| FREQUENCY RANGE | 9kHz ~ 1GHz    |                      |                 |
| TEST MODE       | C              |                      |                 |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 57.12          | 30.0 QP                       | 40.0              | -10.0          | 1.99 H                   | 47                         | 44.60                  | -14.60                         |
| 2                                                   | 199.05         | 35.5 QP                       | 43.5              | -8.0           | 1.00 H                   | 115                        | 52.00                  | -16.50                         |
| 3                                                   | 249.60         | 36.0 QP                       | 46.0              | -10.0          | 1.00 H                   | 5                          | 50.00                  | -14.00                         |
| 4                                                   | 374.04         | 30.5 QP                       | 46.0              | -15.5          | 1.99 H                   | 138                        | 41.00                  | -10.50                         |
| 5                                                   | 500.42         | 28.9 QP                       | 46.0              | -17.1          | 1.50 H                   | 236                        | 36.80                  | -7.90                          |
| 6                                                   | 700.68         | 31.2 QP                       | 46.0              | -14.8          | 1.00 H                   | 207                        | 34.80                  | -3.60                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 45.86          | 35.6 QP                       | 40.0              | -4.4           | 1.00 V                   | 6                          | 50.30                  | -14.70                         |
| 2                                                   | 62.95          | 36.7 QP                       | 40.0              | -3.3           | 1.00 V                   | 47                         | 51.80                  | -15.10                         |
| 3                                                   | 199.05         | 35.4 QP                       | 43.5              | -8.1           | 1.00 V                   | 4                          | 51.90                  | -16.50                         |
| 4                                                   | 249.60         | 33.4 QP                       | 46.0              | -12.6          | 1.00 V                   | 231                        | 47.40                  | -14.00                         |
| 5                                                   | 374.04         | 31.0 QP                       | 46.0              | -15.0          | 1.00 V                   | 161                        | 41.50                  | -10.50                         |
| 6                                                   | 500.42         | 30.1 QP                       | 46.0              | -15.9          | 1.00 V                   | 258                        | 38.00                  | -7.90                          |

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)  
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

|                 |                |                      |                 |
|-----------------|----------------|----------------------|-----------------|
| CHANNEL         | TX Channel 149 | DETECTOR<br>FUNCTION | Quasi-Peak (QP) |
| FREQUENCY RANGE | 9kHz ~ 1GHz    |                      |                 |
| TEST MODE       | D              |                      |                 |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 57.12          | 28.9 QP                       | 40.0              | -11.1          | 1.50 H                   | 109                        | 43.50                  | -14.60                         |
| 2                                                   | 125.17         | 30.9 QP                       | 43.5              | -12.6          | 1.50 H                   | 279                        | 47.00                  | -16.10                         |
| 3                                                   | 199.05         | 35.4 QP                       | 43.5              | -8.1           | 1.50 H                   | 147                        | 51.90                  | -16.50                         |
| 4                                                   | 286.55         | 33.2 QP                       | 46.0              | -12.8          | 1.01 H                   | 119                        | 45.60                  | -12.40                         |
| 5                                                   | 700.68         | 33.6 QP                       | 46.0              | -12.4          | 1.01 H                   | 141                        | 37.20                  | -3.60                          |
| 6                                                   | 897.05         | 42.5 QP                       | 46.0              | -3.5           | 1.50 H                   | 224                        | 41.70                  | 0.80                           |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 45.45          | 35.8 QP                       | 40.0              | -4.2           | 1.00 V                   | 19                         | 50.50                  | -14.70                         |
| 2                                                   | 55.18          | 34.0 QP                       | 40.0              | -6.0           | 1.00 V                   | 76                         | 48.40                  | -14.40                         |
| 3                                                   | 199.05         | 32.1 QP                       | 43.5              | -11.4          | 1.49 V                   | 16                         | 48.60                  | -16.50                         |
| 4                                                   | 249.60         | 32.5 QP                       | 46.0              | -13.5          | 1.00 V                   | 232                        | 46.50                  | -14.00                         |
| 5                                                   | 374.04         | 32.7 QP                       | 46.0              | -13.3          | 1.00 V                   | 166                        | 43.20                  | -10.50                         |
| 6                                                   | 500.42         | 28.8 QP                       | 46.0              | -17.2          | 1.00 V                   | 230                        | 36.70                  | -7.90                          |

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)  
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

## 4.2 Conducted Emission Measurement

### 4.2.1 Limits of Conducted Emission Measurement

| Frequency (MHz) | Conducted Limit (dBuV) |         |
|-----------------|------------------------|---------|
|                 | Quasi-peak             | Average |
| 0.15 - 0.5      | 66 - 56                | 56 - 46 |
| 0.50 - 5.0      | 56                     | 46      |
| 5.0 - 30.0      | 60                     | 50      |

Note: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

### 4.2.2 Test Instruments

| Description & Manufacturer                  | Model No.                | Serial No.     | Cal. Date     | Cal. Due      |
|---------------------------------------------|--------------------------|----------------|---------------|---------------|
| Test Receiver<br>ROHDE & SCHWARZ            | ESCI                     | 100613         | Nov. 16, 2015 | Nov. 15, 2016 |
| RF signal cable (with 10dB PAD)<br>Woken    | 5D-FB                    | Cable-cond1-01 | Dec. 26, 2015 | Dec. 25, 2016 |
| LISN/AMN<br>ROHDE & SCHWARZ<br>(EUT)        | ESH3-Z5                  | 835239/001     | Feb. 26, 2016 | Feb. 25, 2017 |
| LISN/AMN<br>ROHDE & SCHWARZ<br>(Peripheral) | ESH3-Z5                  | 100220         | Nov. 13, 2015 | Nov. 12, 2016 |
| Software<br>ADT                             | BV ADT_Conc_<br>V7.3.7.3 | NA             | NA            | NA            |

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. The test was performed in HwaYa Shielded Room 1.

3. The VCCI Site Registration No. is C-2040.

#### 4.2.3 Test Procedure


- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

**NOTE:** The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.

#### 4.2.4 Deviation from Test Standard

No deviation.

#### 4.2.5 Test Setup



**Note:** 1.Support units were connected to second LISN.  
 2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.2.6 EUT Operating Conditions

Same as 4.1.6.

## 4.2.7 Test Results


### Radio 2: CDD Mode

| Phase     | Line (L) | Detector Function | Quasi-Peak (QP) / Average (AV) |
|-----------|----------|-------------------|--------------------------------|
| Test Mode | A        |                   |                                |

| No | Freq.<br>[MHz] | Corr.<br>Factor<br>(dB) | Reading Value<br>[dB (uV)] |       | Emission Level<br>[dB (uV)] |       | Limit<br>[dB (uV)] |       | Margin<br>(dB) |        |
|----|----------------|-------------------------|----------------------------|-------|-----------------------------|-------|--------------------|-------|----------------|--------|
|    |                |                         |                            |       |                             |       |                    |       |                |        |
|    |                |                         | Q.P.                       | AV.   | Q.P.                        | AV.   | Q.P.               | AV.   | Q.P.           | AV.    |
| 1  | 0.17374        | 10.08                   | 37.04                      | 26.28 | 47.12                       | 36.36 | 64.78              | 54.78 | -17.66         | -18.42 |
| 2  | 0.20865        | 10.08                   | 35.39                      | 25.19 | 45.47                       | 35.27 | 63.26              | 53.26 | -17.79         | -17.99 |
| 3  | 0.27120        | 10.11                   | 29.86                      | 16.28 | 39.97                       | 26.39 | 61.08              | 51.08 | -21.11         | -24.69 |
| 4  | 0.31813        | 10.13                   | 32.69                      | 24.49 | 42.82                       | 34.62 | 59.76              | 49.76 | -16.94         | -15.14 |
| 5  | 0.52536        | 10.20                   | 34.04                      | 28.77 | 44.24                       | 38.97 | 56.00              | 46.00 | -11.76         | -7.03  |
| 6  | 18.92582       | 11.34                   | 20.98                      | 16.36 | 32.32                       | 27.70 | 60.00              | 50.00 | -27.68         | -22.30 |

#### Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




|           |             |                   |                                |
|-----------|-------------|-------------------|--------------------------------|
| Phase     | Neutral (N) | Detector Function | Quasi-Peak (QP) / Average (AV) |
| Test Mode | A           |                   |                                |

| No | Freq.<br>[MHz] | Corr.<br>Factor<br>(dB) | Reading Value<br>[dB (uV)] |       | Emission Level<br>[dB (uV)] |       | Limit<br>[dB (uV)] |       | Margin<br>(dB) |        |
|----|----------------|-------------------------|----------------------------|-------|-----------------------------|-------|--------------------|-------|----------------|--------|
|    |                |                         |                            |       |                             |       |                    |       |                |        |
|    |                |                         | Q.P.                       | AV.   | Q.P.                        | AV.   | Q.P.               | AV.   | Q.P.           | AV.    |
| 1  | 0.17283        | 10.08                   | 37.27                      | 29.04 | 47.35                       | 39.12 | 64.82              | 54.82 | -17.47         | -15.70 |
| 2  | 0.28288        | 10.15                   | 32.01                      | 23.18 | 42.16                       | 33.33 | 60.73              | 50.73 | -18.57         | -17.40 |
| 3  | 0.31031        | 10.17                   | 35.18                      | 28.32 | 45.35                       | 38.49 | 59.96              | 49.96 | -14.61         | -11.47 |
| 4  | 0.34159        | 10.19                   | 31.14                      | 20.32 | 41.33                       | 30.51 | 59.16              | 49.16 | -17.83         | -18.65 |
| 5  | 0.52927        | 10.25                   | 34.67                      | 27.31 | 44.92                       | 37.56 | 56.00              | 46.00 | -11.08         | -8.44  |
| 6  | 15.31298       | 11.21                   | 21.93                      | 17.20 | 33.14                       | 28.41 | 60.00              | 50.00 | -26.86         | -21.59 |

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




|           |          |                   |                                   |
|-----------|----------|-------------------|-----------------------------------|
| Phase     | Line (L) | Detector Function | Quasi-Peak (QP) /<br>Average (AV) |
| Test Mode | B        |                   |                                   |

| No | Freq.<br>[MHz] | Corr.<br>Factor<br>(dB) | Reading Value<br>[dB (uV)] |       | Emission Level<br>[dB (uV)] |       | Limit<br>[dB (uV)] |       | Margin<br>(dB) |        |
|----|----------------|-------------------------|----------------------------|-------|-----------------------------|-------|--------------------|-------|----------------|--------|
|    |                |                         |                            |       |                             |       |                    |       |                |        |
|    |                |                         | Q.P.                       | AV.   | Q.P.                        | AV.   | Q.P.               | AV.   | Q.P.           | AV.    |
| 1  | 0.16181        | 10.08                   | 23.97                      | 15.37 | 34.05                       | 25.45 | 65.37              | 55.37 | -31.32         | -29.92 |
| 2  | 0.42370        | 10.17                   | 26.03                      | 20.54 | 36.20                       | 30.71 | 57.38              | 47.38 | -21.18         | -16.67 |
| 3  | 0.50000        | 10.19                   | 34.39                      | 27.57 | 44.58                       | 37.76 | 56.00              | 46.00 | -11.42         | -8.24  |
| 4  | 0.52544        | 10.20                   | 33.31                      | 27.43 | 43.51                       | 37.63 | 56.00              | 46.00 | -12.49         | -8.37  |
| 5  | 0.62689        | 10.22                   | 23.31                      | 15.27 | 33.53                       | 25.49 | 56.00              | 46.00 | -22.47         | -20.51 |
| 6  | 19.96979       | 11.42                   | 24.02                      | 18.23 | 35.44                       | 29.65 | 60.00              | 50.00 | -24.56         | -20.35 |

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




|           |             |                   |                                |
|-----------|-------------|-------------------|--------------------------------|
| Phase     | Neutral (N) | Detector Function | Quasi-Peak (QP) / Average (AV) |
| Test Mode | B           |                   |                                |

| No | Freq.<br>[MHz] | Corr.<br>Factor<br>(dB) | Reading Value<br>[dB (uV)] |       | Emission Level<br>[dB (uV)] |       | Limit<br>[dB (uV)] |       | Margin<br>(dB) |        |
|----|----------------|-------------------------|----------------------------|-------|-----------------------------|-------|--------------------|-------|----------------|--------|
|    |                |                         |                            |       |                             |       |                    |       |                |        |
|    |                |                         | Q.P.                       | AV.   | Q.P.                        | AV.   | Q.P.               | AV.   | Q.P.           | AV.    |
| 1  | 0.15000        | 10.08                   | 18.42                      | 9.69  | 28.50                       | 19.77 | 66.00              | 56.00 | -37.50         | -36.23 |
| 2  | 0.17346        | 10.08                   | 27.80                      | 21.49 | 37.88                       | 31.57 | 64.79              | 54.79 | -26.91         | -23.22 |
| 3  | 0.50000        | 10.25                   | 33.86                      | 26.93 | 44.11                       | 37.18 | 56.00              | 46.00 | -11.89         | -8.82  |
| 4  | 0.52536        | 10.25                   | 34.38                      | 28.50 | 44.63                       | 38.75 | 56.00              | 46.00 | -11.37         | -7.25  |
| 5  | 0.63875        | 10.26                   | 27.36                      | 18.36 | 37.62                       | 28.62 | 56.00              | 46.00 | -18.38         | -17.38 |
| 6  | 19.31291       | 11.53                   | 21.25                      | 15.08 | 32.78                       | 26.61 | 60.00              | 50.00 | -27.22         | -23.39 |

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




|           |          |                   |                                |
|-----------|----------|-------------------|--------------------------------|
| Phase     | Line (L) | Detector Function | Quasi-Peak (QP) / Average (AV) |
| Test Mode | C        |                   |                                |

| No | Freq.<br>[MHz] | Corr.<br>Factor<br>(dB) | Reading Value<br>[dB (uV)] |       | Emission Level<br>[dB (uV)] |       | Limit<br>[dB (uV)] |       | Margin<br>(dB) |        |
|----|----------------|-------------------------|----------------------------|-------|-----------------------------|-------|--------------------|-------|----------------|--------|
|    |                |                         |                            |       |                             |       |                    |       |                |        |
|    |                |                         | Q.P.                       | AV.   | Q.P.                        | AV.   | Q.P.               | AV.   | Q.P.           | AV.    |
| 1  | 0.17374        | 10.08                   | 40.39                      | 31.29 | 50.47                       | 41.37 | 64.78              | 54.78 | -14.31         | -13.41 |
| 2  | 0.24384        | 10.10                   | 34.26                      | 26.00 | 44.36                       | 36.10 | 61.96              | 51.96 | -17.60         | -15.86 |
| 3  | 0.34550        | 10.15                   | 32.16                      | 24.15 | 42.31                       | 34.30 | 59.07              | 49.07 | -16.76         | -14.77 |
| 4  | 0.52544        | 10.20                   | 34.00                      | 26.69 | 44.20                       | 36.89 | 56.00              | 46.00 | -11.80         | -9.11  |
| 5  | 15.06665       | 11.07                   | 22.16                      | 17.49 | 33.23                       | 28.56 | 60.00              | 50.00 | -26.77         | -21.44 |
| 6  | 18.39406       | 11.31                   | 21.03                      | 16.37 | 32.34                       | 27.68 | 60.00              | 50.00 | -27.66         | -22.32 |

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




|           |             |                   |                                |
|-----------|-------------|-------------------|--------------------------------|
| Phase     | Neutral (N) | Detector Function | Quasi-Peak (QP) / Average (AV) |
| Test Mode | C           |                   |                                |

| No | Freq.<br>[MHz] | Corr.<br>Factor<br>(dB) | Reading Value<br>[dB (uV)] |       | Emission Level<br>[dB (uV)] |       | Limit<br>[dB (uV)] |       | Margin<br>(dB) |        |
|----|----------------|-------------------------|----------------------------|-------|-----------------------------|-------|--------------------|-------|----------------|--------|
|    |                |                         |                            |       |                             |       |                    |       |                |        |
|    |                |                         | Q.P.                       | AV.   | Q.P.                        | AV.   | Q.P.               | AV.   | Q.P.           | AV.    |
| 1  | 0.17374        | 10.08                   | 40.74                      | 30.29 | 50.82                       | 40.37 | 64.78              | 54.78 | -13.96         | -14.41 |
| 2  | 0.20474        | 10.08                   | 36.60                      | 23.81 | 46.68                       | 33.89 | 63.42              | 53.42 | -16.74         | -19.53 |
| 3  | 0.31422        | 10.17                   | 34.07                      | 25.57 | 44.24                       | 35.74 | 59.86              | 49.86 | -15.62         | -14.12 |
| 4  | 0.34550        | 10.20                   | 31.35                      | 21.72 | 41.55                       | 31.92 | 59.07              | 49.07 | -17.52         | -17.15 |
| 5  | 0.52536        | 10.25                   | 32.45                      | 25.73 | 42.70                       | 35.98 | 56.00              | 46.00 | -13.30         | -10.02 |
| 6  | 17.80365       | 11.41                   | 20.23                      | 15.49 | 31.64                       | 26.90 | 60.00              | 50.00 | -28.36         | -23.10 |

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




|           |          |                   |                                   |
|-----------|----------|-------------------|-----------------------------------|
| Phase     | Line (L) | Detector Function | Quasi-Peak (QP) /<br>Average (AV) |
| Test Mode | D        |                   |                                   |

| No | Freq.<br>[MHz] | Corr.<br>Factor<br>(dB) | Reading Value<br>[dB (uV)] |       | Emission Level<br>[dB (uV)] |       | Limit<br>[dB (uV)] |       | Margin<br>(dB) |        |
|----|----------------|-------------------------|----------------------------|-------|-----------------------------|-------|--------------------|-------|----------------|--------|
|    |                |                         |                            |       |                             |       |                    |       |                |        |
|    |                |                         | Q.P.                       | AV.   | Q.P.                        | AV.   | Q.P.               | AV.   | Q.P.           | AV.    |
| 1  | 0.17744        | 10.08                   | 24.29                      | 17.83 | 34.37                       | 27.91 | 64.60              | 54.60 | -30.23         | -26.69 |
| 2  | 0.32986        | 10.14                   | 21.38                      | 14.42 | 31.52                       | 24.56 | 59.45              | 49.45 | -27.93         | -24.89 |
| 3  | 0.49017        | 10.19                   | 33.61                      | 26.68 | 43.80                       | 36.87 | 56.16              | 46.16 | -12.36         | -9.29  |
| 4  | 0.52682        | 10.20                   | 32.84                      | 26.47 | 43.04                       | 36.67 | 56.00              | 46.00 | -12.96         | -9.33  |
| 5  | 0.62702        | 10.22                   | 23.50                      | 15.73 | 33.72                       | 25.95 | 56.00              | 46.00 | -22.28         | -20.05 |
| 6  | 20.86518       | 11.47                   | 21.86                      | 16.22 | 33.33                       | 27.69 | 60.00              | 50.00 | -26.67         | -22.31 |

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




|           |             |                   |                                |
|-----------|-------------|-------------------|--------------------------------|
| Phase     | Neutral (N) | Detector Function | Quasi-Peak (QP) / Average (AV) |
| Test Mode | D           |                   |                                |

| No | Freq.<br>[MHz] | Corr.<br>Factor<br>(dB) | Reading Value<br>[dB (uV)] |       | Emission Level<br>[dB (uV)] |       | Limit<br>[dB (uV)] |       | Margin<br>(dB) |        |
|----|----------------|-------------------------|----------------------------|-------|-----------------------------|-------|--------------------|-------|----------------|--------|
|    |                |                         |                            |       |                             |       |                    |       |                |        |
|    |                |                         | Q.P.                       | AV.   | Q.P.                        | AV.   | Q.P.               | AV.   | Q.P.           | AV.    |
| 1  | 0.16181        | 10.08                   | 27.11                      | 17.95 | 37.19                       | 28.03 | 65.37              | 55.37 | -28.18         | -27.34 |
| 2  | 0.32986        | 10.18                   | 25.00                      | 18.27 | 35.18                       | 28.45 | 59.45              | 49.45 | -24.27         | -21.00 |
| 3  | 0.49799        | 10.25                   | 33.11                      | 26.70 | 43.36                       | 36.95 | 56.03              | 46.03 | -12.67         | -9.08  |
| 4  | 0.52544        | 10.25                   | 34.18                      | 27.83 | 44.43                       | 38.08 | 56.00              | 46.00 | -11.57         | -7.92  |
| 5  | 0.83106        | 10.28                   | 25.07                      | 17.02 | 35.35                       | 27.30 | 56.00              | 46.00 | -20.65         | -18.70 |
| 6  | 20.26304       | 11.60                   | 21.44                      | 15.86 | 33.04                       | 27.46 | 60.00              | 50.00 | -26.96         | -22.54 |

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.



### 4.3 Transmit Power Measurement

#### 4.3.1 Limits of Transmit Power Measurement

| Operation Band | EUT Category |                                   | Limit                                                                                                                        |
|----------------|--------------|-----------------------------------|------------------------------------------------------------------------------------------------------------------------------|
| U-NII-1        |              | Outdoor Access Point              | 1 Watt (30 dBm)<br>(Max. e.i.r.p $\leq$ 125mW (21 dBm) at any elevation angle above 30 degrees as measured from the horizon) |
|                |              | Fixed point-to-point Access Point | 1 Watt (30 dBm)                                                                                                              |
|                | √            | Indoor Access Point               | 1 Watt (30 dBm)                                                                                                              |
|                |              | Mobile and Portable client device | 250mW (24 dBm)                                                                                                               |
| U-NII-2A       | ---          |                                   | 250mW (24 dBm) or 11 dBm+10 log B*                                                                                           |
| U-NII-2C       | ---          |                                   | 250mW (24 dBm) or 11 dBm+10 log B*                                                                                           |
| U-NII-3        | √            |                                   | 1 Watt (30 dBm)                                                                                                              |

\*B is the 26 dB emission bandwidth in megahertz

Per KDB 662911 Method of conducted output power measurement on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for  $N_{ANT} \leq 4$ ;

Array Gain = 0 dB (i.e., no array gain) for channel widths  $\geq 40$  MHz for any  $N_{ANT}$ ;


Array Gain = 5 log( $N_{ANT}/N_{SS}$ ) dB or 3 dB, whichever is less for 20-MHz channel widths with  $N_{ANT} \geq 5$ .

For power measurements on all other devices: Array Gain = 10 log( $N_{ANT}/N_{SS}$ ) dB.


#### 4.3.2 Test Setup

For Power Output Measurement


For 802.11a, 802.11n (HT20), 802.11n (HT40)



For 802.11ac (VHT80)



For 26dB Bandwidth



#### 4.3.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

#### 4.3.4 Test Procedure

##### For Average Power Measurement

##### For 802.11a, 802.11n (HT20), 802.11n (HT40)

Method PM is used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst. Duty factor is not added to measured value.

##### For 802.11ac (VHT80)

- a. Set span to encompass the entire 26 dB EBW (or, alternatively, the entire 99% occupied bandwidth) of the signal.
- b. Set sweep trigger to “free run”.
- c. Set RBW = 1 MHz.
- d. Set VBW  $\geq$  3 MHz
- e. Number of points in sweep  $\geq$  2 Span / RBW.
- f. Sweep time  $\leq$  (number of points in sweep) \* T
- g. Using emission bandwidth to determine the frequency span for integration the channel bandwidth.
- h. Detector = RMS.
- i. Trace mode = max hold.
- j. Allow max hold to run for at least 60 seconds, or longer as needed to allow the trace to stabilize.
- k. Compute power by integrating the spectrum across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the signal using the instrument’s band power measurement function with band limits set equal to the EBW (or occupied bandwidth) band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at 1 MHz intervals extending across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the spectrum.

##### For 26dB Bandwidth

- a. Set RBW = approximately 1% of the emission bandwidth.
- b. Set the VBW > RBW.
- c. Detector = Peak.
- d. Trace mode = max hold.
- e. Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

#### 4.3.5 Deviation from Test Standard

No deviation.

#### 4.3.6 EUT Operating Conditions

The software provided by client to enable the EUT under transmission Condition continuously at lowest, middle and highest channel frequencies individually.

#### 4.3.7 Test Result

Power Output:

Radio 2: CDD Mode

##### 802.11a

| Channel | Freq. (MHz) | Maximum Conducted Power (dBm) |         |         |         | Total Power (mW) | Total Power (dBm) | Limit (dBm) | Pass / Fail |
|---------|-------------|-------------------------------|---------|---------|---------|------------------|-------------------|-------------|-------------|
|         |             | Chain 0                       | Chain 1 | Chain 2 | Chain 3 |                  |                   |             |             |
| 36      | 5180        | 15.68                         | 15.42   | 15.69   | 15.79   | 146.816          | 21.67             | 30.00       | Pass        |
| 40      | 5200        | 17.50                         | 17.75   | 17.64   | 17.52   | 230.370          | 23.62             | 30.00       | Pass        |
| 48      | 5240        | 16.36                         | 16.48   | 16.25   | 16.39   | 173.435          | 22.39             | 30.00       | Pass        |
| 149     | 5745        | 19.31                         | 19.15   | 19.20   | 19.06   | 331.248          | 25.20             | 30.00       | Pass        |
| 157     | 5785        | 19.62                         | 19.40   | 19.37   | 19.35   | <b>351.314</b>   | 25.46             | 30.00       | Pass        |
| 165     | 5825        | 18.53                         | 18.13   | 18.25   | 18.42   | 272.634          | 24.36             | 30.00       | Pass        |

##### 802.11n (HT20)

| Channel | Freq. (MHz) | Maximum Conducted Power (dBm) |         |         |         | Total Power (mW) | Total Power (dBm) | Limit (dBm) | Pass / Fail |
|---------|-------------|-------------------------------|---------|---------|---------|------------------|-------------------|-------------|-------------|
|         |             | Chain 0                       | Chain 1 | Chain 2 | Chain 3 |                  |                   |             |             |
| 36      | 5180        | 16.65                         | 16.63   | 16.86   | 16.86   | 189.322          | 22.77             | 30.00       | Pass        |
| 40      | 5200        | 18.06                         | 18.26   | 18.01   | 18.02   | 257.589          | 24.11             | 30.00       | Pass        |
| 48      | 5240        | 17.36                         | 17.42   | 17.13   | 17.24   | 214.266          | 23.31             | 30.00       | Pass        |
| 149     | 5745        | 19.62                         | 19.46   | 19.43   | 19.22   | 351.190          | 25.46             | 30.00       | Pass        |
| 157     | 5785        | 19.52                         | 19.27   | 19.37   | 19.42   | 348.059          | 25.42             | 30.00       | Pass        |
| 165     | 5825        | 17.98                         | 17.66   | 17.83   | 17.94   | 244.055          | 23.87             | 30.00       | Pass        |

##### 802.11n (HT40)

| Channel | Freq. (MHz) | Maximum Conducted Power (dBm) |         |         |         | Total Power (mW) | Total Power (dBm) | Limit (dBm) | Pass / Fail |
|---------|-------------|-------------------------------|---------|---------|---------|------------------|-------------------|-------------|-------------|
|         |             | Chain 0                       | Chain 1 | Chain 2 | Chain 3 |                  |                   |             |             |
| 38      | 5190        | 12.84                         | 12.68   | 12.81   | 12.98   | 76.726           | 18.85             | 30.00       | Pass        |
| 46      | 5230        | 18.05                         | 18.04   | 18.69   | 18.22   | <b>267.841</b>   | 24.28             | 30.00       | Pass        |
| 151     | 5755        | 18.44                         | 18.18   | 17.99   | 18.05   | 262.366          | 24.19             | 30.00       | Pass        |
| 159     | 5795        | 19.59                         | 19.27   | 19.29   | 19.43   | 348.137          | 25.42             | 30.00       | Pass        |

##### 802.11ac (VHT80)

| Channel | Freq. (MHz) | Maximum Conducted Power (dBm) |         |         |         | Total Power (mW) | Total Power (dBm) | Limit (dBm) | Pass / Fail |
|---------|-------------|-------------------------------|---------|---------|---------|------------------|-------------------|-------------|-------------|
|         |             | Chain 0                       | Chain 1 | Chain 2 | Chain 3 |                  |                   |             |             |
| 42      | 5210        | 9.89                          | 9.97    | 10.07   | 10.05   | 39.959           | 16.02             | 30.00       | Pass        |
| 155     | 5775        | 16.20                         | 15.86   | 15.90   | 16.03   | 159.227          | 22.02             | 30.00       | Pass        |

802.11ac (VHT80+VHT80)

| Channel | Freq.<br>(MHz) | Maximum Conducted Power (dBm) |         |         |         | Total<br>Power<br>(mW) | Total<br>Power<br>(dBm) | Limit<br>(dBm) | Pass /<br>Fail |
|---------|----------------|-------------------------------|---------|---------|---------|------------------------|-------------------------|----------------|----------------|
|         |                | Chain 0                       | Chain 1 | Chain 2 | Chain 3 |                        |                         |                |                |
| 42      | 5210           | 10.51                         | 10.76   | -       | -       | 23.158                 | 13.65                   | 30.00          | Pass           |
| 155     | 5775           | -                             | -       | 10.59   | 10.47   | 22.598                 | 13.54                   | 30.00          | Pass           |

## Radio 2: Beamforming Mode

### 802.11n (HT20)

| Channel | Freq. (MHz) | Maximum Conducted Power (dBm) |         |         |         | Total Power (mW) | Total Power (dBm) | Limit (dBm) | Pass / Fail |
|---------|-------------|-------------------------------|---------|---------|---------|------------------|-------------------|-------------|-------------|
|         |             | Chain 0                       | Chain 1 | Chain 2 | Chain 3 |                  |                   |             |             |
| 36      | 5180        | 10.63                         | 10.61   | 10.84   | 10.84   | 47.337           | 16.75             | 24.27       | Pass        |
| 40      | 5200        | 12.04                         | 12.24   | 11.99   | 12.00   | 64.406           | 18.09             | 24.27       | Pass        |
| 48      | 5240        | 11.34                         | 11.40   | 11.11   | 11.22   | 53.573           | 17.29             | 24.27       | Pass        |
| 149     | 5745        | 13.60                         | 13.44   | 13.41   | 13.20   | <b>87.810</b>    | 19.44             | 24.27       | Pass        |
| 157     | 5785        | 13.50                         | 13.25   | 13.35   | 13.40   | 87.027           | 19.40             | 24.27       | Pass        |
| 165     | 5825        | 11.96                         | 11.64   | 11.81   | 11.92   | 61.023           | 17.85             | 24.27       | Pass        |

Note: Beamforming gain =  $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/4] = 11.73\text{dBi} > 6\text{dBi}$ , so the power limit shall be reduced to  $30 - (11.73 - 6) = 24.27\text{dBm}$ .

### 802.11n (HT40)

| Channel | Freq. (MHz) | Maximum Conducted Power (dBm) |         |         |         | Total Power (mW) | Total Power (dBm) | Limit (dBm) | Pass / Fail |
|---------|-------------|-------------------------------|---------|---------|---------|------------------|-------------------|-------------|-------------|
|         |             | Chain 0                       | Chain 1 | Chain 2 | Chain 3 |                  |                   |             |             |
| 38      | 5190        | 6.82                          | 6.66    | 6.79    | 6.96    | 19.183           | 12.83             | 24.27       | Pass        |
| 46      | 5230        | 12.03                         | 12.02   | 12.67   | 12.20   | <b>66.970</b>    | 18.26             | 24.27       | Pass        |
| 151     | 5755        | 12.42                         | 12.16   | 11.97   | 12.03   | 65.601           | 18.17             | 24.27       | Pass        |
| 159     | 5795        | 13.57                         | 13.25   | 13.27   | 13.41   | 87.046           | 19.40             | 24.27       | Pass        |

Note: Beamforming gain =  $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/4] = 11.73\text{dBi} > 6\text{dBi}$ , so the power limit shall be reduced to  $30 - (11.73 - 6) = 24.27\text{dBm}$ .

### 802.11ac (VHT80)

| Channel | Freq. (MHz) | Maximum Conducted Power (dBm) |         |         |         | Total Power (mW) | Total Power (dBm) | Limit (dBm) | Pass / Fail |
|---------|-------------|-------------------------------|---------|---------|---------|------------------|-------------------|-------------|-------------|
|         |             | Chain 0                       | Chain 1 | Chain 2 | Chain 3 |                  |                   |             |             |
| 42      | 5210        | 3.87                          | 3.95    | 4.05    | 4.03    | 9.991            | 10.00             | 24.27       | Pass        |
| 155     | 5775        | 10.18                         | 9.84    | 9.88    | 10.01   | 39.811           | 16.00             | 24.27       | Pass        |

Note: Beamforming gain =  $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/4] = 11.73\text{dBi} > 6\text{dBi}$ , so the power limit shall be reduced to  $30 - (11.73 - 6) = 24.27\text{dBm}$ .

### 802.11ac (VHT80+VHT80)

| Channel | Freq. (MHz) | Maximum Conducted Power (dBm) |         |         |         | Total Power (mW) | Total Power (dBm) | Limit (dBm) | Pass / Fail |
|---------|-------------|-------------------------------|---------|---------|---------|------------------|-------------------|-------------|-------------|
|         |             | Chain 0                       | Chain 1 | Chain 2 | Chain 3 |                  |                   |             |             |
| 42      | 5210        | 4.49                          | 4.74    | -       | -       | 5.791            | 7.63              | 24.27       | Pass        |
| 155     | 5775        | -                             | -       | 4.57    | 4.45    | 5.650            | 7.52              | 24.27       | Pass        |

Note: Beamforming gain =  $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/4] = 11.73\text{dBi} > 6\text{dBi}$ , so the power limit shall be reduced to  $30 - (11.73 - 6) = 24.27\text{dBm}$ .

26dB Bandwidth:

Radio 2: CDD Mode

802.11a

| Channel | Frequency (MHz) | 26dBc Bandwidth (MHz) |         |         |         |
|---------|-----------------|-----------------------|---------|---------|---------|
|         |                 | Chain 0               | Chain 1 | Chain 2 | Chain 3 |
| 36      | 5180            | 34.84                 | 19.42   | 19.26   | 18.99   |
| 40      | 5200            | 20.33                 | 21.54   | 19.27   | 19.36   |
| 48      | 5240            | 19.41                 | 19.36   | 19.20   | 19.17   |

802.11n (HT20)

| Channel | Frequency (MHz) | 26dBc Bandwidth (MHz) |         |         |         |
|---------|-----------------|-----------------------|---------|---------|---------|
|         |                 | Chain 0               | Chain 1 | Chain 2 | Chain 3 |
| 36      | 5180            | 20.70                 | 20.51   | 20.20   | 20.24   |
| 40      | 5200            | 25.30                 | 25.18   | 20.87   | 20.82   |
| 48      | 5240            | 20.72                 | 20.69   | 20.33   | 20.45   |

802.11n (HT40)

| Channel | Frequency (MHz) | 26dBc Bandwidth (MHz) |         |         |         |
|---------|-----------------|-----------------------|---------|---------|---------|
|         |                 | Chain 0               | Chain 1 | Chain 2 | Chain 3 |
| 38      | 5190            | 40.71                 | 40.85   | 40.77   | 40.56   |
| 46      | 5230            | 41.29                 | 43.33   | 47.39   | 54.39   |

802.11ac (VHT80)

| Channel | Frequency (MHz) | 26dBc Bandwidth (MHz) |         |         |         |
|---------|-----------------|-----------------------|---------|---------|---------|
|         |                 | Chain 0               | Chain 1 | Chain 2 | Chain 3 |
| 42      | 5210            | 84.57                 | 84.44   | 84.59   | 85.49   |



802.11ac (VHT80+VHT80)

| Channel | Frequency (MHz) | 26dBc Bandwidth (MHz) |         |         |         |
|---------|-----------------|-----------------------|---------|---------|---------|
|         |                 | Chain 0               | Chain 1 | Chain 2 | Chain 3 |
| 42      | 5210            | 84.93                 | 85.60   | -       | -       |

## Spectrum Plot of Worst Value



802.11a

802.11n (HT20) Ch 40/Chain 0




802.11n (HT40)

802.11ac (VHT80)




802.11ac (VHT80+VHT80)



## 4.4 Occupied Bandwidth Measurement

### 4.4.1 Test Setup



### 4.4.2 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

### 4.4.3 Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with resolution bandwidth in the range of 1% to 5% of the anticipated emission bandwidth, and a video bandwidth at least 3x the resolution bandwidth and set the detector to Sample. The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 %of the total mean power of a given emission.

#### 4.4.4 Test Result

Radio 2: CDD Mode

##### 802.11a

| Channel | Frequency (MHz) | Occupied Bandwidth (MHz) |         |         |         |
|---------|-----------------|--------------------------|---------|---------|---------|
|         |                 | Chain 0                  | Chain 1 | Chain 2 | Chain 3 |
| 36      | 5180            | 18.36                    | 16.56   | 16.56   | 16.56   |
| 40      | 5200            | 16.56                    | 16.56   | 16.56   | 16.56   |
| 48      | 5240            | 16.56                    | 16.56   | 16.56   | 16.56   |
| 149     | 5745            | 16.69                    | 16.95   | 16.95   | 16.78   |
| 157     | 5785            | 16.80                    | 17.04   | 17.28   | 16.92   |
| 165     | 5825            | 16.56                    | 16.44   | 16.56   | 16.44   |

##### 802.11n (HT20)

| Channel | Frequency (MHz) | Occupied Bandwidth (MHz) |         |         |         |
|---------|-----------------|--------------------------|---------|---------|---------|
|         |                 | Chain 0                  | Chain 1 | Chain 2 | Chain 3 |
| 36      | 5180            | 17.76                    | 17.76   | 17.76   | 17.64   |
| 40      | 5200            | 17.76                    | 17.76   | 17.76   | 17.76   |
| 48      | 5240            | 17.76                    | 17.76   | 17.76   | 17.64   |
| 149     | 5745            | 17.88                    | 18.00   | 18.12   | 17.88   |
| 157     | 5785            | 18.00                    | 18.12   | 18.36   | 18.00   |
| 165     | 5825            | 17.64                    | 17.64   | 17.76   | 17.64   |

##### 802.11n (HT40)

| Channel | Frequency (MHz) | Occupied Bandwidth (MHz) |         |         |         |
|---------|-----------------|--------------------------|---------|---------|---------|
|         |                 | Chain 0                  | Chain 1 | Chain 2 | Chain 3 |
| 38      | 5190            | 36.12                    | 36.12   | 36.36   | 36.12   |
| 46      | 5230            | 36.24                    | 36.24   | 36.36   | 36.48   |
| 151     | 5755            | 36.24                    | 36.24   | 36.24   | 36.24   |
| 159     | 5795            | 36.36                    | 36.60   | 36.60   | 36.36   |

##### 802.11ac (VHT80)

| Channel | Frequency (MHz) | Occupied Bandwidth (MHz) |         |         |         |
|---------|-----------------|--------------------------|---------|---------|---------|
|         |                 | Chain 0                  | Chain 1 | Chain 2 | Chain 3 |
| 42      | 5210            | 76.08                    | 75.84   | 76.08   | 76.08   |
| 155     | 5775            | 75.88                    | 75.88   | 75.88   | 75.88   |



##### 802.11ac (VHT80+VHT80)

| Channel | Frequency (MHz) | Occupied Bandwidth (MHz) |         |         |         |
|---------|-----------------|--------------------------|---------|---------|---------|
|         |                 | Chain 0                  | Chain 1 | Chain 2 | Chain 3 |
| 42      | 5210            | 76.32                    | 75.84   | -       | -       |
| 155     | 5775            | -                        | -       | 75.84   | 75.84   |

## Spectrum Plot of Worst Value



802.11a

802.11n (HT20)




802.11n (HT40)

802.11ac (VHT80)



802.11ac (VHT80+VHT80)




## 4.5 Peak Power Spectral Density Measurement

### 4.5.1 Limits of Peak Power Spectral Density Measurement

| Operation Band | EUT Category |                                   | Limit         |
|----------------|--------------|-----------------------------------|---------------|
| U-NII-1        |              | Outdoor Access Point              | 17dBm/ MHz    |
|                |              | Fixed point-to-point Access Point |               |
|                | √            | Indoor Access Point               |               |
|                |              | Mobile and Portable client device | 11dBm/ MHz    |
| U-NII-2A       | ---          |                                   | 11dBm/ MHz    |
| U-NII-2C       | ---          |                                   | 11dBm/ MHz    |
| U-NII-3        | √            |                                   | 30dBm/ 500kHz |

### 4.5.2 Test Setup



### 4.5.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

#### 4.5.4 Test Procedure

##### For U-NII-1 band:

Using method SA-1, Duty cycle >98%:

- Set span to encompass the entire emission bandwidth (EBW) of the signal.
- Set RBW = 1 MHz, Set VBW  $\geq$  3 MHz, Detector = RMS
- Sweep time = auto, trigger set to "free run".
- Trace average at least 100 traces in power averaging mode.
- Record the max value

Using method SA-2, Duty cycle <98%

- Set span to encompass the entire emission bandwidth (EBW) of the signal.
- Set RBW = 1 MHz, Set VBW  $\geq$  3 MHz, Detector = RMS
- Sweep time = auto, trigger set to "free run".
- Trace average at least 100 traces in power averaging mode.
- Record the max value and add  $10 \log (1/\text{duty cycle})$

##### For U-NII-3 band:

Duty cycle >98%

- Set span to encompass the entire emission bandwidth (EBW) of the signal.
- Set RBW = 300 kHz, Set VBW  $\geq$  1 MHz, Detector = RMS
- Use the peak marker function to determine the maximum power level in any 300 kHz band segment within the fundamental EBW.
- Scale the observed power level to an equivalent value in 500 kHz by adjusting (reducing) the measured power by a bandwidth correction factor (BWCF) where  $\text{BWCF} = 10\log(500 \text{ kHz}/300\text{kHz})$
- Sweep time = auto, trigger set to "free run".
- Trace average at least 100 traces in power averaging mode.
- Record the max value

Duty cycle <98%

- Set span to encompass the entire emission bandwidth (EBW) of the signal.
- Set RBW = 300 kHz, Set VBW  $\geq$  1 MHz, Detector = RMS
- Use the peak marker function to determine the maximum power level in any 300 kHz band segment within the fundamental EBW.
- Scale the observed power level to an equivalent value in 500 kHz by adjusting (reducing) the measured power by a bandwidth correction factor (BWCF) where  $\text{BWCF} = 10\log(500 \text{ kHz}/300\text{kHz})$
- Sweep time = auto, trigger set to "free run".
- Trace average at least 100 traces in power averaging mode.
- Record the max value and add  $10 \log (1/\text{duty cycle})$

#### 4.5.5 Deviation from Test Standard

No deviation.

#### 4.5.6 EUT Operating Condition

Same as Item 4.3.6.

#### 4.5.7 Test Results

For U-NII-1 band:

Radio 2: CDD Mode

##### 802.11a

| Chan. | Freq. (MHz) | PSD (dBm) |         |         |         | Total PSD w/o duty factor (dBm/MHz) | Duty factor (dB) | Total PSD with duty factor (dBm/MHz) | Max. Limit (dBm/MHz) | Pass / Fail |
|-------|-------------|-----------|---------|---------|---------|-------------------------------------|------------------|--------------------------------------|----------------------|-------------|
|       |             | Chain 0   | Chain 1 | Chain 2 | Chain 3 |                                     |                  |                                      |                      |             |
| 36    | 5180        | 1.89      | 1.87    | 2.20    | 1.80    | 7.96                                | 0.17             | 8.13                                 | 11.27                | Pass        |
| 40    | 5200        | 4.64      | 4.64    | 4.73    | 4.41    | 10.63                               | 0.17             | 10.80                                | 11.27                | Pass        |
| 48    | 5240        | 3.77      | 3.62    | 3.47    | 3.38    | 9.58                                | 0.17             | 9.75                                 | 11.27                | Pass        |

Note:

- Method 1 of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
- Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/4] = 11.73\text{dBi} > 6\text{dBi}$ , so the power density limit shall be reduced to  $17-(11.73-6) = 11.27\text{dBm}$ .
- Refer to section 3.3 for duty cycle spectrum plot.

##### 802.11n (HT20)

| Chan. | Freq. (MHz) | PSD (dBm) |         |         |         | Total PSD (dBm/MHz) | Max. Limit (dBm/MHz) | Pass / Fail |
|-------|-------------|-----------|---------|---------|---------|---------------------|----------------------|-------------|
|       |             | Chain 0   | Chain 1 | Chain 2 | Chain 3 |                     |                      |             |
| 36    | 5180        | 2.39      | 2.97    | 3.34    | 2.53    | 8.84                | 11.27                | Pass        |
| 40    | 5200        | 4.62      | 4.94    | 5.36    | 4.85    | 10.97               | 11.27                | Pass        |
| 48    | 5240        | 4.38      | 4.32    | 4.56    | 4.17    | 10.38               | 11.27                | Pass        |

Note:

- Method 1 of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
- Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/4] = 11.73\text{dBi} > 6\text{dBi}$ , so the power density limit shall be reduced to  $17-(11.73-6) = 11.27\text{dBm}$ .

##### 802.11n (HT40)

| Chan. | Freq. (MHz) | PSD (dBm) |         |         |         | Total PSD w/o duty factor (dBm/MHz) | Duty factor (dB) | Total PSD with duty factor (dBm/MHz) | Max. Limit (dBm/MHz) | Pass / Fail |
|-------|-------------|-----------|---------|---------|---------|-------------------------------------|------------------|--------------------------------------|----------------------|-------------|
|       |             | Chain 0   | Chain 1 | Chain 2 | Chain 3 |                                     |                  |                                      |                      |             |
| 38    | 5190        | -4.02     | -3.52   | -3.06   | -3.71   | 2.46                                | 0.12             | 2.58                                 | 11.27                | Pass        |
| 46    | 5230        | 2.16      | 2.31    | 2.58    | 2.31    | 8.36                                | 0.12             | 8.48                                 | 11.27                | Pass        |

Note:

- Method 1 of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
- Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/4] = 11.73\text{dBi} > 6\text{dBi}$ , so the power density limit shall be reduced to  $17-(11.73-6) = 11.27\text{dBm}$ .
- Refer to section 3.3 for duty cycle spectrum plot.

#### 802.11ac (VHT80)

| Chan. | Freq.<br>(MHz) | PSD (dBm) |         |         |         | Total PSD w/o<br>duty factor<br>(dBm/MHz) | Duty<br>factor<br>(dB) | Total PSD with<br>duty factor<br>(dBm/MHz)) | Max.<br>Limit<br>(dBm/<br>MHz) | Pass /<br>Fail |
|-------|----------------|-----------|---------|---------|---------|-------------------------------------------|------------------------|---------------------------------------------|--------------------------------|----------------|
|       |                | Chain 0   | Chain 1 | Chain 2 | Chain 3 |                                           |                        |                                             |                                |                |
| 42    | 5210           | -9.75     | -9.61   | -10.20  | -9.84   | -3.82                                     | 0.26                   | -3.56                                       | 11.27                          | Pass           |

Note:

- Method 1 of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
- Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/4] = 11.73\text{dBi} > 6\text{dBi}$ , so the power density limit shall be reduced to  $17-(11.73-6) = 11.27\text{dBm}$ .
- Refer to section 3.3 for duty cycle spectrum plot.

#### 802.11ac (VHT80+VHT80)

| Chan. | Freq.<br>(MHz) | PSD (dBm) |         |         |         | Total PSD w/o<br>duty factor<br>(dBm/MHz) | Duty<br>factor<br>(dB) | Total PSD with<br>duty factor<br>(dBm/MHz)) | Max.<br>Limit<br>(dBm/<br>MHz) | Pass /<br>Fail |
|-------|----------------|-----------|---------|---------|---------|-------------------------------------------|------------------------|---------------------------------------------|--------------------------------|----------------|
|       |                | Chain 0   | Chain 1 | Chain 2 | Chain 3 |                                           |                        |                                             |                                |                |
| 42    | 5210           | -8.47     | -8.61   | -       | -       | -5.53                                     | 0.28                   | -5.25                                       | 11.27                          | Pass           |



Note:

- Method 1 of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
- Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/4] = 11.73\text{dBi} > 6\text{dBi}$ , so the power density limit shall be reduced to  $17-(11.73-6) = 11.27\text{dBm}$ .
- Refer to section 3.3 for duty cycle spectrum plot.

# Spectrum Plot of Worst Value



802.11a / Ch 40 / Chain 2

802.11n (HT20) / Ch 40 / Chain 2




802.11n (HT40) / Ch 46 / Chain 2

802.11ac (VHT80) / Ch 42 / Chain 1



802.11ac (VHT80+VHT80) / Ch 42 / Chain 0



# For U-NII-3 Band

## Radio 2: CDD Mode

### 802.11a

| TX chain | Channel | Chan. Freq. (MHz) | PSD W/O Duty Factor |              | 10 log (N=4) dB | Duty factor (dB) | Total PSD With Duty Factor (dBm/500kHz) | Limit (dBm/500kHz) | Pass / Fail |
|----------|---------|-------------------|---------------------|--------------|-----------------|------------------|-----------------------------------------|--------------------|-------------|
|          |         |                   | (dBm/300kHz)        | (dBm/500kHz) |                 |                  |                                         |                    |             |
| 0        | 149     | 5745              | -2.55               | -0.33        | 6.02            | 0.17             | 5.86                                    | 24.27              | Pass        |
|          | 157     | 5785              | -2.45               | -0.23        | 6.02            | 0.17             | 5.96                                    | 24.27              | Pass        |
|          | 165     | 5825              | -3.57               | -1.35        | 6.02            | 0.17             | 4.84                                    | 24.27              | Pass        |
| 1        | 149     | 5745              | -2.93               | -0.71        | 6.02            | 0.17             | 5.48                                    | 24.27              | Pass        |
|          | 157     | 5785              | -2.63               | -0.41        | 6.02            | 0.17             | 5.78                                    | 24.27              | Pass        |
|          | 165     | 5825              | -3.67               | -1.45        | 6.02            | 0.17             | 4.74                                    | 24.27              | Pass        |
| 2        | 149     | 5745              | -2.96               | -0.74        | 6.02            | 0.17             | 5.45                                    | 24.27              | Pass        |
|          | 157     | 5785              | -2.87               | -0.65        | 6.02            | 0.17             | 5.54                                    | 24.27              | Pass        |
|          | 165     | 5825              | -4.05               | -1.83        | 6.02            | 0.17             | 4.36                                    | 24.27              | Pass        |
| 3        | 149     | 5745              | -2.91               | -0.69        | 6.02            | 0.17             | 5.50                                    | 24.27              | Pass        |
|          | 157     | 5785              | -2.91               | -0.69        | 6.02            | 0.17             | 5.50                                    | 24.27              | Pass        |
|          | 165     | 5825              | -3.94               | -1.72        | 6.02            | 0.17             | 4.47                                    | 24.27              | Pass        |

Note:

- Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/4] = 11.73\text{dBi} > 6\text{dBi}$ , so the power density limit shall be reduced to  $30 - (11.73 - 6) = 24.27\text{dBm}$ .
- Refer to section 3.3 for duty cycle spectrum plot.

### 802.11n (HT20)

| TX chain | Channel | Freq. (MHz) | PSD          |              | 10 log (N=4) dB | Total PSD (dBm/500kHz) | Limit (dBm/500kHz) | Pass / Fail |
|----------|---------|-------------|--------------|--------------|-----------------|------------------------|--------------------|-------------|
|          |         |             | (dBm/300kHz) | (dBm/500kHz) |                 |                        |                    |             |
| 0        | 149     | 5745        | -2.81        | -0.59        | 6.02            | 5.43                   | 24.27              | Pass        |
|          | 157     | 5785        | -2.68        | -0.46        | 6.02            | 5.56                   | 24.27              | Pass        |
|          | 165     | 5825        | -4.14        | -1.92        | 6.02            | 4.10                   | 24.27              | Pass        |
| 1        | 149     | 5745        | -2.86        | -0.64        | 6.02            | 5.38                   | 24.27              | Pass        |
|          | 157     | 5785        | -2.86        | -0.64        | 6.02            | 5.38                   | 24.27              | Pass        |
|          | 165     | 5825        | -4.24        | -2.02        | 6.02            | 4.00                   | 24.27              | Pass        |
| 2        | 149     | 5745        | -2.86        | -0.64        | 6.02            | 5.38                   | 24.27              | Pass        |
|          | 157     | 5785        | -2.89        | -0.67        | 6.02            | 5.35                   | 24.27              | Pass        |
|          | 165     | 5825        | -4.53        | -2.31        | 6.02            | 3.71                   | 24.27              | Pass        |
| 3        | 149     | 5745        | -2.58        | -0.36        | 6.02            | 5.66                   | 24.27              | Pass        |
|          | 157     | 5785        | -2.58        | -0.36        | 6.02            | 5.66                   | 24.27              | Pass        |
|          | 165     | 5825        | -3.94        | -1.72        | 6.02            | 4.30                   | 24.27              | Pass        |

Note:

- Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/4] = 11.73\text{dBi} > 6\text{dBi}$ , so the power density limit shall be reduced to  $30 - (11.73 - 6) = 24.27\text{dBm}$ .

### 802.11n (HT40)

| TX chain | Channel | Chan. Freq. (MHz) | PSD W/O Duty Factor |              | 10 log (N=4) dB | Duty factor (dB) | Total PSD With Duty Factor (dBm/500kHz) | Limit (dBm/500kHz) | Pass / Fail |
|----------|---------|-------------------|---------------------|--------------|-----------------|------------------|-----------------------------------------|--------------------|-------------|
|          |         |                   | (dBm/300kHz)        | (dBm/500kHz) |                 |                  |                                         |                    |             |
| 0        | 151     | 5755              | -6.93               | -4.71        | 6.02            | 0.12             | 1.43                                    | 24.27              | Pass        |
|          | 159     | 5795              | -5.99               | -3.77        | 6.02            | 0.12             | 2.37                                    | 24.27              | Pass        |
| 1        | 151     | 5755              | -7.37               | -5.15        | 6.02            | 0.12             | 0.99                                    | 24.27              | Pass        |
|          | 159     | 5795              | -6.15               | -3.93        | 6.02            | 0.12             | 2.21                                    | 24.27              | Pass        |
| 2        | 151     | 5755              | -7.22               | -5.00        | 6.02            | 0.12             | 1.14                                    | 24.27              | Pass        |
|          | 159     | 5795              | -6.23               | -4.01        | 6.02            | 0.12             | 2.13                                    | 24.27              | Pass        |
| 3        | 151     | 5755              | -6.99               | -4.77        | 6.02            | 0.12             | 1.37                                    | 24.27              | Pass        |
|          | 159     | 5795              | -6.05               | -3.83        | 6.02            | 0.12             | 2.31                                    | 24.27              | Pass        |

Note:

1. Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/4] = 11.73\text{dBi} > 6\text{dBi}$ , so the power density limit shall be reduced to  $30 - (11.73 - 6) = 24.27\text{dBm}$ .
2. Refer to section 3.3 for duty cycle spectrum plot.

### 802.11ac (VHT80)

| TX chain | Channel | Chan. Freq. (MHz) | PSD W/O Duty Factor |              | 10 log (N=4) dB | Duty factor (dB) | Total PSD With Duty Factor (dBm/500kHz) | Limit (dBm/500kHz) | Pass / Fail |
|----------|---------|-------------------|---------------------|--------------|-----------------|------------------|-----------------------------------------|--------------------|-------------|
|          |         |                   | (dBm/300kHz)        | (dBm/500kHz) |                 |                  |                                         |                    |             |
| 0        | 155     | 5775              | -12.53              | -10.31       | 6.02            | 0.26             | -4.03                                   | 24.27              | Pass        |
| 1        | 155     | 5775              | -13.11              | -10.89       | 6.02            | 0.26             | -4.61                                   | 24.27              | Pass        |
| 2        | 155     | 5775              | -13.09              | -10.87       | 6.02            | 0.26             | -4.59                                   | 24.27              | Pass        |
| 3        | 155     | 5775              | -12.75              | -10.53       | 6.02            | 0.26             | -4.25                                   | 24.27              | Pass        |

Note:

1. Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/4] = 11.73\text{dBi} > 6\text{dBi}$ , so the power density limit shall be reduced to  $30 - (11.73 - 6) = 24.27\text{dBm}$ .
2. Refer to section 3.3 for duty cycle spectrum plot.

### 802.11ac (VHT80+VHT80)

| TX chain | Channel | Chan. Freq. (MHz) | PSD W/O Duty Factor |              | 10 log (N=4) dB | Duty factor (dB) | Total PSD With Duty Factor (dBm/500kHz) | Limit (dBm/500kHz) | Pass / Fail |
|----------|---------|-------------------|---------------------|--------------|-----------------|------------------|-----------------------------------------|--------------------|-------------|
|          |         |                   | (dBm/300kHz)        | (dBm/500kHz) |                 |                  |                                         |                    |             |
| 2        | 155     | 5775              | -17.22              | -15.00       | 6.02            | 0.28             | -8.70                                   | 24.27              | Pass        |
| 3        | 155     | 5775              | -17.33              | -15.11       | 6.02            | 0.28             | -8.81                                   | 24.27              | Pass        |



Note:

1. Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/4] = 11.73\text{dBi} > 6\text{dBi}$ , so the power density limit shall be reduced to  $30 - (11.73 - 6) = 24.27\text{dBm}$ .
2. Refer to section 3.3 for duty cycle spectrum plot.

## Spectrum Plot of Worst Value



**802.11a**

**802.11n (HT20)**




**802.11n (HT40)**

**802.11ac (VHT80)**



**802.11ac (VHT80+VHT80)**




## 4.6 Frequency Stability

### 4.6.1 Limits of Frequency Stability Measurement

The frequency of the carrier signal shall be maintained within band of operation

### 4.6.2 Test Setup



### 4.6.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

### 4.6.4 Test Procedure

- The EUT was placed inside the environmental test chamber and powered by nominal AC voltage.
- Turn the EUT on and couple its output to a spectrum analyzer.
- Turn the EUT off and set the chamber to the highest temperature specified.
- Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize, turn the EUT on and measure the operating frequency after 2, 5, and 10 minutes.
- Repeat step 2 and 3 with the temperature chamber set to the lowest temperature.
- The test chamber was allowed to stabilize at +20 degree C for a minimum of 30 minutes. The supply voltage was then adjusted on the EUT from 85% to 115% and the frequency record.

### 4.6.5 Deviation from Test Standard

No deviation.

### 4.6.6 EUT Operating Condition

Set the EUT transmit at un-modulation mode to test frequency stability.

#### 4.6.7 Test Results

##### Radio 2: CDD Mode

| Frequency Stability Versus Temp. |                          |                                |                           |                                |                           |                                |                           |                                |                           |
|----------------------------------|--------------------------|--------------------------------|---------------------------|--------------------------------|---------------------------|--------------------------------|---------------------------|--------------------------------|---------------------------|
| Operating Frequency: 5180MHz     |                          |                                |                           |                                |                           |                                |                           |                                |                           |
| Temp.<br>(°C)                    | Power<br>Supply<br>(Vac) | 0 Minute                       |                           | 2 Minute                       |                           | 5 Minute                       |                           | 10 Minute                      |                           |
|                                  |                          | Measured<br>Frequency<br>(MHz) | Frequency<br>Drift<br>(%) | Measured<br>Frequency<br>(MHz) | Frequency<br>Drift<br>(%) | Measured<br>Frequency<br>(MHz) | Frequency<br>Drift<br>(%) | Measured<br>Frequency<br>(MHz) | Frequency<br>Drift<br>(%) |
| 50                               | 120                      | 5180.0192                      | 0.00037                   | 5180.0193                      | 0.00037                   | 5180.0212                      | 0.00041                   | 5180.0200                      | 0.00039                   |
| 40                               | 120                      | 5180.0124                      | 0.00024                   | 5180.0129                      | 0.00025                   | 5180.0146                      | 0.00028                   | 5180.0131                      | 0.00025                   |
| 30                               | 120                      | 5179.9765                      | -0.00045                  | 5179.9721                      | -0.00054                  | 5179.9754                      | -0.00047                  | 5179.9722                      | -0.00054                  |
| 20                               | 120                      | 5180.0220                      | 0.00042                   | 5180.0220                      | 0.00042                   | 5180.0228                      | 0.00044                   | 5180.0230                      | 0.00044                   |
| 10                               | 120                      | 5179.9860                      | -0.00027                  | 5179.9897                      | -0.00020                  | 5179.9864                      | -0.00026                  | 5179.9896                      | -0.00020                  |
| 0                                | 120                      | 5179.9899                      | -0.00019                  | 5179.9906                      | -0.00018                  | 5179.9906                      | -0.00018                  | 5179.9921                      | -0.00015                  |
| -10                              | 120                      | 5180.0166                      | 0.00032                   | 5180.0144                      | 0.00028                   | 5180.0144                      | 0.00028                   | 5180.0170                      | 0.00033                   |
| -20                              | 120                      | 5180.0056                      | 0.00011                   | 5180.0102                      | 0.00020                   | 5180.0075                      | 0.00014                   | 5180.0080                      | 0.00015                   |
| -30                              | 120                      | 5180.0201                      | 0.00039                   | 5180.0224                      | 0.00043                   | 5180.0197                      | 0.00038                   | 5180.0212                      | 0.00041                   |


| Frequency Stability Versus Voltage |                          |                                |                           |                                |                           |                                |                           |                                |                           |
|------------------------------------|--------------------------|--------------------------------|---------------------------|--------------------------------|---------------------------|--------------------------------|---------------------------|--------------------------------|---------------------------|
| Operating Frequency: 5180MHz       |                          |                                |                           |                                |                           |                                |                           |                                |                           |
| Temp.<br>(°C)                      | Power<br>Supply<br>(Vac) | 0 Minute                       |                           | 2 Minute                       |                           | 5 Minute                       |                           | 10 Minute                      |                           |
|                                    |                          | Measured<br>Frequency<br>(MHz) | Frequency<br>Drift<br>(%) | Measured<br>Frequency<br>(MHz) | Frequency<br>Drift<br>(%) | Measured<br>Frequency<br>(MHz) | Frequency<br>Drift<br>(%) | Measured<br>Frequency<br>(MHz) | Frequency<br>Drift<br>(%) |
| 20                                 | 138                      | 5180.0226                      | 0.00044                   | 5180.0228                      | 0.00044                   | 5180.0237                      | 0.00046                   | 5180.0238                      | 0.00046                   |
|                                    | 120                      | 5180.0220                      | 0.00042                   | 5180.0220                      | 0.00042                   | 5180.0228                      | 0.00044                   | 5180.0230                      | 0.00044                   |
|                                    | 102                      | 5180.0225                      | 0.00043                   | 5180.0221                      | 0.00043                   | 5180.0226                      | 0.00044                   | 5180.0235                      | 0.00045                   |

## 4.7 6dB Bandwidth Measurement

### 4.7.1 Limits of 6dB Bandwidth Measurement

The minimum of 6dB Bandwidth Measurement is 0.5MHz.

### 4.7.2 Test Setup



### 4.7.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

### 4.7.4 Test Procedure

- Set resolution bandwidth (RBW) = 100kHz
- Set the video bandwidth (VBW)  $\geq 3 \times$  RBW, Detector = Peak
- Trace mode = max hold
- Sweep = auto couple
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

### 4.7.5 Deviation from Test Standard

No deviation.

### 4.7.6 EUT Operating Condition

The software provided by client to enable the EUT under transmission Condition continuously at lowest, middle and highest channel frequencies individually.

#### 4.7.7 Test Results

Radio 2: CDD Mode

##### 802.11a

| Channel | Frequency (MHz) | 6dB Bandwidth (MHz) |         |         |         | Minimum Limit (MHz) | Pass / Fail |
|---------|-----------------|---------------------|---------|---------|---------|---------------------|-------------|
|         |                 | Chain 0             | Chain 1 | Chain 2 | Chain 3 |                     |             |
| 149     | 5745            | 16.35               | 16.34   | 16.34   | 16.36   | 0.5                 | Pass        |
| 157     | 5785            | 16.37               | 16.37   | 16.37   | 16.39   | 0.5                 | Pass        |
| 165     | 5825            | 16.38               | 16.38   | 16.38   | 16.40   | 0.5                 | Pass        |

##### 802.11n (HT20)

| Channel | Frequency (MHz) | 6dB Bandwidth (MHz) |         |         |         | Minimum Limit (MHz) | Pass / Fail |
|---------|-----------------|---------------------|---------|---------|---------|---------------------|-------------|
|         |                 | Chain 0             | Chain 1 | Chain 2 | Chain 3 |                     |             |
| 149     | 5745            | 17.60               | 17.58   | 17.61   | 17.61   | 0.5                 | Pass        |
| 157     | 5785            | 17.59               | 17.62   | 17.59   | 17.62   | 0.5                 | Pass        |
| 165     | 5825            | 17.61               | 17.61   | 17.62   | 17.63   | 0.5                 | Pass        |

##### 802.11n (HT40)

| Channel | Frequency (MHz) | 6dB Bandwidth (MHz) |         |         |         | Minimum Limit (MHz) | Pass / Fail |
|---------|-----------------|---------------------|---------|---------|---------|---------------------|-------------|
|         |                 | Chain 0             | Chain 1 | Chain 2 | Chain 3 |                     |             |
| 151     | 5755            | 35.33               | 35.23   | 35.31   | 35.24   | 0.5                 | Pass        |
| 159     | 5795            | 35.23               | 35.27   | 35.25   | 35.19   | 0.5                 | Pass        |

##### 802.11ac (VHT80)

| Channel | Frequency (MHz) | 6dB Bandwidth (MHz) |         |         |         | Minimum Limit (MHz) | Pass / Fail |
|---------|-----------------|---------------------|---------|---------|---------|---------------------|-------------|
|         |                 | Chain 0             | Chain 1 | Chain 2 | Chain 3 |                     |             |
| 155     | 5775            | 75.68               | 75.49   | 75.49   | 75.54   | 0.5                 | Pass        |



##### 802.11ac (VHT80+VHT80)

| Channel | Frequency (MHz) | 6dB Bandwidth (MHz) |         |         |         | Minimum Limit (MHz) | Pass / Fail |
|---------|-----------------|---------------------|---------|---------|---------|---------------------|-------------|
|         |                 | Chain 0             | Chain 1 | Chain 2 | Chain 3 |                     |             |
| 155     | 5775            | -                   | -       | 75.52   | 75.47   | 0.5                 | Pass        |

## Spectrum Plot of Worst Value



802.11a

802.11n (HT20)




802.11n (HT40)

802.11ac (VHT80)



802.11ac (VHT80+VHT80)



## 5 Pictures of Test Arrangements


Please refer to the attached file (Test Setup Photo).

## Annex A- Radiated Out of Band Emission (OOBE) Measurement (For U-NII-3 band)


Radio 2: CDD Mode

Test Mode A



802.11a




# 802.11n (HT20)




## 802.11n (HT40)



## 802.11ac (VHT80)




## 802.11ac (VHT80+VHT80)




Test Mode C



802.11a




# 802.11n (HT20)




## 802.11n (HT40)



## 802.11ac (VHT80)



## 802.11ac (VHT80+VHT80)



## Appendix – Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

**Linko EMC/RF Lab**

Tel: 886-2-26052180

Fax: 886-2-26051924

**Hsin Chu EMC/RF/Telecom Lab**

Tel: 886-3-6668565

Fax: 886-3-6668323

**Hwa Ya EMC/RF/Safety Lab**

Tel: 886-3-3183232

Fax: 886-3-3270892

**Email:** [service.adt@tw.bureauveritas.com](mailto:service.adt@tw.bureauveritas.com)

**Web Site:** [www.bureauveritas-adt.com](http://www.bureauveritas-adt.com)

The address and road map of all our labs can be found in our web site also.

--- END ---