



**FCC & IC Certification Test Report
Addendum**

for

ADTRAN, Inc.

FCC ID: HDCTRC5045L1

IC: 2250A-TRC5045L1

April 26, 2005

Prepared for:

**ADTRAN, Inc.
901 Explorer Blvd
Huntsville, AL 35806**

Prepared By:

**Washington Laboratories, Ltd.
7560 Lindbergh Drive
Gaithersburg, Maryland 20879**



**FCC & IC Certification Test Report Addendum
for the
ADTRAN, Inc.
TRACER
Transceiver 5045L1
FCC ID: HDCTRC5045L1**

WLL JOB# 8031

Prepared by: Gregory M. Snyder
Chief EMC Engineer

Reviewed by: Steve Koster
EMC Operation Manager

Abstract

This report has been prepared on behalf of ADTRAN, Inc. to supply emissions test data in support of large high gain antenna systems. The ADTRAN TRACER Model 5045 was originally tested with a 2' diameter dish antenna (28.5dBi). As this device is being sought for certification under §15.247 and operates as a fixed installation point-to-point system at 5.8GHz, the antenna gain can exceed 6dBi without any reduction in output power. The user manual specifies antennas up to 12' in diameter with gains up to 44.2dBi.

This test report presents emissions data for the 10' dish antenna (42.5dBi). It can be seen from the spurious emission data collected at the antenna terminal and the comparison of the radiated emissions data from the 2' to 10' dish antenna that the spurious emissions are not increased by the use of the high gain antenna.

Testing was performed at Washington Laboratories, Ltd, 7560 Lindbergh Drive, Gaithersburg, MD 20879.

Table of Contents

Abstract	ii
1 Introduction	1
1.1 Compliance Statement	1
1.2 Test Scope	1
1.3 Contract Information	1
1.4 Test Dates	1
1.5 Test and Support Personnel	1
2 Equipment Under Test	2
2.1 EUT Identification & Description	2
2.2 Test Configuration	2
3 Test Equipment	2
4 Test Results	4
4.1 Radiated Spurious Emissions: (FCC Part §15.247(c))	4
4.1.1 Test Procedure	4
4.1.2 Test results	5
4.2 E-Mail From FCC Referencing Testing of Large Dish	9

List of Tables

Table 1: Test Equipment List.....	3
Table 2: Radiated Emission Test Data - Plan A, Band 1	5

List of Figures

Figure 1. Test Setup Photograph.....	7
Figure 2. Test Setup Photograph.....	8

1 Introduction

1.1 Compliance Statement

The ADTRAN, Inc. TRACER 5045L1 Spread Spectrum System with dish antennas up to 44.2dBi gain complies with the limits for a Digitally Modulated intentional radiator device under FCC Part 15.247 and Industry Canada RSS-210.

1.2 Test Scope

Tests for radiated emissions of the TRACER 5045L1 with a 10' dish antenna were performed in accordance with guidance provided by the FCC Laboratory. Reference the e-mail included in 4.2.

The face of the antenna was scanned to determine the location of maximum field intensity. Both horizontal and vertical polarities were evaluated.

1.3 Contract Information

Customer: ADTRAN, Inc.
901 Explorer Blvd
Huntsville, AL 35806

Quotation Number: 62208

1.4 Test Dates

Testing was performed on March 7, 2005.

1.5 Test and Support Personnel

Washington Laboratories, LTD Greg Snyder, Mike Violette

2 Equipment Under Test

2.1 EUT Identification & Description

ADTRAN Part #	Product Name/Description
12805045L1A	Tracer 5045 Plan A
12805045L1B	Tracer 5045 Plan B

Top Assembly #:	12805045L1A/B
Sub Assembly #(s):	2280030-6, 2280018-11
Circuit Board #(s):	5280030-6, 5280018-11

Antenna Description:

Manufacturer	Model	Description	Gain
Andrew	PL10F-23-N7A	10' Dish Antenna with 5.8GHz Feed Horn	42.5dBi

2.2 Test Configuration

The antenna and TRACER 5045L1 were placed in the parking lot of Washington Laboratories at a location that allowed a clear 10m path to the receive antenna. The EUT was configured with an external power adapter to provide 48Vdc. Cables with loopback connections were connected to the I/O ports. The RF output port was connected to the input of the dish antenna.

The EUT was setup for a continuous transmission at the maximum data rate and output power. Both Plan A lower frequency (5.747GHz) and Plan B upper frequency (5.827GHz) were evaluated.

3 Test Equipment

Table 1 shows a list of the test equipment used for measurements along with the calibration information.

Table 1: Test Equipment List

Equipment	WLL Asset #	Calibration Due
Hewlett-Packard 8568B Spectrum Analyzer	0073	7/08/05
Hewlett-Packard 85650A Quasi-Peak Adapter	0069	7/08/05
Hewlett-Packard 8593A Spectrum Analyzer	0074	8/17/05
Hewlett-Packard 8449B Microwave Preamp	0312	9/29/05
Hewlett-Packard 8672A Signal Generator	0080	3/25/05
ARA LPB-2520 BiconiLog Antenna	0007	9/14/05
ARA DRG118/A Microwave Horn Antenna	0425	4/17/05
Narda V638 Horn Antenna	0210	12/25/08
Hewlett-Packard 85685A RF Preselector	0071	7/08/05
Hewlett-Packard 438A Power Meter	0394	3/10/05
Hewlett-Packard 8481B Power Head	0390	4/15/05

4.1.2 Test results

Data are supplied in the following table. Testing was performed to 40GHz. No emissions were detected above 12GHz. All detected emissions are reported in the following tables. Note that bandedge tests were performed here for informational purposes only. These do not fall within the restricted bands. The measurements were made to show the 20dBc requirement is met although this was done at the antenna terminal.

Table 2: Radiated Emission Test Data

Restricted Band Spurious Emissions (§15.205)

CLIENT: ADTRAN DATE: 3/7/2005
TESTER: Greg Snyder/Mike Violette JOB #: 8031

EUT Information:

EUT: Tracer 5045L1 w/10'Dish
DISTANCE: 3m

Test Requirements:

TEST STANDARD: FCC Part 15
CLASS: B

Test Equipment/Limit:

ANTENNA: 00425 LIMIT: LFCC_3m_Class_B
CABLE: Assem#1 AMPLIFIER (dB) A_00312

Plan B: Tx = 5827MHz

Freq (MHz)	Pol H/V	Az Deg	Ant. Hght (m)	SA Level (dBµV)	Ant. Corr. (dB/m)	Cable Corr. (dB)	Distance Corr.	Amp Gain (dB)	Corr. Level dBµV/m	Corr. Level µV/m	Limit (µV/m)	Margin dB	Notes
				Avg.									
5827	H	0	1.5	77.3	35.0	1.3	10.5	0.0	124.1	1603115.2	N/A	N/A	Avg
5827	V	0	1.5	49.2	35.0	1.3	10.5	0.0	96.0	63090.6	N/A	N/A	Avg
11654	H	0	1.5	32.3	41.1	2.3	10.5	35.7	50.5	333.6	500.0	-3.5	NF
11654	V	0	1.5	32.3	41.1	2.3	10.5	35.7	50.5	333.6	500.0	-3.5	NF
				Peak									
5827	H	0	1.5	88.5	35.0	1.3	10.5	0.0	135.3	5820559.5	N/A	N/A	Peak
5827	V	0	1.5	61.5	35.0	1.3	10.5	0.0	108.3	259994.8	N/A	N/A	Peak
5850	H	0	1.5	80.7	35.0	1.3	10.5	35.5	92.0	39770.2	582056.0	-23.3	20dBc
5850	V	0	1.5	52.7	35.0	2.3	10.5	35.5	65.0	1768.3	25999.5	-23.3	20dBc
11654	V	0	1.5	43.0	41.1	2.3	10.5	35.7	61.2	1143.4	5000.0	-12.8	NF
11654	H	0	1.5	43.0	41.1	2.3	10.5	35.7	61.2	1143.4	5000.0	-12.8	NF

NF = Noise Floor; No detectable signal

Plan A: Tx = 5747MHz

Freq (MHz)	Pol H/V	Az Deg	Ant. Hight (m)	SA Level (dBμV)	Ant. Corr. (dB/m)	Cable Corr. (dB)	Distance Corr.	Amp Gain (dB)	Corr. Level dBμV/m	Corr. Level μV/m	Limit (μV/m)	Margin dB	Notes
				Avg.									
5747	H	0	1.5	78.2	34.8	1.3	10.5	0.0	124.9	1755003.4	N/A	N/A	Avg
5747	V	0	1.5	59.1	34.8	1.3	10.5	0.0	105.8	194660.6	N/A	N/A	Avg
11494	H	0	1.5	33.5	40.9	2.3	10.5	35.6	51.5	376.3	500.0	-2.5	NF
11494	V	0	1.5	33.3	40.9	2.3	10.5	35.6	51.3	367.7	500.0	-2.7	NF
				Peak									
5747	H	0	1.5	89.5	34.8	1.3	10.5	0.0	136.2	6445816.7	N/A	N/A	Peak
5747	V	0	1.5	70.2	34.8	1.3	10.5	0.0	116.9	698679.4	N/A	N/A	Peak
5725	H	0	1.5	79.7	34.8	1.3	10.5	35.6	90.7	34453.8	644581.7	-25.4	20dBc
5725	V	0	1.5	62.3	34.8	2.3	10.5	35.6	74.3	5190.8	69867.9	-22.6	20dBc
11494	V	0	1.5	43.5	40.9	2.3	10.5	35.6	61.5	1189.8	5000.0	-12.5	NF
11494	H	0	1.5	43.3	40.9	2.3	10.5	35.6	61.3	1162.8	5000.0	-12.7	NF

NF = Noise Floor; No detectable signal



Figure 1. Test Setup Photograph



Figure 2. Test Setup Photograph

4.2 E-Mail From FCC Referencing Testing of Large Dish

From: Rich Fabina [Rich.Fabina@fcc.gov]
Sent: Friday, February 18, 2005 2:54 PM
To: mikev@wll.com
Subject: RE: Big old antenna

Mike,

Attached are the guidelines for testing a 10 foot dish with as Part 15, spread spectrum device.

Remember we are concerned about band edge compliance particularly in the 2.4 GHz band at 2.4835 MHz in the restricted band. If the device is a 2.4 GHz device, you will have to use the delta method (posted on our KDB) to determine the level of the emission at the band edge.

We are also concerned with the defacto EIRP limits in the 900 MHz and 2.4 GHz bands listed in the rules. Be careful with those.

For EMC/EMI Measurements:

Place the 10' parabolic antenna on a 10 meter OATS and bore-site the parabolic antenna to the receive antenna. To ensure measuring a maximized signal, with the transmission system transmitting rotate the EUT (left and right) slightly while monitoring the transmission - this is to ensure measuring in the center of the transmission beam. Then, with the transmission system still transmitting, raise and lower the receive antenna 1 to 4 meters to ensure that a maximized signal is being measured. Note: both horizontal and vertical polarities of the receiver antenna should be used to ensure a maximized signal will be measured. You will have to perform this for the fundamental to measure band edge compliance and for all the restricted band emissions. A look at the conducted emissions from this device should give you some guidance on where to look for spurious emissions from the system.

During all measurements, the measurement equipment requirements defined in Part 15, section 15.35 Measurement detector functions and bandwidths should be met.

These 10 meter measurements will then have to be extrapolated to 3 meters for comparison to the limits.

Let me know if we can be of further help.

Rich