FCC 15 SUBPART C

EMI MEASUREMENT AND TEST REPORT

For

Accton Technology Corporation

No.1 Creation Rd. III,
Science-based Industrial Park,
Hsin Chu 300, Taiwan, R.O.C.

FCC ID: HEDACC300568

May 9, 2002

This Report Concerns:	**Equipment Type:**
☒ Original Report	Base Station

Test Engineer:	Jeff Lee
Report No.:	R0205018
Test Date:	March 10, 2002
Reviewed By:	Benjamin Jin
Prepared By:	Bay Area Compliance Laboratory Corporation 230 Commercial Street Sunnyvale, CA 94085 Tel: (408) 732-9162 Fax: (408) 732 9164

Note: This test report is specially limited to the above client company and the product model only. It may not be duplicated without prior written consent of Bay Area Compliance Laboratory Corporation. This report **must not** be used by the client to claim product endorsement by NVLAP or any agency of the U.S. Government.

TABLE OF CONTENTS

1 - GENERAL INFORMATION 4
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) 4
1.2 OBJECTIVE 4
1.3 RELATED SUBMITTAL(S)/GRANT(S) 4
1.4 TEST METHODOLOGY 4
1.5 TEST FACILITY 5
1.6 TEST EQUIPMENT LIST AND DETAILS 5
1.7 HOST SYSTEM CONFIGURATION LIST AND DETAILS 6
1.8 LOCAL SUPPORT EQUIPMENT LIST AND DETAILS 6
1.9 EXTERNAL I/O CABLING LIST AND DETAILS 6

2 - SYSTEM TEST CONFIGURATION 7
2.1 JUSTIFICATION 7
2.2 EUT EXERCISE SOFTWARE 7
2.3 SPECIAL ACCESSORIES 7
2.4 SCHEMATICS / BLOCK DIAGRAM 7
2.5 EQUIPMENT MODIFICATIONS 7
2.6 CONFIGURATION OF TEST SYSTEM 8
2.7 TEST SETUP BLOCK DIAGRAM 8

3 - SUMMARY OF TEST RESULTS 9

4 - PEAK OUTPUT POWER MEASUREMENT 10
4.1 STANDARD APPLICABLE 10
4.2 MEASUREMENT PROCEDURE 10
4.3 MEASUREMENT RESULT 10

5 - SPURIOUS EMISSION 12
5.1 STANDARD APPLICABLE 12
5.2 MEASUREMENT PROCEDURE 12
5.3 MEASUREMENT DATA 12

6 - PEAK POWER SPECTRAL DENSITY 16
6.1 STANDARD APPLICABLE 16
6.2 MEASUREMENT PROCEDURE 16
6.3 TEST RESULTS 16

7 - 6 DB BANDWIDTH 18
7.1 STANDARD APPLICABLE 18
7.2 MEASUREMENT PROCEDURE 18
7.3 MEASUREMENT DATA 18

8 -100 KHZ BANDWIDTH OF BAND EDGES MEASUREMENT 20
8.1 STANDARD APPLICABLE 20
8.2 MEASUREMENT PROCEDURE 20
8.3 TEST RESULTS 20

9 - ANTENNA REQUIREMENT 22
9.1 STANDARD APPLICABLE 22
9.2 ANTENNA CONNECTED CONSTRUCTION 22

10 - RF EXPOSURE 23

11 - SPURIOUS RADIATED EMISSION DATA 24
11.1 MEASUREMENT UNCERTAINTY 24
11.2 EUT SETUP 24
11.3 SPECTRUM ANALYZER SETUP 24
11.4 TEST PROCEDURE 25
11.5 CORRECTED AMPLITUDE & MARGIN CALCULATION 25

11.6 SUMMARY OF TEST RESULTS....25

12 - CONDUCTED EMISSIONS TEST DATA....27

12.1 MEASUREMENT UNCERTAINTY....27
12.2 EUT SETUP....27
12.3 SPECTRUM ANALYZER SETUP....27
12.4 TEST PROCEDURE....27
12.5 SUMMARY OF TEST RESULTS....28
12.6 CONDUCTED EMISSIONS TEST DATA....28
12.7 PLOT OF CONDUCTED EMISSIONS TEST DATA....28

13 - PROCESSING GAIN....29

13.1 BRIEF EXPLANATIONS ON PROCESSING GAIN DATA....29
13.2 TEST DATA FOR PROCESSING GAIN....29
13.3 TEST SETUP - PROCESSING GAIN....29

1 - General Information

1.1 Product Description for Equipment Under Test (EUT)

Applicant:	Accton Technology Corporation
Product Description:	Base Station
Product Name:	MN-500
FCC ID:	HEDACC300568
Serial Number:	None
Transmitter Frequency:	2400-2483.5MHz
Maximum Output Power:	16.12dBm (40.93mW)
Dimension:	4.5”L x 2.0”W x 0.2”H approximately
Power Supply:	12Vdc/500mA power adapter
Applicable Standard(s)	FCC 15.247

** The test data in this test report was good for the test sample only. It may have deviation for other test samples.*

1.2 Objective

This type approval report is prepared on behalf of. *Accton Technology Corporation* in accordance with Part 2, Subpart J, Part 15, Subparts A, B and C of the Federal Communication Commissions rules.

The objective of the manufacturer is to demonstrate compliance with FCC rules for Output Power, Antenna Requirements, 6 dB Bandwidth, power density, 100 kHz Bandwidth of Band Edges Measurement, Conducted and Spurious Radiated Emission, and processing gain.

1.3 Related Submittal(s)/Grant(s)

No Related Submittal(s).

1.4 Test Methodology

All measurements contained in this report were conducted with ANSI C63.4 –1992, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz. All radiated and conducted emissions measurement was performed at Bay Area Compliance Laboratory Corporation. The radiated testing was performed at an antenna-to-EUT distance of 3 Meters.

1.5 Test Facility

The Open Area Test site used by Bay Area Compliance Laboratory Corporation to collect radiated and conducted emission measurement data is located in the back parking lot of the building at 230 Commercial Street, Sunnyvale, California, USA.

Test site at Bay Area Compliance Laboratory Corporation has been fully described in reports submitted to the Federal Communication Commission (FCC) and Voluntary Control Council for Interference (VCCI).

The details of these reports has been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 11 and December 10, 1997 and Article 8 of the VCCI regulations on December 25, 1997. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-1992.

The Federal Communications Commission and Voluntary Control Council for Interference has the reports on file and is listed under FCC file 31040/SIT 1300F2 and VCCI Registration No.: C-1298 and R-1234. The test site has been approved by the FCC and VCCI for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, Bay Area Compliance Laboratory Corporation is a National Institute of Standards and Technology (NIST) accredited laboratory, under the National Voluntary Laboratory Accredited Program (NVLAP). The scope of the accreditation covers the FCC Method - 47 CFR Part 15 - Digital Devices, IEC/CISPR 22: 1998, and AS/NZS 3548: Electromagnetic Interference - Limits and Methods of Measurement of Information Technology Equipment test methods under NVLAP Lab Code 200167-0.

1.6 Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Cal. Due Date
HP	Spectrum Analyzer	8568B	2610A02165	12/6/02
HP	Spectrum Analyzer	8593B	2919A00242	12/20/02
HP	Amplifier	8349B	2644A02662	12/20/02
HP	Quasi-Peak Adapter	85650A	917059	12/6/02
HP	Amplifier	8447E	1937A01046	12/6/02
A.H. System	Horn Antenna	SAS0200/571	261	12/27/02
Com-Power	Log Periodic Antenna	AL-100	16005	11/2/02
Com-Power	Biconical Antenna	AB-100	14012	11/2/02
Solar Electronics	LISN	8012-50-R-24-BNC	968447	12/28/02
Com-Power	LISN	LI-200	12208	12/20/02
Com-Power	LISN	LI-200	12005	12/20/02
BACL	Data Entry Software	DES1	0001	12/20/02

*** Statement of Traceability: Bay Area Compliance Laboratory Corp.** certifies that all calibration has been performed using suitable standards traceable to the NATIONAL INSTITUTE of STANDARDS and TECHNOLOGY (NIST).

1.7 Host System Configuration List and Details

Manufacturer	Description	Model	Serial Number	FCC ID
Sony	Notebook	PCG-885	00043-167-411-849	DOC
Accton Technology Corporation	Base Station	MN500	None	HEDACC 300568
Sony	Power Supply	PCGA-AC16V	0111A0217169P	DOC

1.8 Local Support Equipment List and Details

Manufacturer	Description	Model	Serial Number	FCC ID
HP	Printer	2225C	N/A	DOC
Kensinton	Mouse	X03-48591	6818005-00000	C3KKMPS
Sony	Notebook	PCG-885L	00043-167-411-849	DOC

1.9 External I/O Cabling List and Details

Cable Description	Length (M)	Port/From	To
Shielded Mouse Cable	1.8	Mouse Port/Notebook	Mouse
Shielded Printer Cable	2.0	Parallel Port/Notebook	Printer

2 - SYSTEM TEST CONFIGURATION

2.1 Justification

The host system was configured for testing in a typical fashion (as a normally used by a typical user).

The EUT was tested in the normal (native) operating mode to represent *worst*-case results during the final qualification test.

2.2 EUT Exercise Software

The EUT exercising program used during radiated and conducted testing was designed to exercise the various system components in a manner similar to a typical use. The test software, terminal.exe, provided by the customer, is started the Windows 98 terminal program under the Windows 98 operating system. Once loaded, the program sequentially exercises each system component.

The sequence used is as follows:

1. Lines of Hs scroll across the notebook monitor.
2. The printer output Hs.

This process is continuous throughout all tests.

2.3 Special Accessories

As shown in section 2.5, all interface cables used for compliance testing are shielded as normally supplied by INMAC and their respective support equipment manufacturers. The host pc and other peripherals featured shielded metal connectors.

2.4 Schematics / Block Diagram

Please refer to Appendix D.

2.5 Equipment Modifications

No modifications were made by BACL Corporation to ensure the EUT to comply with the applicable limits and requirements.

2.6 Configuration of Test System



2.7 Test Setup Block Diagram



3 - SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT
§ 15.205	Restricted Bands	Compliant
§ 2.1091	RF Safety Requirements	Compliant
§15.203	Antenna Requirement	Compliant
§15.207 (a)	Conducted Emission	Compliant
§15.209 (a)	Radiated Emission	Compliant
§15.209 (f)	Spurious Emission	Compliant
§15.247 (a) (2)	6 dB Bandwidth	Compliant
§15.247 (b) (2)	Peak Output Power	Compliant
§15.247 (b) (4)	RF Exposure	Compliant
§ 15.247 (c)	100 kHz Bandwidth of Frequency Band Edges	Compliant
§15.247 (d)	Peak Power Spectral Density	Compliant
§15.247 (e)	Processing Gain	Compliant

4 - PEAK OUTPUT POWER MEASUREMENT

4.1 Standard Applicable

According to §15.247(b) (2), for all direct sequence systems, the maximum peak output power of the intentional radiator shall not exceed 1 Watt.

4.2 Measurement Procedure

1. Place the EUT on the turntable and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the power meter.

4.3 Measurement Result

Please refer to the attached pictures for more information.

Frequency (MHz)	Output Power in dBm	Output Power in W	Standard	Result
Low	15.22	0.033	≤ 1W	Compliant
Middle	15.73	0.037	≤ 1W	Compliant
High	16.12	0.041	≤ 1W	Compliant

4.4 Test Equipment

Manufacturer	Model No.	Serial No.	Calibration Due Date
Agilent	E4419b	GB40202891	4/8/03
Agilent	E4412a	US38486529	4/8/03

Agilent
15.22dBm

Agilent
15.73dBm

Agilent
16.12dBm

5 - SPURIOUS EMISSION

5.1 Standard Applicable

According to §15.209 (f) and §15.33(a), in some cases the emissions from an intentional radiator must be measured to beyond the tenth harmonic of the highest fundamental frequency designed to be emitted by the intentional radiator because of the incorporation f a digital device. If measurements above the tenth harmonic are so required, the radiated emissions above the tenth harmonic shall comply with the general radiated emission limits applicable to the incorporated digital device, as shown in §15.109 and as based on the frequency of the emission being measured, or, except for emissions contained in the restricted frequency bands shown in §15.205, the limit on spurious emissions specified for the intentional radiator, whichever is the higher limit.

5.2 Measurement Procedure

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Position the EUT as shown in figure 4 without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set the SA on Max-Hold Mode, and then keep the EUT in transmitting mode. Record all the signals from each channel until each one has been recorded.
4. Set the SA on View mode and then plot the result on SA screen.
5. Repeat above procedures until all frequencies measured were complete.

5.3 Measurement Data

Please refer to the appending for more information.


ATTEN 20dB
RL 10.0dBm
10dB/
ΔMKR -38.83dB
-1.737GHz
ACCTON MN-500
LOW CH.
ΔMKR
-1.737 GHz
-38.83 dB
START 30MHz
STOP 3.000GHz
*RBW 100kHz
VBW 100kHz
SWP 750ms


ATTEN 20dB
RL 10.0dBm
10dB/
MKR -56.17dBm
24.01GHz
ACCTON MN-500
LOW CH.
MKR
24.01 GHz
-56.17 dBm
START 3.00GHz
STOP 25.00GHz
*RBW 100kHz
VBW 100kHz
SWP 5.50sec


ATTEN 20dB
RL 10.0dBm
10dB/
ΔMKR -37.66dB
-1.757GHz
ACCTON MN-500
MID. CH.
ΔMKR
-1.757 GHz
-37.66 dB
START 30MHz
STOP 3.000GHz
*RBW 100kHz
VBW 100kHz
*SWP 5.50sec


ATTEN 20dB
RL 10.0dBm
10dB/
MKR -55.67dBm
23.97GHz
ACCTON MN-500
MID. CH.
MKR
23.97 GHz
-55.67 dBm
START 3.00GHz
STOP 25.00GHz
*RBW 100kHz
VBW 100kHz
*SWP 5.50sec


ATTEN 20dB
RL 10.0dBm
10dB/
ΔMKR -38.83dB
-1.782GHz
ACCTON MN-500
HIGH CH.
ΔMKR
-1.782 GHz
-38.83 dB
START 30MHz
STOP 3.000GHz
*RBW 100kHz
VBW 100kHz
*SWP 5.50sec


ATTEN 20dB
RL 10.0dBm
10dB/
MKR -55.83dBm
24.01GHz
ACCTON MN-500
HIGH CH.
MKR
24.01 GHz
-55.83 dBm
START 3.00GHz
STOP 25.00GHz
*RBW 100kHz
VBW 100kHz
*SWP 5.50sec

6 - PEAK POWER SPECTRAL DENSITY

6.1 Standard Applicable

According to §15.247 (d), for direct sequence systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

6.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT was set without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Adjust the center frequency of SA on any frequency be measured and set SA to zero span mode. And then, set RBW and VBW of spectrum analyzer to proper value.
4. Repeat above procedures until all frequencies measured were complete.

6.3 Test Results

Please refer to the attached plot(s).


ATTEN 20dB
RL 10.0dBm 10dB/
MKR -28.33dBm
2.410300GHz
ACCTON MN-500
LOW CH.
MKR
2.410300 GHz
-28.33 dBm
CENTER 2.412000GHz
SPAN 6.000MHz
*RBW 3.0kHz VBW 3.0kHz *SWP 2.0ksec


ATTEN 20dB
RL 10.0dBm 10dB/
MKR -31.00dBm
2.435600GHz
ACCTON MN-500
MID. CH.
MKR
2.435600 GHz
-31.00 dBm
CENTER 2.437300GHz
SPAN 6.000MHz
*RBW 3.0kHz VBW 3.0kHz *SWP 2.0ksec


ATTEN 20dB
RL 10.0dBm 10dB/
MKR -30.50dBm
2.464900GHz
ACCTON MN-500
HIGH CH.
MKR
2.464900 GHz
-30.50 dBm
CENTER 2.462300GHz
SPAN 6.000MHz
*RBW 3.0kHz VBW 3.0kHz *SWP 2.0ksec

7 - 6 DB BANDWIDTH

7.1 Standard Applicable

According to §15.247(a)(2), for direct sequence systems, the minimum 6dB bandwidth shall be at least 500 kHz.

7.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

7.3 Measurement Data

The measured minimum 6 dB bandwidth was 10.25MHz. Please refer to appending plot for more information.

ATTEN 20dB
RL 10.0dBm
10dB/
ΔMKR .16dB
10.58MHz
ACCTON MN-500
LOW CH.
ΔMKR
10.58 MHz
.16 dB
CENTER 2.41200GHz
SPAN 50.00MHz
*RBW 100kHz
VBW 100kHz
SWP 50.0ms


ATTEN 20dB
RL 10.0dBm
10dB/
ΔMKR .50dB
10.25MHz
ACCTON MN-500
MID. CH.
ΔMKR
10.25 MHz
.50 dB
CENTER 2.43730GHz
SPAN 50.00MHz
*RBW 100kHz
VBW 100kHz
*SWP 50.0ms


ATTEN 20dB
RL 10.0dBm
10dB/
ΔMKR .67dB
10.42MHz
ACCTON MN-500
HIGH CH.
ΔMKR
10.42 MHz
.67 dB
CENTER 2.46230GHz
SPAN 50.00MHz
*RBW 100kHz
VBW 100kHz
*SWP 50.0ms

8 -100 KHZ BANDWIDTH OF BAND EDGES MEASUREMENT

8.1 Standard Applicable

According to §15.247(c), in *any* 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) see §15.2057(c)).

8.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set both RBW and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

8.3 Test Results

Please refer to the appending plot for more information.


ATTEN 20dB
RL 10.0dBm
10dB/
ΔMKR -33.33dB
-11.97MHz
ACCTON MN-500
LOW CH.
ΔMKR
-11.97 MHz
-33.33 dB
START 2.40000GHz
STOP 2.48350GHz
*RBW 100kHz
VBW 100kHz
SWP 50.0ms


ATTEN 20dB
RL 10.0dBm
10dB/
ΔMKR -52.50dB
20.88MHz
ACCTON MN-500
HIGH CH.
ΔMKR
20.88 MHz
-52.50 dB
START 2.40000GHz
STOP 2.48350GHz
*RBW 100kHz
VBW 100kHz
*SWP 50.0ms

9 - ANTENNA REQUIREMENT

9.1 Standard Applicable

For intentional device, according to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to § 15.247 (1), if transmitting antennas of directional gain greater than 6 dBi are used the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

9.2 Antenna Connected Construction

The directional gain of antenna used for transmitting is 2 dBi, and the antenna connector is designed with permanent attachment and no consideration of replacement. Please see EUT photo for details.

10 - RF EXPOSURE

According to §15.247(b)(4) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1093 RF exposure is calculated.

Limits for Maximum Permissive Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm^2)	Averaging Time (minute)
Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*($180/f^2$)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-15000	/	/	1.0	30

f = frequency in MHz
* = Plane-wave equivalent power density

MPE Prediction

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$S = PG/4\pi R^2$

Where: S = power density
P = power input to antenna
G = power gain of the antenna in the direction of interest relative to an isotropic radiator
R = distance to the center of radiation of the antenna

Maximum peak output power at antenna input terminal: 16.12 (dBm)
Maximum peak output power at antenna input terminal: 40.93 (mW)
Antenna Gain (typical): 2 (dBi)
Maximum antenna gain: 1.58 (numeric)
Prediction distance: 3 (cm)
Predication frequency: 2400 (MHz)
MPE limit for uncontrolled exposure at prediction frequency: 1 (mW/cm^2)
Power density at predication frequency: 0.572 (mW/cm^2)
Maximum allowable antenna gain: 2.76 (numeric)
Maximum allowable antenna gain: 4.41 (dBi)

Test Result

The predicted power density level at 3 cm is 0.572mW/cm². This is below the uncontrolled exposure limit of 1mW/cm² at 2400 MHz.

This EUT is intended to be installed in desktop PC only and is thus classed as mobile equipment.

11 - SPURIOUS RADIATED EMISSION DATA

11.1 Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement at BACL is ±4.0 dB.

11.2 EUT Setup

The radiated emission tests were performed in the open area 3-meter test site, using the setup in accordance with the ANSI C63.4 - 1992. The specification used was the FCC 15 Subpart C limits.

The EUT was put in the front of the test table. The host PC system was placed on the center of the back edge on the test table. The modem and the monitor were placed on the left side of the host PC system, and the printer was placed on the left side of the host PC system. The rear of the EUT and peripherals were placed flushed with the rear of the tabletop.

The keyboard was placed directly in front of the monitor, flushed with the front of tabletop. The mouse was placed next to the keyboard, flushed with the back of keyboard.

The spacing between the peripherals was 10 centimeters.

External I/O cables were draped along the edge of the test table and bundle when necessary.

The host PC system was connected with 110 Vac/60Hz power source.

11.3 Spectrum Analyzer Setup

According to FCC Rules, 47 CFR §15.33 (a) (1), the system was tested to 26GHz.

During the radiated emission test, the spectrum analyzer was set with the following configurations:

Start Frequency .....30 MHz
Stop Frequency 26GHz
Sweep Speed.....Auto
IF Bandwidth.....1 MHz
Video Bandwidth .....1 MHz
Quasi-Peak Adapter Bandwidth.....120 kHz
Quasi-Peak Adapter Mode.....Normal
Resolution Bandwidth.....1MHz

11.4 Test Procedure

For the radiated emissions test, the Host PC system and all support equipment power cords were connected to the AC floor outlet since the power supply used in the EUT did not provide an accessory power outlet.

Maximizing procedure was performed on the six (6) highest emissions to ensure EUT compliance is with all installation combinations. All data was recorded in the peak detection mode. Quasi-peak readings was performed only when an emission was found to be marginal (within -4 dBμV of specification limits), and are distinguished with a "**Qp**" in the data table.

11.5 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

Corr. Ampl. = Indicated Reading + Antenna Factor + Cable Factor - Amplifier Gain

The "**Margin**" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dBμV means the emission is 7dBμV below the maximum limit for Subpart C. The equation for margin calculation is as follows:

Margin = Corr. Ampl. – Subpart C Limit

11.6 Summary of Test Results

According to the data in section 11.7, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.207 and 15.247, and had the worst margin of:

-9.9 dBmV at **4824.00 MHz** in the **Vertical** polarization, 30 MHz to 26GHz, **Low Channel, 3 meters**

-11.3 dBmV at **4884.00 MHz** in the **Vertical** polarization, 30 MHz to 26GHz, **Middle Channel, 3 meters**

-10.8 dBmV at **4924.60 MHz** in the **Horizontal** polarization, 30 MHz to 26GHz, **High Channel, 3 meters**

-5.2 dBmV at **492.60 MHz** in the **Vertical** polarization, *Unintentional Emission*, 30 MHz to 1000MHz, **3 meters**

Intentional Emission, 30MHz to 26GHz, 3 meters

INDICATED			TABLE	ANTENNA		CORRECTION FACTOR			CORRECTED AMPLITUDE	FCC 15 Subpart C	
Frequency MHz	Ampl. dBμV/m	Comments	Angle Degree	Height Meter	Polar H/ V	Antenna dBμV/m	Cable DB	Amp. DB	Corr. Ampl. dBμV/m	Limit dBμV/m	Margin dB
Low Channel											
2412.00	101.8	Fund.	270	1.2	V	28.1	3.4	30.0	103.3	/	/
2412.00	95.2	Fund.	330	1.5	H	28.1	3.4	30.0	96.7	/	/
4824.00	36.7	RBN	310	1.2	V	32.5	4.9	30.0	44.1	54	-9.9
4824.00	35.5	RBN	0	1.5	H	32.5	4.9	30.0	42.9	54	-11.1
Middle Channel											
2442.00	100.80	Fund.	270	1.2	V	28.1	3.4	30.0	102.3	/	/
2442.00	95.3	Fund.	310	1.0	H	28.1	3.4	30.0	96.8	/	/
4874.00	35.3	RBN	60	1.2	V	32.5	4.9	30.0	42.7	54	-11.3
4884.00	34.6	RBN	90	1.5	H	32.5	4.9	30.0	42.0	54	-12.0
High Channel											
2462.30	107.0	Fund.	270	1.5	V	28.1	3.4	30.0	108.5	/	/
2462.30	93.1	Fund.	160	1.0	H	28.1	3.4	30.0	94.6	/	/
4924.60	35.8	RBN	210	1.5	H	32.5	4.9	30.0	43.2	54	-10.8
4924.60	32.4	RBN	150	1.2	V	32.5	4.9	30.0	39.8	54	-14.2

* There was no apparent emission after the 2nd harmonics.

Unintentional Emission, 30MHz to 1000MHz, 3 meters

INDICATED		TABLE	ANTENNA		CORRECTION FACTOR			CORRECTED AMPLITUDE	FCC 15 Class B	
Frequency MHz	Ampl. dBμV/m	Angle Degree	Height Meter	Polar H/ V	Antenna dBμV/m	Cable dB	Amp. dB	Corr. Ampl. dBμV/m	Limit dBμV/m	Margin dB
492.60	45.3	160	1.5	V	18.2	2.3	25.0	40.8	46	-5.2
492.60	44.2	180	1.5	H	18.2	2.3	25.0	39.7	46	-6.3
352.78	38.5	210	1.2	V	15.5	4.3	25.0	33.3	40	-6.7
352.78	42.9	270	1.2	H	15.5	4.3	25.0	37.7	46	-8.3
253.39	45.7	330	1.0	V	13.1	3.0	25.0	36.8	46	-9.2
137.90	43.6	240	1.5	V	12.9	1.8	25.0	33.3	43.5	-10.2
304.13	40.5	210	1.5	V	15.1	4.6	25.0	35.2	46	-10.8
64.1	42.7	30	1.2	V	9.7	1.3	25.0	28.7	40	-11.3
304.13	39.6	270	1.5	H	15.1	4.6	25.0	34.3	46	-11.7
253.39	42.2	60	1.2	H	13.1	3.0	25.0	33.3	46	-12.7
241.24	41.8	30	1.0	V	12.6	2.3	25.0	31.7	46	-14.3
241.24	38.6	0	1.2	H	12.6	2.3	25.0	28.5	46	-17.5

12 - CONDUCTED EMISSIONS TEST DATA

12.1 Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, and LISN.

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of any conducted emissions measurement at BACL is ±2.4 dB.

12.2 EUT Setup

The measurement was performed at the **O**pen **A**rea **T**est **S**ite, using the same setup per ANSI C63.4 - 1992 measurement procedure. The specification used was FCC 15 Subpart C limits.

The EUT inserted into the notebook. The notebook was put on the center back edge of the test table. The printer was put along with the notebook. The mouse was placed in front of the notebook.

The spacing between the peripherals was 10 centimeters.

External I/O cables were draped along the edge of the test table and bundle when necessary.

The notebook was connected with 110 Vac/60Hz power source.

12.3 Spectrum Analyzer Setup

The spectrum analyzer was set with the following configurations during the conduction test:

Start Frequency .....450 kHz
Stop Frequency .....30 MHz
Sweep Speed.....Auto
IF Bandwidth.....10 kHz
Video Bandwidth .....10 kHz
Quasi-Peak Adapter Bandwidth.....9 kHz
Quasi-Peak Adapter Mode.....Normal

12.4 Test Procedure

During the conducted emission test, the power cord of the host system was connected to the auxiliary outlet of the first LISN.

Maximizing procedure was performed on the six (6) highest emissions of each modes tested to ensure EUT is compliant with all installation combination.

All data was recorded in the peak detection mode. Quasi-peak readings were only performed when an emission was found to be marginal (within -4 dBμV of specification limits). Quasi-peak readings are distinguished with a "**Qp**".

12.5 Summary of Test Results

According to the data in section 12.6, the EUT complied with the FCC Conducted margin for a Class B device, with the *worst* margin reading of:

> **-2.1 dB■V** at **24.400 MHz** in the **Neutral** mode, 450kHz~30MHz, SONY power supply, M/N: PCGA-AC16V

12.6 Conducted Emissions Test Data

LINE CONDUCTED EMISSIONS				FCC CLASS B	
Frequency MHz	Amplitude dBμV	Detector Qp/Ave/Peak	Phase Line/Neutral	Limit dBμV	Margin dB
24.400	45.9	QP	Neutral	48	-2.1
25.100	45.2	QP	Line	48	-2.8
0.750	43.3	QP	Neutral	48	-4.7
0.710	42.6	QP	Line	48	-5.4
22.300	41.9	QP	Neutral	48	-6.1
21.900	40.8	QP	Line	48	-7.2

12.7 Plot of Conducted Emissions Test Data

Plot(s) of Conducted Emissions Test Data is presented hereinafter as reference.



13 - PROCESSING GAIN

According to §15.247(e), the processing gain of a direct sequence system shall be at least 10 dB. The processing gain represents the improvement to the received signal-to-noise ratio, after filtering to the information bandwidth, from the spreading/dispreading function.

13.1 Brief Explanations on Processing Gain Data

Please see the attached file.

13.2 Test Data for Processing Gain

Please see the attached file.

13.3 Test Setup - Processing Gain

Please see the attached file.