FCC TEST REPORT

REPORT NO.: RF950314H03
MODEL NO.: WM1212M
RECEIVED: March 15, 2006
TESTED: March 20 to 26, 2006
ISSUED: March 27, 2006

APPLICANT: Accton Technology Corporation

ADDRESS: No.1, Creation Rd. III, Science-based Industrial Park, Hsinchu, Taiwan, R.O.C.

ISSUED BY: Advance Data Technology Corporation

LAB LOCATION: No. 81-1, Lu Liao Keng, 9 Ling, Wu Lung Tsuen, Chiung Lin Hsiang, Hsin Chu Hsien, Taiwan, R.O.C.

This test report consists of 61 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CNLA, A2LA or any government agencies. The test results in the report only apply to the tested sample. The test results in this report are traceable to the national or international standards.

0536

No. 2177-01

Table of Contents

1 CERTIFICATION 4
2 SUMMARY OF TEST RESULTS 5
3 GENERAL INFORMATION 6
3.1 GENERAL DESCRIPTION OF EUT 6
3.2 DESCRIPTION OF TEST MODES 7
3.3 TEST MODE APPLICABLITY AND TESTED CHANNEL DETAIL: 8
3.4 GENERAL DESCRIPTION OF APPLIED STANDARDS 10
3.5 DESCRIPTION OF SUPPORT UNITS 11
3.6 CONFIGURATION OF SYSTEM UNDER TEST 11
4 TEST TYPES AND RESULTS 12
4.1 CONDUCTED EMISSION MEASUREMENT 12
4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT 12
4.1.2 TEST INSTRUMENTS 12
4.1.3 TEST PROCEDURES 13
4.1.4 TEST SETUP 13
4.1.5 EUT OPERATING CONDITIONS 14
4.1.6 TEST RESULTS 15
4.2 RADIATED EMISSION MEASUREMENT 17
4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT 17
4.2.2 TEST INSTRUMENTS 18
4.2.3 TEST PROCEDURES 19
4.2.4 TEST SETUP 20
4.2.5 EUT OPERATING CONDITIONS 20
4.2.6 TEST RESULTS 21
4.2.7 TEST RESULTS - DSSS 22
4.2.8 TEST RESULTS - OFDM 25
4.3 6dB BANDWIDTH MEASUREMENT 28
4.3.1 LIMITS OF 6DB BANDWIDTH MEASUREMENT 28
4.3.2 TEST INSTRUMENTS 28
4.3.3 TEST PROCEDURE 29
4.3.4 TEST SETUP 29
4.3.5 EUT OPERATING CONDITIONS 29
4.3.6 TEST RESULTS – DSSS 30
4.3.7 TEST RESULTS - OFDM 33
4.4 MAXIMUM PEAK OUTPUT POWER 36

4.4.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT 36
4.4.2 TEST INSTRUMENTS 36
4.4.3 TEST PROCEDURES 37
4.4.4 TEST SETUP 37
4.4.5 EUT OPERATING CONDITIONS 37
4.4.6 TEST RESULTS – DSSS 38
4.4.7 TEST RESULTS – OFDM 39
4.5 POWER SPECTRAL DENSITY MEASUREMENT 40
4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT 40
4.5.2 TEST INSTRUMENTS 40
4.5.3 TEST PROCEDURE 41
4.5.4 TEST SETUP 41
4.5.5 EUT OPERATING CONDITIONS 41
4.5.6 TEST RESULTS – DSSS 42
4.5.7 TEST RESULTS – OFDM 45
4.6 BAND EDGES MEASUREMENT 48
4.6.1 LIMITS OF BAND EDGES MEASUREMENT 48
4.6.2 TEST INSTRUMENTS 48
4.6.3 TEST PROCEDURE 48
4.6.4 EUT OPERATING CONDITION 48
4.6.5 TEST RESULTS - DSSS 49
4.6.6 TEST RESULTS - OFDM 53
4.7 ANTENNA REQUIREMENT 57
4.7.1 STANDARD APPLICABLE 57
4.7.2 ANTENNA CONNECTED CONSTRUCTION 57
5 PHOTOGRAPHS OF THE TEST CONFIGURATION 58
6 INFORMATION ON THE TESTING LABORATORIES 60
APPENDIX-A A-1

1 CERTIFICATION

PRODUCT :	SDIO WLAN 802.11b/g Card
BRAND NAME :	Accton
MODEL NO. :	WM1212M
TESTED:	March 20 to 26, 2006
APPLICANT :	Accton Technology Corporation
TEST ITEM:	ENGINEERING SAMPLE
STANDARDS :	47 CFR Part 15, Subpart C (Section 15.247), ANSI C63.4-2003

The above equipment (Model: WM1212M) has been tested by **Advance Data Technology Corporation**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : _____ , **DATE:** March 27, 2006
(Midoli Peng)

TECHNICAL ACCEPTANCE : _____ , **DATE:** March 27, 2006
Responsible for RF
(Hank Chung)

APPROVED BY : _____ , **DATE:** March 27, 2006
(May Chen, Deputy Manager)

2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: 47 CFR Part 15, Subpart C			
Standard Section	**Test Type and Limit**	**Result**	**REMARK**
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit Minimum passing margin is –15.11 dB at 0.240 MHz
15.247(a)(2)	Spectrum Bandwidth of a Direct Sequence Spread Spectrum System Limit: min. 500kHz	PASS	Meet the requirement of limit
15.247(b)	Maximum Peak Output Power Limit: max. 30dBm	PASS	Meet the requirement of limit
15.247(c)	Transmitter Radiated Emissions Limit: Table 15.209	PASS	Meet the requirement of limit Minimum passing margin is –8.7 dB at 565.47 MHz
15.247(d)	Power Spectral Density Limit: max. 8dBm	PASS	Meet the requirement of limit
15.247(c)	Band Edge Measurement Limit: 20 dB less than the peak value of fundamental frequency	PASS	Meet the requirement of limit

3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	SDIO WLAN 802.11b/g Card
MODEL NO.	WM1212M
FCC ID	HEDWM1212M
POWER SUPPLY	DC 3.3V from host equipment
MODULATION TYPE	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
RADIO TECHNOLOGY	DSSS, OFDM
TRANSFER RATE	802.11b: 11/5.5/2/1Mbps 802.11g: 54/48/36/24/18/12/9/6Mbps
FREQUENCY RANGE	2412MHz ~ 2462MHz
NUMBER OF CHANNEL	11
CHANNEL SPACING	5MHz
OUTPUT POWER	802.11b: 13.18mW 802.11g: 35.48mW
ANTENNA TYPE	Chip Antenna with 0dBi antenna gain
INTERFACE	SDIO interface
DATA CABLE	NA
ASSOCIATED DEVICES	NA

NOTE:

1. The EUT, operates in the 2.4GHz frequency range, lets you connect IEEE 802.11g or IEEE 802.11b devices to the network. With its high-speed data transmissions of up to 54Mbps.

2. The EUT was pre-tested under following test mode, and the test data was recorded in this report:

3. Pre-tested under the following test modes for two different filter:

Test Mode	Description
Mode A	Filter : TDK
Mode B	**Filter : Chilisin**

From the above modes, the worst case was found in **Mode B**. Therefore only the test data of the modes were recorded in this report individually.

4. The above EUT information was declared by the manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

3.2 DESCRIPTION OF TEST MODES

Operated in 2400 ~ 2483.5MHz band:

For 802.11b/g normal mode: Eleven channels are provided to this EUT.

Channel	Frequency	Channel	Frequency
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

3.3 TEST MODE APPLICABLITY AND TESTED CHANNEL DETAIL:

EUT configure mode	Applicable to				Description
	PLC	RE<1G	RE≥1G	APCM	
-	√	√	√	√	NA

Where PLC: Power Line Conducted Emission RE<1G RE: Radiated Emission below 1GHz
RE≥1G: Radiated Emission above 1GHz APCM: Antenna Port Conducted Measurement

Power Line Conducted Emission Test:

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
802.11g	1 to 11	11	OFDM	BPSK	6

Radiated Emission Test (Below 1 GHz):

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
802.11b	1 to 11	1	DSSS	CCK	11

Radiated Emission Test (Above 1 GHz):

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	CCK	11
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6

Bandedge Measurement:

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
802.11b	1 to 11	1, 11	DSSS	CCK	11
802.11g	1 to 11	1, 11	OFDM	BPSK	6

Antenna Port Conducted Measurement:

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	CCK	11
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6

3.4 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a SDIO WLAN 802.11b/g Card. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

47 CFR Part 15, Subpart C. (15.247)
ANSI C63.4 : 2003

All tests have been performed and recorded as per the above standards.

NOTE: The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of 47 CFR Part 15, Subpart B, Class B (DoC). The test report has been issued separately.

3.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

No.	Product	Brand	Model No.	Serial No.	FCC ID
1	PDA	ACER	n50	CPN500H01252500250PQ00	NA

No.	Signal cable description
1	NA

Note: 1. All power cords of the above support units are unshielded (1.8m).

3.6 CONFIGURATION OF SYSTEM UNDER TEST



NOTE: 1. Please refer to the photos of test configuration in Item 5 also.

4 TEST TYPES AND RESULTS

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. All emanations from a class B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
Test Receiver	ESCS 30	100375	Sep. 19, 2006
Line-Impedance Stabilization Network(for EUT)	ENV-216	100071	Nov. 10, 2006
ROHDE & SCHWARZ LISN	KNW-407	8/1395/12	Jul. 19, 2006
RF Signal Cable	RG233/U	Cable_CA_02	Dec. 10, 2006
Terminator(for KYORITSU)	50	2	Oct. 08, 2006
Software	ADT_Cond_V7.3.2	NA	NA

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in ADT Shielded Room No. B.
3 The VCCI Con B Registration No. is C-2193.
4 The measurement uncertainty is 2.26 dB, which is calculated as per the document CISPR 16-4 This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

4.1.3 TEST PROCEDURES

a. The EUT/HOST was placed 0.4 meters from the conducting wall of the shielded room with EUT/HOST being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.

b. Both lines of the power mains connected to the EUT/HOST were checked for maximum conducted interference.

c. The frequency range from 150 kHz to 30 MHz was searched. Emission levels over 10dB under the prescribed limits could not be reported

4.1.4 TEST SETUP



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.1.5 EUT OPERATING CONDITIONS

a. Plug the EUT into the support unit 1 (PDA) and placed it on the testing table.

b. The support unit 1 (PDA) ran a test program “Marvell RF tool” to enable EUT under transmission condition continuously at specific channel frequency.

4.1.6 TEST RESULTS

MODULATION TYPE	BPSK	CHANNEL	Channel 11
INPUT POWER (SYSTEM)	120Vac, 60 Hz	6dB BANDWIDTH	9 kHz
ENVIRONMENTAL CONDITIONS	20deg. C, 60%RH, 972hPa	TRANSFER RATE	6Mbps
TESTED BY	Eric Lee	PHASE	Line (L)

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.166	9.60	32.91	-	42.51	-	65.18	55.18	-22.67	-
2	0.240	9.60	36.61	-	46.21	-	62.10	52.10	-15.89	-
3	0.439	9.60	9.13	-	18.73	-	57.08	47.08	-38.35	-
4	0.685	9.60	10.60	-	20.20	-	56.00	46.00	-35.80	-
5	1.787	9.68	20.24	-	29.92	-	56.00	46.00	-26.08	-
6	5.000	9.73	13.85	-	23.58	-	56.00	46.00	-32.42	-

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



MODULATION TYPE	BPSK	**CHANNEL**	Channel 11
INPUT POWER (SYSTEM)	120Vac, 60 Hz	**6dB BANDWIDTH**	9 kHz
ENVIRONMENTAL CONDITIONS	20deg. C, 60%RH, 972hPa	**TRANSFER RATE**	6Mbps
TESTED BY	Eric Lee	**PHASE**	Neutral (N)

No	Freq.	Corr. Factor	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.173	9.60	27.00	-	36.60	-	64.79	54.79	-28.19	-
2	**0.240**	**9.60**	**37.39**	**-**	**46.99**	**-**	**62.10**	**52.10**	**-15.11**	**-**
3	0.361	9.60	23.84	-	33.44	-	58.71	48.71	-25.27	-
4	0.599	9.60	20.79	-	30.39	-	56.00	46.00	-25.61	-
5	2.744	9.70	20.79	-	30.49	-	56.00	46.00	-25.51	-
6	4.957	9.73	15.15	-	24.88	-	56.00	46.00	-31.12	-

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



4.2 RADIATED EMISSION MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

Frequencies (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
ADVANTEST Spectrum Analyzer	R3271A	85060311	July 07, 2006
HP Pre_Amplifier	8449B	3008A01922	Oct. 02, 2006
ROHDE & SCHWARZ Test Receiver	ESCS30	100287	Dec. 08, 2006
CHASE Broadband Antenna	VULB9168	138	Dec. 21, 2006
Schwarzbeck Horn_Antenna	BBHA9120	D124	Dec. 11, 2006
Schwarzbeck Horn_Antenna	BBHA 9170	BBHA9170153	Jan. 05, 2007
SCHWARZBECK Biconical Antenna	VHBA9123	459	Jun. 26, 2006
SCHWARZBECK Periodic Antenna	UPA6108	1148	Jun. 26, 2006
RF Switches (ARNITSU)	CS-201	1565157	NA
RF CABLE (Chaintek) 1GHz-20GHz	SF102	22054-2	Nov. 16. 2006
RF Cable(RICHTEC)	9913-30M	STCCAB-30M-1GHz-021	Jul. 16, 2006
Software	ADT_Radiated_V 5.14	NA	NA
CHANCE MOST Antenna Tower	AT-100	0203	NA
CHANCE MOST Turn Table	TT-100	0203	NA

Note: 1. The calibration interval of the above test instruments is 12 months (36 months for Periodic Antenna)and the calibrations are traceable to NML/ROC and NIST/USA.
2. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
3. The test was performed in ADT Open Site No. C.
4. The FCC Site Registration No. is 656396.
5. The VCCI Site Registration No. is R-1626.
6. The CANADA Site Registration No. is IC 4824-3.
7. The following table is for the measurement uncertainty, which is calculated as per the document CISPR 16-4. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Measurement	Value
Radiated emissions (30MHz-1GHz)	2.98 dB
Radiated emissions (1GHz ~18GHz)	2.21 dB
Radiated emissions (18GHz ~20GHz)	1.88 dB

4.2.3 TEST PROCEDURES

a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

f. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz for Average detection (AV) at frequency above 1GHz.

4.2.4 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.2.5 EUT OPERATING CONDITIONS

Same as 4.1.5

4.2.6 TEST RESULTS

Below 1GHz Worst-Case Data

MODULATION TYPE	CCK	**CHANNEL**	Channel 1
INPUT POWER (SYSTEM)	120Vac, 60 Hz	**FREQUENCY RANGE**	30-1000 MHz
ENVIRONMENTAL CONDITIONS	20deg. C, 68%RH, 972hPa	**TRANSFER RATE**	11Mbps
TESTED BY	Rex Huang	**DETECTOR FUNCTION**	Quasi-Peak, 120kHz

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	214.49	24.50 QP	43.50	-19.00	1.78 H	148	12.70	11.80
2	370.48	28.80 QP	46.00	-17.20	1.00 H	111	11.30	17.50
3	448.49	30.10 QP	46.00	-15.90	1.00 H	308	10.40	19.70
4	565.47	32.70 QP	46.00	-13.30	1.84 H	300	10.00	22.70
5	604.47	30.30 QP	46.00	-15.70	1.69 H	195	6.70	23.60
6	721.27	30.00 QP	46.00	-16.00	1.22 H	60	4.50	25.50
7	877.28	32.80 QP	46.00	-13.20	1.12 H	336	5.10	27.70

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	214.49	22.30 QP	43.50	-21.20	1.00 V	252	10.50	11.80
2	370.48	26.20 QP	46.00	-19.80	1.00 V	3	8.80	17.50
3	448.48	30.40 QP	46.00	-15.60	1.00 V	282	10.80	19.70
4	**565.47**	**37.30 QP**	**46.00**	**-8.70**	**1.00 V**	**48**	**14.70**	**22.70**
5	604.69	34.40 QP	46.00	-11.60	1.00 V	24	10.80	23.60
6	721.67	30.20 QP	46.00	-15.80	1.16 V	110	4.70	25.60
7	877.50	32.40 QP	46.00	-13.60	1.42 V	239	4.70	27.70

REMARKS:
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.

4.2.7 TEST RESULTS - DSSS

802.11b DSSS modulation

MODE	Channel 1	**FREQUENCY RANGE**	1000~25000MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	**DETECTOR FUNCTION & BANDWIDTH**	Peak (PK) Average (AV) 1 MHz
ENVIRONMENTAL CONDITIONS	19 deg. C, 63%RH, 972hPa	**TESTED BY**	Tony Chen

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	51.20 PK	74.00	-22.80	1.05 H	305	17.50	33.70
1	2390.00	39.60 AV	54.00	-14.40	1.05 H	305	5.90	33.70
2	*2412.00	101.60 PK			1.05 H	305	71.80	29.80
2	*2412.00	98.30 AV			1.05 H	305	68.40	29.80
3	4824.00	45.50 PK	74.00	-28.50	1.15 H	157	10.40	35.10
3	4824.00	34.70 AV	54.00	-19.30	1.15 H	157	-0.40	35.10
4	7236.00	46.20 PK	74.00	-27.80	1.00 H	354	5.70	40.50
4	7236.00	34.40 AV	54.00	-19.60	1.00 H	354	-6.10	40.50

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	39.70 PK	74.00	-34.30	1.17 V	253	6.00	33.70
1	2390.00	24.50 AV	54.00	-29.50	1.17 V	253	-9.20	33.70
2	*2412.00	90.10 PK			1.17 V	253	60.20	29.80
2	*2412.00	83.20 AV			1.17 V	253	53.40	29.80
3	4824.00	46.50 PK	74.00	-27.50	1.03 V	123	11.40	35.10
3	4824.00	35.70 AV	54.00	-18.30	1.03 V	123	0.60	35.10
4	7236.00	46.00 PK	74.00	-28.00	1.00 V	360	5.50	40.50
4	7236.00	34.30 AV	54.00	-19.70	1.00 V	360	-6.20	40.50

REMARKS:
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. The limit value is defined as per 15.247
6. " * " : Fundamental frequency

MODE	Channel 6	**FREQUENCY RANGE**	1000~25000MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	**DETECTOR FUNCTION & BANDWIDTH**	Peak (PK) Average (AV) 1 MHz
ENVIRONMENTAL CONDITIONS	19 deg. C, 63%RH, 972hPa	**TESTED BY**	Tony Chen

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	101.30 PK			1.04 H	311	71.40	29.90
1	*2437.00	98.10 AV			1.04 H	311	68.20	29.90
2	4874.00	46.40 PK	74.00	-27.60	1.14 H	254	11.10	35.30
2	4874.00	35.20 AV	54.00	-18.80	1.14 H	254	-0.10	35.30
3	7311.00	45.60 PK	74.00	-28.40	1.02 H	111	4.90	40.70
3	7311.00	34.20 AV	54.00	-19.80	1.02 H	111	-6.40	40.70

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	89.70 PK			1.23 V	276	59.80	29.90
1	*2437.00	82.90 AV			1.23 V	276	53.00	29.90
2	4874.00	46.50 PK	74.00	-27.50	1.24 V	360	11.10	35.30
2	4874.00	35.70 AV	54.00	-18.30	1.24 V	360	0.40	35.30
3	7311.00	45.20 PK	74.00	-28.80	1.13 V	236	4.50	40.70
3	7311.00	34.40 AV	54.00	-19.60	1.13 V	236	-6.30	40.70

REMARKS:
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. The limit value is defined as per 15.247
6. " * " : Fundamental frequency

MODE	Channel 11	**FREQUENCY RANGE**	1000~25000MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	**DETECTOR FUNCTION & BANDWIDTH**	Peak (PK) Average (AV) 1 MHz
ENVIRONMENTAL CONDITIONS	19 deg. C, 63%RH, 972hPa	**TESTED BY**	Tony Chen

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	102.70 PK			1.04 H	309	72.60	30.00
1	*2462.00	95.50 AV			1.04 H	309	65.50	30.00
2	2483.50	53.80 PK	74.00	-20.20	1.04 H	309	23.70	30.10
2	2483.50	37.40 AV	54.00	-16.60	1.04 H	309	7.30	30.10
3	4924.00	46.90 PK	74.00	-27.10	1.13 H	234	11.40	35.50
3	4924.00	35.90 AV	54.00	-18.10	1.13 H	234	0.40	35.50
4	7386.00	45.70 PK	74.00	-28.30	1.00 H	264	4.90	40.80
4	7386.00	34.90 AV	54.00	-19.10	1.00 H	264	-5.90	40.80

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	91.90 PK			1.00 V	352	61.90	30.00
1	*2462.00	84.90 AV			1.00 V	352	54.90	30.00
2	2483.50	43.00 PK	74.00	-31.00	1.00 V	352	12.90	30.10
2	2483.50	26.80 AV	54.00	-27.20	1.00 V	352	-3.30	30.10
3	4924.00	48.90 PK	74.00	-25.10	1.01 V	120	13.40	35.50
3	4924.00	37.80 AV	54.00	-16.20	1.01 V	120	2.30	35.50
4	7386.00	45.80 PK	74.00	-28.20	1.00 V	360	4.90	40.80
4	7386.00	34.70 AV	54.00	-19.30	1.00 V	360	-6.10	40.80

REMARKS:
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. The limit value is defined as per 15.247
6. " * " : Fundamental frequency

4.2.8 TEST RESULTS - OFDM

802.11g Normal OFDM modulation

MODE	Channel 1	**FREQUENCY RANGE**	1000~25000MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	**DETECTOR FUNCTION & BANDWIDTH**	Peak (PK) Average (AV) 1 MHz
ENVIRONMENTAL CONDITIONS	19 deg. C, 63%RH, 972hPa	**TESTED BY**	Tony Chen

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	58.00 PK	74.00	-16.00	1.03 H	308	24.30	33.70
1	2390.00	42.20 AV	54.00	-11.80	1.03 H	308	8.50	33.70
2	*2412.00	100.30 PK			1.03 H	308	70.50	29.80
2	*2412.00	92.70 AV			1.03 H	308	62.90	29.80
3	4824.00	48.00 PK	74.00	-26.00	1.00 H	205	12.90	35.10
3	4824.00	35.90 AV	54.00	-18.10	1.00 H	205	0.80	35.10
4	7236.00	45.50 PK	74.00	-28.50	1.00 H	309	5.00	40.50
4	7236.00	34.40 AV	54.00	-19.60	1.00 H	309	-6.10	40.50

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	50.30 PK	74.00	-23.70	1.10 V	16	16.60	33.70
1	2390.00	34.30 AV	54.00	-19.70	1.10 V	16	0.60	33.70
2	*2412.00	92.60 PK			1.10 V	16	62.80	29.80
2	*2412.00	84.80 AV			1.10 V	16	55.00	29.80
3	4824.00	49.90 PK	74.00	-24.10	1.00 V	106	14.80	35.10
3	4824.00	38.30 AV	54.00	-15.70	1.00 V	106	3.20	35.10
4	7236.00	45.20 PK	74.00	-28.80	1.01 V	305	4.70	40.50
4	7236.00	34.30 AV	54.00	-19.70	1.01 V	305	-6.20	40.50

REMARKS:
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. The limit value is defined as per 15.247
6. " * " : Fundamental frequency

MODE	Channel 6	**FREQUENCY RANGE**	1000~25000MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	**DETECTOR FUNCTION & BANDWIDTH**	Peak (PK) Average (AV) 1 MHz
ENVIRONMENTAL CONDITIONS	19 deg. C, 63%RH, 972hPa	**TESTED BY**	Tony Chen

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	100.70 PK			1.02 H	314	70.80	29.90
1	*2437.00	92.90 AV			1.02 H	314	63.00	29.90
2	4874.00	49.10 PK	74.00	-24.90	1.10 H	360	13.80	35.30
2	4874.00	36.10 AV	54.00	-17.90	1.10 H	360	0.80	35.30
3	7311.00	45.50 PK	74.00	-28.50	1.04 H	320	4.80	40.70
3	7311.00	34.60 AV	54.00	-19.40	1.04 H	320	-6.10	40.70

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	92.80 PK			1.12 V	23	62.90	29.90
1	*2437.00	85.10 AV			1.12 V	23	55.20	29.90
2	4874.00	49.00 PK	74.00	-25.00	1.23 V	111	13.70	35.30
2	4874.00	37.30 AV	54.00	-16.70	1.23 V	111	2.00	35.30
3	7311.00	45.10 PK	74.00	-28.90	1.11 V	10	4.40	40.70
3	7311.00	34.20 AV	54.00	-19.80	1.11 V	10	-6.50	40.70

REMARKS:
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. The limit value is defined as per 15.247
6. “ * “ : Fundamental frequency

MODE	Channel 11	**FREQUENCY RANGE**	1000~25000MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	**DETECTOR FUNCTION & BANDWIDTH**	Peak (PK) Average (AV) 1 MHz
ENVIRONMENTAL CONDITIONS	19 deg. C, 63%RH, 972hPa	**TESTED BY**	Tony Chen

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	99.60 PK			1.52 H	125	69.50	30.00
1	*2462.00	91.40 AV			1.52 H	125	61.40	30.00
2	2483.50	55.90 PK	74.00	-18.10	1.52 H	125	25.80	30.10
2	2483.50	40.70 AV	54.00	-13.30	1.52 H	125	10.60	30.10
3	4924.00	47.50 PK	74.00	-26.50	1.19 H	226	12.00	35.50
3	4924.00	36.20 AV	54.00	-17.80	1.19 H	226	0.70	35.50
4	7386.00	46.00 PK	74.00	-28.00	1.10 H	350	5.20	40.80
4	7386.00	35.00 AV	54.00	-19.00	1.10 H	350	-5.90	40.80

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	89.90 PK			1.42 V	26	59.90	30.00
1	*2462.00	81.70 AV			1.42 V	26	51.70	30.00
2	2483.50	46.20 PK	74.00	-27.80	1.42 V	26	16.10	30.10
2	2483.50	31.00 AV	54.00	-23.00	1.42 V	26	0.90	30.10
3	4924.00	49.10 PK	74.00	-24.90	1.19 V	267	13.60	35.50
3	4924.00	37.10 AV	54.00	-16.90	1.19 V	267	1.60	35.50
4	7386.00	46.40 PK	74.00	-27.60	1.23 V	247	5.60	40.80
4	7386.00	35.10 AV	54.00	-18.90	1.23 V	247	-5.80	40.80

REMARKS:
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. The limit value is defined as per 15.247
6. " * " : Fundamental frequency

4.3 6dB BANDWIDTH MEASUREMENT

4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSP40	100036	Nov. 23, 2006

NOTE:

1. The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.3.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100 kHz RBW and 100 kHz VBW. The 6 dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6 dB.

4.3.4 TEST SETUP



For the actual test configuration, please refer to the related Item – Photographs of the Test Configuration.

4.3.5 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.3.6 TEST RESULTS –DSSS

802.11b DSSS modulation

MODULATION TYPE	CCK	**TRANSFER RATE**	11Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	**ENVIRONMENTAL CONDITIONS**	22deg. C, 68%RH, 972hPa
TESTED BY	Rex Huang		

CHANNEL	CHANNEL FREQUENCY (MHz)	6 dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS/FAIL
1	2412	9.55	0.5	PASS
6	2437	9.55	0.5	PASS
11	2462	9.55	0.5	PASS

CH1


*RBW 100 kHz
*VBW 100 kHz
SWT 5 ms
Delta 1 [T1]
-0.46 dB
9.550000000 MHz
Ref 20 dBm
*Att 30 dB
20 Offset 1 dB
Marker 1 [T1]
-5.27 dBm
2.407000000 GHz
1 PK
VIEW
D1 0.29 dBm
D2 -5.71 dBm
F1
F2
Center 2.412 GHz
2.5 MHz/
Span 25 MHz

CH6


*RBW 100 kHz
*VBW 100 kHz
SWT 5 ms
Delta 1 [T1]
0.04 dB
9.550000000 MHz
Ref 20 dBm
*Att 30 dB
20 Offset 1 dB
Marker 1 [T1]
-5.71 dBm
2.432000000 GHz
1 PK
VIEW
D1 -0.17 dBm
D2 -6.17 dBm
F1
F2
2.5 MHz/
Span 25 MHz

CH11


*RBW 100 kHz
*VBW 100 kHz
SWT 5 ms
Delta 1 [T1]
0.29 dB
9.550000000 MHz
Ref 20 dBm
*Att 30 dB
20 Offset 1 dB
Marker 1 [T1]
-5.55 dBm
2.457000000 GHz
1 PK
VIEW
D1 0.06 dBm
D2 -5.94 dBm
F1
F2
A
LVL
PRN
Center 2.462 GHz
2.5 MHz/
Span 25 MHz

4.3.7 TEST RESULTS-OFDM

802.11g OFDM modulation

MODULATION TYPE	BPSK	**TRANSFER RATE**	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	**ENVIRONMENTAL CONDITIONS**	22deg. C, 68%RH, 972hPa
TESTED BY	Rex Huang		

CHANNEL	CHANNEL FREQUENCY (MHz)	6 dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS/FAIL
1	2412	16.60	0.5	PASS
6	2437	16.55	0.5	PASS
11	2462	16.60	0.5	PASS

CH1


*RBW 100 kHz
*VBW 100 kHz
Delta 1 [T1]
-0.25 dB
16.600000000 MHz
Ref 20 dBm
*Att 30 dB
SWT 5 ms
20 Offset 1 dB
Marker 1 [T1]
-10.06 dBm
2.403700000 GHz
1 PK
VIEW
D1 -4.47 dBm
D2 -10.47 dBm
F1
F2
Center 2.412 GHz
2.5 MHz/
Span 25 MHz

CH6


*RBW 100 kHz
*VBW 100 kHz
Delta 1 [T1]
-0.23 dB
16.550000000 MHz
Ref 20 dBm
*Att 30 dB
SWT 5 ms
20 Offset 1 dB
Marker 1 [T1]
-9.67 dBm
2.428750000 GHz
1 PK
VIEW
D1 -4.78 dBm
D2 -10.78 dBm
F1
F2
Center 2.437 GHz
2.5 MHz/
Span 25 MHz

CH11


RBW 100 kHz
VBW 100 kHz
SWT 5 ms
Delta 1 [T1]
0.21 dB
16.600000000 MHz
Ref 20 dBm
Att 30 dB
20 Offset 1 dB
Marker 1 [T1]
-10.73 dBm
2.453700000 GHz
1 PK
VIEW
D1 -5.03 dBm
D2 -11.03 dBm
F1
F2
2.5 MHz/
Span 25 MHz

4.4 MAXIMUM PEAK OUTPUT POWER

4.4.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT

The Maximum Peak Output Power Measurement is 30dBm.

4.4.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSP40	100036	Nov. 23, 2006
Agilent SIGNAL GENERATOR	E8257C	MY43320668	Dec. 07, 2006
TEKTRONIX OSCILLOSCOPE	TDS380	B016335	Jun. 22, 2006
NARDA DETECTOR	4503A	FSCM99899	NA

NOTE:
The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.4.3 TEST PROCEDURES

1. A detector was used on the output port of the EUT. An oscilloscope was used to read the peak response of the detector.
2. Replaced the EUT by the signal generator. The center frequency of the S.G was adjusted to the center frequency of the measured channel.
3. Adjusted the power to have the same peak reading on oscilloscope. Record the power level.

4.4.4 TEST SETUP



4.4.5 EUT OPERATING CONDITIONS

Same as Item 4.3.5

4.4.6 TEST RESULTS – DSSS

802.11b DSSS modulation

MODULATION TYPE	CCK	**TRANSFER RATE**	11Mbps
INPUT POWER (SYSTEM)	120Vac, 60Hz	**ENVIRONMENTAL CONDITIONS**	22deg. C, 68%RH, 972hPa
TESTED BY	Rex Huang		

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
1	2412	12.59	11.00	30	PASS
6	2437	13.18	11.20	30	PASS
11	2462	12.30	10.90	30	PASS

4.4.7 TEST RESULTS –OFDM

802.11g OFDM modulation

MODULATION TYPE	BPSK	**TRANSFER RATE**	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60Hz	**ENVIRONMENTAL CONDITIONS**	22deg. C, 68%RH, 972hPa
TESTED BY	Rex Huang		

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
1	2412	35.48	15.50	30	PASS
6	2437	33.88	15.30	30	PASS
11	2462	32.36	15.10	30	PASS

4.5 POWER SPECTRAL DENSITY MEASUREMENT

4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

4.5.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSP40	100036	Nov. 23, 2006

NOTE:

1. The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.5.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator, the bandwidth of the fundamental frequency was measured with the spectrum analyzer using 3 kHz RBW and 30 kHz VBW, set sweep time=span/3kHz. The power spectral density was measured and recorded.
The sweep time is allowed to be longer than span/3KHz for a full response of the mixer in the spectrum analyzer.

4.5.4 TEST SETUP



4.5.5 EUT OPERATING CONDITIONS

Same as 4.3.5

4.5.6 TEST RESULTS –DSSS

802.11b DSSS modulation

MODULATION TYPE	CCK	**TRANSFER RATE**	11Mbps
INPUT POWER (SYSTEM)	120Vac, 60Hz	**ENVIRONMENTAL CONDITIONS**	22deg. C, 68%RH, 972hPa
TESTED BY	Rex Huang		

CHANNEL NUMBER	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3 KHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS/FAIL
1	2412	-13.45	8	PASS
6	2437	-13.89	8	PASS
11	2462	-13.78	8	PASS

CH1


RBW 3 kHz
VBW 30 kHz
SWT 500 s
Marker 1 [T1]
-13.45 dBm
2.411341000 GHz
Ref 20 dBm
Att 30 dB
20 Offset 1 dB
1 PK
VIEW
A
LVL
PRN
Center 2.411341 GHz
150 kHz/
Span 1.5 MHz

CH6


RBW 3 kHz
VBW 30 kHz
SWT 500 s
Marker 1 [T1]
-13.89 dBm
2.436341000 GHz
Ref 20 dBm
Att 30 dB
20 Offset 1 dB
1 PK
VIEW
A
LVL
PRN
150 kHz/
Span 1.5 MHz

CH11


*RBW 3 kHz
*VBW 30 kHz
*SWT 500 s
Marker 1 [T1]
-13.78 dBm
2.461342000 GHz
Ref 20 dBm
*Att 30 dB
20 Offset 1 dB
1 PK
VIEW
A
LVL
PRN
Center 2.461342 GHz
150 kHz/
Span 1.5 MHz

4.5.7 TEST RESULTS –OFDM

802.11g OFDM modulation

MODULATION TYPE	BPSK	**TRANSFER RATE**	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60Hz	**ENVIRONMENTAL CONDITIONS**	22deg. C, 68%RH, 972hPa
TESTED BY	Rex Huang		

CHANNEL NUMBER	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3 KHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS/FAIL
1	2412	-18.43	8	PASS
6	2437	-18.54	8	PASS
11	2462	-18.66	8	PASS

CH1


*RBW 3 kHz
*VBW 30 kHz
*SWT 500 s
Marker 1 [T1]
-18.43 dBm
2.411074000 GHz
Ref 20 dBm
*Att 30 dB
20 Offset 1 dB
1 PK
VIEW
A
LVL
PRN
150 kHz/
Span 1.5 MHz

CH6


*RBW 3 kHz
*VBW 30 kHz
*SWT 500 s
Marker 1 [T1]
-18.54 dBm
2.436076000 GHz
Ref 20 dBm
*Att 30 dB
20 Offset 1 dB
1 PK
VIEW
A
LVL
PRN
150 kHz/
Span 1.5 MHz

CH11


*RBW 3 kHz
*VBW 30 kHz
*SWT 500 s
Marker 1 [T1]
-18.66 dBm
2.464179000 GHz
Ref 20 dBm
*Att 30 dB
20 Offset 1 dB
1 PK
VIEW
A
LVL
PRN
Center 2.464176 GHz
150 kHz/
Span 1.5 MHz

4.6 BAND EDGES MEASUREMENT

4.6.1 LIMITS OF BAND EDGES MEASUREMENT

Below –20dB of the highest emission level of operating band (in 1MHz Resolution Bandwidth).

4.6.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSP40	100036	Nov. 23, 2006

NOTE:

1. The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.6.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low lose cable. Set RBW spectrum analyzer to 1 MHz and set VBW spectrum analyzer to 10 Hz with suitable frequency span including 1 MHz bandwidth from band edge. The band edges was measured and recorded.

The spectrum plots (Peak RBW=VBW=100kHz ; Average RBW=1MHz, VBW=10Hz) are attached on the following pages.

4.6.4 EUT OPERATING CONDITION

Same as Item 4.3.5

4.6.5 TEST RESULTS - DSSS

The spectrum plots are attached on the following page. D1 line indicates the highest level, D2 line indicates the 20dB offset below D1. It shows compliance with the requirement in part 15.247(C).

Note - The delta method is only used up to 2 MHz away from the restricted bandage, The radiated emissions which located in other restricted frequency band, the result, please refer to 4.2.

NOTE (Peak):
The band edge emission plot of DSSS technique on the following first page show 50.44dB delta between carrier maximum power and local maximum emission in restrict band (2.3900GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2 is 101.6dBuV/m, so the maximum field strength in restrict band is 101.6-50.44=51.16dBuV/m which is under 74 dBuV/m limit.

The band edge emission plot of DSSS technique on the following first page shows 48.87dB delta between carrier maximum power and local maximum emission in restrict band (2.4835GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2 is 102.7dBuV/m, so the maximum field strength in restrict band is 102.7-48.87=53.83dBuV/m which is under 74 dBuV/m limit.

NOTE (Average):
The band edge emission plot of DSSS technique on the following second page shows 58.71dB delta between carrier maximum power and local maximum emission in restrict band (2.3900GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2 is 98.3dBuV/m, so the maximum field strength in restrict band is 98.3-58.71=39.59dBuV/m which is under 54 dBuV/m limit.

The band edge emission plot of DSSS technique on the following second page shows 58.07dB delta between carrier maximum power and local maximum emission in restrict band (2.4835GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2 is 95.5dBuV/m, so the maximum field strength in restrict band is 95.5-58.07=37.43dBuV/m which is under 54 dBuV/m limit.

CH1


RBW 100 kHz
VBW 100 kHz
SWT 10 ms
Marker 1 [T1]
0.59 dBm
2.412000000 GHz
Ref 20 dBm
Att 30 dB
20 Offset 1 dB
Marker 2 [T1]
-49.85 dBm
2.390000000 GHz
Marker 3 [T1]
-47.51 dBm
2.400000000 GHz
Marker 4 [T1]
-44.57 dBm
2.398800000 GHz
D1 0.59 dBm
D2 -19.41 dBm
1 PK VIEW
A
LVL
PRN
F1
F2
Center 2.372 GHz
10 MHz/
Span 100 MHz

CH11


RBW 100 kHz
VBW 100 kHz
SWT 10 ms
Marker 1 [T1]
0.31 dBm
2.461800000 GHz
Ref 20 dBm
Att 30 dB
20 Offset 1 dB
Marker 2 [T1]
-48.56 dBm
2.483500000 GHz
Marker 3 [T1]
-49.89 dBm
2.500000000 GHz
Marker 4 [T1]
-47.73 dBm
2.495400000 GHz
D1 0.31 dBm
D2 -19.69 dBm
1 PK VIEW
A
LVL
PRN
F1
F2
Center 2.502 GHz
10 MHz/
Span 100 MHz

CH1


RBW 1 MHz
VBW 10 Hz
SWT 25 s
Marker 1 [T1]
-1.37 dBm
2.413400000 GHz
Ref 20 dBm
Att 30 dB
20 Offset 1 dB
Marker 2 [T1]
-60.08 dBm
2.390000000 GHz
Marker 3 [T1]
-49.77 dBm
2.400000000 GHz
1 PK
VIEW
D1 -1.37 dBm
D2 -21.37 dBm
F1
F2
LVL
PRN
Center 2.372 GHz
10 MHz/
Span 100 MHz

CH11


RBW 1 MHz
VBW 10 Hz
SWT 25 s
Marker 1 [T1]
-1.70 dBm
2.463200000 GHz
Ref 20 dBm
Att 30 dB
20 Offset 1 dB
Marker 2 [T1]
-59.77 dBm
2.483500000 GHz
Marker 3 [T1]
-60.37 dBm
2.500000000 GHz
1 PK
VIEW
D1 -1.7 dBm
D2 -21.7 dBm
F1
F2
LVL
PRN
Center 2.502 GHz
10 MHz/
Span 100 MHz

CH1


RBW 100 kHz
VBW 100 kHz
SWT 2.5 s
Marker 4 [T1]
-47.29 dBm
12.060000000 GHz
Ref 20 dBm
Att 30 dB
20 Offset 1 dB
Marker 1 [T1]
-48.67 dBm
4.824000000 GHz
Marker 2 [T1]
-48.73 dBm
7.236000000 GHz
Marker 3 [T1]
-47.96 dBm
9.648000000 GHz
1 PK
VIEW
D1 -0.09 dBm
D2 -20.09 dBm
Start 30 MHz
2.497 GHz/
Stop 25 GHz

CH11


RBW 100 kHz
VBW 100 kHz
SWT 2.5 s
Marker 1 [T1]
-48.71 dBm
4.924000000 GHz
Ref 20 dBm
Att 30 dB
20 Offset 1 dB
Marker 2 [T1]
-47.26 dBm
7.386000000 GHz
Marker 3 [T1]
-48.13 dBm
9.848000000 GHz
Marker 4 [T1]
-49.25 dBm
12.310000000 GHz
1 PK
VIEW
D1 0.08 dBm
D2 -19.92 dBm
Start 30 MHz
2.497 GHz/
Stop 25 GHz

4.6.6 TEST RESULTS -OFDM

The spectrum plots are attached on the following page. D1 line indicates the highest level, D2 line indicates the 20dB offset below D1. It shows compliance with the requirement in part 15.247(C).

Note - The delta method is only used up to 2 MHz away from the restricted bandage, The radiated emissions which located in other restricted frequency band, the result, please refer to 4.2.

NOTE (Peak):
The band edge emission plot of OFDM technique on the following first page show 42.33dB delta between carrier maximum power and local maximum emission in restrict band (2.3900GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2 is 100.3dBuV/m, so the maximum field strength in restrict band is 100.3-42.33=57.97dBuV/m which is under 74 dBuV/m limit.

The band edge emission plot of OFDM technique on the following first page shows 43.67dB delta between carrier maximum power and local maximum emission in restrict band (2.4835GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2 is 99.6dBuV/m, so the maximum field strength in restrict band is 99.6-43.67=55.93dBuV/m which is under 74 dBuV/m limit.

NOTE (Average):
The band edge emission plot of OFDM technique on the following second page shows 50.53dB delta between carrier maximum power and local maximum emission in restrict band (2.3900GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2 is 92.7dBuV/m, so the maximum field strength in restrict band is 92.7-50.53=42.17dBuV/m which is under 54 dBuV/m limit.

The band edge emission plot of OFDM technique on the following second page shows 50.67dB delta between carrier maximum power and local maximum emission in restrict band (2.4835GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2 is 91.4dBuV/m, so the maximum field strength in restrict band is 91.4-50.67=40.73dBuV/m which is under 54 dBuV/m limit.

CH1


RBW 100 kHz
VBW 100 kHz
SWT 10 ms
Marker 1 [T1]
-4.47 dBm
2.414200000 GHz
Ref 20 dBm
Att 30 dB
20 Offset 1 dB
Marker 2 [T1]
-46.80 dBm
2.390000000 GHz
Marker 3 [T1]
-35.40 dBm
2.400000000 GHz
Marker 4 [T1]
-35.40 dBm
2.400000000 GHz
D1 -4.47 dBm
D2 -24.47 dBm
1 PK VIEW
A
LVL
PRN
F1
F2
10 MHz/
Span 100 MHz

CH11


RBW 100 kHz
VBW 100 kHz
SWT 10 ms
Marker 1 [T1]
-4.72 dBm
2.459600000 GHz
Ref 20 dBm
Att 30 dB
20 Offset 1 dB
Marker 2 [T1]
-48.39 dBm
2.483500000 GHz
Marker 3 [T1]
-49.08 dBm
2.500000000 GHz
Marker 4 [T1]
-46.59 dBm
2.487000000 GHz
D1 -4.72 dBm
D2 -24.72 dBm
1 PK VIEW
A
LVL
PRN
F1
F2
Center 2.502 GHz
10 MHz/
Span 100 MHz

CH1


*RBW 1 MHz
*VBW 10 Hz
SWT 25 s
Marker 1 [T1]
-4.29 dBm
2.418000000 GHz
Ref 20 dBm
*Att 30 dB
20 Offset 1 dB
Marker 2 [T1]
-54.82 dBm
2.390000000 GHz
Marker 3 [T1]
-42.28 dBm
2.400000000 GHz
1 PK
VIEW
D1 -4.29 dBm
D2 -24.29 dBm
LVL
PRN
F1
F2
10 MHz/
Span 100 MHz
Date: 20.MAR.2006 09:08:43

CH11


*RBW 1 MHz
*VBW 10 Hz
SWT 25 s
Marker 1 [T1]
-4.58 dBm
2.460200000 GHz
Ref 20 dBm
*Att 30 dB
20 Offset 1 dB
Marker 2 [T1]
-55.25 dBm
2.483500000 GHz
Marker 3 [T1]
-58.63 dBm
2.500000000 GHz
1 PK
VIEW
D1 -4.58 dBm
D2 -24.58 dBm
LVL
PRN
F1
F2
10 MHz/
Span 100 MHz

CH1


RBW 100 kHz
VBW 100 kHz
SWT 2.5 s
Marker 1 [T1]
-48.63 dBm
4.824000000 GHz
Ref 20 dBm
Att 30 dB
20 Offset 1 dB
Marker 2 [T1]
-48.18 dBm
7.236000000 GHz
Marker 3 [T1]
-47.30 dBm
9.648000000 GHz
Marker 4 [T1]
-49.10 dBm
12.060000000 GHz
1 PK
VIEW
D1 -4.65 dBm
D2 -24.65 dBm
LVL
PRN
Start 30 MHz
2.497 GHz/
Stop 25 GHz

CH11


RBW 100 kHz
VBW 100 kHz
SWT 2.5 s
Marker 1 [T1]
-47.65 dBm
4.924000000 GHz
Ref 20 dBm
Att 30 dB
20 Offset 1 dB
Marker 2 [T1]
-47.35 dBm
7.386000000 GHz
Marker 3 [T1]
-47.81 dBm
9.848000000 GHz
Marker 4 [T1]
-48.50 dBm
12.310000000 GHz
1 PK
VIEW
D1 -5.24 dBm
D2 -25.24 dBm
LVL
PRN
Start 30 MHz
2.497 GHz/
Stop 25 GHz

4.7 ANTENNA REQUIREMENT

4.7.1 STANDARD APPLICABLE

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.
And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

4.7.2 ANTENNA CONNECTED CONSTRUCTION

The antenna used in this product is Chip antenna without connector. The maximum Gain of the antenna is 0 dBi.

5 PHOTOGRAPHS OF THE TEST CONFIGURATION

CONDUCTED EMISSION TEST



RADIATED EMISSION TEST

6 INFORMATION ON THE TESTING LABORATORIES

We, ADT Corp., were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025:

USA	FCC, UL, A2LA
Germany	TUV Rheinland
Japan	VCCI
Norway	NEMKO
Canada	INDUSTRY CANADA, CSA
R.O.C.	CNLA, BSMI, DGT
Netherlands	Telefication
Singapore	PSB, GOST-ASIA (MOU)
Russia	CERTIS (MOU)

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site: www.adt.com.tw/index.5/phtml.
If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab:
Tel: 886-2-26052180
Fax: 886-2-26052943

Hsin Chu EMC/RF Lab:
Tel: 886-3-5935343
Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety/Telecom Lab:
Tel: 886-3-3183232
Fax: 886-3-3185050

Email: service@adt.com.tw
Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.

APPENDIX-A

MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.