ADT CORP.

FCC TEST REPORT

REPORT NO.: RF910131R05
MODEL NO.: WN3501C
(the other OEM models please refer to page 6)
RECEIVED: Jan. 31, 2002
TESTED: Feb. 26 ~ Mar. 4, 2002

APPLICANT: ACCTON TECHNOLOGY CORPORATION

ADDRESS: No. 1, Creation Rd., III, Science-Based Industrial Park, Hsinchu, Taiwan, R.O.C.

ISSUED BY: Advance Data Technology Corporation

LAB LOCATION: 47 14th Lin, Chiapau Tsun, Linko, Taipei, Taiwan, R.O.C.

This test report consists of 48 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CNLA, NVLAP or any government agencies. The test results in the report only apply to the tested sample.

CNLA
0528
ILAC MRA

NVLAP®
Lab Code: 200102-0

Table of Contents

1 CERTIFICATION 4
2 SUMMARY OF TEST RESULTS 5
3 GENERAL INFORMATION 6
3.1 GENERAL DESCRIPTION OF EUT 6
3.2 DESCRIPTION OF TEST MODES 7
3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS 7
3.4 DESCRIPTION OF SUPPORT UNITS 8
4 TEST TYPES AND RESULTS 9
4.1 CONDUCTED EMISSION MEASUREMENT 9
4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT 9
4.1.2 TEST INSTRUMENTS 9
4.1.3 TEST PROCEDURES 10
4.1.4 TEST SETUP 10
4.1.5 EUT OPERATING CONDITIONS 11
4.1.6 TEST RESULTS 12
4.2 RADIATED EMISSION MEASUREMENT 18
4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT 18
4.2.2 TEST INSTRUMENTS 19
4.2.3 TEST PROCEDURES 20
4.2.4 TEST SETUP 21
4.2.5 EUT OPERATING CONDITIONS 21
4.2.6 TEST RESULTS 22
4.3 6dB BANDWIDTH MEASUREMENT 26
4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT 26
4.3.2 TEST INSTRUMENTS 26
4.3.3 TEST PROCEDURE 27
4.3.4 TEST SETUP 27
4.3.5 EUT OPERATING CONDITIONS 27
4.3.6 TEST RESULTS 28
4.4 MAXIMUM PEAK OUTPUT POWER 32
4.4.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT 32
4.4.2 INSTRUMENTS 32
4.4.3 TEST PROCEDURES 33
4.4.4 TEST SETUP 33
4.4.5 EUT OPERATING CONDITIONS 33
4.4.6 TEST RESULTS 34
4.5 POWER SPECTRAL DENSITY MEASUREMENT 35
4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT 35
4.5.2 TEST INSTRUMENTS 35
4.5.3 TEST PROCEDURE 36
4.5.4 TEST SETUP 36
4.5.5 EUT OPERATING CONDITION 36
4.5.6 TEST RESULTS 37

4.6 BAND EDGES MEASUREMENT 41
4.6.1 LIMITS OF BAND EDGES MEASUREMENT 41
4.6.2 TEST INSTRUMENTS 41
4.6.3 TEST PROCEDURE 41
4.6.4 EUT OPERATING CONDITION 42
4.6.5 TEST RESULTS 42
4.7 ANTENNA REQUIREMENT 45
4.7.1 STANDARD APPLICABLE 45
4.7.2 ANTENNA CONNECTED CONSTRUCTION 45
5 PHOTOGRAPHS OF THE TEST CONFIGURATION 46
6 INFORMATION ON THE TESTING LABORATORIES 48

1 CERTIFICATION

PRODUCT :	11Mbps Wireless USB Adapter
BRAND NAME :	Accton
MODEL NO. :	WN3501C
OEM BRAND NAME :	SMC, Allied Telesyn Incorporated, Hewlett-Packard
OEM MODEL NO. :	SMC2664W, AT-WRUSB, hn215w
APPLICANT :	ACCTON TECHNOLOGY CORPORATION
STANDARDS :	47 CFR Part 15, Subpart C (Section 15.247), ANSI C63.4-1992, Canada RSS 210, New Zealand RFS 29

We, **Advance Data Technology Corporation**, hereby certify that one sample of the designation has been tested in our facility from Feb. 26, 2002 to Mar. 4, 2002. The test record, data evaluation and Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions herein specified.

TESTED BY: Gary Chang, DATE: Mar. 7, 2002
Gary Chang

CHECKED BY: Demi Chen, DATE: Mar. 7. 2002
Demi Chen

APPROVED BY: Alan Lane, DATE: Mar. 7, 2002
Dr. Alan Lane
Manager

2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: 47 CFR Part 15, Subpart C			
Standard Section	**Test Type and Limit**	**Result**	**REMARK**
15.207	AC Power Conducted Emission Limit: 48dBuV	PASS	Meet the requirement of limit Minimum passing margin is –9.52dBuV at 2.391MHz
15.247(a)(2)	Spectrum Bandwidth of a Direct Sequence Spread Spectrum System Limit: min. 500kHz	PASS	Meet the requirement of limit
15.247(b)	Maximum Peak Output Power Limit: max. 30dBm	PASS	Meet the requirement of limit
15.247(c)	Radiated Emissions Limit: Table 15.209	PASS	Meet the requirement of limit Minimum passing margin is –9.1dBuV at 748.00MHz
15.247(d)	Power Spectral Density Limit: max. 8dBm	PASS	Meet the requirement of limit
15.247(c)	Band Edge Measurement Limit: 20 dB less than the peak value of fundamental frequency	PASS	Meet the requirement of limit

3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	11Mbps Wireless USB Adapter
MODEL NO.	WN3501C
POWER SUPPLY	5VDC from host equipment
MODULATION TYPE	DSSS
TRANSFER RATE	1/2/5.5/11Mbps
FREQUENCY RANGE	2412MHz ~ 2462MHz
NUMBER OF CHANNEL	11
OUTPUT POWER	16.32dBm
ANTENNA TYPE	Chip Antenna
DATA CABLE	1.8m (Shielded)
I/O PORTS	USB port
ASSOCIATED DEVICES	NA

NOTE:

1. There are 3 OEM models listed as following:

PRODUCT NAME	MODEL	BRAND
EZ Connect 11Mbps Wireless USB Adapter	SMC2664W	SMC
IEEE802.11b USB Adapter	AT-WRUSB	Allied Telesyn Incorporated
11Mbps WLAN USB Adapter	hn215w	Hewlett-Packed

2. Four models are classified as four types for different housings, please refer to EUT PHOTO.

3. For more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

3.2 DESCRIPTION OF TEST MODES

Eleven channels are provided in this EUT.

Channel	Frequency	Channel	Frequency
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

NOTE: 1. Below 1 GHz, the channel 1, 6, and 11 were pre-tested in chamber. The channel 11, worst case one, was chosen for final test.
2. Above 1 GHz, the channel 1, 6, and 11 were tested individually.

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is an 11Mbps Wireless USB Adapter. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

47 CFR Part 15, Subpart C (Section 15.247),
ANSI C63.4-1992, Canada RSS 210,
New Zealand RFS 29

All tests have been performed and recorded as per the above standards.

NOTE: The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.

3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	NOTEBOOK	DELL	PP01L	TW-09C748-12800-19O-B220	FCC DoC APPROVED
2	PRINTER	HP	2225C+	3123S97230	DSI6XU2225
3	MODEM	ACEEX	1414	980020510	IFAXDM1414

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	NA
2	1.2m braid shielded wire, terminated with DB25 and Centronics connector via metallic frame, w/o core.
3	1.2 m braid shielded wire, terminated with DB25 and DB9 connector via metallic frame, w/o core.

NOTE: All power cords of the above support units are non shielded (1.8m).

4 TEST TYPES AND RESULTS

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY (MHz)	Class B (dBuV)	
	Quasi-peak	Average
0.45 – 30	48	-

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. All emanations from a class B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
ROHDE & SCHWARZ Test Receiver	ESCS30	845552/004	May. 22, 2002
ROHDE & SCHWARZ Artificial Mains Network (for EUT)	ESH2-Z5	828075/003	July 19, 2002
ROHDE & SCHWARZ 200-A Four-line V-Network	ENV4200	830326/018	Oct. 25, 2002
* ROHDE & SCHWARZ 4-wire ISN	ENY41	838119/028	Dec. 2, 2002
* ROHDE & SCHWARZ 2-wire ISN	ENY22	837497/018	Dec. 2, 2002
EMCO-L.I.S.N. (for peripheral)	3825/2	90031627	July 19, 2002
Software	Cond-V2L	NA	NA
RF cable (JYEBAO)	5D-FB	Cable-C05.01	July 19, 2002
LYNICS Terminator (For EMCO LISN)	0900510	E1-01-305	Feb. 20, 2003
LYNICS Terminator (For EMCO LISN)	0900510	E1-01-306	Feb. 20, 2003
Shielded Room	Site 5	ADT-C05	NA
VCCI Site Registration No.	Site 5	C-1093	NA

NOTE: 1. The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.

2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

3. "*": These equipment are used for conducted telecom port test only (if tested).

4.1.3 TEST PROCEDURES

a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.

b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.

c. The frequency range from 450 kHz to 30 MHz was searched. Emission levels over 10dB under the prescribed limits could not be reported.

4.1.4 TEST SETUP



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.1.5 EUT OPERATING CONDITIONS

a. Connected the EUT to a computer system placed on a testing table.
b. The computer system ran a test program to enable EUT under transmission/receiving condition continuously at specific channel frequency.
c. The computer system sent "H" messages to its screen.
d. The computer system sent “H” messages to modem.
e. The computer system sent "H" messages to printer, and the printer prints them on paper.

4.1.6 TEST RESULTS

EUT	11Mbps Wireless USB Adapter	**MODEL**	WN3501C
MODE	Channel 1	**6dB BANDWIDTH**	10 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	**PHASE**	Line (L)
ENVIRONMENTAL CONDITIONS	20 deg. C, 70%RH, 1005 hPa	**TESTED BY**: Gary Chang	

No	Freq.	Corr. Factor	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.454	0.11	31.36	-	31.47	-	48.00	-	-16.53	-
2	0.966	0.19	32.63	-	32.82	-	48.00	-	-15.18	-
3	2.102	0.21	37.09	-	37.30	-	48.00	-	-10.70	-
4	5.059	0.44	36.00	-	36.44	-	48.00	-	-11.56	-
5	8.355	0.55	29.93	-	30.48	-	48.00	-	-17.52	-
6	11.141	0.62	26.26	-	26.88	-	48.00	-	-21.12	-

NOTE:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



EUT	11Mbps Wireless USB Adapter	**MODEL**	WN3501C
MODE	Channel 1	**6dB BANDWIDTH**	10 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	**PHASE**	Neutral (N)
ENVIRONMENTAL CONDITIONS	20 deg. C, 70%RH, 1005 hPa	**TESTED BY**: Gary Chang	

No	Freq.	Corr. Factor	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.454	0.11	29.64	-	29.75	-	48.00	-	-18.25	-
2	1.023	0.20	33.00	-	33.20	-	48.00	-	-14.80	-
3	2.160	0.21	38.00	-	38.21	-	48.00	-	-9.79	-
4	5.059	0.32	36.10	-	36.42	-	48.00	-	-11.58	-
5	8.016	0.37	29.87	-	30.24	-	48.00	-	-17.76	-
6	11.484	0.43	26.68	-	27.11	-	48.00	-	-20.89	-

NOTE:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



EUT	11Mbps Wireless USB Adapter	**MODEL**	WN3501C
MODE	Channel 6	**6dB BANDWIDTH**	10 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	**PHASE**	Line (L)
ENVIRONMENTAL CONDITIONS	20 deg. C, 70%RH, 1005 hPa	**TESTED BY**: Gary Chang	

No	Freq.	Corr. Factor	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.454	0.11	31.08	-	31.19	-	48.00	-	-16.81	-
2	0.852	0.18	31.63	-	31.81	-	48.00	-	-16.19	-
3	1.879	0.20	37.04	-	37.24	-	48.00	-	-10.76	-
4	5.117	0.44	34.83	-	35.27	-	48.00	-	-12.73	-
5	8.305	0.54	30.34	-	30.88	-	48.00	-	-17.12	-
6	10.691	0.61	25.65	-	26.26	-	48.00	-	-21.74	-

NOTE:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



EUT	11Mbps Wireless USB Adapter	**MODEL**	WN3501C
MODE	Channel 6	**6dB BANDWIDTH**	10 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	**PHASE**	Neutral (N)
ENVIRONMENTAL CONDITIONS	20 deg. C, 70%RH, 1005 hPa	**TESTED BY**: Gary Chang	

No	Freq.	Corr. Factor	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.454	0.11	29.56	-	29.67	-	48.00	-	-18.33	-
2	0.513	0.12	30.21	-	30.33	-	48.00	-	-17.67	-
3	2.105	0.21	38.05	-	38.26	-	48.00	-	-9.74	-
4	4.945	0.32	35.56	-	35.88	-	48.00	-	-12.12	-
5	7.508	0.36	29.30	-	29.66	-	48.00	-	-18.34	-
6	11.543	0.43	25.97	-	26.40	-	48.00	-	-21.60	-

NOTE:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



EUT	11Mbps Wireless USB Adapter	**MODEL**	WN3501C
MODE	Channel 11	**6dB BANDWIDTH**	10 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	**PHASE**	Line (L)
ENVIRONMENTAL CONDITIONS	20 deg. C, 70%RH, 1005 hPa	**TESTED BY**: Gary Chang	

No	Freq.	Corr. Factor	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.454	0.11	31.01	-	31.12	-	48.00	-	-16.88	-
2	0.911	0.19	32.18	-	32.37	-	48.00	-	-15.63	-
3	2.105	0.21	38.03	-	38.24	-	48.00	-	-9.76	-
4	2.844	0.28	36.51	-	36.79	-	48.00	-	-11.21	-
5	5.008	0.43	35.90	-	36.33	-	48.00	-	-11.67	-
6	8.363	0.55	30.11	-	30.66	-	48.00	-	-17.34	-

NOTE:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



EUT	11Mbps Wireless USB Adapter	**MODEL**	WN3501C
MODE	Channel 11	**6dB BANDWIDTH**	10 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	**PHASE**	Neutral (N)
ENVIRONMENTAL CONDITIONS	20 deg. C, 70%RH, 1005 hPa	**TESTED BY**: Gary Chang	

No	Freq.	Corr. Factor	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.454	0.11	29.15	-	29.26	-	48.00	-	-18.74	-
2	1.422	0.20	36.25	-	36.45	-	48.00	-	-11.55	-
3	2.391	0.22	38.26	-	38.48	-	48.00	-	-9.52	-
4	5.008	0.32	36.37	-	36.69	-	48.00	-	-11.31	-
5	8.023	0.37	30.25	-	30.62	-	48.00	-	-17.38	-
6	11.438	0.43	26.92	-	27.35	-	48.00	-	-20.65	-

NOTE:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



4.2 RADIATED EMISSION MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Field strength limits are at the distance of 3 meters, emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

Frequencies (MHz)	Field Strength of Fundamental	
	uV/m	dBuV/m
30-88	100	40.0
88-216	150	43.5
216-960	200	46.0
Above 960	500	54.0

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
* HP Spectrum Analyzer	8590L	3544A01176	May 7, 2002
* HP Preamplifier	8447D	2944A08485	May 7, 2002
* HP Preamplifier	8449B	3008A01201	Dec. 06, 2002
* HP Preamplifier	8449B	3008A01292	Aug. 21, 2002
* ROHDE & SCHWARZ TEST RECEIVER	ESMI	839013/007 839379/002	Jan. 27, 2003
SCHWARZBECK Tunable Dipole Antenna	VHA 9103 UHA 9105	E101051 E101055	Nov. 23, 2002
* CHASE BILOG Antenna	CBL6112A	2221	Aug. 2, 2002
* SCHWARZBECK Horn Antenna	BBHA9120-D1	D130	July 6, 2002
* EMCO Horn Antenna	3115	9312-4192	April 15, 2002
* EMCO Turn Table	1060	1115	NA
* SHOSHIN Tower	AP-4701	A6Y005	NA
* Software	AS61D4	NA	NA
* ANRITSU RF Switches	MP59B	M35046	Aug. 2, 2002
* TIMES RF cable	LMR-600	CABLE-ST5-01	Aug. 2, 2002
Antenna (Horn)	BBHA9120-D	D130	July 10, 2002
Open Field Test Site	Site 5	ADT-R05	July 28, 2002
VCCI Site Registration No.	Site 5	R-1039	NA
Site Registration No.	FCC: 90422 Canada IC: IC 3789 VCCI : R-1039		

NOTE: 1.The measurement uncertainty is less than +/- 3.0dB, which is calculated as per the NAMAS document NIS81.

2.The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.

3. "*" = These equipment are used for the final measurement.

4. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.

4.2.3 TEST PROCEDURES

a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

f. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using the quasi-peak method or average method as specified and then reported in Data sheet peak mode and QP mode.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 300 Hz for Average detection (AV) at frequency above 1GHz.

4.2.4 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.2.5 EUT OPERATING CONDITIONS

Same as 4.1.5.

4.2.6 TEST RESULTS

EUT	11Mbps Wireless USB Adapter	**MODEL**	WN3501C
MODE	Channel 11	**FREQUENCY RANGE**	30-1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	**DETECTOR FUNCTION**	Quasi-Peak
ENVIRONMENTAL CONDITIONS	20 deg. C, 70%RH, 1005 hPa	**TESTED BY**: Gary Chang	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	120.00	30.7 QP	43.50	-12.80	1.17H	154	18.00	11.65	1.08	0.00	-12.73
2	144.00	29.3 QP	43.50	-14.20	1.14H	115	17.50	10.58	1.18	0.00	-11.76
3	176.00	28.4 QP	43.50	-15.10	1.18H	237	18.00	9.08	1.33	0.00	-10.42
4	352.00	32.8 QP	46.00	-13.20	1.09H	46	16.40	14.31	2.05	0.00	-16.37
5	440.00	31.7 QP	46.00	-14.30	1.00H	5	13.00	16.32	2.38	0.00	-18.70
6	528.00	35.9 QP	46.00	-10.10	1.05H	197	15.70	17.62	2.60	0.00	-20.22
7	616.00	36.7 QP	46.00	-9.30	1.08H	120	15.00	18.82	2.89	0.00	-21.71
8	748.00	36.9 QP	46.00	-9.10	1.09H	238	13.50	20.14	3.26	0.00	-23.40

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	120.00	30.7 QP	43.50	-12.80	1.15V	5	18.00	11.65	1.08	0.00	-12.73
2	156.00	28.1 QP	43.50	-15.40	1.16V	334	17.00	9.88	1.24	0.00	-11.12
3	176.00	30.4 QP	43.50	-13.10	1.15V	343	20.00	9.08	1.33	0.00	-10.41
4	220.00	30.0 QP	46.00	-16.00	1.11V	291	18.40	10.12	1.51	0.00	-11.63
5	396.00	35.2 QP	46.00	-10.80	1.05V	188	17.00	15.96	2.22	0.00	-18.18
6	528.00	36.2 QP	46.00	-9.80	1.10V	128	16.00	17.62	2.60	0.00	-20.23
7	748.00	35.4 QP	46.00	-10.60	1.23V	14	12.00	20.14	3.26	0.00	-23.41

NOTE:

1. Emission level(dBuV/m)=Raw Value(dBuV) – Correction Factor(dB)
2. Correction Factor(dB) = Pre-Amplifier Factor (dB) - Antenna Factor (dB) - Cable Factor (dB)
3. Pre-Amplifier Factor (dB) = 0, when the test receiver is used to read the value and because it did not use the Pre-Amplifier.
4. The other emission levels were very low against the limit.
5. Margin value = Emission level – Limit value.

EUT	11Mbps Wireless USB Adapter	**MODEL**	WN3501C
MODE	Channel 1	**FREQUENCY RANGE**	Above 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	**DETECTOR FUNCTION**	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	20 deg. C, 70%RH, 1005 hPa	**TESTED BY**: Gary Chang	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	2038.00	52.0 PK	74.00	-22.00	1.00H	270	56.80	25.20	4.86	34.90	4.84
2	*2412.00	100.2 PK	-	-	1.47H	62	68.00	27.11	5.10	0.00	-32.22
3	*2412.00	95.7 AV	-	-	1.47H	62	63.50	27.11	5.10	0.00	-32.22
4	4076.00	49.1 PK	74.00	-24.90	1.19H	78	46.70	30.13	6.78	34.52	-2.39
5	4824.00	49.7 PK	74.00	-24.30	1.17H	66	45.70	31.43	7.23	34.63	-4.02

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	2038.00	50.6 PK	74.00	-23.40	1.00V	356	55.40	25.20	4.86	34.90	4.84
2	*2412.00	93.2 PK	-	-	1.00V	76	61.00	27.11	5.10	0.00	-32.22
3	*2412.00	88.2 AV	-	-	1.00V	76	56.00	27.11	5.10	0.00	-32.22
4	4076.00	49.4 PK	74.00	-24.60	1.32V	354	47.00	30.13	6.78	34.52	-2.39
5	4824.00	49.7 PK	74.00	-24.30	1.28V	327	45.70	31.43	7.23	34.63	-4.02

NOTE:

1. Emission level(dBuV/m)=Raw Value(dBuV) – Correction Factor(dB)
2. Correction Factor(dB) = Pre-Amplifier Factor (dB) - Antenna Factor (dB) - Cable Factor (dB)
3. Pre-Amplifier Factor (dB) = 0, when the test receiver is used to read the value and because it did not use the Pre-Amplifier.
4. The other emission levels were very low against the limit.
5. Margin value = Emission level – Limit value.
6. “ * “ = Fundamental frequency

EUT	11Mbps Wireless USB Adapter	**MODEL**	WN3501C
MODE	Channel 6	**FREQUENCY RANGE**	Above 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	**DETECTOR FUNCTION**	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	20 deg. C, 70%RH, 1005 hPa	**TESTED BY**: Gary Chang	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	2063.00	49.7 PK	74.00	-24.30	1.15H	52	54.20	25.41	4.96	34.90	4.53
2	*2437.00	102.4 PK	-	-	1.05H	129	70.00	27.33	5.08	0.00	-32.40
3	*2437.00	97.8 AV	-	-	1.05H	129	65.40	27.33	5.08	0.00	-32.40
4	4126.00	50.0 PK	74.00	-24.00	1.21H	221	47.50	30.32	6.70	34.56	-2.46
5	4874.00	50.2 PK	74.00	-23.80	1.25H	100	46.10	31.47	7.21	34.63	-4.05

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	2063.00	51.3 PK	74.00	-22.70	1.00V	89	55.80	25.41	4.96	34.90	4.53
2	*2437.00	93.8 PK	-	-	1.00V	290	61.40	27.33	5.08	0.00	-32.40
3	*2437.00	88.1 AV	-	-	1.00V	290	55.70	27.33	5.08	0.00	-32.40
4	4126.00	48.7 PK	74.00	-25.30	1.22V	247	46.20	30.32	6.70	34.56	-2.46
5	4874.00	51.3 PK	74.00	-22.70	1.26V	150	47.20	31.47	7.21	34.63	-4.05

NOTE:

1. Emission level(dBuV/m)=Raw Value(dBuV) – Correction Factor(dB)
2. Correction Factor(dB) = Pre-Amplifier Factor (dB) - Antenna Factor (dB) - Cable Factor (dB)
3. Pre-Amplifier Factor (dB) = 0, when the test receiver is used to read the value and because it did not use the Pre-Amplifier.
4. The other emission levels were very low against the limit.
5. Margin value = Emission level – Limit value.
6. “ * “ = Fundamental frequency

EUT	11Mbps Wireless USB Adapter	**MODEL**	WN3501C
MODE	Channel 11	**FREQUENCY RANGE**	Above 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	**DETECTOR FUNCTION**	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	20 deg. C, 70%RH, 1005 hPa	**TESTED BY**: Gary Chang	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	2088.00	49.7 PK	74.00	-24.30	1.40H	4	54.00	25.62	5.02	34.90	4.26
2	*2463.00	103.4 PK	-	-	1.11H	21	71.00	27.33	5.08	0.00	-32.40
3	*2463.00	97.9 AV	-	-	1.11H	21	65.50	27.33	5.08	0.00	-32.40
4	2492.00	48.1 PK	74.00	-25.90	1.18H	9	50.40	27.54	5.06	34.90	2.31
5	4176.00	49.0 PK	74.00	-25.00	1.21H	238	46.50	30.41	6.68	34.58	-2.51
6	4924.00	50.1 PK	74.00	-23.90	1.29H	150	46.00	31.51	7.21	34.62	-4.10

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	2088.00	50.2 PK	74.00	-23.80	1.09V	347	54.50	25.62	5.02	34.90	4.26
2	*2463.00	93.4 PK	-	-	1.10V	356	61.00	27.33	5.08	0.00	-32.41
3	*2463.00	88.4 AV	-	-	1.10V	356	56.00	27.33	5.08	0.00	-32.41
4	4176.00	49.9 PK	74.00	-24.10	1.23V	331	47.40	30.41	6.68	34.58	-2.51
5	4924.00	50.8 PK	74.00	-23.20	1.31V	348	46.70	31.51	7.21	34.62	-4.10

NOTE:

1. Emission level(dBuV/m)=Raw Value(dBuV) – Correction Factor(dB)
2. Correction Factor(dB) = Pre-Amplifier Factor (dB) - Antenna Factor (dB) - Cable Factor (dB)
3. Pre-Amplifier Factor (dB) = 0, when the test receiver is used to read the value and because it did not use the Pre-Amplifier.
4. The other emission levels were very low against the limit.
5. Margin value = Emission level – Limit value.
6. " * " = Fundamental frequency

4.3 6dB BANDWIDTH MEASUREMENT

4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSEK30	100049	Jul. 16, 2002

Notes:

1. The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.3.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100 kHz RBW and 100 kHz VBW. The 6 dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6 dB.

4.3.4 TEST SETUP



4.3.5 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.3.6 TEST RESULTS

EUT	11Mbps Wireless USB Adapter	**MODEL**	WN3501C
INPUT POWER (SYSTEM)	120Vac, 60 Hz	**ENVIRONMENTAL CONDITIONS**	26 deg. C, 65%RH, 1005 hPa
TESTED BY: Bruce Shiau			

CHANNEL	CHANNEL FREQUENCY (MHz)	6 dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS/FAIL
1	2412	10.54	0.5	PASS
6	2437	10.54	0.5	PASS
11	2462	10.54	0.5	PASS

CH1


Ref Lvl
20 dBm
1 dB Offset
D1 8.77 dBm
D2 2.77 dBm
Delta 1 [T1]
0.10 dB
10.5410821 6 MHz
RBW 100 kHz
VBW 100 kHz
SWT 100 ms
RF Att 30 dB
Unit dBm
1MA
1EW
F1
F2
Center 2.412 GHz
2 MHz/
Span 20 MHz
20
10
0
-10
-20
-30
-40
-50
-60
-70
-80

CH6


Ref Lvl
20 dBm
1 dB Offset
D1 8.27 dBm
D2 2.27 dBm
Delta 1 [T1]
-0.05 dB
10.54108216 MHz
RBW 100 kHz
VBW 100 kHz
SWT 100 ms
RF Att 30 dB
Unit dBm
1MA
1MEW
F1
F2
Center 2.437 GHz
2 MHz/
Span 20 MHz

CH11


Ref Lvl
20 dBm
Delta 1 [T1]
-0.75 dB
10.54108216 MHz
RBW 100 kHz
VBW 100 kHz
SWT 100 ms
RF Att 30 dB
Unit dBm
1 dB Offset
D1 7.61 dBm
D2 1.61 dBm
1MA
F1
F2
Center 2.462 GHz
2 MHz/
Span 20 MHz
20
10
0
-10
-20
-30
-40
-50
-60
-70
-80

4.4 MAXIMUM PEAK OUTPUT POWER

4.4.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT

The Maximum Peak Output Power Measurement is 30dBm.

4.4.2 INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
Peak Power Sensor	NRV-Z32	100013	Feb. 21, 2003
Power Meter	NRVS	100026	Feb. 21,2003

NOTE: 1. The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.

2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.4.3 TEST PROCEDURES

1. The transmitter output was connected to the peak power meter.

4.4.4 TEST SETUP



4.4.5 EUT OPERATING CONDITIONS

Same as Item 3.4.5

4.4.6 TEST RESULTS

EUT	11Mbps Wireless USB Adapter	**MODEL**	WN3501C
INPUT POWER (SYSTEM)	120Vac, 60 Hz	**ENVIRONMENTAL CONDITIONS**	26 deg. C, 65%RH, 1005 hPa
TESTED BY: Bruce Shiau			

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
1	2412	16.32	30	PASS
6	2437	16.29	30	PASS
11	2462	15.94	30	PASS

4.5 POWER SPECTRAL DENSITY MEASUREMENT

4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

4.5.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSEK30	100049	Jul. 16, 2002

NOTE:1. The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.

2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.5.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator, the bandwidth of the fundamental frequency was measured with the spectrum analyzer using 3 kHz RBW and 30 kHz VBW, set sweep time = span/3 kHz. The power spectral density was measured and recorded.
The sweep time is allowed to be longer than span/3 kHz for a full response of the mixer in the spectrum analyzer.

4.5.4 TEST SETUP



4.5.5 EUT OPERATING CONDITION

Same as Item 3.4.5

4.5.6 TEST RESULTS

EUT	11Mbps Wireless USB Adapter	**MODEL**	WN3501C
INPUT POWER (SYSTEM)	120Vac, 60 Hz	**ENVIRONMENTAL CONDITIONS**	26 deg. C, 65%RH, 1005 hPa
TESTED BY: Bruce Shiau			

CHANNEL NUMBER	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3 kHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS/FAIL
1	2412	-5.49	8	PASS
6	2437	-5.64	8	PASS
11	2462	-6.31	8	PASS

CH1


Ref Lvl
20 dBm
1 dB Offset
Marker 1 [T1]
-5.49 dBm
2.41290470 GHz
RBW 3 kHz
VBW 30 kHz
SWT 100 s
RF Att 30 dB
Unit dBm
1MA
1VIEW
Center 2.412904997 GHz
30 kHz/
Span 300 kHz
20
10
0
-10
-20
-30
-40
-50
-60
-70
-80

CH6


Ref Lvl
20 dBm
1 dB Offset
Marker 1 [T1]
-5.64 dBm
2.43790307 GHz
RBW 3 kHz
VBW 30 kHz
SWT 100 s
RF Att 30 dB
Unit dBm
1MA
Center 2.43790369 GHz
30 kHz/
Span 300 kHz
20
10
0
-10
-20
-30
-40
-50
-60
-70
-80

CH11


Ref Lvl
20 dBm
1 dB Offset
Marker 1 [T1]
-6.31 dBm
2.46290214 GHz
RBW 3 kHz
VBW 30 kHz
SWT 100 s
RF Att 30 dB
Unit dBm
1MA
Center 2.462902442 GHz
30 kHz/
Span 300 kHz

4.6 BAND EDGES MEASUREMENT

4.6.1 LIMITS OF BAND EDGES MEASUREMENT

Below –20dB of the highest emission level of operating band (in 100KHz Resolution Bandwidth).

4.6.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSEK30	100049	Jul. 16, 2002

NOTE:

1. The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.6.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low lose cable. Set both RBW and VBW of spectrum analyzer to 100 kHz with suitable frequency span including 100 kHz bandwidth from band edge. The band edges was measured and recorded.

4.6.4 EUT OPERATING CONDITION

Same as Item 3.4.5

4.6.5 TEST RESULTS

The spectrum plots are attached on the following 2 pages. D2 line indicates the highest level, D1 line indicates the 20dB offset below D2. It shows compliance with the requirement in part 15.247(C).

NOTE: The band edge emission plot on the following 2 pages shows 46.90dB delta between carrier maximum power and local maximum emission in restrict band (2.48389GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.6 (Page 25) is 97.9dBuV/m, so the maximum field strength in restrict band is 97.9-46.9=51.0 dBuV/m which is under 54 dBuV/m limit.


Ref Lvl
20 dBm
1 dB Offset
D1 7.5 dBm
D2 -12.5 dBm
Marker 1 [T1]
-39.40 dBm
2.48389379 GHz
RBW 100 kHz
VBW 100 kHz
SWT 100 ms
RF Att 30 dB
Unit dBm
1MA
1VIEW
Center 2.487 GHz
10 MHz/
Span 100 MHz
F1


Ref Lvl
20 dBm
1 dB Offset
D1 8.0B dBm
D2 -11.97 dBm
1VIEW
Marker 1 [T1]
-22.73 dBm
2.39912425 GHz
RBW 100 kHz
VBW 100 kHz
SWT 100 ms
RF Att 30 dB
Unit dBm
1MA
F1
Center 2.387 GHz
10 MHz/
Span 100 MHz

4.7 ANTENNA REQUIREMENT

4.7.1 STANDARD APPLICABLE

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

4.7.2 ANTENNA CONNECTED CONSTRUCTION

The antenna used in this product is Chip Antenna. There is no antenna connector. The maximum Gain of the antenna is 0dBi only.

5 PHOTOGRAPHS OF THE TEST CONFIGURATION

CONDUCTED EMISSION TEST

RADIATED EMISSION TEST

6 INFORMATION ON THE TESTING LABORATORIES

We, ADT Corp., were founded in 1988 to provide our best service in EMC and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025, Guide 25 or EN 45001:

USA	FCC, NVLAP, UL
Germany	TUV Rheinland
Japan	VCCI
New Zealand	MoC
Norway	NEMKO
R.O.C.	BSMI, DGT, CNLA

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site: www.adt.com.tw/index.5/phtml.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC Lab:
Tel: 886-2-26052180
Fax: 886-2-26052943

Hsin Chu EMC Lab:
Tel: 886-35-935343
Fax: 886-35-935342

Lin Kou Safety Lab:
Tel: 886-2-26093195
Fax: 886-2-26093184

Lin Kou RF&Telecom Lab
Tel: 886-3-3270910
Fax: 886-3-3270892

Email: service@mail.adt.com.tw
Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.