RADIO TEST REPORT
FCC 47 CFR PART 15 SUBPART C

Test Standard	**FCC Part 15.247**
Product name	**QTAX56**
Model No.	**QTAX56**
Test Result	**Pass**
Statements of Conformity	**Determination of compliance is based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.**

The test Result was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were given in ANSI C63.10: 2013 and compliance standards.

The test results of this report relate only to the tested sample (EUT) identified in this report.
The test Report of full or partial shall not copy. Without written approval of Compliance Certification Services Inc.(Wugu Laboratory)

Approved by:

Kevin Tsai
Deputy Manager

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instruction, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced, except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	September 29, 2020	Initial Issue	ALL	Allison Chen
01	October 15, 2020	See the following note Rev.(01)	P.35	Allison Chen

Rev.(01)
1. Modify test data of AFH mode in section 4.7.4.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Table of contents

1. GENERAL INFORMATION 4
1.1 EUT INFORMATION 4
1.2 INFORMATION ABOUT THE FHSS CHARACTERISTICS 5
1.3 EUT CHANNEL INFORMATION 6
1.4 ANTENNA INFORMATION 6
1.5 MEASUREMENT UNCERTAINTY 7
1.6 FACILITIES AND TEST LOCATION 8
1.7 INSTRUMENT CALIBRATION 8
1.8 SUPPORT AND EUT ACCESSORIES EQUIPMENT 9
1.9 TEST METHODOLOGY AND APPLIED STANDARDS 9
2. TEST SUMMERY 10
3. DESCRIPTION OF TEST MODES 11
3.1 THE WORST MODE OF OPERATING CONDITION 11
3.2 THE WORST MODE OF MEASUREMENT 12
3.3 EUT DUTY CYCLE 13
4. TEST RESULT 14
4.1 AC POWER LINE CONDUCTED EMISSION 14
4.2 20DB BANDWIDTH AND OCCUPIED BANDWIDTH (99%) 17
4.3 OUTPUT POWER MEASUREMENT 23
4.4 FREQUENCY SEPARATION 25
4.5 NUMBER OF HOPPING 28
4.6 CONDUCTED BANDEDGE AND SPURIOUS EMISSION 30
4.7 TIME OF OCCUPANCY (DWELL TIME) 35
4.8 RADIATION BANDEDGE AND SPURIOUS EMISSION 37
APPENDIX 1 - PHOTOGRAPHS OF EUT

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

1. GENERAL INFORMATION

1.1 EUT INFORMATION

Applicant	Quanta Computer Inc. No.188, Wenhua 2nd Rd., Guishan Dist., Taoyuan City 33377, Taiwan
Manufacturer	Quanta Computer Inc. No.188, Wenhua 2nd Rd., Guishan Dist., Taoyuan City 33377, Taiwan
Equipment	QTAX56
Model No.	QTAX56
Model Discrepancy	N/A
Received Date	August 21, 2020
Date of Test	September 10 ~ 18, 2020
Power Operation	1. Powered from adapter Model No.: CYSM06-050120-UL Supplier: JIANGSU CHENYANG ELECTRON CO., LTD I/P: 100-240Vac, 50/60Hz, 0.2A O/P: 5Vdc, 1.2A 2. Powered from battery. (Lithium Polymer) Model No.: P0963, Supplier: EVE Rating: 3.85V / 495mAh / 1.91Wh
HW Version	X56_D2B
SW Version	QTAX56_30A11

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

1.2 INFORMATION ABOUT THE FHSS CHARACTERISTICS

1.2.1 Pseudorandom Frequency Hopping Sequence

The channel is represented by a pseudo-random hopping sequence hopping through the 79 RF channels. The hopping sequence is unique for the piconet and is determined by the Bluetooth device address of the master; the phase in the hopping sequence is determined by the Bluetooth clock of the master. The channel is divided into time slots where each slot corresponds to an RF hop frequency. Consecutive hops correspond to different RF hop frequencies. The nominal hop rate is 1 600 hops/s.

1.2.2 Equal Hopping Frequency Use

The channels of this system will be used equally over the long-term distribution of the hopsets.

1.2.3 Example of a 79 hopping sequence in data mode:

02, 05, 31, 24, 20, 10, 43, 36, 30, 23, 40, 06, 21, 50, 44, 09, 71, 78, 01, 13, 73, 07, 70, 72, 35, 62, 42, 11, 41, 08, 16, 29, 60, 15, 34, 61, 58, 04, 67, 12, 22, 53, 57, 18, 27, 76, 39, 32, 17, 77, 52, 33, 56, 46, 37, 47, 64, 49, 45, 38, 69, 14, 51, 26, 79, 19, 28, 65, 75, 54, 48, 03, 25, 66, 05, 16, 68, 74, 59, 63, 55

1.2.4 System Receiver Input Bandwidth

Each channel bandwidth is 1MHz.
The system receivers have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.

1.2.5 Equipment Description

RSS-247, 5.1 (a): The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

1.3 EUT CHANNEL INFORMATION

Frequency Range	2402MHz-2480MHz
Modulation Type	1. GFSK for BDR-1Mbps 2. π/4-DQPSK for EDR-2Mbps 3. 8DPSK for EDR-3Mbps
Number of channel	79 Channels

Remark:
Refer as ANSI C63.10: 2013 clause 5.6.1 Table 4 for test channels

Number of frequencies to be tested		
Frequency range in which device operates	**Number of frequencies**	**Location in frequency range of operation**
☐ 1 MHz or less	1	Middle
☐ 1 MHz to 10 MHz	2	1 near top and 1 near bottom
☒ More than 10 MHz	3	1 near top, 1 near middle, and 1 near bottom

1.4 ANTENNA INFORMATION

Antenna Specification	Monopole Antenna
Antenna Gain	-2.37 dBi
Antenna connector	N/A

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

1.5 MEASUREMENT UNCERTAINTY

PARAMETER	UNCERTAINTY
AC Powerline Conducted Emission	+/- 1.2575
Emission bandwidth, 20dB bandwidth	+/- 0.0014
RF output power, conducted	+/- 1.14
Power density, conducted	+/- 1.40
3M Semi Anechoic Chamber / 30M~200M	+/- 4.12
3M Semi Anechoic Chamber / 200M~1000M	+/- 4.68
3M Semi Anechoic Chamber / 1G~8G	+/- 5.18
3M Semi Anechoic Chamber / 8G~18G	+/- 5.47
3M Semi Anechoic Chamber / 18G~26G	+/- 3.81
3M Semi Anechoic Chamber / 26G~40G	+/- 3.87

Remark:
1.This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2
2. ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

1.6 FACILITIES AND TEST LOCATION

All measurement facilities used to collect the measurement data are located at No.11, Wugong 6th Rd., Wugu Dist., New Taipei City, Taiwan. (R.O.C.)

Test site	Test Engineer	Remark
AC Conduction Room	Rick Lee	-
Radiation	Jerry Chang	-
RF Conducted	Jane Wang	-

Remark: The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22.

1.7 INSTRUMENT CALIBRATION

RF Conducted Test Site					
Name of Equipment	**Manufacturer**	**Model**	**Serial Number**	**Calibration Date**	**Calibration Due**
Coaxial Cable	Woken	WC12	CC001	06/29/2020	06/28/2021
Signal Analyzer	R&S	FSV 40	101073	09/25/2019	09/24/2020
Power Meter	Anritsu	ML2487A	6K00003260	05/21/2020	05/20/2021
Power Seneor	Anritsu	MA2490A	032910	05/21/2020	05/20/2021
Software	N/A				

3M 966 Chamber Test Site					
Equipment	**Manufacturer**	**Model**	**S/N**	**Cal Date**	**Cal Due**
Band Reject Filters	MICRO TRONICS	BRM 50702	120	02/25/2020	02/24/2021
Bilog Antenna	Sunol Sciences	JB3	A030105	07/24/2020	07/23/2021
Coaxial Cable	HUBER SUHNER	SUCOFLEX 104PEA	20995	02/25/2020	02/24/2021
Coaxial Cable	EMCI	EMC105	190914+25111	09/20/2019	09/19/2020
Digital Thermo-Hygro Meter	WISEWIND	1206	D07	01/15/2020	01/14/2021
double Ridged Guide Horn Antenna	ETC	MCTD 1209	DRH13M02003	10/04/2019	10/03/2020
Loop Ant	COM-POWER	AL-130	121051	03/27/2020	03/26/2021
Pre-Amplifier	EMEC	EM330	060609	02/25/2020	02/24/2021
Pre-Amplifier	HP	8449B	3008A00965	02/25/2020	02/24/2021
PSA Series Spectrum Analyzer	Agilent	E4446A	MY46180323	07/24/2020	07/23/2021
Antenna Tower	CCS	CC-A-1F	N/A	N.C.R	N.C.R
Controller	CCS	CC-C-1F	N/A	N.C.R	N.C.R
Turn Table	CCS	CC-T-1F	N/A	N.C.R	N.C.R
Software	e3 6.11-20180413				

Remark: Each piece of equipment is scheduled for calibration once a year.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

AC Conducted Emission Room # B					
Name of Equipment	**Manufacturer**	**Model**	**Serial Number**	**Calibration Date**	**Calibration Due**
CABLE	EMCI	CFD300-NL	CERF	06/29/2020	06/28/2021
EMI Test Receiver	R&S	ESCI	100064	07/17/2020	07/16/2021
LISN	SCHAFFNER	NNB 41	03/10013	02/13/2020	02/12/2021
Software	EZ-EMC(CCS-3A1-CE-wugu)				

Remark: Each piece of equipment is scheduled for calibration once a year.

1.8 SUPPORT AND EUT ACCESSORIES EQUIPMENT

EUT Accessories Equipment					
No.	**Equipment**	**Brand**	**Model**	**Series No.**	**FCC ID**
	N/A				

Support Equipment					
No.	**Equipment**	**Brand**	**Model**	**Series No.**	**FCC ID**
1	DC Power Supplies	GW Instek	SPS-3610	GPE880163	N/A
2	NB(J)	TOSHIBA	PT345T-00L002	N/A	PD97260H

1.9 TEST METHODOLOGY AND APPLIED STANDARDS

The test methodology, setups and results comply with all requirements in accordance with ANSI C63.10:2013, FCC Part 2, FCC Part 15.247.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

2. TEST SUMMERY

FCC Standard Section	Report Section	Test Item	Result
15.203	1.3	Antenna Requirement	Pass
15.207(a)	4.1	AC Conducted Emission	Pass
15.247(a)(1)	4.2	20 dB Bandwidth	Pass
-	4.2	Occupied Bandwidth (99%)	Pass
15.247(b)(1)	4.3	Output Power Measurement	Pass
15.247(a)(1)	4.4	Frequency Separation	Pass
15.247(a)(1)(iii)	4.5	Number of Hopping	Pass
15.247(d)	4.6	Conducted Band Edge	Pass
15.247(d)	4.6	Conducted Spurious Emission	Pass
15.247(a)(1)(iii)	4.7	Time of Occupancy	Pass
15.247(d)	4.8	Radiation Band Edge	Pass
15.247(d)	4.8	Radiation Spurious Emission	Pass

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

3. DESCRIPTION OF TEST MODES

3.1 THE WORST MODE OF OPERATING CONDITION

Operation mode	GFSK for BDR-1Mbps (DH5) 8DPSK for EDR-3Mbps (3DH5)
Test Channel Frequencies	**GFSK for BDR-1Mbps:** 1.Lowest Channel: 2402MHz 2.Middle Channel: 2441MHz 3.Highest Channel: 2480MHz **8DPSK for EDR-3Mbps:** 1.Lowest Channel: 2402MHz 2.Middle Channel: 2441MHz 3.Highest Channel: 2480MHz

Remark:
1. EUT pre-scanned data rate of output power for each mode, the worst data rate were recorded in this report.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

3.2 THE WORST MODE OF MEASUREMENT

AC Power Line Conducted Emission	
Test Condition	AC Power line conducted emission for line and neutral
Power supply Mode	Mode 1: EUT power by Adapter
Worst Mode	☒ Mode 1 ☐ Mode 2 ☐ Mode 3 ☐ Mode 4

Radiated Emission Measurement Above 1G	
Test Condition	Radiated Emission Above 1G
Power supply Mode	Mode 1: EUT power by Adapter
Worst Mode	☒ Mode 1 ☐ Mode 2 ☐ Mode 3 ☐ Mode 4
Worst Position	☐ Placed in fixed position. ☐ Placed in fixed position at X-Plane (E2-Plane) ☐ Placed in fixed position at Y-Plane (E1-Plane) ☒ Placed in fixed position at Z-Plane (H-Plane)

Radiated Emission Measurement Below 1G	
Test Condition	Radiated Emission Below 1G
Power supply Mode	Mode 1: EUT power by Adapter Mode 2: EUT power by Battery
Worst Mode	☒ Mode 1 ☐ Mode 2 ☐ Mode 3 ☐ Mode 4

Remark:
1. The worst mode was record in this test report.
2. EUT pre-scanned in three axis ,X,Y, Z and two polarity, for radiated measurement. The worst case(Z-Plane) were recorded in this report
3. AC power line conducted emission and for below 1G radiation emission were performed the EUT transmit at the highest output power channel as worse case.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

3.3 EUT DUTY CYCLE

Temperature: 24℃ **Humidity:** 50% RH

Tested by: Jane Wang

Duty Cycle				
Configuration	Duty Cycle (%)	Duty Factor (dB) =10*log (1/Duty Cycle)	1/T (kHz)	VBW setting (kHz)
BDR-1Mbps	77.43%	1.11	0.35	1.00
EDR-3Mbps	77.43%	1.11	0.35	1.00

BDR-1Mbps



EDR-3Mbps



This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

4. TEST RESULT

4.1 AC POWER LINE CONDUCTED EMISSION

4.1.1 Test Limit

According to §15.207(a),

Frequency Range (MHz)	Limits(dBμV)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56*	56 to 46*
0.50 to 5	56	46
5 to 30	60	50

* Decreases with the logarithm of the frequency.

4.1.2 Test Procedure

Test method Refer as ANSI C63.10: 2013 clause 6.2,

1. The EUT was placed on a non-conducted table, which is 0.8m above horizontal ground plane and 0.4m above vertical ground plane.
2. EUT connected to the line impedance stabilization network (LISN)
3. Receiver set RBW of 9kHz and Detector Peak, and note as quasi-peak and average.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. Recorded Line for Neutral and Line.

4.1.3 Test Setup



4.1.4 Test Result

PASS

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Data

Test Mode:	Mode 1	Temp/Hum	24(℃)/ 50%RH
Phase:	Line	Test Date	September 15, 2020
Test Voltage:	120Vac, 60Hz	Test Engineer	Rick Lee



Frequency (MHz)	Quasi Peak reading (dBuV)	Average reading (d uV)	Correction factor (dB)	Quasi Peak result (dBuV)	Average result (dBuV)	Quasi Peak limit (dBuV)	Average limit (dBuV)	Quasi Peak margin (dB)	Average margin (dB)	Remark
0.1820	28.73	18.45	10.21	38.94	28.66	64.39	54.39	-25.45	-25.73	Pass
0.3020	19.06	11.92	10.22	29.28	22.14	60.19	50.19	-30.91	-28.05	Pass
0.3660	22.75	14.51	10.22	32.97	24.73	58.59	48.59	-25.62	-23.86	Pass
0.4540	25.25	17.34	10.22	35.47	27.56	56.80	46.80	-21.33	-19.24	Pass
0.6620	12.01	5.78	10.22	22.23	16.00	56.00	46.00	-33.77	-30.00	Pass
0.9620	18.54	9.73	10.24	28.78	19.97	56.00	46.00	-27.22	-26.03	Pass

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode:	Mode 1	Temp/Hum	24(℃)/ 50%RH
Phase:	Neutral	Test Date	September 15, 2020
Test Voltage:	120Vac, 60Hz	Test Engineer	Rick Lee

Frequency (MHz)	Quasi Peak reading dBuV)	Average reading (dBuV)	Correction factor (dB)	Quasi Peak result (dBuV)	Average result (dBuV)	Quasi Peak limit (dBuV)	Average limit (dBuV)	Quasi Peak margin (dB)	Average margin (dB)	Remark
0.1500	31.91	21.37	10.18	42.09	31.55	66.00	56.00	-23.91	-24.45	Pass
0.1700	28.89	19.90	10.18	39.07	30.08	64.96	54.96	-25.89	-24.88	Pass
0.1900	27.75	19.53	10.19	37.94	29.72	64.04	54.04	-26.10	-24.32	Pass
0.2900	19.81	11.02	10.19	30.00	21.21	60.52	50.52	-30.52	-29.31	Pass
0.3140	19.42	13.06	10.19	29.61	23.25	59.86	49.86	-30.25	-26.61	Pass
0.3620	23.77	14.63	10.19	33.96	24.82	58.68	48.68	-24.72	-23.86	Pass

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

4.2 20dB BANDWIDTH AND OCCUPIED BANDWIDTH (99%)

4.2.1 Test Limit

According to §15.247(a) (1),

20 dB Bandwidth ：For reporting purposes only.

Occupied Bandwidth(99%) ：For reporting purposes only.

4.2.2 Test Procedure

Test method Refer as ANSI C63.10: 2013 clause 7.8.7,

1. The EUT RF output connected to the spectrum analyzer by RF cable.
2. Setting maximum power transmit of EUT
3. SA set RBW = 30kHz, VBW = 100kHz and Detector = Peak, to measurement 20 dB Bandwidth and 99% Bandwidth.
4. SA set RBW = 1% ~ 5% OBW, VBW = three times the RBW and Detector = Peak, to measurement 99% Bandwidth
5. Measure and record the result of 20 dB Bandwidth and 99% Bandwidth. in the test report.

4.2.3 Test Setup



This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

4.2.4 Test Result

Temperature: 24℃ **Humidity:** 50% RH

Tested by: Jane Wang

Test mode: GFSK_BDR-1Mbps mode / 2402-2480 MHz			
Channel	**Frequency (MHz)**	**OBW(99%) (MHz)**	**20dB BW (MHz)**
Low	2402	0.8856	0.9521
Mid	2441	0.8856	0.9565
High	2480	0.8769	0.9565

Test mode: 8DPSK_EDR-3Mbps mode / 2402-2480 MHz			
Channel	**Frequency (MHz)**	**OBW(99%) (MHz)**	**20dB BW (MHz)**
Low	2402	1.1765	1.2869
Mid	2441	1.1765	1.2869
High	2480	1.1722	1.2826

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Data

20dB BANDWIDTH

GFSK_BDR-1Mbps mode

Low CH



Date: 10.SEP.2020 11:41:22

Mid CH



Date: 10.SEP.2020 11:39:06

High CH



Date: 10.SEP.2020 11:55:07

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

8DPSK_EDR-3Mbps mode

Low CH



Mid CH



High CH



This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Data

BANDWIDTH 99%

GFSK_BDR-1Mbps mode	
Low CH	**Mid CH**
	
High CH	
	

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

8DPSK_EDR-3Mbps mode

Low CH



Mid CH



High CH



This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

4.3 OUTPUT POWER MEASUREMENT

4.3.1 Test Limit

According to §15.247(a)(1)

Peak output power：

FCC

Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Limit	☒ Antenna not exceed 6 dBi：21dBm ☐ Antenna with DG greater than 6 dBi：21dBm [Limit = 30 – (DG – 6)]

Average output power：For reporting purposes only.

4.3.2 Test Procedure

1. The EUT RF output connected to the power meter by RF cable.
2. Setting maximum power transmit of EUT.
3. The path loss was compensated to the results for each measurement.
4. Measure and record the result of Peak output power and Average output power. in the test report.

4.3.3 Test Setup



This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

4.3.4 Test Result

Temperature:	24℃	**Humidity:**	50% RH
Tested by:	Jane Wang	**Test Date:**	September 10, 2020

Peak output power：

BT							
Config.	CH	Freq. (MHz)	Power Setting	PK Power (dBm)	PK Power (W)	Ant. Gain (dBi)	Limit (dBm)
GFSK BR-1Mbps (DH5)	0	2402	9	10.00	0.0100	-2.37	21
	39	2441	9	10.10	0.0102		
	78	2480	9	9.51	0.0089		
8DPSK EDR-3Mbps (3DH5)	0	2402	9	**10.42**	0.0110		
	39	2441	9	10.18	0.0104		
	78	2480	9	9.57	0.0091		

Average output power：

BT				
Config.	CH	Freq. (MHz)	Power setting	AV Power (dBm)
GFSK BR-1Mbps (DH5)	0	2402	9	9.77
	39	2441	9	9.87
	78	2480	9	9.28
8DPSK EDR-3Mbps (3DH5)	0	2402	9	7.60
	39	2441	9	7.80
	78	2480	9	7.01

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

4.4 FREQUENCY SEPARATION

4.4.1 Test Limit

According to §15.247(a)(1)

Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Limit	> two-thirds of the 20 dB bandwidth

4.4.2 Test Procedure

1. Place the EUT on the table and set it in transmitting mode.
2. EUT RF output port connected to the SA by RF cable.
3. Set the spectrum analyzer as RBW = 100kHz, VBW = 300kHz, Sweep = auto. Max hold, mark 3 peaks of hopping channel and record the 3 peaks frequency

4.4.3 Test Setup



This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

4.4.4 Test Result

Temperature: 24℃ **Humidity:** 50% RH

Tested by: Jane Wang

Test mode: GFSK_BDR-1Mbps mode / 2402-2480 MHz				
Channel	**Frequency (MHz)**	**Channel Separation (MHz)**	**Channel Separation Limits (MHz)**	**Result**
Low	2402	1.0029	0.635	PASS
Mid	2441	1.0029	0.638	PASS
High	2480	1.0029	0.638	PASS

Test mode: 8DPSK_EDR-3Mbps mode / 2402-2480 MHz				
Channel	**Frequency (MHz)**	**Channel Separation (MHz)**	**Channel Separation Limits (MHz)**	**Result**
Low	2402	0.9986	0.858	PASS
Mid	2441	0.9986	0.858	PASS
High	2480	0.9986	0.855	PASS

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Data

GFSK_BDR-1Mbps mode



8DPSK_EDR-3Mbps mode



Note: We selected worst case to performed test in middle channel, The results can be meet other channel.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

4.5 NUMBER OF HOPPING

4.5.1 Test Limit

According to §15.247(a)(1)(iii)

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

4.5.2 Test Procedure

Test method Refer as ANSI C63.10: 2013 clause 7.8.3
1. Place the EUT on the table and set it in transmitting mode.
2. EUT RF output port connected to the SA by RF cable.
3. Set spectrum analyzer Start Freq. = 2400 MHz, Stop Freq. = 2483.5 MHz, RBW=100KHz, VBW = 300KHz.
4. Max hold, view and count how many channel in the band.

4.5.3 Test Setup



4.5.4 Test Result

Temperature: 24℃ **Humidity:** 50% RH

Tested by: Jane Wang

Number of Hopping				
Mode	**Frequency (MHz)**	**Hopping Channel Number**	**Hopping Channel Number Limits**	**Result**
BDR-1Mbps	2402-2480	79	15	Pass
EDR-3Mbps	2402-2480	79	15	

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Data

Number of Hopping	
GFSK_BDR-1Mbps mode	**8DPSK_EDR-3Mbps mode**
	

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

4.6 CONDUCTED BANDEDGE AND SPURIOUS EMISSION

4.6.1 Test Limit

According to §15.247(d)

Limit	-20 dBc

.

4.6.2 Test Procedure

1. EUT RF output port connected to the SA by RF cable, and the path loss was compensated to result.

2. SA setting, RBW=100kHz, VBW=300kHz, Detector=Peak, Trace mode = max hold, SWT = Auto.

3. The Band Edge at 2.4GHz and 2.4835GHz are investigated with both hopping “ON” and “OFF” modes “.

4.6.3 Test Setup



This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

4.6.4 Test Result

Temperature: 24℃ **Humidity:** 50% RH

Tested by: Jane Wang

Test Data

GFSK_BDR-1Mbps mode Low CH	
Band Edge	**Spurious Emission 30MHz-25GHz**
	
GFSK_BDR-1Mbps mode Mid CH	
Spurious Emission 30MHz-25GHz	
	

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

GFSK_BDR-1Mbps mode High CH

Band Edge



Spurious Emission 30MHz-25GHz



GFSK_BDR-1Mbps Hopping mode

Low Band Edge



High Band Edge



This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

8DPSK_EDR-3Mbps mode Low CH

Band Edge



Spurious Emission 30MHz-25GHz



8DPSK_EDR-3Mbps mode Mid CH

Spurious Emission 30MHz-25GHz



This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

8DPSK_EDR-3Mbps mode High CH

Band Edge



Spurious Emission 30MHz-25GHz



8DPSK_EDR-3Mbps Hopping mode

Low Band Edge



High Band Edge



This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

4.7 TIME OF OCCUPANCY (DWELL TIME)

4.7.1 Test Limit

According to §15.247(a)(1)(iii)

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

4.7.2 Test Procedure

1. EUT RF output port connected to the SA by RF cable.
2. Set center frequency of spectrum analyzer = operating frequency.
3. Set the spectrum analyzer as RBW, VBW=1MHz, Sweep = 1 ms

4.7.3 Test Setup



4.7.4 Test Result

Temperature: 24℃ **Humidity:** 50% RH

Tested by: Jane Wang

Time of Occupancy (Dwell Time)							
Mode	**Frequency (MHz)**	**Pulse Time Per Hopping (ms)**	**Minimum Number of Hopping Freq.**	**Number of pulse in (0.4 * N sec)**	**Dwell Time IN (0.4 * N sec)**	**Dwell Time Limits (s)**	**Result**
DH5	2441	2.8841	79	106.67	0.3076	0.4	Pass
3DH5	2441	2.8841	79	106.67	0.3076	0.4	
AFH: DH5	2441	2.8841	20	53.33	0.1538	0.4	
Non-AFH: DH5 Packet permit maximum 1600/ 79 / 6 = 3.37 hops per second in each channel (5 time slots RX, 1 time slot TX). So, the dwell time is the time duration of the pulse times 3.37 * 0.4 *79 = 106.6							
AFH: DH5 Packet permit maximum 800/ 20 / 6 = 6.666 hops per second in each channel (5 time slots RX, 1 time slot TX). So, the dwell time is the time duration of the pulse times 6.666*0.4*20 = 53.33							

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Data

Time of Occupancy (Dwell Time)	
GFSK_BDR-1Mbps mode	**8DPSK_EDR-3Mbps mode**
	

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

4.8 RADIATION BANDEDGE AND SPURIOUS EMISSION

4.8.1 Test Limit

FCC according to §15.247(d), §15.209 and §15.205,

In any 100 kHz bandwidth outside the authorized frequency band, all harmonic and spurious must be least 20 dB below the highest emission level with the authorized frequency band. Radiation emission which fall in the restricted bands must also follow the FCC section 15.209 as below limit in table.

Below 30 MHz

Frequency	Field Strength (microvolts/m)	Magnetic H-Field (microamperes/m)	Measurement Distance (metres)
9-490 kHz	2,400/F (F in kHz)	2,400/F (F in kHz)	300
490-1,705 kHz	24,000/F (F in kHz)	24,000/F (F in kHz)	30
1.705-30 MHz	30	N/A	30

Above 30 MHz

Frequency (MHz)	Field Strength microvolts/m at 3 metres (watts, e.i.r.p.)	
	Transmitters	Receivers
30-88	100 (3 nW)	100 (3 nW)
88-216	150 (6.8 nW)	150 (6.8 nW)
216-960	200 (12 nW)	200 (12 nW)
Above 960	500 (75 nW)	500 (75 nW)

Remark:
Although these tests were performed other than open area test site, adequate comparison measurements were confirmed against 30 m open are test site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

4.8.2 Test Procedure

1. The EUT is placed on a turntable, Above 1 GHz is 1.5m and below 1 GHz is 0.8m above ground plane. The EUT Configured un accordance with ANSI C63.10: 2013, and the EUT set in a continuous mode.

2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level. And EUT is set 3m away from the receiving antenna, which is scanned from 1m to 4m above the ground plane to find out the highest emissions. Measurement are made polarized in both the vertical and the horizontal positions with antenna.

3. Span shall wide enough to full capture the emission measured. The SA from 9kHz to 26.5GHz set to the low, Mid and High channels with the EUT transmit.

Note: No emission found between lowest internal used/generated frequency to 30MHz(9KHz~30MHz)

4. For harmonic, the worst case of output power was BDR-1Mbps. Therefore only BDR-1Mbps record in the report.

5. The SA setting following：

(1) Below 1G：RBW = 100kHz, VBW ≥ 3 RBW, Sweep = Auto, Detector = Peak, Trace = Max hold.

(2) Above 1G：

(2.1) For Peak measurement：RBW = 1MHz, VBW ≥ 3 RBW, Sweep = Auto, Detector = Peak, Trace = Max hold.

(2.2) For Average measurement：RBW = 1MHz, VBW

˙If Duty Cycle ≥ 98%, VBW=10Hz.

˙If Duty Cycle < 98%, VBW≥1/T.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

4.8.3 Test Setup

9kHz ~ 30MHz



30MHz ~ 1GHz



This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Above 1 GHz



This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

4.8.4 Test Result

Band Edge Test Data

Test Mode:	GFSK_BDR-1Mbps Low CH	Temp/Hum	25.0(℃)/ 42%RH
Test Item	Band Edge	Test Date	September 11, 2020
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak / Average		



Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBµV	Factor dB	Actual FS dBµV/m	Limit @3m dBµV/m	Margin dB
2390.00	Peak	50.72	-3.17	47.55	74.00	-26.45
2390.00	Average	38.45	-3.17	35.28	54.00	-18.72

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode:	GFSK_BDR-1Mbps Low CH	Temp/Hum	25.0(℃)/ 42%RH
Test Item	Band Edge	Test Date	September 11, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak / Average		



Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
2390.00	Peak	50.76	-3.17	47.59	74.00	-26.41
2390.00	Average	37.75	-3.17	34.58	54.00	-19.42

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode:	GFSK_BDR-1Mbps High CH	Temp/Hum	25.0(℃)/ 42%RH
Test Item	Band Edge	Test Date	September 11, 2020
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak / Average		



Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBµV	Factor dB	Actual FS dBµV/m	Limit @3m dBµV/m	Margin dB
2483.50	Peak	50.36	-2.71	47.65	74.00	-26.35
2483.50	Average	38.49	-2.71	35.78	54.00	-18.22

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode:	GFSK_BDR-1Mbps High CH	Temp/Hum	25.0(℃)/ 42%RH
Test Item	Band Edge	Test Date	September 11, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak / Average		



Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBµV	Factor dB	Actual FS dBµV/m	Limit @3m dBµV/m	Margin dB
2483.50	Peak	54.57	-2.71	51.86	74.00	-22.14
2483.50	Average	45.59	-2.71	42.88	54.00	-11.12
2484.25	Peak	58.02	-2.70	55.32	74.00	-18.68
2484.25	Average	45.83	-2.70	43.13	54.00	-10.87
2485.18	Peak	56.92	-2.70	54.22	74.00	-19.78
2485.18	Average	47.16	-2.70	44.46	54.00	-9.54

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode:	GFSK_BDR-1Mbps Low CH Hopping	Temp/Hum	25.0(℃)/ 42%RH
Test Item	Band Edge	Test Date	September 11, 2020
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak / Average		



Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
2390.00	Peak	50.20	-3.17	47.03	74.00	-26.97
2390.00	Average	39.12	-3.17	35.95	54.00	-18.05

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode:	GFSK_BDR-1Mbps Low CH Hopping	Temp/Hum	25.0(℃)/ 42%RH
Test Item	Band Edge	Test Date	September 11, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak / Average		



Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBµV	Factor dB	Actual FS dBµV/m	Limit @3m dBµV/m	Margin dB
2390.00	Peak	47.71	-3.17	44.54	74.00	-29.46
2390.00	Average	38.00	-3.17	34.83	54.00	-19.17

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode:	GFSK_BDR-1Mbps High CH Hopping	Temp/Hum	25.0(℃)/ 42%RH
Test Item	Band Edge	Test Date	September 11, 2020
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak / Average		



Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBµV	Factor dB	Actual FS dBµV/m	Limit @3m dBµV/m	Margin dB
2483.50	Peak	48.01	-2.71	45.30	74.00	-28.70
2483.50	Average	43.00	-2.71	40.29	54.00	-13.71

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode:	GFSK_BDR-1Mbps High CH Hopping	Temp/Hum	25.0(℃)/ 42%RH
Test Item	Band Edge	Test Date	September 11, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak / Average		



Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBµV	Factor dB	Actual FS dBµV/m	Limit @3m dBµV/m	Margin dB
2483.50	Peak	49.94	-2.71	47.23	74.00	-26.77
2483.50	Average	45.74	-2.71	43.03	54.00	-10.97
2484.18	Peak	56.15	-2.70	53.45	74.00	-20.55
2484.18	Average	45.72	-2.70	43.02	54.00	-10.98
2484.83	Peak	55.78	-2.70	53.08	74.00	-20.92
2484.83	Average	45.34	-2.70	42.64	54.00	-11.36

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode:	8DPSK_EDR-3Mbps Low CH	Temp/Hum	25.0(℃)/ 42%RH
Test Item	Band Edge	Test Date	September 11, 2020
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak / Average		



Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBµV	Factor dB	Actual FS dBµV/m	Limit @3m dBµV/m	Margin dB
2390.00	Peak	50.61	-3.17	47.44	74.00	-26.56
2390.00	Average	38.41	-3.17	35.24	54.00	-18.76

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode:	8DPSK_EDR-3Mbps Low CH	Temp/Hum	25.0(℃)/ 42%RH
Test Item	Band Edge	Test Date	September 11, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak / Average		



Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBµV	Factor dB	Actual FS dBµV/m	Limit @3m dBµV/m	Margin dB
2390.00	Peak	50.67	-3.17	47.50	74.00	-26.50
2390.00	Average	37.79	-3.17	34.62	54.00	-19.38

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode:	8DPSK_EDR-3Mbps High CH	Temp/Hum	25.0(℃)/ 42%RH
Test Item	Band Edge	Test Date	September 11, 2020
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak / Average		



Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBµV	Factor dB	Actual FS dBµV/m	Limit @3m dBµV/m	Margin dB
2483.50	Peak	50.27	-2.71	47.56	74.00	-26.44
2483.50	Average	38.44	-2.71	35.73	54.00	-18.27

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode:	8DPSK_EDR-3Mbps High CH	Temp/Hum	25.0(℃)/ 42%RH
Test Item	Band Edge	Test Date	September 11, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak / Average		



Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBµV	Factor dB	Actual FS dBµV/m	Limit @3m dBµV/m	Margin dB
2483.50	Peak	54.48	-2.71	51.77	74.00	-22.23
2483.50	Average	45.36	-2.71	42.65	54.00	-11.35
2483.93	Peak	57.48	-2.70	54.78	74.00	-19.22
2483.93	Average	45.78	-2.70	43.08	54.00	-10.92
2484.85	Peak	56.52	-2.70	53.82	74.00	-20.18
2484.85	Average	47.12	-2.70	44.42	54.00	-9.58

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode:	8DPSK_EDR-3Mbps Low CH Hopping	Temp/Hum	25.0(℃)/ 42%RH
Test Item	Band Edge	Test Date	September 11, 2020
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak / Average		



Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBµV	Factor dB	Actual FS dBµV/m	Limit @3m dBµV/m	Margin dB
2390.00	Peak	54.70	-3.17	51.53	74.00	-22.47
2390.00	Average	39.00	-3.17	35.83	54.00	-18.17

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode:	8DPSK_EDR-3Mbps Low CH Hopping	Temp/Hum	25.0(℃)/ 42%RH
Test Item	Band Edge	Test Date	September 11, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak / Average		



Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBµV	Factor dB	Actual FS dBµV/m	Limit @3m dBµV/m	Margin dB
2390.00	Peak	48.59	-3.17	45.42	74.00	-28.58
2390.00	Average	38.22	-3.17	35.05	54.00	-18.95

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode:	8DPSK_EDR-3Mbps High CH Hopping	Temp/Hum	25.0(℃)/ 42%RH
Test Item	Band Edge	Test Date	September 11, 2020
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak / Average		



Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
2483.50	Peak	48.20	-2.71	45.49	74.00	-28.51
2483.50	Average	43.25	-2.71	40.54	54.00	-13.46

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode:	8DPSK_EDR-3Mbps High CH Hopping	Temp/Hum	25.0(℃)/ 42%RH
Test Item	Band Edge	Test Date	September 11, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak / Average		



Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBµV	Factor dB	Actual FS dBµV/m	Limit @3m dBµV/m	Margin dB
2483.50	Peak	50.06	-2.71	47.35	74.00	-26.65
2483.50	Average	45.87	-2.71	43.16	54.00	-10.84
2484.23	Peak	56.46	-2.70	53.76	74.00	-20.24
2484.23	Average	45.69	-2.70	42.99	54.00	-11.01
2484.85	Peak	56.47	-2.70	53.77	74.00	-20.23
2484.85	Average	45.29	-2.70	42.59	54.00	-11.41

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Below 1G Test Data

Test Mode:	Mode 1	Temp/Hum	25.0(℃)/ 42%RH
Test Item	30MHz-1GHz	Test Date	September 11, 2020
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak		



Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBµV	Factor dB	Actual FS dBµV/m	Limit @3m dBµV/m	Margin dB
47.46	Peak	39.88	-14.32	25.56	40.00	-14.44
57.16	Peak	41.64	-16.16	25.48	40.00	-14.52
132.82	Peak	32.71	-9.33	23.38	43.50	-20.12
217.21	Peak	39.72	-11.84	27.88	46.00	-18.12
313.24	Peak	31.88	-8.05	23.83	46.00	-22.17
898.15	Peak	26.89	3.03	29.92	46.00	-16.08

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode:	Mode 1	Temp/Hum	25.0(℃)/ 42%RH
Test Item	30MHz-1GHz	Test Date	September 11, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak		



Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBµV	Factor dB	Actual FS dBµV/m	Limit @3m dBµV/m	Margin dB
105.66	Peak	35.08	-11.23	23.85	43.50	-19.65
133.79	Peak	32.57	-9.36	23.21	43.50	-20.29
221.09	Peak	39.42	-11.69	27.73	46.00	-18.27
276.38	Peak	35.86	-8.76	27.10	46.00	-18.90
315.18	Peak	34.75	-7.94	26.81	46.00	-19.19
841.89	Peak	26.25	2.36	28.61	46.00	-17.39

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode:	Mode 2	Temp/Hum	25.0(℃)/ 42%RH
Test Item	30MHz-1GHz	Test Date	September 18, 2020
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak		



Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBµV	Factor dB	Actual FS dBµV/m	Limit @3m dBµV/m	Margin dB
44.55	Peak	32.79	-12.85	19.94	40.00	-20.06
68.80	Peak	36.98	-15.06	21.92	40.00	-18.08
159.98	Peak	32.39	-10.20	22.19	43.50	-21.31
223.03	Peak	36.87	-11.58	25.29	46.00	-20.71
341.37	Peak	28.90	-7.71	21.19	46.00	-24.81
887.48	Peak	24.61	2.68	27.29	46.00	-18.71

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode:	Mode 2	Temp/Hum	25.0(℃)/ 42%RH
Test Item	30MHz-1GHz	Test Date	September 18, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak		



Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBµV	Factor dB	Actual FS dBµV/m	Limit @3m dBµV/m	Margin dB
36.79	Peak	27.38	-7.36	20.02	40.00	-19.98
108.57	Peak	30.97	-10.80	20.17	43.50	-23.33
130.88	Peak	28.61	-9.16	19.45	43.50	-24.05
224.00	Peak	38.28	-11.52	26.76	46.00	-19.24
477.17	Peak	25.57	-3.43	22.14	46.00	-23.86
835.10	Peak	25.26	2.13	27.39	46.00	-18.61

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Above 1G Test Data

Test Mode:	GFSK_BDR-1Mbps Low CH	Temp/Hum	25.0(℃)/ 42%RH
Test Item	Harmonic	Test Date	September 11, 2020
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak		



Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBµV	Factor dB	Actual FS dBµV/m	Limit @3m dBµV/m	Margin dB
4804.00	Peak	37.05	3.36	40.41	74.00	-33.59
7206.00	Peak	35.38	10.77	46.15	74.00	-27.85
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode:	GFSK_BDR-1Mbps Low CH	Temp/Hum	25.0(℃)/ 42%RH
Test Item	Harmonic	Test Date	September 11, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak		



Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBµV	Factor dB	Actual FS dBµV/m	Limit @3m dBµV/m	Margin dB
4804.00	Peak	37.11	3.36	40.47	74.00	-33.53
7206.00	Peak	35.31	10.77	46.08	74.00	-27.92
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode:	GFSK_BDR-1Mbps Mid CH	Temp/Hum	25.0(℃)/ 42%RH
Test Item	Harmonic	Test Date	September 11, 2020
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak		



Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBµV	Factor dB	Actual FS dBµV/m	Limit @3m dBµV/m	Margin dB
4882.00	Peak	37.29	3.52	40.81	74.00	-33.19
7323.00	Peak	34.04	11.01	45.05	74.00	-28.95
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode:	GFSK_BDR-1Mbps Mid CH	Temp/Hum	25.0(℃)/ 42%RH
Test Item	Harmonic	Test Date	September 11, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak		



Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBµV	Factor dB	Actual FS dBµV/m	Limit @3m dBµV/m	Margin dB
4882.00	Peak	36.71	3.52	40.23	74.00	-33.77
7323.00	Peak	34.21	11.01	45.22	74.00	-28.78
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode:	GFSK_BDR-1Mbps High CH	Temp/Hum	25.0(℃)/ 42%RH
Test Item	Harmonic	Test Date	September 11, 2020
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak		



Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBµV	Factor dB	Actual FS dBµV/m	Limit @3m dBµV/m	Margin dB
4960.00	Peak	37.65	4.46	42.11	74.00	-31.89
7440.00	Peak	34.91	10.66	45.57	74.00	-28.43
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode:	GFSK_BDR-1Mbps High CH	Temp/Hum	25.0(℃)/ 42%RH
Test Item	Harmonic	Test Date	September 11, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak		



Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBµV	Factor dB	Actual FS dBµV/m	Limit @3m dBµV/m	Margin dB
4960.00	Peak	36.98	4.46	41.44	74.00	-32.56
7440.00	Peak	33.82	10.66	44.48	74.00	-29.52
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	8DPSK_EDR-3Mbps Low CH	Temp/Hum	25.0(℃)/ 42%RH
Test Item	Harmonic	Test Date	September 11, 2020
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak		



Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBµV	Factor dB	Actual FS dBµV/m	Limit @3m dBµV/m	Margin dB
4804.00	Peak	37.02	3.36	40.38	74.00	-33.62
7206.00	Peak	35.26	10.77	46.03	74.00	-27.97
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	8DPSK_EDR-3Mbps Low CH	Temp/Hum	25.0(℃)/ 42%RH
Test Item	Harmonic	Test Date	September 11, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak		



Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBµV	Factor dB	Actual FS dBµV/m	Limit @3m dBµV/m	Margin dB
4804.00	Peak	36.99	3.36	40.35	74.00	-33.65
7206.00	Peak	35.37	10.77	46.14	74.00	-27.86
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	8DPSK_EDR-3Mbps Mid CH	Temp/Hum	25.0(℃)/ 42%RH
Test Item	Harmonic	Test Date	September 11, 2020
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak		



Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBµV	Factor dB	Actual FS dBµV/m	Limit @3m dBµV/m	Margin dB
4882.00	Peak	37.35	3.52	40.87	74.00	-33.13
7323.00	Peak	34.19	11.01	45.20	74.00	-28.80
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	8DPSK_EDR-3Mbps Mid CH	Temp/Hum	25.0(℃)/ 42%RH
Test Item	Harmonic	Test Date	September 11, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak		



Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBµV	Factor dB	Actual FS dBµV/m	Limit @3m dBµV/m	Margin dB
4882.00	Peak	36.83	3.52	40.35	74.00	-33.65
7323.00	Peak	34.35	11.01	45.36	74.00	-28.64
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	8DPSK_EDR-3Mbps High CH	Temp/Hum	25.0(℃)/ 42%RH
Test Item	Harmonic	Test Date	September 11, 2020
Polarize	Vertical	Test Engineer	Jerry Chang
Detector	Peak		



Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBµV	Factor dB	Actual FS dBµV/m	Limit @3m dBµV/m	Margin dB
4960.00	Peak	37.71	4.46	42.17	74.00	-31.83
7440.00	Peak	34.86	10.66	45.52	74.00	-28.48
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Mode	8DPSK_EDR-3Mbps High CH	Temp/Hum	25.0(℃)/ 42%RH
Test Item	Harmonic	Test Date	September 11, 2020
Polarize	Horizontal	Test Engineer	Jerry Chang
Detector	Peak		



Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBµV	Factor dB	Actual FS dBµV/m	Limit @3m dBµV/m	Margin dB
4960.00	Peak	37.15	4.46	41.61	74.00	-32.39
7440.00	Peak	33.94	10.66	44.60	74.00	-29.40
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit

--End of Test Report--

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。