

Modular Approval Request FCC (KDB 996369 D01 & Part 15.212)

FCC ID: HFS-QV28NRW

Items to be covered by Single modular transmitters.	Answer from applicant
1. The radio elements must have the radio frequency circuitry shielded. Physical components and tuning capacitor(s) may be located external to the shield, but must be on the module assembly.	This module has the own shielding on transmitter.
2. The module must have buffered modulation/data inputs to ensure that the device will comply with Part 15 requirements with any type of input signal.	This module has the buffered modulation/data inputs.
3. The module must contain power supply regulation on the module.	This module has own power supply regulation.
4. The module must contain a permanently attached antenna, or contain a unique antenna connector, and be marketed and operated only with specific antenna(s), per §§ 15.203, 15.204(b), 15.204(c), 15.212(a), 2.929(b).	This module includes external antennas and an internal BUA antenna, both of which are connected to the NAD module.
5. The module must demonstrate compliance in a stand-alone configuration.	The test was performed in a stand-alone configuration without any host product.
6. The module must be labeled with its permanently affixed FCC ID label, or use an electronic display (see KDB Publication 784748)	The FCC ID is labelled on the shield can of this module.
7. The module must comply with all specific rules applicable to the transmitter, including all the conditions provided in the integration instructions by the grantee.	This module complies with all specific rules and operating requirements.
8. The module must comply with RF exposure requirements.	This module complies with the RF Exposure requirements

Note: A limited modular approval (LMA) may be granted for *single* or *split* modular transmitters that comply partially with the requirements above.

Name and surname of applicant (or authorized representative): Joyce Kuo

Date: 26 March 2026

Signature: 