FCC RF Test Report

APPLICANT	:	Acer Incorporated
EQUIPMENT	:	Tablet Computer
BRAND NAME	:	acer
MODEL NAME	:	A7003
FCC ID	:	HLZA7003
STANDARD	:	FCC Part 15 Subpart C §15.247
CLASSIFICATION	:	(DTS) Digital Transmission System

The product was received on Jul. 28, 2017 and testing was completed on Aug. 14, 2017. We, Sporton International (Shenzhen) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Shenzhen) Inc., the test report shall not be reproduced except in full.

Eric Shih

Approved by: Eric Shih / Manager

NVLAP®
TESTING
NVLAP LAB CODE 600156-0

Sporton International (Shenzhen) Inc.
1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan Shenzhen City Guangdong Province 518055 China

TABLE OF CONTENTS

REVISION HISTORY **3**

SUMMARY OF TEST RESULT **4**

1 GENERAL DESCRIPTION **5**

1.1 Applicant 5
1.2 Manufacturer 5
1.3 Product Feature of Equipment Under Test 5
1.4 Product Specification of Equipment Under Test 6
1.5 Modification of EUT 6
1.6 Testing Location 7
1.7 Applicable Standards 7

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST **8**

2.1 Carrier Frequency and Channel 8
2.2 Test Mode 8
2.3 Connection Diagram of Test System 9
2.4 Support Unit used in test configuration and system 10
2.5 EUT Operation Test Setup 10
2.6 Measurement Results Explanation Example 11

3 TEST RESULT **12**

3.1 6dB and 99% Bandwidth Measurement 12
3.2 Output Power Measurement 14
3.3 Power Spectral Density Measurement 16
3.4 Conducted Band Edges and Spurious Emission Measurement 18
3.5 Radiated Band Edges and Spurious Emission Measurement 31
3.6 AC Conducted Emission Measurement 35
3.7 Antenna Requirements 39

4 LIST OF MEASURING EQUIPMENT **40**

5 UNCERTAINTY OF EVALUATION **41**

APPENDIX A. CONDUCTED TEST RESULTS

APPENDIX B. RADIATED SPURIOUS EMISSION

APPENDIX C. DUTY CYCLE PLOTS

APPENDIX D. SETUP PHOTOGRAPHS

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR772802C	Rev. 01	Initial issue of report	Sep. 04, 2017

SUMMARY OF TEST RESULT

Report Section	FCC Rule	IC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	RSS-247 5.2(a)	6dB Bandwidth	≥ 0.5MHz	Pass	-
3.1	-	RSS-Gen 6.6	99% Bandwidth	-	Pass	-
3.2	15.247(b)	RSS-247 5.4(d)	Power Output Measurement	≤ 30dBm	Pass	-
3.3	15.247(e)	RSS-247 5.2(b)	Power Spectral Density	≤ 8dBm/3kHz	Pass	-
3.4	15.247(d)	RSS-247 5.5	Conducted Band Edges	≤ 20dBc	Pass	-
			Conducted Spurious Emission		Pass	-
3.5	15.247(d)	RSS-247 5.5	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 1.93 dB at 2390.00 MHz
3.6	15.207	RSS-GEN 8.8	AC Conducted Emission	15.207(a)	Pass	Under limit 14.99 dB at 0.20 MHz
3.7	15.203 & 15.247(b)	N/A	Antenna Requirement	N/A	Pass	-

1 General Description

1.1 Applicant

Acer Incorporated
8F , 88, Sec.1 Xintai 5th Rd., Xizhi, New Taipei City 221, Taiwan, R.O.C

1.2 Manufacturer

Acer Incorporated
8F , 88, Sec.1 Xintai 5th Rd., Xizhi, New Taipei City 221, Taiwan, R.O.C

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Tablet Computer
Brand Name	acer
Model Name	A7003
FCC ID	HLZA7003
EUT supports Radios application	WLAN2.4GHz 802.11b/g/n HT20/HT40 WLAN5GHz 802.11a/n HT20/HT40 WLAN5GHz 802.11ac VHT20/VHT40/VHT80 Bluetooth v3.0+EDR/Bluetooth v4.0 LE Bluetooth v4.1 LE
HW Version	A10H2_MB_V1.2
SW Version	Acer_AV0N0_A3-A50_RV01RA01_WW_GEN1
EUT Stage	Production Unit

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Channel Frequency Range	2412 MHz ~ 2462 MHz
Maximum (Peak) Output Power to antenna	802.11b : 15.83 dBm (0.0383 W) 802.11g : 21.28 dBm (0.1343 W) 802.11n HT20 : 21.15 dBm (0.1303 W) 802.11n HT40 : 17.41 dBm (0.0551 W)
99% Occupied Bandwidth	802.11b : 13.79MHz 802.11g : 18.13MHz 802.11n HT20 : 18.58MHz 802.11n HT40 : 36.76MHz
Antenna Type / Gain	FPC Antenna type with gain 3.75 dBi
Type of Modulation	802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM)

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Location

Sporton Lab is accredited to ISO 17025 by National Voluntary Laboratory Accreditation Program (NVLAP code: 600156-0) and the FCC designation No. are CN5018 and CN5019.

Test Site	Sporton International (Shenzhen) Inc.		
Test Site Location	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan Shenzhen City Guangdong Province 518055 China TEL: +86-755-8637-9589 FAX: +86-755-8637-9595		
Test Site No.	**Sporton Site No.**		**FCC Test Firm Registration No.**
	TH01-SZ	CO01-SZ	251365

Test Site	Sporton International (Shenzhen) Inc.	
Test Site Location	No. 3 Bldg the third floor of south, Shahe River west, Fengzeyuan Warehouse, Nanshan District Shenzhen City Guangdong Province 518055 China TEL: +86-755-3320-2398	
Test Site No.	**Sporton Site No.**	**FCC Test Firm Registration No.**
	03CH01-SZ	577730

Note: The test site complies with ANSI C63.4 2014 requirement.

1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart C §15.247
- FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04
- ANSI C63.10-2013
- IC RSS-247 Issue 2
- IC RSS-Gen Issue 4

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conducted emission (150 kHz to 30 MHz) and radiated emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (X plane) were recorded in this report.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437	-	-

2.2 Test Mode

Final test mode of conducted test items and radiated spurious emissions are considering the modulation and worse data rates as below table.

Modulation	Data Rate
802.11b	**1 Mbps**
802.11g	**6 Mbps**
802.11n HT20	**MCS0**
802.11n HT40	**MCS0**

Test Cases	
AC Conducted Emission	Mode 1 : Bluetooth Link + WLAN2.4G Link + USB Cable(Charging from Adapter1) + Earphone Mode 2 : :Bluetooth Link + WLAN2.4G Link + USB Cable(Charging from Adapter2) + Earphone
Remark: The worst case of conducted emission is mode 2; only the test data of it was reported.	

2.3 Connection Diagram of Test System

<WLAN Tx Mode>



<AC Conducted Emission Mode>



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	WLAN AP	D-Link	DIR-820L	KA2IR820LA1	N/A	Unshielded, 1.8 m
2.	Bluetooth Earphone	Sumsung	BH-108	PYAHS-107W	N/A	N/A
3.	Notebook	Lenovo	E540	FCC DoC	N/A	AC I/P：Unshielded, 1.2m DC O/P：Shielded, 1.8m
4.	Earphone	Coolpad	N/A	N/A	N/A	Unshielded,1.0m

2.5 EUT Operation Test Setup

For WLAN function, the engineering test program was provided and enabled to make EUT continuous transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 5.0dB and 10dB attenuator.

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

= 5.0 + 10 = 15.0 (dB)

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 DTS D01 Meas. Guidance v04.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) = 1MHz and set the Video bandwidth (VBW) = 3MHz.
6. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB and 99% Occupied Bandwidth

Please refer to Appendix A.

Minimum 6dB Bandwidth	Maximum 99% Occupied Bandwidth
	

Note : The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi are used the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v04 section 9.1.2 PKPM1 Peak power meter method.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Peak Output Power

Please refer to Appendix A.

3.2.6 Test Result of Average output Power (Reporting Only)

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

Worst Case Power Density (dBm/3kHz)



3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement.

3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup



3.4.5 Test Result of Conducted Band Edges and Spurious Emission

Test Mode :	802.11b	**Temperature :**	24~25℃
Test Band :	2.4GHz Low	**Relative Humidity :**	48~49%
Test Channel :	01	**Test Engineer :**	Liu lun

WLAN 802.11b Channel 01

100kHz PSD reference Level



Low Channel Plot



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz



Test Mode :	802.11b	**Temperature :**	24~25℃
Test Band :	2.4GHz Mid	**Relative Humidity :**	48~49%
Test Channel :	06	**Test Engineer :**	Liu lun

WLAN 802.11b Channel 06

100kHz PSD reference Level



Mid Channel Plot

Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz



Test Mode :	802.11b	**Temperature :**	24~25℃
Test Band :	2.4GHz High	**Relative Humidity :**	48~49%
Test Channel :	11	**Test Engineer :**	Liu lun

WLAN 802.11b Channel 11

100kHz PSD reference Level



High Channel Plot



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz



Test Mode :	802.11g	**Temperature :**	24~25℃
Test Band :	2.4GHz Low	**Relative Humidity :**	48~49%
Test Channel :	01	**Test Engineer :**	Liu lun

WLAN 802.11g Channel 01

100kHz PSD reference Level



Low Channel Plot



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz



Test Mode :	802.11g	**Temperature :**	24~25℃
Test Band :	2.4GHz Mid	**Relative Humidity :**	48~49%
Test Channel :	06	**Test Engineer :**	Liu lun

WLAN 802.11g Channel 06

100kHz PSD reference Level



Mid Channel Plot

Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz



Test Mode :	802.11g	**Temperature :**	24~25℃
Test Band :	2.4GHz High	**Relative Humidity :**	48~49%
Test Channel :	11	**Test Engineer :**	Liu lun

WLAN 802.11g Channel 11

100kHz PSD reference Level



High Channel Plot



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz



Test Mode :	802.11n HT20	**Temperature :**	24~25℃
Test Band :	2.4GHz Low	**Relative Humidity :**	48~49%
Test Channel :	01	**Test Engineer :**	Liu lun

WLAN 802.11n HT20 Channel 01

100kHz PSD reference Level



Low Channel Plot



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz



Test Mode :	802.11n HT20	**Temperature :**	24~25℃
Test Band :	2.4GHz Mid	**Relative Humidity :**	48~49%
Test Channel :	06	**Test Engineer :**	Liu lun

WLAN 802.11n HT20 Channel 06

100kHz PSD reference Level	Mid Channel Plot
	

Spurious Emission 30MHz~3GHz	Spurious Emission 2GHz~25GHz
	

Test Mode :	802.11n HT20	**Temperature :**	24~25℃
Test Band :	2.4GHz High	**Relative Humidity :**	48~49%
Test Channel :	11	**Test Engineer :**	Liu lun

WLAN 802.11n HT20 Channel 11

100kHz PSD reference Level



High Channel Plot



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz



Test Mode :	802.11n HT40	**Temperature :**	24~25℃
Test Band :	2.4GHz Low	**Relative Humidity :**	48~49%
Test Channel :	03	**Test Engineer :**	Liu lun

WLAN 802.11n HT40 Channel 03

100kHz PSD reference Level



Low Channel Plot



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz



Test Mode :	802.11n HT40	**Temperature :**	24~25℃
Test Band :	2.4GHz Mid	**Relative Humidity :**	48~49%
Test Channel :	06	**Test Engineer :**	Liu lun

WLAN 802.11n HT40 Channel 06

100kHz PSD reference Level



Mid Channel Plot

Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz



Test Mode :	802.11n HT40	**Temperature :**	24~25℃
Test Band :	2.4GHz High	**Relative Humidity :**	48~49%
Test Channel :	09	**Test Engineer :**	Liu lun

WLAN 802.11n HT40 Channel 09

100kHz PSD reference Level



High Channel Plot



Spurious Emission 30MHz~3GHz



Spurious Emission 2GHz~25GHz



3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. Use the following spectrum analyzer settings:
   (1) Span shall wide enough to fully capture the emission being measured;
   (2) Set RBW=100 kHz for f < 1 GHz; VBW ≥ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
   (3) Set RBW = 1 MHz, VBW= 3MHz for f ≥ 1 GHz for peak measurement.
   For average measurement:
   - VBW = 10 Hz, when duty cycle is no less than 98 percent.
   - VBW ≥ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup

For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.5.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix B.

3.5.7 Duty Cycle

Please refer to Appendix C.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix B.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dBμV)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF bandwidth = 9kHz) with Maximum Hold Mode.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Test Mode :	Mode 2	**Temperature :**	24~25℃
Test Engineer :	HaoHai YE	**Relative Humidity :**	50~55%
Test Voltage :	120Vac / 60Hz	**Phase :**	Line
Function Type :	Bluetooth Link + WLAN2.4G Link + USB Cable(Charging from Adapter2) + Earphone		



Site : CO01-SZ
Condition: FCC 15E QP LISN 20170301_L LINE

		Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
		MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1		0.18	35.33	-19.26	54.59	25.00	0.03	10.30	Average
2	*	0.18	48.23	-16.36	64.59	37.90	0.03	10.30	QP
3		0.21	33.55	-19.77	53.32	23.30	0.03	10.22	Average
4		0.21	46.75	-16.57	63.32	36.50	0.03	10.22	QP
5		0.27	29.55	-21.52	51.07	19.30	0.03	10.22	Average
6		0.27	41.65	-19.42	61.07	31.40	0.03	10.22	QP
7		0.31	25.95	-24.07	50.02	15.70	0.03	10.22	Average
8		0.31	38.85	-21.17	60.02	28.60	0.03	10.22	QP
9		0.37	19.63	-28.98	48.61	9.40	0.03	10.20	Average
10		0.37	35.83	-22.78	58.61	25.60	0.03	10.20	QP
11		0.50	21.30	-24.70	46.00	11.10	0.02	10.18	Average
12		0.50	32.20	-23.80	56.00	22.00	0.02	10.18	QP
13		0.65	25.99	-20.01	46.00	15.80	0.02	10.17	Average
14		0.65	37.59	-18.41	56.00	27.40	0.02	10.17	QP
15		15.07	29.43	-20.57	50.00	18.60	0.51	10.32	Average
16		15.07	38.63	-21.37	60.00	27.80	0.51	10.32	QP

Test Mode :	Mode 2	Temperature :	24~25℃
Test Engineer :	HaoHai YE	Relative Humidity :	50~55%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	Bluetooth Link + WLAN2.4G Link + USB Cable(Charging from Adapter2) + Earphone		



Site : CO01-SZ
Condition: FCC 15E_QP LISN_20170301_N NEUTRAL

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.18	27.91	-26.46	54.37	17.60	0.03	10.28	Average
2	0.18	41.81	-22.56	64.37	31.50	0.03	10.28	QP
3 *	0.20	38.55	-14.99	53.54	28.30	0.03	10.22	Average
4	0.20	43.35	-20.19	63.54	33.10	0.03	10.22	QP
5	0.37	17.72	-30.71	48.43	7.50	0.02	10.20	Average
6	0.37	32.92	-25.51	58.43	22.70	0.02	10.20	QP
7	0.42	17.61	-29.90	47.51	7.40	0.02	10.19	Average
8	0.42	32.11	-25.40	57.51	21.90	0.02	10.19	QP
9	0.63	17.69	-28.31	46.00	7.50	0.02	10.17	Average
10	0.63	32.19	-23.81	56.00	22.00	0.02	10.17	QP
11	1.86	20.71	-25.29	46.00	10.50	0.05	10.16	Average
12	1.86	33.11	-22.89	56.00	22.90	0.05	10.16	QP

3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101078	9kHz~40GHz	Apr. 20.2017	Aug. 01.2017	Apr. 19.2018	Conducted (TH01-SZ)
Pulse Power Senor	Anritsu	MA2411B	1207253	30MHz~40GHz	Jan. 06, 2017	Aug. 01.2017	Jan. 05, 2018	Conducted (TH01-SZ)
Power Meter	Anritsu	ML2495A	1218010	50MHz Bandwidth	Jan. 06, 2017	Aug. 01.2017	Jan. 05, 2018	Conducted (TH01-SZ)
EMI Receiver	R&S	ESR7	101630	9kHz~7GHz;	Jan. 06, 2017	Aug. 11.2017	Jan. 05, 2018	Conduction (CO01-SZ)
AC LISN	EMCO	3816/2SH	00103912	9kHz~30MHz	Jan. 05, 2017	Aug. 11.2017	Jan. 04, 2018	Conduction (CO01-SZ)
AC LISN (for auxiliary equipment)	MessTec	3816/2SH	00103892	9kHz~30MHz	Jan. 05, 2017	Aug. 11.2017	Jan. 04, 2018	Conduction (CO01-SZ)
AC Power Source	Chroma	61602	616020000891	100Vac~250Vac	Jul. 19, 2017	Aug. 11.2017	Jul. 18, 2018	Conduction (CO01-SZ)
EMI Test Receiver &SA	KEYSIGHT	N9038A	MY54450083	20Hz~8.4GHz	Apr. 20, 2017	Aug. 14.2017	Apr.19, 2018	Radiation (03CH03-SZ)
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY55150246	10Hz~44GHz;	Apr. 20, 2017	Aug. 14.2017	Apr.19, 2018	Radiation (03CH03-SZ
Loop Antenna	R&S	HFH2-Z2	100354	9kHz~30MHz	May 14, 2017	Aug. 14.2017	May13, 2018	Radiation (03CH03-SZ)
Bilog Antenna	TeseQ	CBL6112D	35408	30MHz-2GHz	May.14, 2017	Aug. 14.2017	May 13, 2018	Radiation (03CH03-SZ)
Double Ridge Horn Antenna	SCHWARZBECK	BBHA9120D	9120D-1355	1GHz~18GHz	Jul. 09.2017	Aug. 14.2017	Jul. 08, 2018	Radiation (03CH03-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18Ghz-40GHz	Jun.16, 2017	Aug. 14.2017	Jun.15, 2018	Radiation (03CH03-SZ)
Amplifier	Burgeon	BPA-530	102210	0.01Hz ~3000MHz	Oct. 11, 2016	Aug. 14.2017	Oct. 10, 2017	Radiation (03CH03-SZ)
HF Amplifier	MITEQ	AMF-7D-00101800-30-10P-R	1943528	1GHz~18GHz	Oct. 11, 2016	Aug. 14.2017	Oct. 10, 2017	Radiation (03CH03-SZ)
Amplifier	Agilent Technologies	83017A	MY39501302	500MHz~26.5GHz	Jan.06,2017	Aug. 14.2017	Jan. 05,2018	Radiation (03CH03-SZ)
AC Power Source	Chroma	61601	616010001985	N/A	NCR	Aug. 14.2017	NCR	Radiation (03CH03-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	Aug. 14.2017	NCR	Radiation (03CH03-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	Aug. 14.2017	NCR	Radiation (03CH03-SZ)

5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.5dB

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.1 dB

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.2 dB

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.1 dB

Appendix A. Conducted Test Results

Report Number : FR772802C

A1 - DTS Part

Test Engineer:	Sam Zheng	Temperature:	24~26	°C
Test Date:	2017/8/1~2017/8/7	Relative Humidity:	50~53	%

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

2.4GHz Band								
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
11b	1Mbps	1	1	2412	13.79	9.03	0.50	Pass
11b	1Mbps	1	6	2437	13.79	9.01	0.50	Pass
11b	1Mbps	1	11	2462	13.79	9.03	0.50	Pass
11g	6Mbps	1	1	2412	18.13	15.66	0.50	Pass
11g	6Mbps	1	6	2437	18.13	15.68	0.50	Pass
11g	6Mbps	1	11	2462	18.08	15.47	0.50	Pass
HT20	MCS0	1	1	2412	18.48	15.94	0.50	Pass
HT20	MCS0	1	6	2437	18.58	16.06	0.50	Pass
HT20	MCS0	1	11	2462	18.43	16.76	0.50	Pass
HT40	MCS0	1	3	2422	36.76	35.29	0.50	Pass
HT40	MCS0	1	6	2437	36.76	35.29	0.50	Pass
HT40	MCS0	1	9	2452	36.76	35.33	0.50	Pass

TEST RESULTS DATA
Peak Power Table

2.4GHz Band										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
11b	1Mbps	1	1	2412	15.54	30.00	3.75	19.29	36.00	Pass
11b	1Mbps	1	6	2437	15.71	30.00	3.75	19.46	36.00	Pass
11b	1Mbps	1	11	2462	15.83	30.00	3.75	19.58	36.00	Pass
11g	6Mbps	1	1	2412	20.52	30.00	3.75	24.27	36.00	Pass
11g	6Mbps	1	6	2437	20.87	30.00	3.75	24.62	36.00	Pass
11g	6Mbps	1	11	2462	21.28	30.00	3.75	25.03	36.00	Pass
HT20	MCS0	1	1	2412	20.42	30.00	3.75	24.17	36.00	Pass
HT20	MCS0	1	6	2437	20.89	30.00	3.75	24.64	36.00	Pass
HT20	MCS0	1	11	2462	21.15	30.00	3.75	24.90	36.00	Pass
HT40	MCS0	1	3	2422	17.00	30.00	3.75	20.75	36.00	Pass
HT40	MCS0	1	6	2437	17.32	30.00	3.75	21.07	36.00	Pass
HT40	MCS0	1	9	2452	17.41	30.00	3.75	21.16	36.00	Pass

TEST RESULTS DATA
Average Power Table
(Reporting Only)

2.4GHz Band						
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)
11b	1Mbps	1	1	2412	0.00	13.34
11b	1Mbps	1	6	2437	0.00	13.53
11b	1Mbps	1	11	2462	0.00	13.65
11g	6Mbps	1	1	2412	0.11	12.15
11g	6Mbps	1	6	2437	0.11	12.45
11g	6Mbps	1	11	2462	0.11	12.52
HT20	MCS0	1	1	2412	0.12	10.23
HT20	MCS0	1	6	2437	0.12	10.51
HT20	MCS0	1	11	2462	0.12	10.63
HT40	MCS0	1	3	2422	0.21	6.43
HT40	MCS0	1	6	2437	0.21	6.64
HT40	MCS0	1	9	2452	0.21	6.75

TEST RESULTS DATA
Peak Power Density

2.4GHz Band								
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
11b	1Mbps	1	1	2412	-14.26	3.75	8.00	Pass
11b	1Mbps	1	6	2437	-13.73	3.75	8.00	Pass
11b	1Mbps	1	11	2462	-14.51	3.75	8.00	Pass
11g	6Mbps	1	1	2412	-13.56	3.75	8.00	Pass
11g	6Mbps	1	6	2437	-13.35	3.75	8.00	Pass
11g	6Mbps	1	11	2462	-13.47	3.75	8.00	Pass
HT20	MCS0	1	1	2412	-16.41	3.75	8.00	Pass
HT20	MCS0	1	6	2437	-15.84	3.75	8.00	Pass
HT20	MCS0	1	11	2462	-14.70	3.75	8.00	Pass
HT40	MCS0	1	3	2422	-18.61	3.75	8.00	Pass
HT40	MCS0	1	6	2437	-18.89	3.75	8.00	Pass
HT40	MCS0	1	9	2452	-18.38	3.75	8.00	Pass

Appendix B. Radiated Spurious Emission

2.4GHz 2400~2483.5MHz

WIFI 802.11b (Band Edge @ 3m)

WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b CH 01 2412MHz		2387.91	47.5	-26.5	74	46.67	27.23	6.81	33.21	125	302	P	H
		2387.28	40.09	-13.91	54	39.26	27.23	6.81	33.21	125	302	A	H
	*	2412	103.48	-	-	102.58	27.28	6.81	33.19	125	302	P	H
	*	2412	102.61	-	-	101.71	27.28	6.81	33.19	125	302	A	H
		2387.28	46.41	-27.59	74	45.58	27.23	6.81	33.21	366	256	P	V
		2387.28	37.71	-16.29	54	36.88	27.23	6.81	33.21	366	256	A	V
	*	2412	102.7	-	-	101.8	27.28	6.81	33.19	366	256	P	V
	*	2412	100.82	-	-	99.92	27.28	6.81	33.19	366	256	A	V
802.11b CH 06 2437MHz		2390	48.85	-25.15	74	48.02	27.23	6.81	33.21	100	302	P	H
		2389.94	38.79	-15.21	54	37.96	27.23	6.81	33.21	100	302	A	H
	*	2437	103.25	-	-	102.17	27.37	6.86	33.15	100	302	P	H
	*	2437	101.32	-	-	100.24	27.37	6.86	33.15	100	302	A	H
		2485.65	44.7	-29.3	74	43.45	27.46	6.91	33.12	100	302	P	H
		2483.5	34.42	-19.58	54	33.17	27.46	6.91	33.12	100	302	A	H
		2389.8	47.25	-26.75	74	46.42	27.23	6.81	33.21	323	261	P	V
		2389.94	37.13	-16.87	54	36.3	27.23	6.81	33.21	323	261	A	V
	*	2437	102.11	-	-	101.03	27.37	6.86	33.15	323	261	P	V
	*	2437	100.22	-	-	99.14	27.37	6.86	33.15	323	261	A	V
		2497.62	43.24	-30.76	74	41.93	27.5	6.91	33.1	323	261	P	V
		2484.81	33.06	-20.94	54	31.81	27.46	6.91	33.12	323	261	A	V

802.11b CH 11 2462MHz	*	2462	100.16	-	-	99.03	27.41	6.86	33.14	108	333	P	H
	*	2462	98.27	-	-	97.14	27.41	6.86	33.14	108	333	A	H
		2484.28	43.62	-30.38	74	42.37	27.46	6.91	33.12	108	333	P	H
		2485.32	33.72	-20.28	54	32.47	27.46	6.91	33.12	108	333	A	H
	*	2462	102.78	-	-	101.65	27.41	6.86	33.14	361	248	P	V
	*	2462	100.67	-	-	99.54	27.41	6.86	33.14	361	248	A	V
		2489.72	46.26	-27.74	74	44.95	27.5	6.91	33.1	361	248	P	V
		2483.52	35.2	-18.8	54	33.95	27.46	6.91	33.12	361	248	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

2.4GHz 2400~2483.5MHz

WIFI 802.11b (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11b CH 01 2412MHz		4824	45.96	-28.04	74	59.94	31.73	10.89	56.6	185	255	P	H
		4824	45.5	-28.5	74	59.48	31.73	10.89	56.6	185	255	P	V
802.11b CH 06 2437MHz		4874	44.55	-29.45	74	58.76	31.78	10.92	56.91	165	106	P	H
		7311	50.82	-23.18	74	59.87	35.66	13.29	58	174	100	P	H
		4874	44	-30	74	58.21	31.78	10.92	56.91	165	106	P	V
		7311	49.16	-24.84	74	58.21	35.66	13.29	58	174	100	P	V
802.11b CH 11 2462MHz		4924	46.31	-27.69	74	59.57	31.83	10.99	56.08	150	285	P	H
		7386	48.74	-25.26	74	57.82	35.81	13.12	58.01	155	274	P	H
		4924	44.82	-29.18	74	58.08	31.83	10.99	56.08	150	285	P	V
		7386	48.94	-25.06	74	58.02	35.81	13.12	58.01	155	274	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

2.4GHz 2400~2483.5MHz

WIFI 802.11g (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11g CH 01 2412MHz		2389.905	65.08	-8.92	74	64.25	27.23	6.81	33.21	161	300	P	H
		2390	52.07	-1.93	54	51.24	27.23	6.81	33.21	161	300	A	H
	*	2412	103.59	-	-	102.69	27.28	6.81	33.19	161	300	P	H
	*	2412	97.54	-	-	96.64	27.28	6.81	33.19	161	300	A	H
		2389.8	60.9	-13.1	74	60.07	27.23	6.81	33.21	337	247	P	V
		2390	49.42	-4.58	54	48.59	27.23	6.81	33.21	337	247	A	V
	*	2412	102.57	-	-	101.67	27.28	6.81	33.19	337	247	P	V
	*	2412	96.07	-	-	95.17	27.28	6.81	33.19	337	247	A	V
802.11g CH 06 2437MHz		2387.14	53.79	-20.21	74	52.96	27.23	6.81	33.21	100	289	P	H
		2388.82	44.79	-9.21	54	43.96	27.23	6.81	33.21	100	289	A	H
	*	2437	105.2	-	-	104.12	27.37	6.86	33.15	100	289	P	H
	*	2437	98.83	-	-	97.75	27.37	6.86	33.15	100	289	A	H
		2494.4	49.57	-24.43	74	48.26	27.5	6.91	33.1	100	289	P	H
		2483.62	39.74	-14.26	54	38.49	27.46	6.91	33.12	100	289	A	H
		2387.42	53.77	-20.23	74	52.94	27.23	6.81	33.21	100	290	P	V
		2388.96	44.82	-9.18	54	43.99	27.23	6.81	33.21	100	290	A	V
	*	2437	105.16	-	-	104.08	27.37	6.86	33.15	100	290	P	V
	*	2437	98.85	-	-	97.77	27.37	6.86	33.15	100	290	A	V
		2483.97	48.84	-25.16	74	47.59	27.46	6.91	33.12	100	290	P	V
		2499.72	39.72	-14.28	54	38.41	27.5	6.91	33.1	100	290	A	V

802.11g CH 11 2462MHz	*	2462	104.25	-	-	103.12	27.41	6.86	33.14	100	174	P	H
	*	2462	97.64	-	-	96.51	27.41	6.86	33.14	100	174	A	H
		2483.96	58.6	-15.4	74	57.35	27.46	6.91	33.12	100	174	P	H
		2483.52	46.39	-7.61	54	45.14	27.46	6.91	33.12	100	174	A	H
	*	2462	102.2	-	-	101.07	27.41	6.86	33.14	358	237	P	V
	*	2462	95.15	-	-	94.02	27.41	6.86	33.14	358	237	A	V
		2484	54.85	-19.15	74	53.6	27.46	6.91	33.12	358	237	P	V
		2483.56	43.56	-10.44	54	42.31	27.46	6.91	33.12	358	237	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

2.4GHz 2400~2483.5MHz

WIFI 802.11g (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11g CH 01 2412MHz		4824	44.8	-29.2	74	58.78	31.73	10.89	56.6	185	255	P	H
		4824	44.47	-29.53	74	58.45	31.73	10.89	56.6	185	255	P	V
802.11g CH 06 2437MHz		4874	44.96	-29.04	74	59.17	31.78	10.92	56.91	165	106	P	H
		7311	49.39	-24.61	74	58.44	35.66	13.29	58	174	100	P	H
		4874	43.83	-30.17	74	58.04	31.78	10.92	56.91	165	106	P	V
		7311	49.69	-24.31	74	58.74	35.66	13.29	58	174	100	P	V
802.11g CH 11 2462MHz		4924	44.26	-29.74	74	57.52	31.83	10.99	56.08	150	285	P	H
		7386	49.51	-24.49	74	58.59	35.81	13.12	58.01	155	274	P	H
		4924	46.22	-27.78	74	59.48	31.83	10.99	56.08	150	285	P	V
		7386	48.32	-25.68	74	57.4	35.81	13.12	58.01	155	274	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

2.4GHz 2400~2483.5MHz

WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 01 2412MHz		2389.59	65.88	-8.12	74	65.05	27.23	6.81	33.21	195	301	P	H
		2390	51.39	-2.61	54	50.56	27.23	6.81	33.21	195	301	A	H
	*	2412	101.17	-	-	100.27	27.28	6.81	33.19	195	301	P	H
	*	2412	95.1	-	-	94.2	27.28	6.81	33.19	195	301	A	H
		2389.905	64.62	-9.38	74	63.79	27.23	6.81	33.21	336	245	P	V
		2389.905	48.46	-5.54	54	47.63	27.23	6.81	33.21	336	245	A	V
		2412	100.23	-	-	99.33	27.28	6.81	33.19	336	245	P	V
	*	2412	93.85	-	-	92.95	27.28	6.81	33.19	336	245	A	V
802.11n HT20 CH 06 2437MHz		2389.24	49.2	-24.8	74	48.37	27.23	6.81	33.21	163	294	P	H
		2382.66	39.48	-14.52	54	38.79	27.19	6.73	33.23	163	294	A	H
	*	2437	101.9	-	-	100.82	27.37	6.86	33.15	163	294	P	H
	*	2437	95.71	-	-	94.63	27.37	6.86	33.15	163	294	A	H
		2490.27	44.22	-29.78	74	42.91	27.5	6.91	33.1	163	294	P	H
		2483.69	35.19	-18.81	54	33.94	27.46	6.91	33.12	163	294	A	H
		2388.82	47.05	-26.95	74	46.22	27.23	6.81	33.21	331	246	P	V
		2388.68	38.16	-15.84	54	37.33	27.23	6.81	33.21	331	246	A	V
	*	2437	100.65	-	-	99.57	27.37	6.86	33.15	331	246	P	V
	*	2437	94.34	-	-	93.26	27.37	6.86	33.15	331	246	A	V
		2490.62	42.93	-31.07	74	41.62	27.5	6.91	33.1	331	246	P	V
		2484.25	33.69	-20.31	54	32.44	27.46	6.91	33.12	331	246	A	V

802.11n HT20 CH 11 2462MHz	*	2462	103.23	-	-	102.1	27.41	6.86	33.14	158	301	P	H
	*	2462	96.65	-	-	95.52	27.41	6.86	33.14	158	301	A	H
		2483.64	60.09	-13.91	74	58.84	27.46	6.91	33.12	158	301	P	H
		2483.52	46.39	-7.61	54	45.14	27.46	6.91	33.12	158	301	A	H
	*	2462	101.42	-	-	100.29	27.41	6.86	33.14	359	248	P	V
	*	2462	94.81	-	-	93.68	27.41	6.86	33.14	359	248	A	V
		2483.52	57	-17	74	55.75	27.46	6.91	33.12	359	248	P	V
		2483.52	43.94	-10.06	54	42.69	27.46	6.91	33.12	359	248	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

2.4GHz 2400~2483.5MHz

WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 01 2412MHz		4824	45.15	-28.85	74	59.13	31.73	10.89	56.6	185	255	P	H
		4824	45.05	-28.95	74	59.03	31.73	10.89	56.6	185	255	P	V
802.11n HT20 CH 06 2437MHz		4874	44.4	-29.6	74	58.61	31.78	10.92	56.91	165	230	P	H
		7311	49.56	-24.44	74	58.61	35.66	13.29	58	186	323	P	H
		4874	43.26	-30.74	74	57.47	31.78	10.92	56.91	165	230	P	V
		7311	49	-25	74	58.05	35.66	13.29	58	186	323	P	V
802.11n HT20 CH 11 2462MHz		4924	44.87	-29.13	74	58.13	31.83	10.99	56.08	150	285	P	H
		7386	48.06	-25.94	74	57.14	35.81	13.12	58.01	155	274	P	H
		4924	45.01	-28.99	74	58.27	31.83	10.99	56.08	150	285	P	V
		7386	49.71	-24.29	74	58.79	35.81	13.12	58.01	155	274	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

2.4GHz 2400~2483.5MHz

WIFI 802.11n HT40 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 03 2422MHz		2389.66	65.73	-8.27	74	64.9	27.23	6.81	33.21	205	116	P	H
		2389.52	52.06	-1.94	54	51.23	27.23	6.81	33.21	205	116	A	H
		2422	96.8	-	-	95.84	27.32	6.81	33.17	205	116	P	H
	*	2422	90.89	-	-	89.93	27.32	6.81	33.17	205	116	A	H
		2499.86	42.97	-31.03	74	41.66	27.5	6.91	33.1	205	116	P	H
		2484.67	34.81	-19.19	54	33.56	27.46	6.91	33.12	205	116	A	H
		2389.94	66.11	-7.89	74	65.28	27.23	6.81	33.21	358	83	P	V
		2389.38	51.53	-2.47	54	50.7	27.23	6.81	33.21	358	83	A	V
	*	2422	96.2	-	-	95.24	27.32	6.81	33.17	358	83	P	V
	*	2422	89.76	-	-	88.8	27.32	6.81	33.17	358	83	A	V
		2486.91	43.22	-30.78	74	41.97	27.46	6.91	33.12	358	83	P	V
		2484.32	34.6	-19.4	54	33.35	27.46	6.91	33.12	358	83	A	V
802.11n HT40 CH 06 2437MHz		2388.26	50.75	-23.25	74	49.92	27.23	6.81	33.21	109	294	P	H
		2389.8	40.25	-13.75	54	39.42	27.23	6.81	33.21	109	294	A	H
	*	2437	97.38	-	-	96.3	27.37	6.86	33.15	109	294	P	H
	*	2437	90.48	-	-	89.4	27.37	6.86	33.15	109	294	A	H
		2485.16	45.12	-28.88	74	43.87	27.46	6.91	33.12	109	294	P	H
		2483.69	35.7	-18.3	54	34.45	27.46	6.91	33.12	109	294	A	H
		2389.24	51.84	-22.16	74	51.01	27.23	6.81	33.21	347	256	P	V
		2388.82	39.13	-14.87	54	38.3	27.23	6.81	33.21	347	256	A	V
	*	2437	96.32	-	-	95.24	27.37	6.86	33.15	347	256	P	V
	*	2437	89.8	-	-	88.72	27.37	6.86	33.15	347	256	A	V
		2483.69	45.29	-28.71	74	44.04	27.46	6.91	33.12	347	256	P	V
		2483.5	35.03	-18.97	54	33.78	27.46	6.91	33.12	347	256	A	V

802.11n HT40 CH 09 2452MHz		2388.54	49.98	-24.02	74	49.15	27.23	6.81	33.21	126	303	P	H
		2389.52	40.77	-13.23	54	39.94	27.23	6.81	33.21	126	303	A	H
	*	2452	96.44	-	-	95.36	27.37	6.86	33.15	126	303	P	H
	*	2452	90.28	-	-	89.2	27.37	6.86	33.15	126	303	A	H
		2484.39	57.34	-16.66	74	56.09	27.46	6.91	33.12	126	303	P	H
		2484.39	42.85	-11.15	54	41.6	27.46	6.91	33.12	126	303	A	H
		2381.54	48.25	-25.75	74	47.56	27.19	6.73	33.23	347	252	P	V
		2388.54	38.68	-15.32	54	37.85	27.23	6.81	33.21	347	252	A	V
	*	2452	96.09	-	-	95.01	27.37	6.86	33.15	347	252	P	V
	*	2452	89.82	-	-	88.74	27.37	6.86	33.15	347	252	A	V
		2483.83	55.12	-18.88	74	53.87	27.46	6.91	33.12	347	252	P	V
		2484.39	42.67	-11.33	54	41.42	27.46	6.91	33.12	347	252	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

2.4GHz 2400~2483.5MHz

WIFI 802.11n HT40 (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n		4844	44.53	-29.47	74	58.45	31.74	10.92	56.58	150	350	P	H
HT40		7266	49.04	-24.96	74	58.33	35.6	13.38	58.27	200	360	P	H
CH 03		4844	44.62	-29.38	74	58.54	31.74	10.92	56.58	150	350	P	V
2422MHz		7266	48.81	-25.19	74	58.1	35.6	13.38	58.27	200	360	P	V
802.11n		4874	43.52	-30.48	74	57.73	31.78	10.92	56.91	165	106	P	H
HT40		7311	49.56	-24.44	74	58.61	35.66	13.29	58	174	100	P	H
CH 06		4874	43.09	-30.91	74	57.3	31.78	10.92	56.91	165	106	P	V
2437MHz		7311	49	-25	74	58.05	35.66	13.29	58	174	100	P	V
802.11n		4904	44.85	-29.15	74	58.44	31.81	10.95	56.35	150	360	P	H
HT40		7356	49.26	-24.74	74	58.26	35.75	13.21	57.96	165	335	P	H
CH 09		4904	45.74	-28.26	74	59.33	31.81	10.95	56.35	150	360	P	V
2452MHz		7356	49.67	-24.33	74	58.67	35.75	13.21	57.96	165	335	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Emission below 1GHz

2.4GHz WIFI 802.11g (LF)

WIFI Ant.	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
1													
2.4GHz 802.11g LF		33.88	24.56	-15.44	40	30.95	24.96	0.3	31.65	-	-	P	H
		108.57	17.37	-26.13	43.5	30.69	17.33	0.93	31.58	-	-	P	H
		157.07	17.55	-25.95	43.5	30.85	16.7	1.36	31.36	-	-	P	H
		264.74	31.16	-14.84	46	42.77	17.64	1.91	31.16	100	205	P	H
		529.55	28.08	-17.92	46	32.92	23.77	2.79	31.4	-	-	P	H
		998.06	31.61	-22.39	54	29.93	28.98	4.2	31.5	-	-	P	H
		32.91	24.87	-15.13	40	31.12	25.12	0.28	31.65	100	153	P	V
		118.27	17.13	-26.37	43.5	30.42	17.21	1.02	31.52	-	-	P	V
		208.48	17.91	-25.59	43.5	31.1	16.33	1.66	31.18	-	-	P	V
		264.74	26.95	-19.05	46	38.56	17.64	1.91	31.16	-	-	P	V
		529.55	28.19	-17.81	46	33.03	23.77	2.79	31.4	-	-	P	V
		988.36	32.15	-21.85	54	30.59	28.91	4.15	31.5	-	-	P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												

Note symbol

*	**Fundamental Frequency** which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is **over limit** line.
P/A	**P**eak or **A**verage
H/V	**H**orizontal or **V**ertical

A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b CH 01 2412MHz		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)

= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is "PASS".

Appendix C. Duty Cycle Plots

Band	Duty Cycle(%)	T(ms)	1/T(KHz)	VBW Setting
802.11b	100	-	-	10Hz
802.11g	97.46	1.391	0.719	1KHz
802.11n HT20	97.28	1.297	0.771	1KHz
802.11n HT40	95.32	0.649	1.540	3KHz

802.11b



802.11g



802.11n HT20



802.11n HT40


Spectrum
Ref Level 30.00 dBm Offset 16.30 dB RBW 10 MHz
Att 30 dB SWT 3 ms VBW 10 MHz
SGL
1Pk Max
D3[1]
-0.02 dB
681.16 µs
9.24 dBm
M1[1]
M1
D2
D3
20 dBm
10 dBm
0 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
CF 2.422 GHz
691 pts
300.0 µs/
Marker
Type Ref Trc X-value Y-value Function Function Result
M1 1 339.13 µs 9.24 dBm
D2 M1 1 649.28 µs 3.43 dB
D3 M1 1 681.16 µs -0.02 dB