


FCC SAR Test Report

APPLICANT : Acer Incorporated
EQUIPMENT : Smart HandHeld
BRAND NAME : Acer
MODEL NAME : Z220AWS, M220AWS
MARKETING NAME : Liquid Z220, Liquid M220
FCC ID : HLZDMZ220AWS
STANDARD : FCC 47 CFR Part 2 (2.1093)
ANSI/IEEE C95.1-1992
IEEE 1528-2003

We, SPORTON INTERNATIONAL (XI'AN) INC., would like to declare that the tested sample has been evaluated in accordance with the procedures and had been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (XI'AN) INC., the test report shall not be reproduced except in full.



Reviewed by: Eric Huang / Deputy Manager



Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL (XI'AN) INC.

1F, Building A3, No. 39 Chuangye Rd., Xi'an Hi-tech Zone, Shanxi Province, P. R. C.



Table of Contents

1. Statement of Compliance	4
2. Administration Data	5
3. Guidance Standard	5
4. Equipment Under Test (EUT)	6
4.1 General Information	6
4.2 Maximum Tune-up Limit	7
5. RF Exposure Limits	8
5.1 Uncontrolled Environment	8
5.2 Controlled Environment	8
6. Specific Absorption Rate (SAR)	9
6.1 Introduction	9
6.2 SAR Definition	9
7. System Description and Setup	10
8. Measurement Procedures	11
8.1 Spatial Peak SAR Evaluation	11
8.2 Power Reference Measurement	12
8.3 Area Scan	12
8.4 Zoom Scan	13
8.5 Volume Scan Procedures	13
8.6 Power Drift Monitoring	13
9. Test Equipment List	14
10. System Verification	15
10.1 Tissue Verification	15
10.2 System Performance Check Results	16
11. RF Exposure Positions	17
11.1 Ear and handset reference point	17
11.2 Definition of the cheek position	18
11.3 Definition of the tilt position	19
11.4 Body Worn Accessory	20
11.5 Wireless Router	20
12. Conducted RF Output Power (Unit: dBm)	21
13. Antenna Location	28
14. SAR Test Results	29
14.1 Head SAR	30
14.2 Hotspot SAR	32
14.3 Body Worn Accessory SAR	34
14.4 Repeated SAR Measurement	35
15. Simultaneous Transmission Analysis	36
15.1 Head Exposure Conditions	37
15.2 Hotspot Exposure Conditions	38
15.3 Body-Worn Accessory Exposure Conditions	40
16. Uncertainty Assessment	41
17. References	43
Appendix A. Plots of System Performance Check	
Appendix B. Plots of High SAR Measurement	
Appendix C. DASY Calibration Certificate	
Appendix D. Test Setup Photos	

Revision History

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FA510940-02	Rev. 01	Initial issue of report	May 15, 2015

1. Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) found during testing for **Acer Incorporated, Smart HandHeld, Z220AWS, M220AWS** are as follows.

Equipment Class	Frequency Band	Highest SAR Summary			
		Head (Separation 0mm) 1g SAR (W/kg)	Body-worn (Separation 10mm) 1g SAR (W/kg)	Wireless Router (Separation 10mm) 1g SAR (W/kg)	Highest Simultaneous Transmission 1g SAR (W/kg)
PCE	GSM850	0.71	1.19	1.19	1.23
	GSM1900	0.59	1.11	1.11	
	WCDMA Band V	0.61	1.19	1.19	
	WCDMA Band IV	0.79	1.20	1.20	
DTS	WLAN 2.4GHz Band	0.20	<0.10	<0.10	1.23
DSS	Bluetooth	<0.10	<0.10	<0.10	1.22
Date of Testing:		May 04 2015 ~ May 07, 2015			

This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2003.

2. Administration Data

Testing Laboratory	
Test Site	SPORTON INTERNATIONAL (XI'AN) INC.
Test Site Location	1F, Building A3, No. 39 Chuangye Rd., Xi'an Hi-tech Zone, Shanxi Province, P. R. C. TEL: +86-029-8860-8767 FAX: +86-029-8860-8791
Applicant	
Company Name	Acer Incorporated
Address	8F., No. 88, Sec. 1, Xintai 5th Rd., Xizhi Dist., New Taipei City 22181, Taiwan (R.O.C)
Manufacturer	
Company Name	Shanghai Wingtech Electronic Technology Co., Ltd.
Address	6th Floor, G Block, No. 668, East Beijing Road, HuangPu District, Shanghai, P. R. China

3. Guidance Standard

The Specific Absorption Rate (SAR) testing specification, method, and procedure for this device is in accordance with the following standards:

- FCC 47 CFR Part 2 (2.1093)
- ANSI/IEEE C95.1-1992
- IEEE 1528-2003
- FCC KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r03
- FCC KDB 865664 D02 SAR Reporting v01r01
- FCC KDB 447498 D01 General RF Exposure Guidance v05r02
- FCC KDB 648474 D04 SAR Evaluation Considerations for Wireless Handsets v01r02
- FCC KDB 248227 D01 SAR meas for 802 11abg v01r02
- FCC KDB 941225 D01 3G SAR Procedures v03
- FCC KDB 941225 D06 Hotspot Mode SAR v02

4. Equipment Under Test (EUT)

4.1 General Information

Product Feature & Specification	
Equipment Name	Smart HandHeld
Brand Name	Acer
Model Name	Z220AWS, M220AWS
Marketing Name	Liquid Z220, Liquid M220
FCC ID	HLZDMZ220AWS
IMEI Code	SIM1: 358744060001097 SIM2: 358744060001089
Wireless Technology and Frequency Range	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8 MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz WCDMA Band IV: 1712.4 MHz ~ 1752.6 MHz WLAN 2.4GHz Band: 2412 MHz ~ 2462 MHz Bluetooth: 2402 MHz ~ 2480 MHz
Mode	•GSM/GPRS/EGPRS •RMC/AMR 12.2Kbps •HSDPA •HSUPA •HSPA+ (Downlink Only) •802.11b/g/n HT20 •Bluetooth v3.0 + EDR, Bluetooth v4.0 LE
GSM / (E)GPRS Transfer mode	Class B – EUT cannot support Packet Switched and Circuit Switched Network simultaneously but can automatically switch between Packet and Circuit Switched Network.
EUT Stage	Identical Prototype
Remark: 1. This device 2.4GHz WLAN supports hotspot operation and 802.11n-HT40 is not supported in 2.4GHz WLAN. 2. This device supported VoIP in GPRS, EGPRS and WCDMA (e.g. 3rd party VoIP). 3. This device supports GRPS / EGPRS mode up to multi-slot class 33 and does not support DTM function. 4. There are two SIM cards for EUT. SIM card 1 supports GSM and WCDMA functions, and SIM card 2 only supports GSM function. EUT supports dual SIM dual standby. The WWAN radio transmission will be enabled by either one SIM at a time (single active). 5. The difference between Z220AWS and M220AWS is only with different operating system. Z220AWS with Android 5.0 Lollipop and M220AWS with Windows 8.1 (Blue GDR1), since the test result is not affected by the operating system difference, so only choose M220AWS to perform all tests.	

4.2 Maximum Tune-up Limit

Mode	Burst Average Power (dBm)	
	GSM850	GSM1900
GSM (GMSK, 1 Tx slot)	33.50	30.50
GPRS (GMSK, 1 Tx slot)	33.50	30.50
GPRS (GMSK, 2 Tx slots)	30.50	29.00
GPRS (GMSK, 3 Tx slots)	28.50	26.50
GPRS (GMSK, 4 Tx slots)	27.00	24.50
EDGE (8PSK, 1 Tx slot)	27.00	25.50
EDGE (8PSK, 2 Tx slots)	25.50	24.50
EDGE (8PSK, 3 Tx slots)	24.50	23.50
EDGE (8PSK, 4 Tx slots)	23.50	22.50

Mode	Average Power (dBm)	
	WCDMA Band V	WCDMA Band IV
AMR 12.2Kbps	23.5	23.0
RMC 12.2Kbps	23.5	23.0
HSDPA Subtest-1	22.0	22.0
HSDPA Subtest-2	22.0	22.0
HSDPA Subtest-3	21.5	22.0
HSDPA Subtest-4	21.5	22.0
HSUPA Subtest-1	22.0	22.0
HSUPA Subtest-2	21.0	21.0
HSUPA Subtest-3	21.0	20.5
HSUPA Subtest-4	21.5	21.5
HSUPA Subtest-5	21.5	21.5

Mode		Average Power (dBm)
2.4GHz	802.11b	14.0
	802.11g	12.5
	802.11n HT20	11.5
Bluetooth v3.0+EDR		9.0
Bluetooth v4.0 LE		1.0

5. RF Exposure Limits

5.1 Uncontrolled Environment

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

5.2 Controlled Environment

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. The exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

Whole-Body SAR is averaged over the entire body, partial-body SAR is averaged over any 1gram of tissue defined as a tissue volume in the shape of a cube. SAR for hands, wrists, feet and ankles is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

6. Specific Absorption Rate (SAR)

6.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

6.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$


SAR is expressed in units of Watts per kilogram (W/kg)

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

7. System Description and Setup

The DASY system used for performing compliance tests consists of the following items:



- A standard high precision 6-axis robot with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic Field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running WinXP or Win7 and the DASY5 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

8. Measurement Procedures

The measurement procedures are as follows:

<Conducted power measurement>

- (a) For WWAN power measurement, use base station simulator to configure EUT WWAN transmission in conducted connection with RF cable, at maximum power in each supported wireless interface and frequency band.
- (b) Read the WWAN RF power level from the base station simulator.
- (c) For WLAN/BT power measurement, use engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power in each supported wireless interface and frequency band
- (d) Connect EUT RF port through RF cable to the power meter, and measure WLAN/BT output power

<SAR measurement>

- (a) Use base station simulator to configure EUT WWAN transmission in radiated connection, and engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power, in the highest power channel.
- (b) Place the EUT in the positions as Appendix D demonstrates.
- (c) Set scan area, grid size and other setting on the DASY software.
- (d) Measure SAR results for the highest power channel on each testing position.
- (e) Find out the largest SAR result on these testing positions of each band
- (f) Measure SAR results for other channels in worst SAR testing position if the reported SAR of highest power channel is larger than 0.8 W/kg

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

8.1 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

8.2 Power Reference Measurement

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

8.3 Area Scan

The area scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASY software can find the maximum found in the scanned area, within a range of the global maximum. The range (in dB0) is specified in the standards for compliance testing. For example, a 2 dB range is required in IEEE standard 1528 and IEC 62209 standards, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan), if only one zoom scan follows the area scan, then only the absolute maximum will be taken as reference. For cases where multiple maximums are detected, the number of zoom scans has to be increased accordingly.

Area scan parameters extracted from FCC KDB 865664 D01v01r03 SAR measurement 100 MHz to 6 GHz.

	≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location	$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
Maximum area scan spatial resolution: Δx_{Area} , Δy_{Area}	≤ 2 GHz: ≤ 15 mm $2 - 3$ GHz: ≤ 12 mm	$3 - 4$ GHz: ≤ 12 mm $4 - 6$ GHz: ≤ 10 mm
	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	

8.4 Zoom Scan

Zoom scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 gram and 10 gram of simulated tissue. The zoom scan measures points (refer to table below) within a cube whose base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the zoom scan evaluates the averaged SAR for 1 gram and 10 gram and displays these values next to the job's label.

Zoom scan parameters extracted from FCC KDB 865664 D01v01r03 SAR measurement 100 MHz to 6 GHz.

			≤ 3 GHz	> 3 GHz
Maximum zoom scan spatial resolution: $\Delta x_{\text{Zoom}}, \Delta y_{\text{Zoom}}$			≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm*	3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{\text{Zoom}}(n)$		≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm
	graded grid	$\Delta z_{\text{Zoom}}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		$\Delta z_{\text{Zoom}}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{\text{Zoom}}(n-1)$	
Minimum zoom scan volume	x, y, z		≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm
Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.				
* When zoom scan is required and the <i>reported</i> SAR from the <i>area scan based 1-g SAR estimation</i> procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.				

8.5 Volume Scan Procedures

The volume scan is used to assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

8.6 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASy measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drifts more than 5%, the SAR will be retested.

9. Test Equipment List

Manufacturer	Name of Equipment	Type/Model	Serial Number	Calibration	
				Last Cal.	Due Date
SPEAG	835MHz System Validation Kit	D835V2	4d091	Nov. 21, 2014	Nov. 20, 2015
SPEAG	1750MHz System Validation Kit	D1750V2	1069	Nov. 21, 2014	Nov. 20, 2015
SPEAG	1900MHz System Validation Kit	D1900V2	5d118	Nov. 21, 2014	Nov. 20, 2015
SPEAG	2450MHz System Validation Kit	D2450V2	840	Nov. 19, 2014	Nov. 18, 2015
SPEAG	Data Acquisition Electronics	DAE4	918	Dec. 29, 2014	Dec. 28, 2015
SPEAG	Data Acquisition Electronics	DAE4	1210	May 19, 2014	May 18, 2015
SPEAG	Dosimetric E-Field Probe	EX3DV4	3857	May 23, 2014	May 22, 2015
SPEAG	Dosimetric E-Field Probe	EX3DV4	3911	Oct. 02, 2014	Oct. 01, 2015
SPEAG	SAM Twin Phantom	QD 000 P40 CD	TP-1753	NCR	NCR
SPEAG	SAM Twin Phantom	QD 000 P40 CD	TP-1754	NCR	NCR
SPEAG	SAM Twin Phantom	QD 000 P40 CB	TP-1479	NCR	NCR
SPEAG	Phone Positioner	N/A	N/A	NCR	NCR
Agilent	Wireless Communication Test Set	E5515C	MY52102600	Dec. 09, 2014	Dec. 08, 2015
Agilent	ENA Series Network Analyzer	E5071C	MY46317418	Dec. 09, 2014	Dec. 08, 2015
R&S	CBT BLUETOOTH TESTER	CBT	100783	Aug. 11, 2014	Aug. 10, 2015
Agilent	Dielectric Probe Kit	85070E	MY44300751	NCR	NCR
Anritsu	Power Sensor	MA2411B	0917070	Jan. 23, 2015	Jan. 22, 2016
Anritsu	Power Meter	ML2495A	1218010	Jan. 23, 2015	Jan. 22, 2016
R&S	Spectrum Analyzer	FSP7	101045	Dec. 09, 2014	Dec. 08, 2015
Agilent	Dual Directional Coupler	778D	50422	Note1	
Woken	Attenuator 1	WK0602-XX	N/A	Note1	
PE	Attenuator 2	PE7005-10	N/A	Note1	
PE	Attenuator 3	PE7005- 3	N/A	Note1	
AR	Power Amplifier	5S1G4M2	0328767	Note1	
Mini-Circuits	Power Amplifier	ZVE-3W	162601250	Note1	
Mini-Circuits	Power Amplifier	ZHL-42W+	13440021344	Note1	

General Note:

Prior to system verification and validation, the path loss from the signal generator to the system check source and the power meter, which includes the amplifier, cable, attenuator and directional coupler, was measured by the network analyzer. The reading of the power meter was offset by the path loss difference between the path to the power meter and the path to the system check source to monitor the actual power level fed to the system check source.

10. System Verification

10.1 Tissue Verification

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation.

Frequency (MHz)	Water (%)	Sugar (%)	Cellulose (%)	Salt (%)	Preventol (%)	DGBE (%)	Conductivity (σ)	Permittivity (ϵ_r)
For Head								
835	40.3	57.9	0.2	1.4	0.2	0	0.90	41.5
1800, 1900, 2000	55.2	0	0	0.3	0	44.5	1.40	40.0
2450	55.0	0	0	0	0	45.0	1.80	39.2
For Body								
835	50.8	48.2	0	0.9	0.1	0	0.97	55.2
1800, 1900, 2000	70.2	0	0	0.4	0	29.4	1.52	53.3
2450	68.6	0	0	0	0	31.4	1.95	52.7

<Tissue Dielectric Parameter Check Results>

Frequency (MHz)	Tissue Type	Liquid Temp. (°C)	Conductivity (σ)	Permittivity (ϵ_r)	Conductivity Target (σ)	Permittivity Target (ϵ_r)	Delta (σ) (%)	Delta (ϵ_r) (%)	Limit (%)	Date
835	Head	22.4	0.900	42.153	0.90	41.50	0.00	1.57	±5	May 06, 2015
1750	Head	22.5	1.346	40.221	1.37	40.10	-1.75	0.30	±5	May 06, 2015
1900	Head	22.5	1.456	40.840	1.40	40.00	4.00	2.10	±5	May 06, 2015
2450	Head	22.4	1.882	37.652	1.80	39.20	4.56	-3.95	±5	May 07, 2015
2450	Head	22.7	1.820	39.202	1.80	39.20	1.11	0.01	±5	May 07, 2015
835	Body	22.3	0.978	54.413	0.97	55.20	0.82	-1.43	±5	May 05, 2015
1750	Body	22.6	1.498	53.247	1.49	53.40	0.54	-0.29	±5	May 04, 2015
1900	Body	22.5	1.528	55.266	1.52	53.30	0.53	3.69	±5	May 05, 2015
2450	Body	22.5	1.997	51.227	1.95	52.70	2.41	-2.80	±5	May 07, 2015
2450	Body	22.6	1.943	50.960	1.95	52.70	-0.36	-3.30	±5	May 07, 2015

10.2 System Performance Check Results

Comparing to the original SAR value provided by SPEAG, the verification data should be within its specification of 10 %. Below table shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance check can meet the variation criterion and the plots can be referred to Appendix A of this report.

Date	Frequency (MHz)	Tissue Type	Input Power (mW)	Dipole S/N	Probe S/N	DAE S/N	Measured SAR (W/kg)	Targeted SAR (W/kg)	Normalized SAR (W/kg)	Deviation (%)
May 06, 2015	835	Head	250	4d091	3911	918	2.31	9.11	9.24	1.43
May 06, 2015	1750	Head	250	1069	3911	918	9.19	37.10	36.76	-0.92
May 06, 2015	1900	Head	250	5d118	3911	918	10.60	40.10	42.4	5.74
May 07, 2015	2450	Head	250	840	3911	918	14.20	52.30	56.8	8.60
May 07, 2015	2450	Head	250	840	3857	1210	12.90	52.30	51.6	-1.34
May 05, 2015	835	Body	250	4d091	3911	918	2.45	9.60	9.8	2.08
May 04, 2015	1750	Body	250	1069	3911	918	9.51	38.10	38.04	-0.16
May 05, 2015	1900	Body	250	5d118	3911	918	10.10	40.00	40.4	1.00
May 07, 2015	2450	Body	250	840	3911	918	13.80	51.00	55.2	8.24
May 07, 2015	2450	Body	250	840	3857	1210	12.30	51.00	49.2	-3.53




Fig 8.3.1 System Performance Check Setup



Fig 8.3.2 Setup Photo

11. RF Exposure Positions

11.1 Ear and handset reference point

Figure 9.1.1 shows the front, back, and side views of the SAM phantom. The center-of-mouth reference point is labeled "M," the left ear reference point (ERP) is marked "LE," and the right ERP is marked "RE." Each ERP is 15 mm along the B-M (back-mouth) line behind the entrance-to-ear-canal (EEC) point, as shown in Figure 9.1.2 The Reference Plane is defined as passing through the two ear reference points and point M. The line N-F (neck-front), also called the reference pivoting line, is normal to the Reference Plane and perpendicular to both a line passing through RE and LE and the B-M line (see Figure 9.1.3). Both N-F and B-M lines should be marked on the exterior of the phantom shell to facilitate handset positioning. Posterior to the N-F line the ear shape is a flat surface with 6 mm thickness at each ERP, and forward of the N-F line the ear is truncated, as illustrated in Figure 9.1.2. The ear truncation is introduced to preclude the ear lobe from interfering with handset tilt, which could lead to unstable positioning at the cheek.




Fig 9.1.1 Front, back, and side views of SAM twin phantom




Fig 9.1.2 Close-up side view of phantom showing the ear region.




Fig 9.1.3 Side view of the phantom showing relevant markings and seven cross-sectional plane locations

11.2 Definition of the cheek position

1. Ready the handset for talk operation, if necessary. For example, for handsets with a cover piece (flip cover), open the cover. If the handset can transmit with the cover closed, both configurations must be tested.
2. Define two imaginary lines on the handset—the vertical centerline and the horizontal line. The vertical centerline passes through two points on the front side of the handset—the midpoint of the width w_t of the handset at the level of the acoustic output (point A in Figure 9.2.1 and Figure 9.2.2), and the midpoint of the width w_b of the bottom of the handset (point B). The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output (see Figure 9.2.1). The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset (see Figure 9.2.2), especially for clamshell handsets, handsets with flip covers, and other irregularly-shaped handsets.
3. Position the handset close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 9.2.3), such that the plane defined by the vertical centerline and the horizontal line of the handset is approximately parallel to the sagittal plane of the phantom.
4. Translate the handset towards the phantom along the line passing through RE and LE until handset point A touches the pinna at the ERP.
5. While maintaining the handset in this plane, rotate it around the LE-RE line until the vertical centerline is in the plane normal to the plane containing B-M and N-F lines, i.e., the Reference Plane.
6. Rotate the handset around the vertical centerline until the handset (horizontal line) is parallel to the N-F line.
7. While maintaining the vertical centerline in the Reference Plane, keeping point A on the line passing through RE and LE, and maintaining the handset contact with the pinna, rotate the handset about the N-F line until any point on the handset is in contact with a phantom point below the pinna on the cheek. See Figure 9.2.3. The actual rotation angles should be documented in the test report.




Fig 9.2.1 Handset vertical and horizontal reference lines—“fixed case”




Fig 9.2.2 Handset vertical and horizontal reference lines—“clam-shell case”




Fig 9.2.3 cheek or touch position. The reference points for the right ear (RE), left ear (LE), and mouth (M), which establish the Reference Plane for handset positioning, are indicated.

11.3 Definition of the tilt position

1. Ready the handset for talk operation, if necessary. For example, for handsets with a cover piece (flip cover), open the cover. If the handset can transmit with the cover closed, both configurations must be tested.
2. While maintaining the orientation of the handset, move the handset away from the pinna along the line passing through RE and LE far enough to allow a rotation of the handset away from the cheek by 15°.
3. Rotate the handset around the horizontal line by 15°.
4. While maintaining the orientation of the handset, move the handset towards the phantom on the line passing through RE and LE until any part of the handset touches the ear. The tilt position is obtained when the contact point is on the pinna. See Figure 9.3.1. If contact occurs at any location other than the pinna, e.g., the antenna at the back of the phantom head, the angle of the handset should be reduced. In this case, the tilt position is obtained if any point on the handset is in contact with the pinna and a second point




Fig 9.3.1 Tilt position. The reference points for the right ear (RE), left ear (LE), and mouth (M), which define the Reference Plane for handset positioning, are indicated.

11.4 Body Worn Accessory

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 9.4). Per KDB 648474 D04v01r02, body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB 447498 D01v05r02 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for body-worn accessory, measured without a headset connected to the handset is $< 1.2 \text{ W/kg}$, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a handset attached to the handset.

Accessories for body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are test with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-chip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.




Fig 9.4 Body Worn Position

11.5 Wireless Router

Some battery-operated handsets have the capability to transmit and receive user through simultaneous transmission of WIFI simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC HDB Publication 941225 D06 v02 where SAR test considerations for handsets ($L \times W \geq 9 \text{ cm} \times 5 \text{ cm}$) are based on a composite test separation distance of 10mm from the front, back and edges of the device containing transmitting antennas within 2.5cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WIFI transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WIFI transmitter according to FCC KDB Publication 447498 D01v05r02 publication procedures. The "Portable Hotspot" feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.

12. Conducted RF Output Power (Unit: dBm)

<GSM Conducted Power>

1. Per KDB 447498 D01v05r02, the maximum output power channel is used for SAR testing and for further SAR test reduction.
2. Per KDB 941225 D01v03, considering the possibility of e.g. 3rd party VoIP operation for Head and body-worn SAR test reduction for GSM and GPRS and EDGE modes is determined by the source-based time-averaged output power including tune-up tolerance. The mode with highest specified time-averaged output power should be tested for SAR compliance in the applicable exposure conditions. For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested. Therefore, the EUT was set in GPRS (2Tx slots) for GSM850 and GSM1900.
3. Per KDB 941225 D01v03, for Hotspot SAR test reduction for GPRS and EDGE modes is determined by the source-based time-averaged output power including tune-up tolerance, for modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested, therefore, the EUT was set in GPRS (2Tx slots) for GSM850 and GSM1900.

SIM1:

Band GSM850		Burst Average Power (dBm)			Tune-up Limit (dBm)	Frame-Average Power (dBm)			Tune-up Limit (dBm)
Tx Channel		128	189	251		128	189	251	
Frequency (MHz)		824.2	836.4	848.8		824.2	836.4	848.8	
GSM (GMSK, 1 Tx slot)		32.97	33.04	33.01	33.50	23.97	24.04	24.01	24.50
GPRS (GMSK, 1 Tx slot) – CS1		32.95	32.97	32.96	33.50	23.95	23.97	23.96	24.50
GPRS (GMSK, 2 Tx slots) – CS1		30.04	30.11	30.07	30.50	24.04	24.11	24.07	24.50
GPRS (GMSK, 3 Tx slots) – CS1		27.93	28.05	28.10	28.50	23.67	23.79	23.84	24.24
GPRS (GMSK, 4 Tx slots) – CS1		26.88	26.91	26.96	27.00	23.88	23.91	23.96	24.00
EDGE (8PSK, 1 Tx slot) – MCS5		26.39	26.40	26.37	27.00	17.39	17.40	17.37	18.00
EDGE (8PSK, 2 Tx slots) – MCS5		25.34	25.35	25.38	25.50	19.34	19.35	19.38	19.50
EDGE (8PSK, 3 Tx slots) – MCS5		24.28	24.27	24.31	24.50	20.02	20.01	20.05	20.24
EDGE (8PSK, 4 Tx slots) – MCS5		23.31	23.26	23.15	23.50	20.31	20.26	20.15	20.50
Band GSM1900		Burst Average Power (dBm)			Tune-up Limit (dBm)	Frame-Average Power (dBm)			Tune-up Limit (dBm)
Tx Channel		512	661	810		512	661	810	
Frequency (MHz)		1850.2	1880	1909.8		1850.2	1880	1909.8	
GSM (GMSK, 1 Tx slot)		30.16	30.08	30.14	30.50	21.16	21.08	21.14	21.50
GPRS (GMSK, 1 Tx slot) – CS1		30.11	29.98	30.08	30.50	21.11	20.98	21.08	21.50
GPRS (GMSK, 2 Tx slots) – CS1		28.33	28.23	28.25	29.00	22.33	22.23	22.25	23.00
GPRS (GMSK, 3 Tx slots) – CS1		26.33	26.22	26.24	26.50	22.07	21.96	21.98	22.24
GPRS (GMSK, 4 Tx slots) – CS1		24.24	24.09	24.01	24.50	21.24	21.09	21.01	21.50
EDGE (8PSK, 1 Tx slot) – MCS5		25.42	25.21	25.21	25.50	16.42	16.21	16.21	16.50
EDGE (8PSK, 2 Tx slots) – MCS5		24.26	24.13	24.03	24.50	18.26	18.13	18.03	18.50
EDGE (8PSK, 3 Tx slots) – MCS5		23.19	22.97	22.94	23.50	18.93	18.71	18.68	19.24
EDGE (8PSK, 4 Tx slots) – MCS5		22.02	21.78	21.74	22.50	19.02	18.78	18.74	19.50

Remark: The frame-averaged power is linearly scaled the maximum burst averaged power over 8 time slots.

The calculated method are shown as below:

Frame-averaged power = Maximum burst averaged power (1 Tx Slot) - 9 dB

Frame-averaged power = Maximum burst averaged power (2 Tx Slots) - 6 dB

Frame-averaged power = Maximum burst averaged power (3 Tx Slots) - 4.26 dB

Frame-averaged power = Maximum burst averaged power (4 Tx Slots) - 3 dB

SIM2:

Band GSM850	Burst Average Power (dBm)			Tune-up	Frame-Average Power (dBm)			Tune-up
Tx Channel	128	189	251	Limit	128	189	251	Limit
Frequency (MHz)	824.2	836.4	848.8	(dBm)	824.2	836.4	848.8	(dBm)
GSM (GMSK, 1 Tx slot)	32.95	33.01	32.98	33.50	23.95	24.01	23.98	24.50
GPRS (GMSK, 1 Tx slot) – CS1	32.93	32.95	32.95	33.50	23.93	23.95	23.95	24.50
GPRS (GMSK, 2 Tx slots) – CS1	30.03	30.10	30.05	30.50	24.03	24.10	24.05	24.50
GPRS (GMSK, 3 Tx slots) – CS1	27.84	28.04	28.08	28.50	23.58	23.78	23.82	24.24
GPRS (GMSK, 4 Tx slots) – CS1	26.85	26.87	26.93	27.00	23.85	23.87	23.93	24.00
EDGE (8PSK, 1 Tx slot) – MCS5	26.38	26.40	26.35	27.00	17.38	17.40	17.35	18.00
EDGE (8PSK, 2 Tx slots) – MCS5	25.31	25.34	25.32	25.50	19.31	19.34	19.32	19.50
EDGE (8PSK, 3 Tx slots) – MCS5	24.28	24.21	24.30	24.50	20.02	19.95	20.04	20.24
EDGE (8PSK, 4 Tx slots) – MCS5	23.30	23.23	23.11	23.50	20.30	20.23	20.11	20.50
Band GSM1900	Burst Average Power (dBm)			Tune-up	Frame-Average Power (dBm)			Tune-up
TX Channel	512	661	810	Limit	512	661	810	Limit
Frequency (MHz)	1850.2	1880	1909.8	(dBm)	1850.2	1880	1909.8	(dBm)
GSM (GMSK, 1 Tx slot)	30.13	30.05	30.10	30.50	21.13	21.05	21.10	21.50
GPRS (GMSK, 1 Tx slot) – CS1	30.10	29.93	30.06	30.50	21.10	20.93	21.06	21.50
GPRS (GMSK, 2 Tx slots) – CS1	28.23	28.19	28.24	29.00	22.23	22.19	22.24	23.00
GPRS (GMSK, 3 Tx slots) – CS1	26.12	26.17	26.23	26.50	21.86	21.91	21.97	22.24
GPRS (GMSK, 4 Tx slots) – CS1	24.21	24.01	24.01	24.50	21.21	21.01	21.01	21.50
EDGE (8PSK, 1 Tx slot) – MCS5	25.34	25.20	25.11	25.50	16.34	16.20	16.11	16.50
EDGE (8PSK, 2 Tx slots) – MCS5	24.21	24.11	24.01	24.50	18.21	18.11	18.01	18.50
EDGE (8PSK, 3 Tx slots) – MCS5	23.11	22.92	22.92	23.50	18.85	18.66	18.66	19.24
EDGE (8PSK, 4 Tx slots) – MCS5	22.00	21.73	21.73	22.50	19.00	18.73	18.73	19.50

Remark: The frame-averaged power is linearly scaled the maximum burst averaged power over 8 time slots.

The calculated method are shown as below:

Frame-averaged power = Maximum burst averaged power (1 Tx Slot) - 9 dB

Frame-averaged power = Maximum burst averaged power (2 Tx Slots) - 6 dB

Frame-averaged power = Maximum burst averaged power (3 Tx Slots) - 4.26 dB

Frame-averaged power = Maximum burst averaged power (4 Tx Slots) - 3 dB

<WCDMA Conducted Power>

1. The following tests were conducted according to the test requirements outlines in 3GPP TS 34.121 specification.
2. The procedures in KDB 941225 D01 are applied for 3GPP Rel. 6 HSPA to configure the device in the required sub-test mode(s) to determine SAR test exclusion.

A summary of these settings are illustrated below:

HSDPA Setup Configuration:

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration.
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting:
 - i. Set Gain Factors (β_c and β_d) and parameters were set according to each
 - ii. Specific sub-test in the following table, C10.1.4, quoted from the TS 34.121
 - iii. Set RMC 12.2Kbps + HSDPA mode.
 - iv. Set Cell Power = -86 dBm
 - v. Set HS-DSCH Configuration Type to FRC (H-set 1, QPSK)
 - vi. Select HSDPA Uplink Parameters
 - vii. Set Delta ACK, Delta NACK and Delta CQI = 8
 - viii. Set Ack-Nack Repetition Factor to 3
 - ix. Set CQI Feedback Cycle (k) to 4 ms
 - x. Set CQI Repetition Factor to 2
 - xi. Power Ctrl Mode = All Up bits
- d. The transmitted maximum output power was recorded.

Table C.10.1.4: β values for transmitter characteristics tests with HS-DPCCH

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{hs} (Note 1, Note 2)	CM (dB) (Note 3)	MPR (dB) (Note 3)
1	2/15	15/15	64	2/15	4/15	0.0	0.0
2	12/15 (Note 4)	15/15 (Note 4)	64	12/15 (Note 4)	24/15	1.0	0.0
3	15/15	8/15	64	15/8	30/15	1.5	0.5
4	15/15	4/15	64	15/4	30/15	1.5	0.5

Note 1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$.

Note 2: For the HS-DPCCH power mask requirement test in clause 5.2C, 5.7A, and the Error Vector Magnitude (EVM) with HS-DPCCH test in clause 5.13.1A, and HSDPA EVM with phase discontinuity in clause 5.13.1AA, Δ_{ACK} and $\Delta_{NACK} = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$, and $\Delta_{CQI} = 24/15$ with $\beta_{hs} = 24/15 * \beta_c$.

Note 3: CM = 1 for $\beta_c/\beta_d = 12/15$, $\beta_{hs}/\beta_c = 24/15$. For all other combinations of DPDCCH, DPCCH and HS-DPCCH the MPR is based on the relative CM difference. This is applicable for only UEs that support HSDPA in release 6 and later releases.

Note 4: For subtest 2 the β_c/β_d ratio of 12/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 11/15$ and $\beta_d = 15/15$.

Setup Configuration

HSUPA Setup Configuration:

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration.
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting * :
 - i. Call Configs = 5.2B, 5.9B, 5.10B, and 5.13.2B with QPSK
 - ii. Set the Gain Factors (β_c and β_d) and parameters (AG Index) were set according to each specific sub-test in the following table, C11.1.3, quoted from the TS 34.121
 - iii. Set Cell Power = -86 dBm
 - iv. Set Channel Type = 12.2k + HSPA
 - v. Set UE Target Power
 - vi. Power Ctrl Mode= Alternating bits
 - vii. Set and observe the E-TFCI
 - viii. Confirm that E-TFCI is equal to the target E-TFCI of 75 for sub-test 1, and other subtest's E-TFCI
- d. The transmitted maximum output power was recorded.

Table C.11.1.3: β values for transmitter characteristics tests with HS-DPCCH and E-DCH

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{HS} (Note 1)	β_{ec}	β_{ed} (Note 5) (Note 6)	β_{ed} (SF)	β_{ed} (Codes)	CM (dB) (Note 2)	MPR (dB) (Note 2)	AG Index (Note 6)	E-TFCI
1	11/15 (Note 3)	15/15 (Note 3)	64	11/15 (Note 3)	22/15	209/25	1309/225	4	1	1.0	0.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	94/75	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	30/15	$\beta_{ed1}: 47/15$ $\beta_{ed2}: 47/15$	4 4	2	2.0	1.0	15	92
4	2/15	15/15	64	2/15	4/15	2/15	56/75	4	1	3.0	2.0	17	71
5	15/15 (Note 4)	15/15 (Note 4)	64	15/15 (Note 4)	30/15	24/15	134/15	4	1	1.0	0.0	21	81

Note 1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$.

Note 2: CM = 1 for $\beta_c/\beta_d = 12/15$, $\beta_{hs}/\beta_c = 24/15$. For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.

Note 3: For subtest 1 the β_c/β_d ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 10/15$ and $\beta_d = 15/15$.

Note 4: For subtest 5 the β_c/β_d ratio of 15/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 14/15$ and $\beta_d = 15/15$.

Note 5: In case of testing by UE using E-DPDCH Physical Layer category 1, Sub-test 3 is omitted according to TS25.306 Table 5.1g.

Note 6: β_{ed} can not be set directly, it is set by Absolute Grant Value.

Setup Configuration

<WCDMA Conducted Power>
General Note:

1. Per KDB 941225 D01v03, SAR for head / hotspot / body-worn exposure is measured using a 12.2 kbps RMC with TPC bits configured to all "1's".
2. Per KDB 941225 D01v03, RMC 12.2kbps setting is used to evaluate SAR. If the maximum output power and tune-up tolerance specified for production units in HSDPA / HSUPA is $\leq \frac{1}{4}$ dB higher than RMC 12.2Kbps or when the highest reported SAR of the RMC12.2Kbps is scaled by the ratio of specified maximum output power and tune-up tolerance of HSDPA / HSUPA to RMC12.2Kbps and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for HSDPA / HSUPA.

SIM1:

Band			WCDMA Band V			WCDMA Band IV		
Tx Channel			4132	4182	4233	1312	1413	1513
Rx Channel			4357	4407	4458	1537	1638	1738
Frequency (MHz)			826.4	836.4	846.6	1712.4	1732.6	1752.6
MPR (dB)	3GPP Rel 99	AMR 12.2Kbps	22.74	22.88	22.90	22.96	22.85	22.88
	3GPP Rel 99	RMC 12.2Kbps	22.75	22.89	22.92	22.98	22.87	22.90
0	3GPP Rel 6	HSDPA Subtest-1	21.84	21.94	21.86	21.59	21.47	21.57
0	3GPP Rel 6	HSDPA Subtest-2	21.83	21.94	21.88	21.54	21.36	21.50
0.5	3GPP Rel 6	HSDPA Subtest-3	21.36	21.38	21.45	21.55	21.33	21.47
0.5	3GPP Rel 6	HSDPA Subtest-4	21.20	21.41	21.42	21.49	21.36	21.51
0	3GPP Rel 6	HSUPA Subtest-1	21.31	21.75	21.53	21.81	21.72	21.77
2	3GPP Rel 6	HSUPA Subtest-2	20.59	20.52	20.33	20.72	20.65	20.76
1	3GPP Rel 6	HSUPA Subtest-3	20.50	20.11	20.19	20.43	20.38	20.40
2	3GPP Rel 6	HSUPA Subtest-4	20.95	21.41	21.36	21.08	20.92	20.88
0	3GPP Rel 6	HSUPA Subtest-5	21.11	21.16	21.35	21.34	21.20	21.13

<WLAN Conducted Power>
General Note:

For 2.4GHz WLAN SAR testing, highest average RF output power channel for the lowest data rate for 802.11b were selected for SAR evaluation. 802.11g/n HT20 were not investigated since the average output powers over all channels and data rates were not more than 0.25 dB higher than the tested channel in the lowest data rate of 802.11b mode.

<2.4GHz WLAN>

WLAN 2.4GHz 802.11b Average Power (dBm)							Tune up Limit (dBm)
Power vs. Channel			Power vs. Data Rate				
Channel	Frequency (MHz)	Data Rate 1Mbps	Channel	2Mbps	5.5Mbps	11Mbps	
CH 01	2412	12.88	CH 06	13.62	13.62	13.67	14.0
CH 06	2437	13.70					
CH 11	2462	13.27					

WLAN 2.4GHz 802.11g Average Power (dBm)											Tune up Limit (dBm)
Power vs. Channel			Power vs. Data Rate								
Channel	Frequency (MHz)	Data Rate 6Mbps	Channel	9Mbps	12Mbps	18Mbps	24Mbps	36Mbps	48Mbps	54Mbps	
CH 01	2412	11.39	CH 06	11.82	11.81	11.85	11.86	11.83	11.87	11.84	12.5
CH 06	2437	12.05									
CH 11	2462	11.59									

WLAN 2.4GHz 802.11n HT20 Average Power (dBm)											Tune up Limit (dBm)
Power vs. Channel			Power vs. MCS Index								
Channel	Frequency (MHz)	MCS Index MCS0	Channel	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	
CH 01	2412	10.48	CH 06	10.95	11.02	10.98	11.05	11.08	11.00	11.02	11.5
CH 06	2437	11.25									
CH 11	2462	10.78									


<2.4GHz Bluetooth>
General Note:

1. For 2.4GHz Bluetooth SAR testing was selected 1Mbps, due to its highest average power.
2. The duty factor is selected theoretical 83.3% perform Bluetooth SAR testing.

Mode	Channel	Frequency (MHz)	Average power (dBm)		
			1Mbps	2Mbps	3Mbps
v3.0 with EDR	CH 00	2402	7.20	5.03	4.88
	CH 39	2441	7.96	5.74	5.65
	CH 78	2480	8.47	6.18	5.70

Mode	Channel	Frequency (MHz)	Average power (dBm)
			GFSK
v4.0 with LE	CH 00	2402	-0.88
	CH 19	2440	-0.60
	CH 39	2480	-0.39

13. Antenna Location



Distance of the Antenna to the EUT surface/edge						
Antennas	Back	Front	Top Side	Bottom Side	Right Side	Left Side
WWAN	≤ 25mm	≤ 25mm	115mm	≤ 25mm	≤25mm	≤25mm
Bluetooth & WLAN	≤ 25mm	≤ 25mm	≤ 25mm	107mm	54mm	≤25mm

Positions for SAR tests; Hotspot mode						
Antennas	Back	Front	Top Side	Bottom Side	Right Side	Left Side
WWAN	Yes	Yes	No	Yes	Yes	Yes
Bluetooth & WLAN	Yes	Yes	Yes	No	No	Yes

General Note:

Referring to KDB 941225 D06 v02, when the overall device length and width are $\geq 9\text{cm} \times 5\text{cm}$, the test distance is 10 mm. SAR must be measured for all sides and surfaces with a transmitting antenna located within 25mm from that surface or edge.

14. SAR Test Results

General Note:

1. Per KDB 447498 D01v05r02, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.
 - a. Tune-up scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.
 - b. For SAR testing of WLAN signal with non-100% duty cycle, the measured SAR is scaled-up by the duty cycle scaling factor which is equal to "1/(duty cycle)"
 - c. For WWAN: Reported SAR(W/kg)= Measured SAR(W/kg)*Tune-up Scaling Factor
 - d. For WLAN: Reported SAR(W/kg)= Measured SAR(W/kg)* Duty Cycle scaling factor * Tune-up scaling factor
2. Per KDB 447498 D01v05r02, for each exposure position, testing of other required channels within the operating mode of a frequency band is not required when the *reported* 1-g or 10-g SAR for the mid-band or highest output power channel is:
 - ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz
 - ≤ 0.6 W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
 - ≤ 0.4 W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≥ 200 MHz
3. Per KDB 941225 D01v03, considering the possibility of e.g. 3rd party VoIP operation for Head and body-worn SAR test reduction for GSM and GPRS and EDGE modes is determined by the source-based time-averaged output power including tune-up tolerance. The mode with highest specified time-averaged output power should be tested for SAR compliance in the applicable exposure conditions. For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested. Therefore, the EUT was set in GPRS (2Tx slots) for GSM850 and GSM1900.
4. Per KDB 941225 D01v03, for hotspot SAR test reduction for GPRS and EDGE modes is determined by the source-based time-averaged output power including tune-up tolerance, for modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested, therefore, the EUT was set in GPRS (2Tx slots) for GSM850 and GSM1900.
5. Per KDB 941225 D01v03, SAR for head / hotspot / body-worn exposure is measured using a 12.2 kbps RMC with TPC bits configured to all "1's".
6. Per KDB 941225 D01v03, RMC 12.2kbps setting is used to evaluate SAR. If the maximum output power and tune-up tolerance specified for production units in HSDPA / HSUPA is $\leq \frac{1}{4}$ dB higher than RMC 12.2Kbps or when the highest reported SAR of the RMC12.2Kbps is scaled by the ratio of specified maximum output power and tune-up tolerance of HSDPA / HSUPA to RMC12.2Kbps and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for HSDPA / HSUPA.
7. This device 2.4GHz WLAN supports hotspot operation.
8. Per KDB 648474 D04v01r02, when the reported SAR for a body-worn accessory measured without a headset connected to the handset is ≤ 1.2 W/kg, SAR testing with a headset connected to the handset is not required.

14.1 Head SAR

<GSM SAR>

Plot No.	Band	Mode	Test Position	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	GSM850	GPRS (GMSK 2 Tx slot)	Right Cheek	189	836.4	30.11	30.50	1.094	0.12	0.553	0.605
	GSM850	GPRS (GMSK 2 Tx slot)	Right Tilted	189	836.4	30.11	30.50	1.094	0.04	0.355	0.388
	GSM850	GPRS (GMSK 2 Tx slot)	Left Cheek	189	836.4	30.11	30.50	1.094	0.06	0.555	0.607
	GSM850	GPRS (GMSK 2 Tx slot)	Left Tilted	189	836.4	30.11	30.50	1.094	-0.01	0.355	0.388
	GSM850	GPRS (GMSK 2 Tx slot)	Left Cheek	128	824.2	30.04	30.50	1.112	0.01	0.442	0.491
#01	GSM850	GPRS (GMSK 2 Tx slot)	Left Cheek	251	848.8	30.07	30.50	1.104	0.17	0.639	0.706
#02	GSM1900	GPRS (GMSK 2 Tx slot)	Right Cheek	512	1850.2	28.33	29.00	1.167	-0.01	0.508	0.593
	GSM1900	GPRS (GMSK 2 Tx slot)	Right Tilted	512	1850.2	28.33	29.00	1.167	0.01	0.200	0.233
	GSM1900	GPRS (GMSK 2 Tx slot)	Left Cheek	512	1850.2	28.33	29.00	1.167	-0.06	0.433	0.505
	GSM1900	GPRS (GMSK 2 Tx slot)	Left Tilted	512	1850.2	28.33	29.00	1.167	-0.07	0.202	0.236
	GSM1900	GPRS (GMSK 2 Tx slot)	Right Cheek	661	1880	28.23	29.00	1.194	0.01	0.463	0.553
	GSM1900	GPRS (GMSK 2 Tx slot)	Right Cheek	810	1909.8	28.25	29.00	1.189	0.15	0.404	0.480

<WCDMA SAR>

Plot No.	Band	Mode	Test Position	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WCDMA Band V	RMC 12.2Kbps	Right Cheek	4233	846.6	22.92	23.50	1.143	0.06	0.505	0.577
	WCDMA Band V	RMC 12.2Kbps	Right Tilted	4233	846.6	22.92	23.50	1.143	0.06	0.321	0.367
	WCDMA Band V	RMC 12.2Kbps	Left Cheek	4233	846.6	22.92	23.50	1.143	0.09	0.504	0.576
	WCDMA Band V	RMC 12.2Kbps	Left Tilted	4233	846.6	22.92	23.50	1.143	0.12	0.341	0.390
	WCDMA Band V	RMC 12.2Kbps	Right Cheek	4132	826.4	22.75	23.50	1.189	0.07	0.347	0.412
#03	WCDMA Band V	RMC 12.2Kbps	Right Cheek	4182	836.4	22.89	23.50	1.151	-0.05	0.529	0.609
	WCDMA Band IV	RMC 12.2Kbps	Right Cheek	1312	1712.4	22.98	23.00	1.005	0.02	0.712	0.715
	WCDMA Band IV	RMC 12.2Kbps	Right Tilted	1312	1712.4	22.98	23.00	1.005	0.02	0.307	0.308
	WCDMA Band IV	RMC 12.2Kbps	Left Cheek	1312	1712.4	22.98	23.00	1.005	0.07	0.628	0.631
	WCDMA Band IV	RMC 12.2Kbps	Left Tilted	1312	1712.4	22.98	23.00	1.005	0.03	0.325	0.327
	WCDMA Band IV	RMC 12.2Kbps	Right Cheek	1413	1732.6	22.87	23.00	1.030	-0.01	0.726	0.748
#04	WCDMA Band IV	RMC 12.2Kbps	Right Cheek	1513	1752.6	22.90	23.00	1.023	0.03	0.768	0.786

<DTS WLAN SAR>

Plot No.	Band	Mode	Test Position	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WLAN 2.4GHz	802.11b, 1Mbps	Right Cheek	6	2437	13.70	14.00	1.072	97.59	1.025	0.01	0.119	0.131
	WLAN 2.4GHz	802.11b, 1Mbps	Right Tilted	6	2437	13.70	14.00	1.072	97.59	1.025	0.04	0.069	0.076
	WLAN 2.4GHz	802.11b, 1Mbps	Left Cheek	6	2437	13.70	14.00	1.072	97.59	1.025	-0.1	0.077	0.085
	WLAN 2.4GHz	802.11b, 1Mbps	Left Tilted	6	2437	13.70	14.00	1.072	97.59	1.025	0.04	0.061	0.067
#05	WLAN 2.4GHz	802.11b, 1Mbps	Right Cheek	1	2412	12.88	14.00	1.294	97.59	1.025	0.03	0.147	0.195
	WLAN 2.4GHz	802.11b, 1Mbps	Right Cheek	11	2462	13.27	14.00	1.183	97.59	1.025	-0.04	0.125	0.152

<Bluetooth SAR>

Plot No.	Band	Mode	Test Position	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	Bluetooth	1Mbps	Right Cheek	78	2480	8.47	9	1.130	0.09	0.035	0.040
	Bluetooth	1Mbps	Right Tilted	78	2480	8.47	9	1.130	-0.04	0.021	0.024
	Bluetooth	1Mbps	Left Cheek	78	2480	8.47	9	1.130	0.07	0.020	0.023
	Bluetooth	1Mbps	Left Tilted	78	2480	8.47	9	1.130	0.03	0.014	0.016
#06	Bluetooth	1Mbps	Right Cheek	0	2402	7.20	9	1.514	0.08	0.059	0.089
	Bluetooth	1Mbps	Right Cheek	39	2441	7.96	9	1.271	0.04	0.042	0.053

14.2 Hotspot SAR

Distance of the Antenna to the EUT surface/edge						
Antennas	Back	Front	Top Side	Bottom Side	Right Side	Left Side
WWAN	≤ 25mm	≤ 25mm	115mm	≤ 25mm	≤25mm	≤25mm
Bluetooth & WLAN	≤ 25mm	≤ 25mm	≤ 25mm	107mm	54mm	≤25mm

Positions for SAR tests; Hotspot mode						
Antennas	Back	Front	Top Side	Bottom Side	Right Side	Left Side
WWAN	Yes	Yes	No	Yes	Yes	Yes
Bluetooth & WLAN	Yes	Yes	Yes	No	No	Yes

General Note:

Referring to KDB 941225 D06 v02, when the overall device length and width are ≥ 9cm*5cm, the test distance is 10 mm. SAR must be measured for all sides and surfaces with a transmitting antenna located within 25mm from that surface or edge.

<GSM SAR>

Plot No.	Band	Mode	Test Position	Gap (cm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
#07	GSM850	GPRS (GMSK 2 Tx slot)	Front	1	189	836.4	30.11	30.50	1.094	0.04	0.739	0.808
	GSM850	GPRS (GMSK 2 Tx slot)	Back	1	189	836.4	30.11	30.50	1.094	0.02	1.090	1.192
	GSM850	GPRS (GMSK 2 Tx slot)	Left side	1	189	836.4	30.11	30.50	1.094	0.05	0.682	0.746
	GSM850	GPRS (GMSK 2 Tx slot)	Right side	1	189	836.4	30.11	30.50	1.094	0.04	0.716	0.783
	GSM850	GPRS (GMSK 2 Tx slot)	Bottom side	1	189	836.4	30.11	30.50	1.094	0.05	0.093	0.102
#08	GSM850	GPRS (GMSK 2 Tx slot)	Front	1	128	824.2	30.04	30.50	1.112	-0.01	0.617	0.686
	GSM850	GPRS (GMSK 2 Tx slot)	Front	1	251	848.8	30.07	30.50	1.104	0.01	0.765	0.845
	GSM850	GPRS (GMSK 2 Tx slot)	Back	1	128	824.2	30.04	30.50	1.112	0.03	0.997	1.108
	GSM850	GPRS (GMSK 2 Tx slot)	Back	1	251	848.8	30.07	30.50	1.104	0.08	1.070	1.181
	GSM1900	GPRS (GMSK 2 Tx slot)	Front	1	512	1850.2	28.33	29.00	1.167	0.01	0.568	0.663
	GSM1900	GPRS (GMSK 2 Tx slot)	Back	1	512	1850.2	28.33	29.00	1.167	0.02	0.948	1.106
	GSM1900	GPRS (GMSK 2 Tx slot)	Left side	1	512	1850.2	28.33	29.00	1.167	0.09	0.240	0.280
	GSM1900	GPRS (GMSK 2 Tx slot)	Right side	1	512	1850.2	28.33	29.00	1.167	-0.05	0.143	0.167
	GSM1900	GPRS (GMSK 2 Tx slot)	Bottom side	1	512	1850.2	28.33	29.00	1.167	-0.08	0.832	0.971
	GSM1900	GPRS (GMSK 2 Tx slot)	Back	1	661	1880	28.23	29.00	1.194	-0.13	0.825	0.985
	GSM1900	GPRS (GMSK 2 Tx slot)	Back	1	810	1909.8	28.25	29.00	1.189	-0.13	0.721	0.857
	GSM1900	GPRS (GMSK 2 Tx slot)	Bottom side	1	661	1880	28.23	29.00	1.194	-0.12	0.812	0.970
	GSM1900	GPRS (GMSK 2 Tx slot)	Bottom side	1	810	1909.8	28.25	29.00	1.189	-0.04	0.788	0.937

<WCDMA SAR>

Plot No.	Band	Mode	Test Position	Gap (cm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WCDMA Band V	RMC 12.2Kbps	Front	1	4233	846.6	22.92	23.50	1.143	0.02	0.696	0.795
	WCDMA Band V	RMC 12.2Kbps	Back	1	4233	846.6	22.92	23.50	1.143	0.01	0.963	1.101
	WCDMA Band V	RMC 12.2Kbps	Left side	1	4233	846.6	22.92	23.50	1.143	0.05	0.717	0.819
	WCDMA Band V	RMC 12.2Kbps	Right side	1	4233	846.6	22.92	23.50	1.143	-0.05	0.554	0.633
	WCDMA Band V	RMC 12.2Kbps	Bottom side	1	4233	846.6	22.92	23.50	1.143	-0.14	0.083	0.095
	WCDMA Band V	RMC 12.2Kbps	Back	1	4132	826.4	22.75	23.50	1.189	0.01	0.827	0.983
#09	WCDMA Band V	RMC 12.2Kbps	Back	1	4182	836.4	22.89	23.50	1.151	-0.08	1.030	1.185
	WCDMA Band V	RMC 12.2Kbps	Left side	1	4132	826.4	22.75	23.50	1.189	0.04	0.592	0.704
	WCDMA Band V	RMC 12.2Kbps	Left side	1	4182	836.4	22.89	23.50	1.151	0.01	0.821	0.945
	WCDMA Band IV	RMC 12.2Kbps	Front	1	1312	1712.4	22.98	23.00	1.005	0.07	0.852	0.856
	WCDMA Band IV	RMC 12.2Kbps	Back	1	1312	1712.4	22.98	23.00	1.005	-0.01	1.130	1.135
	WCDMA Band IV	RMC 12.2Kbps	Left side	1	1312	1712.4	22.98	23.00	1.005	0.03	0.321	0.322
	WCDMA Band IV	RMC 12.2Kbps	Right side	1	1312	1712.4	22.98	23.00	1.005	0.04	0.199	0.200
	WCDMA Band IV	RMC 12.2Kbps	Bottom side	1	1312	1712.4	22.98	23.00	1.005	-0.05	0.850	0.854
	WCDMA Band IV	RMC 12.2Kbps	Front	1	1413	1732.6	22.87	23.00	1.030	0.04	0.835	0.860
	WCDMA Band IV	RMC 12.2Kbps	Front	1	1513	1752.6	22.90	23.00	1.023	0.05	0.829	0.848
	WCDMA Band IV	RMC 12.2Kbps	Back	1	1413	1732.6	22.87	23.00	1.030	-0.01	1.140	1.175
#10	WCDMA Band IV	RMC 12.2Kbps	Back	1	1513	1752.6	22.90	23.00	1.023	-0.01	1.170	1.197
	WCDMA Band IV	RMC 12.2Kbps	Bottom side	1	1413	1732.6	22.87	23.00	1.030	0.03	0.892	0.919
	WCDMA Band IV	RMC 12.2Kbps	Bottom side	1	1513	1752.6	22.90	23.00	1.023	-0.04	0.944	0.966

<DTS WLAN SAR>

Plot No.	Band	Mode	Test Position	Gap (cm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WLAN 2.4GHz	802.11b, 1Mbps	Front	1	6	2437	13.70	14.00	1.072	97.59	1.025	0.16	0.034	0.037
	WLAN 2.4GHz	802.11b, 1Mbps	Back	1	6	2437	13.70	14.00	1.072	97.59	1.025	-0.09	0.033	0.036
	WLAN 2.4GHz	802.11b, 1Mbps	Left side	1	6	2437	13.70	14.00	1.072	97.59	1.025	0.12	0.035	0.038
	WLAN 2.4GHz	802.11b, 1Mbps	Top side	1	6	2437	13.70	14.00	1.072	97.59	1.025	-0.09	0.023	0.025
	WLAN 2.4GHz	802.11b, 1Mbps	Front	1	1	2412	12.88	14.00	1.294	97.59	1.025	-0.02	0.031	0.041
	WLAN 2.4GHz	802.11b, 1Mbps	Front	1	11	2462	13.27	14.00	1.183	97.59	1.025	-0.12	0.025	0.030
#11	WLAN 2.4GHz	802.11b, 1Mbps	Left side	1	1	2412	12.88	14.00	1.294	97.59	1.025	0.01	0.035	0.046
	WLAN 2.4GHz	802.11b, 1Mbps	Left side	1	11	2462	13.27	14.00	1.183	97.59	1.025	-0.05	0.033	0.040

<Bluetooth SAR>

Plot No.	Band	Mode	Test Position	Gap (cm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	Bluetooth	1Mbps	Front	1	78	2480	8.47	9	1.130	-0.08	0.00795	0.009
	Bluetooth	1Mbps	Back	1	78	2480	8.47	9	1.130	-0.02	0.012	0.014
	Bluetooth	1Mbps	Left side	1	78	2480	8.47	9	1.130	0.05	0.010	0.011
	Bluetooth	1Mbps	Top side	1	78	2480	8.47	9	1.130	-0.02	0.00629	0.007
#12	Bluetooth	1Mbps	Back	1	0	2402	7.20	9	1.514	-0.09	0.016	0.024
	Bluetooth	1Mbps	Back	1	39	2441	7.96	9	1.271	-0.10	0.015	0.019

14.3 Body Worn Accessory SAR

<GSM SAR>

Plot No.	Band	Mode	Test Position	Gap (cm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	GSM850	GPRS (GMSK 2 Tx slot)	Front	1	189	836.4	30.11	30.50	1.094	0.04	0.739	0.808
#07	GSM850	GPRS (GMSK 2 Tx slot)	Back	1	189	836.4	30.11	30.50	1.094	0.02	1.090	1.192
	GSM850	GPRS (GMSK 2 Tx slot)	Front	1	128	824.2	30.04	30.50	1.112	-0.01	0.617	0.686
	GSM850	GPRS (GMSK 2 Tx slot)	Front	1	251	848.8	30.07	30.50	1.104	0.01	0.765	0.845
	GSM850	GPRS (GMSK 2 Tx slot)	Back	1	128	824.2	30.04	30.50	1.112	0.03	0.997	1.108
	GSM850	GPRS (GMSK 2 Tx slot)	Back	1	251	848.8	30.07	30.50	1.104	0.08	1.070	1.181
	GSM1900	GPRS (GMSK 2 Tx slot)	Front	1	512	1850.2	28.33	29.00	1.167	0.01	0.568	0.663
#08	GSM1900	GPRS (GMSK 2 Tx slot)	Back	1	512	1850.2	28.33	29.00	1.167	0.02	0.948	1.106
	GSM1900	GPRS (GMSK 2 Tx slot)	Back	1	661	1880	28.23	29.00	1.194	-0.13	0.825	0.985
	GSM1900	GPRS (GMSK 2 Tx slot)	Back	1	810	1909.8	28.25	29.00	1.189	-0.13	0.721	0.857

<WCDMA SAR>

Plot No.	Band	Mode	Test Position	Gap (cm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WCDMA Band V	RMC 12.2Kbps	Front	1	4233	846.6	22.92	23.50	1.143	0.02	0.696	0.795
	WCDMA Band V	RMC 12.2Kbps	Back	1	4233	846.6	22.92	23.50	1.143	0.01	0.963	1.101
	WCDMA Band V	RMC 12.2Kbps	Back	1	4132	826.4	22.75	23.50	1.189	0.01	0.827	0.983
#09	WCDMA Band V	RMC 12.2Kbps	Back	1	4182	836.4	22.89	23.50	1.151	-0.08	1.030	1.185
	WCDMA Band IV	RMC 12.2Kbps	Front	1	1312	1712.4	22.98	23.00	1.005	0.07	0.852	0.856
	WCDMA Band IV	RMC 12.2Kbps	Back	1	1312	1712.4	22.98	23.00	1.005	-0.01	1.130	1.135
	WCDMA Band IV	RMC 12.2Kbps	Front	1	1413	1732.6	22.87	23.00	1.030	0.04	0.835	0.860
	WCDMA Band IV	RMC 12.2Kbps	Front	1	1513	1752.6	22.90	23.00	1.023	0.05	0.829	0.848
	WCDMA Band IV	RMC 12.2Kbps	Back	1	1413	1732.6	22.87	23.00	1.030	-0.01	1.140	1.175
#10	WCDMA Band IV	RMC 12.2Kbps	Back	1	1513	1752.6	22.90	23.00	1.023	-0.01	1.170	1.197

<DTS WLAN SAR>

Plot No.	Band	Mode	Test Position	Gap (cm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WLAN 2.4GHz	802.11b, 1Mbps	Front	1	6	2437	13.70	14.00	1.072	97.59	1.025	0.16	0.034	0.037
	WLAN 2.4GHz	802.11b, 1Mbps	Back	1	6	2437	13.70	14.00	1.072	97.59	1.025	-0.09	0.033	0.036
#13	WLAN 2.4GHz	802.11b, 1Mbps	Front	1	1	2412	12.88	14.00	1.294	97.59	1.025	-0.02	0.031	0.041
	WLAN 2.4GHz	802.11b, 1Mbps	Front	1	11	2462	13.27	14.00	1.183	97.59	1.025	-0.12	0.025	0.030

<Bluetooth SAR>

Plot No.	Band	Mode	Test Position	Gap (cm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	Bluetooth	1Mbps	Front	1	78	2480	8.47	9	1.130	-0.08	0.00795	0.009
	Bluetooth	1Mbps	Back	1	78	2480	8.47	9	1.130	-0.02	0.012	0.014
#12	Bluetooth	1Mbps	Back	1	0	2402	7.20	9	1.514	-0.09	0.016	0.024
	Bluetooth	1Mbps	Back	1	39	2441	7.96	9	1.271	-0.10	0.015	0.019

14.4 Repeated SAR Measurement

No.	Band	Mode	Test Position	Gap (cm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Ratio	Reported 1g SAR (W/kg)
1st	GSM850	GPRS (GMSK 2 Tx slot)	Back	1	189	836.4	30.11	30.50	1.094	0.02	1.090	1	1.192
2nd	GSM850	GPRS (GMSK 2 Tx slot)	Back	1	189	836.4	30.11	30.50	1.094	0.04	1.050	1.038	1.149
1st	GSM1900	GPRS (GMSK 2 Tx slot)	Back	1	512	1850.2	28.33	29.00	1.167	0.02	0.948	1	1.106
2nd	GSM1900	GPRS (GMSK 2 Tx slot)	Back	1	512	1850.2	28.33	29.00	1.167	-0.13	0.893	1.062	1.042
1st	WCDMA Band IV	RMC 12.2Kbps	Back	1	1513	1752.6	22.90	23.00	1.023	-0.01	1.170	1	1.197
2nd	WCDMA Band IV	RMC 12.2Kbps	Back	1	1513	1752.6	22.90	23.00	1.023	0.01	1.150	1.017	1.177

General Note:

1. Per KDB 865664 D01v01r03, for each frequency band, repeated SAR measurement is required only when the measured SAR is ≥ 0.8 W/kg.
2. Per KDB 865664 D01v01r03, if the ratio among the repeated measurement is ≤ 1.2 and the measured SAR < 1.45 W/kg, only one repeated measurement is required.
3. The ratio is the difference in percentage between original and repeated *measured SAR*.
4. All measurement SAR result is scaled-up to account for tune-up tolerance and is compliant.

15. Simultaneous Transmission Analysis

NO.	Simultaneous Transmission Configurations	Portable Handset			Note
		Head	Body-worn	Hotspot	
1.	GSM(voice) + WLAN2.4GHz(data)	Yes	Yes		
2.	WCDMA(voice) + WLAN2.4GHz(data)	Yes	Yes		
3.	GSM(voice) + Bluetooth(data)	Yes	Yes		
4.	WCDMA((voice) + Bluetooth(data)	Yes	Yes		
5.	GPRS/EDGE(data) + WLAN2.4GHz(data)	Yes	Yes	Yes	2.4GHz Hotspot
6.	WCDMA(data) + WLAN2.4GHz(data)	Yes	Yes	Yes	2.4GHz Hotspot
7.	GPRS/EDGE(data) + Bluetooth(data)	Yes	Yes	Yes	Bluetooth Tethering
8.	WCDMA(data) + Bluetooth(data)	Yes	Yes	Yes	Bluetooth Tethering

General Note:

1. This device supported VoIP in GPRS, EGPRS and WCDMA (e.g. 3rd party VoIP).
2. This device 2.4GHz WLAN supports Hotspot operation.
3. WLAN 2.4GHz and Bluetooth share the same antenna, and cannot transmit simultaneously.
4. EUT will choose either GSM or WCDMA according to the network signal condition; therefore, they will not operate simultaneously at any moment.
5. The reported SAR summation is calculated based on the same configuration and test position.
6. Per KDB 447498 D01v05r02, simultaneous transmission SAR is compliant if,
 - i) Scalar SAR summation $< 1.6\text{W/kg}$.
 - ii) $\text{SPLSR} = (\text{SAR}_1 + \text{SAR}_2)^{1.5} / (\text{min. separation distance, mm})$, and the peak separation distance is determined from the square root of $[(x_1-x_2)^2 + (y_1-y_2)^2 + (z_1-z_2)^2]$, where (x_1, y_1, z_1) and (x_2, y_2, z_2) are the coordinates of the extrapolated peak SAR locations in the zoom scan. If $\text{SPLSR} \leq 0.04$, simultaneously transmission SAR measurement is not necessary.
 - iii) Simultaneously transmission SAR measurement, and the reported multi-band SAR $< 1.6\text{W/kg}$.

15.1 Head Exposure Conditions
<WWAN PCE + WLAN DTS>

WWAN Band		Exposure Position	WWAN PCE Max. WWAN SAR (W/kg)	WLAN DTS Max. WLAN SAR (W/kg)	Summed SAR (W/kg)
GSM	GSM850	Right Cheek	0.605	0.195	0.80
		Right Tilted	0.388	0.076	0.46
		Left Cheek	0.706	0.085	0.79
		Left Tilted	0.388	0.067	0.46
	GSM1900	Right Cheek	0.593	0.195	0.79
		Right Tilted	0.233	0.076	0.31
		Left Cheek	0.505	0.085	0.59
		Left Tilted	0.236	0.067	0.30
WCDMA	Band V	Right Cheek	0.609	0.195	0.80
		Right Tilted	0.367	0.076	0.44
		Left Cheek	0.576	0.085	0.66
		Left Tilted	0.390	0.067	0.46
	Band IV	Right Cheek	0.786	0.195	0.98
		Right Tilted	0.308	0.076	0.38
		Left Cheek	0.631	0.085	0.72
		Left Tilted	0.327	0.067	0.39

<WWAN PCE + Bluetooth DSS>

WWAN Band		Exposure Position	WWAN PCE Max. WWAN SAR (W/kg)	Bluetooth DSS Max. Bluetooth SAR (W/kg)	Summed SAR (W/kg)
GSM	GSM850	Right Cheek	0.605	0.089	0.69
		Right Tilted	0.388	0.024	0.41
		Left Cheek	0.706	0.023	0.73
		Left Tilted	0.388	0.016	0.40
	GSM1900	Right Cheek	0.593	0.089	0.68
		Right Tilted	0.233	0.024	0.26
		Left Cheek	0.505	0.023	0.53
		Left Tilted	0.236	0.016	0.25
WCDMA	Band V	Right Cheek	0.609	0.089	0.70
		Right Tilted	0.367	0.024	0.39
		Left Cheek	0.576	0.023	0.60
		Left Tilted	0.390	0.016	0.41
	Band IV	Right Cheek	0.786	0.089	0.88
		Right Tilted	0.308	0.024	0.33
		Left Cheek	0.631	0.023	0.65
		Left Tilted	0.327	0.016	0.34

15.2 Hotspot Exposure Conditions
<WWAN PCE+ WLAN DTS>

WWAN Band		Exposure Position	WWAN PCE Max. WWAN SAR (W/kg)	WLAN DTS Max. WLAN SAR (W/kg)	Summed SAR (W/kg)
GSM	GSM850	Front	0.845	0.041	0.89
		Back	1.192	0.036	1.23
		Left side	0.746	0.046	0.79
		Right side	0.783		0.78
		Top side		0.025	0.03
		Bottom side	0.102		0.10
GSM	GSM1900	Front	0.663	0.041	0.70
		Back	1.106	0.036	1.14
		Left side	0.280	0.046	0.33
		Right side	0.167		0.17
		Top side		0.025	0.03
		Bottom side	0.971		0.97
WCDMA	Band V	Front	0.795	0.041	0.84
		Back	1.185	0.036	1.22
		Left side	0.945	0.046	0.99
		Right side	0.633		0.63
		Top side		0.025	0.03
		Bottom side	0.095		0.10
	Band IV	Front	0.860	0.041	0.90
		Back	1.197	0.036	1.23
		Left side	0.322	0.046	0.37
		Right side	0.200		0.20
		Top side		0.025	0.03
		Bottom side	0.966		0.97

<WWAN PCE+ Bluetooth DSS>

WWAN Band		Exposure Position	WWAN PCE Max. WWAN SAR (W/kg)	Bluetooth DSS Max. Bluetooth SAR (W/kg)	Summed SAR (W/kg)
GSM	GSM850	Front	0.845	0.009	0.85
		Back	1.192	0.024	1.22
		Left side	0.746	0.011	0.76
		Right side	0.783		0.78
		Top side		0.007	0.01
		Bottom side	0.102		0.10
GSM	GSM1900	Front	0.663	0.009	0.67
		Back	1.106	0.024	1.13
		Left side	0.280	0.011	0.29
		Right side	0.167		0.17
		Top side		0.007	0.01
		Bottom side	0.971		0.97
WCDMA	Band V	Front	0.795	0.009	0.80
		Back	1.185	0.024	1.21
		Left side	0.945	0.011	0.96
		Right side	0.633		0.63
		Top side		0.007	0.01
		Bottom side	0.095		0.10
	Band IV	Front	0.860	0.009	0.87
		Back	1.197	0.024	1.22
		Left side	0.322	0.011	0.33
		Right side	0.200		0.20
		Top side		0.007	0.01
		Bottom side	0.966		0.97

15.3 Body-Worn Accessory Exposure Conditions
<WWAN PCE+ WLAN DTS>

WWAN Band		Exposure Position	WWAN PCE Max. WWAN SAR (W/kg)	WLAN DTS Max. WLAN SAR (W/kg)	Summed SAR (W/kg)
GSM	GSM850	Front	0.845	0.041	0.89
		Back	1.192	0.036	1.23
GSM	GSM1900	Front	0.663	0.041	0.70
		Back	1.106	0.036	1.14
WCDMA	Band V	Front	0.795	0.041	0.84
		Back	1.185	0.036	1.22
	Band IV	Front	0.860	0.041	0.90
		Back	1.197	0.036	1.23

<WWAN PCE+ Bluetooth DSS>

WWAN Band		Exposure Position	WWAN PCE Max. WWAN SAR (W/kg)	Bluetooth DSS Max. Bluetooth SAR (W/kg)	Summed SAR (W/kg)
GSM	GSM850	Front	0.845	0.009	0.85
		Back	1.192	0.024	1.22
GSM	GSM1900	Front	0.663	0.009	0.67
		Back	1.106	0.024	1.13
WCDMA	Band V	Front	0.795	0.009	0.80
		Back	1.185	0.024	1.21
	Band IV	Front	0.860	0.009	0.87
		Back	1.197	0.024	1.22

Test Engineer : Fulu Hu

16. Uncertainty Assessment

The component of uncertainty may generally be categorized according to the methods used to evaluate them. The evaluation of uncertainty by the statistical analysis of a series of observations is termed a Type A evaluation of uncertainty. The evaluation of uncertainty by means other than the statistical analysis of a series of observation is termed a Type B evaluation of uncertainty. Each component of uncertainty, however evaluated, is represented by an estimated standard deviation, termed standard uncertainty, which is determined by the positive square root of the estimated variance.

A Type A evaluation of standard uncertainty may be based on any valid statistical method for treating data. This includes calculating the standard deviation of the mean of a series of independent observations; using the method of least squares to fit a curve to the data in order to estimate the parameter of the curve and their standard deviations; or carrying out an analysis of variance in order to identify and quantify random effects in certain kinds of measurement.

A type B evaluation of standard uncertainty is typically based on scientific judgment using all of the relevant information available. These may include previous measurement data, experience, and knowledge of the behavior and properties of relevant materials and instruments, manufacture's specification, data provided in calibration reports and uncertainties assigned to reference data taken from handbooks. Broadly speaking, the uncertainty is either obtained from an outdoor source or obtained from an assumed distribution, such as the normal distribution, rectangular or triangular distributions indicated in table below.

Uncertainty Distributions	Normal	Rectangular	Triangular	U-Shape
Multi-plying Factor ^(a)	$1/k^{(b)}$	$1/\sqrt{3}$	$1/\sqrt{6}$	$1/\sqrt{2}$

(a) standard uncertainty is determined as the product of the multiplying factor and the estimated range of variations in the measured quantity

(b) k is the coverage factor

Table 16.1. Standard Uncertainty for Assumed Distribution

The combined standard uncertainty of the measurement result represents the estimated standard deviation of the result. It is obtained by combining the individual standard uncertainties of both Type A and Type B evaluation using the usual "root-sum-squares" (RSS) methods of combining standard deviations by taking the positive square root of the estimated variances.

Expanded uncertainty is a measure of uncertainty that defines an interval about the measurement result within which the measured value is confidently believed to lie. It is obtained by multiplying the combined standard uncertainty by a coverage factor. Typically, the coverage factor ranges from 2 to 3. Using a coverage factor allows the true value of a measured quantity to be specified with a defined probability within the specified uncertainty range. For purpose of this document, a coverage factor two is used, which corresponds to confidence interval of about 95 %. The DASY uncertainty Budget is shown in the following tables.

Error Description	Uncertainty Value (±%)	Probability Distribution	Divisor	Ci (1g)	Ci (10g)	Standard Uncertainty (1g)	Standard Uncertainty (10g)
Measurement System							
Probe Calibration	6.0	Normal	1	1	1	± 6.0 %	± 6.0 %
Axial Isotropy	4.7	Rectangular	√3	0.7	0.7	± 1.9 %	± 1.9 %
Hemispherical Isotropy	9.6	Rectangular	√3	0.7	0.7	± 3.9 %	± 3.9 %
Boundary Effects	1.0	Rectangular	√3	1	1	± 0.6 %	± 0.6 %
Linearity	4.7	Rectangular	√3	1	1	± 2.7 %	± 2.7 %
System Detection Limits	1.0	Rectangular	√3	1	1	± 0.6 %	± 0.6 %
Readout Electronics	0.3	Normal	1	1	1	± 0.3 %	± 0.3 %
Response Time	0.8	Rectangular	√3	1	1	± 0.5 %	± 0.5 %
Integration Time	2.6	Rectangular	√3	1	1	± 1.5 %	± 1.5 %
RF Ambient Noise	3.0	Rectangular	√3	1	1	± 1.7 %	± 1.7 %
RF Ambient Reflections	3.0	Rectangular	√3	1	1	± 1.7 %	± 1.7 %
Probe Positioner	0.4	Rectangular	√3	1	1	± 0.2 %	± 0.2 %
Probe Positioning	2.9	Rectangular	√3	1	1	± 1.7 %	± 1.7 %
Max. SAR Eval.	1.0	Rectangular	√3	1	1	± 0.6 %	± 0.6 %
Test Sample Related							
Device Positioning	2.9	Normal	1	1	1	± 2.9 %	± 2.9 %
Device Holder	3.6	Normal	1	1	1	± 3.6 %	± 3.6 %
Power Drift	5.0	Rectangular	√3	1	1	± 2.9 %	± 2.9 %
Phantom and Setup							
Phantom Uncertainty	4.0	Rectangular	√3	1	1	± 2.3 %	± 2.3 %
Liquid Conductivity (Target)	5.0	Rectangular	√3	0.64	0.43	± 1.8 %	± 1.2 %
Liquid Conductivity (Meas.)	2.5	Normal	1	0.64	0.43	± 1.6 %	± 1.1 %
Liquid Permittivity (Target)	5.0	Rectangular	√3	0.6	0.49	± 1.7 %	± 1.4 %
Liquid Permittivity (Meas.)	2.5	Normal	1	0.6	0.49	± 1.5 %	± 1.2 %
Combined Standard Uncertainty						± 11.0 %	± 10.8 %
Coverage Factor for 95 %						K=2	
Expanded Uncertainty						± 22.0 %	± 21.5 %

Table 16.2. Uncertainty Budget for frequency range 300 MHz to 3 GHz

17. References

- [1] FCC 47 CFR Part 2 "Frequency Allocations and Radio Treaty Matters; General Rules and Regulations"
- [2] ANSI/IEEE Std. C95.1-1992, "IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz", September 1992
- [3] IEEE Std. 1528-2003, "Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- [4] SPEAG DASY System Handbook
- [5] FCC KDB 865664 D01 v01r03, "SAR Measurement Requirements for 100 MHz to 6 GHz", Feb 2014
- [6] FCC KDB 865664 D02 v01r01, "RF Exposure Compliance Reporting and Documentation Considerations" May 2013
- [7] FCC KDB 447498 D01 v05r02, "Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies", Feb 2014
- [8] FCC KDB 648474 D04 v01r02, "SAR Evaluation Considerations for Wireless Handsets", Dec 2013
- [9] FCC KDB 248227 D01 v01r02, "SAR Measurement Procedures for 802.11 a/b/g Transmitters", May 2007
- [10] FCC KDB 941225 D01 v03, "3G SAR MEAUREMENT PROCEDURES", Oct 2014
- [11] FCC KDB 941225 D06 v02, "SAR Evaluation Procedures for Portable Devices with Wireless Router Capabilities", Oct 2014