



Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China

RF Exposure evaluation

Report Reference No.....: CTA26060301105

FCC ID.....: HQXTT-05

Compiled by

(position+printed name+signature) .: File administrators Zoey Cao

Supervised by

(position+printed name+signature) .: Project Engineer Ace Chai

Approved by

(position+printed name+signature) .: RF Manager Eric Wang

Date of issue: Jul. 22, 2026

Testing Laboratory Name: Shenzhen CTA Testing Technology Co., Ltd.

Address.....: Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China

Applicant's name.....: Sysgration Ltd.

Address.....: 6F.,No.1,Sec.1,Tiding Blvd.,Neihu Dist.Taipei City, 114 Taiwan

Standard: 47CFR §1.1310

47CFR §2.1093

KDB447498 D01 General RF Exposure Guidance v06

Shenzhen CTA Testing Technology Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen CTA Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen CTA Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description: TPMS Programming Tool

Trade Mark: N/A

Manufacturer: Sysgration Ltd.

Model/Type reference: TT-05

Listed Models: N/A

Rating: Input: 5V=== 2A
Battery: 3.7V 3200mAh 11.84Wh

Result: PASS

Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China
Tel:+86-755 2322 5875 E-mail:cta@cta-test.cn Web:http://www.cta-test.cn

TEST REPORT

Equipment under Test : TPMS Programming Tool

Model /Type : TT-05

Listed Models : N/A

Applicant : **Sysgration Ltd.**

Address : 6F.,No.1,Sec.1,Tiding Blvd.,Neihu Dist.Taipei City, 114 Taiwan

Manufacturer : **Sysgration Ltd.**

Address : 6F.,No.1,Sec.1,Tiding Blvd.,Neihu Dist.Taipei City, 114 Taiwan

Test Result:	PASS
---------------------	-------------

The test report merely corresponds to the test sample.
It is not permitted to copy extracts of these test result without the written permission of
the test laboratory.

Contents

1	TEST STANDARDS	4
2	SUMMARY	5
2.1	General Remarks	5
2.2	Product Description	5
2.3	Special Accessories	6
2.4	Modifications	6
3	TEST ENVIRONMENT	7
3.1	Address of the test laboratory	7
3.2	Test Facility	7
3.3	Statement of the measurement uncertainty	7
4	Test limit	8
4.1	Requirement	8
4.2	Conducted Power Results	8
4.3	Manufacturing tolerance	10
4.4	Evaluation Result	10
4.5	Simultaneous Transmission for SAR Exclusion	10
5	Conclusion	10

1 TEST STANDARDS

The tests were performed according to following standards:

[ANSI C95.1-1999](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

[FCC KDB 447498 D01 General RF Exposure Guidance v06](#): Mobile and Portable Device, RF Exposure, Equipment Authorization Procedures.

[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.

[FCC CFR 47 part2 2.1093](#): Radiofrequency radiation exposure evaluation: portable devices

2 SUMMARY

2.1 General Remarks

Date of receipt of test sample	:	Jun. 03, 2026
Testing commenced on	:	Jun. 03, 2026
Testing concluded on	:	Jul. 22, 2026

2.2 Product Description

Product Name:	TPMS Programming Tool
Model/Type reference:	TT-05
Power supply:	Input: 5V $\overline{\text{---}}$ 2A Battery: 3.7V 3200mAh 11.84Wh
Hardware version:	V1.0
Software version:	V1.0
Testing sample ID:	CTA260603011-1# (Engineer sample) CTA260603011-2# (Normal sample)
Bluetooth :	
Supported Type:	Bluetooth BR/EDR
Modulation:	GFSK, $\pi/4$ DQPSK, 8DPSK
Operation frequency:	2402MHz~2480MHz
Channel number:	79
Channel separation:	1MHz
Antenna type:	PCB antenna
Antenna gain:	0.81 dBi
Bluetooth BLE	
Supported type:	Bluetooth low Energy
Modulation:	GFSK
Operation frequency:	2402MHz to 2480MHz
Channel number:	40
Channel separation:	2 MHz
Antenna type:	PCB antenna
Antenna gain:	0.81 dBi
2.4GWIFI :	
Supported type:	802.11b/802.11g/802.11n(HT20)
Modulation:	802.11b: DSSS 802.11g/802.11n(HT20): OFDM
Operation frequency:	802.11b/802.11g/802.11n(HT20): 2412MHz~2462MHz
Channel number:	802.11b/802.11g/802.11n(HT20): 11
Channel separation:	5MHz
Antenna type:	PCB antenna
Antenna gain:	0.81 dBi
5GWIFI	

Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China

Tel:+86-755 2322 5875 E-mail:cta@cta-test.cn Web:http://www.cta-test.cn

	20MHz system	40MHz system	80MHz system	160MHz system
Supported type:	802.11a 802.11n 802.11ac	N/A	N/A	N/A
Operation frequency:	5180MHz-5240MHz 5745MHz-5825MHz	N/A	N/A	N/A
Modulation:	OFDM	N/A	N/A	N/A
Channel number:	9	N/A	N/A	N/A
Channel separation:	20MHz	N/A	N/A	N/A
Antenna type:	PCB antenna			
Antenna gain:	1.81 dBi for 5180-5240MHz 4.45 dBi for 5745-5825MHz			

2.3 Special Accessories

The following is the EUT test of the auxiliary equipment provided by the laboratory:

Description	Manufacturer	Model	Technical Parameters	Certificate	Provided by
/	/	/	/	/	/

2.4 Modifications

No modifications were implemented to meet testing criteria.

3 TEST ENVIRONMENT

3.1 Address of the test laboratory

Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community,
Fuhai Street, Bao'an District, Shenzhen, China

3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 517856 Designation Number: CN1318

Shenzhen CTA Testing Technology Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

A2LA-Lab Cert. No.: 6534.01

Shenzhen CTA Testing Technology Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.

ISED#: 27890 CAB identifier: CN0127

Shenzhen CTA Testing Technology Co., Ltd. has been listed by Innovation, Science and Economic Development Canada to perform electromagnetic emission measurement.

3.3 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 2" and is documented in the Shenzhen CTA Testing Technology Co., Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen CTA Testing Technology Co., Ltd. :

Test	Range	Measurement Uncertainty	Notes
Radiated Emission	9KHz~30MHz	3.02 dB	(1)
Radiated Emission	30~1000MHz	4.06 dB	(1)
Radiated Emission	1~18GHz	5.14 dB	(1)
Radiated Emission	18-40GHz	5.38 dB	(1)
Conducted Disturbance	0.15~30MHz	2.14 dB	(1)
Output Peak power	30MHz~18GHz	0.55 dB	(1)
Power spectral density	/	0.57 dB	(1)
Spectrum bandwidth	/	1.1%	(1)
Radiated spurious emission (30MHz-1GHz)	30~1000MHz	4.10 dB	(1)
Radiated spurious emission (1GHz-18GHz)	1~18GHz	4.32 dB	(1)
Radiated spurious emission (18GHz-40GHz)	18-40GHz	5.54 dB	(1)
Time	/	±2%	(1)

Shenzhen CTA Testing Technology Co., Ltd.

Room 106, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, China

Tel: +86-755 2322 5875 E-mail: cta@cta-test.cn Web: http://www.cta-test.cn

4 Test limit

4.1 Requirement

According to KDB447498 D01 General RF Exposure Guidance v06 Section 4.3.1 Standalone SAR test exclusion considerations: "Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Test Exclusion Threshold condition, listed below, is satisfied. These test exclusion conditions are based on source-based time-averaged maximum conducted output power of the RF channel requiring evaluation, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions.²² The minimum test separation distance is determined by the smallest distance from the antenna and radiating structures or outer surface of the device, according to the host form factor, exposure conditions and platform requirements, to any part of the body or extremity of a user or bystander (see 5) of section 4.1). To qualify for SAR test exclusion, the test separation distances applied must be fully explained and justified by the operating configurations and exposure conditions of the transmitter and applicable host platform requirements, typically in the SAR measurement or SAR analysis report, according to the required published RF exposure KDB procedures. When no other RF exposure testing or reporting is required, a statement of justification and compliance must be included in the equipment approval, in lieu of the SAR report, to qualify for the SAR test exclusion. When required, the device specific conditions described in the other published RF exposure KDB procedures must be satisfied before applying these SAR test exclusion provisions; for example, handheld PTT two-way radios, handsets, laptops & tablets etc.²³ "

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f \text{ (GHz)}}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where:}$$

- f (GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

4.2 Conducted Power Results

Type	Channel	Output power (dBm)
GFSK 1Mbps	00	0.19
	19	0.11
	39	-0.11

Type	Channel	Output power (dBm)
GFSK	00	0.29
	39	0.17
	78	-0.12
$\pi/4$ DQPSK	00	2.91
	39	2.74
	78	2.53
8DPSK	00	3.39
	39	3.15
	78	2.96

Type	Channel	Output power PK (dBm)
802.11b	01	-7.23
	06	-7.66
	11	-7.57
802.11g	01	-1.78
	06	-2.60
	11	-3.08
802.11n(HT20)	01	-6.39
	06	-6.93
	11	-7.47

Test Mode	Antenna	Freq(MHz)	Result [dBm]
11A	Ant1	5180	-6.80
		5220	-7.51
		5240	-8.04
		5745	-10.10
		5785	-10.81
		5825	-10.79
11N20SISO	Ant1	5180	-6.86
		5220	-7.52
		5240	-8.21
		5745	-9.91
		5785	-10.59
		5825	-10.78

4.3 Manufacturing tolerance

Mode	Max. Peak Conducted Output Power (dBm)	Max. tune-up
BLE	0.19	0.0 ± 1
BR/EDR	3.39	2.5 ± 1
2.4GWIFI	-1.78	-2.0 ± 1
Mode	Max. Average Conducted Output Power (dBm)	Max. tune-up
5.2GWIFI	-6.80	-7.0 ± 1
5.8GWIFI	-9.91	-10.0 ± 1

4.4 Evaluation Result

Evaluation Results

Band/Mode	f (GHz)	Antenna Distance (mm)	RF output power (including tune-up tolerance)		SAR Test Exclusion Threshold	SAR Test Exclusion Threshold Limit	SAR Test Exclusion
			dBm	mW			
BLE	2.480	5	1.0	1.2589	0.3965	3.0	Yes
BR/EDR	2.480	5	3.5	2.2387	0.7051	3.0	Yes
2.4G WIFI	2.462	5	-1.0	0.7943	0.2493	3.0	Yes
5.2G WIFI	5.240	5	-6.0	0.2512	0.1150	3.0	Yes
5.8G WIFI	5.825	5	-9.0	0.1259	0.0608	3.0	Yes

4.5 Simultaneous Transmission for SAR Exclusion

N/A

5 Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1093 for the uncontrolled RF Exposure and SAR Exclusion Threshold per KDB 447498 D01v06

***** End of Report *****