

RADIO TEST REPORT

Test Report No. 16480071H

Customer	DENSO CORPORATION
Description of EUT	Electronic Key
Model Number of EUT	14AHW
FCC ID	HYQ14AHW
Test Regulation	FCC Part 15 Subpart C
Test Result	Complied
Issue Date	September 28, 2026
Remarks	-

Representative test engineerHiroki Numata
Engineer**Approved by**Shinichi Miyazono
Test report signatory

CERTIFICATE 5107.02

- ☐ The testing in which "Non-accreditation" is displayed is outside the accreditation scopes in UL Japan, Inc.
- ☒ There is no testing item of "Non-accreditation".

Report Cover Page - Form-ULID-003532 (DCS:13-EM-F0429) Issue# 27.0

ANNOUNCEMENT

- This test report shall not be reproduced in full or partial, without the written approval of UL Japan, Inc.
- The results in this report apply only to the sample tested. (Laboratory was not involved in sampling.)
- This sample tested is in compliance with the limits of the above regulation.
- The test results in this test report are traceable to the national or international standards.
- This test report must not be used by the customer to claim product certification, approval, or endorsement by the A2LA accreditation body.
- This test report shall not be relied upon or used in support of any Federal Communications Commission ("FCC") approval where the subject device constitutes "covered equipment" as defined under <https://www.fcc.gov/supplychain/coveredlist>, except where a Conditional Approval has been granted for the equipment. The responsible party, as defined in FCC rules, shall bear sole responsibility for reviewing the FCC Covered List and determining its applicability to the equipment.
- This test report covers Radio technical requirements.
It does not cover administrative issues such as Manual or non-Radio test related Requirements. (if applicable)
- The all test items in this test report are conducted by UL Japan, Inc. Ise EMC Lab.
- The opinions and the interpretations to the result of the description in this report are outside scopes where UL Japan, Inc. has been accredited.
- The information provided by the customer for this report is identified in SECTION 1.
- The laboratory is not responsible for information provided by the customer which can impact the validity of the results.
- For any test report referred in this report, the latest version (including any revisions) is always referred to.
- If the latest version is a revision, it replaces the previous version. See the table below for revisions and versions.

REVISION HISTORY

Revision	Test Report No.	Date	Page Revised Contents
- (Original)	16480071H	September 28, 2026	-

Reference: Abbreviations (Including words undescribed in this report)

A2LA	The American Association for Laboratory Accreditation	ICES	Interference-Causing Equipment Standard
AC	Alternating Current	IEC	International Electrotechnical Commission
AFH	Adaptive Frequency Hopping	IEEE	Institute of Electrical and Electronics Engineers
AM	Amplitude Modulation	IF	Intermediate Frequency
Amp, AMP	Amplifier	ILAC	International Laboratory Accreditation Conference
ANSI	American National Standards Institute	ISED	Innovation, Science and Economic Development Canada
Ant, ANT	Antenna	ISO	International Organization for Standardization
AP	Access Point	JAB	Japan Accreditation Board
ASK	Amplitude Shift Keying	LAN	Local Area Network
Atten., ATT	Attenuator	LIMS	Laboratory Information Management System
AV	Average	MCS	Modulation and Coding Scheme
BPSK	Binary Phase-Shift Keying	MRA	Mutual Recognition Arrangement
BR	Bluetooth Basic Rate	N/A	Not Applicable
BT	Bluetooth	NIST	National Institute of Standards and Technology
BT LE	Bluetooth LE	NS	No signal detect.
BW	BandWidth	NSA	Normalized Site Attenuation
Cal Int	Calibration Interval	NVLAP	National Voluntary Laboratory Accreditation Program
CCK	Complementary Code Keying	OBW	Occupied Band Width
Ch., CH	Channel	OFDM	Orthogonal Frequency Division Multiplexing
CISPR	Comite International Special des Perturbations Radioelectriques	P/M	Power meter
CW	Continuous Wave	PCB	Printed Circuit Board
DBPSK	Differential BPSK	PER	Packet Error Rate
DC	Direct Current	PHY	Physical Layer
D-factor	Distance factor	PK	Peak
DFS	Dynamic Frequency Selection	PN	Pseudo random Noise
DQPSK	Differential QPSK	PRBS	Pseudo-Random Bit Sequence
DSSS	Direct Sequence Spread Spectrum	PSD	Power Spectral Density
EDR	Enhanced Data Rate	QAM	Quadrature Amplitude Modulation
EIRP, e.i.r.p.	Equivalent Isotropically Radiated Power	QP	Quasi-Peak
EMC	ElectroMagnetic Compatibility	QPSK	Quadri-Phase Shift Keying
EMI	ElectroMagnetic Interference	RBW	Resolution Band Width
EN	European Norm	RDS	Radio Data System
ERP, e.r.p.	Effective Radiated Power	RE	Radio Equipment
EU	European Union	RF	Radio Frequency
EUT	Equipment Under Test	RMS	Root Mean Square
Fac.	Factor	RSS	Radio Standards Specifications
FCC	Federal Communications Commission	Rx	Receiving
FHSS	Frequency Hopping Spread Spectrum	SA, S/A	Spectrum Analyzer
FM	Frequency Modulation	SG	Signal Generator
Freq.	Frequency	SVSWR	Site-Voltage Standing Wave Ratio
FSK	Frequency Shift Keying	TR	Test Receiver
GFSK	Gaussian Frequency-Shift Keying	Tx	Transmitting
GNSS	Global Navigation Satellite System	VBW	Video BandWidth
GPS	Global Positioning System	Vert.	Vertical
Hori.	Horizontal	WLAN	Wireless LAN

CONTENTS	PAGE
SECTION 1: Customer Information	5
SECTION 2: Equipment Under Test (EUT).....	5
SECTION 3: Test Summary	6
SECTION 4: Operation of EUT during testing	9
SECTION 5: Radiated Spurious Emission.....	10
SECTION 6: Automatically deactivate	12
SECTION 7: -20 dB Bandwidth and 99% emission bandwidth	12
APPENDIX 1: Test Data	13
Automatically deactivate	13
Radiated Emission (Fundamental and Spurious Emission).....	14
-20 dB Bandwidth / 99% emission bandwidth.....	16
APPENDIX 2: Test Instruments	17
APPENDIX 3: Photographs of Test Setup	18
Radiated Spurious Emission.....	18
Worst Case Position	20

SECTION 1: Customer Information

Company Name	DENSO CORPORATION
Address	1-1, Showa-cho, Kariya-shi, Aichi-ken, 448-8661, Japan
Telephone Number	+81-50-1727-0009
Contact Person	Koji Yamashita

The information provided by the customer is as follows;

- Customer, Description of EUT, Model Number of EUT, FCC ID on the cover and other relevant pages
- Operating/Test Mode(s) (Mode(s)) on all the relevant pages
- SECTION 1: Customer Information
- SECTION 2: Equipment Under Test (EUT) other than the Receipt Date and Test Date
- SECTION 4: Operation of EUT during testing

SECTION 2: Equipment Under Test (EUT)

2.1 Identification of EUT

Description	Electronic Key
Model Number	14AHW
Serial Number	Refer to SECTION 4.2
Condition	Production prototype (Not for Sale: This sample is equivalent to mass-produced items.)
Modification	No Modification by the test lab
Receipt Date	September 4, 2026
Test Date	September 13, 2026

2.2 Product Description

General Specification

Rating	DC 3 V
--------	--------

Radio Specification

Equipment Type	Transmitter
Frequency of Operation	433.92 MHz
Type of Modulation	FSK (F1D)
Type of Battery	One lithium battery
Antenna type	Built-in type (Fixed)

Equipment Type	Receiver
Frequency of Operation	125 kHz

SECTION 3: Test Summary

3.1 Test Specification

Test Specification	FCC Part 15 Subpart C The latest version on the first day of the testing period
Title	FCC 47CFR Part15 Radio Frequency Device Subpart C Intentional Radiators Section 15.231 Periodic operation in the band 40.66-40.70 MHz and above 70 MHz.

3.2 Reference Standards

ANSI/USEMCSC C63.2-2023
ANSI C63.4-2014/C63.4a-2017
ANSI C63.5-2017
ANSI C63.10-2020
ANSI/USEMCSC C63.10/Cor 1-2023
ANSI/USEMCSC C63.10a-2024 (incl. Errata)
ANSI C63.25.1-2018

3.3 Summary of Test Results

Item	Specification	Results	Remarks
Conducted emission	FCC: Section 15.207 ISED: RSS-Gen 8.8	N/A	*1)
Automatically deactivate	FCC: Section 15.231(a)(1) ISED: RSS-210 A1.2	Complied	Radiated
Electric Field Strength of Fundamental Emission	FCC: Section 15.231(b) ISED: RSS-210 A1.3	Complied	Radiated
Electric Field Strength of Spurious Emission	FCC: Section 15.205 Section 15.209 Section 15.231(b) ISED: RSS-210 A1.3 RSS-Gen 8.9	Complied	Radiated
-20 dB Bandwidth	FCC: Section 15.231(c) ISED: Reference data	Complied	Radiated

Note: UL Japan, Inc.'s EMI Work Procedures: Work Instructions-ULID-003591 and Work Instructions-ULID-003593.
*1) The test is not applicable since the EUT does not have AC Mains.

FCC Part 15.31 (e)

The test was performed with the New Battery during the tests.
Therefore, this EUT complies with the requirement.

FCC Part 15.203 Antenna requirement

It is impossible for end users to replace the antenna, because the antenna is mounted inside of the EUT.
Therefore, the equipment complies with the antenna requirement of Section 15.203.

3.4 Addition to Standard

Item	Specification	Results	Remarks
99% emission bandwidth	FCC: Reference data	-	Radiated

Note: UL Japan, Inc.'s EMI Work Procedures: Work Instructions-ULID-003591 and Work Instructions-ULID-003593.

Other than above, no addition, exclusion nor deviation has been made from the standard.

3.5 Uncertainty

Measurement uncertainty is not taken into account when stating conformity with a specified requirement.
Note: When margins obtained from test results are less than the measurement uncertainty, the test results may exceed the limit.

The following uncertainties have been calculated to provide a confidence level of 95 % using a coverage factor $k = 2$.

Radiated emission

Measurement distance	Frequency range		Unit	Calculated Uncertainty (+/-)
3 m	9 kHz to 30 MHz		dB	4.8
10 m			dB	4.7
3 m	30 MHz to 200 MHz	Horizontal	dB	5.0
		Vertical	dB	5.0
	200 MHz to 1000 MHz	Horizontal	dB	5.2
		Vertical	dB	6.2
10 m	30 MHz to 200 MHz	Horizontal	dB	5.5
		Vertical	dB	5.4
	200 MHz to 1000 MHz	Horizontal	dB	5.5
		Vertical	dB	5.5
3 m	1 GHz to 6 GHz		dB	5.1
	6 GHz to 18 GHz		dB	5.5
1 m	6 GHz to 18 GHz		dB	5.5
	18 GHz to 26.5 GHz		dB	5.7
	26.5 GHz to 40 GHz		dB	4.8
0.5 m	18 GHz to 40 GHz		dB	5.8

Automatically deactivate, -20 dB Bandwidth and 99% Occupied Bandwidth

Item	Unit	Calculated Uncertainty (+/-)
Bandwidth (OBW)	%	0.96
Time readout (time span upto 100 msec)	%	0.11
Time readout (time span upto 1000 msec)	%	0.11
Time readout (time span upto 60 sec)	%	0.02

3.6 Test Location

UL Japan, Inc. Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 Japan

Telephone: +81-596-24-8999

*A2LA Certificate Number: 5107.02 / FCC Test Firm Registration Number: 884919

ISED Lab Company Number: 2973C / CAB identifier: JP0002

Test site	Width x Depth x Height (m)	Size of reference ground plane (m) / horizontal conducting plane	Other rooms	Maximum measurement distance
No.1 semi-anechoic chamber (SAC1)	19.2 x 11.2 x 7.7	7.0 x 6.0	No.1 Power source room	10 m
No.2 semi-anechoic chamber (SAC2)	7.5 x 5.8 x 5.2	4.0 x 4.0	-	3 m
No.3 semi-anechoic chamber (SAC3)	12.0 x 8.5 x 5.9	6.8 x 5.75	No.3 Preparation room (PR3)	3 m
No.3 shielded room (SR3)	4.0 x 6.0 x 2.7	N/A	-	-
No.4 semi-anechoic chamber (SAC4)	12.0 x 8.5 x 5.9	6.8 x 5.75	No.4 Preparation room (PR4)	3 m
No.4 shielded room (SR4)	4.0 x 6.0 x 2.7	N/A	-	-
No.5 semi-anechoic chamber (SAC5)	6.0 x 6.0 x 3.9	6.0 x 6.0	-	-
No.5 measurement room (MR5)	6.4 x 6.4 x 3.0	6.4 x 6.4	-	-
No.6 shielded room (SR6)	4.0 x 4.5 x 2.7	4.0 x 4.5	-	-
No.6 measurement room (MR6)	4.75 x 5.4 x 3.0	4.75 x 4.15	-	-
No.7 shielded room (SR7)	4.7 x 7.5 x 2.7	4.7 x 7.5	-	-
No.8 measurement room (MR8)	3.1 x 5.0 x 2.7	3.1 x 5.0	-	-
No.9 measurement room (MR9)	8.8 x 4.6 x 2.8	2.4 x 2.4	-	-
No.10 shielded room (SR10)	3.8 x 2.8 x 2.8	3.8 x 2.8	-	-
No.11 measurement room (MR11)	4.0 x 3.4 x 2.5	N/A	-	-
No.12 measurement room (MR12)	2.6 x 3.4 x 2.5	N/A	-	-
Large Chamber	16.9 x 22.1 x 10.17	16.9 x 22.1	-	10 m
Small Chamber	5.3 x 6.69 x 3.59	5.3 x 6.69	-	-

3.7 Test Data, Test Instruments, and Test Set Up

Refer to APPENDIX.

SECTION 4: Operation of EUT during testing


4.1 Operating Mode(s)

Test mode	Remarks
1) Normal use mode (Tx 433.92 MHz)	-
2) Transmitting mode (Tx 433.92 MHz) *1)	-
* The system was configured in typical fashion (as a user would normally use it) for testing.	
*Power of the EUT was set by the software as follows; Software: Product program Version: 01100401 (Date: 2026.09.13, Storage location: EUT memory)	
*This setting of software is the worst case. Any conditions under the normal use do not exceed the condition of setting. In addition, end users cannot change the settings of the output power of the product.	
Justification: The system was configured in typical fashion (as a user would normally use it) for testing.	

*1) The software of this mode is the same as one of normal product, except that EUT continues to transmit (For Normal use mode, EUT stops to transmit in a given time, even if transceiver button is being pressed.).

This EUT has two modes which mechanical key is inserted or not. The worst case was confirmed with and without mechanical key inserted, as a result, the test without mechanical key inserted was the worst case. Therefore, the test without mechanical key inserted was performed only.

4.2 Configuration and Peripherals



*Setup was taken into consideration and test data was taken under worse case conditions.

Description of EUT

No.	Item	Model number	Serial Number	Manufacturer	Remark
A	Electronic Key	14AHW	No3 *1) No1 *2)	DENSO CORPORATION	EUT

*1) Used for Automatically deactivate test

*2) Used for other tests except for Automatically deactivate

SECTION 5: Radiated Spurious Emission

Test Procedure

[For below 30 MHz]

The noise level was checked by moving a search-coil (Loop Antenna) close to the EUT.

[For 30 MHz to 1 GHz]

EUT was placed on the platform of nominal size, 1.0 m by 1.5 m, raised 0.8 m above the conducting ground plane.

The Radiated Electric Field Strength has been measured in a Semi Anechoic Chamber with a ground plane.

[For above 1 GHz]

EUT was placed on the platform of nominal size, 0.5 m by 0.5 m, raised 1.5 m above the conducting ground plane.

The Radiated Electric Field Strength has been measured in a Semi Anechoic Chamber with absorbent materials lined on a ground plane.

The measuring antenna height was varied between 1 and 4 m and EUT was rotated a full revolution in order to obtain the maximum value of the electric field strength.

Test antenna was aimed at the EUT for receiving the maximum signal and always kept within the illumination area of the 3 dB beamwidth of the antenna.

The measurements were performed for both vertical and horizontal antenna polarization.

The radiated emission measurements were made with the following detector function of the test receiver / spectrum analyzer.



Test Antennas are used as below;

Frequency	Below 30 MHz	30 MHz to 200 MHz	200 MHz to 1 GHz	Above 1 GHz
Antenna Type	Loop	Biconical	Logperiodic	Horn

Setting;

Frequency	From 9 kHz to 90 kHz and From 110 kHz to 150 kHz	From 90 kHz to 110 kHz	From 150 kHz to 490 kHz	From 490 kHz to 30 MHz	From 30 MHz to 1 GHz	Above 1 GHz
Instrument Used	Test Receiver				Test Receiver	Spectrum Analyzer
Detector Type	Peak				Peak, Peak with Duty factor	Peak, Peak with Duty factor
Bandwidth setting	BW: 200 Hz		BW: 9 kHz		BW: 120 kHz	PK: RBW: 1 MHz, VBW: 3 MHz

[Test Setup]

Below 1 GHz	
 × : Center of turn table	Test Distance: 3 m
1 GHz to 4.4 GHz	
 × : Center of turn table	Test Distance: 3 m

- The carrier level and noise levels were confirmed at each position of X, Y and Z axes of EUT to see the position of maximum noise, and the test was made at the position that has the maximum noise.

The test results and limit are rounded off to one decimal place, so some differences might be observed.

Measurement range : 9 kHz to 4.4 GHz
Test data : APPENDIX
Test result : Pass

SECTION 6: Automatically deactivate

Test Procedure

The measurement was performed with Electric field strength using a spectrum analyzer.

Test data : APPENDIX
Test result : Pass

SECTION 7: -20 dB Bandwidth and 99% emission bandwidth

Test Procedure

The test was measured with a spectrum analyzer using a test fixture.

Test	Span	RBW	VBW	Sweep	Detector	Trace	Instrument used
-20 dB Bandwidth	2 to 5 times of OBW	1 to 5 % of OBW	Three times of RBW	Auto	Peak *1)	Max Hold *1)	Spectrum Analyzer
99% emission bandwidth	1.5 to 5 times of OBW	1 to 5 % of OBW	Three times of RBW	Auto	Peak *1)	Max Hold *1)	Spectrum Analyzer

*1) Peak hold was applied as Worst-case measurement.


Test data : APPENDIX
Test result : Pass

APPENDIX 1: Test Data

Automatically deactivate

Mode	Mode 1			
Date	Test site	Temperature	Humidity	Engineer
September 13, 2026	SAC4	23 deg. C	60 % RH	Hiroki Numata

Time of Transmitting [s]	Limit [s]	Result
0.7206	5.00	Pass



*The EUT transmits UHF when LF signal is received from a car or a button on the EUT is pressed. In both cases, the UHF transmission is stopped within 5 seconds. So the test was performed by a button-pressed operation as the worst case.

Radiated Emission (Fundamental and Spurious Emission)

Mode	Mode 2
------	--------

Date	Test site	Temperature	Humidity	Engineer	Measurement Range
September 13, 2026	SAC4	23 deg. C	60 % RH	Hiroki Numata	30 MHz to 4.4 GHz

Polarity [Hori/Vert]	Frequency [MHz]	Reading (PK) [dBuV]	Ant Factor [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Result (PK) [dBuV/m]	Result (PK with Duty Factor) [dBuV/m]	Limit (PK) [dBuV/m]	Limit (AV) [dBuV/m]	Margin (PK) [dB]	Margin (AV) [dB]	Inside or Outside of Restricted Bands	Remarks
Hori.	433.920	80.8	16.3	10.4	32.2	0.0	75.3	75.3	100.8	80.8	25.5	5.5	Carrier	
Hori.	867.840	36.0	22.1	12.5	31.3	0.0	39.3	39.3	80.8	60.8	41.5	21.5	Outside	
Hori.	1301.760	45.1	25.5	2.2	34.0	-	38.8	38.8	73.9	53.9	35.1	15.1	Inside	Floor noise
Hori.	1735.680	49.5	25.1	2.3	32.9	0.0	44.0	44.0	80.8	60.8	36.8	16.8	Outside	
Hori.	2169.600	44.6	27.9	2.4	32.1	-	42.8	42.8	80.8	60.8	38.0	18.0	Outside	Floor noise
Hori.	2603.520	44.3	27.9	2.6	31.8	0.0	43.0	43.0	80.8	60.8	37.8	17.8	Outside	
Hori.	3037.440	43.2	28.6	2.8	31.6	0.0	43.0	43.0	80.8	60.8	37.8	17.8	Outside	
Hori.	3471.360	46.3	28.6	3.0	31.4	0.0	46.5	46.5	80.8	60.8	34.3	14.3	Outside	
Hori.	3905.280	43.3	29.6	3.2	31.2	0.0	44.9	44.9	73.9	53.9	29.0	9.0	Inside	
Hori.	4339.200	44.3	30.5	3.4	31.0	0.0	47.2	47.2	73.9	53.9	26.7	6.7	Inside	
Vert.	433.920	81.9	16.3	10.4	32.2	0.0	76.4	76.4	100.8	80.8	24.4	4.4	Carrier	
Vert.	867.840	31.3	22.1	12.5	31.3	0.0	34.6	34.6	80.8	60.8	46.2	26.2	Outside	
Vert.	1301.760	46.2	25.5	2.2	34.0	-	39.9	39.9	73.9	53.9	34.0	14.0	Inside	Floor noise
Vert.	1735.680	48.9	25.1	2.3	32.9	0.0	43.4	43.4	80.8	60.8	37.4	17.4	Outside	
Vert.	2169.600	43.6	27.9	2.4	32.1	-	41.8	41.8	80.8	60.8	39.0	19.0	Outside	Floor noise
Vert.	2603.520	44.4	27.9	2.6	31.8	0.0	43.1	43.1	80.8	60.8	37.7	17.7	Outside	
Vert.	3037.440	46.0	28.6	2.8	31.6	0.0	45.8	45.8	80.8	60.8	35.0	15.0	Outside	
Vert.	3471.360	45.0	28.6	3.0	31.4	0.0	45.2	45.2	80.8	60.8	35.6	15.6	Outside	
Vert.	3905.280	43.2	29.6	3.2	31.2	0.0	44.8	44.8	73.9	53.9	29.1	9.1	Inside	
Vert.	4339.200	44.5	30.5	3.4	31.0	0.0	47.4	47.4	73.9	53.9	26.5	6.5	Inside	

Sample calculation:

Result of PK = Reading + Ant Factor + Loss {Cable + Attenuator + Filter (above 1 GHz)} - Gain (Amplifier)

Result of PK with Duty factor (PK / W) = Reading + Ant Factor + Loss {Cable + Attenuator + Filter (above 1 GHz)} - Gain (Amplifier) + Duty factor

*Other frequency noises omitted in this report were not seen or had enough margin (more than 20 dB).



Since the peak emission result satisfied the average limit, duty factor was omitted.

Although Duty of this product was 100% or less, the result of AV (PK with Duty factor) was calculated by applying Duty 100 % as worst.

If Gain 0.0 dB shown in the above table, pre-amplifier was not used to avoid the influence of carrier power. The pre-amplifier used for carrier frequency measurement was not saturated.

Radiated Spurious Emission
(Plot data, Worst case for Fundamental Emission)

Mode	Mode 2				
Date	Test site	Temperature	Humidity	Engineer	Measurement Range
September 13, 2026	SAC4	23 deg. C	60 % RH	Hiroki Numata	30 MHz to 4.4 GHz



-20 dB Bandwidth / 99% emission bandwidth


Mode	Mode 2
------	--------

Date	Test site	Temperature	Humidity	Engineer
September 13, 2026	SAC4	23 deg. C	60 % RH	Hiroki Numata

Bandwidth Limit : Fundamental Frequency 433.92 MHz x 0.25 % = 1084.800 kHz

-20 dB Bandwidth [kHz]	Bandwidth Limit [kHz]	Result
70.2520	1084.800	Pass

99% emission bandwidth [kHz]	Bandwidth Limit [kHz]	Result
76.9602	1084.800	Pass



APPENDIX 2: Test Instruments

Test Equipment

Test Item	LIMS ID	Description	Manufacturer	Model	Serial	Last Calibration Date	Cal Int
RE	141397	Coaxial Cable	UL-ISE EMC	-	-	09/07/2026	12
RE	141425	Biconical Antenna	Schwarzbeck Mess-Elektronik OHG	VHA9103+BBA9106	VHA 91031302	08/13/2026	12
RE	141508	Horn Antenna 1-18GHz	Schwarzbeck Mess-Elektronik OHG	BBHA9120D	557	05/19/2026	12
RE	141581	MicroWave System Amplifier	Keysight Technologies Inc	83017A	00650	09/11/2026	12
RE	141583	Pre Amplifier	SONOMA INSTRUMENT	310	260833	04/16/2026	12
RE	141902	Spectrum Analyzer	Keysight Technologies Inc	E4440A	MY46187105	10/06/2025	12
RE	141951	EMI Test Receiver	Rohde & Schwarz	ESR26	101408	06/11/2026	12
RE	142011	AC4_Semi Anechoic Chamber(NSA)	TDK	Semi Anechoic Chamber 3m	DA-10005	07/10/2025	24
RE	142017	AC4_Semi Anechoic Chamber(SVSWR)	TDK	Semi Anechoic Chamber 3m	DA-10005	04/17/2025	24
RE	142230	Measure, Tape, Steel	KOMELON	KMC-36	-	-	-
RE	178648	EMI measurement program	TSJ (Techno Science Japan)	TEPTO-DV	-	-	-
RE	220646	Attenuator	Huber+Suhner	6806 N-50-1	-	03/06/2026	12
RE	242170	Logperiodic Antenna	Schwarzbeck Mess-Elektronik OHG	VUSLP9111B	00728	01/15/2026	12
RE	242978	High Pass Filter 1-13 GHz	Pasternak	PE87FL1018	D.C. 2215	02/09/2026	12
RE	244710	Thermo-Hygrometer	HIOKI E. E. CORPORATION	LR5001	231202104	01/14/2026	12
RE	272098	DIGITAL MULTIMETER	HIOKI E. E. CORPORATION	DT4255	250902199	11/27/2025	12
RE	276744	Microwave cable	Huber+Suhner	SF103/11PC35/11PC35/1000mm / SF126E/11PC35/5000mm	800674 /3(1m) / 616530/126E(5m)	03/17/2026	12
RE	202511	Loop Antenna	UL-ISE	-	-	-	-

*Hyphens for Last Calibration Date and Cal Int (month) are instruments that Calibration is not required (e.g. software), or instruments checked in advance before use.

The expiration date of the calibration is the end of the expired month.

As for some calibrations performed after the tested dates, those test equipment have been controlled by means of an unbroken chains of calibrations.

All equipment is calibrated with valid calibrations. Each measurement data is traceable to the national or international standards.

Test item:

RE: Radiated Emission