

FCC RF EXPOSURE REPORT

FCC ID: I46INF6501C

Project No. : 1412C151
Equipment : TouchScreen Displays
Model : INF6501c
Applicant : InFocus Corporation
Address : 13190 SW 68th Parkway Suite 200 Portland,
OR 97223-8368

According: : FCC Guidelines for Human Exposure IEEE
C95.1

B T L I N C .

No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan, China.
TEL: +86-769-8318-3000 FAX: +86-769-8319-6000

MPE CALCULATION METHOD:

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi^2} = \frac{EIRP}{4\pi^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain(dBi)	Note
1		ANTS71L-DJ65 1-DH	Internal	N/A	-2.92	TX/RX

TEST RESULTS

EUT :	TouchScreen Displays	Model Name :	InFocus
Temperature :	25 °C	Relative Humidity:	55 %
Test Voltage :	AC 120V/60Hz		
Test Mode :	UNII-1/TX A Mode		

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
-2.35	0.5821	12.97	19.8153	0.00229589	1	Complies
-2.35	0.5821	13.03	20.0909	0.00232783	1	Complies
-2.35	0.5821	13.01	19.9986	0.00231713	1	Complies

EUT :	TouchScreen Displays	Model Name :	InFocus
Temperature :	25 °C	Relative Humidity:	55 %
Test Voltage :	AC 120V/60Hz		
Test Mode :	UNII-1/TX N20 Mode		

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
-2.35	0.5821	10.75	11.8850	0.00137705	1	Complies
-2.35	0.5821	11.01	12.6183	0.00146201	1	Complies
-2.35	0.5821	10.86	12.1899	0.00141238	1	Complies

EUT :	TouchScreen Displays	Model Name :	InFocus
Temperature:	25 °C	Relative Humidity:	55 %
Test Voltage :	AC 120V/60Hz		
Test Mode :	UNII-2A/TX A Mode		

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
-2.35	0.5821	13.03	20.0909	0.00232783	1	Complies
-2.35	0.5821	13.05	20.1837	0.00233857	1	Complies
-2.35	0.5821	12.97	19.8153	0.00229589	1	Complies

EUT :	TouchScreen Displays	Model Name :	InFocus
Temperature:	25 °C	Relative Humidity:	55 %
Test Voltage :	AC 120V/60Hz		
Test Mode :	UNII-2A/TX N20 Mode		

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
-2.35	0.5821	10.79	11.9950	0.00138979	1	Complies
-2.35	0.5821	10.92	12.3595	0.00143202	1	Complies
-2.35	0.5821	10.72	11.8032	0.00136757	1	Complies

EUT :	TouchScreen Displays	Model Name :	InFocus
Temperature:	25 °C	Relative Humidity:	55 %
Test Voltage :	AC 120V/60Hz		
Test Mode :	UNII-2C/TX A Mode		

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
-2.35	0.5821	13.06	20.2302	0.00234396	1	Complies
-2.35	0.5821	12.81	19.0985	0.00221284	1	Complies
-2.35	0.5821	12.27	16.8655	0.00195412	1	Complies

EUT :	TouchScreen Displays	Model Name :	InFocus
Temperature:	25 °C	Relative Humidity:	55 %
Test Voltage :	AC 120V/60Hz		
Test Mode :	UNII-2C/TX N20 Mode		

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
-2.35	0.5821	11.01	12.6183	0.00146201	1	Complies
-2.35	0.5821	10.76	11.9124	0.00138023	1	Complies
-2.35	0.5821	10.59	11.4551	0.00132724	1	Complies

EUT :	TouchScreen Displays	Model Name :	InFocus
Temperature:	25 °C	Relative Humidity:	55 %
Test Voltage :	AC 120V/60Hz		
Test Mode :	UNII-3/ TX A Mode		

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
-2.35	0.5821	13.06	20.2302	0.00234396	1	Complies
-2.35	0.5821	13.04	20.1372	0.00233319	1	Complies
-2.35	0.5821	13.05	20.1837	0.00233857	1	Complies

EUT :	TouchScreen Displays	Model Name :	InFocus
Temperature:	25 °C	Relative Humidity:	55 %
Test Voltage :	AC 120V/60Hz		
Test Mode :	UNII-3/TX N20 Mode		

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
-2.35	0.5821	11.01	12.6183	0.00146201	1	Complies
-2.35	0.5821	11.06	12.7644	0.00147894	1	Complies
-2.35	0.5821	11.07	12.7938	0.00148235	1	Complies

Note: the calculated distance is 20 cm.