

RF Exposure Report

Report No.: SA190806E11

FCC ID: I88EX5510-B0

Test Model: EX5510-B0, PX7511-B0, DX5510-B0

Received Date: Aug. 06, 2019

Test Date: Aug. 26, 2019

Issued Date: Oct. 04, 2019

Applicant: Zyxel Communications Corporation

Address: No.2 Industry East RD. IX, Hsinchu Science Park, Hsinchu 30075, Taiwan

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan.

Test Location: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan.

**FCC Registration /
Designation Number:** 723255 / TW2022

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

Release Control Record	3
1 Certificate of Conformity.....	4
2 RF Exposure.....	5
2.1 Limits For Maximum Permissible Exposure (MPE).....	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
2.4 Antenna Gain	6
2.5 Calculation Result of Maximum Conducted Power	7

Release Control Record

Issue No.	Description	Date Issued
SA190806E11	Original release.	Oct. 04, 2019

1 Certificate of Conformity

Product: Dual-Band Wireless AX Gigabit Ethernet Gateway,
Wireless AX 10G PON Gateway with VoIP,
Wireless AX VDSL Bonding Gateway

Brand: ZYXEL

Test Model: EX5510-B0, PX7511-B0, DX5510-B0

Sample Status: ENGINEERING SAMPLE

Applicant: Zyxel Communications Corporation

Test Date: Aug. 26, 2019

Standards: FCC Part 2 (Section 2.1091)
KDB 447498 D01 General RF Exposure Guidance v06
IEEE C95.1-1992

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by : Wendy Wu , **Date:** Oct. 04, 2019
Wendy Wu / Specialist

Approved by : May Chen , **Date:** Oct. 04, 2019
May Chen / Manager

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	...	...	f/1500	30
1500-100,000	...	...	1.0	30

f = Frequency in MHz ; *Plane-wave equivalent power density

2.2 MPE Calculation Formula

$$Pd = (P_{out} * G) / (4 * \pi * r^2)$$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416


R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 27cm away from the body of the user.
So, this device is classified as **Mobile Device**.

2.4 Antenna Gain

Ant. No.	Chain No.	Brand	Model	Antenna Gain (dBi)	Frequency range (GHz)	Antenna Type	Connector Type	Cable Length (mm)
1	2G Chain 2	Airgain	65-034-000014B	0.12	2.4~2.4835	Dipole	i-pex (MHF)	150
2	2G Chain 3		65-034-000015B	0.12	2.4~2.4835 5.15~5.85 (5G for RX zero wait DFS)	Dipole	i-pex (MHF)	100
3	2G Chain 0		65-034-000016B	0.12	2.4~2.4835	Dipole	i-pex (MHF)	65
4	2G Chain 1		65-034-000017B	0.12	2.4~2.4835	Dipole	i-pex (MHF)	130
5	5G Chain 2	Airgain	65-034-000018B	0	5.15~5.85	Dipole	i-pex (MHF)	195
6	5G Chain 0		65-034-000019B	0	5.15~5.85	Dipole	i-pex (MHF)	150
7	5G Chain 3		65-034-000020B	0	5.15~5.85	Dipole	i-pex (MHF)	250
8	5G Chain 1		65-034-000021B	0	5.15~5.85	Dipole	i-pex (MHF)	230



2.5 Calculation Result of Maximum Conducted Power

Operation Mode	Evaluation Frequency (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
WLAN 2.4GHz	2437	995.204	6.14	27	0.44666	1
WLAN U-NII-1	5200	975.47	6.02	27	0.42587	1
WLAN U-NII-3	5785	988.981	6.02	27	0.43177	1

NOTE:

1. Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.
2. 2.4GHz: Directional gain = 0.12dBi + 10log(4) = 6.14dBi
5GHz: Directional gain = 0dBi + 10log(4) = 6.02dBi

Conclusion:

The formula of calculated the MPE is:

$$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$$

CPD = Calculation power density

LPD = Limit of power density

$$WLAN\ 2.4GHz + WLAN\ 5GHz = 0.44666 / 1 + 0.43177 / 1 = 0.87843$$

Therefore the maximum calculations of above situations are less than the “1” limit.

--- END ---