FCC TEST REPORT (15.247)

REPORT NO.: RF140605C26

MODEL NO.: NBG6616 (Refer to item 3.1 for more details)

FCC ID: I88NBG6616

RECEIVED: Jun. 05, 2014

TESTED: Jun. 12 ~ Jul. 04, 2014

ISSUED: Jul. 14, 2014

APPLICANT: ZyXEL Communications Corporation

ADDRESS: No. 2, Gongye E. 9th Road Hsinchu Science Park, Hsinchu, Taiwan

ISSUED BY: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan, R.O.C.

TEST LOCATION: No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

This report should not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

TABLE OF CONTENTS

RELEASE CONTROL RECORD 4
1. CERTIFICATION 5
2. SUMMARY OF TEST RESULTS 6
2.1 MEASUREMENT UNCERTAINTY 6
3. GENERAL INFORMATION 7
3.1 GENERAL DESCRIPTION OF EUT 7
3.2 DESCRIPTION OF TEST MODES 9
3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL 10
3.3 DUTY CYCLE OF TEST SIGNAL 12
3.4 DESCRIPTION OF SUPPORT UNITS 13
3.4.1 CONFIGURATION OF SYSTEM UNDER TEST 13
3.5 GENERAL DESCRIPTION OF APPLIED STANDARDS 14
4. TEST TYPES AND RESULTS 15
4.1 RADIATED EMISSION AND BANDEDGE MEASUREMENT 15
4.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT 15
4.1.2 TEST INSTRUMENTS 16
4.1.3 TEST PROCEDURES 17
4.1.4 DEVIATION FROM TEST STANDARD 17
4.1.5 TEST SETUP 18
4.1.6 EUT OPERATING CONDITIONS 19
4.1.7 TEST RESULTS 20
4.2 CONDUCTED EMISSION MEASUREMENT 33
4.2.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT 33
4.2.2 TEST INSTRUMENTS 33
4.2.3 TEST PROCEDURES 34
4.2.4 DEVIATION FROM TEST STANDARD 34
4.2.5 TEST SETUP 34
4.2.6 EUT OPERATING CONDITIONS 34
4.2.7 TEST RESULTS 35
4.3 6dB BANDWIDTH MEASUREMENT 37
4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT 37
4.3.2 TEST SETUP 37
4.3.3 TEST INSTRUMENTS 37
4.3.4 TEST PROCEDURE 37
4.3.5 DEVIATION FROM TEST STANDARD 37
4.3.6 EUT OPERATING CONDITIONS 37
4.3.7 TEST RESULTS 38
4.4 CONDUCTED OUTPUT POWER 40
4.4.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT 40
4.4.2 TEST SETUP 40
4.4.3 TEST INSTRUMENTS 40
4.4.4 TEST PROCEDURES 40

4.4.5 DEVIATION FROM TEST STANDARD 41
4.4.6 EUT OPERATING CONDITIONS 41
4.4.7 TEST RESULTS 42
4.5 POWER SPECTRAL DENSITY MEASUREMENT 44
4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT 44
4.5.2 TEST SETUP 44
4.5.3 TEST INSTRUMENTS 44
4.5.4 TEST PROCEDURE 44
4.5.5 DEVIATION FROM TEST STANDARD 44
4.5.6 EUT OPERATING CONDITION 44
4.5.7 TEST RESULTS 45
4.6 CONDUCTED OUT OF BAND EMISSION MEASUREMENT 47
4.6.1 LIMITS OF CONDUCTED OUT OF BAND EMISSION MEASUREMENT 47
4.6.2 TEST SETUP 47
4.6.3 TEST INSTRUMENTS 47
4.6.4 TEST PROCEDURE 48
4.6.5 DEVIATION FROM TEST STANDARD 48
4.6.6 EUT OPERATING CONDITION 48
4.6.7 TEST RESULTS 49
5. PHOTOGRAPHS OF THE TEST CONFIGURATION 58
6. INFORMATION ON THE TESTING LABORATORIES 59
7. APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB 60

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF140605C26	Original release	Jul. 14, 2014

1. CERTIFICATION

PRODUCT:	Simultaneous Dual-Band Wireless AC1200 HD Media Router
MODEL NO.:	NBG6616 (Refer to item 3.1 for more details)
BRAND:	ZyXEL
APPLICANT:	ZyXEL Communications Corporation
TESTED:	Jun. 12 ~ Jul. 04, 2014
TEST SAMPLE:	ENGINEERING SAMPLE
STANDARDS:	**FCC Part 15, Subpart C (Section 15.247)** ANSI C63.10-2009

The above equipment (model: NBG6616) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch,** and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Celine Chou **, DATE :** Jul. 14, 2014

Celine Chou / Specialist

APPROVED BY : Ken Liu **, DATE :** Jul. 14, 2014

Ken Liu / Senior Manager

2. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.247)			
STANDARD SECTION	**TEST TYPE**	**RESULT**	**REMARK**
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -19.19dB at 4.59958MHz.
15.205 & 209	Radiated Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -1.0dB at 2483.50MHz.
15.247(d)	Band Edge Measurement	PASS	Meet the requirement of limit. Minimum passing margin is -1.0dB at 2483.50MHz.
15.247(d)	Antenna Port Emission	PASS	Meet the requirement of limit.
15.247(a)(2)	6dB bandwidth	PASS	Meet the requirement of limit.
15.247(b)	Conducted power	PASS	Meet the requirement of limit.
15.247(e)	Power Spectral Density	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	Antenna connector is RSMA not a standard connector.

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	150kHz~30MHz	2.44 dB
Radiated emissions	30MHz ~ 200MHz	3.34 dB
	200MHz ~1000MHz	3.35 dB
	1GHz ~ 18GHz	2.26 dB
	18GHz ~ 40GHz	1.94 dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k = 2.

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

EUT	Simultaneous Dual-Band Wireless AC1200 HD Media Router
MODEL NO.	NBG6616 (Refer to note for more details)
POWER SUPPLY	12Vdc from Adapter
MODULATION TYPE	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
MODULATION TECHNOLOGY	DSSS, OFDM
TRANSFER RATE	802.11b:11.0/ 5.5/ 2.0/ 1.0Mbps 802.11g: 54.0/ 48.0/ 36.0/ 24.0/ 18.0/ 12.0/ 9.0/ 6.0Mbps 802.11n: up to 300.0Mbps
OPERATING FREQUENCY	2412 ~ 2462MHz
NUMBER OF CHANNEL	11 for 802.11b, 802.11g, 802.11n (20MHz) 7 for 802.11n (40MHz)
OUTPUT POWER	572.207mW
ANTENNA TYPE	Refer to note
ANTENNA CONNECTOR	Refer to note
DATA CABLE	0.9m non-shielded RJ45 cable without core
I/O PORTS	Refer to user's manual
ACCESSORY DEVICES	Adapter

NOTE:

1. The following product names & models are provided to this EUT.

Brand	Model	DESCRIPTION
ZyXEL	NBG6616	For marketing purpose
	EMG2826-Q10A	
	EMG2806-Q10A	

* The model of the NBG6616 was chosen for final test.

2. The EUT incorporates a MIMO function. Physically, the EUT provides two completed transmitters and two receivers.

MODULATION MODE	TX FUNCTION
802.11b	2TX
802.11g	2TX
802.11n (20MHz)	2TX
802.11n (40MHz)	2TX

3. The EUT uses following antennas.

Antenna Item	Brand	Model	Antenna Type	Connector	Gain(dBi)	
					2.4GHz	5GHz
1	WHA YU	C496-510124-A	Dipole	RSMA	3.4	4.3
2	WHA YU	C496-510125-A			3.5	4.0

4. The EUT uses following RF control IC.

BRAND:	Qualcomm Atheros
MODEL:	QCA9557
	QCA9882

5. The EUT consumes power from the following adapter.

ADAPTER	
BRAND:	DVE
MODEL:	DSA-24PFD-15 FUS 120200
INPUT:	100-240Vac, 50/60Hz, 0.8A
OUTPUT:	12Vdc, 2A
POWER LINE:	1.5m cable without core attached on adapter

6. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

3.2 DESCRIPTION OF TEST MODES

11 channels are provided for 802.11b, 802.11g and 802.11n (20MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
1	2412MHz	7	2442MHz
2	2417MHz	8	2447MHz
3	2422MHz	9	2452MHz
4	2427MHz	10	2457MHz
5	2432MHz	11	2462MHz
6	2437MHz		

7 channels are provided for 802.11n (40MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
3	2422MHz	7	2442MHz
4	2427MHz	8	2447MHz
5	2432MHz	9	2452MHz
6	2437MHz		

3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE≥1G	RE<1G	PLC	APCM	
-	√	√	√	√	-

Where **RE≥1G:** Radiated Emission above 1GHz **RE<1G:** Radiated Emission below 1GHz
PLC: Power Line Conducted Emission **APCM:** Antenna Port Conducted Measurement

NOTE:
The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on **X-plane.**

RADIATED EMISSION TEST (ABOVE 1GHz):

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
-	802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1.0
-	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0
-	802.11n (20MHz)	1 to 11	1, 6, 11	OFDM	BPSK	7.2
-	802.11n (40MHz)	3 to 9	3, 6, 9	OFDM	BPSK	15.0

RADIATED EMISSION TEST (BELOW 1GHz):

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
-	802.11b	1 to 11	1	DSSS	DBPSK	1.0

POWER LINE CONDUCTED EMISSION TEST:

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
-	802.11b	1 to 11	1	DSSS	DBPSK	1.0

BANDEDGE MEASUREMENT:

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
-	802.11b	1 to 11	1, 11	DSSS	DBPSK	1.0
-	802.11g	1 to 11	1, 11	OFDM	BPSK	6.0
-	802.11n (20MHz)	1 to 11	1, 11	OFDM	BPSK	7.2
-	802.11n (40MHz)	3 to 9	3, 9	OFDM	BPSK	15.0

ANTENNA PORT CONDUCTED MEASUREMENT:

☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
-	802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1.0
-	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0
-	802.11n (20MHz)	1 to 11	1, 6, 11	OFDM	BPSK	7.2
-	802.11n (40MHz)	3 to 9	3, 6, 9	OFDM	BPSK	15.0

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
RE≥1G	21deg. C, 65%RH	120Vac, 60Hz	Chris Lin
RE<1G	21deg. C, 65%RH	120Vac, 60Hz	Chris Lin
PLC	25deg. C, 65%RH	120Vac, 60Hz	Chris Lin
APCM	24deg. C, 64%RH	120Vac, 60Hz	Match Tsui

3.3 DUTY CYCLE OF TEST SIGNAL

802.11b: Duty cycle of test signal is 100 %

802.11g, 802.11n (20MHz), 802.11n (40MHz): Duty cycle is < 98%

802.11g: Duty cycle = 2.023/2.074 = 0.975, Duty factor = 10 * log(1/0.975) = 0.11

802.11n (20MHz): Duty cycle = 1.886/1.937 = 0.974, Duty factor = 10 * log(1/0.974) = 0.11

802.11n (40MHz): Duty cycle = 0.925/0.966 = 0.958, Duty factor = 10 * log(1/0.958) = 0.19

802.11b



802.11g



802.11n (20MHz)



802.11n (40MHz)



3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	Notebook	DELL	E5410	1HC2XM1	FCC DoC Approved
2	USB Flash	Transcend	V85	569992-8209	NA
3	USB Flash	Transcend	V85	538455 4490	NA

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	10m LAN cable
2	NA
3	NA

NOTE:

1. All power cords of the above support units are non-shielded (1.8m).
2. Item 1 acted as a communication partner to transfer data.

3.4.1 CONFIGURATION OF SYSTEM UNDER TEST



3.5 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C (15.247)
558074 D01 DTS Meas Guidance v03r02
662911 D01 Multiple Transmitter Output v02r01
ANSI C63.10-2009

All test items have been performed and recorded as per the above standards.

NOTE: The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.

4. TEST TYPES AND RESULTS

4.1 RADIATED EMISSION AND BANDEDGE MEASUREMENT

4.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver ROHDE & SCHWARZ	ESIB7	100187	Jan. 02, 2014	Jan. 01, 2015
Spectrum Analyzer ROHDE & SCHWARZ	FSP40	100039	Mar. 03, 2014	Mar. 02, 2015
BILOG Antenna SCHWARZBECK	VULB9168	9168-160	Feb. 26, 2014	Feb. 25, 2015
HORN Antenna SCHWARZBECK	9120D	209	Sep. 12, 2013	Sep. 11, 2014
HORN Antenna SCHWARZBECK	BBHA 9170	148	Jul. 15, 2013	Jul. 14, 2014
Preamplifier Agilent	8447D	2944A10633	Oct. 07, 2013	Oct. 06, 2014
Preamplifier Agilent	8449B	3008A01964	Aug. 26, 2013	Aug. 25, 2014
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	214378/4	Aug. 26, 2013	Aug. 25, 2014
RF signal cable HUBER+SUHNNER	SUCOFLEX 106	12738/6 +309224/4	Aug. 26, 2013	Aug. 25, 2014
Software BV ADT	ADT_Radiated_ V7.6.15.9.4	NA	NA	NA
Antenna Tower inn-co GmbH	MA 4000	013303	NA	NA
Antenna Tower Controller inn-co GmbH	CO2000	017303	NA	NA
Turn Table BV ADT	TT100	TT93021703	NA	NA
Turn Table Controller BV ADT	SC100	SC93021703	NA	NA
High Speed Peak Power Meter	ML2495A	0824011	Jul. 29, 2013	Jul. 28, 2014
Power Sensor	MA2411B	0738171	Jul. 29, 2013	Jul. 28, 2014

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. The test was performed in HwaYa Chamber 3.

3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.

4. The FCC Site Registration No. is 988962.

5. The IC Site Registration No. is IC 7450F-3.

4.1.3 TEST PROCEDURES

a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meters semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. Height of receiving antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

f. If the emission level of the EUT in peak mode was lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is ≥ 1/T (Duty cycle < 98%) or 10Hz(Duty cycle > 98%) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation.

4.1.5 TEST SETUP

Frequency range 30MHz~1GHz



Frequency range above 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT OPERATING CONDITIONS

a. Placed the EUT on the testing table.
b. Prepared notebook to act as communication partner and placed it outside of testing area.
c. The communication partner connected with EUT via a RJ45 cable and run a test program (provided by manufacturer) to enable EUT under transmission condition continuously at specific channel frequency.
d. The communication partner sent data to EUT by command "PING".

4.1.7 TEST RESULTS

ABOVE 1GHz DATA：

802.11b

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	**FREQUENCY RANGE**	1 ~ 25GHz
INPUT POWER	120Vac, 60Hz	**DETECTOR FUNCTION**	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	21deg. C, 65%RH	**TESTED BY**	Chris Lin

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	58.2 PK	74.0	-15.8	1.13 H	136	26.40	31.80
2	2390.00	47.3 AV	54.0	-6.7	1.13 H	136	15.50	31.80
3	*2412.00	108.5 PK			1.00 H	112	76.60	31.90
4	*2412.00	104.6 AV			1.00 H	112	72.70	31.90
5	4824.00	49.9 PK	74.0	-24.1	1.04 H	142	45.50	4.40
6	4824.00	41.6 AV	54.0	-12.4	1.04 H	142	37.20	4.40
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	64.5 PK	74.0	-9.5	1.62 V	167	32.70	31.80
2	2390.00	52.4 AV	54.0	-1.6	1.62 V	167	20.60	31.80
3	*2412.00	116.4 PK			1.00 V	338	84.50	31.90
4	*2412.00	112.2 AV			1.00 V	338	80.30	31.90
5	4824.00	55.5 PK	74.0	-18.5	1.08 V	132	51.10	4.40
6	4824.00	50.1 AV	54.0	-3.9	1.08 V	132	45.70	4.40

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	21deg. C, 65%RH	TESTED BY	Chris Lin

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	57.9 PK	74.0	-16.1	1.10 H	50	26.10	31.80
2	2390.00	47.5 AV	54.0	-6.5	1.10 H	50	15.70	31.80
3	*2437.00	108.2 PK			1.03 H	145	76.20	32.00
4	*2437.00	103.9 AV			1.03 H	145	71.90	32.00
5	2483.50	57.2 PK	74.0	-16.8	1.09 H	87	25.10	32.10
6	2483.50	45.7 AV	54.0	-8.3	1.09 H	87	13.60	32.10
7	4874.00	51.3 PK	74.0	-22.7	1.03 H	137	46.80	4.50
8	4874.00	43.4 AV	54.0	-10.6	1.03 H	137	38.90	4.50
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	28.7 PK	74.0	-45.3	1.21 V	17	30.30	-1.60
2	2390.00	17.2 AV	54.0	-36.8	1.21 V	17	18.80	-1.60
3	*2437.00	118.1 PK			1.00 V	168	86.10	32.00
4	*2437.00	113.9 AV			1.00 V	168	81.90	32.00
5	2483.50	62.8 PK	74.0	-11.2	1.17 V	139	30.70	32.10
6	2483.50	50.2 AV	54.0	-3.8	1.17 V	139	18.10	32.10
7	4874.00	56.5 PK	74.0	-17.5	1.62 V	82	52.00	4.50
8	4874.00	52.3 AV	54.0	-1.7	1.62 V	82	47.80	4.50

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	21deg. C, 65%RH	TESTED BY	Chris Lin

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	108.1 PK			1.01 H	136	76.10	32.00
2	*2462.00	104.6 AV			1.01 H	136	72.60	32.00
3	2483.50	58.1 PK	74.0	-15.9	1.00 H	136	26.00	32.10
4	2483.50	48.9 AV	54.0	-5.1	1.00 H	136	16.80	32.10
5	4924.00	49.5 PK	74.0	-24.5	1.00 H	137	44.70	4.80
6	4924.00	41.0 AV	54.0	-13.0	1.00 H	137	36.20	4.80
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	114.5 PK			1.18 V	153	82.50	32.00
2	*2462.00	110.7 AV			1.18 V	153	78.70	32.00
3	2483.50	62.3 PK	74.0	-11.7	1.16 V	139	30.20	32.10
4	**2483.50**	**53.0 AV**	**54.0**	**-1.0**	**1.16 V**	**139**	**20.90**	**32.10**
5	4924.00	55.3 PK	74.0	-18.7	1.00 V	85	50.50	4.80
6	4924.00	51.1 AV	54.0	-2.9	1.00 V	85	46.30	4.80

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

802.11g

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	21deg. C, 65%RH	TESTED BY	Chris Lin

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	63.9 PK	74.0	-10.1	1.05 H	141	32.10	31.80
2	2390.00	47.7 AV	54.0	-6.3	1.05 H	141	15.90	31.80
3	*2412.00	103.7 PK			1.04 H	137	71.80	31.90
4	*2412.00	94.6 AV			1.04 H	137	62.70	31.90
5	4824.00	45.6 PK	74.0	-28.4	1.15 H	74	41.20	4.40
6	4824.00	32.3 AV	54.0	-21.7	1.15 H	74	27.90	4.40
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	70.0 PK	74.0	-4.0	1.00 V	165	38.20	31.80
2	2390.00	52.5 AV	54.0	-1.5	1.00 V	165	20.70	31.80
3	*2412.00	111.1 PK			1.00 V	153	79.20	31.90
4	*2412.00	102.3 AV			1.00 V	153	70.40	31.90
5	4824.00	46.0 PK	74.0	-28.0	1.05 V	32	41.60	4.40
6	4824.00	32.8 AV	54.0	-21.2	1.05 V	32	28.40	4.40

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	21deg. C, 65%RH	TESTED BY	Chris Lin

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	60.2 PK	74.0	-13.8	1.04 H	81	28.40	31.80
2	2390.00	46.7 AV	54.0	-7.3	1.04 H	81	14.90	31.80
3	*2437.00	108.6 PK			1.06 H	135	76.60	32.00
4	*2437.00	99.1 AV			1.06 H	135	67.10	32.00
5	2483.50	62.5 PK	74.0	-11.5	1.27 H	19	30.40	32.10
6	2483.50	46.9 AV	54.0	-7.1	1.27 H	19	14.80	32.10
7	4874.00	45.5 PK	74.0	-28.5	1.16 H	30	41.00	4.50
8	4874.00	32.1 AV	54.0	-21.9	1.16 H	30	27.60	4.50
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	68.3 PK	74.0	-5.7	1.58 V	165	36.50	31.80
2	2390.00	52.6 AV	54.0	-1.4	1.58 V	165	20.80	31.80
3	*2437.00	115.9 PK			1.00 V	161	83.90	32.00
4	*2437.00	106.5 AV			1.00 V	161	74.50	32.00
5	2483.50	70.5 PK	74.0	-3.5	1.17 V	161	38.40	32.10
6	2483.50	52.8 AV	54.0	-1.2	1.17 V	161	20.70	32.10
7	4874.00	47.5 PK	74.0	-26.5	1.15 V	74	43.00	4.50
8	4874.00	33.5 AV	54.0	-20.5	1.15 V	74	29.00	4.50

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	21deg. C, 65%RH	TESTED BY	Chris Lin

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	103.6 PK			1.01 H	136	71.60	32.00
2	*2462.00	94.4 AV			1.01 H	136	62.40	32.00
3	2483.50	66.2 PK	74.0	-7.8	1.31 H	14	34.10	32.10
4	2483.50	47.8 AV	54.0	-6.2	1.31 H	14	15.70	32.10
5	4924.00	45.8 PK	74.0	-28.2	1.15 H	41	41.00	4.80
6	4924.00	32.8 AV	54.0	-21.2	1.15 H	41	28.00	4.80
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	111.7 PK			1.19 V	161	79.70	32.00
2	*2462.00	102.2 AV			1.19 V	161	70.20	32.00
3	2483.50	72.8 PK	74.0	-1.2	1.45 V	159	40.70	32.10
4	2483.50	52.9 AV	54.0	-1.1	1.45 V	159	20.80	32.10
5	4924.00	47.5 PK	74.0	-26.5	1.15 V	74	42.70	4.80
6	4924.00	33.8 AV	54.0	-20.2	1.15 V	74	29.00	4.80

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

802.11n (20MHz)

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	21deg. C, 65%RH	TESTED BY	Chris Lin

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	56.4 PK	74.0	-17.6	1.12 H	279	24.60	31.80
2	2390.00	47.4 AV	54.0	-6.6	1.12 H	279	15.60	31.80
3	*2412.00	102.1 PK			1.30 H	141	70.20	31.90
4	*2412.00	92.7 AV			1.30 H	141	60.80	31.90
5	4824.00	46.3 PK	74.0	-27.7	1.15 H	203	41.90	4.40
6	4824.00	32.0 AV	54.0	-22.0	1.15 H	203	27.60	4.40
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	71.9 PK	74.0	-2.1	1.82 V	165	40.10	31.80
2	2390.00	52.7 AV	54.0	-1.3	1.82 V	165	20.90	31.80
3	*2412.00	111.4 PK			1.26 V	158	79.50	31.90
4	*2412.00	101.3 AV			1.26 V	158	69.40	31.90
5	4824.00	47.4 PK	74.0	-26.6	1.17 V	123	43.00	4.40
6	4824.00	33.4 AV	54.0	-20.6	1.17 V	123	29.00	4.40

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	21deg. C, 65%RH	TESTED BY	Chris Lin

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	63.5 PK	74.0	-10.5	1.33 H	142	31.70	31.80
2	2390.00	48.3 AV	54.0	-5.7	1.33 H	142	16.50	31.80
3	*2437.00	108.7 PK			1.04 H	135	76.70	32.00
4	*2437.00	99.3 AV			1.04 H	135	67.30	32.00
5	2483.50	60.1 PK	74.0	-13.9	1.37 H	351	28.00	32.10
6	2483.50	47.4 AV	54.0	-6.6	1.37 H	351	15.30	32.10
7	4874.00	45.6 PK	74.0	-28.4	1.05 H	26	41.10	4.50
8	4874.00	31.6 AV	54.0	-22.4	1.05 H	26	27.10	4.50
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	68.2 PK	74.0	-5.8	1.54 V	151	36.40	31.80
2	2390.00	52.6 AV	54.0	-1.4	1.54 V	151	20.80	31.80
3	*2437.00	115.9 PK			1.21 V	157	83.90	32.00
4	*2437.00	106.4 AV			1.21 V	157	74.40	32.00
5	2483.50	68.6 PK	74.0	-5.4	1.44 V	360	36.50	32.10
6	2483.50	52.1 AV	54.0	-1.9	1.44 V	360	20.00	32.10
7	4874.00	47.5 PK	74.0	-26.5	1.33 V	206	43.00	4.50
8	4874.00	33.5 AV	54.0	-20.5	1.33 V	206	29.00	4.50

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	21deg. C, 65%RH	TESTED BY	Chris Lin

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	101.5 PK			1.04 H	136	69.50	32.00
2	*2462.00	91.9 AV			1.04 H	136	59.90	32.00
3	2483.50	58.1 PK	74.0	-15.9	1.14 H	20	26.00	32.10
4	2483.50	46.6 AV	54.0	-7.4	1.14 H	20	14.50	32.10
5	4924.00	46.7 PK	74.0	-27.3	1.15 H	203	41.90	4.80
6	4924.00	32.3 AV	54.0	-21.7	1.15 H	203	27.50	4.80
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	110.2 PK			1.20 V	158	78.20	32.00
2	*2462.00	100.5 AV			1.20 V	158	68.50	32.00
3	**2483.50**	**73.0 PK**	**74.0**	**-1.0**	**1.17 V**	**172**	**40.90**	**32.10**
4	2483.50	50.8 AV	54.0	-3.2	1.17 V	172	18.70	32.10
5	4924.00	47.4 PK	74.0	-26.6	1.15 V	47	42.60	4.80
6	4924.00	33.8 AV	54.0	-20.2	1.15 V	47	29.00	4.80

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

802.11n (40MHz)

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 3	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	21deg. C, 65%RH	TESTED BY	Chris Lin

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	55.1 PK	74.0	-18.9	1.37 H	262	23.30	31.80
2	2390.00	46.3 AV	54.0	-7.7	1.37 H	262	14.50	31.80
3	*2422.00	98.9 PK			1.03 H	133	66.90	32.00
4	*2422.00	88.5 AV			1.03 H	133	56.50	32.00
5	4844.00	46.0 PK	74.0	-28.0	1.16 H	30	41.50	4.50
6	4844.00	32.0 AV	54.0	-22.0	1.16 H	30	27.50	4.50
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	66.1 PK	74.0	-7.9	1.21 V	11	34.30	31.80
2	2390.00	52.6 AV	54.0	-1.4	1.21 V	11	20.80	31.80
3	*2422.00	106.0 PK			1.00 V	159	74.00	32.00
4	*2422.00	96.7 AV			1.00 V	159	64.70	32.00
5	4844.00	47.1 PK	74.0	-26.9	1.05 V	223	42.60	4.50
6	4844.00	33.5 AV	54.0	-20.5	1.05 V	223	29.00	4.50

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	21deg. C, 65%RH	TESTED BY	Chris Lin

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	58.8 PK	74.0	-15.2	1.07 H	252	27.00	31.80
2	2390.00	46.6 AV	54.0	-7.4	1.07 H	252	14.80	31.80
3	*2437.00	100.7 PK			1.02 H	139	68.70	32.00
4	*2437.00	91.9 AV			1.02 H	139	59.90	32.00
5	2483.50	58.6 PK	74.0	-15.4	1.10 H	20	26.50	32.10
6	2483.50	47.3 AV	54.0	-6.7	1.10 H	20	15.20	32.10
7	4874.00	45.5 PK	74.0	-28.5	1.14 H	15	41.00	4.50
8	4874.00	31.6 AV	54.0	-22.4	1.14 H	15	27.10	4.50
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	68.1 PK	74.0	-5.9	1.22 V	13	36.30	31.80
2	2390.00	52.3 AV	54.0	-1.7	1.22 V	13	20.50	31.80
3	*2437.00	108.4 PK			1.00 V	160	76.40	32.00
4	*2437.00	99.5 AV			1.00 V	160	67.50	32.00
5	2483.50	69.0 PK	74.0	-5.0	1.17 V	163	36.90	32.10
6	**2483.50**	**53.0 AV**	**54.0**	**-1.0**	**1.17 V**	**163**	**20.90**	**32.10**
7	4874.00	47.5 PK	74.0	-26.5	1.33 V	225	43.00	4.50
8	4874.00	33.5 AV	54.0	-20.5	1.33 V	225	29.00	4.50

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 9	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	21deg. C, 65%RH	TESTED BY	Chris Lin

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2452.00	97.2 PK			1.29 H	135	65.20	32.00
2	*2452.00	87.7 AV			1.29 H	135	55.70	32.00
3	2483.50	59.0 PK	74.0	-15.0	1.15 H	63	26.90	32.10
4	2483.50	47.0 AV	54.0	-7.0	1.15 H	63	14.90	32.10
5	4904.00	45.7 PK	74.0	-28.3	1.23 H	55	41.00	4.70
6	4904.00	32.1 AV	54.0	-21.9	1.23 H	55	27.40	4.70
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2452.00	106.2 PK			1.00 V	162	74.20	32.00
2	*2452.00	96.9 AV			1.00 V	162	64.90	32.00
3	2483.50	72.2 PK	74.0	-1.8	1.14 V	172	40.10	32.10
4	2483.50	50.8 AV	54.0	-3.2	1.14 V	172	18.70	32.10
5	4904.00	47.3 PK	74.0	-26.7	1.15 V	203	42.60	4.70
6	4904.00	33.7 AV	54.0	-20.3	1.15 V	203	29.00	4.70

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

BELOW 1GHz WORST-CASE DATA：802.11b

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	Below 1000MHz
INPUT POWER	120Vac, 60Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	21deg. C, 65%RH	TESTED BY	Chris Lin

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	57.12	32.7 QP	40.0	-7.3	2.00 H	319	47.30	-14.60
2	152.39	30.2 QP	43.5	-13.3	2.00 H	95	44.00	-13.80
3	375.98	28.7 QP	46.0	-17.3	1.01 H	317	39.40	-10.70
4	480.97	34.3 QP	46.0	-11.7	2.00 H	8	43.00	-8.70
5	624.85	32.3 QP	46.0	-13.7	1.26 H	100	37.80	-5.50
6	961.21	36.7 QP	54.0	-17.3	1.50 H	16	36.00	0.70
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	49.34	34.2 QP	40.0	-5.8	1.25 V	299	48.70	-14.50
2	150.45	32.3 QP	43.5	-11.2	1.00 V	300	46.10	-13.80
3	375.98	29.6 QP	46.0	-16.4	1.25 V	320	40.30	-10.70
4	500.42	36.4 QP	46.0	-9.6	1.25 V	301	44.70	-8.30
5	624.85	29.8 QP	46.0	-16.2	1.00 V	27	35.30	-5.50
6	959.27	33.9 QP	46.0	-12.1	1.25 V	53	33.20	0.70

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

4.2 CONDUCTED EMISSION MEASUREMENT

4.2.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBμV)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

NOTE: 1. The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.
3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver ROHDE & SCHWARZ	ESCS30	100289	Nov. 29, 2013	Nov. 28, 2014
RF signal cable Woken	5D-FB	Cable-HYC01-01	Dec. 27, 2013	Dec. 26, 2014
LISN ROHDE & SCHWARZ (EUT)	ESH3-Z5	835239/001	Feb. 13, 2014	Feb. 12, 2015
LISN ROHDE & SCHWARZ (Peripheral)	ESH3-Z5	100311	Jul. 17, 2013	Jul. 16, 2014
Software ADT	BV ADT_Cond_ V7.3.7.3	NA	NA	NA

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in HwaYa Shielded Room 1.
3. The VCCI Site Registration No. is C-2040.

4.2.3 TEST PROCEDURES

a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.

b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.

c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

NOTE: All modes of operation were investigated and the worst-case emissions are reported.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation.

4.2.5 TEST SETUP



Note: 1.Support units were connected to second LISN.
2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6.

4.2.7 TEST RESULTS

CONDUCTED WORST-CASE DATA：802.11b

PHASE	Line 1	6dB BANDWIDTH	9kHz

No	Freq.	Corr. Factor	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.17346	0.08	39.95	27.69	40.03	27.77	64.79	54.79	-24.77	-27.03
2	0.23648	0.07	36.58	29.19	36.65	29.26	62.22	52.22	-25.57	-22.96
3	0.40479	0.08	26.68	19.68	26.76	19.76	57.75	47.75	-30.99	-27.99
4	**4.59958**	**0.26**	**31.71**	**26.55**	**31.97**	**26.81**	**56.00**	**46.00**	**-24.03**	**-19.19**
5	7.21537	0.38	33.07	28.33	33.45	28.71	60.00	50.00	-26.55	-21.29
6	12.88878	0.66	21.94	16.88	22.60	17.54	60.00	50.00	-37.40	-32.46

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



PHASE	Line 2	6dB BANDWIDTH	9kHz

No	Freq.	Corr. Factor	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15000	0.05	44.42	30.06	44.47	30.11	66.00	56.00	-21.53	-25.89
2	0.19301	0.05	38.32	28.29	38.37	28.34	63.91	53.91	-25.54	-25.57
3	0.23216	0.05	32.41	21.37	32.46	21.42	62.37	52.37	-29.91	-30.95
4	0.87834	0.09	25.70	18.98	25.79	19.07	56.00	46.00	-30.21	-26.93
5	2.95738	0.17	28.69	22.63	28.86	22.80	56.00	46.00	-27.14	-23.20
6	7.39523	0.34	32.77	28.13	33.11	28.47	60.00	50.00	-26.89	-21.53

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



4.3 6dB BANDWIDTH MEASUREMENT

4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 TEST SETUP



4.3.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

4.3.4 TEST PROCEDURE

a. Set resolution bandwidth (RBW) = 100kHz
b. Set the video bandwidth (VBW) ≥ 3 x RBW, Detector = Peak.
c. Trace mode = max hold.
d. Sweep = auto couple.
e. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

4.3.5 DEVIATION FROM TEST STANDARD

No deviation.

4.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.3.7 TEST RESULTS

802.11b

CHANNEL	FREQUENCY (MHz)	6dB BANDWIDTH (MHz)		MINIMUM LIMIT (MHz)	PASS / FAIL
		CHAIN 0	CHAIN 1		
1	2412	7.11	7.12	0.5	PASS
6	2437	7.11	7.09	0.5	PASS
11	2462	7.11	7.09	0.5	PASS

802.11g

CHANNEL	FREQUENCY (MHz)	6dB BANDWIDTH (MHz)		MINIMUM LIMIT (MHz)	PASS / FAIL
		CHAIN 0	CHAIN 1		
1	2412	16.42	16.43	0.5	PASS
6	2437	16.38	16.39	0.5	PASS
11	2462	16.39	16.42	0.5	PASS

802.11n (20MHz)

CHANNEL	FREQUENCY (MHz)	6dB BANDWIDTH (MHz)		MINIMUM LIMIT (MHz)	PASS / FAIL
		CHAIN 0	CHAIN 1		
1	2412	17.64	17.63	0.5	PASS
6	2437	17.59	17.60	0.5	PASS
11	2462	17.64	17.61	0.5	PASS

802.11n (40MHz)

CHANNEL	FREQUENCY (MHz)	6dB BANDWIDTH (MHz)		MINIMUM LIMIT (MHz)	PASS / FAIL
		CHAIN 0	CHAIN 1		
3	2422	36.44	36.17	0.5	PASS
6	2437	36.13	36.37	0.5	PASS
9	2452	36.20	36.37	0.5	PASS

SPECTRUM PLOT OF WORST VALUE

802.11b



802.11g



802.11n (20MHz)



802.11n (40MHz)



4.4 CONDUCTED OUTPUT POWER

4.4.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT

For systems using digital modulation in the 2400–2483.5 MHz bands: 1 Watt (30dBm)

Per KDB 662911 D01 Multiple Transmitter Output v02r01 Method of conducted output power measurement on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for NANT ≤ 4;
Array Gain = 0 dB (i.e., no array gain) for channel widths ≥ 40 MHz for any NANT;
Array Gain = 5 log(NANT/NSS) dB or 3 dB, whichever is less for 20-MHz channel widths with NANT ≥ 5.

For power measurements on all other devices: Array Gain = 10 log(NANT/NSS) dB.

4.4.2 TEST SETUP



4.4.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

4.4.4 TEST PROCEDURES

An average power sensor was used on the output port of the EUT. A power meter was used to read the response of the average power sensor. Record the power level.

4.4.5 DEVIATION FROM TEST STANDARD

No deviation.

4.4.6 EUT OPERATING CONDITIONS

Same as Item 4.3.6.

4.4.7 TEST RESULTS

FOR PEAK POWER

802.11b

CHAN.	FREQ. (MHz)	PEAK POWER (dBm)		TOTAL POWER (mW)	TOTAL POWER (dBm)	LIMIT (dBm)	PASS / FAIL
		CHAIN 0	CHAIN 1				
1	2412	22.64	23.02	384.101	25.84	30	PASS
6	2437	23.55	23.60	455.551	26.59	30	PASS
11	2462	22.94	23.09	400.493	26.03	30	PASS

802.11g

CHAN.	FREQ. (MHz)	PEAK POWER (dBm)		TOTAL POWER (mW)	TOTAL POWER (dBm)	LIMIT (dBm)	PASS / FAIL
		CHAIN 0	CHAIN 1				
1	2412	22.00	22.89	353.025	25.48	30	PASS
6	2437	24.52	24.61	**572.207**	27.58	30	PASS
11	2462	21.59	22.96	341.909	25.34	30	PASS

802.11n (20MHz)

CHAN.	FREQ. (MHz)	PEAK POWER (dBm)		TOTAL POWER (mW)	TOTAL POWER (dBm)	LIMIT (dBm)	PASS / FAIL
		CHAIN 0	CHAIN 1				
1	2412	21.58	22.38	316.862	25.01	30	PASS
6	2437	24.26	24.79	567.987	27.54	30	PASS
11	2462	22.44	22.19	340.965	25.33	30	PASS

802.11n (40MHz)

CHAN.	FREQ. (MHz)	PEAK POWER (dBm)		TOTAL POWER (mW)	TOTAL POWER (dBm)	LIMIT (dBm)	PASS / FAIL
		CHAIN 0	CHAIN 1				
3	2422	20.80	20.59	234.777	23.71	30	PASS
6	2437	22.54	22.47	356.077	25.52	30	PASS
9	2452	21.00	22.11	288.448	24.60	30	PASS

FOR AVERAGE POWER

802.11b

CHAN.	FREQUENCY (MHz)	AVG. POWER (dBm)		TOTAL POWER (mW)	TOTAL POWER (dBm)
		CHAIN 0	CHAIN 1		
1	2412	19.85	20.21	201.559	23.04
6	2437	21.19	21.10	260.347	24.16
11	2462	20.36	20.56	222.406	23.47

802.11g

CHAN.	FREQUENCY (MHz)	AVG. POWER (dBm)		TOTAL POWER (mW)	TOTAL POWER (dBm)
		CHAIN 0	CHAIN 1		
1	2412	14.81	15.51	65.832	18.18
6	2437	20.22	20.71	222.957	23.48
11	2462	14.96	15.08	63.544	18.03

802.11n (20MHz)

CHAN.	FREQUENCY (MHz)	AVG. POWER (dBm)		TOTAL POWER (mW)	TOTAL POWER (dBm)
		CHAIN 0	CHAIN 1		
1	2412	14.06	14.71	55.048	17.41
6	2437	19.79	19.95	194.135	22.88
11	2462	14.02	14.36	52.525	17.20

802.11n (40MHz)

CHAN.	FREQUENCY (MHz)	AVG. POWER (dBm)		TOTAL POWER (mW)	TOTAL POWER (dBm)
		CHAIN 0	CHAIN 1		
1	2412	12.37	12.78	36.225	15.59
6	2437	15.08	15.47	67.448	18.29
11	2462	13.05	12.93	39.818	16.00

4.5 POWER SPECTRAL DENSITY MEASUREMENT

4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

4.5.2 TEST SETUP



4.5.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

4.5.4 TEST PROCEDURE

a. Set the RBW = 3 kHz, VBW =10 kHz, Detector = RMS.
b. Sweep time = auto couple, Trace mode = max hold, allow trace to fully stabilize.
c. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

4.5.5 DEVIATION FROM TEST STANDARD

No deviation.

4.5.6 EUT OPERATING CONDITION

Same as Item 4.3.6

4.5.7 TEST RESULTS

802.11b

TX chain	Channel	Freq. (MHz)	PSD (dBm/3kHz)	10 log (N=2) dB	Total PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
0	1	2412	-2.04	3.01	0.97	7.54	PASS
	6	2437	-0.81	3.01	2.20	7.54	PASS
	11	2462	-1.30	3.01	1.71	7.54	PASS
1	1	2412	-1.55	3.01	1.46	7.54	PASS
	6	2437	0.42	3.01	3.43	7.54	PASS
	11	2462	-0.05	3.01	2.96	7.54	PASS

NOTE: Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + ... + 10^{GN/20})^2 / N_{ANT}]$= 6.46 > 6dBi, so the power density limit shall be reduced to 8-(6.46-6) = 7.54dBm.

802.11g

TX chain	Channel	Freq. (MHz)	PSD (dBm/3kHz)	10 log (N=2) dB	Total PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
0	1	2412	-11.44	3.01	-8.43	7.54	PASS
	6	2437	-4.86	3.01	-1.85	7.54	PASS
	11	2462	-10.97	3.01	-7.96	7.54	PASS
1	1	2412	-10.46	3.01	-7.45	7.54	PASS
	6	2437	-4.81	3.01	-1.80	7.54	PASS
	11	2462	-9.58	3.01	-6.57	7.54	PASS

NOTE: Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + ... + 10^{GN/20})^2 / N_{ANT}]$= 6.46 > 6dBi, so the power density limit shall be reduced to 8-(6.46-6) = 7.54dBm.

802.11n (20MHz)

TX chain	Channel	Freq. (MHz)	PSD (dBm/3kHz)	10 log (N=2) dB	Total PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
0	1	2412	-12.43	3.01	-9.42	7.54	PASS
	6	2437	-7.00	3.01	-3.99	7.54	PASS
	11	2462	-11.18	3.01	-8.17	7.54	PASS
1	1	2412	-11.27	3.01	-8.26	7.54	PASS
	6	2437	-5.85	3.01	-2.84	7.54	PASS
	11	2462	-11.06	3.01	-8.05	7.54	PASS

NOTE: Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + ... + 10^{GN/20})^2 / N_{ANT}]$= 6.46 > 6dBi, so the power density limit shall be reduced to 8-(6.46-6) = 7.54dBm.

802.11n (40MHz)

TX chain	Channel	Freq. (MHz)	PSD (dBm/3kHz)	10 log (N=2) dB	Total PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
0	1	2412	-18.15	3.01	-15.14	7.54	PASS
	6	2437	-13.16	3.01	-10.15	7.54	PASS
	11	2462	-16.19	3.01	-13.18	7.54	PASS
1	1	2412	-16.67	3.01	-13.66	7.54	PASS
	6	2437	-14.50	3.01	-11.49	7.54	PASS
	11	2462	-17.25	3.01	-14.24	7.54	PASS

NOTE: Directional gain = 10 log[$(10^{G1/20} + 10^{G2/20} + ... + 10^{GN/20})^2 / N_{ANT}$]= 6.46 > 6dBi, so the power density limit shall be reduced to 8-(6.46-6) = 7.54dBm.

SPECTRUM PLOT OF WORST VALUE

802.11b



802.11g



802.11n (20MHz)



802.11n (40MHz)



4.6 CONDUCTED OUT OF BAND EMISSION MEASUREMENT

4.6.1 LIMITS OF CONDUCTED OUT OF BAND EMISSION MEASUREMENT

Below –20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.6.2 TEST SETUP



4.6.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

4.6.4 TEST PROCEDURE

MEASUREMENT PROCEDURE REF

1. Set the RBW = 100 kHz.
2. Set the VBW ≥ 300 kHz.
3. Detector = average.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

MEASUREMENT PROCEDURE OOBE

1. Set RBW = 100 kHz.
2. Set VBW ≥ 300 kHz.
3. Detector = peak.
4. Sweep = auto couple.
5. Trace Mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum amplitude level.

4.6.5 DEVIATION FROM TEST STANDARD

No deviation.

4.6.6 EUT OPERATING CONDITION

Same as Item 4.3.6

4.6.7 TEST RESULTS

The conducted emission test is performed on each TX port of operating mode without summing or adding 10log (N) since the limit is relative emission limit. Only worst data of each operating mode is presented.

The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement.

802.11b

CHAIN 0

CH 1





CH 6





CH 11





CH 1 Band edge



CH 11 Band edge



CHAIN 1

CH 1





CH 6





CH 11





CH 1 Band edge



CH 11 Band edge



802.11g

CHAIN 0

CH 1





CH 6





CH 11





CH 1 Band edge



CH 11 Band edge



CHAIN 1

CH 1





CH 6





CH 11





CH 1 Band edge



CH 11 Band edge



802.11n (20MHz)

CHAIN 0

CH 1





CH 6





CH 11





CH 1 Band edge



CH 11 Band edge



CHAIN 1

CH 1





CH 6





CH 11





CH 1 Band edge



CH 11 Band edge



802.11n (40MHz)

CHAIN 0

CH 3





CH 6





CH 9





CH 3 Band edge



CH 9 Band edge



CHAIN 1

CH 3





CH 6





CH 9





CH 3 Band edge



CH 9 Band edge



5. PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).

6. INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab:
Tel: 886-2-26052180
Fax: 886-2-26051924

Hsin Chu EMC/RF Lab:
Tel: 886-3-5935343
Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety Telecom Lab:
Tel: 886-3-3183232
Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com
Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

7. APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications were made to the EUT by the lab during the test.

---END---