



**SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch**

No. 1 Workshop, M-10, Middle section, Science & Technology Park,
Shenzhen, Guangdong, China 518057
Telephone: +86 (0) 755 2601 2053
Fax: +86 (0) 755 2671 0594
Email: ee.shenzhen@sgs.com

Report No.: SZEM131200649710
Page: 1 of 10

SAR Evaluation Report

Application No.: SZEM1611010036CR
Applicant: Creative Labs Inc.
Manufacturer: Creative Labs Pte. Ltd.
Product Name: SOUND BLASTER ROAR CLASSIC LITE
Model No.(EUT): MF8172
Trade Mark: Creative
FCC ID: IBAMF8170
Standards: 47 CFR Part 1.1307 (2015)
47 CFR Part 2.1093 (2015)
KDB447498D01 General RF Exposure Guidance v06
Date of Receipt: 2016-11-25
Date of Test: 2016-11-29 to 2016-12-14
Date of Issue: 2016-12-14

Test Result :	PASS*
----------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Jack Zhang
EMC Laboratory Manager


The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



2 Version

Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2016-12-14		Original

Authorized for issue by:			
			2016-12-14
Tested By	(Benson Wang) /Project Engineer		Date
			2016-12-14
Checked By	(Eric Fu) /Reviewer		Date



3 Contents

	Page
1 COVER PAGE.....	1
2 VERSION	2
3 CONTENTS	3
4 GENERAL INFORMATION.....	4
4.1 CLIENT INFORMATION.....	4
4.2 GENERAL DESCRIPTION OF EUT	4
4.3 TEST LOCATION	9
4.4 TEST FACILITY	9
4.5 DEVIATION FROM STANDARDS.....	9
4.6 ABNORMALITIES FROM STANDARD CONDITIONS	9
4.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER	9
5 SAR EVALUATION	10
5.1 RF EXPOSURE COMPLIANCE REQUIREMENT	10
5.1.1 <i>Standard Requirement</i>	10
5.1.2 <i>Limits</i>	10
5.1.3 <i>EUT RF Exposure</i>	10



4 General Information

4.1 Client Information

Applicant:	Creative Labs Inc
Address of Applicant:	1901 McCarthy Blvd, Milpitas, California, United States
Manufacturer:	Creative Labs Pte. Ltd.
Address of Manufacturer:	31, International Business Park, #03-01 Creative Resource, Singapore 609921

4.2 General Description of EUT

Product Name:	SOUND BLASTER ROAR CLASSIC LITE
Model No.:	MF8172
Trade Mark:	Creative
Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	V3.0
Test Software of EUT:	Blue Test 3
Test Power Grade:	255, 46 (manufacturer declare)
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Modulation Type:	GFSK, $\pi/4$ DQPSK, 8DPSK
Number of Channel:	79
Hopping Channel Type:	Adaptive Frequency Hopping systems
Sample Type:	Portable production
Antenna Type:	Integral
Antenna Gain:	4.11dBi
Power Supply	Battery Model No.:BJ-ACEXX-3KXKUX-01 Li-ion Battery: DC 7.56V 2950mAh 22.3Wh (Charge by adapter) Adapter Model:FJ-SW1501600N INPUT: AC100-240V 50/60Hz 0.6A Max OUTPUT: DC15V 1600mA
Test Voltage	AC 120V 60Hz



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM131200649710

Page: 5 of 10

Remark:

Model No.: MF8172

This test report (Ref. No.: SZEM1312006497010) is only valid with the original test report (Ref. No.: SZEM131200649702, SZEM131200649704, SZEM131200649706 and SZEM131200649708).

Review this report and original report, the major change filed under this application is:

1. Add Model No: MF8172, Product Name: SOUND BLASTER ROAR CLASSIC LITE
2. SOUND BLASTER ROAR CLASSIC LITE is a derivative model of CREATIVE SOUND BLASTER ROAR PRO with changes in product features. No other electrical differences other than those stated below. Mechanical design and construction are identical for both models.

	BEFORE	AFTER
Model No.	MF8171	MF8172
Product Name	SOUND BLASTER ROAR PRO	SOUND BLASTER ROAR CLASSIC LITE
Function / Feature	- Speaker - NFC - Aux in - Bluetooth - micro SD card slot - MP3 player - USB Audio - USB external smart phone charging	- Speaker - NFC - Aux in - Bluetooth
Input rating	15VDC 1.6A	15VDC 1.2A
Original Power Adapter	Model: GPE024W-150160-Z Input: 100-240Vac 50/60Hz 0.75A, Output: 15Vdc 1.6A	N/A
Alternate Power Adapter	Model: FJ-SW1501600N Input: 100-240Vac 50/60Hz 0.6A, Output: 15Vdc 1.6A	Model: FJ-SW1501600N Input: 100-240Vac 50/60Hz 0.6A, Output: 15Vdc 1.6A
Multifunction Button, Volume up/down, ROAR Button, Power ON/Standby	MS2160A	MS2160A



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM131200649710

Page: 6 of 10

Board		
Main Board	MS2160B	MS2166B * For detail, pls refer to appendix
NFC Board	MS2160D	MS2160D
MP3 key board	MS2160E	Deleted

Review the SZEM131200649708 and original report, the major change filed under this application is:

1. Add alternate power adapter model FJ-SW1501600N.

	Before	After
	Model:GPE024W-150160-Z INPUT: AC 100-240V 50/60Hz 0.75A	Model:GPE024W-150160-Z INPUT: AC 100-240V 50/60Hz 0.75A OUTPUT: DC 15V 1600mA 24W
Adapter	OUTPUT: DC 15V 1600mA 24W	Model: FJ-SW1501600N Input: 100-240V, 50/60Hz 0.6A Max output: DC 15V,1600mA

Review SZEM131200649706 and original report, the major change filed under this application is:

3. Add Model No: MF8171, Product Name CREATIVE SOUND BLASTER ROAR PRO.
4. CREATIVE SOUND BLASTER ROAR PRO is a derivative model of CREATIVE SOUND BLASTER ROAR SR20A with changes in product features, antenna gain and adapter. No other electrical differences other than those stated below. Mechanical design and construction are identical for both models.

	BEFORE	AFTER
Model No	1. MF8170	1. MF8170 2. MF8171
Product Name	SOUND BLASTER ROAR SR20, SOUND BLASTER ROAR SR20A	SOUND BLASTER ROAR SR20 (Model No: MF8170) SOUND BLASTER ROAR SR20A (Model No: MF8170) SOUND BLASTER ROAR PRO (Model No: MF8171)
Antenna Gain	0.25 dBi	No change for SOUND BLASTER ROAR SR20 and SOUND BLASTER ROAR SR20A.



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM131200649710
Page: 7 of 10

		SOUND BLASTER ROAR PRO: 4.11 dBi																		
Main Board	MS2160B REV A (0514116)	No change for SOUND BLASTER ROAR SR20 and SOUND BLASTER ROAR SR20A. SOUND BLASTER ROAR PRO: MS2160B Rev A (081520) & MS2165B Rev 1P (001521): Add C334 (10PF), C335 (10PF), C336 (10PF), C337 (10PF), C339 (10PF) Change: R162 (12K to 100R), R203 (12K to 100R), R142 (22K to 15K), R143 (22K to 15K), R219 (10K to 12K), R116 (330K to 300K) Remove: R92 (10K), R93 (10K), C72 (820PF), C77 (820PF). <table border="1"> <thead> <tr> <th>Version</th><th>Old Volume IC</th><th>New Volume IC</th></tr> </thead> <tbody> <tr> <td>Main board</td><td>MS2160B Rev A (081520)</td><td>MS2165B Rev 1P (001521)</td></tr> <tr> <td>Volume IC</td><td>MP61545 (U17)</td><td>NJU72431 (U4)</td></tr> <tr> <td>R214</td><td>Not Mounted</td><td>4K7</td></tr> <tr> <td>C313</td><td>Not Mounted</td><td>10UF</td></tr> <tr> <td>R324</td><td>Not Mounted</td><td>10K</td></tr> </tbody> </table>	Version	Old Volume IC	New Volume IC	Main board	MS2160B Rev A (081520)	MS2165B Rev 1P (001521)	Volume IC	MP61545 (U17)	NJU72431 (U4)	R214	Not Mounted	4K7	C313	Not Mounted	10UF	R324	Not Mounted	10K
Version	Old Volume IC	New Volume IC																		
Main board	MS2160B Rev A (081520)	MS2165B Rev 1P (001521)																		
Volume IC	MP61545 (U17)	NJU72431 (U4)																		
R214	Not Mounted	4K7																		
C313	Not Mounted	10UF																		
R324	Not Mounted	10K																		
Mp3 Key Board	SOUND BLASTER ROAR SR20: MS2160E, REV A (031404) SOUND BLASTER ROAR SR20A: MS2160E, REV A (041422)	No change for SOUND BLASTER ROAR SR20 and SOUND BLASTER ROAR SR20A. SOUND BLASTER ROAR PRO: MS2165E, REV A (011520).																		
Product Feature	SOUND BLASTER ROAR SR20: Loud Sounds SOUND BLASTER ROAR SR20A: Remove Loud Sounds. Add Link Security and Tera Bass.	No change for SOUND BLASTER ROAR SR20 and SOUND BLASTER ROAR SR20A. SOUND BLASTER ROAR PRO: Remove Link Security. Add EQ – Warm / Neutral / Energetic.																		



**SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch**

Report No.: SZEM131200649710

Page: 8 of 10

Additionally, just updated the below standards.

Original report standards

47 CFR Part 1.1307(2013)

47 CFR Part 2.1093 (2013)

KDB447498D01 General RF Exposure Guidance v05

KDB447498D01 General RF Exposure Guidance v05r02

The newest report standards

47 CFR Part 1.1307 (2015)

47 CFR Part 2.1093 (2015)

KDB447498D01 General RF Exposure Guidance v06



4.3 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Shenzhen, Guangdong, China
518057

Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594

No tests were sub-contracted.

4.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

- **VCCI**

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

- **FCC – Registration No.: 556682**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

- **Industry Canada (IC)**

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.

4.5 Deviation from Standards

None.

4.6 Abnormalities from Standard Conditions

None.

4.7 Other Information Requested by the Customer

None.



5 SAR Evaluation

5.1 RF Exposure Compliance Requirement

5.1.1 Standard Requirement

KDB447498D01 General RF Exposure Guidance v06

4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

5.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$\left[\frac{(\text{max. power of channel, including tune-up tolerance, mW})}{(\text{min. test separation distance, mm})} \right] \cdot \sqrt{f(\text{GHz})} \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation¹⁷

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

5.1.3 EUT RF Exposure

The Max Conducted Peak Output Power is -1.13dBm in middle channel(2.441GHz);

The best case gain of the antenna is 4.11dBi.

$\text{EIRP} = -1.13\text{dBm} + 4.11\text{dBi} = 2.98\text{dBm}$

2.98dBm logarithmic terms convert to numeric result is nearly 1.986mW

According to the formula. calculate the EIRP test result:

$$\left[\frac{(\text{max. power of channel, including tune-up tolerance, mW})}{(\text{min. test separation distance, mm})} \right] \cdot \sqrt{f(\text{GHz})}$$

General RF Exposure = $(1.986\text{mW} / 5 \text{ mm}) \times \sqrt{2.441\text{GHz}} = 0.62$ ①

SAR requirement:

$S = 3.0$

② ;

① < ②.

So the SAR report is not required.