

# **FCC TEST REPORT**

for

**CISPR PUB. 22 Class B**

Equipment : CARDEXpert TM64(VANTA)  
Model No. : P/N:VZD-01  
FCC ID : ICUVGA-GWVZD  
Filing Type : Original Grant  
Applicant : **GAINWARD CO., LTD.**  
12F., No. 96, Hsin Tai Wu Rd., Sec. 1,  
Hsi-Chih, Taipei Hsien, Taiwan, R.O.C.

- The test result refers exclusively to the test presented test model / sample.
- Without the written authorization of the test lab., the Test Report may not be copied.
- **Certificate or Test Report must not be used by the applicant to claim the product in this test report endorsement by NVLAP or any agency of U.S. government.**

***SPORTON International Inc.***

6F, No.106, Sec. 1, Hsin Tai Wu Rd., Hsi Chih, Taipei Hsien, Taiwan, R.O.C.

## Table of Contents

|                                                                  |           |
|------------------------------------------------------------------|-----------|
| <b>CERTIFICATE OF COMPLIANCE .....</b>                           | <b>3</b>  |
| <b>1. General Description of Equipment under Test .....</b>      | <b>4</b>  |
| 1.1. Applicant .....                                             | 4         |
| 1.2. Manufacturer .....                                          | 4         |
| 1.3. Basic Description of Equipment under Test .....             | 4         |
| 1.4. Feature of Equipment under Test .....                       | 4         |
| <b>2. Test Configuration of Equipment under Test .....</b>       | <b>5</b>  |
| 2.1. Test Manner .....                                           | 5         |
| 2.2. Description of Test System .....                            | 5         |
| 2.3. Connection Diagram of Test System .....                     | 7         |
| <b>3. Test Software .....</b>                                    | <b>8</b>  |
| <b>4. General Information of Test .....</b>                      | <b>9</b>  |
| 4.1. Test Facility .....                                         | 9         |
| 4.2. Standard for Methods of Measurement .....                   | 9         |
| 4.3. Test in Compliance with .....                               | 9         |
| 4.4. Frequency Range Investigated .....                          | 9         |
| 4.5. Test Distance .....                                         | 9         |
| <b>5. Test of Conducted Powerline .....</b>                      | <b>10</b> |
| 5.1. Major Measuring Instruments .....                           | 10        |
| 5.2. Test Procedures .....                                       | 10        |
| 5.3. Typical Test Setup Layout of Conducted Powerline .....      | 12        |
| 5.4. Test Result of AC Powerline Conducted Emission .....        | 13        |
| 5.5. Photographs of Conducted Powerline Test Configuration ..... | 21        |
| <b>6. Test of Radiated Emission .....</b>                        | <b>33</b> |
| 6.1. Major Measuring Instruments .....                           | 33        |
| 6.2. Test Procedures .....                                       | 34        |
| 6.3. Typical Test Setup Layout of Radiated Emission .....        | 35        |
| 6.4. Test Result of Radiated Emission .....                      | 36        |
| 6.5. Photographs of Radiated Emission Test Configuration .....   | 44        |
| <b>7. Antenna Factor &amp; Cable Loss .....</b>                  | <b>50</b> |
| <b>8. List of Measuring Equipment Used .....</b>                 | <b>51</b> |

# **CERTIFICATE OF COMPLIANCE**

**for**

## **CISPR PUB. 22 Class B**

Equipment : CARDEXpert TM64(VANTA)  
Model No. : P/N:VZD-01  
FCC ID : ICUVGA-GWVZD  
Applicant : **GAINWARD CO., LTD.**  
12F., No. 96, Hsin Tai Wu Rd., Sec. 1,  
Hsi-Chih, Taipei Hsien, Taiwan, R.O.C.

### **I HEREBY CERTIFY THAT :**

The measurements shown in this test report were made in accordance with the procedures given in **ANSI C63.4 - 1992** and the energy emitted by this equipment was **passed CISPR PUB. 22** both radiated and conducted emission class B limits. Testing was carried out on Oct. 27, 1999 at **SPORTON International Inc.** LAB. in Nei Hwu.

---

W. L. Huang  
General Manager

***SPORTON International Inc.***

6F, No.106, Sec. 1, Hsin Tai Wu Rd., Hsi Chih, Taipei Hsien, Taiwan, R.O.C.

## **1. General Description of Equipment under Test**

### **1.1. Applicant**

GAINWARD CO., LTD.  
12F., No. 96, Hsin Tai Wu Rd., Sec. 1,  
Hsi-Chih, Taipei Hsien, Taiwan, R.O.C.

### **1.2. Manufacturer**

Same as 1.1.

### **1.3. Basic Description of Equipment under Test**

|                   |                           |
|-------------------|---------------------------|
| Equipment         | : CARDEXpert TM64 (VANTA) |
| Model No.         | : P/N:VZD-01              |
| FCC ID            | : ICUVGA-GWVZD            |
| Trade Name        | : CARDEXpert              |
| Data Cable        | : Shielded                |
| S-video cable     | : Non-Shielded, 1.8m      |
| AV-video cable    | : Non-Shielded,1.2m       |
| Power Supply Type | : From PC                 |
| Power Cord        | : N/A                     |

### **1.4. Feature of Equipment under Test**

- nVIDIA RIVA TNT TwiN-Texel 32-bit Graphics Engine.
- 24-bit Z-buffer, 8-bit Stencil Buffer
- High Performance 128-bit 2D/GUI/DirectDraw Acceleration
- 128-bit Wide Framebuffer Interface Supports up to 16MB SGRAM/SDRAM
- 250 MHz Palette-DAC Supports up to 1600x1200@85Hz
- NTSC and PALD Digital Output Port External Digital TV Encoders Support (optional)
- Variable Length Burst DMA Bus Mastering for Data transfers over 450MB/s Throughput.
- 66MHz AGP clock rate and AGP 2X mode

## **2. Test Configuration of Equipment under Test**

### **2.1. Test Manner**

- a. The EUT has been associated with personal computer and peripherals pursuant to ANSI C63.4-1992 and configuration operated in a manner which tended to maximize its emission characteristics in a typical application.
- b. The HITACHI Monitor, DELL Keyboard, PRIMAX PS/2 Mouse, HP Printer, ACEEX Modem, SONY TV, VIEW SONIC LCD Monitor and EUT were connected to the FIC PC for EMI test.
- c. The Following display resolution were investigated during the compliance test:
  1. Horizontal frequency (640x480 to 1,600x1,200, 31.5 KHz to 106 KHz)
  2. Vertical frequency (60 Hz to 85 Hz)
- d. According to the above tests, we listed the following display modes as the worst cases:
  1. 1,600x1,200 (non-interlanced 106 KHz), refresh rate 85 Hz, CRT mode.
  2. 1,280x1,024 (non-interlanced 91 KHz), refresh rate 85 Hz, CRT mode.
  3. 1,024x768, LCD mode.
  4. 640x480, TV mode.
- e. Frequency range investigated: conduction 150 KHz to 30 MHz, radiation 30 MHz to 2,000 MHz.

### **2.2. Description of Test System**

#### **Support Unit 1. -- Personal Computer (FIC)**

|                   |                                                                                                                 |
|-------------------|-----------------------------------------------------------------------------------------------------------------|
| FCC ID            | : N/A                                                                                                           |
| Model No.         | : P2L97                                                                                                         |
| Power Supply Type | : Switching                                                                                                     |
| Power Cord        | : Non-Shielded                                                                                                  |
| Serial No.        | : SP0037                                                                                                        |
| Data Cable        | : Shielded, 360 degree via metal backshells                                                                     |
| Remark            | : This support device was tested to comply with FCC standards and authorized under a declaration of conformity. |

#### **Support Unit 2. -- Monitor (HITACHI)**

|                   |                                                   |
|-------------------|---------------------------------------------------|
| FCC ID            | : M9U9705C97BMD                                   |
| Model No.         | : CM803ET                                         |
| Power Supply Type | : Switching                                       |
| Power Cord        | : Non-Shielded                                    |
| Serial No.        | : SP0181                                          |
| Data Cable        | : Shielded, 360 degree via metal backshells, 2.0m |

## Support Unit 3. -- Keyboard (DELL)

Model No. : AT101W  
Serial No. : SP00186  
Data Cable : Shielded, 360 degree via metal backshells, 2.0m

## Support Unit 4. -- PS/2 Mouse (PRIMAX)

FCC ID : EMJMUSJQ  
Model No. : MUS9J  
Serial No. : SP0045  
Data Cable : Non-shielded, 1.75m

## Support Unit 5. -- Printer (HP)

FCC ID : DSI6XU2225  
Model No. : 2225C  
Power Supply Type : Linear  
Power Cord : Non-Shielded  
Serial No. : SP0014  
Data Cable : Shielded, 360 degree via metal backshells, 1.35m

## Support Unit 6. -- Modem (ACEEX)

FCC ID : IFAXDM1414  
Model No. : DM1414  
Power Supply Type : Linear  
Power Cord : Non-Shielded  
Serial No. : SP0015  
Data Cable : Shielded, 360 degree via metal backshells, 1.2m


## Support Unit 7. -- TV (SONY)

Model No. : PVM-14N2E  
Power Supply Type : Switching  
Serial No. : SP0097  
Power Cord : Non-Shielded  
S-video cable : Non-Shielded, 1.8m  
AV-video cable : Non-Shielded, 1.2m

## Support Unit 8. -- LCD Monitor (ViewSonic)

FCC ID : N/A  
Model No. : VPD150  
Serial No. : SP0201  
Power Supply Type : Switching  
Power Cord : Non-Shielded  
Data Cable : Shielded, 360 degree via metal backshells, 1.5m  
Remark : This support device was tested to comply with FCC standards and authorized under a declaration of conformity.

### 2.3. Connection Diagram of Test System



1. The I/O cable is connected from PC to the support unit 5.
2. The I/O cable is connected from EUT to the support unit 7.
3. The I/O cable is connected from PC to the support unit 3.
4. The I/O cable is connected from EUT to the support unit 2.
5. The I/O cable is connected from EUT to the support unit 8.
6. The I/O cable is connected from PC to the support unit 4.
7. The I/O cable is connected from PC to the support unit 6.

### **3. Test Software**

An executive program, WINFCC.EXE, which generates a complete line of continuously repeating "H" pattern was used as the test software.

The program was executed as follows :

- a. Turn on the power of all equipment.
- b. The PC reads the test program from the floppy disk drive and runs it.
- c. The PC sends "H" messages to the monitor, and the monitor displays "H" patterns on the screen.
- d. The PC sends "H" messages to the printer, then the printer prints them on the paper.
- e. The PC sends "H" messages to the modem.
- f. The PC sends "H" messages to the internal Hard Disk, and the Hard Disk reads and writes the message.
- g. Repeat the steps from b to f.

## **4. General Information of Test**

### **4.1. Test Facility**

This test was carried out by SPORTON International Inc.

Test Site Location : No. 3, Lane 238, Kang Lo Street, Nei Hwu District,  
Taipei 11424, Taiwan, R.O.C.

TEL : 886-2-2631-9739

FAX : 886-2-2631-9740

### **4.2. Standard for Methods of Measurement**

ANSI C63.4-1992

### **4.3. Test in Compliance with**

CISPR PUB. 22 Class B

### **4.4. Frequency Range Investigated**

- a. Conduction: from 150 kHz to 30 MHz
- b. Radiation : from 30 MHz to 2,000 MHz

### **4.5. Test Distance**

The test distance of radiated emission from antenna to EUT is 10 M.

## **5. Test of Conducted Powerline**

Conducted Emissions were measured from 150 kHz to 30 MHz with a bandwidth of 9 KHz on the 115 VAC power and return leads of the EUT according to the methods defined in ANSI C63.4-1992 Section 3.1. The EUT was placed on a nonmetallic stand in a shielded room 0.8 meters above the ground plane as shown in section 5.3. The interface cables and equipment positioning were varied within limits of reasonable applications to determine the position produced maximum conducted emissions.


### **5.1. Major Measuring Instruments**

|                 |              |
|-----------------|--------------|
| ● Test Receiver | ( R&S ESH3 ) |
| Attenuation     | 0 dB         |
| Start Frequency | 0.15 MHz     |
| Stop Frequency  | 30 MHz       |
| Step MHz        | 0.007 MHz    |
| IF Bandwidth    | 9 KHz        |

## **5.2. Test Procedures**

- a. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
- b. Connect EUT to the power mains through a line impedance stabilization network (LISN).
- c. All the support units are connect to the other LISN.
- d. The LISN provides 50 ohm coupling impedance for the measuring instrument.
- e. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
- f. Both sides of AC line were checked for maximum conducted interference.
- g. The frequency range from 150 kHz to 30 MHz was searched.
- h. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- i. If the emission level of the EUT in peak mode was 6 dB lower than the limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 6 dB margin will be retested one by one using the quasi-peak method and reported.

### 5.3. Typical Test Setup Layout of Conducted Powerline



## 5.4. Test Result of AC Powerline Conducted Emission

5.4.1. Test mode : VANTA Chipset 1600x1200 85Hz/106K (CRT mode)

- Temperature : 28°C
- Relative Humidity : 59 %
- Test Date : Oct. 27, 1999

**The Conducted Emission test was passed at minimum margin**

### LINE 0.160 MHz / 48.20 dBuV.

| Freq.<br>(MHz) | Line<br>or<br>Neutral | Meter Reading  |                |              |              | Limits         |                |              |              | Margin       |              |
|----------------|-----------------------|----------------|----------------|--------------|--------------|----------------|----------------|--------------|--------------|--------------|--------------|
|                |                       | Q.P.<br>(dBuV) | A.V.<br>(dBuV) | Q.P.<br>(uV) | A.V.<br>(uV) | Q.P.<br>(dBuV) | A.V.<br>(dBuV) | Q.P.<br>(uV) | A.V.<br>(uV) | Q.P.<br>(dB) | A.V.<br>(dB) |
| 0.160          | L                     | 51.00          | 48.20          | 354.81       | 257.04       | 65.46          | 55.46          | 1875.85      | 593.20       | -14.5        | -7.3         |
| 0.270          | L                     | 49.40          | 42.10          | 295.12       | 127.35       | 61.12          | 51.12          | 1137.36      | 359.66       | -11.7        | -9.0         |
| 0.420          | L                     | 45.70          | 38.60          | 192.75       | 85.11        | 57.45          | 47.45          | 745.43       | 235.73       | -11.7        | -8.8         |
| 0.170          | N                     | 50.20          | 46.70          | 323.59       | 216.27       | 64.96          | 54.96          | 1770.19      | 559.78       | -14.8        | -8.3         |
| 0.250          | N                     | 47.20          | 42.10          | 229.09       | 127.35       | 61.76          | 51.76          | 1224.22      | 387.13       | -14.6        | -9.7         |
| 0.350          | N                     | 44.70          | 38.30          | 171.79       | 82.22        | 58.96          | 48.96          | 887.41       | 280.62       | -14.3        | -10.7        |

Test Engineer : \_\_\_\_\_  
Samuel Chang

5.4.2. Test mode : VANTA Chipset 1280x1024 85Hz/91K (CRT mode)

- Temperature : 28°C
- Relative Humidity : 59 %
- Test Date : Oct. 27, 1999

**The Conducted Emission test was passed at minimum margin**

**NEUTRAL 0.340 MHz / 34.10 dBuV.**

| Freq.<br>(MHz) | Line<br>or<br>Neutral | Meter Reading  |                |              |              | Limits         |                |              |              | Margin       |              |
|----------------|-----------------------|----------------|----------------|--------------|--------------|----------------|----------------|--------------|--------------|--------------|--------------|
|                |                       | Q.P.<br>(dBuV) | A.V.<br>(dBuV) | Q.P.<br>(uV) | A.V.<br>(uV) | Q.P.<br>(dBuV) | A.V.<br>(dBuV) | Q.P.<br>(uV) | A.V.<br>(uV) | Q.P.<br>(dB) | A.V.<br>(dB) |
| 0.170          | L                     | 49.10          | 32.70          | 285.10       | 43.15        | 64.96          | 54.96          | 1770.19      | 559.78       | -15.9        | -22.3        |
| 0.250          | L                     | 38.20          | 31.10          | 81.28        | 35.89        | 61.76          | 51.76          | 1224.22      | 387.13       | -23.6        | -20.7        |
| 0.350          | L                     | 39.50          | 33.70          | 94.41        | 48.42        | 58.96          | 48.96          | 887.41       | 280.62       | -19.5        | -15.3        |
| 0.160          | N                     | 50.10          | 40.20          | 319.89       | 102.33       | 65.46          | 55.46          | 1875.85      | 593.20       | -15.4        | -15.3        |
| 0.250          | N                     | 41.70          | 35.10          | 121.62       | 56.89        | 61.76          | 51.76          | 1224.22      | 387.13       | -20.1        | -16.7        |
| 0.340          | N                     | 39.80          | 34.10          | 97.72        | 50.70        | 59.20          | 49.20          | 912.35       | 288.51       | -19.4        | -15.1        |

Test Engineer : \_\_\_\_\_  
Samuel Chang

## 5.4.3. Test mode : VANTA Chipset 1024x768 (LCD mode)

- Temperature : 28°C
- Relative Humidity : 59 %
- Test Date : Oct. 27, 1999

**The Conducted Emission test was passed at minimum margin**

**NEUTRAL 0.160 MHz / 47.70 dBuV.**

| Freq.<br>(MHz) | Line<br>or<br>Neutral | Meter Reading  |                |              |              | Limits         |                |              |              | Margin       |              |
|----------------|-----------------------|----------------|----------------|--------------|--------------|----------------|----------------|--------------|--------------|--------------|--------------|
|                |                       | Q.P.<br>(dBuV) | A.V.<br>(dBuV) | Q.P.<br>(uV) | A.V.<br>(uV) | Q.P.<br>(dBuV) | A.V.<br>(dBuV) | Q.P.<br>(uV) | A.V.<br>(uV) | Q.P.<br>(dB) | A.V.<br>(dB) |
| 0.170          | L                     | 50.80          | 47.10          | 346.74       | 226.46       | 64.96          | 54.96          | 1770.19      | 559.78       | -14.2        | -7.9         |
| 0.240          | L                     | 39.90          | 32.50          | 98.86        | 42.17        | 62.10          | 52.10          | 1272.95      | 402.54       | -22.2        | -19.6        |
| 0.370          | L                     | 41.50          | 35.70          | 118.85       | 60.95        | 58.50          | 48.50          | 841.49       | 266.10       | -17.0        | -12.8        |
| 0.160          | N                     | 51.10          | 47.70          | 358.92       | 242.66       | 65.46          | 55.46          | 1875.85      | 593.20       | -14.4        | -7.8         |
| 0.250          | N                     | 39.20          | 31.10          | 91.20        | 35.89        | 61.76          | 51.76          | 1224.22      | 387.13       | -22.6        | -20.7        |
| 0.350          | N                     | 40.10          | 32.50          | 101.16       | 42.17        | 58.96          | 48.96          | 887.41       | 280.62       | -18.9        | -16.5        |

Test Engineer : \_\_\_\_\_  
Samuel Chang

## 5.4.4. Test mode : VANTA Chipset 640x480 (TV mode)

- Temperature : 28°C
- Relative Humidity : 59 %
- Test Date : Oct. 27, 1999

**The Conducted Emission test was passed at minimum margin**

**NEUTRAL 0.160 MHz / 47.50 dBuV.**

| Freq.<br>(MHz) | Line<br>or<br>Neutral | Meter Reading  |                |              |              | Limits         |                |              |              | Margin       |              |
|----------------|-----------------------|----------------|----------------|--------------|--------------|----------------|----------------|--------------|--------------|--------------|--------------|
|                |                       | Q.P.<br>(dBuV) | A.V.<br>(dBuV) | Q.P.<br>(uV) | A.V.<br>(uV) | Q.P.<br>(dBuV) | A.V.<br>(dBuV) | Q.P.<br>(uV) | A.V.<br>(uV) | Q.P.<br>(dB) | A.V.<br>(dB) |
| 0.160          | L                     | 51.30          | 46.30          | 367.28       | 206.54       | 65.46          | 55.46          | 1875.85      | 593.20       | -14.2        | -9.2         |
| 0.250          | L                     | 47.70          | 41.40          | 242.66       | 117.49       | 61.76          | 51.76          | 1224.22      | 387.13       | -14.1        | -10.4        |
| 0.350          | L                     | 39.30          | 36.40          | 92.26        | 66.07        | 58.96          | 48.96          | 887.41       | 280.62       | -19.7        | -12.6        |
| 0.160          | N                     | 50.30          | 47.50          | 327.34       | 237.14       | 65.46          | 55.46          | 1875.85      | 593.20       | -15.2        | -8.0         |
| 0.250          | N                     | 49.10          | 42.30          | 285.10       | 130.32       | 61.76          | 51.76          | 1224.22      | 387.13       | -12.7        | -9.5         |
| 0.340          | N                     | 41.80          | 38.60          | 123.03       | 85.11        | 59.20          | 49.20          | 912.35       | 288.51       | -17.4        | -10.6        |

Test Engineer : \_\_\_\_\_  
Samuel Chang

5.4.5. Test mode : TNT2 M64 Chipset 1600x1200 85Hz/106K (CRT mode)

- Temperature : 28°C
- Relative Humidity : 59 %
- Test Date : Oct. 27, 1999

**The Conducted Emission test was passed at minimum margin**

**NEUTRAL 0.170 MHz / 46.70 dBuV.**

| Freq.<br>(MHz) | Line<br>or<br>Neutral | Meter Reading  |                |              |              | Limits         |                |              |              | Margin       |              |
|----------------|-----------------------|----------------|----------------|--------------|--------------|----------------|----------------|--------------|--------------|--------------|--------------|
|                |                       | Q.P.<br>(dBuV) | A.V.<br>(dBuV) | Q.P.<br>(uV) | A.V.<br>(uV) | Q.P.<br>(dBuV) | A.V.<br>(dBuV) | Q.P.<br>(uV) | A.V.<br>(uV) | Q.P.<br>(dB) | A.V.<br>(dB) |
| 0.160          | L                     | 49.80          | 47.20          | 309.03       | 229.09       | 65.46          | 55.46          | 1875.85      | 593.20       | -15.7        | -8.3         |
| 0.210          | L                     | 45.10          | 41.70          | 179.89       | 121.62       | 63.21          | 53.21          | 1446.32      | 457.37       | -18.1        | -11.5        |
| 0.270          | L                     | 40.50          | 38.50          | 105.93       | 84.14        | 61.12          | 51.12          | 1137.36      | 359.66       | -20.6        | -12.6        |
| 0.170          | N                     | 49.50          | 46.70          | 298.54       | 216.27       | 64.96          | 54.96          | 1770.19      | 559.78       | -15.5        | -8.3         |
| 0.220          | N                     | 45.40          | 42.10          | 186.21       | 127.35       | 62.82          | 52.82          | 1383.40      | 437.47       | -17.4        | -10.7        |
| 0.260          | N                     | 40.70          | 37.80          | 108.39       | 77.62        | 61.43          | 51.43          | 1179.15      | 372.88       | -20.7        | -13.6        |

Test Engineer : \_\_\_\_\_  
Samuel Chang

5.4.6. Test mode : TNT2 M64 Chipset 1280x1024 85Hz/91K (CRT mode)

- Temperature : 28°C
- Relative Humidity : 59 %
- Test Date : Oct. 27, 1999

**The Conducted Emission test was passed at minimum margin**

**LINE 0.170 MHz / 45.70 dBuV.**

| Freq.<br>(MHz) | Line<br>or<br>Neutral | Meter Reading  |                |              |              | Limits         |                |              |              | Margin       |              |
|----------------|-----------------------|----------------|----------------|--------------|--------------|----------------|----------------|--------------|--------------|--------------|--------------|
|                |                       | Q.P.<br>(dBuV) | A.V.<br>(dBuV) | Q.P.<br>(uV) | A.V.<br>(uV) | Q.P.<br>(dBuV) | A.V.<br>(dBuV) | Q.P.<br>(uV) | A.V.<br>(uV) | Q.P.<br>(dB) | A.V.<br>(dB) |
| 0.170          | L                     | 50.10          | 45.70          | 319.89       | 192.75       | 64.96          | 54.96          | 1770.19      | 559.78       | -14.9        | -9.3         |
| 0.250          | L                     | 40.80          | 37.60          | 109.65       | 75.86        | 61.76          | 51.76          | 1224.22      | 387.13       | -21.0        | -14.2        |
| 0.350          | L                     | 37.80          | 32.50          | 77.62        | 42.17        | 58.96          | 48.96          | 887.41       | 280.62       | -21.2        | -16.5        |
| 0.160          | N                     | 49.70          | 42.60          | 305.49       | 134.90       | 65.46          | 55.46          | 1875.85      | 593.20       | -15.8        | -12.9        |
| 0.260          | N                     | 38.60          | 35.50          | 85.11        | 59.57        | 61.43          | 51.43          | 1179.15      | 372.88       | -22.8        | -15.9        |
| 0.350          | N                     | 32.50          | 28.90          | 42.17        | 27.86        | 58.96          | 48.96          | 887.41       | 280.62       | -26.5        | -20.1        |

Test Engineer : \_\_\_\_\_  
Samuel Chang

5.4.7. Test mode : TNT2 M64 Chipset 1024x768 (LCD mode)

- Temperature : 28°C
- Relative Humidity : 59 %
- Test Date : Oct. 27, 1999

**The Conducted Emission test was passed at minimum margin**

**LINE 0.160 MHz / 47.20 dBuV.**

| Freq.<br>(MHz) | Line<br>or<br>Neutral | Meter Reading  |                |              |              | Limits         |                |              |              | Margin       |              |
|----------------|-----------------------|----------------|----------------|--------------|--------------|----------------|----------------|--------------|--------------|--------------|--------------|
|                |                       | Q.P.<br>(dBuV) | A.V.<br>(dBuV) | Q.P.<br>(uV) | A.V.<br>(uV) | Q.P.<br>(dBuV) | A.V.<br>(dBuV) | Q.P.<br>(uV) | A.V.<br>(uV) | Q.P.<br>(dB) | A.V.<br>(dB) |
| 0.160          | L                     | 50.50          | 47.20          | 334.97       | 229.09       | 65.46          | 55.46          | 1875.85      | 593.20       | -15.0        | -8.3         |
| 0.250          | L                     | 39.20          | 31.60          | 91.20        | 38.02        | 61.76          | 51.76          | 1224.22      | 387.13       | -22.6        | -20.2        |
| 0.360          | L                     | 37.10          | 27.50          | 71.61        | 23.71        | 58.73          | 48.73          | 863.82       | 273.16       | -21.6        | -21.2        |
| 0.160          | N                     | 49.70          | 41.10          | 305.49       | 113.50       | 65.46          | 55.46          | 1875.85      | 593.20       | -15.8        | -14.4        |
| 0.260          | N                     | 38.80          | 38.40          | 87.10        | 83.18        | 61.43          | 51.43          | 1179.15      | 372.88       | -22.6        | -13.0        |
| 0.350          | N                     | 40.20          | 39.50          | 102.33       | 94.41        | 58.96          | 48.96          | 887.41       | 280.62       | -18.8        | -9.5         |

Test Engineer : \_\_\_\_\_  
Samuel Chang

5.4.8. Test mode : TNT2 M64 Chipset 640x480 (TV mode)

- Temperature : 28°C
- Relative Humidity : 59 %
- Test Date : Oct. 27, 1999

**The Conducted Emission test was passed at minimum margin**

**LINE 0.170 MHz / 42.70 dBuV.**

| Freq.<br>(MHz) | Line<br>or<br>Neutral | Meter Reading  |                |              |              | Limits         |                |              |              | Margin       |              |
|----------------|-----------------------|----------------|----------------|--------------|--------------|----------------|----------------|--------------|--------------|--------------|--------------|
|                |                       | Q.P.<br>(dBuV) | A.V.<br>(dBuV) | Q.P.<br>(uV) | A.V.<br>(uV) | Q.P.<br>(dBuV) | A.V.<br>(dBuV) | Q.P.<br>(uV) | A.V.<br>(uV) | Q.P.<br>(dB) | A.V.<br>(dB) |
| 0.170          | L                     | 49.50          | 42.70          | 298.54       | 136.46       | 64.96          | 54.96          | 1770.19      | 559.78       | -15.5        | -12.3        |
| 0.250          | L                     | 41.60          | 39.40          | 120.23       | 93.33        | 61.76          | 51.76          | 1224.22      | 387.13       | -20.2        | -12.4        |
| 0.270          | L                     | 38.50          | 36.10          | 84.14        | 63.83        | 61.12          | 51.12          | 1137.36      | 359.66       | -22.6        | -15.0        |
| 0.160          | N                     | 48.10          | 43.20          | 254.10       | 144.54       | 65.46          | 55.46          | 1875.85      | 593.20       | -17.4        | -12.3        |
| 0.250          | N                     | 40.70          | 38.20          | 108.39       | 81.28        | 61.76          | 51.76          | 1224.22      | 387.13       | -21.1        | -13.6        |
| 0.360          | N                     | 37.80          | 31.60          | 77.62        | 38.02        | 58.73          | 48.73          | 863.82       | 273.16       | -20.9        | -17.1        |

Test Engineer : \_\_\_\_\_  
Samuel Chang

**5.5. Photographs of Counducted Powerline Test Configuration**

- The photographs show the configuration that generates the maximum emission.  
VANTA Chipset CRT mode

FRONT VIEW



REAR VIEW



SIDE VIEW



VANTA Chipset LCD mode

FRONT VIEW



REAR VIEW



SIDE VIEW



VANTA Chipset TV mode

FRONT VIEW



REAR VIEW



SIDE VIEW



TNT2 M64 Chipset CRT mode

FRONT VIEW



REAR VIEW



SIDE VIEW



TNT2 M64 Chipset LCD mode

FRONT VIEW



REAR VIEW



SIDE VIEW



TNT2 M64 Chipset TV mode

FRONT VIEW



REAR VIEW



SIDE VIEW



## **6. Test of Radiated Emission**

Radiated emissions from 30 MHz to 2,000 MHz were measured with a bandwidth of 120 kHz according to the methods defines in ANSI C63.4-1992. The EUT was placed on a nonmetallic stand in the open-field site, 0.8 meter above the ground plane, as shown in section 6.3. The interface cables and equipment positions were varied within limits of reasonable applications to determine the positions producing maximum radiated emissions.


### **6.1. Major Measuring Instruments**

- Amplifier ( HP 87405A )
  - Attenuation 0 dB
  - RF Gain 20 dB
  - Signal Input 10 MHz to 3 GHz
  
- Spectrum Analyzer ( HP 8594A )
  - Attenuation 0 dB
  - Start Frequency 30 MHz
  - Stop Frequency 2000 MHz
  - Resolution Bandwidth 1 MHz
  - Video Bandwidth 1 MHz
  - Signal Input 9 KHz to 2.9 GHz

**6.2. Test Procedures**

- a. The EUT was placed on a rotatable table top 0.8 meter above ground.
- b. The EUT was set 10 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
- c. The table was rotated 360 degrees to determine the position of the highest radiation.
- d. The antenna is a half wave dipole and its height is varied between one meter and four meters above ground to find the maximum value of the field strength both horizontal polarization and vertical polarization of the antenna are set to make the measurement.
- e. For each suspected emission the EUT was arranged to its worst case and then tune the antenna tower (from 1 M to 4 M) and turn table (from 0 degree to 360 degrees) to find the maximum reading.
- f. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 6 dB lower than the limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 6 dB margin will be repeated one by one using the quasi-peak method and reported.

### 6.3. Typical Test Setup Layout of Radiated Emission



## 6.4. Test Result of Radiated Emission

6.4.1. Test mode : VANTA Chipset 1600x1200 85Hz/106K (CRT mode)

- Test Distance : 10 M
- Temperature : 31°C
- Relative Humidity : 62 %
- Test Date : Oct. 20, 1999
- Emission level (dBuV/m) = 20 log Emission level (uV/m)
- Corrected Reading : Antenna Factor + Cable Loss + Reading = Emission

The Radiated Emission test was passed at minimum margin

400.962 MHz / 33.10 dBuV (VERTICAL) Antenna Height 4 Meter, Turntable Degree 180 °.

| Frequency<br>(MHz) | Polarity | Antenna<br>Factor<br>(dB/m) | Cable<br>Loss<br>(dB) | Reading<br>(dBuV) | Limits   |        | Emission<br>(dBuV/m) | Level<br>(uV/m) | Margin<br>(dB) |
|--------------------|----------|-----------------------------|-----------------------|-------------------|----------|--------|----------------------|-----------------|----------------|
|                    |          |                             |                       |                   | (dBuV/m) | (uV/m) |                      |                 |                |
| 57.507             | H        | 5.82                        | 1.08                  | 11.35             | 30.00    | 31.62  | 18.25                | 8.18            | -11.75         |
| 117.365            | H        | 12.08                       | 1.83                  | 6.06              | 30.00    | 31.62  | 19.97                | 9.97            | -10.03         |
| 137.433            | H        | 10.61                       | 1.66                  | 9.06              | 30.00    | 31.62  | 21.33                | 11.65           | -8.67          |
| 400.962            | H        | 15.47                       | 3.20                  | 11.03             | 37.00    | 70.79  | 29.70                | 30.55           | -7.30          |
| 57.507             | V        | 5.82                        | 1.08                  | 15.15             | 30.00    | 31.62  | 22.05                | 12.66           | -7.95          |
| 400.962            | V        | 15.47                       | 3.20                  | 14.43             | 37.00    | 70.79  | 33.10                | 45.19           | -3.90          |

Test Engineer : \_\_\_\_\_  
Samuel Chang

**6.4.2. Test mode : VANTA Chipset 1280x1024 85Hz/91K (CRT mode)**

- Test Distance : 10 M
- Temperature : 31°C
- Relative Humidity : 62 %
- Test Date : Oct. 20, 1999
- Emission level (dBuV/m) = 20 log Emission level (uV/m)
- Corrected Reading : Antenna Factor + Cable Loss + Reading = Emission

**The Radiated Emission test was passed at minimum margin**

**429.688 MHz / 31.44 dBuV (VERTICAL) Antenna Height 4 Meter, Turntable Degree 180 °.**

| Frequency<br>(MHz) | Polarity | Antenna<br>Factor<br>(dB/m) | Cable<br>Loss<br>(dB) | Reading<br>(dBuV) | Limits   |        | Emission<br>(dBuV/m) | Level<br>(uV/m) | Margin<br>(dB) |
|--------------------|----------|-----------------------------|-----------------------|-------------------|----------|--------|----------------------|-----------------|----------------|
|                    |          |                             |                       |                   | (dBuV/m) | (uV/m) |                      |                 |                |
| 143.142            | H        | 10.53                       | 1.75                  | 8.52              | 30.00    | 31.62  | 20.80                | 10.96           | -9.20          |
| 334.313            | H        | 14.14                       | 3.20                  | 11.91             | 37.00    | 70.79  | 29.25                | 29.01           | -7.75          |
| 429.870            | H        | 16.22                       | 3.26                  | 9.54              | 37.00    | 70.79  | 29.02                | 28.25           | -7.98          |
| 240.362            | V        | 12.02                       | 2.41                  | 14.89             | 37.00    | 70.79  | 29.32                | 29.24           | -7.68          |
| 334.313            | V        | 14.14                       | 3.20                  | 10.91             | 37.00    | 70.79  | 28.25                | 25.85           | -8.75          |
| 429.688            | V        | 16.22                       | 3.26                  | 11.96             | 37.00    | 70.79  | 31.44                | 37.33           | -5.56          |

Test Engineer : \_\_\_\_\_  
Samuel Chang

**6.4.3. Test mode : VANTA Chipset 1024x768 (LCD mode)**

- Test Distance : 10 M
- Temperature : 31°C
- Relative Humidity : 62 %
- Test Date : Oct. 22, 1999
- Emission level (dBuV/m) = 20 log Emission level (uV/m)
- Corrected Reading : Antenna Factor + Cable Loss + Reading = Emission

**The Radiated Emission test was passed at minimum margin**

**601.712 MHz / 33.07 dBuV (HORIZONTAL) Antenna Height 4 Meter, Turntable Degree 265 °.**

| Frequency<br>(MHz) | Polarity | Antenna<br>Factor<br>(dB/m) | Cable<br>Loss<br>(dB) | Reading<br>(dBuV) | Limits   |        | Emission<br>(dBuV/m) | Level<br>(uV/m) | Margin<br>(dB) |
|--------------------|----------|-----------------------------|-----------------------|-------------------|----------|--------|----------------------|-----------------|----------------|
|                    |          |                             |                       |                   | (dBuV/m) | (uV/m) |                      |                 |                |
| 601.712            | H        | 19.01                       | 4.10                  | 9.96              | 37.00    | 70.79  | 33.07                | 45.03           | -3.93          |
| 146.602            | V        | 10.52                       | 1.85                  | 12.13             | 30.00    | 31.62  | 24.50                | 16.79           | -5.50          |
| 194.523            | V        | 9.45                        | 1.75                  | 14.53             | 30.00    | 31.62  | 25.73                | 19.34           | -4.27          |
| 216.272            | V        | 10.43                       | 2.27                  | 11.92             | 30.00    | 31.62  | 24.62                | 17.02           | -5.38          |
| 294.163            | V        | 13.18                       | 2.77                  | 17.08             | 37.00    | 70.79  | 33.03                | 44.82           | -3.97          |
| 390.523            | V        | 15.29                       | 3.16                  | 13.24             | 37.00    | 70.79  | 31.69                | 38.41           | -5.31          |

Test Engineer : \_\_\_\_\_  
Samuel Chang

**6.4.4. Test mode : VANTA Chipset 640x480 (TV mode)**

- Test Distance : 10 M
- Temperature : 31°C
- Relative Humidity : 62 %
- Test Date : Oct. 20, 1999
- Emission level (dBuV/m) = 20 log Emission level (uV/m)
- Corrected Reading : Antenna Factor + Cable Loss + Reading = Emission

**The Radiated Emission test was passed at minimum margin**

**133.400 MHz / 24.87 dBuV (VERTICAL) Antenna Height 1 Meter, Turntable Degree 150 °.**

| Frequency<br>(MHz) | Polarity | Antenna<br>Factor<br>(dB/m) | Cable<br>Loss<br>(dB) | Reading<br>(dBuV) | Limits   |        | Emission<br>(dBuV/m) | Level<br>(uV/m) | Margin<br>(dB) |
|--------------------|----------|-----------------------------|-----------------------|-------------------|----------|--------|----------------------|-----------------|----------------|
|                    |          |                             |                       |                   | (dBuV/m) | (uV/m) |                      |                 |                |
| 149.000            | H        | 10.52                       | 1.96                  | 7.61              | 30.00    | 31.62  | 20.09                | 10.10           | -9.91          |
| 450.748            | H        | 16.76                       | 3.30                  | 7.38              | 37.00    | 70.79  | 27.44                | 23.55           | -9.56          |
| 120.200            | V        | 12.33                       | 1.80                  | 6.20              | 30.00    | 31.62  | 20.33                | 10.39           | -9.67          |
| 133.400            | V        | 10.77                       | 1.78                  | 12.32             | 30.00    | 31.62  | 24.87                | 17.52           | -5.13          |
| 148.200            | V        | 10.52                       | 1.93                  | 11.42             | 30.00    | 31.62  | 23.87                | 15.61           | -6.13          |
| 204.413            | V        | 9.67                        | 1.87                  | 9.24              | 30.00    | 31.62  | 20.78                | 10.94           | -9.22          |

Test Engineer : \_\_\_\_\_  
Samuel Chang

**6.4.5. Test mode : TNT2 M64 Chipset 1600x1200 85Hz/106K (CRT mode)**

- Test Distance : 10 M
- Temperature : 31°C
- Relative Humidity : 62 %
- Test Date : Oct. 20, 1999
- Emission level (dBuV/m) = 20 log Emission level (uV/m)
- Corrected Reading : Antenna Factor + Cable Loss + Reading = Emission

**The Radiated Emission test was passed at minimum margin**

**152.657 MHz / 26.40 dBuV (VERTICAL) Antenna Height 1 Meter, Turntable Degree 320 °.**

| Frequency<br>(MHz) | Polarity | Antenna<br>Factor<br>(dB/m) | Cable<br>Loss<br>(dB) | Reading<br>(dBuV) | Limits   |        | Emission<br>(dBuV/m) | Level<br>(uV/m) | Margin<br>(dB) |
|--------------------|----------|-----------------------------|-----------------------|-------------------|----------|--------|----------------------|-----------------|----------------|
|                    |          |                             |                       |                   | (dBuV/m) | (uV/m) |                      |                 |                |
| 119.614            | H        | 12.25                       | 1.81                  | 12.11             | 30.00    | 31.62  | 26.17                | 20.35           | -3.83          |
| 128.956            | H        | 10.96                       | 1.89                  | 9.86              | 30.00    | 31.62  | 22.71                | 13.66           | -7.29          |
| 200.212            | H        | 9.35                        | 1.70                  | 13.86             | 30.00    | 31.62  | 24.91                | 17.60           | -5.09          |
| 205.833            | H        | 9.73                        | 1.90                  | 13.67             | 30.00    | 31.62  | 25.30                | 18.41           | -4.70          |
| 50.587             | V        | 7.01                        | 1.00                  | 16.67             | 30.00    | 31.62  | 24.68                | 17.14           | -5.32          |
| 152.657            | V        | 10.34                       | 2.02                  | 14.04             | 30.00    | 31.62  | 26.40                | 20.89           | -3.60          |

Test Engineer : \_\_\_\_\_  
Samuel Chang

**6.4.6. Test mode : TNT2 M64 Chipset 1280x1024 85Hz/91K (CRT mode)**

- Test Distance : 10 M
- Temperature : 31°C
- Relative Humidity : 62 %
- Test Date : Oct. 20, 1999
- Emission level (dBuV/m) = 20 log Emission level (uV/m)
- Corrected Reading : Antenna Factor + Cable Loss + Reading = Emission

**The Radiated Emission test was passed at minimum margin**

**430.107 MHz / 31.61 dBuV (VERTICAL) Antenna Height 1 Meter, Turntable Degree 262 °.**

| Frequency<br>(MHz) | Polarity | Antenna<br>Factor<br>(dB/m) | Cable<br>Loss<br>(dB) | Reading<br>(dBuV) | Limits   |        | Emission<br>(dBuV/m) | Level<br>(uV/m) | Margin<br>(dB) |
|--------------------|----------|-----------------------------|-----------------------|-------------------|----------|--------|----------------------|-----------------|----------------|
|                    |          |                             |                       |                   | (dBuV/m) | (uV/m) |                      |                 |                |
| 224.108            | H        | 10.94                       | 2.40                  | 11.24             | 30.00    | 31.62  | 24.58                | 16.94           | -5.42          |
| 427.976            | H        | 16.19                       | 3.26                  | 10.55             | 37.00    | 70.79  | 30.00                | 31.62           | -7.00          |
| 50.933             | V        | 6.84                        | 1.00                  | 16.75             | 30.00    | 31.62  | 24.59                | 16.96           | -5.41          |
| 86.052             | V        | 8.14                        | 1.40                  | 9.98              | 30.00    | 31.62  | 19.52                | 9.46            | -10.48         |
| 217.750            | V        | 10.56                       | 2.33                  | 8.99              | 30.00    | 31.62  | 21.88                | 12.42           | -8.12          |
| 430.107            | V        | 16.22                       | 2.44                  | 12.95             | 37.00    | 70.79  | 31.61                | 38.06           | -5.39          |

Test Engineer : \_\_\_\_\_  
Samuel Chang

**6.4.7. Test mode : TNT2 M64 Chipset 1024x768 (LCD mode)**

- Test Distance : 10 M
- Temperature : 31°C
- Relative Humidity : 62 %
- Test Date : Oct. 27, 1999
- Emission level (dBuV/m) = 20 log Emission level (uV/m)
- Corrected Reading : Antenna Factor + Cable Loss + Reading = Emission

**The Radiated Emission test was passed at minimum margin**

**162.496 MHz / 25.98 dBuV (VERTICAL) Antenna Height 1 Meter, Turntable Degree 269 °.**

| Frequency<br>(MHz) | Polarity | Antenna<br>Factor<br>(dB/m) | Cable<br>Loss<br>(dB) | Reading<br>(dBuV) | Limits   |        | Emission<br>(dBuV/m) | Level<br>(uV/m) | Margin<br>(dB) |
|--------------------|----------|-----------------------------|-----------------------|-------------------|----------|--------|----------------------|-----------------|----------------|
|                    |          |                             |                       |                   | (dBuV/m) | (uV/m) |                      |                 |                |
| 129.994            | V        | 10.93                       | 1.90                  | 12.14             | 30.00    | 31.62  | 24.97                | 17.72           | -5.03          |
| 162.496            | V        | 9.60                        | 1.95                  | 14.43             | 30.00    | 31.62  | 25.98                | 19.91           | -4.02          |
| 178.434            | V        | 9.69                        | 1.93                  | 12.94             | 30.00    | 31.62  | 24.56                | 16.90           | -5.44          |
| 194.869            | V        | 9.45                        | 1.75                  | 14.73             | 30.00    | 31.62  | 25.93                | 19.79           | -4.07          |
| 201.015            | V        | 9.42                        | 1.73                  | 13.52             | 30.00    | 31.62  | 24.67                | 17.12           | -5.33          |
| 228.317            | V        | 11.20                       | 2.40                  | 11.76             | 30.00    | 31.62  | 25.36                | 18.54           | -4.64          |

Test Engineer : \_\_\_\_\_  
Samuel Chang

**6.4.8. Test mode : TNT2 M64 Chipset 640x480 (TV mode)**

- Test Distance : 10 M
- Temperature : 31°C
- Relative Humidity : 62 %
- Test Date : Oct. 22, 1999
- Emission level (dBuV/m) = 20 log Emission level (uV/m)
- Corrected Reading : Antenna Factor + Cable Loss + Reading = Emission

**The Radiated Emission test was passed at minimum margin**

**205.833 MHz / 25.87 dBuV (HORIZONTAL) Antenna Height 4 Meter, Turntable Degree 145 °.**

| Frequency<br>(MHz) | Polarity | Antenna<br>Factor<br>(dB/m) | Cable<br>Loss<br>(dB) | Reading<br>(dBuV) | Limits   |        | Emission<br>(dBuV/m) | Level<br>(uV/m) | Margin<br>(dB) |
|--------------------|----------|-----------------------------|-----------------------|-------------------|----------|--------|----------------------|-----------------|----------------|
|                    |          |                             |                       |                   | (dBuV/m) | (uV/m) |                      |                 |                |
| 59.064             | H        | 5.49                        | 1.16                  | 14.68             | 30.00    | 31.62  | 21.33                | 11.65           | -8.67          |
| 131.897            | H        | 10.85                       | 1.84                  | 12.04             | 30.00    | 31.62  | 24.73                | 17.24           | -5.27          |
| 205.833            | H        | 9.73                        | 1.90                  | 14.24             | 30.00    | 31.62  | 25.87                | 19.66           | -4.13          |
| 217.878            | H        | 10.56                       | 2.33                  | 7.87              | 30.00    | 31.62  | 20.76                | 10.91           | -9.24          |
| 133.973            | V        | 10.77                       | 1.78                  | 7.54              | 30.00    | 31.62  | 20.09                | 10.10           | -9.91          |
| 147.813            | V        | 10.52                       | 1.89                  | 8.73              | 30.00    | 31.62  | 21.14                | 11.40           | -8.86          |

Test Engineer : \_\_\_\_\_  
Samuel Chang

**6.5. Photographs of Radiated Emission Test Configuration**

- The photographs show the configuration that generates the maximum emission.  
VANTA Chipset CRT mode

FRONT VIEW



REAR VIEW



VANTA Chipset LCD mode

FRONT VIEW



REAR VIEW



VANTA Chipset TV mode

FRONT VIEW



REAR VIEW



TNT2 M64 Chipset CRT mode

FRONT VIEW



REAR VIEW



TNT2 M64 Chipset LCD mode

FRONT VIEW



REAR VIEW



TNT2 M64 Chipset TV mode

FRONT VIEW



REAR VIEW



## 7. Antenna Factor & Cable Loss

| Frequency (MHz) | Antenna Factor (dB) | Cable Loss (dB) |
|-----------------|---------------------|-----------------|
| 30              | 17.2                | 0.7             |
| 35              | 16.2                | 0.8             |
| 40              | 13.0                | 0.8             |
| 45              | 10.5                | 0.9             |
| 50              | 7.0                 | 1.0             |
| 55              | 6.2                 | 1.0             |
| 60              | 5.3                 | 1.2             |
| 65              | 5.2                 | 1.1             |
| 70              | 5.2                 | 1.2             |
| 75              | 5.9                 | 1.2             |
| 80              | 6.8                 | 1.3             |
| 85              | 7.9                 | 1.4             |
| 90              | 9.0                 | 1.4             |
| 95              | 9.8                 | 1.5             |
| 100             | 10.6                | 1.9             |
| 110             | 11.5                | 1.9             |
| 120             | 12.3                | 1.8             |
| 130             | 10.9                | 1.9             |
| 140             | 10.5                | 1.6             |
| 150             | 10.5                | 2.0             |
| 160             | 9.6                 | 2.1             |
| 170             | 9.6                 | 1.6             |
| 180             | 9.7                 | 2.0             |
| 190             | 9.5                 | 1.8             |
| 200             | 9.4                 | 1.7             |
| 220             | 10.7                | 2.4             |
| 240             | 12.0                | 2.4             |
| 260             | 12.8                | 2.6             |
| 280             | 13.0                | 2.7             |
| 300             | 13.3                | 2.8             |
| 320             | 13.8                | 3.1             |
| 340             | 14.3                | 3.2             |
| 360             | 14.7                | 3.2             |
| 380             | 15.1                | 3.1             |
| 400             | 15.5                | 3.2             |
| 450             | 16.7                | 3.3             |
| 500             | 17.8                | 3.3             |
| 550             | 19.2                | 3.8             |
| 600             | 19.0                | 4.1             |
| 650             | 18.7                | 4.0             |
| 700             | 18.5                | 4.2             |
| 750             | 18.5                | 4.4             |
| 800             | 16.8                | 3.8             |
| 850             | 17.0                | 4.8             |
| 900             | 19.0                | 4.3             |
| 950             | 19.9                | 5.5             |
| 1000            | 20.4                | 5.0             |
| 2000            | 26.4                | 8.6             |

NHOP1

## 8. List of Measuring Equipment Used

| Instrument                           | Manufacturer | Model No.  | Serial No. | Characteristics     | Calibration Date | Remark     |
|--------------------------------------|--------------|------------|------------|---------------------|------------------|------------|
| Test Receiver                        | R&S          | ESH3       | 893495/013 | 9 KHz - 30 MHz      | Apr. 19, 1999    | Conduction |
| Spectrum Monitor                     | R&S          | EZM        | 894987/011 | N/A                 | Apr. 21, 1999    | Conduction |
| LISN (for EUT)                       | KYORITSU     | KNW-407    | 8-1010-15  | 50 ohm / 50 $\mu$ H | Nov. 17, 1998    | Conduction |
| LISN<br>(for support device)         | EMCO         | 3810/2     | 9703-1838  | 50 ohm / 50 $\mu$ H | Aug. 30, 1999    | Conduction |
| EMI Filter                           | CORCOM       | MRI-2030   | N/A        | 480VAC / 30A        | N/A              | Conduction |
| Amplifier (Site 1)                   | HP           | 87405A     | 3207A01437 | 10MHz –3.0GHz       | Jun. 25, 1999    | Radiation  |
| Spectrum Analyzer<br>(site 1)        | HP           | 8594A      | 3051A00172 | 9KHz –2.9GHz        | Apr. 16, 1999    | Radiation  |
| Bilog Antenna<br>(site 1)            | CHASE        | CBL6112A   | 2302       | 30MHz - 2GHz        | Jan. 29, 1999    | Radiation  |
| Half-wave dipole<br>antenna (site 1) | EMCO         | 3121C      | 8912-1285  | 20MHz - 1GHz        | May. 18, 1999    | Radiation  |
| Turn Table                           | EMCO         | 1060-1.211 | 9507-1805  | 0 ~ 360 degree      | N/A              | Radiation  |
| Antenna Mast                         | EMCO         | 2075       | 9806-2160  | 1 m - 4 m           | N/A              | Radiation  |