



***FCC Part 15 Subpart C***  
***EMI TEST REPORT***  
*of*

E.U.T. : WIRELESS AUTO-THERMOMETER  
FCC ID. : IERD6660  
MODEL : TM-666  
Working Frequency : 433 MHz

*for*

APPLICANT : BRIGHT HEADPHONE ELECTRONICS CO.  
ADDRESS : 2ND FL., NO. 8 & 10, LANE 337, YUNG HO  
ROAD, CHUNG HO CITY, TAIPEI HSIEN,  
TAIWAN, R.O.C.

Test Performed by

**ELECTRONICS TESTING CENTER, TAIWAN**  
NO. 8 LANE 29, WENMIMG ROAD,  
LOSHAN TSUN, KWEISHAN HSIANG,  
TAOYUAN, TAIWAN, R.O.C.

Tel:(03)3280026-32  
Fax:(03)3280034  
Report Number : ET88R-05-025-01

## TEST REPORT CERTIFICATION

Applicant : BRIGHT HEADPHONE ELECTRONICS CO.  
2ND FL., NO. 8 & 10, LANE 337, YUNG HO ROAD, CHUNG HO  
CITY, TAIPEI HSIEN, TAIWAN, R.O.C.

Manufacturer : BRIGHT HEADPHONE ELECTRONICS CO.  
2ND FL., NO. 8 & 10, LANE 337, YUNG HO ROAD, CHUNG HO  
CITY, TAIPEI HSIEN, TAIWAN, R.O.C.

Description of EUT :

a) Type of EUT : WIRELESS AUTO-THERMOMETER  
b) Trade Name : BRIGHT  
c) Model No. : TM-666  
d) FCC ID : IERD6660  
e) Working Frequency : 433 MHz  
f) Power Supply : DC 3V Battery

Regulation Applied : FCC Rules and Regulations Part 15 Subpart C (1996)

I HEREBY CERTIFY THAT; The data shown in this report were made in accordance with the procedures given in ANSI C63.4 and the energy emitted by the device was founded to be within the limits applicable. I assume full responsibility for accuracy and completeness of these data.

Note : 1. The results of the testing report relate only to the items tested.  
2. The testing report shall not be reproduced except in full, without the written approval of ETC.

Issued Date : JUL. 19, 1999

Test Engineer : Chin Cheng Yeh  
( Chin Cheng Yeh )

Approve & Authorized Signer : Will Yauo  
Will Yauo, Supervisor  
EMI Test Site of ELECTRONICS  
TESTING CENTER, TAIWAN

# Table of Contents

# Page

|                                                        |           |
|--------------------------------------------------------|-----------|
| <b>1. GENERAL INFORMATION .....</b>                    | <b>1</b>  |
| 1.1 PRODUCT DESCRIPTION .....                          | 1         |
| 1.2 CHARACTERISTICS OF DEVICE: .....                   | 1         |
| 1.3 TEST METHODOLOGY .....                             | 1         |
| 1.4 TEST FACILITY .....                                | 1         |
| <b>2. DEFINITION AND LIMITS .....</b>                  | <b>2</b>  |
| 2.1 DEFINITION .....                                   | 2         |
| 2.2 RESTRICTED BANDS OF OPERATION .....                | 2         |
| 2.3 LIMITATION .....                                   | 2         |
| 2.4 LABELING REQUIREMENT .....                         | 4         |
| 2.5 USER INFORMATION .....                             | 4         |
| <b>3. RADIATED EMISSION MEASUREMENT.....</b>           | <b>5</b>  |
| 3.1 APPLICABLE STANDARD .....                          | 5         |
| 3.2 MEASUREMENT PROCEDURE .....                        | 5         |
| 3.3 TEST DATA .....                                    | 7         |
| 3.4 FIELD STRENGTH CALCULATION.....                    | 8         |
| 3.5 ACTIVATE TIME .....                                | 8         |
| 3.6 CALCULATION OF DUTY FACTOR.....                    | 8         |
| 3.7 RADIATED TEST EQUIPMENT .....                      | 9         |
| 3.8 MEASURING INSTRUMENT SETUP .....                   | 9         |
| 3.9 RADIATED MEASUREMENT PHOTOS .....                  | 10        |
| <b>4. BANDWIDTH OF EMISSION.....</b>                   | <b>11</b> |
| 4.1 APPLICABLE STANDARD PLOT GRAPHIC OF BANDWIDTH..... | 11        |
| 4.2 BANDWIDTH TEST EQUIPMENT .....                     | 11        |
| 4.3 PLOT GRAPHIC OF BANDWIDTH .....                    | 11        |
| <b>5. CONDUCTED EMISSION MEASUREMENT .....</b>         | <b>12</b> |
| 5.1 STANDARD APPLICABLE .....                          | 12        |
| <b>APPENDIX 1 : PLOTTED DATA FOR DUTY FACTOR.....</b>  | <b>13</b> |
| <b>APPENDIX 2 : PLOTTED DATA FOR BANDWIDTH.....</b>    | <b>14</b> |

## 1. GENERAL INFORMATION

### 1.1 Product Description

|                      |                             |
|----------------------|-----------------------------|
| a) Type of EUT       | : WIRELESS AUTO-THERMOMETER |
| b) Trade Name        | : BRIGHT                    |
| c) Model No.         | : TM-666                    |
| d) FCC ID            | : IERD6660                  |
| e) Working Frequency | : 433 MHz                   |
| f) Power Supply      | : DC 3V Battery             |

### 1.2 Characteristics of Device:

The Wireless Multi-functional Themomeler uses the latest wireless transmitting and receiving technology to inform you the surrounding indoor and outdoor temperature. If detects temperature from -10 C to + 70 C (-14 F to + 156 F) and each pair of degree (indoor and outdoor) has maximum and minimum temperature set up. The Wireless Multi-functional Thermometer is of a brilliant design with an automatic pick-hold memory which records the highest and lowest degree it ever detects in a day.

### 1.3 Test Methodology

Both conducted and radiated testing were performed according to the procedures in chapter 13 of ANSI C63.4.

The WIRELESS AUTO-THERMOMETER under test was operated continuously in its normal operating mode for the purpose of the measurements. In order to secure the continuous operation of the device under test, rewiring in the circuit was done by the manufacturer so as to affect its intended operation.

The receiving antenna polarized horizontally was varied from 1 to 4 meters and the wooden turntable was rotated through 360 degrees to obtain the highest reading on the field strength meter or on the display of the spectrum analyzer. And also, each emission was to be maximized by changing the orientation of the WIRELESS AUTO-THERMOMETER under test.

In order to determining the average value during one pulse train of the radiated power generated from the WIRELESS AUTO-THERMOMETER under test, the encoded wave form in the time domain was used.

### 1.4 Test Facility

The open area test site and conducted measurement facility used to collect the radiated data is located on the roof top of Building at No. 34, Lin 5, Ding Fu Tsung, Linkou Hsiang, Taipei Hisen, Taiwan 244, R.O.C.

This site has been fully described in a report submitted to your office, and accepted in a letter dated Feb. 10, 1997.

## 2. DEFINITION AND LIMITS

### 2.1 Definition

Intentional radiator:

A device that intentionally generates and emits radio frequency energy by radiation or induction.

### 2.2 Restricted Bands of Operation

Only spurious emissions are permitted in any of the frequency bands listed below:

| MHz               | MHz                   | MHz           | GHz         |
|-------------------|-----------------------|---------------|-------------|
| 0.090 - 0.110     | 16.42-16.423          | 399.9-410     | 4.5-5.25    |
| 0.495 - 0.505 **  | 16.69475 - 16.69525   | 608-614       | 5.35-5.46   |
| 2.1735 - 2.1905   | 16.80425 - 16.80475   | 960-1240      | 7.25-7.75   |
| 4.125-4.128       | 25.5-25.67            | 1300-1427     | 8.025-8.5   |
| 4.17725-4.17775   | 37.5-38.25            | 1435-1626.5   | 9.0-9.2     |
| 4.20725-4.20775   | 73-74.6               | 1645.5-1646.5 | 9.3-9.5     |
| 6.215-6.218       | 74.8-75.2             | 1660-1710     | 10.6-12.7   |
| 6.26775-6.26825   | 108-121.94            | 1718.8-1722.2 | 13.25-13.4  |
| 6.31175-6.31225   | 123-138               | 2200-2300     | 14.47-14.5  |
| 8.291-8.294       | 149.9-150.05          | 2310-2390     | 15.35-16.2  |
| 8.362-8.366       | 156.52475 - 156.52525 | 2483.5-2500   | 17.7-21.4   |
| 8.37625-8.38675   | 156.7-156.9           | 2655-2900     | 22.01-23.12 |
| 8.41425-8.41475   | 162.0125-167.17       | 3260-3267     | 23.6-24.0   |
| 12.29-12.293      | 167.72-173.2          | 3332-3339     | 31.2-31.8   |
| 12.51975-12.52025 | 240-285               | 3345.8-3358   | 36.43-36.5  |
| 12.57675-12.57725 | 322-335.4             | 3360-4400     | Above 38.6  |
| 13.36-13.41       |                       |               |             |

Remark "\*\*\*" : Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz

### 2.3 Limitation

#### (1) Conducted Emission Limits :

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the conducted limit is the following:

| Frequency<br>( MHz ) | Emission<br>( $\mu$ V ) | Emission<br>( dB $\mu$ V ) |
|----------------------|-------------------------|----------------------------|
| 0.45 - 30.0          | 250                     | 48.0                       |

**(2) Radiated Emission Limits :**

According to 15.231 ,Periodic operation in the band 40.66-40.70 MHz and above 70 MHz, the field strength of emissions from intentional radiators operated under this section shall not exceed the following:

| Frequency Band (MHz) | Field strength of Fundamental (uV/m) | Field strength of Spurious (uV/m) |
|----------------------|--------------------------------------|-----------------------------------|
| 40.66-40.70          | 2250                                 | 225                               |
| 70-130               | 1250                                 | 125                               |
| 130-174              | *1,250 to 3,750                      | *125 to 375                       |
| 174-260              | 3750                                 | 375                               |
| 260-470              | *3,750 to 12,500                     | *375 to 1250                      |
| Above 470            | 12500                                | 1250                              |

\* Linear interpolations.

According to 15.235, the field strength of emissions from intentional radiators operated under these frequency bands shall not exceed the following:

| Fundamental Frequency (MHz) | Field Strength of Fundamental |                                     |
|-----------------------------|-------------------------------|-------------------------------------|
|                             | $\mu\text{V}/\text{meter}$    | $\text{dB}\mu\text{V}/\text{meter}$ |
| 49.82 - 49.90               | 10000                         | 80                                  |

Field strength limits are at the distance of 3 meters, emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209,as following table:

| Other Frequencies (MHz) | Field Strength of Fundamental |                                     |
|-------------------------|-------------------------------|-------------------------------------|
|                         | $\mu\text{V}/\text{meter}$    | $\text{dB}\mu\text{V}/\text{meter}$ |
| 30 - 88                 | 100                           | 40.0                                |
| 88 - 216                | 150                           | 43.5                                |
| 216 - 960               | 200                           | 46.0                                |
| Above 960               | 500                           | 54.0                                |

As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

### **(3) Limit of transmission time**

- a) A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.
- b) A transmitter activated automatically shall cease transmission within 5 seconds after activation.

## **2.4 Labeling Requirement**

The device shall bear the following statement in a conspicuous location on the device :

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

## **2.5 User Information**

The users manual or instruction manual for an intentional or unintentional radiator shall caution the user that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.



### 3. RADIATED EMISSION MEASUREMENT

#### 3.1 Applicable Standard

For periodic operation intentional radiator, the radiated emission shall comply with §  
 5.231(b).

#### 3.2 Measurement Procedure

1. Setup the configuration per figure 1 and 2 for frequencies measured below and above 1 GHz respectively. Turn on EUT and make sure that it is in normal function.
2. For emission frequencies measured below 1 GHz, a pre-scan is performed in a shielded chamber to determine the accurate frequencies of higher emissions will be checked on a open test site. As the same purpose, for emission frequencies measured above 1 GHz, a pre-scan also be performed with a 1 meter measuring distance before final test.
3. For emission frequencies measured below and above 1 GHz, set the spectrum analyzer on a 100 kHz and 1 MHz resolution bandwidth respectively for each frequency measured in step 2.
4. The search antenna is to be raised and lowered over a range from 1 to 4 meters in horizontally polarized orientation. Position the highness when the highest value is indicated on spectrum analyzer, then change the orientation of EUT on test table over a range from 0 ° to 360 ° with a speed as slow as possible, and keep the azimuth that highest emission is indicated on the spectrum analyzer. Vary the antenna position again and record the highest value as a final reading. A RF test receiver is also used to confirm emissions measured.
5. Repeat step 4 until all frequencies need to be measured were complete.
6. Repeat step 5 with search antenna in vertical polarized orientations.
7. Check the three frequencies of highest emission with varying the placement of cables (if any) associated with EUT to obtain the worse case and record the result.

Figure 1 : Frequencies measured below 1 GHz configuration





Figure 2 : Frequencies measured above 1 GHz configuration



**3.3 Test Data**

Temperature : 25 °C  
 Humidity : 50 %  
 Operated mode : Transmitting  
 Test Date : MAY 26, 1999

| Frequency<br>(MHz) | Ant<br>Pol<br>H/V | Reading<br>(dBUV)<br>Peak | Factor<br>(dB) |      | Result @3m<br>(dBUV/m) |      | Limit @3m<br>(dBUV/m) |      | Margin<br>(dB) | Table<br>Degree<br>(Deg.) | Ant.<br>High<br>(m) |
|--------------------|-------------------|---------------------------|----------------|------|------------------------|------|-----------------------|------|----------------|---------------------------|---------------------|
|                    |                   |                           | C              | D    | Peak                   | Ave. | Peak                  | Ave. |                |                           |                     |
| 433.921            | H                 | 81.5                      | -5.5           | -7.6 | 76.0                   | 68.4 | 100.9                 | 80.9 | -12.5          | 180                       | 1.10                |
| 867.842            | H                 | 54.7                      | 2.3            | -7.6 | 57.0                   | 49.4 | 80.9                  | 60.9 | -11.5          | 180                       | 1.10                |
| *1301.763          | H                 | 56.5                      | -8.4           | -7.6 | 48.1                   | 40.5 | 74.0                  | 54.0 | -13.5          | 180                       | 1.10                |
| 1735.684           | H/V               | ---                       | -6.1           | -7.6 | ---                    | ---  | 80.9                  | 60.9 | ---            | ---                       | ---                 |
| 2169.605           | H/V               | ---                       | -4.0           | -7.6 | ---                    | ---  | 80.9                  | 60.9 | ---            | ---                       | ---                 |
| 2603.526           | H/V               | ---                       | -2.4           | -7.6 | ---                    | ---  | 80.9                  | 60.9 | ---            | ---                       | ---                 |
| 3037.447           | H/V               | ---                       | -1.1           | -7.6 | ---                    | ---  | 80.9                  | 60.9 | ---            | ---                       | ---                 |
| 3471.368           | H/V               | ---                       | -0.1           | -7.6 | ---                    | ---  | 80.9                  | 60.9 | ---            | ---                       | ---                 |
| *3905.289          | H/V               | ---                       | 1.6            | -7.6 | ---                    | ---  | 74.0                  | 54.0 | ---            | ---                       | ---                 |
| *4339.210          | H/V               | ---                       | 2.0            | -7.6 | ---                    | ---  | 74.0                  | 54.0 | ---            | ---                       | ---                 |

**Note :**

1. Factor C means "corrected", and that includes antenna factor, cable loss, amplifier gain (if any). And Factor D means "Duty", that is for calculating the average value and derived from section 3.6 in this test report.
2. Peak Result = Reading + C. Factor  
Ave. Result = Peak Result + D Factor
3. "\*" means the frequency fall in the restricted frequency band, and the limit of emission is referred to FCC class B
4. The limit for spurious emissions refers to FCC §15.231.

If the measured frequencies fall in the restricted frequency band, the limit employed is § 15.209 general requirement when frequencies are below or equal to 1 GHz. And the measuring instrument is set to quasi peak detector function, no duty factor applied.

### 3.4 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any) from the measured reading. For the limit is employed average value, therefore the peak value can be transferred to average value by subtracting the duty factor. The basic equation with a sample calculation is as follows:

$$\text{Peak} = \text{Reading} + \text{Corrected Factor}$$

where

Corr. Factor = Antenna Factor + Cable Factor - Amplifier Gain (if any)

And the average value is

$$\text{Average} = \text{Peak Value} + \text{Duty Factor}$$

*Note : If the measured frequencies are fall in the restricted frequency band, the limit employed must be quasi peak value when frequencies are below or equal to 1 GHz. And the measuring instrument is set to quasi peak detector function.*

### 3.5 Activate Time

This WIRELESS AUTO-THERMOMETER is operated by Manual, and Activate Time is less than 5 second after being released.

### 3.6 Calculation of Duty Factor

The total period of pulse train is 60.0 ms, and the total duty is 41.7 ms, and the duty factor is calculated with following formula :

$$20\log \frac{\text{Total Duty}}{\text{Period of Pulse Train}}$$

*Note : Please see appendix 1 for Plotted Data*

**3.7 Radiated Test Equipment**

| Equipment                 | Manufacturer    | Model No. | Next Cal. Date |
|---------------------------|-----------------|-----------|----------------|
| Spectrum Analyzer         | Hewlett-Packard | 8568B     | 12/02/1999     |
| Pre-selector              | Hewlett-Packard | 85685A    | 12/07/1999     |
| Quasi Peak Detector       | Hewlett-Packard | 85650A    | 12/02/1999     |
| RF Test Receiver          | Rohde & Schwarz | ESVS 30   | 01/10/2000     |
| Log periodic Antenna      | EMCO            | 3146      | 09/15/1999     |
| Biconical Antenna         | EMCO            | 3110      | 09/15/1999     |
| Preamplifier              | Hewlett-Packard | 8447D     | 11/30/1999     |
| Microwave EMI Test System | Hewlett-Packard | 84125C    | 01/24/2000     |

**3.8 Measuring Instrument Setup**

Explanation of measuring instrument setup in frequency band measured is as following :

| Frequency Band (MHz) | Instrument        | Function   | Resolution bandwidth | Video Bandwidth |
|----------------------|-------------------|------------|----------------------|-----------------|
| 30 to 1000           | RF Test Receiver  | Quasi Peak | 120 kHz              | N/A             |
|                      | Spectrum Analyzer | Peak       | 100 kHz              | 100 kHz         |
| Above 1000           | Spectrum Analyzer | Peak       | 1 MHz                | 1 MHz           |

## 4. BANDWIDTH OF EMISSION

### 4.1 Applicable Standard Plot Graphic of Bandwidth

Per FCC rule § 15.231(c), the permitted emission bandwidth is no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz.

### 4.2 Bandwidth Test Equipment

| Equipment         | Manufacturer    | Model No. | Next Cal. Date |
|-------------------|-----------------|-----------|----------------|
| Spectrum Analyzer | ADVANTEST       | R3261A    | 09/21/1999     |
| Plotter           | Hewlett-Packard | 7550A     | N/A            |
|                   |                 |           |                |

### 4.3 Plot Graphic of Bandwidth

The emission bandwidth limit for this transmitter is

$$433.92 \times 0.25\% = 1084.8 \text{ KHz}$$

*Note : Please see appendix 2 for Plotted Data*


## **5. CONDUCTED EMISSION MEASUREMENT**

### **5.1 Standard Applicable**


This EUT is excused from investigation of conducted emission, for it is powered by battery only. According to § 15.207 (d), measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines.

## APPENDIX 1 : PLOTTED DATA FOR DUTY FACTOR

$$20\log\frac{(3.6ms \times 4) + (2.1ms \times 13)}{100ms} = -7.6 \text{ dB}$$



REF -30.0 dBm      ATT 10 dB      A\_view B\_blank



RBW 100 KHZ  
 VBW 100 KHZ  
 SWP 180 MS


CENTER 433.979300 MHZ      SPAN 0.000 KHZ

REF -30.0 dBm  
10dB/

ATT 10 dB



A\_view B\_blank

RBW  
100 kHz  
VBW  
100 kHz  
SWP  
180 ms



CENTER 433.979300 MHz

SPAN 0.000 kHz




## **APPENDIX 2 : PLOTTED DATA FOR BANDWIDTH**

$$\text{Bandwidth Limit} = 3433.921 \text{ MHz} \times 0.25\% = 1084.8 \text{ KHz}$$

$$\text{Bandwidth} = 134 \text{ KHz} < 1084.8 \text{ KHz}$$

CISPR    HOR. REM.    MODEL:    ETC LAB  
 REF 80.0 dB $\mu$ V    ATT 0 dB    A\_view B\_blank  
 10dB/



REF 80.0 dB $\mu$ V    ATT 0 dB    ETC LAB  
 10dB/    A\_view B\_blank

