

RF EXPOSURE REPORT

REPORT NO.: SA990421C04-1

MODEL NO.: EX115, EX112

FCC ID: IHDP56LJ3

ACCORDING: FCC Guidelines for Human Exposure
IEEE C95.1

APPLICANT: Motorola Inc

ADDRESS: Mobile Devices 600 N. U.S. Highway 45,
Libertyville, Illinois, United States, 60048-5343

ISSUED BY: Bureau Veritas Consumer Products Services (H.K.)
Ltd., Taoyuan Branch

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou Hsiang,
Taipei Hsien 244, Taiwan, R.O.C.

TEST LOCATION: No. 19, Hwa Y a 2nd Rd, Wen Hwa T suen, Kwei
Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

1. Conclusion

No Evaluation Required if power is below this threshold:

F(GHz)	mW
Low 2.402	24.580
High 2.480	

Maximum measured transmitter power:

Pout (dBm)	Pout (mW)
Conducted Power	3.6
EIRP Power	1.4

***Note:** The antenna is Embedded inverted-F antenna with -3.94dBi gain.

Threshold for no SAR evaluation is 24.580mW
Transmitter power is 3.6mW

Conclusion: No SAR evaluation required since Transmitter Pout is below FCC threshold